

OPTICAL TOUCH SCREEN SYSTEMS USING REFLECTED LIGHT

FIELD OF THE INVENTION

[0001] The field of the present invention is light-based touch screens.

BACKGROUND OF THE INVENTION

[0002] Many consumer electronic devices are now being built with touch sensitive screens, for use with finger or stylus touch user inputs. These devices range from small screen devices such as mobile phones and car entertainment systems, to mid-size screen devices such as notebook computers, to large screen devices such as check-in stations at airports.

[0003] Most conventional touch screen systems are based on resistive or capacitive layers. Such systems are not versatile enough to offer an all encompassing solution, as they are not easily scalable.

[0004] Reference is made to **FIG. 1**, which is a prior art illustration of a conventional touch screen system. Such systems include an LCD display surface, a resistive or capacitive overlay that is placed over the LCD surface, and a controller integrated circuit (IC) that connects to the overlay and converts inputs from the overlay to meaningful signals. A host device (not shown), such as a computer, receives the signals from the controller IC, and a device driver or such other program interprets the signals to detect a touch-based input such as a key press or scroll movement.

[0005] Reference is made to **FIG. 2**, which is a prior art illustration of a conventional resistive touch screen. Shown in **FIG. 2** are conductive and resistive layers **1** separated by thin spaces. When a pointer **2**, such as a finger or a stylus, touches the screen, a contact is created between resistive layers, closing a switch. A controller **3** determines the current between layers to derive the position of the touch point.

[0006] Advantages of resistive touch screens are their low cost, low power consumption and stylus support.

[0007] A disadvantage of resistive touch screens is that as a result of the overlay, the screens are not fully transparent. Another disadvantage is that the screens require periodic re-calibration. Another disadvantage is that pressure is required for touch detection; i.e., a pointer that touches the screen without sufficient pressure goes undetected. As a consequence, resistive touch screens do not work well with fingers. Another disadvantage is that resistive touch screens are generally unreadable in direct sunlight. Another disadvantage is that resistive touch screens are sensitive to scratches. Yet another disadvantage is that resistive touch screens are unable to discern that two or more pointers are touching the screen simultaneously, referred to as "multi-touch".

[0008] Reference is made to **FIG. 3**, which is a prior art illustration of a conventional surface capacitive touch screen. As shown in **FIG. 3**, two sides of a glass substrate **1** are coated with a uniform conductive indium tin oxide (ITO) coating. In addition, a silicon dioxide hard coating is coated on the front side of one of the ITO coating layers. Electrodes **2** are attached at the four corners of the glass, for generating an electric current. A pointer **3**, such as a finger or a stylus, touches the screen, and draws a small amount of current to the point of contact. A controller **4** then determines the location of the touch point based on the proportions of current passing through the four electrodes.

[0009] Advantages of surface capacitive touch screens are finger touch support and a durable surface.

[0010] A disadvantage of surface capacitive touch screens is that as a result of the overlay, the screens are not fully transparent. Another disadvantage is a limited temperature range for operation. Another

disadvantage is a limited capture speed of pointer movements, due to the capacitive nature of the touch screens. Another disadvantage is that surface capacitive touch screens are susceptible to radio frequency (RF) interference and electromagnetic (EM) interference. Another disadvantage is that the accuracy of touch location determination depends on the capacitance. Another disadvantage is that surface capacitive touch screens cannot be used with gloves. Another disadvantage is that surface capacitive touch screens require periodic re-calibration. Another disadvantage is that surface capacitive touch screens require a large screen border. As a consequence, surface capacitive touch screens cannot be used with small screen devices. Yet another disadvantage is that surface capacitive touch screens are unable to discern a multi-touch.

[0011] Reference is made to **FIG. 4**, which is a prior art illustration of a conventional projective capacitive touch screen. Shown in **FIG. 4** are etched ITO layers **1** that form multiple horizontal (X-axis) and vertical (Y-axis) electrodes. AC signals **2** drive one axis and the response through the screen loops back via the other electrodes. Location of a pointer touching the screen is determined based on the signal level changes **3** between the horizontal and vertical electrodes.

[0012] Advantages of projective capacitive touch screens are finger multi-touch detection and a durable surface.

[0013] A disadvantage of projective capacitive touch screens is that as a result of the overlay, the screens are not fully transparent. Another disadvantage is their high cost. Another disadvantage is a limited temperature range for operation. Another disadvantage is a limited capture speed, due to the capacitive nature of the touch screens. Another disadvantage is a limited screen size, typically less than 5". Another disadvantage is that surface capacitive touch screens are

susceptible to RF interference and EM interference. Yet another disadvantage is that the accuracy of touch location determination depends on the capacitance.

[0014] It will thus be appreciated that conventional touch screens are impractical for general use with small mobile devices and devices with large screens.

SUMMARY OF THE DESCRIPTION

[0015] The present invention provides touch screens that overcome the drawbacks of conventional resistive and capacitive touch screens.

[0016] Aspects of the present invention relate to various embodiments of touch screens, including inter alia (i) touch screens that are responsive to both blocked and reflected light, (ii) touch screens with selective area touch, (iii) touch screens with embedded reflective elements, (iv) touch screens with multi-layer screens, (v) touch screens with wide light beams, and (vi) touch screens with image sensors and image processing logic.

Touch Screens Responsive to Blocked and Reflected Light

[0017] In these embodiments of the present invention, light beams are emitted by one or more light sources. A pointer, such as a finger or stylus, touching the screen blocks some of the emitted light and also reflects some of the emitted light. By measuring the blocked and reflected light, the location of the pointer on the screen is determined.

Touch Screens with Selective Area Touch

[0018] In these embodiments of the present invention, a sub-area of the screen is touch-sensitive, and the remainder of the screen is not touch-sensitive. Generally, selective area touch is used with mid-size and large-size screens, for which it is unnecessary that the entire screen surface area be touch sensitive.

[0019] For example, a user interface may include a touch-sensitive keyboard for text input. The location of the keyboard within the screen is designated, and then light sources and light detectors are positioned so as to be able to detect touches on the keyboard keys. I.e., the light sources and light detectors are aligned to match the user interface.

[0020] The present invention is of particular advantage in providing low cost touch screens with selective area touch. Conventional capacitive and resistive touch screens are costly, since the required screen overlay generally cannot be used to cover only a sub-area of the screen surface. Furthermore, the wiring used in conventional capacitive and resistive touch screens generally traverses the entire screen. As such, for large screens the wires must be long and thick.

[0021] In distinction, the present invention is scalable, and the cost of the touch screen is generally proportional to the perimeter of the touch sensitive sub-area.

Touch Screens with Embedded Reflective Elements

[0022] In these embodiments of the present invention elements that reflect light are embedded within the touch screen. A light sensor or camera is used to capture an image of the screen when one or more pointers are touching the screen, or approaching the screen. The image is analyzed to determine the locations of the one or more pointers; in particular, the locations of a multi-touch.

Touch Screens with Multi-Layer Screens

[0023] In these embodiments of the present invention the screen includes multiple layers. Light emitted by one or more light sources is guided through some of the layers, and light received by one or more photo detectors is guided through others of the layers.

Touch Screens with Wide Light Beams

[0024] In these embodiments of the present invention light from a narrow source, such as a near infrared LED, is widened, using lenses or reflective elements, to project over a wide swath of screen area. In order

to widen a narrow cone of light, the light source is placed at a relatively long distance from the screen edge. In one embodiment, the light source is placed underneath the screen, at an appropriate distance from the screen edge to allow for a gradual widening of the beam. The widened beam is reflected above the screen surface by reflectors placed near the screen edge.

[0025] In another embodiment of the present invention the light source is placed along a screen edge. Reflectors that reflect light over the screen surface are also placed along the same screen edge, at an appropriate distance away from the light source, to allow for a gradual widening of the light beam before it is reflected over the screen surface. The light source emits a narrow cone of light at a distance substantially along the screen edge, and the light is reflected as a wide beam over the screen surface. A pointer, such as a finger or stylus, touching the screen blocks some of the emitted light. By measuring the blocked light, the location of the pointer on the screen is determined.

[0026] In an embodiment of the present invention the wide beam converges onto a narrow light detector after traversing the screen, via reflectors placed an appropriate distance away from respective light detectors. The light detectors are placed either underneath the screen, or along a screen edge.

Touch Screens with Image Sensors and Image Processing Logic

[0027] In these embodiments of the present invention images of light projected over a screen are captured by at least one image sensor. Due to the focal distance of an image sensor and its lenses, the image captured when a pointer touches the screen depends on the distance between the pointer and the sensor. Specifically, the pointer generates a sequence of sub-patterns on the sensor, where the number of sub-

patterns varies according to the distance of the pointer from the sensor. Thus the location of the pointer may be calculated in part based on the number of sub-patterns in the image.

[0028] For ease of exposition, throughout the present specification the term "glass screen" is used as a generic term to refer to a transparent screen surface. The screen may be constructed from glass, or instead from a non-glass material including inter alia crystal, acrylic and plastic. In some embodiments of the present invention, the screen allows near-infrared light to pass through, but is otherwise non-transparent.

[0029] For ease of exposition, throughout the present specification the term "touch screen" is used as a generic term to include touch sensitive surfaces that may or may not include an electronic display. As such, the term "touch screen" includes inter alia a mouse touchpad as included in many laptop computers, and the back cover of a handheld electronic device.

[0030] There is thus provided in accordance with an embodiment of the present invention a touch screen system, including a near-infrared transparent screen including a plurality of reflective elements embedded therein, a circuit board including circuitry for controlled selective activation of electronic components connected thereto, at least one light source connected to the circuit board, for emitting light, and at least one light detector connected to the circuit board, for detecting light emitted by the at least one light source and reflected by the reflective elements.

[0031] There is additionally provided in accordance with an embodiment of the present invention a touch screen system including a display screen, a circuit board including circuitry for controlled selective activation of electronic components connected thereto, a plurality of near-infrared

LEDs connected to the circuit board, for emitting light, a first plurality of photo diodes connected to the circuit board, for detecting received light along a first edge of the display screen, and a second plurality of photo diodes connected to the circuit board, for detecting received light along a second edge of the display screen, wherein the circuitry generates signals responsive to blocked light from the near-infrared LEDs detected at the first plurality of photo diodes and signals responsive to reflected light from the near-infrared LEDs detected at the second plurality of photo diodes.

[0032] There is further provided in accordance with an embodiment of the present invention a touch screen system, including a display screen for displaying a plurality of buttons at designated horizontal and vertical screen coordinates thereon, a plurality of photo diodes coupled with the display screen, for detecting received light, and a plurality of lenses coupled with the display screen, wherein the designated horizontal and vertical screen coordinates span a touch sensitive sub-area of the display screen, wherein the photo diodes and lenses are positioned so as to detect a touch of the display screen at the touch sensitive sub-area, and wherein the remainder of the display screen is non-functional for detecting screen coordinates of a touch thereof.

[0033] There is yet further provided in accordance with an embodiment of the present invention a touch screen system, including a display screen including a touch sensitive sub-area, a plurality of photo diodes coupled with the display screen, for detecting received light, and a plurality of lenses coupled with the display screen, wherein the photo diodes and the lenses are positioned so as to detect the position of a touch of the display screen within the touch sensitive sub-area, and wherein the remainder of the display screen is non-functional for detecting the location of a touch thereof.

[0034] There is moreover provided in accordance with an embodiment of the present invention a touch screen system including a display screen including a plurality of layers substantially parallel to one another, a circuit board including circuitry for controlled selective activation of electronic components connected thereto, a plurality of near-infrared LEDs connected to the circuit board, for emitting light that is guided through a first layer of the display screen, and a plurality of photo diodes connected to the circuit board, for receiving light that is guided through a second layer of said display screen, wherein said circuitry generates signals responsive to light detected at the plurality of photo diodes.

[0035] There is additionally provided in accordance with an embodiment of the present invention a touch screen system, including a screen, a plurality of light sources coupled with the screen, for emitting light, a plurality of photo diodes coupled with the screen, for detecting the light emitted by the light sources, and for identifying the location of a touch on the screen when an absence of the emitted light is detected, and a plurality of lenses coupled respectively with the plurality of light sources to generate wide beams of light over a portion of the screen wherein substantially connected areas of the screen are covered by neighboring wide beams.

[0036] There is further provided in accordance with an embodiment of the present invention a touch screen system, including a glass screen including a plurality of reflective elements embedded therein, a display screen backlight for projecting light through the glass screen, a circuit board including circuitry for controlled selective activation of electronic components connected thereto, and a plurality of light detectors connected to the circuit board and arranged along a portion of the periphery of the glass screen, for detecting received light. When a pointer approaches near or touches the screen, the backlight is reflected

by the pointer onto at least one of the reflective elements, which reflect the light onto at least one of the light detectors. An approaching pointer is thus recognized by an increase in detected light by at least one of the light detectors.

[0037] There is yet further provided in accordance with an embodiment of the present invention a touch screen system, including a glass screen including a plurality of reflective elements embedded therein, a front light display screen for reflecting light through the glass screen, a circuit board including circuitry for controlled selective activation of electronic components connected thereto, and a plurality of light detectors connected to the circuit board and arranged along a portion of the periphery of the glass screen, for detecting received light. When a pointer approaches near or touches the screen, the front light is reflected by the pointer onto at least one of the reflective elements, which reflect the light onto at least one of the light detectors. An approaching pointer is thus recognized by an increase in detected light by at least one of the light detectors.

[0038] There is moreover provided in accordance with an embodiment of the present invention a touch screen system, including a glass screen including first and second pluralities of reflective elements embedded therein, a circuit board including circuitry for controlled selective activation of electronic components connected thereto, and a plurality of light detectors connected to the circuit board and arranged along a portion of the periphery of the glass screen, for detecting received light. A portion of ambient light that enters the glass screen is reflected back above the screen by at least one of the first reflective elements. When a pointer approaches or touches the screen, the light reflected back above the screen is reflected by the pointer onto at least one of the second reflective elements, which reflect the light onto at least one of the light

detectors. An approaching pointer is thus recognized by an increase in detected light by at least one of the light detectors.

[0039] Additionally, in accordance with an embodiment of the present invention, the light detectors are placed underneath the screen, and light is reflected below the screen via lenses placed around the periphery of the screen. Alternatively, in accordance with an embodiment of the present invention, the light penetrates below the screen by passing directly through the screen glass.

[0040] Alternatively, in accordance with an embodiment of the present invention, the light detectors are placed inside the screen glass, yet the circuit board circuitry controls selective activation of the light detectors.

[0041] Further, in accordance with an embodiment of the present invention, a plurality of LEDs are placed underneath the screen, and light is reflected above the screen surface via lenses placed around the periphery of the screen. Alternatively, in accordance with an embodiment of the present invention, the light penetrates above the screen by passing directly through the screen.

[0042] Alternatively, in accordance with an embodiment of the present invention, the LEDs are placed inside the screen glass, yet the circuit board circuitry controls selective activation of the LEDs.

BRIEF DESCRIPTION OF THE DRAWINGS

[0043] The present invention will be more fully understood and appreciated from the following detailed description, taken in conjunction with the drawings in which:

[0044] **FIG. 1** is a prior art illustration of a conventional touch screen system;

[0045] **FIG. 2** is a prior art illustration of a conventional resistive touch screen;

[0046] **FIG. 3** is a prior art illustration of a conventional surface capacitive touch screen;

[0047] **FIG. 4** is a prior art illustration of a conventional projective capacitive touch screen;

[0048] **FIG. 5** is a diagram of a touch screen having 16 LEDs and 16 PDs, in accordance with an embodiment of the present invention;

[0049] **FIGS. 6 – 8** are diagrams of a touch screen that detects two pointers that touch the screen simultaneously, in accordance with an embodiment of the present invention;

[0050] **FIGS. 9 and 10** are diagrams of a touch screen that detects a two finger glide movement, in accordance with an embodiment of the present invention;

[0051] **FIG. 11** is a circuit diagram of the touch screen from **FIG. 5**, in accordance with an embodiment of the present invention;

[0052] **FIG. 12** is a diagram of a touch screen with four LEDs placed in the four corners of the screen, and plural PDs are arranged along the four sides of the screen, in accordance with an embodiment of the present invention;

[0053] **FIG. 13** is a simplified diagram of a touch screen system responsive to blocked light and reflected light, in accordance with an embodiment of the present invention;

[0054] **FIG. 14** is a simplified diagram of a touch screen system with selective area touch aligned with user interface buttons, in accordance with an embodiment of the present invention;

[0055] **FIG. 15** is a simplified diagram of another touch screen system with selective area touch, in accordance with an embodiment of the present invention;

[0056] **FIG. 16** is a simplified diagram of a touch screen system with reflective elements embedded in the screen, in accordance with an embodiment of the present invention;

[0057] **FIG. 17** is a simplified diagram of a touch screen system with a multi-layer screen, in accordance with an embodiment of the present invention;

[0058] **FIG. 18** is a simplified diagram of a light-based touch screen system, in accordance with an embodiment of the present invention;

[0059] **FIG. 19** is a simplified cross-sectional diagram of the touch screen system of **FIG. 18**, in accordance with an embodiment of the present invention;

[0060] **FIG. 20** is a simplified diagram of a light-based touch screen system with 4 LEDs and 4 photo detectors, in accordance with an embodiment of the present invention;

[0061] **FIG. 21** is a simplified illustration of a touch screen system that measures blocked light and reflected light to determine a location of touch, in accordance with an embodiment of the present invention;

[0062] **FIG. 22** is a simplified illustration of reflector lenses using with the touch screen system of **FIG. 21**, in accordance with an embodiment of the present invention;

[0063] **FIG. 23** is a simplified illustration of a touch screen system with PDs positioned along three edges of a touch screen, in accordance with an embodiment of the present invention;

[0064] **FIG. 24** is a simplified illustration of a portion of a touch screen display and surrounding frame, in accordance with an embodiment of the present invention;

[0065] **FIG. 25** is a projection view of the section of **FIG. 23** designated A-A, in accordance with an embodiment of the present invention;

[0066] **FIG. 26** is a simplified diagram of an LED for a touch screen system, with a diode that emits light from the side, in accordance with an embodiment of the present invention;

[0067] **FIG. 27** is a simplified diagram of an LED for a touch screen system, with a diode that emits lights from the top, in accordance with an embodiment of the present invention;

[0068] **FIG. 28** is a simplified diagram of an optical element that focuses light emitted by an LED focused into a narrow beam, in accordance with an embodiment of the present invention;

[0069] **FIG. 29** is a simplified diagram of a PD that is placed underneath the plane of a touch screen for detecting reflected light above the touch screen, in accordance with an embodiment of the present invention;

[0070] **FIG. 30** is a simplified illustration of an arrangement of photo diodes, photo transistors and optical elements that enable a touch screen system to read pointers that are smaller than the sensor elements, in accordance with an embodiment of the present invention;

[0071] **FIGS. 31 – 34** are simplified illustrations of touch screen systems with selective area touch, in accordance with an embodiment of the present invention;

[0072] **FIG. 35** is a simplified illustration of a touch screen with four LEDs and 4 PDs surrounding the screen, in accordance with an embodiment of the present invention;

[0073] **FIG. 36** is a simplified illustration of a finger blocking one of the light beams of **FIG. 35**, in accordance with an embodiment of the present invention;

[0074] **FIG. 37** is a simplified illustration of a touch screen with light beams that are focused diagonally relative to the screen edges, in accordance with an embodiment of the present invention;

[0075] **FIG. 38** is a simplified illustration of a finger blocking one of the light beams of **FIG. 37**, in accordance with an embodiment of the present invention;

[0076] **FIG. 39** is a simplified illustration of a touch screen that uses light beams projected in two non-orthogonal directions across a portion of the screen surface, in accordance with an embodiment of the present invention;

[0077] **FIG. 40** is a simplified illustration of a touch screen with a single LED and multiple PDs arranged along each of two adjacent screen edges, in accordance with an embodiment of the present invention;

[0078] **FIG. 41** is a simplified illustration of a touch screen system with eight LEDs positioned along two adjacent edges of a display area, and eight PDs positioned along the opposite edges of the display area, in accordance with an embodiment of the present invention;

[0079] **FIG. 42** is a simplified illustration of a zoom user interface mode for panning pictures or pages by using sweep gestures, in accordance with an embodiment of the present invention;

[0080] **FIG. 43** is a simplified illustration of a menu user interface mode, in accordance with an embodiment of the present invention;

[0081] **FIG. 44** is a simplified illustration of a text input user interface mode, in accordance with an embodiment of the present invention;

[0082] **FIGS. 45 and 46** are simplified illustrations of touch screen systems with embedded reflective elements, in accordance with an embodiment of the present invention;

[0083] **FIG. 47** is a simplified illustration of a touch screen system with embedded photo receiver elements, in accordance with an embodiment of the present invention;

[0084] **FIG. 48** is a simplified illustration of a touch screen system with embedded light sources and embedded photo receiver elements, in accordance with an embodiment of the present invention;

[0085] **FIG. 49** is a simplified illustration of a touch screen system with a picture array that reads incoming light from spread locations, in accordance with an embodiment of the present invention;

[0086] **FIG. 50** is a simplified illustration of light from a pointed being reflected back into the touch screen of **FIG. 49**, in accordance with an embodiment of the present invention;

[0087] **FIG. 51** is a simplified illustration of light from a display being reflected from a pointer back into the touch screen of **FIG. 49**, in accordance with an embodiment of the present invention;

[0088] **FIG. 52** is a simplified illustration of light under a glass being reflected from a pointer back into a touch screen, in accordance with an embodiment of the present invention;

[0089] **FIG. 53** is a simplified illustration of a touch screen having detection points with reflective elements embedded in the screen glass, in accordance with an embodiment of the present invention;

[0090] **FIG. 54** is a simplified illustration of a light source positioned at a corner of the touch screen of **FIG. 53** that projects light into the screen glass, in accordance with an embodiment of the present invention;

[0091] **FIGS. 55 and 56** are simplified illustrations of light sources positioned along an edge of the touch screen of **FIG. 53** that project light

into the screen glass, in accordance with an embodiment of the present invention;

[0092] **FIG. 57** is a simplified illustration of a light source that projects light into a screen glass, in accordance with an embodiment of the present invention;

[0093] **FIG. 58** is a simplified illustration of an arrangement of three light sources of **FIG. 57** placed below the screen glass, which project light into the screen glass, in accordance with an embodiment of the present invention;

[0094] **FIG. 59** is a simplified illustration showing top and side views of light sources from the arrangement of **FIG. 55** with top-emitting LEDs placed below the screen glass, which project light into the screen glass, in accordance with an embodiment of the present invention;

[0095] **FIG. 60** is a simplified illustration showing top and side views of light sources from the arrangement of **FIG. 55** with side-emitting LEDs placed alongside the screen glass, which project light into the screen glass, in accordance with an embodiment of the present invention;

[0096] **FIG. 61** is a simplified illustration of light guides that direct light to a desired location in a glass screen of a touch screen system, in accordance with an embodiment of the present invention;

[0097] **FIG. 62** is a simplified illustration of a touch screen that serves as a light conductor, for guiding light emitted by an LED, in accordance with an embodiment of the present invention;

[0098] **FIG. 63** is a simplified illustration of the touch screen of **FIG. 62** with microstructures embedded in the glass, in accordance with an embodiment of the present invention;

[0099] **FIG. 64** is a simplified illustration of a touch screen that guides light over the surface of the touch screen, in accordance with an embodiment of the present invention;

[00100] **FIG. 65** is a simplified illustration of a touch screen with fibers integrated into the screen, in accordance with an embodiment of the present invention;

[00101] **FIGS. 66 - 68** are simplified illustrations of a photo detector for the touch screen system of **FIG. 53**, which is mounted vertical to a light source, in accordance with an embodiment of the present invention;

[00102] **FIG. 69** is a simplified illustration of reflected light being re-directed by a reflective element embedded in a touch screen and directed towards a photo detector, in accordance with an embodiment of the present invention;

[00103] **FIG. 70** is a simplified illustration of light that is reflected onto multiple areas of a touch screen and directed towards a photo detector, in accordance with an embodiment of the present invention;

[00104] **FIG. 71** is a simplified diagram of the touch screen system of **FIG. 53** with a camera that functions as a photo detector, in accordance with an embodiment of the present invention;

[00105] **FIGS. 72 - 79** are simplified illustrations of a camera lens capturing reflected light from the touch screen of **FIG. 53**, with the camera at various distances away from a pointer that is touching the screen, and the corresponding images captured by the camera, in accordance with an embodiment of the present invention;

[00106] **FIG. 80** is a simplified diagram of a side view showing the sub-patterns in the camera sensor generated from the embedded reflective elements, in accordance with an embodiment of the present invention;

[00107] **FIGS. 81 - 87** are images of light beams reflected from three different pointer touch locations, in accordance with an embodiment of the present invention;

[00108] **FIGS. 88 - 90** are simplified illustrations of a simulation of light at multiple points on a touch screen, at which reflective elements are embedded, in accordance with an embodiment of the present invention;

[00109] **FIGS. 91 and 92** are simplified illustrations of light emitted from an LED lighting up a fingertip of 4 mm x 4 mm, for the touch screen of **FIG. 88**, in accordance with an embodiment of the present invention;

[00110] **FIGS. 93 - 95** are images of test results captured by a camera for the touch screen of **FIG. 88**, in accordance with an embodiment of the present invention;

[00111] **FIG. 96** is a simplified diagram of a dual layer touch screen where the bottom layer transmits light emitted from an LED and the top layer transmits reflected light, in accordance with an embodiment of the present invention;

[00112] **FIG. 97** is a simplified diagram of a multi-layer touch screen with filamentary light guides, in accordance with an embodiment of the present invention;

[00113] **FIG. 98** is a simplified diagram of light beams guided through different layers of a multi-layer touch screen, in accordance with an embodiment of the present invention;

[00114] **FIG. 99** is a simplified diagram of a multi-layer touch screen with embedded reflective elements oriented in different directions, in accordance with an embodiment of the present invention;

[00115] **FIG. 100** is a simplified diagram of a touch screen with wide light beams covering the screen, in accordance with an embodiment of the present invention;

[00116] **FIG. 101** is a simplified diagram of a portion of a wide-beam touch screen, in accordance with an embodiment of the present invention; and

[00117] **FIG. 102** is a top view of a simplified diagram of lenses with applied feather patterns and light beams, in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

[00118] Aspects of the present invention relate to light-based touch screens and light-based touch surfaces. According to embodiments of the present invention, a light-based touch screen includes one or more infra-red or near infra-red light-emitting diodes (LEDs) and a plurality of photodiodes (PDs) arranged along the perimeter surrounding the touch screen or touch surface. The LEDs project light substantially parallel to the screen surface, and this light is detected by the PDs. A pointer, such as a finger or a stylus, placed over a portion of the screen blocks some of the light beams, and correspondingly some of the PDs detect less light intensity. The geometry of the locations of the PDs, and the light intensities they detect, suffice to determine screen coordinates of the pointer. The LEDs and PDs are controlled for selective activation and de-activation by a controller. Generally, each LED and PD has I/O connectors, and signals are transmitted to specify which LEDs and which PDs are activated.

[00119] In an embodiment of the present invention, plural LEDs are arranged along two adjacent sides of a rectangular screen, and plural PDs are arranged along the other two adjacent sides. In this regard, reference is now made to **FIG. 5**, which is a diagram of a touch screen **100** having 16 LEDs **130** and 16 PDs **140**, in accordance with an embodiment of the present invention. The LEDs **130** emit infra-red or near infra-red light beams across the top of the touch screen, which are detected by corresponding PD receivers that are directly opposite the LEDs. When a pointer touches touch screen **100**, it blocks light from reaching some of PD receivers **140**. By identifying, from the PD receiver outputs, which light beams have been blocked by the pointer, the pointer's location can be determined.

[00120] Reference is now made to **FIGS. 6 – 8**, which are diagrams of a touch screen that detects two pointers, **10** and **20**, that touch the screen simultaneously, in accordance with an embodiment of the present invention. When two or more pointers touch the screen simultaneously, this is referred to as a "multi-touch." Pointers **10** and **20**, which are touching the screen, block light from reaching some of PD receivers **140**. In accordance with an embodiment of the present invention, the locations of pointers **10** and **20** are determined from the crossed lines of the infra-red beams that the pointers block. In distinction, prior art resistance-based and capacitance-based touch screens are generally unable to detect a multi-touch.

[00121] When two or more pointers touch screen **100** simultaneously along a common horizontal or vertical axis, the positions of the pointers are determined by the PD receivers **140** that are blocked. Pointers **10** and **20** in **FIG. 6** are aligned along a common vertical axis and block substantially the same PD receivers **140** along the bottom edge of touch screen **100**; namely the PD receivers marked **a**, **b**, **c** and **d**. Along the left edge of touch screen, two different sets of PD receivers **140** are blocked. Pointer **10** blocks the PD receivers marked **e** and **f**, and pointer **20** blocks the PD receivers marked **g** and **h**. The two pointers are thus determined to be situated at two locations. Pointer **10** has screen coordinates located at the intersection of the light beams blocked from PD receivers **a – d** and PD receivers **e** and **f**; and pointer **20** has screen coordinates located at the intersection of the light beams blocked from PD receivers **a – d** and PD receivers **g** and **h**.

[00122] Pointers **10** and **20** shown in **FIGS. 7** and **8** are not aligned along a common horizontal or vertical axis, and they have different horizontal locations and different vertical locations. From the blocked PD receivers **a – h**, it is determined that pointers **10** and **20** are diagonally

opposite one another. They are either respectively touching the top right and bottom left of touch screen **100**, as illustrated in **FIG. 7**; or else respectively touching the bottom right and top left of touch screen **100**, as illustrated in **FIG. 8**.

[00123] Discriminating between **FIG. 7** and **FIG. 8** is resolved by either (i) associating the same meaning to both touch patterns, or (ii) by associating meaning to only one of the two touch patterns, or (iii) by measuring the amount of light detected at the blocked PDs. In case (i), the UI arranges its icons, or is otherwise configured, such that the effects of both touch patterns **FIG. 7** and **FIG. 8** are the same. For example, touching any two diagonally opposite corners of touch screen **100** operates to unlock the screen.

[00124] In case (ii), the UI arranges its icons, or is otherwise configured, such that only one of the touch patterns **FIG. 7** and **FIG. 8** has a meaning associated therewith. For example, touching the upper right and lower left corners of touch screen **100** operates to unlock the screen, and touch the lower right and upper left of touch screen **100** has no meaning associated therewith. In this case, the UI discriminates that **FIG. 7** is the correct touch pattern.

[00125] In case (iii), a finger closer to a PD blocks more light from reaching the PD than does a finger that is farther from the PD. In part, this is due to the closer finger blocking more ambient light from reaching the PD that does the farther finger. The light intensities at PDs **e** and **f** are compared with the light intensities detected at PDs **g** and **h**. Similarly, the light intensities detected at PDs **a** and **b** are compared with the light intensities detected at PDs **c** and **d**. If the light detected at **e**, **f** and at PDs **c** and **d** is greater than the light detected at PDs **g** and **h** and at PDs **a** and **b**, then it is inferred that the fingers are positioned as shown in **FIG. 7**. Similarly, if the light detected at PDs **e** and **f** and at

PDs **c** and **d** is less than the light detected at PDs **g** and **h** and at PDs **a** and **b**, then it is inferred that the fingers are positioned as shown in **FIG. 8**.

8. The comparison may be based on summing or averaging the respective blocked PDs along each edge separately, **e+f** vs. **g+h**, and **a+b** vs. **c+d**. Alternatively, the comparison may be based on summing or averaging blocked PDs along two edges; i.e., based on the maximum and minimum of the values **a+b+e+f**, **a+b+g+h**, **c+d+e+f**, and **c+d+g+h**. The maximum and minimum values determine the locations of the fingers. E.g., if **c+d+e+f** is the maximum value and if **a+b+g+h** is the minimum value, then it is inferred that the fingers are positioned as shown in **FIG. 7**.

[00126] Reference is now made to **FIGS. 9** and **10**, which are diagrams of a touch screen that detects a two finger glide movement, in accordance with an embodiment of the present invention. The glide movement illustrated in **FIGS. 9** and **10** is a diagonal glide that brings pointers **10** and **20** closer together. The direction of the glide is determined from changes in which PD receivers **140** are blocked. As shown in **FIGS. 9** and **10**, blocked PD receivers are changing from **a** and **b** to PD receivers **140** more to the right, and from **c** and **d** to PD receivers **140** more to the left. Similarly, blocked PD receivers are changing from **e** and **f** to PD receivers **140** more to the bottom, and from **g** and **h** to PD receivers **140** more to the top. For a glide in the opposite direction, that moves pointers **10** and **20** farther apart, the blocked PD receivers change in the opposite directions.

[00127] When pointers **10** and **20** are aligned in a common vertical or horizontal axis, there is no ambiguity in identifying glide patterns. When pointers **10** and **20** are not aligned in a common vertical or horizontal axis, there may be ambiguity in identifying glide patterns, as illustrated in **FIGS. 9** and **10**. In case of such ambiguity, and as described

hereinabove with reference to **FIGS. 7** and **8**, discriminating between **FIG. 9** and **FIG. 10** is resolved by either (i) by associating the same meaning to both glide patterns, or (ii) by associating meaning to only one of the two glide patterns, or (iii) by measuring and comparing the amounts of light detected at the blocked PDs.

[00128] Reference is now made to **FIG. 11**, which is a circuit diagram of touch screen **100** from **FIG. 5**, in accordance with an embodiment of the present invention. The LEDs **130** and PDs **140** are controlled by a controller (not shown). The LEDs receive respective signals *LED00* – *LED15* from LED switches **A**, and receive current from *VROW* and *VCOL* through current limiters **B**. The PDs receive respective signals *PD01* – *PD15* from shift register **120**. PD output is sent to the controller via signals *PDROW* and *PDCOL*. Operation of the controller, of LED switches **A** and of current limiters **B** is described in applicant's co-pending application, U.S. Application Serial No. 12/371,609 filed on February 15, 2009 and entitled LIGHT-BASED TOUCH SCREEN, the contents of which are hereby incorporated by reference.

[00129] According to an embodiment of the present invention, the LEDs are controlled via a first serial interface, which transmits a binary string to a shift register **110**. Each bit of the binary string corresponds to one of the LEDs, and indicates whether to activate or deactivate the corresponding LED, where a bit value "1" indicates activation and a bit value "0" indicates deactivation. Successive LEDs are activated and deactivated by shifting the bit string within shift register **110**.

[00130] Similarly, the PDs are controlled by a second serial interface, which transmits a binary string to a shift register **120**. Successive PDs are activated and deactivated by shifting the bit string in shift register **120**. Operation of shift registers **110** and **120** is described in applicant's co-pending application, U.S. Application Serial No. 12/371,609 filed on

February 15, 2009 and entitled LIGHT-BASED TOUCH SCREEN, the contents of which are hereby incorporated by reference.

[00131] In distinction to the embodiment shown in **FIG. 5**, in accordance with another embodiment of the present invention, four LEDs **130** are placed in the four corners of a touch screen, and plural PDs **140** are arranged along the four sides of the screen, as shown in **FIG. 12**. When an LED **130** is lit, it projects an arc of light substantially parallel to the surface of the screen. The PDs **140** detect respective portions of this light, according to the positions of the LED **130** and the PDs **140**. The four LEDs **130** suffice to determine the screen coordinates of a pointer, such as a finger, placed over a portion of the screen, based on the light intensities detected by the PDs **140**.

[00132] The present invention may be implemented in several types of touch screens, including inter alia (i) touch screens that are responsive to both blocked and reflected light, (ii) touch screens with selective area touch, (iii) touch screens with embedded reflective elements, (iv) touch screens with multi-layer screens, (v) touch screens with wide light beams, and (vi) touch screens with image sensors and image processing logic. Several implementation of the present invention are described hereinbelow, organized as configurations 1 - 33.

[00133] Reference is made to **FIG. 13**, which is a simplified diagram of a touch screen system responsive to blocked light and reflected light, in accordance with an embodiment of the present invention. Shown in **FIG. 13** is a touch screen system with a glass screen **210**, and a printed circuit board **220** with circuitry **225** for controlling the components mounted on it; namely, a plurality of near infra-red LEDs **230**, a first plurality of PDs **250**, and a second plurality of PDs **260**. Circuitry **225** is operative to generate signals in response to light emitted by LEDs **230**

that is blocked from PDs **250** by a pointer touching screen **210**, and in response to light that is reflected by the pointer to PDs **260**.

[00134] Details of the touch screen system of **FIG. 13** are described hereinbelow with reference to configurations nos. 1 – 3 and **FIGS. 21 – 30**.

[00135] Reference is made to **FIG. 14**, which is a simplified diagram of a touch screen system with selective area touch aligned with user interface buttons, in accordance with an embodiment of the present invention. Selective area touch refers to a touch screen for which a sub-area of the screen is touch-sensitive, and the remainder of the screen is not touch-sensitive. Generally, selective area touch is used with mid-size and large-size screens, for which it is unnecessary that the entire screen surface area be touch sensitive. The touch screen of **FIG. 14** provides a low cost solution by employing a small number of LEDs and PDs, which are strategically positioned so as to optimize touch detection in the touch sensitive sub-area.

[00136] For example, a user interface may include a touch-sensitive keyboard for text input. The location of the keyboard within the screen is designated, and then the LEDs and PDs are positioned so as to be able to detect touches on the keyboard keys. I.e., the LEDs and PDs are aligned to match the user interface. For another example, a user interface may include stylus support for handwriting on a corner of the screen.

[00137] The present invention is of particular advantage in providing low cost touch screens with selective area touch. Conventional capacitive and resistive touch screens are costly, since the required screen overlay generally cannot be used to cover only a sub-area of the screen surface. Furthermore, the wiring used in conventional capacitive and resistive touch screens generally traverses the entire screen. As such, for large screens the wires must be large and thick.

[00138] In distinction, the present invention is scalable, and the cost of the touch screen is generally proportional to the perimeter of the touch sensitive sub-area. The touch screen shown in **FIG. 32**, for example, uses only a single LED in a corner of the screen, and PDs along the edges that meet at the corner, for a keypad user interface. The PDs detect light reflected by a pointer touching the screen at one of the keypad buttons, which suffices to determine which button is being touched.

[00139] Shown in **FIG. 14** is a touch system with a glass screen **210** including a touch-sensitive sub-area **213** containing an array of buttons **215**, and a printed circuit board **220** with circuitry **225** for controlling a plurality of PDs **270** that are mounted thereon. Also shown in **FIG. 14** are lenses **280** which direct light to PDs **270**.

[00140] Reference is made to **FIG. 15**, which is a simplified diagram of another touch screen system with selective area touch, in accordance with an embodiment of the present invention. The touch-sensitive sub-area **213** shown in **FIG. 15** is non-rectangular shaped, and may be designated at will by a user interface designer. PDs **270** are positioned and oriented according to sub-area **213**, such that the touch screen is functional for detecting touches within sub-area **213** but not for detecting touches outside of sub-area **213**.

[00141] Details of the touch screen systems of **FIGS. 14** and **15** are described hereinbelow with reference to configurations nos. 4 – 14 and **FIGS. 31 – 44**.

[00142] Reference is made to **FIG. 16**, which is a simplified diagram of a touch screen system with reflective elements embedded in the screen, in accordance with an embodiment of the present invention. Shown in **FIG. 16** is a touch screen with a glass **210** that has reflective elements **217** embedded within the glass, and a printed circuit board **220** with circuitry **225** for controlling components mounted thereon; namely, a plurality of

LEDs **230** and a plurality of PDs **270**. Also shown in **FIG. 16** are lenses **240** that direct light emitted by LEDs **230** to reflective elements **217**.

When a pointer touches screen **210**, the light reflected by the pointer is detected at PDs **270**, and used to determine the location of the pointer.

[00143] Details of the touch screen system of **FIG. 16** are described hereinbelow with reference to configurations nos. 15 – 29 and **FIGS. 45 – 92**. **FIGS. 93 – 95** show test results of simulations of the touch screen system of **FIG. 16**.

[00144] Reference is made to **FIG. 17**, which is a simplified diagram of a touch screen system with a multi-layer screen, in accordance with an embodiment of the present invention. Shown in **FIG. 17** is a touch screen with a multi-layer glass **290**, and a printed circuit board **220** with circuitry **225** for controlling components mounted thereon; namely, LEDs **230** and PDs **270**. Light emitted from LEDs **230** is guided through some of the layers of glass **290**, and light received by PDs **270** is transmitted through others of the layers of glass **290**.

[00145] Details of the touch screen system of **FIG. 17** are described hereinbelow with reference to configurations nos. 30 and 31 and **FIGS. 96 – 99**.

[00146] Reference is made to **FIG. 18**, which is a simplified diagram of a light-based touch screen system, in accordance with an embodiment of the present invention. The touch screen system of **FIG. 18** does not require an overlay. Instead, a small frame **1** surrounds the display with infra-red or near LEDs **2** and photo receptors positioned on opposite sides of the screen, and hidden behind an infra-red transparent bezel. When a pointer, such as a finger or a stylus, touches the screen in a specific area **3**, one or more light beams generated by the LEDs are obstructed. The obstructed light beams are detected by corresponding decreases in light

received by one or more photo receptors, and are used to determine the location of the pointer.

[00147] The touch screen system of **FIG. 18** overcomes the disadvantages of conventional resistive and capacitive touch screen systems, described hereinabove. In particular, the touch screen system of **FIG. 5** is able to detect a multi-touch. The system is a low cost system, with low power requirements. The screen surface is 100% transparent, since there is no overlay. The system is able to capture fast pointer movements. The system is operable in an extended temperature range. The system supports both small and large screens. The system does not require calibration. The system has a durable glass surface.

[00148] A disadvantage of the touch screen system of **FIG. 18** is the bezel height, approximately 4 mm, surrounding the display.

[00149] Reference is made to **FIG. 19**, which is a simplified cross-sectional diagram of the touch screen system of **FIG. 18**, in accordance with an embodiment of the present invention. Shown in **FIG. 18** is a cross-sectional view of a section A-A of an LCD display and its surrounding infra-red transparent frame. The cross-sectional view shows an LED emitting light that is reflected by a cut-out in the frame, and directed substantially parallel over the display surface, as described in detail hereinbelow with reference to **FIGS. 24 - 29**. As a finger approaches near the display surface, some of the light emitted by the LEDs and directed over the location of the near touch is blocked by the finger, and some of the light passes between the fingertip and the screen glass. When the finger touches the display surface, all of the light emitted by the LEDs and directed over the touch location is blocked by the finger.

[00150] Reference is now made to **FIG. 20**, which is a simplified diagram of a light-based touch screen system with 4 LEDs and 4 photo detectors,

in accordance with an embodiment of the present invention. The system shown in **FIG. 20** is advantageous for a wide variety of screen sizes, including inter alia LCD panels, which typically range from 7" to 8", screens for e-book readers and netbooks, which typically range from 9" to 13", and HDTV panels and electronic billboards, which typically range from 42" to over 100".

[00151] As shown in **FIG. 20**, there are sixteen locations at which a pointer touch can be determined; namely, the intersections of the four horizontal and the four vertical lines. The system is thus able to identify touch inputs for sixteen icons, such as numbers and characters, that are displayed at these locations, as described in detail hereinbelow with reference to **FIGS. 41 - 44**.

[00152] It will thus be appreciated by those skilled in the art that the present invention enables selective area touch, to localize touch sensitive functionality to a designated sub-area of the display, such as inter alia the top right of the display, the bottom right of the display, the middle of the display, or the entire display. The sub-area with touch sensitive functionality may be selected by a designer, and the LEDs and photo detectors are then positioned and orientated accordingly.

Touch Screen System Configuration No. 1

[00153] Touch screen system configurations nos. 1 - 3 relate to using light reflected off of a pointer to determine the location of the pointer. In distinction, conventional light-based touch screens use only light blocked by a pointer to determine the location of the pointer.

[00154] Reference is made to **FIG. 21**, which is a simplified illustration of a touch screen system that measures blocked light and reflected light to determine a location of touch, in accordance with an embodiment of the present invention. Shown in **FIG. 21** is a top view with four near-

infrared LEDs, **NIR1**, **NIR2**, **NIR3** and **NIR4** arranged along the bottom edge of a screen, four PDs **Pd1**, **Pd2**, **Pd3** and **Pd4** arranged along the top edge of the screen, and four more PDs **Pd5**, **Pd6**, **Pd7** and **Pd8** arranged along the right edge of the screen. It is noted that PDs **Pd1**, **Pd2**, **Pd3** and **Pd4** are positioned directly across from respective LEDs **NIR1**, **NIR2**, **NIR3** and **NIR4**. The screen itself is positioned within the borders delineated by the LEDs and PDs, but is not shown.

[00155] A pointer **Pntr**, including inter alia a finger or a stylus, touching the screen blocks light emitted by one or more of the LEDs, and also reflects light emitted by one or more of the LEDs. The blocked light is identified by one or more of **Pd1**, **Pd2**, **Pd3** and **Pd4**, as a decrease of expected light. The reflected light is identified by one or more of **Pd5**, **Pd6**, **Pd7** and **Pd8** as an increase in expected light. Together, the location of the blocked light and the reflected light determine the location of pointer **Pntr**.

[00156] In **FIG. 21**, for example, light beams **Lb1**, **Lb2**, **Lb3** and **Lb4** from respective LEDs **NIR1**, **NIR2**, **NIR3** and **NIR4** are shown directed towards respective PDs **Pd1**, **Pd2**, **Pd3** and **Pd4**. Similarly, reflected light beams **Pb1**, **Pb2**, **Pb3** and **Pb4** are shown directed towards respective PDs **Pd5**, **Pd6**, **Pd7** and **Pd8**. A reflected light beam **Pb1**, **Pb2**, **Pb3** or **Pb4** is generated when a pointer is placed in the path of one of light beams **Lb1**, **Lb2**, **Lb3** or **Lb4** at an appropriate position. As shown in **FIG. 21**, **Pntr** is placed in the path of **Lb1** opposite **Pd7**. Blocked light is detected at **Pd1** and reflected light is detected at **Pd7**, thus determining the location of pointer **Pntr** at the intersection of the vertical line from **Pd1** and the horizontal line from **Pd7**. In this case, reflected light beams **Pb1**, **Pb2** and **Pb4** are not generated.

[00157] A controller operating the touch screen system of **FIG. 21**, pulses the LEDs separately. When a single LED is activated, the PD

located directly across therefrom is read, and each of the PDs **Pd5**, **Pd6**, **Pd7** and **Pd8** are also read. When pointer **Pntr** touches the screen, light blocked by **Pntr** is identified at one or more of PDs **Pd1**, **Pd2**, **Pd3** and **Pd4**, and light reflected by **Pntr** is identified at one or more of PDs **Pd5**, **Pd6**, **Pd7** and **Pd8**. Referring to **FIG. 21**, the signal detected at **Pd1** when **NIR1** is activated, is lower than the signals detected at **Pd2**, **Pd3** and **Pd4** when respective LEDs **NIR2**, **NIR3** and **NIR4** are activated, as a result of blocked beam **Lb1**; and the signal at **Pd7** is higher than the signals at **Pd5**, **Pd6** and **Pd8** as a result of reflected beam **Pb3**. Thus the location of **Pntr** is determined to be at the coordinates (**Pd1**, **Pd7**).

[00158] It will be appreciated by those skilled in the art that analysis of intensity of light reflected by a pointer and read by a PD leads to determination of both a horizontal and a vertical position of a pointer. Specifically, referring to **FIG. 21**, if PD **Pd7** detects reflected light, then it may be inferred that a pointer is located somewhere on the horizontal line from **Pd7**. Furthermore, the intensity of reflected light read by **Pd7** is a function of the distance of the pointer from **Pd7**. The closer the pointer is to **Pd7**, the higher the intensity of the reflected light read by **Pd7**. As such, the intensity of the reflected light may be used to infer at which vertical line the pointer is located. Use of intensity to infer distance is a feature of reflected light, but not of blocked light. As such, reflected light generally provides more information than blocked light.

[00159] Reference is made to **FIG. 22**, which is a simplified illustration of reflector lenses used with the touch screen system of **FIG. 21**, in accordance with an embodiment of the present invention. The four edges **E1**, **E2**, **E3** and **E4** of the touch screen are shown. As shown in **FIG. 22**, reflector lenses are only provided at two of the four edges. A first reflector lens is provided at edge **E1** along which LEDs **NIR1**, **NIR2**, **NIR3** and **NIR4** are positioned, in order to direct light beams **Lb1**, **Lb2**,

Lb3 and **Lb4** emitted from respective LEDs **NIR1**, **NIR2**, **NIR3** and **NIR4** across the surface of the screen to respective PEDs **Pd1**, **Pd2**, **Pd3** and **Pd4**. A second reflector lens is provided at edge **E3** in order to direct the light beams transmitted across the surface of the screen to respective PDs **Pd1**, **Pd2**, **Pd3** and **Pd4**.

[00160] As described below with reference to **FIG. 29**, PDs **Pd5**, **Pd6**, **Pd7** and **Pd8**, which detect reflected light, are positioned below the screen surface and do not require a reflector lens above the screen. As such, edge **E2** does not have a reflector lens.

Touch Screen System Configuration No. 2

[00161] Reference is made to **FIG. 23**, which is a simplified illustration of a touch screen system with PDs positioned along three edges of a touch screen, in accordance with an embodiment of the present invention. By adding PDs along edge **E4**, the touch screen system is able to achieve higher precision in determining the location of **Pntr**. Moreover, the touch screen system is able to determine a multi-touch; i.e., the locations of multiple pointers touching the screen simultaneously.

[00162] As with the system of **FIG. 21**, the NIRs are pulsed separately. When an NIR is activated, the PD across from the NIR along edge **E3**, and the PDs along edges **E2** and **E4**, are read. Blocked light is detected by the PD along edge **E3**. Reflected light is detected by the PDs along edges **E2** and **E4**.

[00163] In the case of a single pointer touch, the sets of PDs along edges **E2** and **E4** achieve better resolution than a single set of PDs along edge **E2**, as in the system of **FIG. 21**. Specifically, the relative intensities of reflected light detected at a PD along edge **E2** and a PD along edge **E4** determine the distance of the pointer from each respective edge.

[00164] In the case of multiple pointer touches, consider for example two pointers touching two diagonal corners of the screen. A first pointer is closer to edge **E2** than to edge **E4**, and a second pointer is closer to edge **E4** than to edge **E2**. For each pointer, the light reflected to its closer edge is brighter than the light reflected to its farther edge. The relative intensities of light reflected onto the closer and farther edge determine the position of each pointer between the edges. In addition, if blocked light is detected at non-adjacent PDs along edge **E3**, then this indicates that two pointers are touching the screen. Similarly, if reflected light is detected at non-adjacent PDs along edges **E2** and **E4**, then this also indicates that two pointers are touching the screen. E.g., if reflected light is detected at a PD along **E2** near **E3**, and also at a PD along **E4** near **E1**, then this indicates that two pointers are touching the screen. If reflected light is detected at a PD along **E2** near **E3** and at non-adjacent PD along **E2** near **E1**, with an intermediate PD that does not detect reflected light, then this indicates that two pointers are touching the screen.

[00165] Reference is made to **FIG. 24**, which is a simplified illustration of a portion of a touch screen display and surrounding frame, in accordance with an embodiment of the present invention.

[00166] Reference is also made to **FIG. 25**, which is a projection view of the section of **FIG. 24** designated A-A, in accordance with an embodiment of the present invention. Shown in **FIG. 25** is an infra-red transparent frame **1**, an infra-red LED **3**, and a display **5**. Frame **1** may be inter alia a photo frame, a monitor, a TV or an e-book. Also shown in **FIG. 25** is a cut-out **2** in frame **1**. The air gap from cut out **2** generates a mirror with a 45° surface, which directs reflected light **4** above the surface of display **5**.

[00167] Reference is made to **FIG. 26**, which is a simplified diagram of an LED for a touch screen system, with a diode that emits light from the

side, in accordance with an embodiment of the present invention. Shown in **FIG. 26** is a liquid crystal display (LCD) **L1**, a product casing **C1**, a lens and dust protector **Lg1**, and an LED **Cb1** with a side-emitting diode.

[00168] Reference is made to **FIG. 27**, which is a simplified diagram of an LED for a touch screen system, with a diode that emits lights from the top, in accordance with an embodiment of the present invention. Shown in **FIG. 27** is an LCD **L1**, a product casing **C1**, an LED **Cb1** with a top-emitting diode, and a light guide **Lg1** that receives light from LED **Cb1** and re-directs the light over the surface of **L1**.

[00169] Reference is made to **FIG. 28**, which is a simplified diagram of an optical element that focuses light emitted by an LED focused into a narrow beam, in accordance with an embodiment of the present invention. Shown in **FIG. 28** is an LCD **L0**, a PD **L1**, a light beam **Li1** emitted by an LED (not shown) near **L1** and focused by an optical element **O1**, such that light is reflected into a reflected beam **R1** only when a pointer **P1** is sufficiently close to LCD **L0**. The focus of optimal element **O1** ensures the only the focused beam **R1** passes through **O1** to PD **L1**.

[00170] Reference is made to **FIG. 29**, which is a simplified diagram of a PD that is placed underneath the plane of a touch screen for detecting reflected light above the touch screen, in accordance with an embodiment of the present invention. Shown in **FIG. 29** is a display **L1**, a protection glass **G1** overlaying **L1**, and a PD **Pd1** situated underneath **G1**. A pointer **P1** generates a reflected light beam **Pi1**, which is directed by a cutout in **G1** to **Pd1**. As such, reflected light beam **Pi1** is detected by **Pd1** beneath **G1**.

Touch Screen System Configuration No. 3

[00171] Reference is made to **FIG. 30**, which is a simplified illustration of an arrangement of photo diodes, photo transistors and optical elements that enable a touch screen system to read pointers that are smaller than the sensor elements, in accordance with an embodiment of the present invention. Shown in **FIG. 30** are a mirror or optical lens **901**, an infrared LED **902**, a reflected light beam **903**, a pointer **904** and a PD **905**.

Mirror or optical lens **901** generates a wide light beam that is focused onto PD **905** by a second mirror or optical lens. The wide beam makes it possible to sense an analog change in the amount of light detected at PD **905** when a pointer blocks a portion of the wide beam. The wide beam enables sensing an analog change when pointer **904** is placed in front of mirror or lens **901**. The wide beam also enables mounting the mirrors or lenses far apart from one another.

[00172] Without the wide beam, there are generally spaces between beams that go undetected, making it impossible to distinguish between a user dragging a pointer across the beams, and the user tapping on different beams. Moreover, with widely spaced narrow beams the pointer touch must be very precise in order to cross a narrow beam.

Touch Screen System Configuration No. 4

[00173] Touch screen system configurations nos. 4 – 14 relate to selective area touch; namely, the ability to localize pointer location detection to a sub-area of the screen. Selective area touch significantly reduces the cost of providing touch functionality for large screens, by limiting touch functionality to one or more designated areas of the screen; e.g., to one corner of the screen. In distinction, resistive and capacitive touch screen films cannot cover only a sub-area of the screen. In addition, resistive and capacitive touch screen technologies perform

poorly when signal lines are long, as is the case for large screens where the signal lines extend the entire length or width of the screen, even if the touch location is confined to one corner of the screen.

[00174] Reference is made to **FIG. 31**, which is a simplified illustration of a touch screen system with selective area touch, in accordance with an embodiment of the present invention. Shown in **FIG. 31** are three LEDs mounted on a printed circuit board (PCB) **Lb1**, and eight PDs mounted on a PCB **Cb1**. PCBs **Lb1** and **Cb1** are connected by a cable **K1** to enable control via a single integrated circuit (not shown). The PDs are arranged three along the top, for detecting light blocked by a pointer near the surface of a screen; and five arranged along the side, for detecting light reflected by the pointer.

[00175] The configuration shown in **FIG. 31** supports selective area touch, whereby touch screen functionality is enabled on only a portion of the screen. Selective area touch is advantageous inter alia for large screens, for which it would be costly and power consuming to provide touch functionality for the entire screen, due to the large number of LEDs and PDs required to surround the screen. By providing only a small number of LEDs and PDs along portions of the screen edges, the cost is reduced. Moreover, by positioning the PDs close to one another, high precision touch functionality is achieved in the touch sensitive area of the screen.

[00176] Shown in **FIG. 31** are button icons **P1** aligned with the PD arrangement; namely, three columns of buttons aligned with the three PDs along the top edge of the screen, and five rows of buttons aligned with the five PDs along the right edge of the screen. Such alignment enables accurate detection of which one of the buttons **P1** is being touched by a user.

Touch Screen System Configuration No. 5

[00177] Reference is made to **FIG. 32**, which is a simplified illustration of another touch screen system with selective area touch, in accordance with an embodiment of the present invention. Shown in **FIG. 32** is a single LED **Ld1** and eight PDs mounted on a PCB **Cb1**. The PDs read light reflected from **Ld1**; i.e., light emitted by **Ld1** that is reflected by a pointer (not shown) close to or touching the screen.

Touch Screen System Configuration No. 6

[00178] Reference is made to **FIG. 33**, which is a simplified illustration of another touch screen system with selective touch area, in accordance with an embodiment of the present invention. Shown in **FIG. 33** are three LEDs L1, L2 and L3 and five PDs Pd1, Pd2, Pd3, Pd4 and Pd5 mounted on a PCB. Also shown in **FIG. 33** is an optical element O1 which directs light emitted from the LEDs along a plane substantially parallel to and near the screen surface. The PDs read light reflected from the LEDs; i.e., light emitted by the LEDs that is reflected by a pointer (not shown) close to or touching the screen.

[00179] The LEDs are activated separately. If reflected light is detected at a PD, a column coordinate is determined based on the currently activated LED, and a row coordinate is determined based on the PD that detected the reflected light. E.g., if a pointer touches the button marked "1", the second from top PD detects reflected light when the leftmost LED is activated. Similarly, if a pointer touches the button marked "2", the second from top PD detects reflected light when the middle LED is activated. It will thus be appreciated by those skilled in the art that the two-dimensional location of a pointer touch is determined using a single row of LEDs, activated serially, and using a single column of PDs activated in parallel.

Touch Screen System Configuration No. 7

[00180] Reference is made to **FIG. 34**, which is a simplified illustration of another touch screen system with selective touch area, in accordance with an embodiment of the present invention. Shown in **FIG. 34** are three LEDs **L1**, **L2** and **L3** and five PDs **Pd1**, **Pd2**, **Pd3**, **Pd4** and **Pd5**, mounted close together on a small PCB. The PDs read light reflected from the LEDs. A first optical element **O1** directs the light emitted from each LED over a corresponding column of the screen, and substantially parallel to the screen. A second optical element **O2** directs the reflected light to the PDs. The system of **FIG. 34** operates similar to the system of **FIG. 33**; however, optical elements **O1** and **O2** enable use of a small PCB to house all of the LEDs and PDs. Optical element **O1** ensures that light from each LED is directed over a designed area of the screen. Optical element **O2** ensures that light reflected by a pointer is directed from the designated area of the screen to the PDs.

Touch Screen System Configuration No. 8

[00181] Reference is made to **FIG. 35**, which is a simplified illustration of a touch screen with four LEDs and 4 PDs surrounding the screen, in accordance with an embodiment of the present invention. The touch screen shown in **FIG. 35** is generally a large screen; e.g., a 42" television display.

[00182] Reference is also made to **FIG. 36**, which is a simplified illustration of a finger blocking one of the light beams of **FIG. 36**, in accordance with an embodiment of the present invention. The light blocked by the finger is detected by respective PDs, and indicates the location of the finger. A user interface displays icons or buttons on the

screen at positions aligned with the positions of the LEDs and the PDs, where placement of a pointer can be detected.

Touch Screen System Configuration No. 9

[00183] In accordance with an embodiment of the present invention, more LEDs and PDs than those shown in **FIGS. 35** and **36** are employed, and positioned closer together. E.g., instead of two LEDs per each of the two edges as in **FIGS. 35** and **36**, 10 LEDs are placed along each of the two edges, spaced 5 mm apart from one another, concentrated in one portion of each edge. A corresponding number of PDs are positioned in a similar dense arrangement in portions of the other edges. The light beams emitted by the LEDs thus form a dense matrix over a sub-area of the screen.

[00184] Such an arrangement of LEDs and PDs enables accurate precision detection of touches and gestures in the touch sensitive sub-area of the screen. As shown in **FIGS. 35** and **36**, the photodiodes are preferably positioned close to the touch sensitive sub-area of the screen. Such an arrangement improves accuracy of pointer touch location detection, since each touch is close to the PD that senses its location.

Touch Screen System Configuration No. 10

[00185] Reference is made to **FIG. 37**, which is a simplified illustration of a touch screen with light beams that are focused diagonally relative to the screen edges, in accordance with an embodiment of the present invention.

[00186] Reference is also made to **FIG. 38**, which is a simplified illustration of a finger blocking one of the light beams of **FIG. 37**, in accordance with an embodiment of the present invention. **FIGS. 37** and **38** show that location of a pointer touching the screen can be determined

by a single light beam that is blocked. Such a configuration is of particular advantage when only a few buttons are needed to operate a user interface of a device.

Touch Screen System Configuration No. 11

[00187] Reference is made to **FIG. 39**, which is a simplified illustration of a touch screen that uses light beams projected in two non-orthogonal directions across a portion of the screen surface, in accordance with an embodiment of the present invention. **FIG. 39** also shows that light from a single LED can be sensed by sensors positioned along different screen edges, by guiding the light beams in multiple directions.

[00188] Such a configuration provides multiple screen coordinates that can be distinguished based on a combination of PDs that detect blocked light. E.g., each point of intersection between two beams is uniquely identified by two PDs that detect blocked light. Moreover, if only a single PD detects missing light, it can be inferred that the pointer has been placed along the blocked light beam away from the area where the beams intersect. Thus additional buttons or icons can be placed on the screen anywhere along the path of a beam and away from the area where the beams intersect. When only a single beam is detected as being blocked, the user interface may activate a function corresponding to the additional icon or button associated with the single beam, as it infers that a pointer is touching it.

Touch Screen System Configuration No. 12

[00189] Reference is made to **FIG. 40**, which is a simplified illustration of a touch screen with a single LED and multiple PDs arranged along each of two adjacent screen edges, in accordance with an embodiment of the present invention. A lens (not shown) directs light from each LED on one

edge to each of the PDs on the other edge. In this configuration, the light beams are shorter than the dimensions of the screen. As shown in **FIG. 40**, nodes are generated by intersecting light beams. The location of a pointer touching a node is detected by a combination of photodiodes that detect blocked light.

Touch Screen System Configuration No. 13

[00190] According to an embodiment of the present invention, instead of one LED emitting light beams to multiple PDs, a plurality of LEDs positioned along a portion of a first screen edge emit light beams to a like plurality of PDs along a section of a second adjacent screen edge. Furthermore, a plurality of LEDs positioned along a section of the second edge emit light beams to a like plurality of PDs along a section of the first screen edge. Along the first and second edges, the LEDs and PDs are interlaced as PD LED PD LED PD LED ... The light beam emitted from an LED on one edge is directed by one or more lenses to one or more PDs along the adjacent edge. The plurality of light beams emitted by an LED, directed by a lens, and received by a PD, thus form a crisscross pattern over a sub-area of the screen, thereby enabling accurate detection of pointer touch locations and pointer gestures.

Touch Screen System Configuration No. 14

[00191] Touch screen configuration no. 14 is particularly useful for devices with large screens, including inter alia notebook computers, GPS navigators, electronic games and toys, digital photo frames, monitors, TVs and e-books, where high image fidelity and low cost are important. No overlay covers the display. The number of LEDs and PDs is kept to a minimum necessary to detect the user inputs that are required, such as text and number input.

[00192] For electronic games, digital photo frames, monitors, TVs and e-books, picture quality is a very important factor. Specifically, such devices require full clarity, making an overlay undesirable. Such devices also require pure and real colors, a wide viewing angle, a high contrast ratio and a high brightness. Picture quality depends to some extent on the cost and quality of the LCD screen. High quality LCDs are expensive, but provide the best picture quality.

[00193] Conventional touch screen systems, such as resistive and capacitive based systems, have several drawbacks. They require additional glass or plastic layers over the LCD glass, which causes a reduction of picture quality. They have undesirable reflections from internal layers of the screen, reduced contrast ratio, altered colors, reduced viewing angle and increased backlight requirements.

[00194] Moreover, the cost of a device such as a digital photo frame is dominated primarily by the LCD and by the application processor and its memory. Resistive and capacitive overlays of conventional touch screens can double the cost of the device.

[00195] The touch screen systems of the present invention overcome all of these drawbacks. Touch screen systems of the present invention use a small bezel around the display screen, as a lens to project an invisible light field across the display surface. The bezel is generally comprised of an infrared-transparent plastic. For some devices, such as inter alia digital photo frames, a bezel is desirable since it resembles a conventional photo frame.

[00196] Below the bezel, LEDs and photo receptors are arranged on opposite sides of the screen. A controller pulses the LEDs to create invisible light fields across the display surface. When a pointer touches the screen, it obstructs the light field. The blocked light is detected by the photo receptors, and used to determine the location of the touch.

Additional signal processing is used to identify a multi-touch, a pointer contour, and high speed sweeps and other gestures.

[00197] The touch screen systems of the present invention have a fast sampling rate, and are able to detect high speed movements on the screen to accurately trace complex finger or stylus gestures. The touch screen systems of the present invention can detect multiple simultaneous pointer touches, can measure the area of each touch, and track each pointer's motion and velocity.

[00198] Reference is made to **FIG. 41**, which is a simplified illustration of a touch screen system with eight LEDs positioned along two adjacent edges of a display area, and eight PDs positioned along the opposite edges of the display area, in accordance with an embodiment of the present invention. Shown in **FIG. 41** are infra-red LEDs **1 – 8** positioned along two adjacent edges of a display area, and infra-red photo detectors **9 – 16** positioned along opposite edges of the display area. Each LED at one edge of the display area, with a corresponding photo detector at the opposite edge of the display, defines a detection line. Detection lines are horizontally or vertically oriented. When an LED is turned on, the corresponding photo detector opposite the LED senses the light from the LED. This light is the expected light. However, the presence of a pointer on the detection line blocks the expected light, and is detected when at least a portion of the expected light from the LED is not detected by the photo detector.

[00199] Horizontal and vertical detection lines intersect at intersection points. Point **18** is one such intersection point. A pointer **19** may sweep over a portion of the display area, thus creating a gesture. An arrow **20** indicates a sweep gesture performed by pointer **19**. The sweep gesture is detected by photo detectors **13, 14** and **15** sensing an absence of expected light from corresponding LEDs **1, 2** and **3**, due to pointer **19**

blocking light from the LEDs as it sweeps over the display area. Absence of light is sensed serially from left to right; i.e., as pointer **19** sweeps from left to right photo detector **13** detects an absence of expected light, then photo detector **14** detects an absence of expected light, and then photo detector **15** detects an absence of expected light. Similarly, absence of expected light is sensed serially from right to left when pointer **19** sweeps from right to left.

[00200] In general, a left-to-right sweep is detected when at least two detection lines are swept over from left to right. A left-to-right sweep activates a user interface command, such as inter alia a command to display a previous picture in a sequence of pictures displayed on a photo frame, or a command to display a previous page of an e-book.

[00201] An arrow **17** indicates a sweep gesture in the opposite direction to that of arrow **20**; namely, from right to left. A right-to-left sweep activates a user interface command, such as inter alia a command to display a next picture in a sequence of pictures displayed on a photo frame, or a command to display a next page of an e-book.

[00202] A left-to-right or right-to-left sweep can be detected anywhere over the vertical detection lines; i.e., a sweep need not traverse intersection points. Similarly, an up or down sweep can be detected anywhere over the horizontal detection lines. As such, additional gesture support is provided outside the intersection points. The user interface can thus display buttons at intersection points and indicate sweeps outside of the button area. The interface can indicate a sweep by an arrow or by a dynamic video object that slides along the path of the sweep. According to an embodiment of the present invention, the user interface enables a user to toggle sweep detection on and off. In this case, a detected sweep activates a user interface command only when sweep detection is turned on.

[00203] According to another embodiment of the present invention, the user interface enables a user to select a user interface mode from a plurality of possible modes. Each user interface mode associates a different set of commands with sweep gestures. E.g., a first mode is a standard viewing mode, in which a right-to-left sweep navigates to a next picture or page, and a left-to-right sweep navigates to a previous picture or page. A second mode is a zoom mode, in which a picture or page being viewed is larger than the display, and only a portion of the picture or page is displayed. The displayed portion is referred to as the "visible window". In zoom mode, sweep gestures are used to pan the picture or page; i.e., to display different portions of the picture or page, effectively sliding the visible window over the picture or page. A right-to-left sweep may, for example, pan the picture or page to the left, to display a portion of the picture or page that was previously outside to the right of the display area, effectively sliding the visible window to the right. Similarly, a left-to-right sweep may, for example, pan the picture or page to the right, to display a portion of the picture or page that was previously outside to the left of the display area, effectively sliding the visible window to the left. A vertical sweep may, for example, pan the picture or page upwards or downwards. Diagonal sweeps may also be detected as combined horizontal and vertical sweeps, to pan the picture or page in a diagonal direction.

[00204] Reference is now made to **FIG. 42**, which is a simplified illustration of a zoom user interface mode for panning pictures or pages by using sweep gestures, in accordance with an embodiment of the present invention. When a pointer sweeps over two or more adjacent vertical detection lines from right to left, the currently displayed picture or page is panned to the left. When a pointer sweeps over two or more adjacent vertical detection lines from left to right, the currently displayed

picture or page is panned to the right. When a pointer sweeps over two or more adjacent horizontal detection lines from top to bottom, the currently displayed picture or page is panned downwards. When a pointer sweeps over two or more adjacent horizontal detection lines from bottom to top, the currently displayed picture or page is panned upwards.

[00205] Shown in **FIG. 42** is a zoom button **1** at a point of intersection of a horizontal and a vertical detection line. Tapping on zoom button **1** generates a user interface command, such as inter alia, toggling in and out of zoom mode, or changing the zoom factor to increase or decrease the magnification. An arrow **2** shows a left-to-right sweep gesture. An arrow **3** shows a bottom-to-top sweep gesture. The sweep gesture can be detected anywhere over the vertical and horizontal detection lines, except for the intersection points occupied by icons along the right side of the display area.

[00206] Reference is made to **FIG. 43**, which is a simplified illustration of a menu user interface mode, in accordance with an embodiment of the present invention. Three settings are shown in **FIG. 43** along the left side of the screen; namely, brightness, contrast and wired equivalent privacy (WEP). A slide bar **1** indicates that additional settings are available. A tap on the up arrow shown at the top of slide bar **1** causes the three settings to change to other settings, thus navigating through a list of settings. A tap on the down arrow shown at the bottom of slide bar **1** causes the settings to navigate in the other direction through the list of settings.

[00207] A slide bar **2** indicates a current value of a corresponding setting; namely, a brightness setting, a contrast setting and a WEP character string. By tapping with a pointer on the right or left arrows of slide bar **2**, a user causes the value of a setting to increment or decrement, respectively. An extended touch on the right of left arrow of

slide bar **2** causes the value of a setting to increment or decrement continuously until the touch is released.

[00208] Each button in **FIG. 43** is positioned at a cross point between intersecting detection lines, making it possible to identify which button is being touched by a pointer. A tap on icon **3** generates a user interface command to display an alphanumeric keypad for inputting text and numbers.

[00209] Reference is made to **FIG. 44**, which is a simplified illustration of a text input user interface mode, in accordance with an embodiment of the present invention. By using repeated taps, referred to as "multi-tap" with the displayed keyboard, a user selects one of a plurality of characters associated with a button. As such, a full set of characters and numbers are available for input. In addition, a predictive text algorithm, such as T9, may be used to assist the user in inputting words. A button **1**, shown in **FIG. 44**, is associated with the characters w, x, y, z and the number 9. Each button is positioned at a cross point between horizontal and vertical detection lines, thus making it possible to detect which button a pointer is touching.

Touch Screen System Configuration No. 15

[00210] Touch screen system configurations nos. 15 – 29 relate to reflective elements that are embedded in a glass front for a touch screen system.

[00211] Reference is made to **FIG. 45**, which is a simplified illustration of a touch screen system with embedded reflective elements, in accordance with an embodiment of the present invention. Shown in **FIG. 45** is a glass **600** with reflective elements **601** embedded therein. Light generated from under glass **600** by a backlight or an organic light emitting diode (OLED) hits a finger, and generates reflected light rays

602, 603, 604 and **605**. The reflected rays are directed by reflective elements **601** through glass **600** to one or more photo detectors.

Touch Screen System Configuration No. 16

[00212] Reference is made to **FIG. 46**, which is a simplified illustration of another touch screen system with embedded reflective elements, in accordance with an embodiment of the present invention. Shown in **FIG. 46** is a glass **500** with light emitting elements **501** and **502** embedded therein, and a photo detector **503** also embedded in glass **500** or situated beneath glass **500**. Light emitting elements **501** and **502** are arranged to emit light at different angles, enabling determination of the height of a pointer over glass **500** based on the light reflected by the pointer.

[00213] The finger in **FIG. 46** is shown at two heights above glass **500**. Light emitting elements **501** and **502** are activated separately in order to determine which light emitter is detected by photo detector **503**. Since light emitters **501** and **502** emit beams at different angles relative to glass **500**, when the finger is farther from glass **500**, light from light emitter **502** is detected by photo detector **503** and light from light emitter **501** is not detected; and when the finger is placed closer to glass **500**, light from light emitter **501** is detected by photo detector **503**, and light from light emitter **502** is not detected. Since light emitters **501** and **502** are activated separately, the location and orientation of a light emitter determines the location and height of the finger above glass **500**.

[00214] In general, the number of light emitters and photo detectors used in a specific system varies depending on the required functionality, on the resolution and on cost constraints. For some systems, the light emitters and photo detectors are strategically placed so as to detect touch and proximity at designated screen locations used by user interface

icons and gestures. As such, placement and orientation of the light emitters and photo detectors is based on the user interface design. A touch screen controller uses the known locations and orientations of the light emitters and photo detectors to calculate the location and height of a finger approaching the screen or of a finger touching the screen.

Touch Screen System Configuration No. 17

[00215] Reference is made to **FIG. 47**, which is a simplified illustration of a touch screen system with embedded photo receiver elements, in accordance with an embodiment of the present invention. Shown in **FIG. 47** are a glass **300**, photo receiver elements **301**, a row control line **303** for reading signals from a row of photo receiver elements **301**, and a control line **304** for reading signals from all such row control lines **303**. Photo receiver elements **301** are embedded into glass **300**, and function to read a picture of a pointer using display light, i.e., light emitted by the display that is reflected back onto the glass **500** by one or more pointers, or using ambient light, or using a combination of display light and ambient light.

Touch Screen System Configuration No. 18

[00216] Reference is made to **FIG. 48**, which is a simplified illustration of a touch screen system with embedded light sources and embedded photo receiver elements, in accordance with an embodiment of the present invention. Shown in **FIG. 48** are a glass **700**, photo receiver elements **701**, light sources **702**, a row control line **703** for controlling a row of light sources **702** and for reading signals from a row of photo receiver elements **701**, and a control line **704** for controlling all such row control lines **703** and for reading signals from all such row control lines **703**.

Touch Screen System Configuration No. 19

[00217] Reference is made to **FIG. 49**, which is a simplified illustration of a touch screen system with a picture array that reads incoming light from spread locations, in accordance with an embodiment of the present invention. Shown in **FIG. 49** is a glass **401**, an area **402** with embedded reflective elements that break light into glass **401**, directed light **403**, a two-dimensional or three-dimensional picture array **404**, and an additional light source **405**. Light from each reflective element in the screen is projected to a corresponding location on picture array **404**, thereby enabling detection of the location of the reflective element that is being touched, based on the location of the pixel in picture array **404** that detects the touch.

[00218] When light emitted by the screen is used to detect the location of a pointer touching the screen, the touch corresponds to an increase in detected light, since the pointer reflects projected light back onto picture array **404** via a reflective element. In distinction, when ambient light is used to detect the location of a pointer touching the screen, the touch corresponds to a decrease in detected light, as the pointer blocks ambient light from being projected onto picture array **404** via a reflective element.

[00219] Alternatively, the image at picture array **404** may be analyzed to locate contours of a pointer touching the screen. In this case, the image at picture array **404** corresponds to an image of the screen surface.

[00220] Reference is made to **FIG. 50**, which is a simplified illustration of light from a pointer being reflected back into the touch screen of **FIG. 49**, in accordance with an embodiment of the present invention. Shown in **FIG. 50** is a display **801**, a photo detector **802**, an additional light source **803**, embedded reflective elements **804** and a glass front **805** for the display **801**.

[00221] Inside glass front **805** are embedded reflective elements that (i) redirect light arriving from light source **803** to project the light above the screen, as indicated by the arrows pointing up in **FIG. 50**, and (ii) direct light that is reflected by a pointer back into the screen, to photo detector **802**.

[00222] Reference is made to **FIG. 51**, which is a simplified illustration of light from a display being reflected from a pointer back into the touch screen of **FIG. 49**, in accordance with an embodiment of the present invention. Shown in **FIG. 51** is a backlight **90**, a display **91**, a photo detector **92**, a protection glass **93** and an LCD **94**. Embedded inside protection glass **93** are reflective elements that direct light reflected by a pointer back into the screen, to photo detector **92**. The backlight from display **91** is modulated and synchronized with photo detector **92**.

[00223] Reference is made to **FIG. 52**, which is a simplified illustration of light under a glass being reflected from a pointer back into a touch screen, in accordance with an embodiment of the present invention. Shown in **FIG. 52** is a main board **80**, a display **81**, a light receiver **82**, light beams **83** and a protection glass **84**. No reflective elements are required to be embedded in protection glass **84**. Light is projected in an arc above the screen surface, and a pointer substantially reflects oncoming light beams in the opposite direction, so as to be detected by light receiver **82**. Light receiver **82** is preferably a pixel array that detects a plurality of light beams. Analysis of saturated pixels indicates the location of the touch pointer.

Touch Screen System Configuration No. 20

[00224] Reference is made to **FIG. 53**, which is a simplified illustration of a touch screen having detection points with reflective elements embedded in the screen glass, in accordance with an embodiment of the present

invention. A screen glass has reflective elements embedded in the glass, shown in **FIG. 53** as dots. The dots are shown organized in the geometry of a lattice. LEDs emitting infra-red or near infra-red light are used as light sources for the touch screen.

[00225] The LEDs emit light from the edge of the screen glass through the glass, as described hereinabove with reference to **FIG. 50**. The light is projected upward by the embedded reflective elements. A pointer reflects the upward projecting light back onto a reflective element, and the reflective element projects the light back onto a light sensor, or onto an image sensor with a two-dimensional pixel array.

[00226] Reference is made to **FIG. 54**, which is a simplified illustration of a light source positioned at a corner of the touch screen of **FIG. 53** that projects light into the screen glass, in accordance with an embodiment of the present invention. In this embodiment, all of the emitted light beams are generated from the corner of the touch screen, with small angle variations between adjacent beams. As the distance between reflective elements and the light source increases, the angle between light beams directed at neighboring reflective elements decreases. As such, in large screens, such as 13" or 42" screens, the angle between light beams directed at neighboring reflective elements located at the far end of the screen is very small.

[00227] Preferably, a two-dimensional or three-dimensional picture array, similar to picture array **404** of **FIG. 49**, is used here as well. Light from each reflective element in the screen is projected to a corresponding location on the picture array, thus enabling determination of the location of the reflective element being touched based on the location of the pixel in the picture array that detects the touch.

[00228] In an alternative embodiment, the light source positioned at the corner of the touch screen is configured to emit successive beams of light

individually. As such, only one light beam aimed at one reflective element is generated at any given time. When a pointer reflects the light back onto a light sensor (not shown), the touch screen determines the location of the pointer as corresponding to the location of the single reflective element at which the light beam is aimed.

Touch Screen System Configuration No. 21

[00229] Reference is made to **FIGS. 55** and **56**, which are simplified illustrations of light sources positioned along an edge of the touch screen of **FIG. 53** that project light into the screen glass, in accordance with an embodiment of the present invention. Preferably, as shown in **FIG. 55**, the touch screen system is arranged so that the light beams emitted by the light sources do not overlap; i.e., they generate non-overlapping cones. As such, there is an upper bound on the angle of each cone, which depends upon the width of the touch screen. E.g., if the light sources are arranged along the long screen edge spaced a distance d apart, and if the width of the touch screen is w , then the maximum angle is $2 \cdot \tan^{-1}(\frac{d}{2w}) \approx \frac{d}{w}$ (in radians). As such, if the light sources are spaced 5 mm apart, as in **FIG. 56**, then for a touch screen width of 30 mm the maximum angle is approximately 10° , and for a touch screen width of 110 mm the maximum angle is approximately 2.5° .

[00230] Reference is made to **FIG. 57**, which is a simplified illustration of a light source that projects light into a screen glass, in accordance with an embodiment of the present invention. Reference is also made to **FIG. 58**, which is a simplified illustration of an arrangement of three light sources of **FIG. 57** placed below the screen glass, which project light into the screen glass, in accordance with an embodiment of the present invention.

[00231] Shown in **FIG. 57** is a reflective wedge, aligned with the left edge of a screen glass. The screen glass is shown as having a thickness. The wedge diagonal may be planar, or curved such as an elliptical mirror. The wedge receives light beams from a light source below the screen, and reflects the light beams into the screen glass. As shown in **FIG. 57**, the bottom of the wedge is configured to break a cone of light into separate beams such that each beam, when reflected by the wedge, is directed through the screen glass substantially parallel with the screen surface.

[00232] A corresponding reflective wedge (not shown) is placed at the opposite edge of the screen to direct light beams arriving through screen onto a light sensor or pixel array.

[00233] Reference is made to **FIG. 59**, which is a simplified illustration showing top and side views of light sources from the arrangement of **FIG. 55** with top-emitting LEDs placed below the screen glass, which project light into the screen, in accordance with an embodiment of the present invention. A PCB is positioned below the glass screen, and the LEDs are mounted on the PCB below the glass side and to the side. An optical element, such as the wedge of **FIG. 57**, controls the angles of the cones of light shown travelling through the screen glass. Shown in **FIG. 59** are top and side views of two top-emitting LEDs and a reflector, or optical element, along an edge of the glass screen, that directs light from the LEDs through the screen glass.

[00234] The arrangements of **FIGS. 57** and **58** may be modified to project the light cones of **FIG. 59**, in which case the reflective elements direct the light onto an expanding cone instead of a parallel swath through the screen glass.

Touch Screen System Configuration No. 22

[00235] Reference is made to **FIG. 60**, which is a simplified illustration showing top and side views of light sources from the arrangement of **FIG. 55** with side-emitting LEDs placed alongside the screen glass, which project light into the screen glass, in accordance with an embodiment of the present invention. Shown in **FIG. 60** are top and side views of two side-emitting LEDs and a reflector along an edge of the glass screen. Whereas the LEDs in **FIG. 59** are below the screen surface, the LEDs in **FIG. 60** are aligned with the screen glass level.

Touch Screen System Configuration No. 23

[00236] Reference is made to **FIG. 61**, which is a simplified illustration of light guides that direct light to a desired destination in a glass screen of a touch screen system, in accordance with an embodiment of the present invention. As shown in **FIG. 61**, filamentary light guides direct light from along a side of the glass screen to a desired destination.

Touch Screen System Configuration No. 24

[00237] Reference is made to **FIG. 62**, which is a simplified illustration of a touch screen that serves as a light conductor, for guiding light emitted by an LED, in accordance with an embodiment of the present invention. **FIG. 62** is a side view of a touch screen that acts as a light guide.

[00238] Reference is made to **FIG. 63**, which is a simplified illustration of the touch screen of **FIG. 62** with microstructures embedded in the glass, in accordance with an embodiment of the present invention. **FIG. 63** shows that microstructures embedded in the bottom of the touch screen leak portions of light through the top surface of the touch screen. Light reflected by a pointer touching the screen is led back into the light guide to a photo detector.

Touch Screen System Configuration No. 25

[00239] Reference is made to **FIG. 64**, which is a simplified illustration of a touch screen that guides light over the surface of the touch screen, in accordance with an embodiment of the present invention. As shown in **FIG. 64**, light is led in along a parallel plane plate, and exits over the surface of the touch screen. Alternatively, a wedge-shaped plate may be used instead of a parallel plane plate.

Touch Screen System Configuration No. 26

[00240] Reference is made to **FIG. 65**, which is a simplified illustration of a touch screen with fibers integrated into the screen, in accordance with an embodiment of the present invention. Small fibers are used to collect light from a light source and guide the light to a desired destination. The fibers may be round or square fibers, and may be arranged as a fan or as a lattice. Shown in **FIG. 65** are top and side views of fibers arranged as a lattice. For some screens, the lattice arrangement is preferable, since a fan arrangement, in combination with the pixel structure of the display, may generate an undesired Moiré pattern.

[00241] The fibers may be inserted into the touch screen. Alternatively, the touch screen can be designed to be comprised of fibers.

Touch Screen System Configuration No. 27

[00242] Reference is made to **FIGS. 66 - 68**, which are simplified illustrations of a photo detector for the touch screen system of **FIG. 53**, which is mounted vertical to a light source, in accordance with an embodiment of the present invention. The photo detector may be inter alia a photo diode, a light sensor or a camera. As shown in **FIG. 66**, a photo detector is mounted perpendicular to the directions of the light

emitted by the light source. Such arrangement minimizes leakage. Since the amount of light reaching the photo detector is generally less than the amount of light emitted by the light source, photo detectors are preferably positioned along the longer edge of the screen, and light sources are preferably arranged along the shorter edge. Moreover, each photo detector preferably captures light from a single column of embedded reflective elements. Correspondingly, the angle viewed by the photo detector depends on the length of the screen. If the photo detectors are spaced a distance d apart along the shorter edge and if the longer edge is of length x , then the maximum angle viewed by a photo detector is $\tan^{-1}(\frac{d}{x}) \approx \frac{d}{x}$ (in radians). E.g., if the photo detectors are spaced 5 mm apart, then for a touch screen length of 40 mm the maximum viewing angle is approximately 7° , and for a touch screen length of 145 mm the maximum viewing angle is approximately 2° . **FIG. 67** shows a touch screen with a simple light guide geometry, and **FIG. 68** shows a touch screen with dual layer lighting.

[00243] It is noted that having the light beams travel a longer distance before being reflected over the screen surface enables projecting a wide, substantially parallel, light beam across the screen surface. If instead the light were to travel only a short distance before being projected over the screen surface, the light beam would be shaped as a cone with a narrow end at its source. Similarly, it is of advantage to have the wide light beam traverse a longer distance after it traverses the screen, in order that the full wide beam converge with minimal leakage onto a single photo detector.

[00244] Reference is made to **FIG. 69**, which is a simplified illustration of reflected light being re-directed by a reflective element embedded in a touch screen and directed towards a photo detector, in accordance with an embodiment of the present invention. As shown in **FIG. 69**, light

reflected from a pointer is guided back into the screen. The light stops at one of the reflective elements embedded in the screen, and is detected by a photo detector below the screen.

[00245] Reference is made to **FIG. 70**, which is a simplified illustration of light that is reflected onto multiple areas of a touch screen and directed towards a photo detector, in accordance with an embodiment of the present invention. As shown in **FIG. 70**, light reflected onto multiple areas on the screen surface by a pointer is reflected by reflective elements embedded in the screen and directed to a photo detector outside of the screen surface. Thus, light reflected by a pointer is reflected back to a photo detector.

[00246] For a lattice spacing of 10 mm between the reflective elements and the photo detector, approximately 0.6% of the light is detected by the photo detector, and for a lattice spacing of 15 mm between the reflective elements and the photo detector, approximately 0.4% of the light is detected by the photo detector. In general, the amount of light detected by the photo detector depends on the size of the photo detector and the optic elements used.

Touch Screen System Configuration No. 28

[00247] Configuration no. 28 relates to a camera chip that is used as a photo detector of a touch screen. The image of the touch screen captured by the camera is used to infer the location of a pointer that touches the touch screen, or approaches the touch screen.

[00248] Reference is made to **FIG. 71**, which is a simplified diagram of the touch screen system of **FIG. 53** with a camera that functions as a photo detector, in accordance with an embodiment of the present invention. To obtain an optimal image on the camera sensor, the camera is oriented at an angle with respect to an edge of the touch screen, and

arranged so as to collect light at a wide angle. Generally the surface of the touch screen at which the light exits should be approximately concentric with the camera lens.

[00249] In order to minimize lateral angle, it is preferable to mount the camera at a corner of the touch screen. Alternatively, two or more cameras may be used.

[00250] When a pointer touches the screen, or approaches near the screen, a pattern, such as one of the patterns in **FIG. 71**, from the reflective elements embedded in the screen is projected to the camera chip. The light pattern on the camera sensor provides information regarding the distance between the camera and the pointer.

[00251] The two left portions of **FIG. 71** show the touch screen with reflected light at two different distances from the camera lens. The two right portions of **FIG. 71** show the corresponding patterns on the camera sensor. As shown in **FIG. 71**, a larger distance between the camera and the pointer corresponds to a larger number of sub-patterns on the camera sensor.

[00252] Reference is made to **FIG. 72**, which is a simplified illustration of a camera lens capturing reflected light from the touch screen of **FIG. 53**, with the camera 10 mm away from a pointer that is touching the screen, in accordance with an embodiment of the present invention.

[00253] Reference is also made to **FIG. 73**, which is an image captured by the camera of **FIG. 72**, from three reflective elements spaced 5 mm apart and located 10 mm from the screen edge, in accordance with an embodiment of the present invention.

[00254] Reference is made to **FIG. 74**, which is a simplified illustration of a camera lens capturing reflected light from the touch screen of **FIG. 53**, with the camera 20 mm away from a pointer that is touching the screen, in accordance with an embodiment of the present invention.

[00255] Reference is also made to **FIG. 75**, which is an image captured by the camera of **FIG. 74**, from three reflective elements spaced 5 mm apart and located 20 mm from the screen edge, in accordance with an embodiment of the present invention.

[00256] Reference is made to **FIG. 76**, which is a simplified illustration of a camera lens capturing reflected light from the touch screen of **FIG. 53**, with the camera 30 mm away from a pointer that is touching the screen, in accordance with an embodiment of the present invention.

[00257] Reference is also made to **FIG. 77**, which is an image captured by the camera of **FIG. 76**, from three reflective elements spaced 5 mm apart and located 30 mm from the screen edge, in accordance with an embodiment of the present invention.

[00258] Reference is made to **FIG. 78**, which is a simplified illustration of a camera lens capturing reflected light from the touch screen of **FIG. 53**, with the camera 39 mm away from a pointer that is touching the screen, in accordance with an embodiment of the present invention.

[00259] Reference is also made to **FIG. 79**, which is an image captured by the camera of **FIG. 78**, from three reflective elements spaced 5 mm apart and located 39 mm from the screen edge, in accordance with an embodiment of the present invention. By comparing the respective captured images in **FIGS. 73, 75, 77** and **79**, it will be appreciated that the number of sub-patterns in the images corresponds to the distance between the pointer and the camera lens.

[00260] Reference is made to **FIG. 80**, which is a simplified diagram of a side view showing the sub-patterns in the camera sensor generated from the embedded reflective elements, in accordance with an embodiment of the present invention. In the configuration of **FIGS. 72, 74, 76** and **78**, a light source, along an edge of the display screen that is 1 mm thick, is 20 mm away from the camera lens. For such configuration, five sub-

patterns are generated on the camera sensor; namely a central sub-pattern corresponding to an image directly in the center, and two sub-patterns corresponding to reflected images on each side of the central sub-pattern. The sub-patterns correspond to focuses of light from different depths of field; i.e., from different distances at different positions along the beam direction. Shorter focus distances generate fewer but larger sub-patterns, and longer focus distances generate more but smaller sub-patterns. As such, longer focus distances are preferable, as it is easier for a system to count the number of elements than to measure the size of an element.

[00261] Reference is made to **FIGS. 81 - 87**, which are images of light beams reflected from three different pointer touch locations, in accordance with an embodiment of the present invention. The three top portions of **FIG. 81** show the actual camera sensor images, and the three bottom portions of **FIG. 81** show the corresponding optics between the camera lens and the camera sensor. The rightmost portion shows six sub-patterns in the image on the camera sensor, corresponding to a pointer touch location that is far from the camera lens.

Touch Screen System Configuration No. 29

[00262] Configuration no. 29 relates to a light sensor that is used as a photo detector of a touch screen. The advantage of a light sensor over a camera is a larger sensor area that may be used for light detection. The LEDs and light sensors may be frequency modulated in order to improve detection sensitivity.

[00263] Reference is made to **FIGS. 88 - 90**, which are simplified illustrations of a simulation of light at multiple points on a touch screen, at which reflective elements are embedded, in accordance with an embodiment of the present invention. Shown in **FIG. 88** are circular dots

on the touch screen, representing embedded reflective elements. As shown in **FIG. 89**, the circular dots have a relative fill factor of 20%, and the pixel dimensions for the touch screen are approximately 3 mm x 3 mm.

[00264] Reference is made to **FIGS. 91** and **92**, which are simplified illustrations of light emitted from an LED lighting up a fingertip of 4 mm x 4 mm, for the touch screen of **FIG. 88**, in accordance with an embodiment of the present invention. The distance between the LED and the area occupied by the reflective elements is approximately 10 mm. Approximately 3% of the incoming light from the LED lights up the fingertip. The darker lines in **FIG. 91** represent light that escapes from the glass, and the lighter lines represent light inside the glass. **FIG. 91** shows light escaping from the glass surface at a dot location that is 10 mm away from the LED, indicated by a white diamond.

[00265] **FIG. 92** shows only those light beams that reach the dot location. The small box shown at the upper right corner of **FIG. 92** represents a camera that captures the reflected light.

[00266] Reference is made to **FIGS. 93 – 95**, which are images of test results captured by a camera for the touch screen of **FIG. 88**, in accordance with an embodiment of the present invention. The tests used a large screen display of dimensions 30 mm x 40 mm and 1 mm thickness. The tests used simple light guides, of 5 mm thickness. The tests are based on a camera lens with focal length $f = 1.4$ mm and a diameter of 0.7 mm. The tests were simulated from three points on the touch screen at different distances from the camera lens.

[00267] The images shown in **FIGS. 93 – 95** were captured using a mobile phone camera. **FIG. 93** shows an ambient state, where no pointer is touching the screen, and **FIG. 94** shows a state where a pointer is touching the screen. **FIG. 95** shows the results when the

image of **FIG. 93** is subtracted from the image of **FIG. 94**, and the difference is scaled up by a factor of 10.

[00268] The distance of the pointer from the camera lens may be determined from the number of sub-patterns in the captured images and their positions. The positions of the sub-patterns determine the direction from which the light arrives.

Touch Screen System Configuration No. 30

[00269] Configurations nos. 30 and 31 relate to a multi-layer touch screen, with separate layers used to emit light and to detect light.

[00270] To minimize leakage, two or more layers of screen surface are employed, in order to separate layers used to emit light from layers used to detect light. Preferably a faceted or curved grating is used to direct the light across the plane of the touch screen. The reflector for the touch screen may be shaped as a cylinder, or otherwise shaped.

[00271] Reference is made to **FIG. 96**, which is a simplified diagram of a dual layer touch screen where the bottom layer transmits light emitted from an LED and the top layer transmits reflected light, in accordance with an embodiment of the present invention. To reduce space along the sides of the touch screen, it is preferable to focus the light beams narrowly, to direct the light beams along different layers of the touch screen, and to avoid a cluster of light sources in a single group. Instead, the light sources should be distributed.

[00272] Reference is made to **FIG. 97**, which is a simplified diagram of a multi-layer touch screen with filamentary light guides, in accordance with an embodiment of the present invention. **FIG. 97** shows light cut through filamentary light guides, arranged in multiple layers, to reduce space. The touch screen of **FIG. 97** is assembled in several stages, with filamentary light guides running both horizontally and vertically, in order

to accommodate an appropriate number of light beams. Optical fibers may be attached to the screen in order to reduce space.

[00273] By emitting the light beams at different times, the signal-to-noise ratio is increased, and the detection accuracy is made more precise. By regularly sampling the dark, ambient light signal, detection sensitivity is enhanced. Specifically, the signal-to-noise ratio is increased by subtracting the dark, ambient light signal from the active signal. Preferably, this subtraction is implemented in the analog domain instead of the digital domain, since subtraction of images in the digital domain generally requires high resolution.

[00274] Reference is made to **FIG. 98**, which is a simplified diagram of light beams guided through different layers of a multi-layer touch screen, in accordance with an embodiment of the present invention. In order to prevent stray light from being incident, and to prevent reflected light from being transmitted in a wrong direction, the light beams are guided through different layers of the touch screen.

Touch Screen System Configuration No. 31

[00275] Reference is made to **FIG. 99**, which is a simplified diagram of a multi-layer touch screen with embedded reflective elements oriented in different directions, in accordance with an embodiment of the present invention. As shown in **FIG. 99**, incident and reflected light is stopped at reflective elements embedded in the touch screen and oriented in different directions. Use of embedded reflective elements in two different directions serves to minimize leakage between light emitters and light detectors, prevents stray light from being incident, and prevents reflected light from being transmitted in a wrong direction.

Touch Screen System Configuration No. 32

[00276] Reference is made to **FIG. 100**, which is a simplified diagram of a touch screen with wide light beams covering the screen, in accordance with an embodiment of the present invention. Touch screen systems using wide beams are described in applicant's provisional patent application, U.S. Application Serial No. 61/317,255 filed on March 24, 2010 and entitled OPTICAL TOUCH SCREEN WITH WIDE BEAM TRANSMITTERS AND RECEIVERS, the contents of which are hereby incorporated by reference.

[00277] The LEDs and PDs shown in **FIG. 100** are spaced relatively widely apart. Generally, the LEDs are not activated simultaneously. Instead, they are activated one after another, and the coverage areas of their light beams are substantially connected.

[00278] **FIG. 100** shows a top view and a side view of a touch system having a touch screen or touch surface **1000**. The touch system provides touch-sensitive functionality to a surface irrespective of whether or not the surface includes a display screen. Moreover, a physical surface is not required; the light beams may be projected through the air, and the location of a pointer in mid-air that breaks the light beams may be detected.

[00279] Also shown in **FIG. 100** are LEDs **1002**, reflectors **1004** and **1005**, and PDs **1007**. LEDs **1002** and PDs **1007** are positioned beneath screen **1000**. LEDs **1002** project arcs **1003** of light under screen **1000** onto reflectors **1004**. The distance between LEDs **1002** and reflectors **1004** is sufficient for an arc to spread into a wide beam at a reflector **1004**. In various embodiments of the present invention, the distance between LEDs **1002** and reflectors **1004** may be approximately 4 mm, 10 mm, 20 mm or greater, depending on factors including inter alia

screen size, required touch resolution, LED characteristics and optical reflector characteristics.

[00280] Reflectors **1004** direct the light as wide beams **1001** across a swath of screen surface. A wide beams **1001** reaches reflectors **1005**, which (i) redirect the light beam below screen **1000**, and (ii) narrow the wide beam **1001** into arcs **1006**. As such, a wide beam **1001** converges into the surface of one of PDs **1007** below the surface of screen **1000**.

[00281] The configuration of **FIG. 100** is of advantage in that the wide light beams cover the entire screen surface, thereby enabling touch sensitive functionality anywhere on the screen. Additionally, the cost of materials for the touch screen is reduced, since relatively few LEDs and PD components are needed.

Touch Screen System Configuration No. 33

[00282] Reference is made to **FIG. 101**, which is a simplified diagram of a portion of a wide-beam touch screen, in accordance with an embodiment of the present invention. A feather pattern **10** is shown applied to the surface of a lens associated with a photo detector **11**. Feather pattern **10** may also be applied to the surface of a lens associated with a light source.

[00283] When applied to the lens of photo detector **11**, feather pattern **10** is operative to transmit light to photo detector **11** from different angles, instead of from a uniform angle. When applied to the lens of a light source, feather pattern **10** is operative to transmit light emitted at different angles from the light source, in a uniform direction over the screen. A light arc **12** indicates light output through feather pattern **10** that is directed to photo detector **11**.

[00284] Reference is made to **FIG. 102**, which is a top view of a simplified diagram of lenses with applied feather patterns **21** and light

beams **20** and **22**, in accordance with an embodiment of the present invention. The light beams are shown in **FIG. 102** entering lens **21** as parallel beams and exiting lens **21** as non-parallel beams. In a similar manner, when a feather patterned lens is inserted before a light source, non-parallel light beams **22** enter the lens and exit as parallel beams **20**.

[00285] The present invention has broad application to electronic devices with touch sensitive screens, including small-size, mid-size and large-size screens. Such devices include inter alia computers, home entertainment systems, car entertainment systems, security systems, PDAs, cell phones, electronic games and toys, digital photo frames, digital musical instruments, e-book readers, TVs and GPS navigators.

[00286] In the foregoing specification, the invention has been described with reference to specific exemplary embodiments thereof. It will, however, be evident that various modifications and changes may be made to the specific exemplary embodiments without departing from the broader spirit and scope of the invention as set forth in the appended claims. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

CLAIMS

What is claimed is:

- 1.** A touch screen system, comprising:

 - a near-infrared transparent screen comprising a plurality of reflective elements embedded therein;
 - a circuit board comprising circuitry for controlled selective activation of electronic components connected thereto;
 - at least one light source connected to said circuit board, for emitting light; and
 - at least one light detector connected to said circuit board, for detecting light emitted by said at least one light source and reflected by said reflective elements.
- 2.** The touch screen system of claim **1** further comprising at least one optical element for guiding light emitted by said at least one light source towards said reflective elements.
- 3.** The touch screen system of claim **2** wherein said plurality of optical elements comprises fibers.
- 4.** The touch screen system of claim **2** wherein said plurality of optical elements comprises elliptical mirrors.
- 5.** The touch screen system of claim **2** wherein said plurality of optical elements comprise filament light guides.
- 6.** The touch screen system of claim **2** wherein said plurality of optical elements comprises wedge-shaped plates.

- 7.** The touch screen system of claim **2** wherein said plurality of optical elements comprise planar plates positioned parallel to said near-infrared transparent screen.
- 8.** The touch screen system of claim **1** wherein said at least one light detector comprises at least one camera.
- 9.** The touch screen system of claim **1** wherein said at least one light detector comprises at least one photo detector.
- 10.** The touch screen system of claim **1** wherein said at least one light source is placed underneath said near-infrared transparent screen.
- 11.** The touch screen system of claim **1** wherein said at least one light detector is placed underneath said near-infrared transparent screen.
- 12.** The touch screen system of claim **1** wherein said near-infrared transparent screen comprises at least two layers, wherein said at least one light source emits light in a first layer and said at least one light detector detects light transmitted in a second layer.
- 13.** A touch screen system comprising:
a display screen;
a circuit board comprising circuitry for controlled selective activation of electronic components connected thereto;
a plurality of near-infrared LEDs connected to said circuit board, for emitting light;
a first plurality of photo diodes connected to said circuit board, for detecting received light along a first edge of said display screen; and

a second plurality of photo diodes connected to said circuit board, for detecting received light along a second edge of said display screen,
wherein said circuitry generates signals responsive to blocked light from said near-infrared LEDs detected at said first plurality of photo diodes and signals responsive to reflected light from said near-infrared LEDs detected at said second plurality of photo diodes.

14. The touch screen system of claim **13** wherein said circuitry calculates a position of a pointer that touches said display screen, based on the signals for the blocked light and the signals for the reflected light signals.

15. The touch screen system of claim **13** further comprising at least one optical element for guiding light emitted by said near-infrared NIRs over said touch screen.

16. The touch screen system of claim **13** wherein said near-infrared LEDs are embedded within said display screen.

17. The touch screen system of claim **13** wherein said display screen comprises a plurality of reflective elements embedded therein, which reflect light emitted by said near-infrared LEDs.

18. The touch screen system of claim **13** wherein said first plurality of photo diodes are embedded within said display screen.

19. The touch screen system of claim **13** wherein said second plurality of photo diodes are embedded within said display screen.

- 20.** A touch screen system, comprising:
- a display screen for displaying a plurality of buttons at designated horizontal and vertical screen coordinates thereon;
 - a plurality of photo diodes coupled with said display screen, for detecting received light; and
 - a plurality of lenses coupled with said display screen,
- wherein the designated horizontal and vertical screen coordinates span a touch sensitive sub-area of said display screen, wherein said photo diodes and lenses are positioned so as to detect a touch of said display screen at the touch sensitive sub-area, and wherein the remainder of said display screen is non-functional for detecting screen coordinates of a touch thereof.
- 21.** The touch screen system of claim **20** wherein the touch sensitive sub-area comprises less than 25% of the area of said display screen.
- 22.** The touch screen system of claim **20** wherein the touch sensitive sub-area comprises less than 10% of the area of said display screen.
- 23.** The touch screen system of claim **20** wherein the touch sensitive sub-area is situated in a corner of said display screen.
- 24.** The touch screen system of claim **20** wherein said touch sensitive sub-area is surrounded on four sides by portions of the remainder of said display screen.
- 25.** The touch screen system of claim **20** wherein said display screen is between 6" and 9" in length.

26. The touch screen system of claim **20** wherein said display screen is at least 30" in length.

27. The touch screen system of claim **20** wherein said display screen is at least 40" in length.

28. The touch screen system of claim **20** wherein said photo diodes are spaced approximately 10 mm apart.

29. The touch screen system of claim **20** wherein a first coordinate of a touch location is determined based on light detected by at least one of said photo diodes, and a second coordinate of the touch location is determined by correlating the detected light with an activation of at least one of said light sources.

30. A touch screen system, comprising:
a display screen comprising a touch sensitive sub-area;
a plurality of photo diodes coupled with said display screen, for detecting received light; and
a plurality of lenses coupled with said display screen,
wherein said photo diodes and said lenses are positioned so as to detect the position of a touch of said display screen within said touch sensitive sub-area, and wherein the remainder of said display screen is non-functional for detecting the location of a touch thereof.

31. The touch screen system of claim **30** wherein the touch sensitive sub-area comprises less than 25% of the area of said display screen.

- 32.** The touch screen system of claim **30** wherein the touch sensitive sub-area comprises less than 10% of the area of said display screen.
- 33.** The touch screen system of claim **30** wherein the touch sensitive sub-area is situated in a corner of said display screen.
- 34.** The touch screen system of claim **30** wherein said touch sensitive sub-area is surrounded on four sides by portions of the remainder of said display screen.
- 35.** The touch screen system of claim **30** wherein said lenses are operative to focus wide beams of light onto said photo diodes, the touch screen further comprising a processor connected to said photo diodes for calculating a position of a pen tip that touches said display screen within one of the wide beams.
- 36.** The touch screen system of claim **35** wherein said processor calculates the position of the pen tip based upon a light intensity detected by at least one of said photo diodes.
- 37.** The touch screen system of claim **35** wherein said processor calculates the position of the pen tip along one axis based upon light intensities detected by the photo diodes along a single axis.
- 38.** The touch screen system of claim **30** wherein said display screen is between 6" and 9" in length.
- 39.** The touch screen system of claim **30** wherein said display screen is at least 30" in length.

40. The touch screen system of claim **30** wherein said display screen is at least 40" in length.

41. The touch screen system of claim **30** wherein said photo diodes are spaced approximately 10 mm apart.

42. The touch screen system of claim **30** wherein a first coordinate of a touch location is determined based on light detected by at least one of said photo diodes, and a second coordinate of the touch location is determined by correlating the detected light with an activation of at least one of said light sources.

43. A touch screen system comprising:
a display screen comprising a plurality of layers substantially parallel to one another;
a circuit board comprising circuitry for controlled selective activation of electronic components connected thereto;
a plurality of near-infrared LEDs connected to said circuit board, for emitting light that is guided through a first layer of said display screen; and
a plurality of photo diodes connected to said circuit board, for receiving light that is guided through a second layer of said display screen,
wherein said circuitry generates signals responsive to light detected at said plurality of photo diodes.

44. A touch screen system, comprising:
a screen;

a plurality of light sources coupled with said screen, for emitting light;

a plurality of photo diodes coupled with said screen, for detecting the light emitted by said light sources, and for identifying the location of a touch on said screen when an absence of the emitted light is detected;
and

a plurality of lenses coupled respectively with said plurality of light sources to generate wide beams of light over a portion of said screen wherein substantially connected areas of said screen are covered by neighboring wide beams.

45. The touch screen system of claim **44** further comprising a second plurality of lenses coupled respectively with said plurality of photo diodes to narrow the wide beams onto said photo diodes.

46. The touch screen system of claim **45** wherein said second lenses are placed at least 4 mm away from respective ones of said photo diodes.

47. The touch screen system of claim **46** wherein said photo diodes and said second lenses are placed adjacent to an edge of said screen.

48. The touch screen system of claim **46** wherein said light sources are placed under said screen and said second lenses are placed adjacent to an edge of said screen.

49. The touch screen system of claim **44** wherein a first set of the wide beams span the length of said screen and a second set of the wide beams span the width of said screen, wherein an overlap between the first and second sets defines a touch-sensitive sub-area of said screen,

and wherein the remainder of said screen is non-functional for detecting the location of a touch thereon.

50. The touch screen system of claim **49** wherein the touch sensitive sub-area is situated in a corner of said screen.

51. The touch screen system of claim **49** wherein the touch sensitive sub-area is surrounded on four sides by portions of the remainder of said screen.

52. The touch screen system of claim **44** further comprising a processor connected to said photo diodes for calculating a location of a pen tip that touches said screen within one of the wide beams.

53. The touch screen system of claim **52** wherein said processor calculates the location of the pen tip based upon a light intensity detected by at least one of said photo diodes.

54. The touch screen system of claim **52** wherein said processor calculates the location of the pen tip along one axis based upon light intensities detected by said photo diodes along a single axis.

55. The touch screen system of claim **44** wherein said screen is between 6" and 9" in length.

56. The touch screen system of claim **44** wherein said screen is at least 30" in length.

57. The touch screen system of claim **44** wherein said screen is at least 40" in length.

58. The touch screen system of claim **44** wherein said photo diodes are spaced approximately 10 mm apart.

59. The touch screen system of claim **44** wherein a first coordinate of a touch location is determined based on light detected by at least one of said photo diodes, and a second coordinate of the touch location is determined by correlating the detected light with an activation of at least one of said light sources.

60. The touch screen system of claim **44** wherein said lenses are placed at least 4 mm away from respective ones of said light sources.

61. The touch screen system of claim **60** wherein said light sources are placed under said screen and said first lenses are placed adjacent to an edge of said screen.

62. The touch screen system of claim **60** wherein said light sources and said first lenses are placed adjacent to an edge of said screen.

63. The touch screen system of claim **44** wherein said lenses are placed at least 10 mm away from respective ones of said light source.

64. The touch screen system of claim **44** wherein said lenses are placed at least 20 mm away from respective ones of said light sources.