

Description

The present invention relates to rotary peripheral milling cutter tools. In particular, it relates to rotary peripheral milling cutter tools having a longitudinal axis of rotation and having a cutting insert provided with a cutting edge defined between a cutting rake surface and a relief flank having a base edge defined between the relief flank and the base surface.

BACKGROUND OF THE INVENTION

It is known that during milling cutting operations the length of the cutting edge is directly related to the vibrations induced in the milling cutter and the workpiece and the energy requirements in carrying out the cutting operation. These vibrations give rise to so-called "chatter". In other words, "chatter" tends to increase with increasing length of the cutting edge.

The vibrations and consequent "chatter" arise out of the forces exerted on the cutting insert and especially on the cutting rake surface thereof by the chip which is formed and the greater the width of the chip, the greater will be the exerted forces. With a view to decreasing these vibrations and "chatter", it is known to employ milling cutters having cutting inserts with relatively short cutting edges, the inserts being so orientated with respect to the tool holder and with respect to each other that the cutting paths of the cutting edges of successive cutting inserts overlap. In this way each relatively short cutting edge gives rise to a chip of relatively narrow width, the overlap between the cutting edges of successive cutting inserts ensuring that relatively smooth milling is attained.

In practice, however, this proposal is not found to be effective, requiring as it does the careful preliminary orientation of correctly designed cutting inserts on and with respect to the tool holder.

BRIEF SUMMARY OF THE INVENTION

It is an object of the present invention to provide a rotary milling cutter tool having a new and improved cutting insert, which insert is, by itself, capable of achieving the desired objective of reduced "chatter" in the use of the milling cutter tool.

In US-A-4,588,332 there is disclosed a cutting tool which is arranged to be moved longitudinally and which has a cutting face provided with a plurality of grooves.

According to the present invention however, there is provided a rotary peripheral milling cutter tool having a longitudinal axis of rotation and having a cutting insert provided with a cutting edge defined between a cutting rake surface and a relief

flank and having a base edge defined between said relief flank and a base surface, characterised in that said cutting edge comprises a plurality of successive component cutting edges and intermediate edges respectively located between successive component cutting edges each component cutting edge having respective leading and trailing extremities, the trailing extremity of one component cutting edge merging with the leading extremity of a succeeding component cutting edge via an intermediate edge, said intermediate edges being directed from said trailing extremity of said one component cutting edge towards said base edge and being inclined with reference to a normal to an axis of rotation of said cutter tool, which normal passes through a trailing extremity of a component cutting edge and intersects the successive component cutting edge so that, during a milling operation on a workpiece successive component cutting edges overlap.

With such a cutting insert, and in view of the fact that the component cutting edges are very short, the resultant forces exerted on the cutting insert by the chips formed by these short cutting edges are relatively low and, in consequence, the degree of "chatter" encountered is minimal. Thus, in view of the relative disposition of the component cutting edges with the degree of overlapping of adjacent successive component cutting edges, it is ensured that effectively separate chips are formed of relatively low width.

Preferably, the cutting rake, relief flank and land surfaces associated with the respective component cutting edges are so directed that at corresponding locations along the respective component edges, the insert rake and relief angles, as well as the land surface angles as defined with respect to the cutter tool, are substantially equal.

Preferably, the leading component cutting edge defines a first positive axial rake angle with respect to said axis of rotation, whilst the or each succeeding component cutting edge define axial rake angles which are less positive than said first axial rake angle. With such a cutting insert, the fact that the axial rake angles of a subsequent component cutting edge is less positive than that of a leading component cutting edge carried with it the consequence that the forces exerted on the cutting insert as a result of the milling, and which tend to detach the insert from the tool, are significantly less than those which would be exerted with a unitary cutting edge having a unitary positive axial rake angle, e.g. corresponding to that of the leading component cutting edge.

BRIEF SUMMARY OF THE DRAWINGS

Various embodiments of a hard metal cutting insert employed in a rotary milling cutter according to the present invention will now be described by way of example and with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of one embodiment of a cutting insert employed in the invention;

Figure 2 is a plan view from above of the insert shown in Figure 1;

Figure 3 is a side elevation of the insert shown in Figures 1 and 2;

Figure 4 is a schematic side elevation of the insert shown in Figures 1, 2 and 3 when mounted on a cylindrical milling cutter tool;

Figure 5 is a schematic side elevation on an enlarged scale of the mounted insert shown in Figure 4;

Figure 6 is a view similar to that of Figure 5 diagrammatically illustrating cutting forces exerted on the insert;

Figure 6a illustrates diagrammatically the sum of the cutting forces shown in Figure 6;

Figure 7 is a plan view from above of an alternative embodiment of a cutting insert in accordance with the invention;

Figure 8 is a side elevation of the insert shown in Figure 7;

Figure 9 is a schematic side elevation of the insert shown in Figures 7 and 8 when mounted on a conical milling cutter tool;

Figs. 10a; 11a; and 12a are cross-sectional views taken respectively along the lines X-X; XI-XI; and XIIa-XIIb of the insert as mounted in the view shown in Fig. 4 superimposed on associated circular cutting paths;

Figs. 10b; 11b; and 12b are highly enlarged views of the views shown in Figs. 10a; 11a; and 12a designed to illustrate the K-land of the insert; and

Fig. 13 illustrates the production of a multi-component chip in a milling operation using a cutting insert in accordance with the invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

As seen in Figs. 1, 2 and 3 of the drawings, the cutting insert, which is formed of tungsten carbide, is of generally parallelepipedal shape having a central, upper planar surface 11 surrounded by a peripheral, upper cutting rake surface 12. The insert is formed with a planar base surface (not seen), which is parallel with the central, planar surface 11. The insert is further formed with two pairs of relief flanks 13 and, at the corners, with wipers 14 of

conventional construction. Each relief flank 13 comprises three upper component relief flanks 13a, 13b and 13c, which are angularly directed with respect to each other in a manner to be described below, and a lower, planar relief flank portion 13d.

Each upper cutting rake region 12 comprises a longitudinally extending chip forming groove 15 and three component chip rake surfaces 16a, 16b and 16c.

Component cutting edges 17a, 17b and 17c are defined between the respective component relief flanks and component cutting rake surfaces via respective K-lands 18a, 18b and 18c.

The leading component cutting edge 17a merges at its terminal extremity with the succeeding component cutting edge 17b via an intermediate edge 19 which slopes downwardly towards a base edge 20 of the insert. Similarly, the component cutting edge 17b merges with the succeeding cutting edge 17c via an intermediate edge 21, which also slopes downwardly towards the base edge 20 of the insert.

As seen in Fig. 4 of the drawings, the insert just described with reference to Figs. 1, 2 and 3, is mounted in a rotary milling cutter 25 having a cylindrical holder 26, the insert being mounted so as to present a positive axial rake angle α with respect to an axis of rotation 27 of the cutter tool 25.

Reference will now be made to Fig. 5 of the drawings, which shows schematically the location of the cutting insert within the cutter tool during a milling operation. From this drawing, it can be seen that the component cutting edges 17a and 17b effectively overlap during a milling operation by virtue of the fact that a normal 27a with respect to the rotational axis 27, when passing through a trailing extremity of the component cutting edge 17a, intersects the succeeding component cutting edge 17b. Similarly, a normal 27b to the rotational axis 27, when passing through a trailing extremity of the component cutting edge 17b, intersects the succeeding component cutting edge 17c.

It will be readily seen from Fig. 5 of the drawings that, whereas the component cutting edge 17a has a positive axial rake angle equal to α (i.e., the positive rake angle of the insert of a whole as seen in Fig. 4 of the drawings), the component cutting edges 17b and 17c have substantially smaller axial rake angles α_1 and α_2 (in the example now being considered, these angles are not equal but they can also be equal). Now it is known with milling cutting tools of this kind that the cutting forces acting on the insert and tending to detach the insert from the holder, tend to increase with increasing positive axial rake angles. It therefore follows that any reduction in the magnitude of the positive axial rake angle will be accompanied by a

consequent reduction in these forces.

Referring now to Fig. 6 of the drawings, the component forces F_a , F_b and F_c , acting respectively on the component cutting edges 17a, 17b and 17c in a direction tending to detach the insert from the holder, clearly tend to decrease with decreasing positive axial rake angle of the component cutting edges. Fig. 6a shows schematically the sum total F of the individual forces F_a , F_b and F_c , and this sum total F is significantly less than would be the case if a unitary cutting edge was employed with a unitary axial rake angle equal to α .

Thus, in addition to the main purpose and advantage of the cutting insert just described in accordance with the invention, namely, effecting milling operations with component cutting edges of reduced length, thereby giving rise to significantly reduced "chatter", the provision of the cutting insert with component cutting edges of differing axial rake angles, gives rise to a reduction in the forces exerted on the insert and which tend to detach the insert from the holder.

It will be realised that, with an insert in accordance with the present invention, in order to ensure this reduction in the overall forces acting on the insert tending to detach the insert from the holder, it is necessary to provide the insert with component cutting edges which are angularly directed with respect to each other. Where, however, milling considerations are such that this requirement for reduction in the overall so-called detaching forces becomes secondary and it is, on the other hand, desirable to ensure that all the component cutting edges present the same or similar positive axial rake angle, an arrangement such as shown in Figs. 7, 8 and 9 of the drawings can be adopted. As seen in these figures, a modified insert 31 is formed with sets of component cutting edges 32a, 32b and 32c which, whilst being overlapping in the sense that the cutting edges 17a, 17b and 17c of the cutting insert described with reference to the preceding drawings are overlapping, are nevertheless all parallel to each other and define a single axial rake angle which is highly positive.

As seen in Fig. 9 of the drawings, the component cutting forces F_a , F_b and F_c acting respectively on the component cutting edges 32a, 32b and 32c are all equal and, when summed, are substantially greater than the component cutting force F shown in Fig. 6a of the drawings with reference to the insert having component cutting edges as shown in the preceding drawings. Thus, in this case the force tending to detach the insert from the tool holder is significantly greater than the corresponding force acting on the insert in accordance with the preceding drawings. On the other hand, the fact that all constituent component cutting edges present the same significant positive

axial rake angle carries with it its own advantages, which may be preferred under certain circumstances.

Reference will now be made to Figs. 10a, 11a, 12a, 10b, 11b and 12b for a description of the construction of the relief flanks, cutting rake surfaces and K-lands in accordance with a preferred embodiment of the invention.

In order to achieve optimal milling conditions, the component relief flank, cutting rake and K-land surfaces are so disposed with respect to each other so that, at corresponding locations along the component cutting edges, the relief flank, cutting rake and K-land angles are equal. Thus, for example, at the mid points of each component cutting edge, these angular conditions are fulfilled. Figs. 10a, 11a, 12a, 10b, 11b and 12b show sections through the cutting insert along section lines which pass through the respective mid positions of the component cutting edges. In all cases, the component relief flank angles γ_a , γ_b and γ_c are measured between the respective component relief flank surface 13a, 13b and 13c and the respective tangents 41a, 41b and 41c to the circular paths 40a, 40b and 40c at the positions where the mid points of the component cutting edges lie on these circular paths. As can be seen, the component relief flank surfaces 13a, 13b and 13c are angularly disposed with respect to each other so that at these respective mid points the component relief flank angles γ_a , γ_b and γ_c are all equal.

Similarly, the component cutting rake angles β_a , β_b and β_c are measured between the component cutting rake surfaces 16a, 16b and 16c and respective radii 42a, 42b and 42c extending from the centres of the circular paths 40a, 40b and 40c to the positions where the mid points of the component cutting edges lie on these circular paths. Here again, the component cutting surfaces 16a, 16b and 16c are so disposed angularly with respect to each other that the cutting rake angles at the mid points of the component cutting edges β_a , β_b and β_c are all substantially equal.

Finally, the K-land angles θ_a , θ_b and θ_c of the component K-lands 18a, 18b and 18c as measured at the respective mid points of the component cutting edges, and as defined between the K-land surfaces 18a, 18b and 18c and the radii 42a, 42b and 42c, are all substantially equal.

Whilst in the embodiment specifically described above the relief flank cutting rake and K-land angles associated with the component cutting edges are equal when measured with respect to corresponding points on the respective cutting edges (for example, as described above with respect to the mid points of the cutting edges), in accordance with a further refinement, each component cutting edge, relief flank surface and K-land

can be so curved as to ensure that along the entire length of a particular component cutting edge the relief flank, cutting rake and K-land angles remain substantially invariant. The particular modes by which these curvatures are ensured are described in our co-pending British patent applications 90/10769.9; 89/20227.9; and 89/08195.4.

With milling cutting tools employing inserts in accordance with the invention, i.e. with component cutting edges of limited extent and which effectively overlap $v/s-a-v/s$ the milling operation, the forces acting on the cutting insert and which tend to induce vibration ("chatter") are considerably reduced and this by virtue of the fact that the chips created during the milling operation are of relatively restricted width and do not combine so as to create the vibration-generating forces on the insert. The milling operation resulting in the generation of such relatively narrow chips is illustrated schematically in Fig. 13 of the drawings. Here an insert 51 is mounted on a conical holder 52 so as to perform a milling operation. As can be seen, the component cutting edges give rise to the production of a chip 53 which effectively consists of three relatively narrow chips 53a, 53b, 53c which spread apart at their free ends, and are only coupled together by very weak, perforated bridges 54 which are completely ineffective in the transference of forces between the component chips 53a, 53b, 53c and the insert 51.

It will be understood that, in order to ensure that the chips generated during the milling operation are either completely separated into component chips or are generated in the form shown in Fig. 13 of the drawings, where they are held together by very weak bridges, it is necessary to ensure that not only the component cutting edges overlap as described and defined above, but also that the leading end of one cutting edge is spaced from the trailing end of the preceding component cutting edge by a distance which is not less than the thickness of the chip which is to be cut. In other words, that the intermediate edges 19 and 21 between successive component cutting edges slopes towards the base edge 20 of the insert by an amount not less than the maximum thickness of the chip.

Whilst the invention has been specifically described with reference to the milling cutting inserts of parallelepipedal shape, i.e. having four sides and associated cutting edges, it will be readily appreciated that the invention is equally applicable to cutting inserts of other shapes such as, for example, triangular shapes. Similarly, inserts can be employed such as, for example, inserts of oblong rectangular shape wherein the component cutting edges are formed on one pair of opposite sides of the insert. Furthermore, whilst the invention has

been specifically described with reference to inserts having at each side three component cutting edges, it will be appreciated that the invention is equally applicable to inserts wherein two or more component cutting edges are provided.

It will furthermore be noted from Figs. 9 and 13 of the drawings that the inserts are mounted in a conical tool holder as compared with the cylindrical holder shown in Fig. 4 of the drawings. It will be appreciated, however, that the use of inserts in accordance with the invention is not restricted to any particular form of tool holder.

Claims

1. A rotary peripheral milling cutter tool having a longitudinal axis of rotation (27) and having a cutting insert provided with a cutting edge (17) defined between a cutting rake surface (12) and a relief flank (13) and having a base edge (20) defined between said relief flank and a base surface;

characterised in that

said cutting edge (17) comprises a plurality of successive component cutting edges (17a, 17b, 17c) and intermediate edges (19, 21) respectively located between successive component cutting edges (17a, 17b; 17c); each component cutting edge having respective leading and trailing extremities, the trailing extremity of one component cutting edge (17a, 17b, 17c) merging with the leading extremity of a succeeding component cutting edge via an intermediate edge (19, 21), said intermediate edges (19, 21) being directed from said trailing extremity of said one component cutting edge (17a, 17b, 17c) towards said base edge (20); and being inclined with reference to a normal (27a, 27b) to an axis of rotation of said cutter tool, which normal passes through a trailing extremity of a component cutting edge (17a, 17b) and intersects the successive component cutting edge (17b, 17c) so that, during a milling operation on a workpiece, successive component cutting edges overlap.

2. A cutter tool according to Claim 1, characterised in that a leading component cutting edge (17a) defines a first positive axial rake angle (α) with respect to said axis of rotation, whilst the or each succeeding component cutting edge (17b, 17c) define axial rake angles (α) which are less positive than said first axial rake angle (α).
3. A cutter tool according to Claim 1, characterised in that said component cutting edges (17a, 17b, 17c) define substantially equal axial



can be so curved as to ensure that along the entire length of a particular component cutting edge the relief flank, cutting rake and K-land angles remain substantially invariant. The particular modes by which these curvatures are ensured are described in our co-pending British patent applications 90/10769.9; 89/20227.9; and 89/08195.4.

With milling cutting tools employing inserts in accordance with the invention, i.e. with component cutting edges of limited extent and which effectively overlap *v/s*—*a*—*v/s* the milling operation, the forces acting on the cutting insert and which tend to induce vibration ("chatter") are considerably reduced and this by virtue of the fact that the chips created during the milling operation are of relatively restricted width and do not combine so as to create the vibration-generating forces on the insert. The milling operation resulting in the generation of such relatively narrow chips is illustrated schematically in Fig. 13 of the drawings. Here an insert 51 is mounted on a conical holder 52 so as to perform a milling operation. As can be seen, the component cutting edges give rise to the production of a chip 53 which effectively consists of three relatively narrow chips 53a, 53b, 53c which spread apart at their free ends, and are only coupled together by very weak, perforated bridges 54 which are completely ineffective in the transference of forces between the component chips 53a, 53b, 53c and the insert 51.

It will be understood that, in order to ensure that the chips generated during the milling operation are either completely separated into component chips or are generated in the form shown in Fig. 13 of the drawings, where they are held together by very weak bridges, it is necessary to ensure that not only the component cutting edges overlap as described and defined above, but also that the leading end of one cutting edge is spaced from the trailing end of the preceding component cutting edge by a distance which is not less than the thickness of the chip which is to be cut. In other words, that the intermediate edges 19 and 21 between successive component cutting edges slopes towards the base edge 20 of the insert by an amount not less than the maximum thickness of the chip.

Whilst the invention has been specifically described with reference to the milling cutting inserts of parallelepipedal shape, i.e. having four sides and associated cutting edges, it will be readily appreciated that the invention is equally applicable to cutting inserts of other shapes such as, for example, triangular shapes. Similarly, inserts can be employed such as, for example, inserts of oblong rectangular shape wherein the component cutting edges are formed on one pair of opposite sides of the insert. Furthermore, whilst the invention has

been specifically described with reference to inserts having at each side three component cutting edges, it will be appreciated that the invention is equally applicable to inserts wherein two or more component cutting edges are provided.

It will furthermore be noted from Figs. 9 and 13 of the drawings that the inserts are mounted in a conical tool holder as compared with the cylindrical holder shown in Fig. 4 of the drawings. It will be appreciated, however, that the use of inserts in accordance with the invention is not restricted to any particular form of tool holder.

Claims

1. A rotary peripheral milling cutter tool having a longitudinal axis of rotation (27) and having a cutting insert provided with a cutting edge (17) defined between a cutting rake surface (12) and a relief flank (13) and having a base edge (20) defined between said relief flank and a base surface;

characterised in that

said cutting edge (17) comprises a plurality of successive component cutting edges (17a, 17b, 17c) and intermediate edges (19, 21) respectively located between successive component cutting edges (17a, 17b; 17c); each component cutting edge having respective leading and trailing extremities, the trailing extremity of one component cutting edge (17a, 17b, 17c) merging with the leading extremity of a succeeding component cutting edge via an intermediate edge (19, 21), said intermediate edges (19, 21) being directed from said trailing extremity of said one component cutting edge (17a, 17b, 17c) towards said base edge (20); and being inclined with reference to a normal (27a, 27b) to an axis of rotation of said cutter tool, which normal passes through a trailing extremity of a component cutting edge (17a, 17b) and intersects the successive component cutting edge (17b, 17c) so that, during a milling operation on a workpiece, successive component cutting edges overlap.

2. A cutter tool according to Claim 1, characterised in that a leading component cutting edge (17a) defines a first positive axial rake angle (α) with respect to said axis of rotation, whilst the or each succeeding component cutting edge (17b, 17c) define axial rake angles (α) which are less positive than said first axial rake angle (α).

3. A cutter tool according to Claim 1, characterised in that said component cutting edges (17a, 17b, 17c) define substantially equal axial



rake angles (α) with respect to said axis of rotation.

4. A cutter tool according to any one of the preceding claims, characterised in that the component cutting edges (17a, 17b, 17c) are respectively associated with component relief flanks (13a, 13b, 13c), which are so directed towards each other that the insert side relief angles (γ) at corresponding locations on successive component relief flanks (13a, 13b, 13c) and as defined with respect to the milling cutter tool, are substantially equal.
5. A cutter tool according to Claim 4, characterised in that said relief flank surface comprises an upper portion which comprises said component relief flank surfaces (13a, 13b, 13c) and a substantially planar lower portion (13d).
6. A cutter tool according to any one of the preceding claims, characterised in that the component cutting edges (17a, 17b, 17c) are respectively associated with component cutting rake surfaces (16a, 16b, 16c) which are so directed towards each other that insert cutting rake angles (β) at corresponding locations on successive component cutting rake surfaces (16), and as defined with respect to the milling cutter tool, are substantially equal.
7. A cutter tool according to Claim 4, 5 or 6, characterized in that each component relief flank (13) and cutting rake surface (16) are continuously curved so that the insert rake (β) and relief (γ) angles as defined with respect to the cutter tool remain substantially invariant along the length of the component cutting edge (17).
8. A cutter tool according to any one of the preceding claims, characterized in that the component cutting edges (17) are respectively associated with component K-land surfaces (18) which are so directed with respect to each other that insert K-land angles (θ) at corresponding locations on successive component K-land surfaces (18), and as defined with respect to the milling cutter tool, are substantially equal.
9. A cutter tool according to Claim 8, characterized in that each component K-land surface (18) is continuously curved so that the K-land angle (θ) as defined with respect to the cutter tool remains substantially invariant along the length of the component cutting edge (17).

10. A cutter tool according to any one of the preceding claims, characterised in that it is of substantially parallelepipedal shape and is provided with an upper cutting rake surface (12) and a lower base surface and two pairs of sets of component cutting edges (17).

Patentansprüche

1. Rotationsumfangsfräser-Schneidwerkzeug mit einer Längs-Drehachse (27) und einem Schneideinsatz mit einer zwischen einer Spanfläche (12) und einer Freifläche (13) definierten Schneidkante (17) und einer zwischen der Freifläche und der Basisfläche definierten Basis-kante (20),
dadurch gekennzeichnet, daß
die Schneidkante (17) mehrere aufeinanderfolgende Komponentenschneidkanten (17a, 17b, 17c) und Zwischenkanten (19, 21) aufweist, die jeweils zwischen aufeinanderfolgenden Komponentenschneidkanten (17a, 17b, 17c) angeordnet sind, wobei jede Komponentenschneidkante ein vorderes und ein hinteres Ende aufweist, wobei das hintere Ende einer Komponentenschneidkante (17a, 17b, 17c) über eine Zwischenkante (19, 21) in das vordere Ende einer nachfolgenden Komponentenschneidkante übergeht, wobei die Zwischenkanten (19, 21) vom hinteren Ende der einen Komponentenschneidkante (17a, 17b, 17c) zur Basis-kante (20) gerichtet und bezüglich einer Normalen (27a, 27b) zur Drehachse des Schneidwerkzeugs geneigt ist, wobei die Normale durch das hintere Ende einer Komponentenschneidkante (17a, 17b) verläuft und die nachfolgende Komponentenschneidkante (17b, 17c) schneidet, so daß, während ein Werkstück durch einen Fräsvorgang bearbeitet wird, aufeinanderfolgende Komponentenschneidkanten überlappen.
2. Schneidwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß eine vordere Komponentenschneidkante (17a) einen ersten positiven Axial-Spanwinkel (α) bezüglich der Drehachse definiert, während die oder jede folgende Komponentenschneidkante (17b, 17c) einen Axial-Spanwinkel (α) definiert, der weniger positiv ist als der erste Axial-Spanwinkel (α).
3. Schneidwerkzeug nach Anspruch 1, dadurch gekennzeichnet, daß die Komponentenschneidkanten (17a, 17b, 17c) im wesentlichen gleiche Axial-Spanwinkel (α) bezüglich der Drehachse definieren.



4. Schneidwerkzeug nach einem der vorangehenden Ansprüche, **dadurch gekennzeichnet**, daß die Komponentenschneidkanten (17a, 17b, 17c) jeweils Komponentenfreiflächen (13a, 13b, 13c) zugeordnet sind, die derart zueinander ausgerichtet sind, daß die bezüglich dem Fräswerkzeug definierten Einsatz-Seitenfreiwinkel (γ) an entsprechenden Positionen auf aufeinanderfolgenden Komponentenfreiflächen (13a, 13b, 13c) im wesentlichen gleich sind. 10
5. Schneidwerkzeug nach Anspruch 4, **dadurch gekennzeichnet**, daß die Freifläche einen oberen Abschnitt mit den Komponentenfreiflächen (13a, 13b, 13c) und einen im wesentlichen ebenen unteren Abschnitt (13d) aufweist. 15
6. Schneidwerkzeug nach einem der vorangehenden Ansprüche, **dadurch gekennzeichnet**, daß die Komponentenschneidkanten (17a, 17b, 17c) jeweils Spanflächen (16a, 16b, 16c) zugeordnet sind, die derart zueinander ausgerichtet sind, daß die bezüglich dem Fräswerkzeug definierten Einsatzspanwinkel (β) an entsprechenden Positionen auf aufeinanderfolgenden Komponentenspanflächen (16) im wesentlichen gleich sind. 20
7. Schneidwerkzeug nach Anspruch 4, 5 oder 6, **dadurch gekennzeichnet**, daß jede Komponentenfreifläche (13) und jede Komponentenspanfläche (16) fortlaufend gekrümmt ist, so daß der Einsatzspanwinkel (β) und der Einsatzfreiwinkel (γ), die bezüglich dem Fräswerkzeug definiert sind, entlang der Länge der Komponentenschneidkante (17) im wesentlichen gleich bleiben. 25
8. Schneidwerkzeug nach einem der vorangehenden Ansprüche, **dadurch gekennzeichnet**, daß die Komponentenschneidkanten (17) jeweils Komponenten-Fasenflächen (18) zugeordnet sind, die zueinander derart ausgerichtet sind, daß die bezüglich dem Fräswerkzeug definierten Einsatz-Fasenwinkel (θ) an entsprechenden Positionen auf aufeinanderfolgenden Komponenten-Fasenflächen (18) im wesentlichen gleich sind. 30
9. Schneidwerkzeug nach Anspruch 8, **dadurch gekennzeichnet**, daß jede Komponenten-Fasenfläche (18) fortlaufend gekrümmt ist, so daß der bezüglich dem Schneidwerkzeug definierte Fasenwinkel (θ) entlang der Länge der Komponentenschneidkante (17) im wesentlichen gleich bleibt. 35

10. Schneidwerkzeug nach einem der vorangehenden Ansprüche, **dadurch gekennzeichnet**, daß das Werkzeug im wesentlichen quaderförmig ist und eine obere Spanfläche (12) und eine untere Basisfläche sowie zwei Paare von Sätzen von Komponentenschneidkanten (17) aufweist. 40

Revendications

1. Outil rotatif de coupe périphérique par fraisage, ayant un axe longitudinal de rotation (27) et un élément rapporté de coupe muni d'un bord de coupe (17) délimité entre une surface de tranchant de coupe (12) et un flanc en dépouille (13) et ayant un bord de base (20) délimité entre le flanc en dépouille et la surface de base, caractérisé en ce que le bord de coupe (17) comporte plusieurs bords de coupe élémentaires successifs (17a, 17b, 17c) et des bords intermédiaires (19, 21) placés respectivement entre les bords de coupe élémentaires successifs (17a, 17b, 17c), chaque bord de coupe élémentaire ayant des extrémités avant et arrière respectives, l'extrémité arrière d'un premier bord de coupe élémentaire (17a, 17b, 17c) se raccordant avec l'extrémité avant d'un bord de coupe élémentaire suivant avec un bord intermédiaire (19, 21), les bords intermédiaires (19, 21) étant dirigés de l'extrémité arrière d'un premier bord de coupe élémentaire (17a, 17b, 17c) vers le bord de base (20) et étant inclinés par rapport à une perpendiculaire (27a, 27b) à un axe de rotation de l'outil de coupe, cette perpendiculaire passant par l'extrémité arrière d'un bord de coupe élémentaire (17a, 17b) et recoupant le bord de coupe élémentaire suivant (17b, 17c) de manière que, au cours d'une opération de fraisage d'une pièce, les bords de coupe élémentaires successifs se recoupent. 45
2. Outil de coupe selon la revendication 1, caractérisé en ce qu'un bord de coupe élémentaire avant (17a) délimite un premier angle positif de tranchant axial (α) par rapport à l'axe de rotation, alors que le bord de coupe élémentaire suivant ou chaque bord suivant (17b, 17c) délimite un angle de tranchant axial (α) qui est moins positif que le premier angle de tranchant axial (α). 50
3. Outil de coupe selon la revendication 1, caractérisé en ce que les bords de coupe élémentaires (17a, 17b, 17c) délimitent des angles de tranchant axial (α) qui sont sensiblement égaux par rapport à l'axe de rotation. 55



4. Outil de coupe selon l'une quelconque des revendications précédentes, caractérisé en ce que les bords de coupe élémentaires (17a, 17b, 17c) sont associés respectivement à des flancs en dépouille élémentaires (13a, 13b, 13c) qui sont dirigés les uns vers les autres afin que les angles (γ) de dépouille latérale de l'élément rapporté, à des emplacements correspondants sur les flancs de dépouille élémentaires successifs (13a, 13b, 13c) et délimités par rapport à l'outil de coupe par fraisage, soient pratiquement égaux.

5. Outil de coupe selon la revendication 4, caractérisé en ce que la surface de flanc en dépouille comporte une partie supérieure qui comprend les surfaces de flancs en dépouille élémentaires (13a, 13b, 13c) et une partie inférieure sensiblement plane (13d).

6. Outil de coupe selon l'une quelconque des revendications précédentes, caractérisé en ce que les bords de coupe élémentaires (17a, 17b, 17c) sont associés respectivement aux surfaces de tranchant de coupe élémentaires (16a, 16b, 16c) qui sont dirigées les unes vers les autres de manière que les angles de tranchant de coupe élémentaires (β) d'emplacements correspondants sur les surfaces successives de tranchant de coupe élémentaires (16) et délimités par rapport à l'outil de coupe par fraisage soient pratiquement égaux.

7. Outil de coupe selon la revendication 4, 5 ou 6, caractérisé en ce que chaque flanc en dépouille élémentaire (13) et la surface de tranchant de coupe (16) ont une courbure continue afin que les angles de tranchant (β) et de dépouille (γ) de l'élément rapporté, définis par rapport à l'outil de coupe, restent pratiquement constants sur toute la longueur du bord de coupe élémentaire (17).

8. Outil de coupe selon l'une quelconque des revendications précédentes, caractérisé en ce que les bords de coupe élémentaires (17) sont associés respectivement à des surfaces de portée K élémentaires (18) qui sont dirigées les unes par rapport aux autres de manière que les angles des portées K (θ) de l'élément rapporté à des emplacements correspondants sur des surfaces de portée K élémentaires successives (18) et délimitées par rapport à l'outil de coupe par fraisage soient pratiquement égaux.

9. Outil de coupe selon la revendication 8, caractérisé en ce que chaque surface de portée K

élémentaire (18) a une courbure continue afin que l'angle de portée K (θ) défini par rapport à l'outil de coupe reste pratiquement constant sur toute la longueur du bord de coupe élémentaire (17).

10. Outil de coupe selon l'une quelconque des revendications précédentes, caractérisé en ce qu'il a une forme pratiquement parallépipédique et comporte une surface supérieure de tranchant de coupe (12) et une surface inférieure de base et deux paires d'ensembles de bords de coupe élémentaires (17).

5

10

15

20

25

30

35

40

45

50

55