SINGLE DISC CLAMP NUT FOR DISC CLAMPING IN A DISC DRIVE

Field of the Invention

This application relates to magnetic disc drives and more particularly to an improved disc drive spindle motor apparatus for mounting information storage disc within the disc drive.

Background of the Invention

Disc drives are data storage devices that store digital data in magnetic form on a storage medium on a rotating information storage disc. Modern disc drives include one or more rigid discs that are coated with a magnetizable medium and mounted on the hub of a spindle motor for rotation at a constant high speed. Information is stored on the discs in a plurality of concentric circular tracks typically by an array of transducers ("heads") mounted to a radial actuator for movement of the heads relative to the discs. Each of the concentric tracks is generally divided into a plurality of separately addressable data sectors. The read/write transducer, *e.g.*, a magnetoresistive read/write head, is used to transfer data between a desired track and an external environment. During a write operation, data is written onto the disc track and during a read operation the head senses the data previously written on the disc track and transfers the information to the external environment. Critical to both of these operations is the accurate locating of the head over the center of the desired track.

The heads are mounted via flexures at the ends of a plurality of actuator arms that project radially outward from the actuator body. The actuator body pivots about a shaft mounted to the disc drive housing at a position closely adjacent the outer extreme of the discs. The pivot shaft is parallel with the axis of rotation of the spindle motor and the discs, so that the heads move in a plane parallel with the surfaces of the discs.

Spindle motor assemblies often utilize a rotating spindle hub journaled to a non-rotatable spindle shaft. A disc clamp is typically secured to the rotating spindle hub to exert a downward axial force on the mounted information storage

discs and disc spacers. Typically, the disc clamp exerts the downward force through a series of radially positioned screws torqued into the spindle hub. The radial positioning of the screws is beneficial for exerting clamping force on the spindle assembly because the force is exerted at the periphery of the clamp in closer proximity to the mounted information storage discs and disc spacers. However, the peripheral positioning of the series of screws in the disc clamp causes the downward force to be exerted in a non-uniform manner. Non-uniform clamping force can generally cause variations in the load force and, as a result, cause the top mounted information storage disc to be physically distorted. Distortion of the top disc, even by as little as 100 micro inches, can lead to operational errors during recording and reproduction of data on the information storage disc.

In a second type of spindle motor assembly the spindle shaft and spindle hub portion both rotate about a bearing sleeve. Here, a single screw can be used to secure the disc clamp to the rotating spindle shaft because the shaft rotates with the screw (as opposed to the non-rotatable shaft where a plurality of screws must be positioned about the shaft). However, in order to develop a clamping force with a single screw similar to the force developed by the plurality of screws surrounding the non-rotatable shaft, it is necessary to apply a much higher torque to the single screw. This relative high torque can lead to a number of problems including over-stressing the spindle shaft bearing and the generation of particles during the torquing process. These high-torque related problems can damage the bearing and lead to failure of the spindle motor. Currently, there is a need in the relevant art to overcome the shortcomings of the traditional single screw disc drive spindle motor assembly as well as the non-rotatable multiple screw spindle shaft spindle motor.

Summary of the Invention

Against this backdrop the present invention has been developed. The present invention is an apparatus and method for uniformly loading information storage discs onto a spindle motor.

In accordance with a preferred method of the present invention, an information storage disc is assembled on a hub of a disc drive spindle motor and a disc clamp is positioned on the hub so that an outer periphery of the disc clamp engages a top surface of the assembled information storage disc. A predetermined pre-load force is applied to the disc clamp. A disc clamp nut is positioned on the pre-loaded disc clamp to secure the disc clamp to the hub and, once secured, the pre-load force is released from the disc clamp.

The present invention can further be implemented as a disc drive spindle motor assembly including a spindle having a shaft and a cylindrical hub extending radially outward from the shaft, the shaft including a threaded stud extending above a top surface of the cylindrical hub. One or more information storage discs are mounted on the cylindrical hub. A disc clamp having a central aperture, an inner annular contact portion, a middle annular raised portion and a peripheral edge is fitted over the threaded stud to allow the inner annular contact portion to engage the top surface of the hub while the peripheral edge engages the top surface of the information storage disc. The middle annular raised portion extends above the top surface of the hub and is adapted to receive a pre-load force. A disc clamp nut having a contact surface for engaging the inner annular contact portion of the disc clamp is fastened to the threaded stud and secures the pre-loaded disc clamp to the hub.

These and various other features as well as advantages which characterize the present invention will be apparent from a reading of the following detailed description and a review of the associated drawings.

Brief Description of the Drawings

FIG. 1 is a top plan view of a disc drive with a top cover removed to illustrate a single nut disc clamping assembly in accordance with a preferred embodiment of the invention.

FIG. 2 is a representative sectional view of a disc clamping assembly of the present invention showing a disc clamp nut and disc clamp exploded above a threaded stud of a spindle hub.

FIG. 3 is a representative sectional view similar to FIG. 2 illustrating the disc clamp positioned on the disc drive spindle hub and a force applied to a top surface of the disc clamp.

FIG. 4 is a representative sectional view of the disc clamping assembly similar to FIG. 3 showing the disc clamp and disc clamp nut positioned on the disc drive spindle hub.

FIG. 5 is a flow chart showing the steps for assembling the single nut disc clamping assembly in accordance with a preferred embodiment of the present invention.

Detailed Description

A disc drive **100** constructed in accordance with a preferred embodiment of the present invention is shown in FIG. **1**. The disc drive **100** includes a base plate **102** to which various components of the disc drive **100** are mounted. A top cover (not shown) cooperates with the base **102** to form an internal, sealed environment for the disc drive in a conventional manner. The components include a disc drive motor spindle assembly **104** (FIG. **2**) which includes a spindle motor **106** (FIG. **2**) that rotates one or more information storage discs **108** at a constant high speed. Information is written to and read from tracks **109** on the discs **108** through the use of an actuator assembly **110** which rotates about a bearing shaft assembly **112** positioned adjacent the discs **108**. The actuator assembly **110** includes a plurality of actuator arms **114** which extend towards the discs **108**, with one or more flexures **116** extending from each of the actuator arms **114**. Mounted at the distal end of each of the flexures **116** is a head **118** that includes an air bearing slider (not shown) enabling the head **118** to fly in close proximity above the corresponding surface of the associated information storage disc **108**.

The radial position of the heads **118** is controlled through the use of a voice coil motor (VCM) **124**, which typically includes a coil **126** attached to the actuator assembly **110**, as well as one or more permanent magnets **128** that establish a magnetic field in which the coil **126** is immersed. The controlled application of current to the coil **126** causes magnetic interaction between the permanent magnets **128** and the coil **126** so that the coil **126** moves in accordance with the well known

Lorentz relationship. As the coil **126** moves, the actuator assembly **110** pivots about the bearing shaft assembly **112** and the heads **118** are caused to move across the surfaces of the discs **108**.

A representative sectional view of the disc drive spindle motor assembly **104** of the present invention is shown in FIG. **2**. The disc drive spindle motor assembly **104** generally includes a spindle motor **106**, a rotatable spindle **130**, a bearing sleeve **132**, one or more information storage discs **108**, a disc clamp **134** and a disc clamp nut **136**.

In more detail, the generally rectangular shaped base plate **102** acts as a platform for the disc drive spindle motor assembly **104** by defining an indentation **138** that provides a cylindrical wall **140** extending vertically upward from the base plate **102**.

The bearing sleeve **132** defines an exterior sleeve wall **144** and an interior central cavity wall **146**. The bearing sleeve **132** is positioned within the confines of the cylindrical wall **140** and is of a diameter such that the exterior sleeve wall **144** is secured to an interior engagement surface **142** of the cylindrical wall **140**. The bearing sleeve's central cavity wall **146** is also cylindrical in shape and defines a central cavity receiving a rotating shaft **156** of the spindle **130** within the central cavity of the bearing sleeve **132**. The bottom portion **148** of the bearing sleeve **132** defines a downwardly extending peripheral ring **150** that forms part of the bottom surface of the base plate **102**. Interior and adjacent to the peripheral ring **150** is an annular notch **152** for receiving a thrust plate **154** for supporting the rotating shaft **156** of the spindle **130**.

The spindle **130** includes a threaded stud **158** at a top end of the shaft **156**. A hub **160** extends radially from the spindle shaft **156**. The shaft **156** is cylindrical and preferably includes a series of helical oil lubricating grooves **162** coined thereon where the grooves are for lubricating the shaft **156** while the shaft is being rotated within the bearing sleeve **132**. The shaft **156** is journaled to the central cavity wall **144** of the bearing sleeve **132** so that the shaft **156** of the spindle **130** is anchored to the base plate **102** but remains freely rotatable within the bearing sleeve **132**. A lower end **164** of the shaft **156** is secured to the thrust plate **154** where the thrust plate **154** provides the spindle **130** with surfaces for

absorbing the thrust loads generated by the rotating of the disc drive spindle motor assembly **104**.

The hub **160** of the spindle **130** has a top surface **165** which further defines a top interior annular shoulder **166** and a downwardly projecting peripheral ring **168**. The end of the peripheral ring defines an annular flange **170** having a loading surface **172** for receiving a bottom information storage disc **174**. An annular disc spacer **176** is stacked on the bottom information storage disc **174**. A top information storage disc **177** is stacked on the disc spacer **176**. While two discs **174** and **177** are shown in FIGS. **2-4**, it is envisioned that more than two discs and one corresponding spacer **176** may be used with the current invention. Furthermore, the present invention encompasses the use of a single information storage disc secured between the bottom annular flange **170** and the disc clamp **134**.

The top interior annular shoulder **166** defines a flat engagement surface **178** (FIG. **2**) adjacent to the threaded stud **158** of the spindle shaft **156**. Preferably, the flat engagement surface **178** of the top interior annular shoulder **166** is formed substantially parallel to the loading surface **172** of the annular flange **170**. An indentation **182** is formed adjacent to the top interior annular shoulder **166**, surrounding the vertically extending threaded stud **158**, for receiving the disc clamp nut **136** as described below.

The threaded stud **158** defines external threads that are both perpendicular to a spindle assembly axis of rotation **183** and concentric with the peripheral ring **168** of the hub **160**. The threaded stud **158** need only be of such length and size to effectively mate with the disc clamp nut **136** as is described in greater detail below.

The spindle **130** is rotated about the spindle axis of rotation **183** by a spindle motor **106** having a stator core **184** around which a coil **186** is wound. Cooperating with the stator core **184** to rotate the spindle **130** is a cylindrical magnet **188** mounted to an interior surface **190** of the downwardly projecting peripheral ring **168** of the spindle hub **160**. When current is supplied to the coil **186**, a magnetic field is established around the relevant pole of the stator core **184**

causing torque, and thus rotation, between the stationary cylindrical wall **140** of the base plate **102** and the spindle **130** of the present invention.

The disc clamp **134**, best shown in FIG. 2, includes a centrally located aperture **192**, an inner annular spindle contact portion **194**, a middle annular raised portion **196** and an outer periphery **197** that further defines a downward projecting peripheral edge **198**. FIG. 3 illustrates that the aperture **192** of the disc clamp **134** is mounted over the threaded stud **158** of the spindle **130**. The inner annular spindle contact portion **194** defines a bottom surface **200** that is flat and preferably positioned in a plane substantially parallel to the loading surface **172** of the annular flange **170** and the hub flat engagement surface **178**.

The disc clamp nut **136**, having a central threaded aperture **204**, defines a shoulder **206** having a flat engagement surface **208** for interacting with a flat top surface **210** of the inner annular spindle contact portion **194** of the disc clamp **134**. The flat engagement surface **208** is generally parallel to the loading surface **172** of the annular flange **170** and the hub flat engagement surface **178**. The disc clamp nut shoulder **206** preferably includes an inside and outside diameter **207** and **209** that are equal to the respective inner and outer diameter **211** and **213** (FIG. 2) of the annular flat engagement surface **178** of the spindle hub **160**.

As has been noted above, it is important that the flat engagement surface **208** of the disc clamp nut **136**, the inner annular spindle contact portion **194** of the disc clamp **134** and the flat engagement surface **178** of the top interior annular shoulder **166** all be substantially parallel to the loading surface **172** of the annular flange **170**, and hence be parallel to each other. The "parallelism" between these surfaces is important for uniformly pre-loading the disc clamp **134** to clamp the information storage discs as discussed in greater detail below.

In use, the disc clamp **134** is positioned over the threaded stud **158** of the spindle **130** as shown in FIG. 3. The disc clamp's inner annular spindle contact portion **194** engages the flat engagement surface **178** on the inner annular shoulder **166** of the hub **160** while the middle annular raised portion **196** of the disc clamp **134** projects radially across the spindle hub **160** without contact and the downwardly projecting peripheral edge **198** contacts the top surface **180** of the information storage disc **177** at a position adjacent the spindle hub **160** and

directly above and in line with the spacer **176** and radial flange **170** of the hub. Once the disc clamp **134** is in position over the threaded stud **158**, a predetermined downward pre-load force, shown in FIG. **3** as arrow **202**, is applied to the middle annular raised portion **196** of the disc clamp. The pre-load force axially compresses the disc clamp **134** down on the spindle mounted information storage disc **177**. The pre-load force **202** is preferably supplied by air pressure, but may be supplied by other compression means. It is envisioned that the pre-load force be applied in a symmetrically annular fashion around the spindle motor axis of rotation **183** and be directly aligned with the axis of rotation. It is also envisioned that each spindle motor receive the same predetermined amount of pre-load force **202** thus ensuring little clamping force variation between spindle motor units. While the disc clamp is in the compressed position, the disc clamp nut **136** is mated to the threaded stud **158** of the spindle to secure the pre-loaded disc clamp to the mounted information storage disc **177**. It is envisioned that the pre-load force applied to the disc clamp be such that only 15-35 inch-ounces of torque be required to secure the disc clamp nut **136** onto the threaded stud **158** of the spindle **130**.

FIG. **4** shows a deflected disc clamp **134** compressed between the substantially parallel surfaces of the disc clamp nut shoulder surface **208**, the flat engagement surface **178** of the hub **160**, the top surface **180** of the top information storage disc **177** and the loading surface **172** of the annular flange **170**. The substantially parallel orientation of the surfaces **178**, **194** and **208** with surface **172** ensures that the disc clamp's distributed load is uniform and normal to the top surface of the information storage disc **177**. An equal and opposite reaction force, between bottom surface **214** of the bottom information storage disc **174** and the loading surface **172** of the spindle hub annular flange **170**, results from the normal force. The two forces (normal and reaction) create a friction force in the plane of all mating surfaces which prevents the components of the spindle assembly **106** from shifting relative to each other when the disc drive **100** is in use or is subjected to high levels of shock and vibration.

An additional feature of the present invention is that in selecting the diameter of the disc clamp nut shoulder surface **208** and the flat engagement

surface **178** of the spindle hub interior annular shoulder **166** to be equal to each other, the normal force exerted on the top information storage disc remains perpendicular, and not offset, to the spindle axis of rotation **183**.

Finally, as illustrated in FIG. **4**, it is preferable that when the disc clamp is deflected by pre-load force **202**, that the inner annular spindle contact portion **194** of the disc clamp, the downward projecting peripheral edge **198** of the disc clamp, the flat engagement surface **178** of the hub **160** and the top surface **180** of the information storage disc **177** be approximately co-planar and substantially parallel with each other. The substantially parallel and approximately co-planar alignment of the surfaces helps ensure that the disc clamp's distributed load remains uniform and normal to the top information storage disc as the pre-load force is applied to the disc clamp.

FIG. **5** is a flow diagram showing the steps for securing a disc clamp **134** on a disc drive spindle assembly utilizing the preferred embodiment of the present invention. In operation **298**, the information storage disc is assembled on the hub of the disc drive spindle motor. In operation **300**, the disc clamp is positioned over an information storage disc on the spindle motor. In operation **302**, a uniform pre-load force is applied normal to the information storage disc so as to deflect the disc clamp to a predetermined compressed position. In operation **304**, while the pre-load force compresses the mounted information storage disc and disc spacer, a disc clamp nut is threaded on the spindle hub to secure the disc clamp to the spindle assembly. Finally, in operation **306**, the pre-load force is released from the disc clamp.

Therefore, the method entails an evenly distributed predetermined pre-load force being applied to a disc clamp on a spindle motor. The spindle motor has a series of parallel surfaces that interact together under the pre-load force to ensure a uniform loading and consequent reaction force to secure the information storage disc on the spindle motor. The predetermined pre-load force ensures that the force and reaction force are aligned with the spindle axis of rotation and thus that the disc clamp is uniformly loaded onto the information storage disc.

In summary, the preferred embodiment of the invention described herein is directed to a method of securing an information storage disc (such as **108**) within a

disc drive (such as **100**). The method includes assembling (such as in step **298**) an information storage disc (such as **108**) on a hub (such as **160**) of a disc drive spindle motor and then positioning (such as in step **300**) the disc clamp (such as **134**) on the hub (such as **160**) to engage the outer periphery (such as **197**) of the disc clamp with the top surface (such as **180**) of the information storage disc (such as **108**). Next, a predetermined pre-load force (such as **202**) is applied (such as in step **302**) against the disc clamp. A disc clamp nut (such as **136**) is positioned so as to secure the pre-loaded disc clamp to the hub of the disc drive spindle motor (such as in step **304**). Once the disc clamp nut is positioned the pre-load force is released from the disc clamp (such as in step **306**).

In another preferred embodiment of the present invention, the method includes loading an annular disc spacer (such as **176**) and second information storage disc (such as **174**) on the hub (such as **160**) of the disc drive spindle motor (such as **106**). Further, the predetermined pre-load force (such as **202**) can be applied symmetrically around the spindle motor's axis of rotation (such as **183**) and can be perpendicular to the top surface (such as **180**) of the information storage disc (such as **177**).

In another preferred embodiment of the present invention, the disc clamp defines an inner annular spindle contact portion (such as **194**), a middle annular raised portion (such as **196**) and a peripheral edge (such as **198**) where the step of applying a pre-load force (such as step **302**) occurs only against the middle annular raised portion (such as **196**) of the disc clamp (such as **134**).

In another preferred embodiment of the present invention, the hub (such as **160**) defines a peripheral ring (such as **168**) having an annular flange (such as **170**), the annular flange (such as **170**) defining an information storage disc loading surface (such as **172**). The hub further defines a top surface (such as **165**) having an annular shoulder (such as **166**), the annular shoulder defines a flat engagement surface (such as **178**) that is substantially parallel to the loading surface (such as **172**) of the annular flange (such as **170**), and the step of positioning the disc clamp on the hub (such as in step **300**) includes positioning the inner annular spindle contact (such as **194**) of the disc clamp on the flat engagement surface (such as **178**) of the annular shoulder of the hub.

In another preferred embodiment of the present invention, the inner annular spindle contact portion (such as **194**) of the disc clamp (such as **134**) is positioned between the flat engagement surface (such as **178**) of the annular shoulder (such as **166**) and the disc clamp nut (such as **136**).

In another preferred embodiment of the present invention, a disc clamp nut (such as **136**) defines a shoulder (such as **206**) having a flat engagement surface (such as **208**), and the step of positioning the disc clamp nut on the hub (such as in step **304**) includes the step of placing the flat engagement surface (such as **208**) of the disc clamp nut in substantially parallel alignment with the flat engagement surface (such as **178**) of the annular shoulder (such as **166**) of the hub (such as step **304**).

In another preferred embodiment of the present invention, the positioning of the disc clamp nut (such as **136**) on the hub step includes placing the disc clamp inner spindle contact portion (such as **194**) and peripheral edge (such as **198**) approximately co-planar to the annular shoulder (such as **166**) of the hub (such as **160**) and top surface (such as **180**) of the information storage disc (such as **177**).

In another preferred embodiment of the present invention, the inner and outer diameters (such as **207** and **209**) of the flat engagement surface (such as **208**) of the disc clamp nut (such as **136**) are substantially equal to the inner and outer diameters (such as **211** and **213**) of the flat engagement surface (such as **178**) of the annular shoulder (such as **166**) of the hub (such as **160**).

In another preferred embodiment of the present invention, the positioning of the disc clamp nut on the hub (such as in step **300**) further includes the step of aligning the respective inner and outer diameters of the flat engagement surface of the shoulder portion of the disc clamp nut and the flat engagement surface of the annular shoulder of the hub.

A further exemplary preferred embodiment of the present invention includes having a disc drive spindle motor assembly (such as **104**) having a spindle shaft (such as **156**) and a cylindrical hub (such as **160**) extending radially outward from the shaft. The spindle shaft (such as **156**) further includes a threaded stud (such as **158**) extending above a top surface (such as **165**) of the cylindrical hub (such as **160**). An information storage disc (such as **108**) is mounted on the

cylindrical hub (such as **160**). A disc clamp (such as **134**) having a central aperture (such as **204**), an inner annular contact portion (such as **194**), a middle annular raised portion (such as **196**) and a peripheral edge (such as **198**) is fitted over the threaded stud (such as **158**) to allow the inner annular contact portion (such as **194**) to engage the top surface (such as **165**) of the hub (such as **160**) while the peripheral edge (such as **198**) engages the top surface (such as **180**) of the information storage disc (such as **177**). The disc clamp middle annular raised portion (such as **196**) extends above the top surface (such as **165**) of the hub (such as **160**) and is adapted to receive a pre-load force (such as **202**). Finally, a disc clamp nut (such as **136**) is secured to the threaded stud (such as **158**), where the nut includes a contact surface (such as **208**) for engaging the inner annular contact portion (such as **194**) of the disc clamp (such as **134**) to secure the pre-loaded disc clamp to the hub.

In another preferred embodiment of the present invention, the hub top surface (such as **165**) further defines an annular shoulder (such as **166**) having a flat engagement surface (such as **178**) substantially parallel to the loading surface (such as **172**) of the annular flange (such as **170**). The annular shoulder flat engagement surface (such as **178**) receives the disc clamp (such as **134**).

In another preferred embodiment of the present invention, the disc clamp nut (such as **136**) defines a shoulder (such as **206**) having a flat bottom surface (such as **208**) substantially parallel to the loading surface (such as **172**) of the annular flange (such as **170**). The disc clamp (such as **134**) is secured between the flat bottom surface (such as **208**) of the disc clamp nut shoulder (such as **206**) and the flat engagement surface (such as **178**) of the annular shoulder (such as **166**) of the hub (such as **160**).

In another preferred embodiment of the present invention, the flat engagement surface (such as **208**) of the disc clamp nut (such as **136**) has an inner and outer diameter (such as **207** and **209**) that is substantially equal to an inner and outer diameter (such as **211** and **213**) of the flat engagement surface (such as **178**) of the hub annular shoulder (such as **166**).

In another preferred embodiment of the present invention, the disc clamp inner annular shoulder (such as **194**) and peripheral edge (such as **198**) are

approximately co-planar to the hub's annular shoulder (such as **166**) and the top surface (such as **180**) of the information storage disc (such as **177**).

It will be clear that the present invention is well adapted to attain the ends and advantages mentioned as well as those inherent therein. While a presently preferred embodiment has been described for purposes of this disclosure, numerous changes may be made which will readily suggest themselves to those skilled in the art For example, rather than the hub portion of the spindle motor having a threaded stud for interaction with a disc clamp nut, the hub portion could define a threaded aperture for interaction with a threaded disc clamp retaining screw having a mating tapered shoulder. Accordingly, all such modifications, changes and alternatives are encompassed in the spirit of the invention disclosed and as defined in the appended claims.

WHAT IS CLAIMED IS:

1. A method of securing an information storage disc within a disc drive, the method comprising steps of:

(a). assembling the information storage disc on a hub of a disc drive spindle motor;

(b). positioning a disc clamp on the hub to engage an outer periphery of the disc clamp with a top surface of the information storage disc;

(c). applying a predetermined pre-load force against the disc clamp;

(d). positioning a disc clamp nut to secure the disc clamp to the hub of the disc drive spindle motor; and

(e). releasing the pre-load force from the disc clamp.

2. The method according to claim 1, wherein assembling step (a) further comprises the steps of:

(a)(i). positioning an annular disc spacer on the hub portion of the disc drive spindle motor; and

(a)(ii). assembling a second information storage disc on the hub portion such that the annular disc spacer is between the first aforesaid information storage disc and the second information storage disc.

3. The method according to claim 1, wherein the applying step (c) further comprises applying a symmetrical pre-load force around an axis of rotation of the spindle motor.

4. The method according to claim 1, wherein the applying step (c) further comprises applying the predetermined pre-load force perpendicular to the top surface of the information storage disc.

5. The method according to claim 1, wherein the disc clamp defines an inner annular spindle contact portion, a middle annular raised portion, and a peripheral edge and wherein applying step (c) further comprises applying the

This Sheet Has Been Replaced

predetermined pre-load force only against the middle annular raised portion of the disc clamp.

6. The method according to claim 5, wherein the hub defines a peripheral ring having an annular flange, the annular flange defining a loading surface, and the hub further defines a top surface having an annular shoulder, the annular shoulder defining a flat engagement surface substantially parallel to the loading surface of the annular flange, and wherein the positioning step (b) further comprises positioning the inner annular spindle contact portion to engage the flat engagement surface of the annular shoulder of the hub.

7. The method according to claim 6, wherein the positioning step (d) further comprises positioning the inner annular spindle contact portion of the disc clamp between the flat engagement surface of the annular shoulder and the disc clamp nut.

8. The method according to claim 7, wherein the disc clamp nut defines a shoulder having a flat engagement surface and wherein the positioning step (d) further comprises placing the flat engagement surface of the disc clamp nut in substantially parallel alignment with the flat engagement surface of the annular shoulder of the hub.

9. The method according to claim 8, wherein the positioning step (b) further comprises placing the disc clamp inner annular spindle contact portion and peripheral edge approximately co-planar to the flat engagement surface of the annular shoulder of the hub and the top surface of the information storage disc.

10. The method according to claim 8, wherein the flat engagement surface of the disc clamp nut has an inner and outer diameter that is substantially equal to an inner an outer diameter of the flat engagement surface of the annular shoulder of the hub, and wherein the positioning step (d) further comprises aligning the respective inner and outer diameters of the flat engagement surface of

This Sheet Has Been Replaced

the shoulder portion of the disc clamp nut and the flat engagement surface of the annular shoulder of the hub.

11. The method according to claim 8, wherein the positioning step (d) further comprises avoiding contact between the hub and the middle annular raised portion of the disc clamp.

12. A disc drive spindle motor assembly comprising:

a spindle having a shaft and a cylindrical hub extending radially outward from the shaft, the shaft including a threaded stud extending above a top surface of the cylindrical hub;

an information storage disc mounted on the cylindrical hub, the information storage disc having a top surface;

a disc clamp having a central aperture, an inner annular contact portion, a middle annular raised portion, and a peripheral edge, the central aperture of the disc clamp fitted over the threaded stud to allow the inner annular contact portion to engage the top surface of the hub while the peripheral edge engages the top surface of the information storage disc, and the middle annular raised portion extending above the top surface of the hub and adapted to receive a pre-load force; and

a disc clamp nut secured to the threaded stud, the nut including a contact surface for engaging the inner annular contact portion of the disc clamp.

13. The spindle motor assembly of claim 12, wherein the hub defines a peripheral ring having an annular flange, the annular flange defining a loading surface for receiving the information storage disc and the hub further includes a top surface having an annular shoulder that defines a flat engagement surface for receiving the disc clamp; and

the flat engagement surface of the annular shoulder is substantially parallel to the loading surface of the annular flange.

This Sheet Has Been Replaced

14. The spindle motor assembly of claim 13, wherein the disc clamp nut defines a shoulder having a flat bottom surface substantially parallel to the loading surface of the annular flange; and

the disc clamp is secured between the flat bottom surface of the disc clamp nut and the flat engagement surface of the annular shoulder of the hub.

15. The spindle motor assembly of claim 14, wherein the flat bottom surface of the disc clamp nut has an inner and outer diameter that is substantially equal to an inner and outer diameter of the flat engagement surface of the annular shoulder of the hub.

16. The spindle motor assembly of claim 15, wherein the disc clamp inner annular spindle contact portion and peripheral edge are approximately co-planar to the hub annular shoulder and the top surface of the information storage disc.

17. The spindle motor assembly of claim 16, wherein the disc clamp inner annular spindle contact portion and peripheral edge are substantially parallel to the hub annular shoulder and the top surface of the information storage disc.

18. A disc drive spindle motor assembly comprising:

an information storage disc mounted on a cylindrical hub of a rotating spindle; and

means for providing a uniform clamping force to a top surface of the information storage disc.