

Abstract

The invention relates to an encoding safety system for firearms (1, 1a) of the same type but different calibers for preventing confusion of at least one component (2, 2a, 3, 3a, 7, 7a, 8, 8a, 11, 11a, 19, 19a), comprising:

- at least one first firearm (1) of a first caliber, or at least one component (2, 2a, 3, 3a, 7, 7a, 8, 8a, 11, 11a, 19, 19a) thereof,
- at least one second firearm (1a) of a second, different caliber, or at least one component (2, 2a, 3, 3a, 7, 7a, 8, 8a, 11, 11a, 19, 19a) thereof,
- at least one safety element on the first and/or second firearm (1, 1a), or the at least one component (2, 2a, 3, 3a, 7, 7a, 8, 8a, 11, 11a, 19, 19a, 37, 37a) thereof, which is designed to prevent attachment of the at least one (2, 2a, 3, 3a, 7, 7a, 8, 8a, 11, 11a, 19, 19a, 37, 37a) of the at least one first firearm (1) to the at least one second firearm (1a), and

at least one second safety element on the first and/or second firearm or the at least one component (2, 2a, 3, 3a, 7, 7a, 8, 8a, 11, 11a, 19, 19a, 37, 37a) thereof, which is designed to prevent attachment of the at least one component (2, 2a, 3, 3a, 7, 7a, 8, 8a, 11, 11a, 19, 19a, 37, 37a) of the at least one second firearm (1a) to the at least one first firearm (1).

The invention also relates to components (2, 2a, 3, 3a, 7, 7a, 8, 8a, 11, 11a, 19, 19a, 37, 37a) and firearms (1, 1a) for use in the encoding safety system.

Figure 1