

CONNECTION ESTABLISHMENT METHOD AND DEVICE

Technical Field

The present invention relates to network technologies, and in particular to a method and a device for establishing a connection.

Background

Such a scenario occurs frequently: a user A needs to contact a user B for a matter, but user A does not have the contact information of user B and is unable to get in touch with user B. As a result, the matter cannot proceed smoothly; from a point of view of user B, however, he/she does not like to be bothered by any random contact, but would like to receive contacts only for the processing of the above-mentioned matter. At present, it is still impossible to meet the needs of both user A and user B.

Summary

In view of the above, the present invention provides a method and a device for establishing connection to realize a connection required for service processing.

Specifically, the present invention is implemented by means of the following technical solution:

According to a first aspect, a connection establishment method is provided, comprising:

receiving a service connection request sent by a first client, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

acquiring connection reference information, and when it is determined that the connection reference information satisfies a service restriction condition corresponding to the service identifier, establishing a connection between the first client and the second client corresponding to the client identifier.

According to a second aspect, a connection establishment method is provided, which is carried out by a first client, comprising:

sending, to a server, a service connection request, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

establishing, when the server determines that connection reference information satisfies a service restriction condition corresponding to the service identifier, a connection via the server with the second client corresponding to the client identifier.

According to a third aspect, a connection establishment device is provided, comprising:

a request receiving module, configured to receive a service connection request sent by a first client, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

a connection processing module, configured to acquire connection reference information, and when it is determined that the connection reference information satisfies a service restriction condition corresponding to the service identifier, establish a connection between the first client and the second client corresponding to the client identifier.

According to a fourth aspect, a connection establishment device is provided, comprising:

a request sending module, configured to send, to a server, a service connection request, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

a connection establishment module, configured to establish, when the server determines that connection reference information satisfies a service restriction condition corresponding to the service identifier, a connection via the server with the second client corresponding to the client identifier.

According to the method and the device for establishing connection in embodiments of the present invention, a connection between two clients is established only when connection reference information satisfies a service restriction condition corresponding to the service identifier, which realizes a connection required for service processing.

Brief Description of the Drawings

Fig. 1 illustrates a system architecture of a connection establishment method according to an embodiment of the present invention;

Fig. 2 is a flow chart of a connection establishment method according to an embodiment of the present invention;

Fig. 3 is a flow chart of another connection establishment method according to an embodiment of the present invention;

Fig. 4 illustrates a scenario of moving a car for a connection establishment method according to an embodiment of the present invention;

Fig. 5 is a flow chart of yet another connection establishment method according to an embodiment of the present invention;

Fig. 6 is a schematic diagram of an interface of a connection establishment method according to an embodiment of the present invention;

Fig. 7 is a flow chart of yet another connection establishment method according to an embodiment of the present invention;

Fig. 8 illustrates a structural diagram of a connection establishment device according to an embodiment of the present invention;

Fig. 9 illustrates a structural diagram of another connection establishment device according to an embodiment of the present invention;

Fig. 10 illustrates a structural diagram of yet another connection establishment device according to an embodiment of the present invention.

Detailed Description of the Invention

The connection establishment method according to embodiments of the present application is applied to connection establishment when a service is to be performed between a user A and a user B and a service restriction condition is satisfied. Application scenarios that the connection establishment method is applicable to will be briefly described with the following two scenarios as examples:

For example, a user Zhang parks his car by a road to go shopping. However, Zhang forgets to leave his contact information on the car; a user Wang drives by but has to stop, as Zhang's car needs to be moved out of his way. In such a scenario, a situation arises that Wang needs to contact Zhang. A connection request caused by such a "car-moving" need may be called a "car-moving" service, and the request by Wang to connect with Zhang is caused by the car-moving service.

For another example, Zhang waits in a line for eating in a restaurant in a mall. There are many people in the line with the issued waiting number reaching 100, and there are 50 people before Zhang in the line. Zhang thinks that the wait time is too long, so he goes around in the mall without leaving his contact information with the restaurant; when it reaches almost Zhang's number, the restaurant wants to contact Zhang and reminds him to return as quickly as possible. In such a scenario, a situation arises that the restaurant needs to contact Zhang. A connection request caused by such a "queuing" need may be called a

“queuing” service, and the request by the restaurant to connect with Zhang is caused by the queuing service.

Certainly, there are many similar examples, which will not be listed in detail; it can be seen from the examples above that the goal of the connection establishment method according to embodiments of the present application is to achieve connection establishment when a service is to be processed between a user A and a user B, such that Wang can get in touch with Zhang for him to come back to move the car, or the restaurant can get in touch with Zhang for him to come back to eat in the restaurant. To Zhang, moreover, he is only contacted due to a need for a service, such as car moving or queuing, and he will not be bothered randomly. The connection establishment method according to embodiments of the present application involves a system architecture shown in Fig. 1. As shown in Fig. 1, the system comprises a server 11, a first client 12 and a second client 13.

Here, the first client 12 and the second client 13 may be clients corresponding, respectively, to a user A and a user B to be connected, while the server 11 is a server corresponding to these clients. As an example, in the car-moving scenario above, both Zhang and Wang can install an “Alipay Wallet” on their smart phones. The Alipay Wallet on Zhang’s smart phone may be referred to as the first client, the Alipay Wallet on Wang’s smart phone may be referred to as the second client, and correspondingly, the server 11 is an Alipay server. The connection establishment is realized for the car-moving service through cooperation between the Alipay server and the Alipay Wallets. As another example, in the queuing scenario above, the restaurant may install an Alipay Wallet on its terminal, and Zhang also installs an Alipay Wallet on his cell phone. The connection establishment is similarly realized for the queuing service through cooperation between the Alipay server and the Alipay Wallets.

It should be noted that the first client and the second client may not necessarily be the Alipay Wallets above. Embodiments of the present application do not limit the form of clients or servers. They just need to be capable of implementing the connection establishment method according to the embodiment. The main implementation flow of the connection establishment method according to the present application will be first described below, and then applications of the method will be specifically described with reference to the car-moving scenario and the queuing scenario mentioned above. Referring to Fig. 2, an implementation flow of the connection establishment method is illustrated. The method is implemented by a server, comprising:

201. receiving a service connection request sent by a first client, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

202. acquiring connection reference information, and when it is determined that the connection reference information satisfies a service restriction condition corresponding to the service identifier, establishing a connection between the first client and the second client corresponding to the client identifier.

Fig. 3 illustrates an implementation flow of the connection establishment method. The method is implemented by a client, comprising:

301. sending, to a server, a service connection request, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

302. establishing, when the server determines that connection reference information satisfies a service restriction condition corresponding to the service identifier, a connection via the server with the second client corresponding to the client identifier.

In the steps 201 and 301, a service connection request may be sent by the first client to the server. With the use of an Alipay client in the car-moving scenario as an example, a function option, “car moving”, may be set up in the “Alipay Wallet” of the client. When Wang who desires a car to be moved selects the function option, “car moving”, the client sends, to a server, a service connection request. Since the request sending is triggered by clicking the function option, “car moving”, the request may carry information for identifying the “car moving” service, e.g. “01”, which is equivalent to a service identifier. Alternatively, when Wang selects the function option, “car moving”, some sub-menus comprised in the function are displayed. A request sent by operations performed under these sub-menus may also carry a car-moving service identifier. In this scenario, the client identifier carried in the service connection request is, for example, a license plate number. See the embodiment shown in Fig. 5 below for details.

In addition, the client identifier of a second client requested for connection carried in the service connection request above is used to let the server know that the target object to be connected by the first client is the second client. With the use of an Alipay client in the queuing scenario as an example, an Alipay Wallet can be installed on the terminal of the restaurant, and a function option, “queuing”, is set up in the Alipay Wallet. The function option, “queuing”, can provide a two-dimensional barcode for queuing; when Zhang waits in a line for eating in the restaurant, he can scan the two-dimensional barcode for queuing using

the Alipay Wallet on his cell phone. After the Alipay Wallet scans the two-dimensional barcode mentioned above, the terminal of the restaurant can acquire the identifier of Zhang's Alipay Wallet, e.g. the account number of the Alipay Wallet, and the account number can be referred to as the client identifier. When the restaurant sends a service connection request to the server through its queuing function, the client identifier can be carried. In such a scenario, the service identifier carried in the service connection request is information used to represent the queuing function. For example, if a waiter enters the function option, "queuing", in the Alipay Wallet installed on the queuing terminal of the restaurant to process the queuing service, a connection request, when sent from the interface of the service, can automatically carry an identifier corresponding to the "queuing" function, i.e. the service identifier.

In the step 202, upon receiving the service connection request, the server needs to acquire connection reference information, and determine whether the connection reference information satisfies a service restriction condition corresponding to the service identifier. Only when the service restriction condition is satisfied, does the server allow a connection to be established between the first client and the second client.

With the car-moving scenario as an example again, Zhang who parks his car does not want to be contacted randomly, but is typically willing to be contacted when other people need his car to be moved. Therefore, the service restriction condition may be set, according to the characteristic of car-moving situations, to "the cars of Zhang and Wang are within a distance of 100 m". In the case where a car needs to be moved, it is usually because the parked car blocks a road, and the blocked car is relatively close to the parked car. Moreover, the service restriction condition, "the cars of Zhang and Wang are within a distance of 100 m", has been quantified to further facilitate judgment, and can be set to "the distance between a first client and a second client is within 100 m." The position of the first client may be the position that Zhang reports to the server via the first client while parking the car, i.e. the position where the car is parked; on the other hand, the position of the second client is the position reported by Wang to the server via the second client when the current car of Wang is blocked. In this example, the position information reported by the first client and the second client may be referred to as connection reference information, a basis on which the server determines whether the service restriction condition is satisfied. There may be a variety of ways for the server to acquire the connection reference information, for example, the client takes the initiative to report or the server sends a notice for reporting.

In addition, there may also be a variety of ways for the server to establish a connection between the first client and the second client corresponding to the client identifier such that the two clients are connected in this step; for example, as a forwarding device between the first client and the second client, the server may directly send the message to be sent by the first client to the second client; alternatively, the server may provide the pre-stored contact information of the second client to the first client, such that the first client contacts the second client separately without forwarding via the server. In such a case, for example, the telephone number of Zhang corresponding to the second client is sent to the first client, and upon acquiring the telephone number, the user Wang of the first client makes a phone call to Zhang directly. At this moment, it is actually a contact between users corresponding to the clients. For the purpose of simple description, they are collectively referred to as connection between a first client and a second client in the embodiments of the present application. Other connection ways will not be listed in detail.

With the connection establishment method according to the embodiment of the present application, a server controls, when a service restriction condition is satisfied, two clients to establish connection, thereby realizing that a user can, as long as the client is installed, request the server for connection through a function option set in the client. It is very convenient. Specific applications of the connection establishment method will be described below with reference to examples of a few scenarios.

As an example, referring to the car-moving scenario shown in Fig. 4, Zhang parks his car 41 by a road, Wang drives his car 42 to pass the same location and finds that Zhang's car blocks the road and needs to be moved away. At this moment, Wang begins to contact Zhang. With reference to the implementation flow shown in Fig. 5, and assuming that a second client is installed on Zhang's cell phone, a first client is installed on Wang's cell phone, said clients being Alipay Wallets as an example, then the entire processing flow from the moment when Zhang begins to park the car to the moment when Wang contacts Zhang may comprise:

501. The second client reports the parking information to the server, the parking information comprising: connection reference information;

In this embodiment, the parking information comprises two parts: a client identifier of the second client and the connection reference information.

Here, the client identifier of the second client is information used to identify the second client. For example, if the second client is an Alipay Wallet, then the client identifier could be an account number of the Alipay Wallet, or could be some information with a corresponding relationship to the second client. For example, the server side stores a

corresponding relationship between Alipay Wallets of users and license plate numbers of users, and then the server can find a corresponding Alipay Wallet according to a license plate number. In such a case, the license plate number is also referred to as a client identifier of a second client in this embodiment; for another example, the server side stores a corresponding relationship between Alipay Wallets of users and queuing numbers of users. If the server is notified of a user's queuing number, and the server can find the Alipay Wallet of the user according to the queuing number. Then, the user's queuing number may also be referred to as a client identifier. In other words, the client identifier in this embodiment may comprise the client's own information (e.g. an account number of the Alipay Wallet), or information with a corresponding relationship to the client (e.g. a license plate number corresponding to the Alipay Wallet).

Here, the connection reference information is used by the server when making determination of a service restriction condition. Namely, when the server determines whether a service restriction condition required for service connection establishment is met, the connection reference information is needed. For example, the connection reference information in this embodiment could be the parking position information, and the server may determine, according to the position information, whether it is in a position range; alternatively, the connection reference information may be time information in other scenarios.

For example, when Zhang has parked his car 41, he turns on the second client on the cell phone, i.e. the Alipay Wallet. Fig. 6 illustrates the display interface of a part of the Alipay Wallet. The interface comprises many application functions and one of the function options is "I want to park a car". Zhang chooses this function, which triggers the Alipay Wallet client to report the parking information to the server.

The parking information in this embodiment may comprise: a second client identifier (e.g. an account number of the Alipay Wallet, the license plate number of Zhang's car), and the parking position of Zhang's car. Here, regarding the license plate number, an input page may be displayed after Zhang clicks the function, "I want to park a car", for Zhang to input his own license plate number; regarding the parking position, it could be that the second client activates a positioning function to acquire the position information, and the position information could be longitude and latitude coordinates. Moreover, since the parking position of Zhang's car reported in this step will be used in the subsequent determination of a service restriction condition by the server, the parking position information may be referred to as connection reference information.

502. The server stores the parking information reported by the second client;

For example, in this step, the server will store a corresponding relationship between parking information, such as a corresponding relationship between an account number of the Alipay Wallet, the license plate number of Zhang's car, and the parking position of Zhang's car; moreover, the server side could usually acquire contact information of the user Zhang corresponding to the second client, e.g. a telephone number, during registration of the second client, and the telephone number can be bundled to the second client identifier, i.e. the server side can also bundle Zhang's telephone number with the above corresponding relationship.

503. The server receives a service connection request sent by a first client, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

For example, Wang, who wants a car to be moved, can turn on the first client on his cell phone, i.e. the Alipay Wallet, and an interface similar to the one shown in Fig. 6 will also be displayed on the Alipay Wallet. The interface further comprises a function, "car moving". When Wang clicks the function option, "car moving", an input box or a sub-interface can be popped up for Wang to input the license plate number of the car that he wants to be moved. Here, Wang will input the license plate number of Zhang's car and click Send to send a service connection request to the server. As described in 501 above, since the server stores a corresponding relationship between license plate numbers and Alipay Wallets, the license plate number of Zhang's car input by Wang in this step may be referred to as the "client identifier of a second client". It should be noted that, since there is also a corresponding relationship between license plate numbers and Alipay account numbers of second clients, the license plate number may also be treated as a client identifier corresponding to the second client. The service identifier carried in the request is information representing the "car-moving" service.

In this step, moreover, after Wang chooses the function option, "car moving", the first client can further automatically acquire position information that is carried in the service connection request and reported to the server. The position information is equivalent to Wang's current position, and the position information is also connection reference information for subsequent determination by the server.

504. The server determines whether the connection reference information satisfies a service restriction condition corresponding to the service identifier;

For example, the server may determine, according to the position information reported by the first client and the second client, respectively, whether the two satisfy a distance threshold. The service restriction condition is a distance range threshold corresponding to the position information. For example, the service restriction condition corresponding to the car-moving service is that “the distance between the two is within a range of 100 m”, and the condition can be pre-stored in the server.

According to the license plate number in the service connection request and the corresponding relationship stored in 502, the server acquires the first position information corresponding to the license plate number, i.e. the parking position of Zhang’s car, and determines whether the distance between the first position information corresponding to the first client and the second position information reported by the second client is less than 100 m. If yes, the service restriction condition is satisfied, and 505 will be subsequently carried out; otherwise, the service restriction condition is not satisfied, and the server can return a prompt like “connection rejected” to the first client.

505. The server sends the contact information of the second client corresponding to the client identifier to the first client;

For example, when determining that the service restriction condition is satisfied, the server may acquire, according to the corresponding relationship stored in 502, the contact information of Zhang, such as a telephone number, and sends Zhang’s telephone number to the first client. At this point, the telephone number is actually the contact information of the user of the second client, and the user Wang of the first client can establish a phone contact with the user Zhang of the second client.

Optionally, the server may also directly establish a connection between the first client and the second client. For example, when Wang chooses the “car-moving” function through the first client and triggers the first client to send the service connection request to the server, the server can find corresponding Zhang’s telephone number according to the license plate number carried in the request, and automatically send a message (e.g. a car-moving prompt message) to the telephone number, which can also be treated as connection establishment between the two clients. Alternatively, the server can send a car-moving prompt message to Zhang’s Alipay Wallet that is found according to the license plate number, to prompt Zhang to come back and move the car. In addition, other manners may be used, which will not be listed, as long as they can achieve the connection between Zhang and Wang.

Furthermore, when the server finds corresponding Zhang's telephone number according to the license plate number carried in the request as described above, a piece of identification information corresponding to the telephone number (which may be referred to as a "small number") can be generated, for example, the identification information "12589" is used to correspond to Zhang's telephone number, and "12589" is returned to the first client. When Wang contacts the identification information "12589", for example, a connection instruction sent by the first client is received, and the connection instruction carries the identification information, based on which the server sends a message or voice message to the telephone number corresponding to the identification information. This way can make Zhang's telephone number more confidential, leading to better security.

As an example, another application scenario is also a car-moving scenario, which is similar to the scenario shown in Fig. 4. The difference is in that only a function option, "car moving", to be used by car-moving users is set up in the Alipay Wallet, and the function option, "I want to park a car", may not be provided for parking users. Instead, another way is provided as a replacement. Specifically, Zhang who needs to park a car can set up a piece of hardware on his car, e.g. a Bluetooth chip. The Bluetooth chip can be referred to as a marker, and the Bluetooth chip comprises an ID to identify the chip, which can be referred to as a marker identifier.

When Wang wants the car to be moved, he can turn on his Alipay Wallet, i.e. the first client, and enters the "car moving" function of the Alipay Wallet. When the car-moving function is selected, Wang can be prompted to get close to Zhang's car. When the distance is short enough to meet conditions of Bluetooth communication, Wang's Alipay Wallet acquires the ID of the Bluetooth chip on Zhang's car by means of Bluetooth and sends a service connection request to the server. At this moment, the connection request carries the car-moving service identifier and the Bluetooth chip ID. In this embodiment, the Bluetooth chip ID can be, for the time being, referred to as a marker identifier of the second client, since the server side may have pre-stored the corresponding relationship between Zhang's account number of Alipay Wallet, the Bluetooth chip ID on the car, and Zhang's contact information.

At the server side, whenever it is found that the service connection request sent by the Alipay Wallet carries the Bluetooth chip ID, it indicates that Wang is already close to Zhang's car, as the ID can be acquired only when the distance is close enough. The server determines that the service restriction condition is satisfied. Subsequently, the server can acquire Zhang's contact information corresponding to the Bluetooth chip ID, and return the same to the first client for Wang to contact Zhang.

As an example, the method can be further applied to the queuing scenario. In a restaurant at a mall, Zhang goes to the restaurant to eat. He turns on his Alipay Wallet to scan the two-dimensional barcode for queuing at the queuing terminal at the reception desk of the restaurant. When he takes a queue number, he goes shopping in stores nearby. An Alipay Wallet can be installed on the queuing terminal at the reception desk of the restaurant, which provides a queuing function. The queuing function provides the above two-dimensional barcode for queuing. As Zhang scans and takes a number, the first client (the Alipay Wallet) on the queuing terminal of the restaurant acquires the identifier (e.g. an account number) of the second client, i.e. the Alipay Wallet, on Zhang's cell phone, and reports the identifier of Zhang's Alipay Wallet and the service identifier (i.e. the queuing service information) to the Alipay server.

When it is close to Zhang's number, the restaurant contacts Zhang through the queuing function of the Alipay Wallet on its queuing terminal, and the flow shown in Fig. 7 is implemented, comprising:

701. the first client sends, to a server, a service connection request;

For example, the restaurant turns on the queuing function of the Alipay Wallet on its queuing terminal, and finds the information regarding Zhang's scanning and number taking previously. The queuing function of the Alipay Wallet can provide a trigger option for the restaurant to contact Zhang. For example, a "contact" button is added to the queue number of Zhang and displayed on the interface.

When a waiter of the restaurant clicks the "contact" button, the first client, i.e. the Alipay Wallet on the queuing terminal, will send, to a server, a service connection request carrying a service identifier representing the queuing service and a client identifier of the second client.

For example, the above "contact" button may be bundled with the account number of Zhang's Alipay Wallet that is acquired by the first client. When the waiter clicks the button, the account number of the Alipay Wallet and a service identifier (used to indicate that this is a queuing service) will be carried in the service connection request. The account number of the Alipay Wallet is equivalent to a client identifier of the second client.

For another example, prior to the implementation of 701, after Zhang scans and takes a number, the first client on the queuing terminal will report the account number of Zhang's Alipay Wallet, the queue number and the service identifier all to the server. The server side will record the corresponding relationship between the information, including a corresponding relationship between the account number of the Alipay Wallet and the queue

number. In such a situation, when the first client clicks the “contact” button to send a request, the request can carry the service identifier and the queue number, and the queue number may be referred to as a client identifier of the second client.

702. the server acquires connection reference information;

For example, in this embodiment, it is assumed that the service restriction condition corresponding to the queuing service is that “the current time is within 3 hours after the time of number taking, and the current position of the second client is within the range of the geographic location of the business”. In other words, the time when the restaurant contacts Zhang is within 3 hours after the time when Zhang takes a number at the restaurant, and moreover, Zhang’s current position is not too far away from the restaurant, for example, within a range of 500 m.

The server needs to acquire connection reference information for making determination of a service restriction condition. The connection reference information comprises current time, Zhang’s position, and the restaurant’s location. Here, the current time can be easily obtained. With respect to acquiring Zhang’s position, a positioning instruction may be sent, via the server, to the second client, i.e. Zhang’s Alipay Wallet, and when Zhang’s Alipay Wallet positions and acquires the position information, the position information is returned to the server. As for the restaurant’s location, it can be stored in the server in advance. Certainly, other ways of acquisition may be available, and only one of them is listed herein.

703. the server determines whether the connection reference information satisfies a service restriction condition;

For example, the server will determine whether the current time is within 3 hours (a time range threshold) after the time when Zhang takes the number, and the time when Zhang takes the number can be stored by the server when the restaurant client performs uploading in 701; moreover, the server will determine whether the distance between Zhang’s current position and the restaurant is within 1000 m (a distance range threshold).

If the server determines that the connection reference information satisfies a service restriction condition, then proceed to 704;

704. the server sends the contact information of the second client to the first client.

Optionally, the server may find Zhang’s number according to the pre-stored corresponding relationship between Zhang’s Alipay account number, Zhang’s queue number and Zhang’s contact information, and send the same to the first client for the business to

contact Zhang. Alternatively, as described in the embodiment shown in Fig. 5, the server contacts Zhang directly.

Furthermore, to better meet the need of Zhang as a person to be contacted, the server may receive a service restriction condition uploaded by Zhang via the second client. For example, Zhang can set up, via the Alipay Wallet, a condition that he desires for contacting him. For example, “the current time is within 1 hour after the number-taking time” is set as a service restriction condition for contacting Zhang.

No examples will be provided for other scenarios. All similar applications can use the connection establishment method according to the embodiment of the present application, and the method does not impose strict limitations to service restriction conditions or connection manners. For example, a service restriction condition may be limited within the same wifi coverage, or limited within the same geographic range, or limited within the same Bluetooth coverage, or limited within the same permission range. The connection manner includes, but is not limited to, telephone connection, instant messaging connection, and payment connection. The connection establishment method is implemented on the basis of clients and a server, and moreover, such a connection establishment corresponds to services and is a service connection initiated to realize a service. Moreover, a service restriction condition corresponding to the service needs to be satisfied. The method satisfies both the demand for performing the service, and the demand that the terminal to be connected will not be randomly bothered. Furthermore, these can be achieved very conveniently.

To implement the above method, the embodiment of the present application further provides a connection establishment device, and the device can be applied on a server. As shown in Fig. 8, the device can comprise: a request receiving module 81 and a connection processing module 82; wherein,

the request receiving module 81 is configured to receive a service connection request sent by a first client, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

the connection processing module 82 is configured to acquire connection reference information, and when it is determined that the connection reference information satisfies a service restriction condition corresponding to the service identifier, establish a connection between the first client and the second client corresponding to the client identifier.

Furthermore, the connection reference information comprises at least one of the following: position information or time information.

Furthermore, the connection processing module 82 is configured to send contact information of the second client corresponding to the client identifier to the first client, such that the first client establishes, according to the contact information, a connection with the second client.

Furthermore, the connection processing module 82 is specifically configured to send identification information corresponding to the contact information of the second client to the first client, and receive a connection instruction sent by the first client, the connection instruction carrying the identification information; moreover, connect, according to the contact information corresponding to the identification information, the first client with the second client.

To implement the above method, the embodiment of the present application further provides a connection establishment device, and the device can be applied on a server. As shown in Fig. 9, the device can comprise: a request sending module 91 and a connection establishment module 92; wherein,

the request sending module 91 is configured to send, to a server, a service connection request, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

the connection establishment module 92 is configured to establish, when the server determines that connection reference information satisfies a service restriction condition corresponding to the service identifier, a connection via the server with the second client corresponding to the client identifier.

Furthermore, referring to Fig. 10, the device can further comprise: an information reporting module 93, configured to send, to the server, the connection reference information or service restriction condition.

Only preferred embodiments of the present invention are described above, which are not used to limit the present invention. Any modification, equivalent substitution, or improvement made within the spirit and principle of the present invention shall be encompassed by the scope of the present invention.

Claims

1. A connection establishment method, characterized in that the method comprises:
receiving a service connection request sent by a first client, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

acquiring connection reference information, and when it is determined that the connection reference information satisfies a service restriction condition corresponding to the service identifier, establishing a connection between the first client and the second client corresponding to the client identifier.

2. The method according to claim 1, characterized in that the connection reference information comprises at least one of the following: position information or time information;
the service restriction condition corresponding to the service identifier comprises at least one of the following: a distance range threshold corresponding to the position information or a time range threshold corresponding to the time information.

3. The method according to claim 1, characterized in that the method further comprises:
receiving the service restriction condition sent by the second client.

4. The method according to claim 1, characterized in that the establishing a connection between the first client and the second client corresponding to the client identifier comprises:
sending contact information of the second client corresponding to the client identifier to the first client, such that the first client establishes, according to the contact information, a connection with the second client.

5. The method according to claim 4, characterized in that the contact information of the second client comprises: identification information corresponding to the contact information of the second client;

after sending the identification information to the first client, the method further comprises: receiving a connection instruction sent by the first client, the connection instruction carrying the identification information; and connecting, according to the contact

information corresponding to the identification information, the first client with the second client.

6. A connection establishment method, characterized in that the method is carried out by a first client, comprising:

sending, to a server, a service connection request, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

establishing, when the server determines that connection reference information satisfies a service restriction condition corresponding to the service identifier, a connection via the server with the second client corresponding to the client identifier.

7. The method according to claim 6, characterized in that the method further comprises: sending, to a server, the connection reference information.

8. The method according to claim 6, characterized in that the method further comprises: sending, to a server, the service restriction condition.

9. The method according to claim 6, characterized in that the establishing a connection via the server with the second client corresponding to the client identifier comprises:

receiving the contact information of the second client corresponding to the client identifier returned by the server, and establishing, according to the contact information, a connection with the second client.

10. A connection establishment device, characterized in that the device comprises: a request receiving module, configured to receive a service connection request sent by a first client, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

a connection processing module, configured to acquire connection reference information, and when it is determined that the connection reference information satisfies a service restriction condition corresponding to the service identifier, establish a connection between the first client and the second client corresponding to the client identifier.

11. The device according to claim 10, characterized in that the connection reference information comprises at least one of the following: position information or time information.

12. The device according to claim 10, characterized in that,
the connection processing module is configured to send contact information of the second client corresponding to the client identifier to the first client, such that the first client establishes, according to the contact information, a connection with the second client.

13. The device according to claim 12, characterized in that,
the connection processing module is specifically configured to send identification information corresponding to the contact information of the second client to the first client, and receive a connection instruction sent by the first client, the connection instruction carrying the identification information; moreover, connect, according to the contact information corresponding to the identification information, the first client with the second client.

14. A connection establishment device, characterized in that the device comprises:
a request sending module, configured to send, to a server, a service connection request, wherein the service connection request comprises: a service identifier and a client identifier of a second client requested for connection;

a connection establishment module, configured to establish, when the server determines that connection reference information satisfies a service restriction condition corresponding to the service identifier, a connection via the server with the second client corresponding to the client identifier.

15. The device according to claim 14, characterized in that the device further comprises:

an information reporting module, configured to send, to the server, the connection reference information or service restriction condition.