



PROCESS FOR THE PRODUCTION OF BISPHENOL A

Technical Field:

This invention relates to a process for the
5 production of high purity bisphenol A.

Background Art

One known method of producing bisphenol A (2,2-
bis(4'-hydroxyphenyl)propane) includes reacting acetone
10 with excess phenol in the presence of a strong acid
catalyst such as a sulfonic acid-type cation ion exchange
resin. The product is generally cooled to form crystals of
an adduct of bisphenol A with phenol (hereinafter referred
to simply as "crystalline adduct"). The crystalline adduct
15 is collected and is then subjected to a phenol removing
treatment to obtain a high purity bisphenol A. The phenol
removing treatment is generally performed by heating a melt
of the adduct to vaporize and separate phenol using, for
example, a distillation tower.

20 It has been found that during the phenol removing
treatment, bisphenol A is thermally decomposed to form
impurities such as phenol and isopropenyl phenol. The
decomposition of bisphenol A proceeds not only in the
phenol removing device but also in a line downstream of the
25 phenol removing device through which bisphenol A separated
is discharged for recovery. It has also been found that it
is difficult to avoid the decomposition of bisphenol A in
the phenol removing step by mere control of the conditions
of the phenol removing step.

30 The present invention has been made in view of the
above problem.

Disclosure of the Invention

The present invention provides a process for the
35 production of bisphenol A, comprising providing a melt of a



crystalline adduct of bisphenol A and phenol which contains a strong acid contaminant, and heating said melt to vaporize and remove phenol from the melt, characterized in that, before said heating, said melt is contacted with a cation donating solid to neutralize the strong acid contaminant therewith.

It has been found that thermal decomposition of bisphenol A during the phenol removing treatment is ascribed to the presence of a strong acid contaminant such as sulfuric acid or sulfonic acid in the crystalline adduct. The strong acid contaminant is considered to be derived from the strong acid catalyst used for the reaction of acetone with phenol.

The amount of the strong acid contaminant in a melt of the crystalline adduct is generally 0.003 meq/liter or less, typically 0.0001-0.001 meq/liter. By contacting the melt with a cation donating solid, such a trace amount of the strong acid contaminant has been found to be effectively neutralized in a stable manner irrespective of variation of the amount of the acid contaminant. With a liquid alkaline substance, it is impossible to neutralize such trace amount of a strong acid in a stable manner.

Examples of cation donating solids include cation exchange resins (such as -COOM type where M is a cation), inorganic ion exchangers (such as silicate (e.g. zeolite or silicalite) substituted by a cation), ceramics (e.g. glass and porcelain) containing an alkali metal oxide (e.g. Na_2O) and/or alkaline earth metal oxide (e.g. CaO), alkali metal compounds and alkaline earth metal compounds or glass fibers. The cation donating solid may be in any desired shape such as powder,

granule (pellet), fiber, plate, porous plate, film, sheet or cylinder.

As the cation, there may be used alkali metal ions, such as sodium ions, potassium ions or lithium ions; 5 alkaline earth metal ions, such as calcium ions or magnesium ions; ammonium ions; and organic ammonium ions derived from organic amines.

The contact of a melt of the crystalline adduct with the cation donating solid may be carried out in any desired 10 method such as a packed tower method in which the melt is passed through a packed tower containing the cation donating solid, a filtration tower method in which the melt is passed through a filtration tower containing a layer of the cation donating solid, a dispersing method in which 15 powder of the cation donating solid is dispersed in the melt, or a immersion method in which a molded body of the cation donating solid is immersed in the melt. Through the contact of the melt with the cation donating solid, the strong acid contaminant in the melt is neutralized by ion 20 exchange reaction with the cation on surfaces of the solid.

The present invention will now be described in more detail below with reference to the accompanying drawing, in which Fig. 1 is a flow chart diagrammatically illustrating a device useful for carrying out the process of the present 25 invention.

Referring to Fig. 1, a feed of a crystalline adduct of bisphenol A and phenol or a feed of phenol containing the crystalline adduct is introduced through a line 11 into a fusing device 1 where the feed is heated at 100-150° C, 30 preferably 120-130° C, to melt or liquify the crystalline adduct and to form a melt (or a liquified adduct).

The melt is then passed through lines 12 and 13 and a pump 2 to a contacting device 3 where the melt is contacted with a cation donating solid contained therein, so that a 35 strong acid contaminant in the melt is neutralized with the

cation donating solid. The thus treated melt is then fed through a line 14 to a phenol removing device 4, such as a distillation tower or a thin film-type evaporator, where the melt is heated at 160-220° C, preferably 180-200° C, to
5 vaporize and separate phenol from the melt. The vaporized phenol is withdrawn overhead from the phenol removing device through a line 15, while the bisphenol A is discharged through a line 16 and a pump 5 and is fed to a succeeding step such as granulation device (not shown)
10 through a line 17.

The following example will further illustrate the present invention.

Example 1

15 Using the device as shown in Fig. 1, bisphenol A was produced from a crystalline adduct. The operation conditions are summarized below.

Line 11:

20 Feed: crystalline adduct in phenol (in the form of slurry); weight ratio of bisphenol A/phenol:
60:40

Line 12:

Temperature of melt: 120° C
25 Concentration of strong acid: 0.001 meq/liter

Contacting device 3:

Cation donating solid: a filter made of a glass fiber containing Na₂O and CaO

Line 14:

30 Temperature of melt: 150° C
Concentration of strong acid: not detected

Line 16:

Temperature of bisphenol A: 190° C
Concentration of phenol: 5-10 ppm by weight
35

Comparative Example 1

Example 1 was repeated in the same manner as described except that the contacting device 3 was not used. Thus, the melt discharged from the fusing device 1 was
5 directly fed to the phenol removing device 4. The results are as follows.

Line 14:

Temperature of melt: 150° C

Concentration of strong acid: 0.001 meq/liter

10 Line 16:

Temperature of bisphenol A: 190° C

Concentration of phenol: 40-50 ppm by weight

Claims

1. A process for the production of bisphenol A, comprising providing a melt of a crystalline adduct of bisphenol A and phenol which contains a strong acid, and heating said melt to vaporize and remove phenol from the melt, characterized in that, before said heating, said melt is contacted with a cation donating solid selected from the group consisting of cation exchange resins, inorganic exchange resins, glass fibers and ceramics, to neutralize the strong acid therewith.
2. A process as claimed in claim 1, wherein said cation donating solid comprises cations selected from alkali metal ions, alkaline earth metal ions, ammonium ions and organic ammonium ions.
3. A process as claimed in claim 1, wherein said cation donating solid is a glass fiber.