

BLADE AND STRUT OF WIND TURBINE FOR VERTICAL-AXIS WIND POWER GENERATOR

BACKGROUND OF THE INVENTION

5 FIELD OF THE INVENTION

[0001] The present invention relates to a shape of blades and struts of a wind turbine for a vertical-axis wind power generator.

DESCRIPTION OF THE BACKGROUND ART

10 [0002] As described on page 74 of "Book On Wind Power Generation" authored by Izumi Ushiyama, a wind turbine does not rotate under a wind speed of approximately 2 m/s or lower unless the width of blades is set to be larger, for example. A wind speed at which a wind turbine starts rotating is called the starting speed or the start speed, and a wind speed at which the wind turbine starts generating power is called the cut-in speed. Due to the destruction of the
15 Fukushima nuclear power station caused by the Tohoku earthquake disaster, the safety of the nuclear power generation has decreased, and it has been desirable to improve the efficiency of a power generator using renewable energy.

Examples of vertical-axis wind turbines are disclosed in Patent Document 1 and the like. The Document discloses a Savonius wind turbine having a simple structure capable of generating
20 high torque at a low rotation speed without sacrificing the advantageous features of the Savonius wind turbine. According to this Savonius wind turbine, the blades have such a structure that each of the blades is curved stepwise in an inverted Z-shape or a Z-shape at a position closer to an outer end of the blade so that a portion closer to the outer end of the blade is relatively shifted toward a concave curved surface receiving wind. According to such a structure, the wind power
25 received by an outer surface of a step plate assists the wind power received by the concave curved surface. As a result, the wind turbine generates high torque at a low rotation speed.

[0003] (Prior Art Documents)
(Patent Documents)

30 Patent Document 1: Japanese Patent No. 5251458

[0004] (Problems to be Solved)

In this Savonius wind turbine, however, one of the two curved blade plates has received force in a reverse direction in relation to a direction of wind, and for this reason, such drag has
35 inevitably reduced the torque or the output power.

SUMMARY OF THE INVENTION

[0005] In view of the above problems, a technical objective of the present invention is to provide a blade having such a shape that the blade effectively operates in a rotation direction by
40 reducing the force acting in a reverse direction from the rotation direction.

The shape (i.e. the external dimension) of a blade, as the most important portion of a wind turbine for a vertical-axis wind power generator, is different depending upon the output

power of the wind power generator; however, the technical objective of the present invention is to focus on the back side (i.e. the back) of the blade unnoticed generally so as to provide a blade having such a shape that can capture a weak breeze.

5 [0006] (Means for Solving Problems)

For solving the above-described problems, there is provided, as a first aspect of the invention, a wind turbine for a wind power generator comprising: a center shaft arranged in a vertical direction; a plurality of horizontal arms attached in a radial manner to the center shaft; and a plurality of blades each arranged on an outer end of each of the plurality of horizontal arms
10 so as to stand in an upright position, the plurality of blades each having a streamlined shape, in horizontal cross-section, including a $45\pm 10\%$ front side and a rear side, of which the rear side defines a convex arc-shaped outer-side surface and a concave arc-shaped center-shaft-side surface in a continuously closed manner, and a blade thickness across the convex arc-shaped outer-side surface and the concave arc-shaped center-shaft-side surface decreases gradually from a full
15 dimension, in a region from a center-shaft-side point of inflection in blade thickness to a rear end of each of the plurality of blades.

[0007] Further, there is provided, as a second aspect of the invention, the wind turbine for the wind power generator as the first aspect of the invention described above, wherein the concave arc-
20 shaped surface has a depressed region located closer to the outer-side surface than a level of a virtual straight line passing virtually through a front end of the streamlined shape and the rear end.

[0008] Still further, there is provided, as a third aspect of the invention, the wind turbine for the wind power generator as the first or second aspect of the invention described above, wherein
25 each of the plurality of blades has: a surface attached with a thin plate in order to reduce a weight; a hollow structure formed therein in order to further reduce the weight; and a spacer member provided therewith for reinforcement.

[0009] Still further, there is provided, as a fourth aspect of the invention, the wind turbine for the wind power generator as the first, second, or third aspect of the invention described above,
30 wherein a plurality of wings each arranged on an outer side with respect to the center-shaft-side point of inflection in blade thickness in such a manner that each of the plurality of wings is openable and closable through a hinge mechanism, or is fixed in an open state.

[0010] Still further, there is provided, as a fifth aspect of the invention, the wind turbine for the wind power generator as any one of the first, second, third, or fourth aspect of the invention described above, wherein each of the plurality of horizontal arms having a shape in vertical cross-
35 section located closer at least to an outer end thereof has: a reinforcement member interposed in a hollow portion of a hollow streamlined shape; an upper surface in convex arc-shape, as a portion of the streamlined shape, at a rear of $60\pm 10\%$ distance from a forehead thereof; and a rearward
40 opening maintained as a result of removing a lower surface.

[0011] Still further, there is provided, as a sixth aspect of the invention, the wind turbine for the wind power generator as the fifth aspect of the invention described above, wherein a plurality of
45 fixed wings each is attached to the lower surface in an open state.

[0012] (Advantageous Effects of the Invention)

According to the first aspect of the invention described above, a plurality of blades are arranged on outer ends of a plurality of horizontal arms attached in a radial manner to a center shaft arranged in a vertical direction in such a manner that each of the plurality of blades stands in an upright position. Each blade has a streamlined shape, in horizontal cross-section, and such a shape includes a $45\pm 10\%$ front side and a rear side, where the rear side of the blade defines a convex arc-shaped outer-side surface and a concave arc-shaped center-shaft-side surface in a continuously closed manner, and where a thickness of the blade across the convex arc-shaped outer-side surface and the concave arc-shaped center-shaft-side surface decreases gradually from a full dimension from a center-shaft-side point of inflection in blade thickness to a rear end. As a result, each of the plurality of blades receives wind effectively on the back thereof so that the plurality of blades can be pushed by the wind. Further, each of the plurality of blades gradually receives wind power on the lateral side thereof when the wind turbine rotates by being pushed by the wind power on the back thereof. Nevertheless, the other blades are pushed in a forward direction by the wind power striking the concave arc-shaped surfaces on the back-side surfaces thereof, and therefore, the wind power acts as a force for causing the wind turbine to rotate.

[0013] According to the second aspect of the invention described above, as illustrated in FIGS. 4 and 5, an inner surface of the concave arc-shaped surface located closer to the center-shaft-side point of inflection in blade thickness than an inner surface at the rear end is depressed closer to the outer-side surface than a virtual straight line virtually passing a front end of the streamlined shape and the rear end of the blade.

[0014] According to the third aspect of the invention described above, the surface of each of the plurality of blades is formed by attaching thereto a thin plate in order to reduce a weight and a hollow structure is formed therein in order to further reduce the weight, and a spacer member is provided therewith for reinforcement. As a result, the wind turbine is strong in spite of the fact that it is light in weight. Further, by virtue of such a light weight, the wind turbine starts rotating at a small wind power (0.8 m/s) and can generate power with a weak breeze.

[0015] According to the fourth aspect of the invention described above, a plurality of wings each arranged on an outer side with respect to the center-shaft-side point of inflection in blade thickness may be operable and closable through a hinge mechanism, or may be fixed in an open state. When the wing is open, a wind pressure reflected from a concave curved surface is added and the resultant wind pressure is received on a larger surface so that the wind pressure can be utilized more effectively. It is possible, therefore, to generate electric power even when the wind is weak.

[0016] According to the fifth aspect of the invention described above, each of the plurality of horizontal arms having a shape in vertical cross-section located closer at least to an outer end thereof has: a reinforcement member interposed in a hollow portion of a hollow streamlined shape; an upper surface in convex arc-shape, as a portion of the streamlined shape, at a rear of $60\pm 10\%$ distance from a forehead thereof; and a rearward opening maintained as a result of removing a lower surface. As a result, the strut (each of the plurality of horizontal arms) also receives wind effectively on the back thereof so that a force of pushing the plurality of blade as a whole by the wind can be improved.

[0017] According to the sixth aspect of the invention described above, a short fixed wing is attached to the lower surface in an open state so that the wind pressure pushing the strut (each of

the plurality of horizontal arms) can be improved, and the rotation of the wind turbine becomes higher in speed and larger in torque.

[0018] In view of the above, a small torque acts in a direction of causing the wind turbine to rotate in a reverse direction while a large torque acts in a direction of causing the wind turbine to rotate in a forward direction. Further, not only the plurality of blades but also the struts (the plurality of horizontal arms) serve as blades. As a result, the wind turbine can generate electric power by receiving a weak wind power.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] For more thorough understanding of the present invention and advantages thereof, the following descriptions should be read in conjunction with the accompanying drawings in which:

FIG. 1 depicts a plan view of a wind turbine as an embodiment according to the present invention.

FIG. 2 depicts an enlarged perspective view of a portion of the wind turbine shown in FIG. 1.

FIG. 3 depicts a plan view showing the wind power received by and the electric power output from the wind turbine shown in FIG. 1.

FIG. 4 depicts a horizontal cross-sectional view showing details of a blade.

FIG. 5 depicts a horizontal cross-sectional view showing a connection portion of the blade.

FIG. 6 depicts a vertical cross-sectional view showing details of a strut.

FIG. 7 depicts a horizontal cross-sectional view showing an opening/closing operation of an opening/closing wing.

FIG. 8 depicts a vertical cross-sectional view of an embodiment having a strut provided with a fixed wing.

DESCRIPTION OF EMBODIMENTS OF THE INVENTION

[0020] Hereinafter, a wind turbine for a wind power generator as an embodiment according to the present invention will be described with reference to the drawings.

A conventional wind turbine (blade) for a wind power generator rotates through the use of any one of drag or lift. As illustrated in FIG. 1, however, a wind turbine (blade) for a vertical-axis wind power generator as an embodiment according to the present invention is characterized in that the wind turbine (blade) uses the force (the force of drag) striking an operation button in a travelling direction of an airflow received by a surface 2 of a blade 1 as well as the vertical force (the force of lift) resulting from a vertical pressure difference occurring therefrom. That is, a concave curved surface 3 smaller in radius than a convex curved surface of the surface 2 is formed on the inner side (i.e. the side closer to the center of rotation of the blade 1).

According to one of the characteristics of an embodiment, a method allowing the drag R and the lift A to be utilized simultaneously is realized by forming the lower sides of the blade and each of the struts 4 illustrated in FIG. 2 so as to form a concave curved surface. In this way, a novel wind turbine (blade) for a vertical-axis wind power generator capable of generating a wind power twice stronger than a wind power generated by one blow of wind.

[0021] In this way, the wind turbine (blade) for a vertical-axis wind power generator as an

embodiment according to the present invention generates drag R on the surface of the wind turbine (blade) to cause the wind turbine (blade) to rotate and generates lift A through the use of the concave curved surface 3 of the blade 1 and the bag-shaped concave curved portion 5 on the lower side of the strut 4 to obtain satisfactory power generation efficiency. That is, it is possible to generate a wind power twice stronger than a wind power generated by one blow of wind and to allow the wind turbine to start rotating with a weak breeze unlike the conventional wind power generator. Therefore, when strong wind with which power can be generated blows, it is possible to start power generation quickly and to obtain satisfactory power generation efficiency.

[0022] Further specifically, according to one of the characteristics of the wind turbine (blade) for a vertical-axis wind power generator as an embodiment, the best position at which the concave curved surface 3 starts being formed on the inner side of the blade 1 is located at a position corresponding to 45% from a forehead portion 21 as illustrated in FIG. 4. A tail portion in which the concave curved surface 3 is formed has a length approximately three times the full thickness of the blade and is a thin wall as illustrated in FIG. 2 when seen from the front.

Further, according to one of the characteristics of the wind turbine (blade) for a vertical-axis wind power generator as an embodiment, the wind turbine (blade) is manufactured by shaping the blade in a hollow pipe shape which is divided into two portions in a front-rear direction from an approximately central portion as illustrated in FIGS. 4 and 5 by a pressing or drawing method through the use of an aluminum alloy (AL-5025) which is light and strong.

[0023] The two front and rear blades (i.e. the forehead portion 21 and the rearward portion 22) shaped in a pipe shape by the pressing method are combined and assembled at the center as illustrated in FIG. 5 and are fixed by rivet screws, whereby the blades are integrated as one blade for the wind turbine as an embodiment according to the present invention.

Since the blade 1 assembled in one piece is heavy (although the weight is different depending on a model), however, a portion of the rearward portion 22 is uniformly bored to form a plurality of holes to reduce the weight. That is, a rearward thin portion 23 is gradually thinned to become solid.

As an operation of blocking the holes in the bored rearward portion 22, it is necessary to block the upper and lower surfaces thereof through the use of aluminum plates 24 and 25 having a thickness of 0.5 mm after the front and rear blades are combined and assembled. Due to this, the front and rear blades originally have steps formed therein.

[0024] When the blade 1 is connected and fixed to a center shaft 6, the blade 1 is supported by being fixed by a horizontal arm 4 called a strut (beam). An embodiment according to the present invention focuses on the horizontal arm 4 which are generally unnoticed to form the horizontal arm 4 in a bag shape 7 that can receive the resistance of air more easily than the concave curved surface 3 on the inner side of the blade 1 as illustrated in FIG. 6. In this way, the airflow (i.e. wind) generated from the blade 1 caused to rotate with the wind received by the surface of the blade 1 due to drag R is received by the blade 1 rotating with the rotary motion of lift A and the strut (beam) 4 as an embodiment according to the present invention so that the wind turbine is pushed from the rear side. In this way, it is possible to obtain a rotary motion more efficiently. The larger the radius of rotation, the stronger the rotation resulting from the pressure that the bag shape 7 receives.

[0025] According to one of the characteristics of the strut (beam) for a vertical-axis wind power generator as an embodiment, since the strut (beam) 4 has a small area [width: 140×45] unlike

the blade 1 [width: 360 × 65], a bag-shaped concave curved portion 5 of the strut (beam) 4 is open widely in a rearward portion and at a position corresponding to 60±10% of a forehead portion so that the strut (beam) 4 can easily receive wind efficiently.

The blade 1 and the strut 4 have a hollow structure in order to reduce the weight and a reinforcement member S is interposed therein to improve the strength. A surface plate exposed the outside air is manufactured by assembling or machining plates.

The concave curved surface 3 on the rear inner side of the blade 1, the first reinforcement member S, and the second reinforcement member S as necessary may be omitted to create the same bag shape as the strut 4.

[0026] An opening/closing wing M having an opening/closing structure as indicated by a chain line may be attached to the outer surface of the blade 1 and the strut 4. As illustrated in FIG. 7, the opening/closing wing M has a planar shape, and a front end thereof is attached to the outer surface at a blade-thickness-changing position of the blade 1 via a hinge H. As illustrated in (1) of FIG. 7, therefore, when the blade 1 rotates facing the wind W, the opening/closing wing M is closed by the wind pressure. However, as illustrated in (2) of FIG. 7, when the blade 1 rotates by 180° and the wind W pushes the concave curved surface 3 at the rear end thereof, the opening/closing wing M is open by being pushed by the wind pressure and the wind pressure is received by the large surface of the opening/closing wing M. It is possible, therefore, to utilize the wind pressure more effectively.

When the blade 1 rotates further and the wind pressure in a direction of closing the opening/closing wing M is received from the front end, the opening/closing wing M is closed and the force in the direction of pushing the blade 1 is minimized.

When the wind is reflected from the concave curved surface 3 of the blade to strike the opening/closing wing M, since the wind acts in the direction of pushing the blade 1 forward, the wind turbine rotates more smoothly. Moreover, since the wind reflected from the concave curved surface 3 is guided to the bag-shaped strut 4 as an embodiment according to the present invention in the position where the opening/closing wing M is not present, the wind contributes to the rotation of the wind turbine.

[0027] The opening/closing wing M attached to the lower surface of the strut 4 of FIG. 6 by the hinge H is open and closed as indicated by a chain line, and both the open state and the closed state are illustrated.

When the opening angle of the opening/closing wing M is set to approximately 30° or smaller, since the opening/closing wing serves as a resistance, it is necessary to provide a stopper so that the opening/closing wing M is not open further than that angle.

In the example of a strut illustrated in FIG. 8, a fixed wing f is integrally fixed thereto in an open state originally. That is, the opening/closing wing M illustrated in FIG. 6 is fixed in an open state. The dimensions are examples.

The opening/closing wing M of the blade 1 illustrated in FIG. 7 may be fixed in an open state rather than fixing the same using the hinge H.

[0028] (Industrial Applicability)

As described above, in the wind turbine (blade) for a vertical-axis wind power generator, the outer surface at the outer end of the wind turbine (blade) has a convex arc shape, the inner surface thereof has a concave arc shape having a smaller radius than the outer surface, and the strut (beam) has a bag shape. The wind turbine (blade) can therefore rotate by capturing wind effectively and can generate power.

Although the shapes of blades and struts do not change greatly depending on a model, the external sizes are different depending on the model.

[0029] (Reference Numerals)			
5	1	Blade	2 Surface
	3	Concave curved surface	4 Strut (Horizontal arm)
	5	Bag-shaped concave curved portion	6 Center shaft
	7	Bag shape	21 Forehead portion
	22	Rearward portion	23 Rearward thin portion
10	24, 25	Aluminum plate	
	M	Opening/closing wing	H Hinge
	F	Fixed wing	R Drag
	A	Lift	W Wind
15	P	Rotating force	S Reinforcement member

WHAT IS CLAIMED IS:

1. A wind turbine for a wind power generator comprising:
 - a center shaft arranged in a vertical direction;
 - 5 a plurality of horizontal arms attached in a radial manner to the center shaft;
 - a plurality of blades each arranged on an outer end of each of the plurality of horizontal arms so as to stand in an upright position, the plurality of blades each having a streamlined shape, in horizontal cross-section, including a front side having a $45\pm 10\%$ length of a total straight length between a front end and a rear end of the streamlined shape and a rear side, of which
 - 10 the rear side defines a convex arc-shaped outer-side surface and a concave arc-shaped center-shaft-side surface in a continuously closed manner, and
 - a blade thickness across the convex arc-shaped outer-side surface and the concave arc-shaped center-shaft-side surface decreases gradually from a full dimension, in a region from a center-shaft-side point of inflection in blade thickness to a
 - 15 rear end of each of the plurality of blades;
 - a plurality of wings each arranged on an outer side with respect to the center-shaft-side point of inflection in blade thickness in such a manner that a rearward-free end thereof is openable and closable through a hinge mechanism, or is fixed in an open state, wherein
 - each of the plurality of horizontal arms, at its outer end, has a vertical cross-section
 - 20 which has a hollow streamlined shape, and having: a reinforcement member interposed in a hollow portion of said hollow streamlined shape; an upper surface with a convex arc-shape, as a portion of the streamlined shape, at a rear side, said convex arc-shape having a $60\pm 10\%$ length of the total straight length from a forehead thereof; and a rearward opening maintained as a result of removing a lower surface.
 - 25
2. The wind turbine for the wind power generator according to claim 1, wherein
 - the concave arc-shaped surface has a depressed region located closer to the outer-side
 - surface than a level of a virtual straight line passing virtually through a front end of the
 - streamlined shape and the rear end.
 - 30
3. The wind turbine for the wind power generator according to claim 1 or 2, wherein
 - each of the plurality of blades has: a surface obtained by attaching a thin plate in order
 - to reduce a weight; a hollow structure formed therein in order to further reduce the weight; and a
 - spacer member provided therewith for reinforcement.
 - 35
4. The wind turbine for the wind power generator according to claim 1, wherein a plurality of fixed wings each is attached to the lower surface in an open state.