



(51) International Patent Classification:
G01R 31/303 (2006.01) **G01R 1/04** (2006.01)

(21) International Application Number:
PCT/US2011/045459

(22) International Filing Date:
27 July 2011 (27.07.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/368,064 27 July 2010 (27.07.2010) US

(71) Applicant (for all designated States except US): **INTEST CORPORATION** [US/US]; Suite 200, 804 East Gate Drive, Mount Laurel, NJ 07054 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WEST, Christopher, Leonard** [US/US]; 141 West Centennial Drive, Medford, NJ 08055 (US). **NAPPEN, Charles, Paul** [US/US]; 36 North Childs Street, Woodbury, NJ 08096 (US).

(74) Agent: **ASHERY, Lawrence, E.**; RatnerPrestia, P.O. Box 980, Valley Forge, PA 19482 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: POSITIONER SYSTEM AND METHOD OF POSITIONING




Figure 6A

(57) Abstract: A system for positioning a load including a support column, a drive rail unit coupled to the support column, the drive rail unit moveable relative to the support column, a vertical carriage moveable along the support column, wherein the vertical carriage supports the load, an engagement member which engages the drive rail and which moves along the drive rail, and a motor which applies force to the engagement member, causing the engagement member to move along the drive rail. The motor is coupled to the vertical carriage so that, as the motor applies force to the engagement member, the vertical carriage moves relative to the drive rail unit, the vertical carriage is also moveable with the drive rail unit so that the vertical carriage and the drive rail unit move relative to the support column. A method of positioning a load is also provided.



Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*