

CLAIMS

What is claimed is:

1. A support holder for a test device, the holder comprising:

a base having a first plurality of sidewalls having a first length and a second plurality of sidewalls having a second length, wherein the second length is greater than the first length, wherein the first plurality of sidewalls and the second plurality of second sidewalls define a cavity in the base, wherein the cavity includes a surface for receiving a portion of the test device; and

a plurality of projections extending away from the base, wherein a first pair of projections of the plurality of projections extends from one sidewall of the second plurality of sidewalls and a second pair of projections of the plurality of projections extends from another sidewall of the second plurality of sidewalls, wherein each projection of the plurality of projections is configured to be associated with a leg portion, and

wherein a first sidewall of the first plurality of sidewalls includes a center notch positioned between a first corner portion and a second corner portion, and wherein a second sidewall of the first plurality of sidewalls includes a removable portion configured to cover an opening into an interior of the base.

2. The support holder of claim 1, wherein the opening extends at least partially through the interior of the base, from the first sidewall of the first plurality of sidewalls to the second sidewall of the first plurality of sidewalls.

3. The support holder of claim 1, wherein each projection of the plurality of projections includes a housing for receiving the leg portion.

4. The support holder of claim 1, wherein the leg portion includes a nonslip material.
5. The support holder of claim 1, wherein the first length of the first plurality of sidewalls ranges from about 20 mm to about 50 mm.
6. The support holder of claim 1, wherein the second length of the second plurality of sidewalls ranges from about 90 mm to about 130 mm.
7. The support holder of claim 1, wherein the sidewalls have a thickness ranging from about 6 mm to about 8 mm.
8. The support holder of claim 1, wherein the sidewalls have a height ranging from about 20 mm to about 30 mm.
9. The support holder of claim 1, wherein the first corner portion and the second corner portion each has a height about 5 mm greater than a height of the second plurality of sidewalls.
10. The support holder of claim 1, wherein the surface includes a cavity in fluid communication with a plurality of air vents.
11. The support holder of claim 1, wherein each projection of the plurality of projections includes a neck portion having a first height, the leg portion having a second

height, wherein the second height is greater than the first height, and the neck portion is disposed between the leg portion and the base.

12. The support holder of claim 1, wherein the center notch has a length ranging from about 15 mm to about 20 mm.

13. A support holder for a test device, the holder comprising:

a base having a first plurality of sidewalls having a first length and a second plurality of sidewalls having a second length, wherein the second length is greater than the first length, wherein the first plurality of sidewalls and the second plurality of second sidewalls define a cavity in the base, wherein the cavity includes a surface for receiving a portion of the test device; and

a plurality of projections extending away from the base, wherein a first pair of projections of the plurality of projections extends from one sidewall of the second plurality of sidewalls and a second pair of projections of the plurality of projections extends from another sidewall of the second plurality of sidewalls, wherein each projection of the plurality of projections is configured to be associated with a leg portion;

wherein each projection of the plurality of projections comprises a housing for receiving the leg portion, a neck portion having a first height, and the leg portion having a second height, wherein the second height is greater than the first height.

14. The support holder of claim 13, wherein a first sidewall of the first plurality of sidewalls includes a center notch positioned between a first corner portion and a second corner portion.

15. The support holder of claim 14, wherein a second sidewall of the first plurality of sidewalls includes a removable portion configured to cover an opening into an interior of the base.

16. The support holder of claim 15, wherein the opening extends at least partially through the interior of the base, from the first sidewall of the first plurality of sidewalls to the second sidewall of the first plurality of sidewalls.

17. The support holder of claim 16, wherein a weighted insert is disposed in the interior of the base.

18. The support holder of claim 13, wherein the first length of the first plurality of sidewalls ranges from about 20 mm to about 50 mm.

19. The support holder of claim 13, wherein the second length of the second plurality of sidewalls ranges from about 90 mm to about 130 mm.

20. The support holder of claim 13, wherein each sidewall of the second plurality of sidewalls includes an air vent.