

DATA PROCESSING METHOD, SYSTEM AND APPARATUS, DEVICE, AND STORAGE MEDIUM

RELATED APPLICATION

[0001] This application claims priority to Chinese Patent Application No. 202210770957.9, filed on June 30, 2022 and entitled "DATA PROCESSING METHOD, SYSTEM, AND APPARATUS, DEVICE, AND STORAGE MEDIUM", which is incorporated herein by reference in its entirety.

FIELD OF THE TECHNOLOGY

[0002] This application relates to the field of computer technologies, and in particular, to a data processing method, system, and apparatus, a device, and a storage medium.

BACKGROUND OF THE DISCLOSURE

[0003] With rapid development of blockchain technologies, the blockchain technologies are widely applied to various services. A node device in a blockchain system can perform processing, for example, hash computation, signature verification, and key verification on data in the blockchain system.

SUMMARY

[0004] Embodiments of this application provide a data processing method, system, and apparatus, a device, and a storage medium.

[0005] According to an aspect, a data processing method is provided, performed by any node device in a blockchain system, a smart contract being stored in the node device; and the method including: obtaining target data, and generating a data processing request corresponding to the target data if a processing manner corresponding to the target data is an off-chain processing manner, the off-chain processing manner referring to a computer device outside the blockchain system performing processing; sending the data processing request to the computer device outside the blockchain system through the smart contract, the smart contract being provided with an interface configured for performing interaction with the computer device outside the blockchain system, and the computer device being provided with a processing resource configured for processing the data for the smart contract; receiving a data processing result obtained by the

computer device based on the data processing request; and performing a consensus procedure on the data processing result, to obtain a first consensus processing result.

[0006] According to another aspect, a data processing method is provided, performed by any computer device outside a blockchain system, the method including: receiving a data processing request that corresponds to target data and that is sent by a target node device through a smart contract, the target node device being any one of a plurality of node devices in the blockchain system, the smart contract being provided with an interface configured for performing interaction with the computer device outside the blockchain system, the computer device being provided with a processing resource configured for processing the data for the smart contract, the data processing request being generated by the target node device if a processing manner corresponding to the target data belongs to an off-chain processing manner, and the off-chain processing manner referring to the computer device outside the blockchain system performing processing; determining a data processing result in response to the data processing request; and sending the data processing result to the target node device, the target node device being configured to receive the data processing result sent by the computer device and perform a consensus procedure on the data processing result, to obtain a first consensus processing result.

[0007] According to another aspect, a data processing system is provided, the data processing system including a plurality of node devices in a blockchain system and a computer device outside the blockchain system, a smart contract being stored in the node devices, the smart contract being provided with an interface configured for performing interaction with the computer device outside the blockchain system, and the computer device being provided with a processing resource configured for processing data for the smart contract; a target node device in the plurality of node devices being configured to obtain target data, and generate a data processing request corresponding to the target data if a processing manner corresponding to the target data belongs to an off-chain processing manner, the off-chain processing manner referring to a computer device outside the blockchain system performing processing; the target node device being further configured to send the data processing request to the computer device through the smart contract; the computer device being configured to determine data processing result in response to the data processing request and return the data processing result to the target node device; the target node device being further configured to receive the data processing result returned by the computer device; and the target node device being further configured to perform a consensus procedure on the data processing result, to obtain a first consensus processing result.

[0008] According to another aspect, a data processing apparatus is provided, applied to any node device in a blockchain system, a smart contract being stored in the node device; and the apparatus including: a request transmitting module, configured to obtain target data, and generate a data processing request corresponding to the target data if a processing manner corresponding to the target data belongs to an off-chain processing manner, the off-chain processing manner referring to a computer device outside the blockchain system performing processing; the request transmitting module being further configured to send the data processing request to the computer device outside the blockchain system through the smart contract, the smart contract being provided with an interface configured for performing interaction with the computer device outside the blockchain system, and the computer device being provided with a processing resource configured for processing the data for the smart contract; a result receiving module, configured to receive a data processing result obtained by the computer device based on the data processing request; and a consensus module, configured to perform a consensus procedure on the data processing result, to obtain a first consensus processing result.

[0009] According to another aspect, a data processing apparatus is provided, applied to any computer device outside a blockchain system, the apparatus including: a request receiving module, configured to receive a data processing request that corresponds to target data and that is sent by a target node device through a smart contract, the target node device being any one of a plurality of node devices in the blockchain system, the smart contract being provided with an interface configured for performing interaction with the computer device outside the blockchain system, the computer device being provided with a processing resource configured for processing the data for the smart contract, the data processing request being generated by the target node device if a processing manner corresponding to the target data belongs to an off-chain processing manner, and the off-chain processing manner referring to the computer device outside the blockchain system performing processing; a processing module, configured to determine a data processing result in response to the data processing request; and a result transmitting module, configured to send the data processing result to the target node device, the target node device being configured to receive the data processing result sent by the computer device and perform a consensus procedure on the data processing result, to obtain a first consensus processing result.

[0010] According to another aspect, a computer device is provided, the computer device including a processor and a memory, at least one computer program being stored in the memory, and the at least one computer program being loaded and executed by the processor, to implement the data processing method according to any one of the foregoing aspects.

[0011] According to another aspect, a computer-readable storage medium is provided, at least one computer program being stored in the computer-readable storage medium, and the at least one computer program being loaded and executed by a processor, to implement the data processing method according to any one of the foregoing aspects.

[0012] According to another aspect, a computer program product is provided, including a computer program, the computer program being loaded and executed by a processor, to implement the data processing method according to any one of the foregoing aspects.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 is a schematic diagram of an implementation environment of a data processing method according to an embodiment of the present disclosure.

[0014] FIG. 2 is a schematic structural diagram of a blockchain system according to an embodiment of the present disclosure.

[0015] FIG. 3 is a schematic diagram of a block structure according to an embodiment of the present disclosure.

[0016] FIG. 4 is a flowchart of a data processing method according to an embodiment of the present disclosure.

[0017] FIG. 5 is a flowchart of another data processing method according to an embodiment of the present disclosure.

[0018] FIG. 6 is a flowchart of another data processing method according to an embodiment of the present disclosure.

[0019] FIG. 7 is a flowchart of another data processing method according to an embodiment of the present disclosure.

[0020] FIG. 8 is a flowchart of another data processing method according to an embodiment of the present disclosure.

[0021] FIG. 9 is a flowchart of another data processing method according to an embodiment of the present disclosure.

[0022] FIG. 10 is a flowchart of another data processing method according to an embodiment of the present disclosure.

[0023] FIG. 11 is a flowchart of another data processing method according to an embodiment of the present disclosure.

[0024] FIG. 12 is a schematic structural diagram of a data processing apparatus according to an embodiment of the present disclosure.

[0025] FIG. 13 is a schematic structural diagram of another data processing apparatus according to an embodiment of the present disclosure.

[0026] FIG. 14 is a schematic structural diagram of another data processing apparatus according to an embodiment of the present disclosure.

[0027] FIG. 15 is a schematic structural diagram of another data processing apparatus according to an embodiment of the present disclosure.

[0028] FIG. 16 is a schematic structural diagram of a terminal according to an embodiment of the present disclosure.

[0029] FIG. 17 is a schematic structural diagram of a server according to an embodiment of the present disclosure.

DESCRIPTION OF EMBODIMENTS

[0030] The terms "first", "second", and the like used in the present disclosure may be used for describing various concepts in this specification. However, the concepts are not limited by the terms unless otherwise specified. The terms are merely used for distinguishing one concept from another concept. For example, a first prediction result may be referred to as a second prediction result, and similarly, the second prediction result may be referred to as the first prediction result.

[0031] At least one may refer to one or more. For example, at least one node device refers to node devices in any integer quantity greater than or equal to one, for example, one node device, two node devices, or three node devices. A plurality of may refer to two or more. For example, a plurality of node devices refer to node devices in any integer quantity greater than or equal to two, for example, two node devices or three node devices. Each may refer to each of at least one. For example, each node device refers to each of a plurality of node devices. If a plurality of node devices are three node devices, each node device refers to each of the three node devices.

[0032] In the embodiments of the present disclosure, related data such as user information is involved. When the foregoing embodiments of this application are applied to a specific product or technology, permission or consent of a user needs to be obtained, and collection, use, and processing of the related data need obey related laws, regulations, and standards of related nations and districts.

[0033] A node device in a blockchain system can perform processing including, for example, hash computation, signature verification, and key verification on data in the blockchain system. However, because the blockchain system bears a large quantity of data processing tasks, data processing pressure is large, and data processing efficiency may be low.

[0034] For ease of understanding the embodiments of this application, the following related terms are explained first:

[0035] 1. Blockchain: A novel application mode of computer technologies such as distributed data storage, peer to peer transmission, a consensus mechanism, and an encryption algorithm. The blockchain generally refers to a decentralized database and is a string of data blocks generated through association by using a cryptographic method. Each data block includes information of a network transaction, the information being configured for verifying the validity of information of the data block (anti-counterfeiting) and generating a next block, and each block including a timestamp and a link to a previous block. In some instances, a blockchain is a chain data structure formed by combining data blocks according to a time sequence in a sequential connection manner, and a non-tamperable and unforgeable distributed ledger ensured in a cryptography manner. For example, once data in the blockchain is recorded, the data is irreversible.

[0036] 2. Smart contract: A contract defined in a binary format, and that may be automatically executed according to clauses of the contract. In the field of blockchain technologies, the smart contract refers to a tamper-proofing and automatically executed computer program triggered by a pre-defined event. Therefore, the smart contract is also considered as a computer protocol aiming to propagate, verify, or execute a contract in an informatization manner. A contract program automatically executed by each node in a blockchain system according to a particular condition performs an operation on data stored on a chain, and is an important path through which a user interacts with a blockchain and implements service logic by using the blockchain. The smart contract aims to provide a secure method superior to a conventional contract and reduce other transaction costs related to the contract. The smart contract permits trusted transactions to be performed without a third party, and these transactions are traceable and irreversible.

[0037] Further, program code and a processing result of smart contract are stored in a node device of the blockchain system in the form of contract data, and the contract data refers to data for describing dynamic processing logic of a transaction. The contract data mentioned herein includes both executable code of the processing logic and an execution result of the processing logic. A contract, also referred to as a smart contract, is a group of commitments defined in the form of

computer code, and parties of the contract are forced to execute the commitments. A contract is also a protocol that participants can execute.

[0038] 3. Oracle machine: A mechanism of writing data outside a blockchain into the blockchain, and can be mainly classified through the following aspects: (1) a source of a data source comes from software, hardware, or people; (2) flow direction of data: from a contract to the external world or from the external world to a contract; and (3) trust: a centralized oracle machine or a non-centralized oracle machine. Oracle machines can be classified into a plurality of types according to the foregoing types. For example, data of an oracle machine comes from an online website. According to the foregoing classification, the data of the oracle machine comes from software, the flow direction of the data of the oracle machine is from the external world to the contract, and the oracle machine is a centralized oracle machine.

[0039] 1) Software oracle machine: The software oracle machine obtains a data source through online software, and the data source may be a database, a service, a website, or network data. For example, real-time flight information is obtained from a network.

[0040] 2) Hardware oracle machine: The hardware oracle machine obtains a data source through a hardware device, the data source may be an electronic sensor, an Internet of Things (IOT) device, a two-dimensional code, a robot, or another information reading device, and the hardware oracle machine plays a crucial role in "translating" information in the real world, so that the information can be understood by a smart contract.

[0041] 3) Human oracle machine: Through persons with specific knowledge or skills, human oracle machines are used as oracle machines, which can convert various information in the real world into formats that a smart contract can understand, and data sources may be the individuals with specific knowledge or skills. A human oracle machine can reply with some determinate data information, and can also reply with some indeterminate information, for example, "whether team A can defeat team B".

[0042] 4) Computation oracle machine: The computation oracle machine is used as an oracle machine through an off-chain specific computation program, a data source is the off-chain specific computation program, and many resources are consumed when some complicated computations are performed on the chain. Therefore, intensive computations are shifted to an off-chain oracle machine, and an on-chain contract obtains a running result of only the computation oracle machine.

[0043] 5) Input or output oracle machine: The input oracle machine converts data in the external world into a smart contract, and the input oracle machine transfers data of the smart contract to the external world. For example, the input oracle machine transfers an ambient temperature obtained by a sensor to a smart contract, and the output oracle machine transfers an on-chain transaction verification result to an external machine to unfasten a smart lock.

[0044] 6) Specific contract oracle machine: The specific contract oracle machine is an oracle machine customized for a smart contract, a data source is a specific oracle machine, and the oracle machine serves only the smart contract, which can satisfy specific data requirements of different smart contracts.

[0045] 7) Consensus oracle machine: The consensus oracle machine obtains a data source through a plurality of parties, and the data source is a result obtained after the plurality of parties reach a consensus. The consensus oracle machine reduces the security risk by adding a participating party.

[0046] 4. Sub-chain expansion solution: Blockchain expansion solutions on a blockchain mainly include a centralized sub-chain expansion solution and a decentralized sub-chain expansion solution based on a zero-knowledge proof. In the centralized sub-chain expansion, a feasible third party packages a transaction proof on a sub-chain and submits the packaged transaction proof to a main chain (block header or the like). In the decentralized sub-chain expansion solution based on a zero-knowledge proof, a proof is generated by performing a zero-knowledge proof algorithm in a process of running a transaction of a sub-chain, and is submitted to a main chain for verification. If the verification succeeds, the transaction of the sub-chain may be anchored to the main chain, to implement a process of authenticating the transaction of the sub-chain by the main chain.

[0047] 5. Consensus mechanism: A blockchain as a data structure for storing data in a time sequence supports different consensus mechanisms. A consensus mechanism is generally an important component of a blockchain technology, and refers to a consensus protocol or a consensus algorithm adopted by a blockchain system. A consensus mechanism of the blockchain aims to enable all honest nodes to store consistent blockchain views, and simultaneously satisfies two properties: A) consistency: prefix parts of blockchains stored in all honest nodes are completely the same; and B) validity: information published by an honest node is finally recorded by all other honest nodes in their own blockchains. When a blockchain system normally runs, some configuration information (or referred to as configuration data) is required, where the configuration information usually includes a consensus protocol version number, a software version number, and configuration information of peer nodes of an underlying communication network.

[0048] FIG. 1 is a schematic diagram of an implementation environment of a data processing method according to an embodiment of the present disclosure. Referring to FIG. 1, the implementation environment includes a plurality of node devices 101 (two node devices are used as an example in FIG. 1) in a blockchain system and a plurality of computer devices 102 (two computer devices are used as an example in FIG. 1) outside the blockchain system. For example, a computer device outside the blockchain system may be an oracle machine device. Any node device 101 in the blockchain system and any computer device 102 outside the blockchain system can perform one or more operations in the data processing method provided in this embodiment of the present disclosure.

[0049] A smart contract is stored in each node device 101. The node device 101 obtains to-be-processed target data through the smart contract, the target data referring to to-be-processed data; generates a data processing request for the target data if off-chain processing needs to be performed on the target data; and sends the data processing request to at least one computer device 102 outside the blockchain system. Each computer device 102 determines a data processing result in response to the data processing request, and returns the data processing result to the smart contract in the node device 101. The node device 101 then performs a consensus procedure on a plurality of received data processing results, to obtain a consensus processing result.

[0050] In one or more arrangements, the node device 101 or the computer device 102 is a server. The server is an independent physical server, or is a server cluster or a distributed system formed by a plurality of physical servers, or is a cloud server that provides a basic cloud computing service such as a cloud service, a cloud database, cloud computing, a cloud function, cloud storage, a network service, cloud communication, a middleware service, a domain name service, a security service, a content delivery network (CDN), big data, and an artificial intelligence platform. In one or more arrangements, the node device 101 or the computer device 102 may be a terminal. The terminal may be a smartphone, a tablet computer, a laptop computer, a desktop computer, or the like.

[0051] FIG. 2 is a schematic structural diagram of a blockchain system according to an embodiment of the present disclosure. The blockchain system includes a plurality of node devices and a terminal, and the terminal is connected to a node device. A peer-to-peer (P2P) network is formed between the node devices. The P2P protocol is an application-layer protocol running over the Transmission Control Protocol (TCP). In the blockchain system, any computing device such as a server or a terminal can join and become a node device. Functions of each node device in the blockchain system include the following: a) Routing: which is a basic function of the node device,

and is used for supporting communication between node devices. In addition to the routing function, the node device further has the following functions: b) Application: which is deployed in a blockchain, and is used for implementing a particular service according to an actual service requirement, recording data related to function implementation to form recorded data, adding a digital signature to the recorded data to indicate a source of task data, and transmitting the recorded data to another node device in the blockchain system, so that the another node device adds the recorded data to a temporary block when successfully verifying a source and integrity of the recorded data.

[0052] FIG. 3 is a schematic diagram of a block structure according to an embodiment of the present disclosure. Each block includes a hash value of a transaction record stored in the current block (a hash value of the current block) and a hash value of a previous block. Blocks are connected according to hash values to form a blockchain. In addition, the block further includes information or data such as a timestamp indicating a block generation time.

[0053] The data processing method provided in the embodiments of the present disclosure may be applied to any scenario where data in a blockchain system needs to be processed. For example, one application may include scenarios where data is encrypted. After obtaining target data, a node device in the blockchain system automatically triggers execution of a smart contract if the target data needs to be encrypted, and sends an encryption request for the target data to a computer device outside the blockchain system in an execution process of the smart contract, and then the computer device encrypts the target data, to obtain an encryption result, and returns the encryption result to the node device. Therefore, if the node device can receive, in the execution process of the smart contract, the encryption result sent by the computer device, the node device performs a consensus procedure on the received encryption result based on a consensus mechanism of the blockchain system, thereby obtaining a consensus encryption result, where the consensus encryption result is used as an encryption result for the target data. In this scenario, the node device transfers an encryption task in the blockchain system out of the blockchain, thereby reducing data processing pressure of the blockchain system, and the performing a consensus on the encryption result of the computer device through the node device can further ensure the accuracy and the confidence level of the final consensus encryption result.

[0054] FIG. 4 is a flowchart of a data processing method according to an embodiment of the present disclosure. This embodiment of the present disclosure is performed by any node device in a blockchain system, and a smart contract is stored in the node device. Referring to FIG. 4, the method includes:

[0055] 401. The node device obtains target data, and generates a data processing request corresponding to the target data if a processing manner corresponding to the target data belongs to an off-chain processing manner.

[0056] The target data refers to to-be-processed data, for example, data sent by another device to the node device, or data submitted by a user of the node device, or data generated when the smart contract performs processing according to service processing logic. After obtaining the target data, the node device determines whether a processing manner corresponding to the target data belongs to an off-chain processing manner. The processing manner corresponding to the target data refers to a manner of processing the target data, and the off-chain processing manner may refer to a computer device outside the blockchain system performing the processing.

[0057] If the processing manner corresponding to the target data belongs to an off-chain processing manner, it indicates that the computer device needs to be requested to process the target data. Therefore, the node device generates a data processing request corresponding to the target data, where the data processing request includes the target data, and the data processing request is configured for requesting processing of the target data.

[0058] In other words, after obtaining to-be-processed data, the node device generates a data processing request for the data if a processing manner of the data belongs to an off-chain processing manner.

[0059] 402. The node device sends the data processing request to a computer device outside the blockchain system through the smart contract.

[0060] The blockchain system includes a plurality of node devices, and the blockchain system is a consortium blockchain system, a public blockchain system, a private blockchain system, or the like. In addition, a computer device further exists outside the blockchain system, and the computer device does not belong to devices in the blockchain system. A smart contract is stored in the node devices in the blockchain system, the smart contract is provided with an interface configured for performing interaction with the computer device outside the blockchain system, that is, can perform information exchange with the computer device in an execution process of the smart contract, and the computer device is provided with a processing resource configured for processing data for the smart contract. For example, the smart contract includes an oracle machine smart contract, and a computer device outside the blockchain is an oracle machine device. The oracle machine smart contract is provided with an interface configured for performing interaction with the oracle machine device, that is, can perform information exchange with the oracle machine device in

an execution process of the oracle machine smart contract, and the oracle machine device is provided with a processing resource configured for processing data for the smart contract.

[0061] The node device sends the data processing request to the computer device outside the blockchain through the smart contract, to request the computer device to process the target data. In one embodiment, the node device broadcasts the data processing request to the computer device outside the blockchain system, and the computer device outside the blockchain system detects, periodically or in real time, the data processing request sent by the node device in the blockchain system.

[0062] In some embodiments, when the specific condition in operation 401 is satisfied, the node device automatically triggers execution of the smart contract, generates the data processing request in an execution process of the smart contract, and sends the data processing request to the computer device.

[0063] 403. The node device receives a data processing result obtained by the computer device based on the data processing request.

[0064] After obtaining the data processing request sent by the node device, the computer device performs processing based on the data processing request, to obtain a data processing result, and returns the data processing result to the smart contract of the node device. Therefore, the node device can receive the data processing result of the computer device. In other words, the node device receives the data processing result returned by the computer device based on the data processing request.

[0065] 404. The node device performs a consensus on the data processing result, to obtain a first consensus processing result.

[0066] After obtaining the data processing result of the computer device, the node device performs a consensus procedure on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result. The consensus processing result is used as a final processing result of the data processing request, and reliability of data processing is ensured by performing a consensus procedure on the data processing result provided outside the blockchain system.

[0067] In some embodiments, a consensus protocol version number adopted by the blockchain system can be queried through configuration data of the blockchain system, a consensus mechanism adopted by the blockchain system can be determined based on the consensus protocol

version number, and then a consensus procedure is performed on the data processing result based on the determined consensus mechanism, to obtain the first consensus processing result.

[0068] The consensus mechanism is generally an important component of the blockchain technology, as the consensus mechanism aims to enable all honest nodes in the blockchain system to store consistent consensus processing results. As such, the consensus mechanism typically needs to satisfy consistency and validity requirements, where consistency refers to prefix parts of blockchains stored in all honest nodes being the same or identical, and where validity refers to information published by a honest node (for example, the first consensus processing result in operation 404) being finally recorded by all other honest nodes in their own blockchains.

[0069] In some embodiments, types of consensus mechanisms include but are not limited to: proof of work (PoW), proof of stake (PoS), delegated proof of stake (DPoS), verification pool (Verify the Pooling), and the like. Types of consensus mechanisms are not specifically limited herein.

[0070] In the method provided in this embodiment of the present disclosure, if off-chain processing needs to be performed on the target data, the node device in the blockchain system requests, through the smart contract, the computer device outside the blockchain system to process the data processing request of the target data, thereby transferring the data processing request from inside of the blockchain system to outside of the blockchain system for processing. This transfer may reduce data processing pressure of the blockchain system, and facilitate improvement in data processing efficiency. In addition, the node device performs a consensus procedure on the data processing result obtained by performing processing by the computer device, to obtain a consensus processing result, thereby reducing risk of error and improving the accuracy and the confidence level of data processing.

[0071] FIG. 5 is a flowchart of another data processing method according to an embodiment of the present disclosure. This embodiment of the present disclosure is performed by any computer device outside a blockchain system. Referring to FIG. 5, the method includes:

[0072] 501. The computer device receives a data processing request that corresponds to target data and that is sent by a target node device through a smart contract, the target node device being any one of a plurality of node devices in the blockchain system.

[0073] The data processing request is generated by the target node device if a processing manner corresponding to the target data belongs to an off-chain processing manner, the off-chain processing manner referring to a computer device outside the blockchain system performing

processing. A smart contract is stored in the node devices in the blockchain system, the smart contract is provided with an interface configured for performing interaction with the computer device outside the blockchain system (e.g., for performing information exchange with the computer device in an execution process of the smart contract), and the computer device is provided with a processing resource configured for processing data for the smart contract. The computer device outside the blockchain system receives the data processing request sent by the target node device through the smart contract, and the data processing request is configured for requesting the computer device to process the data. For a process in which the target node device sends the data processing request to the computer device through the smart contract, refer to the foregoing embodiment shown in FIG. 4. The target node device may refer to any node device in the blockchain system.

[0074] In other words, the computer device receives a data processing request for to-be-processed data sent by a node device in an execution process of a smart contract, the node device being located in the blockchain system, and the data processing request being generated by the node device if a processing manner of the data belongs to an off-chain processing manner.

[0075] In one embodiment, a computer device detects, periodically or in real time, a data processing request sent by each node device in the blockchain system. When the target node device broadcasts the data processing request to a plurality of computer devices, the computer devices can detect the data processing request.

[0076] 502. The computer device determines a data processing result in response to the data processing request.

[0077] The data processing request includes target data, and the target data refers to the to-be-processed data in the node device. The computer device processes the target data in response to the data processing request, to obtain the data processing result. The data processing request is any type of data processing request, and the processing performed on the target data is any type of processing.

[0078] 503. The computer device sends the data processing result to the target node device, the target node device being configured to receive the data processing result sent by the computer device and perform a consensus procedure on the data processing result, to obtain a first consensus processing result.

[0079] The computer device sends the data processing result to the node device, so that the node device receives the data processing result sent by the computer device and performs a

consensus procedure on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

[0080] In the method provided in this embodiment of the present disclosure, if off-chain processing is to be performed on the target data, the node device in the blockchain system requests, through the smart contract, the computer device outside the blockchain system to process the data processing request of the target data, thereby transferring the data processing request from inside of the blockchain system to outside of the blockchain system for processing. This transfer may reduce data processing pressure of the blockchain system, and facilitate improvement in data processing efficiency. In addition, the node device performs a consensus procedure on the data processing result obtained by performing processing by the computer device, to obtain a consensus processing result, thereby reducing the risk of error and improving the accuracy and the confidence level of data processing.

[0081] For details of a process in which the node device determines, based on the foregoing embodiments shown in FIG. 4 and FIG. 5, whether off-chain processing needs to be performed on the target data, refer to the following embodiment shown in FIG. 6.

[0082] FIG. 6 is a flowchart of another data processing method according to an embodiment of the present disclosure. This embodiment of the present disclosure is performed by a node device in a blockchain system and a computer device outside the blockchain system. Referring to FIG. 6, the method includes:

[0083] 601. The node device obtains target data.

[0084] The target data refers to to-be-processed data, for example, data sent by another device to the node device, or data submitted by a user of the node device, or target data generated when the smart contract performs processing according to service processing logic. The source of the target data is not limited in this embodiment of the present disclosure.

[0085] The target data may be any type of data, for example, video data, voice data, picture data, text data, or table data. The type of the target data is not limited in this embodiment of the present disclosure. In one embodiment, the target data is obtained by the node device through the smart contract.

[0086] 602. The node device determines whether a processing manner corresponding to the target data belongs to an off-chain processing manner.

[0087] After obtaining the target data, the node device determines whether a processing manner corresponding to the target data belongs to an off-chain processing manner. The processing

manner corresponding to the target data refers to a manner of processing the target data, and the off-chain processing manner refers to a computer device outside the blockchain system performing the processing. In other words, after obtaining the to-be-processed data, the node device determines whether a processing manner of the data belongs to an off-chain processing manner.

[0088] In one or more arrangements, if property information of the target data satisfies an intensiveness condition, the node device determines that a processing manner corresponding to the target data belongs to an off-chain processing manner. In other words, if property information of data satisfies an intensiveness condition, the node device determines that a processing manner of the data belongs to an off-chain processing manner. The property information of the target data includes at least one of a computation amount, a data volume, a service party to which the target data belongs, or a data type, and the method includes the following aspects.

[0089] (1) The node device determines, if a computation amount of the target data is greater than a first threshold, that the processing manner corresponding to the target data belongs to the off-chain processing manner.

[0090] For example, the node device determines, if a computation amount of the data is greater than a first threshold, that the processing manner of the data belongs to the off-chain processing manner.

[0091] If the computation amount of the target data is greater than the first threshold, it indicates that intensive computation needs to be performed on the target data, and many processing resources are consumed. To reduce data processing pressure of the blockchain system, the target data is subjected to off-chain processing, so that the computer device outside the blockchain system assists the node device in the blockchain system in processing the target data. Therefore, it is determined, if the computation amount of the target data is greater than the first threshold, that the processing manner of the target data belongs to the off-chain processing manner; or it is determined, if the computation amount of the target data is not greater than the first threshold, that the processing manner of the target data does not belong to the off-chain processing manner. The intensive computation refers to computation with a large computation amount. For example, the intensive computation includes hash computation, a signature, signature verification, and a cryptographic algorithm.

[0092] (2) The node device determines, if a data volume of the target data is greater than a second threshold, that the processing manner corresponding to the target data belongs to the off-chain processing manner.

[0093] For example, the node device determines, if a data volume of the data is greater than a second threshold, that the processing manner of the data belongs to the off-chain processing manner.

[0094] If the data volume of the target data is greater than the second threshold, it indicates that many processing resources are needed or consumed to process the target data. To reduce data processing pressure of the blockchain system, the target data is subjected to off-chain processing, so that the computer device outside the blockchain system assists the node device in the blockchain system in processing the target data. Therefore, it is determined, if the data volume of the target data is greater than the second threshold, that the processing manner of the target data belongs to the off-chain processing manner; or it is determined, if the data volume of the target data is not greater than the second threshold, that the processing manner of the target data does not belong to the off-chain processing manner.

[0095] (3) The node device determines, if a service party to which the target data belongs is a target service party, that the processing manner corresponding to the target data belongs to the off-chain processing manner.

[0096] The target service party is also referred to as a designated service party. For example, the node device determines, if a service party to which the data belongs is a designated service party, that the processing manner of the data belongs to the off-chain processing manner.

[0097] In some embodiments, a processing manner of the data is classified according to a service party. For example, if a service party has an off-chain processing requirement, the service party is set as a target service party, thereby setting a processing manner of data of the service party as an off-chain processing manner. If a service party has no off-chain processing requirement, data of the service party is subjected to on-chain processing, and the on-chain processing is processing performed by the node device in the blockchain system. Therefore, it is determined, if a service party to which the target data belongs is a target service party, that the processing manner of the target data belongs to the off-chain processing manner; or it is determined, if a service party to which the target data belongs is not a target service party, that the processing manner of the target data does not belong to the off-chain processing manner.

[0098] (4) The node device determines, if a data type of the target data belongs to a preset data type, that the processing manner corresponding to the target data belongs to the off-chain processing manner.

[0099] For example, the node device determines, if a data type of the data belongs to a preset data type, that the processing manner of the data belongs to the off-chain processing manner.

[00100] In some embodiments, a processing manner of the data is classified according to a data type. The node device flexibly sets a first data type, data of which is subjected to off-chain processing, and a second data type, data of which is subjected to on-chain processing, and determines the first data type (which needs to be subjected to off-chain processing) as a preset data type. Therefore, it is determined, if the data type of the target data belongs to the preset data type, that the processing manner of the target data belongs to the off-chain processing manner; or it is determined, if the data type of the target data does not belong to the preset data type, that the processing manner of the target data does not belong to the off-chain processing manner.

[00101] In another arrangement, the node device invokes a data prediction model, and performs prediction on the target data, to obtain a target prediction result, where the target prediction result is configured for indicating whether the processing manner corresponding to the target data belongs to the off-chain processing manner. In other words, the node device invokes a data prediction model, and performs prediction on the to-be-processed data, to obtain a prediction result, where the prediction result is configured for indicating whether the processing manner of the data belongs to the off-chain processing manner.

[00102] A data prediction model is stored in the node device. For example, the smart contract stored in the node device includes the data prediction model, and the data prediction model is configured for predicting whether a processing manner of the data belongs to an off-chain processing manner. Therefore, the node device inputs the target data to the data prediction model, and the data prediction model performs prediction on the target data, thereby obtaining the target prediction result of the target data. In this embodiment of the present disclosure, the predicting whether a processing manner of the target data belongs to an off-chain processing manner through the data prediction model simplifies processing logic, thereby facilitating improvement in data processing efficiency.

[00103] In one embodiment, a training process of the data prediction model includes the following operation 6021 to operation 6023:

[00104] 6021. Obtain positive sample data, a corresponding first sample label, negative sample data, and a corresponding second sample label according to a historical processing record, where the first sample label indicates that a processing manner of the positive sample data belongs to the off-chain processing manner, and the second sample label indicates that a processing manner of the negative sample data does not belong to the off-chain processing manner.

[00105] The historical processing record is stored in the node device. The historical processing record includes processed historical data and a label corresponding to each piece of historical data, and the label corresponding to the historical data indicates whether a processing manner of the historical data belongs to an off-chain processing manner. Therefore, according to the historical processing record, the positive sample data and the negative sample data are obtained from the historical data, and the first sample label corresponding to the positive sample data and the second sample label corresponding to the negative sample data are obtained. The positive sample data is historical data indicating that a processing manner belongs to an off-chain processing manner, and the negative sample data is historical data indicating that a processing manner does not belong to an off-chain processing manner.

[00106] 6022. Invoke the data prediction model, and separately perform prediction on the positive sample data and the negative sample data, to obtain a first prediction result and a second prediction result.

[00107] The first prediction result indicates whether a processing manner of the positive sample data predicted by the data prediction model belongs to an off-chain processing manner, and the second prediction result indicates whether a processing manner of the negative sample data predicted by the data prediction model belongs to an off-chain processing manner.

[00108] 6023. Train the data prediction model based on the first sample label, the first prediction result, the second sample label, and the second prediction result, to obtain an increased similarity between a first prediction result and the first sample label and an increased similarity between a second prediction result and the second sample label by invoking a trained data prediction model.

[00109] A higher similarity between the first prediction result and the first sample label and a higher similarity between the second prediction result and the second sample label indicate a more accurate result predicted by the data prediction model. Therefore, the data prediction model is trained, to obtain an increased similarity between a first prediction result and the first sample label and an increased similarity between a second prediction result and the second sample label by invoking a trained data prediction model, which can improve the prediction capability of the data prediction model. Such training may enable the data prediction model to learn how to distinguish between data on which off-chain processing needs to be performed and data on which off-chain processing does not need to be performed.

[00110] 603. The node device generates a data processing request corresponding to the target data if a processing manner corresponding to the target data belongs to an off-chain processing manner.

[00111] If the processing manner corresponding to the target data belongs to an off-chain processing manner, it indicates that the computer device needs to be requested to process the target data. Therefore, the node device generates a data processing request corresponding to the target data, where the data processing request includes the target data, and the data processing request is configured for requesting processing of the target data. In other words, the target data refers to to-be-processed data, and the node device generates a data processing request for the data if a processing manner of the data belongs to an off-chain processing manner.

[00112] In one or more arrangements, the node device queries, if a processing manner corresponding to the target data belongs to an off-chain processing manner, a target program identifier corresponding to the processing manner, where the target program identifier indicates a computation program configured for performing processing in the processing manner; and generates a data processing request based on the target data and the target program identifier.

[00113] The data processing request includes the target data and the target program identifier. For example, a processing manner corresponding to the target data is encryption, and a target program identifier corresponding to the processing manner indicates a computation program configured for performing encryption. For example, a processing manner corresponding to the target data is hash computation, and then a target program identifier corresponding to the processing manner indicates a computation program configured for performing hash computation.

[00114] In other words, the node device queries, if the processing manner of the data belongs to the off-chain processing manner, the program identifier of the computation program for providing the processing manner. The program identifier indicates a computation program configured for providing the processing manner, that is, the program identifier indicates a computation program configured for processing the data. Then, the data processing request is generated based on the data and the program identifier. The data processing request includes the data and the program identifier.

[00115] In this embodiment of the present disclosure, the target program identifier is carried in the data processing request, making it convenient for the computer device to subsequently search, according to the target program identifier, for a computation program configured for performing processing on the target data, thereby improving data processing efficiency.

[00116] In one or more aspects, the node device implements the foregoing operation 602 and operation 603 by executing the smart contract.

[00117] 604. The node device sends the data processing request to a computer device outside the blockchain system through the smart contract.

[00118] The smart contract is provided with an interface configured for performing interaction with the computer device outside the blockchain system, and the computer device is provided with a processing resource configured for processing the data for the smart contract.

[00119] In one or more arrangements, the data processing request includes the target data and the target program identifier, and the target program identifier indicates a computation program configured for processing the target data. The node device sends the data processing request to the computer device through the smart contract if the target program identifier is a registered program identifier. In other words, the data processing request including to-be-processed data and a program identifier indicating a computation program configured for processing the data. In this case, after the smart contract is executed, the data processing request is sent to the computer device if the program identifier is registered in an execution process of the smart contract.

[00120] A program identifier corresponding to a computation program that is in the computer device and that is configured for performing processing on data in the node device is registered in the smart contract of the node device, the registered program identifier is stored in the smart contract. Therefore, after obtaining the data processing request, the node device first determines, by querying contract data of the smart contract, whether the target program identifier in the data processing request is a registered program identifier; and sends the data processing request to the computer device if the target program identifier is a registered program identifier, indicating that the computer device can process the data processing request, or does not need to send the data processing request to the computer device if the target program identifier is not a registered program identifier, indicating that the computer device cannot process the data processing request.

[00121] In the foregoing operation 602 to operation 604, description is made using only an example of first determining whether a processing manner belongs to an off-chain processing manner and then generating a data processing request and sending the data processing request to the computer device if the processing manner belongs to an off-chain processing manner. In another embodiment, the node device performs processing directly according to current service processing logic. If a processing manner of the target data belongs to an off-chain processing manner, a processing function of the target data is a request sending interface. Therefore, the node device only needs to directly invoke the request sending interface to generate a data processing request and send

the data processing request to a plurality of computer devices, but does not need to determine whether a processing manner of the target data belongs to an off-chain processing manner.

[00122] 605. The computer device receives the data processing request sent by the node device through the smart contract.

[00123] 606. The computer device determines a data processing result in response to the data processing request.

[00124] The data processing request includes the target data. The computer device processes the target data in response to the data processing request, to obtain the data processing result. The target data refers to to-be-processed data. Therefore, the computer device processes the data in response to the data processing request, to obtain the data processing result.

[00125] In one or more arrangements, the computer device determines the data processing result in response to the data processing request in at least the following three manners.

[00126] (1) The computer device performs, if the data processing request is a hash computation request for the target data, hash computation on the target data in response to the data processing request, to obtain hash data.

[00127] (2) The computer device performs, if the data processing request is a verification request for the target data, verification on the target data in response to the data processing request, to obtain a verification result.

[00128] (3) The computer device performs, if the data processing request is an encryption request for the target data, encryption on the target data in response to the data processing request, to obtain encrypted data.

[00129] In addition, the data processing request can alternatively be another type of processing request, for example, a model training request or a data recovery request. The model training request is configured for requesting to train an artificial intelligence model. The data recovery request is configured for requesting to recover data where an error occurs.

[00130] In one or more arrangements, an external processing interface is stored in the computer device, and the computer device invokes the external processing interface in response to the data processing request, and performs processing on the target data, to obtain the data processing result.

[00131] The external processing interface is provided by another device different from the computer device. The computer device triggers, by invoking the external processing interface, a

device providing the external processing interface to perform processing on the target data in the data processing request, thereby obtaining the data processing result. For example, the external processing interface is provided by a server of a third-party data website, or the external processing interface is provided by a sensor of an Internet of Things device.

[00132] In other application scenarios, functions of the external processing interface are also different. For example, if weather data is expected to be processed, the target data is historical weather data, the data processing request is a weather data prediction request based on the historical weather data, and the external processing interface has a function of predicting future weather data based on the historical weather data.

[00133] 607. The computer device sends the data processing result to the node device.

[00134] In one or more arrangements, the computer device sends the data processing result to the smart contract in the node device.

[00135] 608. The node device receives a data processing result obtained by the computer device based on the data processing request.

[00136] In other words, the node device receives the data processing result returned by the computer device based on the data processing request.

[00137] 609. The node device performs a consensus on the data processing result, to obtain a first consensus processing result.

[00138] After obtaining the data processing result of the computer device, the node device performs a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result. The first consensus processing result is used as a final processing result of the data processing request. After obtaining the first consensus processing result, the node device continues to process the first consensus processing result according to the service processing logic in the blockchain system, for example, by adding the first consensus processing result to the blockchain in the blockchain system.

[00139] In this embodiment of the present disclosure, the computer device performs processing on the data processing request, and the node device performs a consensus procedure on the data processing result based on a consensus mechanism of the blockchain system, to obtain a consensus processing result, thereby reducing the erring risk and the risk of tampering with the data by the computer device, and improving the accuracy and the confidence level of data processing.

[00140] In addition, the smart contract in the node device is provided with an interface configured for performing interaction with a computer device outside the blockchain system, that is,

the smart contract can perform information exchange with the computer device in an execution process, which is equivalent to providing a bridge for connecting the node device in the blockchain system to the computer device outside the blockchain system. Such an interface or bridge may allow data outside the blockchain system to be input to the blockchain system, thereby reducing data processing pressure and execution complexity in the blockchain system, expanding the blockchain system to some extent without adding a new node device to the blockchain system, simplifying the data processing system architecture, and extending functions of the blockchain system.

[00141] According to one or more aspects, the node device implements the foregoing operation 608 and operation 609 by executing the smart contract.

[00142] In the method provided in this embodiment of the present disclosure, if off-chain processing needs to be performed on the target data, the node device in the blockchain system requests, through the smart contract, the computer device outside the blockchain system to process the data processing request of the target data, thereby transferring the data processing request from inside of the blockchain system to outside of the blockchain system for processing. This transfer may reduce data processing pressure of the blockchain system, and facilitate improvement in data processing efficiency. In addition, the node device performs a consensus procedure on the data processing result obtained by performing processing by the computer device, to obtain a consensus processing result, thereby reducing the risk of errors and improving the accuracy and the confidence level of data processing.

[00143] In addition, whether off-chain processing needs to be performed on the data is determined according to the magnitude of a computation amount or a data volume of the data, so that if the computation amount or the data volume of the data is large, the computer device outside the blockchain system is requested to assist the node device in the blockchain system in performing processing on the data, thereby effectively reducing data processing pressure of the blockchain system.

[00144] In addition, whether off-chain processing needs to be performed on the data is determined according to a service party to which the data belongs or a data type, and a processing manner of the data is classified according to a service party or a data type, so that the node device flexibly sets a service party, data of which is subjected to off-chain processing, or a data type, data of which is subjected to off-chain processing, thereby improving data processing flexibility.

[00145] In addition, the predicting whether a processing manner of the target data belongs to an off-chain processing manner through the data prediction model simplifies processing logic of the smart contract, thereby facilitating improvement in data processing efficiency.

[00146] In addition, the target program identifier is carried in the data processing request, making it convenient for the computer device to subsequently search, according to the target program identifier, for a computation program configured for performing processing on the target data, thereby improving data processing efficiency.

[00147] Based on the foregoing embodiment, the smart contract includes a service smart contract and an oracle machine smart contract, and the node device sends the data processing request and receives the data processing result through interaction between the service smart contract and the oracle machine smart contract. For a specific process, refer to the following embodiment shown in FIG. 7.

[00148] FIG. 7 is a flowchart of another data processing method according to an embodiment of the present disclosure. This embodiment of the present disclosure is performed by a node device in a blockchain system and a computer device outside the blockchain system. Referring to FIG. 7, the method includes:

[00149] 701. The node device sends a data processing request to an oracle machine smart contract through a service smart contract.

[00150] The service smart contract is configured for managing data and processing logic in the blockchain system. The oracle machine smart contract is provided with an interface configured for performing interaction with the computer device outside the blockchain system, that is, can perform information exchange with the computer device in an execution process of the oracle machine smart contract, and the computer device is provided with a processing resource configured for processing data for the smart contract. The oracle machine smart contract is configured for connecting the node device in the blockchain system to the computer device outside the blockchain system, and to input data outside the blockchain system to the blockchain system. Both the service smart contract and the oracle machine smart contract are programs run in the node device.

[00151] Therefore, the node device generates, when processing data through the service smart contract, a data processing request for the data, and sends the data processing request to the oracle machine smart contract. For example, the node device automatically triggers execution of the service smart contract if a processing manner of the data is an off-chain processing manner,

generates a data processing request for the data in an execution process of the service smart contract, and sends the data processing request to the oracle machine smart contract.

[00152] A process in which the node device generates the data processing request through the service smart contract is similar to the process of the foregoing operation 601 to operation 603. Details are not described herein again.

[00153] 702. The node device receives the data processing request through the oracle machine smart contract, and sends the data processing request to the computer device.

[00154] A process in which the oracle machine smart contract sends the data processing request to the computer device is that when the service smart contract invokes the oracle machine smart contract, the oracle machine smart contract is executed, the data processing request is received in an execution process of the oracle machine smart contract, and the data processing request is sent to the computer device. The above process is similar to the process of the foregoing operation 604. Details are not described herein again.

[00155] 703. The computer device receives the data processing request sent by the node device through the oracle machine smart contract.

[00156] 704. The computer device determines a data processing result in response to the data processing request.

[00157] 705. The computer device sends the data processing result to the oracle machine smart contract in the node device.

[00158] 706. The node device receives the data processing result through the oracle machine smart contract.

[00159] 707. The node device performs a consensus procedure on the data processing result through the oracle machine smart contract, to obtain a second consensus processing result, and sends the second consensus processing result to the service smart contract.

[00160] If dynamic processing logic of the oracle machine smart contract includes a consensus mechanism for the data processing result, the node device executes the oracle machine smart contract, and performs a consensus procedure on the data processing result based on the consensus mechanism in an execution process of the oracle machine smart contract, to obtain a relatively accurate and reliable second consensus processing result. Alternatively, the node device can obtain a consensus protocol version number adopted by the blockchain system by querying configuration data of the blockchain system, determine a consensus mechanism of the blockchain system based on the consensus protocol version number obtained through query, and then perform a

consensus procedure on the data processing result based on the consensus mechanism, to obtain a second consensus processing result.

[00161] 708. The node device receives the second consensus processing result through the service smart contract, and performs a consensus on the second consensus processing result, to obtain a first consensus processing result.

[00162] If dynamic processing logic of the service smart contract also includes a consensus mechanism for the data processing result, the node device executes the service smart contract, and performs a consensus procedure on the second consensus processing result based on the consensus mechanism in an execution process of the service smart contract, to obtain a more accurate and reliable first consensus processing result. Alternatively, the node device can obtain a consensus protocol version number adopted by the blockchain system by querying configuration data of the blockchain system, determine a consensus mechanism of the blockchain system based on the consensus protocol version number obtained through query, and then perform a consensus procedure on the second consensus processing result based on the consensus mechanism, to obtain a first consensus processing result.

[00163] In some embodiments, types of consensus mechanisms include but are not limited to: proof of work (PoW), proof of stake (PoS), delegated proof of stake (DPoS), verification pool (Verify the Pooling), and the like. Types of consensus mechanisms are not limited herein.

[00164] A process of determining the data processing result and transmitting the data processing result in the foregoing operation 703 to operation 708 is similar to the process in the foregoing operation 605 to operation 609. Details are not described herein again. A difference is interaction between the service smart contract and the oracle machine smart contract.

[00165] In the method provided in this embodiment of the present disclosure, the node device in the blockchain system requests, through the smart contract, the computer device outside the blockchain system to process the data processing request, thereby transferring the data processing request from the inside of the blockchain system to the outside of the blockchain system for processing, reducing data processing pressure of the blockchain system, and facilitating improvement in data processing efficiency. In addition, the node device performs a consensus procedure twice on the data processing result obtained by performing processing by the computer device, to obtain a final consensus processing result, thereby reducing the risk of errors and improving the accuracy and the confidence level of data processing.

[00166] In addition, the oracle machine smart contract in the node device provides a bridge for connecting the node device in the blockchain system to the computer device outside the blockchain system, so that data outside the blockchain system can be input to the blockchain system, thereby extending functions of the blockchain system. In addition, because data processing pressure and execution complexity in the blockchain system are reduced, the blockchain system is expanded to some extent.

[00167] Based on the foregoing embodiment, the computer device outside the blockchain system includes an oracle machine control device and an oracle machine computing device, where the oracle machine control device is configured to manage a request sent by the oracle machine smart contract, and the oracle machine computing device is configured to process the request. For example, the oracle machine computing device is an intensive computing device. Therefore, the data processing result is generated and sent through interaction between the oracle machine control device and the oracle machine computing device. For an example process, refer to the following embodiment shown in FIG. 8.

[00168] FIG. 8 is a flowchart of another data processing method according to an embodiment of the present disclosure. This embodiment of this application is performed by a node device in a blockchain system and a computer device outside the blockchain system. Referring to FIG. 8, the method includes:

[00169] 801. The node device sends a data processing request to an oracle machine control device outside the blockchain system through a smart contract.

[00170] In some embodiments, the node device automatically triggers execution of the smart contract if it is detected that a processing manner of to-be-processed data is an off-chain processing manner, generates the data processing request in an execution process of the smart contract, and sends the data processing request to the oracle machine control device.

[00171] 802. The oracle machine control device receives the data processing request.

[00172] 803. The oracle machine control device sends the data processing request to an oracle machine computing device.

[00173] Each oracle machine control device is connected to at least one oracle machine computing device, and after receiving a data processing request, the oracle machine control device sends the data processing request to one of the at least one oracle machine computing device.

[00174] 804. The oracle machine computing device determines a data processing result in response to the data processing request.

[00175] In one or more arrangements, a plurality of computation programs are stored in the oracle machine computing device, and the data processing request includes target data and a target program identifier. The target program identifier indicates a computation program configured for processing the target data. Therefore, the oracle machine computing device invokes the computation program indicated by the target program identifier in response to the data processing request, and processes the target data, to obtain the data processing result. In other words, a plurality of computation programs are stored in the oracle machine computing device, the data processing request includes to-be-processed data and a program identifier, and the program identifier indicates a computation program configured for processing the data. Therefore, the oracle machine computing device invokes the computation program indicated by the program identifier in response to the data processing request, and processes the data, to obtain the data processing result.

[00176] In addition, a process of determining the data processing result in the operation 804 is similar to the process of determining the data processing result in the foregoing operation 606. Details are not described herein again.

[00177] 805. The oracle machine computing device sends the data processing result to the oracle machine control device.

[00178] 806. The oracle machine control device sends the data processing result to the node device.

[00179] After receiving the data processing result sent by the oracle machine computing device, the oracle machine control device forwards the data processing result to the node device.

[00180] In one or more arrangements, the oracle machine control device converts the data processing result into a target format, where the target format is a format supported by the smart contract, and the oracle machine control device sends the converted data processing result to the smart contract in the node device, so that the smart contract in the node device can perform processing on the data processing result in the target format. In other words, the oracle machine control device converts the data processing result into a format supported by the smart contract, and the oracle machine control device sends the converted data processing result to the smart contract in the node device, so that the smart contract in the node device can perform processing on the data processing result in the format.

[00181] In the foregoing operation 802 to operation 806, description is made only using one oracle machine control device and one oracle machine computing device as an example. In another embodiment, the node device sends a data processing request to a plurality of oracle machine

control devices, and each of the plurality of oracle machine control devices and a corresponding oracle machine computing device perform one or more of the foregoing operation 802 to operation 806.

[00182] 807. The node device receives the data processing result sent by the oracle machine control device.

[00183] 808. The node device performs a consensus on the data processing result, to obtain a first consensus processing result.

[00184] In some embodiments, the node device performs a consensus procedure on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

[00185] The process of operation 807 and operation 808 is similar to the process of the foregoing operation 608 and operation 609. Details are not described herein again.

[00186] In the method provided in this embodiment of the present disclosure, the node device in the blockchain system requests, through the smart contract, the computer device outside the blockchain system to process the data processing request, thereby transferring the data processing request from inside of the blockchain system to outside of the blockchain system for processing, reducing data processing pressure of the blockchain system, and facilitating improvement in data processing efficiency. In addition, the node device performs a consensus procedure on the data processing result obtained by performing processing by the computer device, to obtain a consensus processing result, thereby reducing the risk of errors and improving the accuracy and the confidence level of data processing.

[00187] In the foregoing embodiment, description is made only using an example in which the node device sends the data processing request to a computer device outside the blockchain system through the smart contract. In another embodiment, the node device sends a data processing request to a plurality of computer devices outside the blockchain system through the smart contract, and the plurality of computer devices determine data processing results in response to the data processing request, and return the data processing results to the node device. The node device receives the data processing results returned by the plurality of computer devices, and performs a consensus procedure on the received plurality of data processing results, to obtain a first consensus processing result.

[00188] Because of factors such as different processing capabilities of different computer devices, data processing results obtained by the different computer devices may be the same or

different. For example, if a processing capability of a computer device is stronger or higher, a data processing result obtained by the computer device is more accurate; or if a processing capability of a computer device is weaker or lower, a data processing result obtained by the computer device may be less accurate. If a computer device has a specific security risk, a data processing result obtained by the computer device may be at a low confidence level.

[00189] In this embodiment of the present disclosure, accuracy of a consensus processing result can be improved by performing a consensus procedure on a plurality of data processing results. In addition, when the data processing results of the data processing request are indeterminate results, determinacy of the consensus processing result can be improved by performing a consensus procedure on the plurality of data processing results. For example, if the data processing request is to predict tomorrow's weather condition, a prediction result obtained by a single computer device may be indeterminate, and determinacy of the final obtained prediction result can be improved with a decentralized consensus mechanism.

[00190] In one or more arrangements, dynamic processing logic for a received data processing result can also be provided in the smart contract. For example, the following three manners in which the node device performs a consensus on a plurality of data processing results, to obtain a first consensus processing result are pre-defined in the smart contract.

[00191] (1) A data processing result with a maximum or most number of times of occurrence among the plurality of data processing results is determined as the first consensus processing result. For example, if the data processing results are values, and the plurality of data processing results include 85, 83, 85, 89, and 87, because 85 is a data processing result with a maximum or most number of times of occurrence, 85 is determined as the first consensus processing result.

[00192] (2) A data processing result whose number of times of occurrence reaches a third threshold among the plurality of data processing results is determined as the first consensus processing result. The third threshold is a threshold preset in the smart contract. For example, the third threshold is half or 80% of the quantity of the plurality of computer devices. Assume, for example, that the data processing results are values, the third threshold is 3, and the plurality of data processing results include 85, 83, 85, 85, and 87. Because 85 is a data processing result with the number of times of occurrence reaching 3, 85 is determined as the first consensus processing result.

[00193] (3) Weighted fusion is performed on the plurality of data processing results if the data processing results are values, to obtain the first consensus processing result. For example, the plurality of computer devices correspond to or are assigned respective weights, and the node device performs weighted averaging on data processing results corresponding to the plurality of computer

devices based on the weights corresponding to the plurality of computer devices through the smart contract, to obtain the first consensus processing result.

[00194] In one or more arrangements, the smart contract includes a service smart contract and an oracle machine smart contract. By executing the oracle machine smart contract, the node device performs a consensus procedure on a plurality of data processing results based on the consensus mechanism in the execution process of the oracle machine smart contract, to obtain a second consensus processing result, and sends the second consensus processing result to the service smart contract. By executing the service smart contract, the node device receives the second consensus processing result in the execution process of the service smart contract, and performs a consensus procedure on the second consensus processing result based on the consensus mechanism, to obtain the first consensus processing result. The same consensus mechanism or different consensus mechanisms may be adopted for the foregoing two consensus procedures, which is not specifically limited herein.

[00195] In this embodiment of the present disclosure, the performing a consensus procedure through the oracle machine smart contract refers to performing processing on a plurality of data processing results, for example, performing processing with the foregoing method of (1), (2), or (3), or performing statistics, screening, or fusion in another manner. In this embodiment of the present disclosure, the performing a consensus procedure through the service smart contract refers to performing verification and validation on the second consensus processing result.

[00196] FIG. 9 is a flowchart of another data processing method according to an embodiment of the present disclosure. As shown in FIG. 9, the method includes the following operations.

[00197] 901. A service smart contract sends a data processing request to an oracle machine smart contract.

[00198] In some embodiments, a node device executes the service smart contract, and invokes the oracle machine smart contract in an execution process of the service smart contract, to send the data processing request to the oracle machine smart contract.

[00199] 902. The oracle machine smart contract broadcasts the data processing request, where the data processing request includes to-be-processed target data and a program identifier corresponding to a computation program configured for processing the target data.

[00200] 903. An oracle machine control device receives the data processing request and forwards the data processing request to an oracle machine computing device.

[00201] 904. The oracle machine computing device determines a data processing result in response to the data processing request and returns the data processing result to the oracle machine control device.

[00202] 905. The oracle machine control device returns the data processing result to the oracle machine smart contract.

[00203] In some embodiments, the node device receives, in an execution process of the oracle machine smart contract, the data processing result returned by the oracle machine control device.

[00204] 906. The oracle machine smart contract performs a consensus on a plurality of received data processing results, to obtain a second consensus processing result, and returns the second consensus processing result to the service smart contract, and the service smart contract performs a consensus on the second consensus processing result, to obtain a first consensus processing result.

[00205] In some embodiments, the node device performs a consensus procedure on a plurality of received data processing results based on the consensus mechanism in the execution process of the oracle machine smart contract, to obtain the second consensus processing result, and returns the second consensus processing result to the service smart contract; and performs a consensus procedure on the second consensus processing result based on the consensus mechanism in the execution process of the service smart contract, to obtain the first consensus processing result. In the foregoing manner, an example in which a consensus process requires participation of the service smart contract and the oracle machine smart contract is provided. Alternatively, a consensus process may be implemented by dynamic processing logic of the node device for a data processing result in contract data and completed with the consensus mechanism of the blockchain system, and does not require participation of the service smart contract and the oracle machine smart contract.

[00206] FIG. 10 is a flowchart of another data processing method according to an embodiment of the present disclosure. As shown in FIG. 10, the method includes the following operations.

[00207] 1001. A service smart contract sends a data processing request to an oracle machine smart contract, to request the oracle machine smart contract to perform off-chain processing, where the data processing request carries to-be-processed target data and a program identifier corresponding to a computation program configured for processing the target data.

[00208] In some embodiments, a node device executes the service smart contract, and invokes the oracle machine smart contract in an execution process of the service smart contract, to send the data processing request to the oracle machine smart contract.

[00209] 1002. The oracle machine smart contract broadcasts the data processing request after being invoked, and a plurality of oracle machine control devices outside a blockchain system detect, in real time, the data processing request broadcast by the oracle machine smart contract.

[00210] In some embodiments, after the oracle machine smart contract is invoked, the oracle machine smart contract is executed, and the data processing request is broadcast in an execution process of the oracle machine smart contract.

[00211] 1003. An oracle machine control device sends, after receiving the data processing request, the data processing request to an oracle machine computing device.

[00212] 1004. The oracle machine computing device receives the data processing request sent by the oracle machine control device, selects a computation program indicated by a program identifier in the data processing request, invokes the computation program to perform processing on target data in the data processing request, to obtain a data processing result, and returns the data processing result to the oracle machine control device.

[00213] 1005. The oracle machine control device converts, after receiving the data processing result, the data processing result into a target format supported by the oracle machine smart contract, and sends the converted data processing result to the oracle machine smart contract.

[00214] 1006. The oracle machine smart contract performs a consensus on data processing results returned by the plurality of oracle machine control devices outside the blockchain system, to obtain a consensus processing result, and returns the consensus processing result to the service smart contract.

[00215] In some embodiments, the node device receives, in an execution process of the oracle machine smart contract, data processing results returned by the plurality of oracle machine control devices outside the blockchain system, then performs a consensus procedure on the plurality of received data processing results based on a consensus mechanism, to obtain a consensus processing result, and returns the consensus processing result to the service smart contract.

[00216] 1007. The service smart contract receives the consensus processing result, and continues to execute processing logic of the service smart contract based on the consensus processing result. For example, the service smart contract performs a consensus procedure on the received consensus processing result again, to verify accuracy and reliability of the consensus

processing result. In another example, the service smart contract adds the consensus processing result to a blockchain.

[00217] In some embodiments, the node device receives, in an execution process of the service smart contract, the consensus processing result sent by the oracle machine smart contract, and then performs a consensus procedure on the consensus processing result again based on the consensus mechanism, to verify accuracy and reliability of the consensus processing result; or does not need to perform a consensus procedure again, but directly adds the consensus processing result to a blockchain.

[00218] FIG. 11 is a flowchart of another data processing method according to an embodiment of the present disclosure. As shown in FIG. 11, the method includes the following operations.

[00219] 1101. A service smart contract sends a data processing request to an oracle machine smart contract.

[00220] In some embodiments, a node device executes the service smart contract, and invokes the oracle machine smart contract in an execution process of the service smart contract, to send the data processing request to the oracle machine smart contract.

[00221] 1102. The oracle machine smart contract broadcasts the data processing request to a plurality of computer devices outside a blockchain system, where the data processing request includes to-be-processed target data.

[00222] In some embodiments, after the oracle machine smart contract is invoked, the oracle machine smart contract is executed, and the data processing request is broadcast in an execution process of the oracle machine smart contract.

[00223] 1103. A computer device receives the data processing request and invokes an external processing interface, and the external processing interface triggers a device providing the external processing interface to perform processing on the data processing request, thereby obtaining a data processing result.

[00224] 1104. The external processing interface returns the obtained data processing result to the computer device.

[00225] 1105. The computer device returns the data processing result to the oracle machine smart contract.

[00226] 1106. The oracle machine smart contract performs a consensus procedure on a plurality of received data processing results, to obtain a consensus processing result, and returns the consensus processing result to the service smart contract.

[00227] In some embodiments, the node device receives, in an execution process of the oracle machine smart contract, a plurality of data processing results returned by a plurality of computer devices, then performs a consensus procedure on the plurality of received data processing results based on a consensus mechanism, to obtain a consensus processing result, and returns the consensus processing result to the service smart contract. The service smart contract performs a consensus procedure again, or directly adds the consensus processing result to a blockchain.

[00228] FIG. 12 is a schematic structural diagram of a data processing apparatus according to an embodiment of the present disclosure. Referring to FIG. 12, the apparatus is applied to any node device in a blockchain system, and a smart contract is stored in the node device. The apparatus includes:

[00229] a request transmitting module 1201, configured to obtain to-be-processed data, and generate a data processing request for the data if a processing manner of the data belongs to an off-chain processing manner, where the off-chain processing manner refers to a computer device outside the blockchain system performing the processing;

[00230] the request transmitting module 1201 being further configured to execute the smart contract and send the data processing request to the computer device outside the blockchain system, the smart contract being enabled to perform information exchange with the computer device outside the blockchain system in an execution process, and the computer device being provided with a processing resource configured for processing the data;

[00231] a result receiving module 1202, configured to receive a data processing result returned by the computer device based on the data processing request; and

[00232] a consensus module 1203, configured to perform a consensus procedure on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

[00233] In the data processing apparatus provided in this embodiment of the present disclosure, if off-chain processing needs to be performed on the data, the node device in the blockchain system requests, through the smart contract, the computer device outside the blockchain system to process the data processing request of the data, thereby transferring the data processing request from the inside of the blockchain system to the outside of the blockchain system for

processing, reducing data processing pressure of the blockchain system, and facilitating improvement in data processing efficiency. In addition, the node device performs a consensus procedure on the data processing result obtained by performing processing by the computer device, to obtain a consensus processing result, thereby reducing the risk of errors and improving the accuracy and the confidence level of data processing.

[00234] In one embodiment, referring to FIG. 13, the smart contract includes a service smart contract and an oracle machine smart contract, and the oracle machine smart contract is enabled to perform information exchange with the computer device outside the blockchain system in the execution process; and the request transmitting module 1201 is configured to: sending the data processing request to the oracle machine smart contract in an execution process of the service smart contract; and receiving the data processing request in an execution process of the oracle machine smart contract, and sending the data processing request to the computer device.

[00235] In one embodiment, referring to FIG. 13, the consensus module 1203 includes: a first consensus unit 1213, configured to perform a consensus procedure on the data processing result based on the consensus mechanism in the execution process of the oracle machine smart contract, to obtain a second consensus processing result, and send the second consensus processing result to the service smart contract; and a second consensus unit 1223, configured to receive the second consensus processing result in the execution process of the service smart contract, and perform a consensus procedure on the second consensus processing result based on the consensus mechanism, to obtain the first consensus processing result.

[00236] In one embodiment, referring to FIG. 13, a plurality of computer devices outside the blockchain system are provided, where data processing results received by the node device are data processing results returned by the plurality of computer devices; and the consensus module 1203 is configured to: determine a data processing result with a maximum number of times of occurrence among the plurality of data processing results as the first consensus processing result; or determine a data processing result whose number of times of occurrence reaches a third threshold among the plurality of data processing results as the first consensus processing result; or perform weighted fusion on the plurality of data processing results if the data processing results are values, to obtain the first consensus processing result.

[00237] In one embodiment, referring to FIG. 13, the apparatus further includes: a prediction module 1204, configured to invoke a data prediction model, and performing prediction on the data, to obtain a prediction result, where the prediction result is configured for indicating whether the processing manner of the data belongs to the off-chain processing manner.

[00238] In one embodiment, referring to FIG. 13, the apparatus further includes a training module 1205, and the training module 1205 is configured to: obtaining positive sample data, a first sample label, negative sample data, and a second sample label according to a historical processing record, where the first sample label indicates that a processing manner of the positive sample data belongs to the off-chain processing manner, and the second sample label indicates that a processing manner of the negative sample data does not belong to the off-chain processing manner; invoking the data prediction model, and separately performing prediction on the positive sample data and the negative sample data, to obtain a first prediction result and a second prediction result; and training the data prediction model based on the first sample label, the first prediction result, the second sample label, and the second prediction result, to obtain an increased similarity between a first prediction result and the first sample label and an increased similarity between a second prediction result and the second sample label by invoking a trained data prediction model.

[00239] In one embodiment, referring to FIG. 13, the apparatus further includes a determining module 1206, and the determining module 1206 is configured to: determining, if a computation amount of the data is greater than a first threshold, that the processing manner of the data belongs to the off-chain processing manner; determining, if a data volume of the data is greater than a second threshold, that the processing manner of the data belongs to the off-chain processing manner; determining, if a service party to which the data belongs is a designated service party, that the processing manner of the data belongs to the off-chain processing manner; and determining, if a data type of the data belongs to a preset data type, that the processing manner of the data belongs to the off-chain processing manner.

[00240] In one embodiment, referring to FIG. 13, the request transmitting module 1201 is configured to: query, if the processing manner of the data belongs to the off-chain processing manner, the program identifier of the computation program for providing the processing manner, where the program identifier indicates a computation program configured for processing the data; and generating the data processing request based on the data and the program identifier.

[00241] In one embodiment, referring to FIG. 13, the data processing request includes the data and a program identifier, and the program identifier indicates a computation program configured for processing the data; and the request transmitting module 1201 is configured to execute the smart contract, and send the data processing request to the computer device if the program identifier is registered.

[00242] The data processing apparatus provided in the foregoing embodiments is illustrated with an example division of functionality between the foregoing modules. In actual application, the

functions are allocated to and completed by different functional modules according to various needs or requirements. That is, the internal structure of the node device is divided into different functional modules, to implement all or some of the functions described above. In addition, the data processing apparatus provided in the foregoing embodiment and the data processing methods may correspond to the same aspects and ideas. Example details of specific implementation processes of the data processing apparatus are provided with respect to the methods described herein. Accordingly, details are not described herein again.

[00243] FIG. 14 is a schematic structural diagram of another data processing apparatus according to an embodiment of the present disclosure. Referring to FIG. 14, the apparatus is applied to and/or operates as any computer device outside a blockchain system, and the apparatus includes:

[00244] a request receiving module 1401, configured to receive a data processing request for to-be-processed data sent by a node device in an execution process of a smart contract, the node device being located in the blockchain system, the smart contract being enabled to perform information exchange with a computer device outside the blockchain system in the execution process, the computer device being provided with a processing resource configured for processing the data, the data processing request being generated by the node device if a processing manner of the data belongs to an off-chain processing manner, and the off-chain processing manner meaning that the computer device outside the blockchain system performs processing;

[00245] a processing module 1402, configured to determine a data processing result in response to the data processing request; and

[00246] a result transmitting module 1403, configured to send the data processing result to the node device, the node device being configured to receive the data processing result sent by the computer device and perform a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

[00247] In the data processing apparatus provided in this embodiment of the present disclosure, the node device in the blockchain system requests, through the smart contract, the computer device outside the blockchain system to process the data processing request, thereby transferring the data processing request from the inside of the blockchain system to the outside of the blockchain system for processing, reducing data processing pressure of the blockchain system, and facilitating improvement in data processing efficiency. In addition, the node device performs a consensus on the data processing result obtained by performing processing by the computer device, to obtain a consensus processing result, thereby reducing the risk of errors and improving the accuracy and the confidence level of data processing.

[00248] In one embodiment, referring to FIG. 15, the computer device includes an oracle machine control device and an oracle machine computing device; the request receiving module 1401 in the oracle machine control device is configured to receive the data processing request. The processing module 1402 includes a first sending unit 1412 in the oracle machine control device and a processing unit 1422 in the oracle machine computing device. The first sending unit 1412 is configured to send the data processing request to the oracle machine computing device; and the processing unit 1422 is configured to generate the data processing result in response to the data processing request. The result transmitting module 1403 includes a second sending unit 1413 in the oracle machine computing device and a third sending unit 1423 in the oracle machine control device. The second sending unit 1413 is configured to send the data processing result to the oracle machine control device; and the third sending unit 1423 is configured to send the data processing result to the node device.

[00249] In one embodiment, referring to FIG. 15, the data processing request includes the data and a program identifier, and the program identifier indicates a computation program configured for processing the data; and the processing unit 1422 is configured to invoke the computation program indicated by the program identifier in response to the data processing request, and process the data, to obtain the data processing result.

[00250] In one embodiment, referring to FIG. 15, the third sending unit 1423 is configured to: convert the data processing result into a target format, where the target format is a format supported by the smart contract; and send the converted data processing result to the smart contract in the node device.

[00251] In one embodiment, referring to FIG. 15, an external processing interface is stored in the computer device, and the external processing interface is provided by another device different from the computer device; and the processing module 1402 is configured to invoke the external processing interface in response to the data processing request, and perform processing on the data, to obtain the data processing result.

[00252] In one embodiment, referring to FIG. 15, the processing module 1402 is configured to: performing, if the data processing request is a hash computation request for the data, hash computation on the data in response to the data processing request, to obtain hash data; or perform, if the data processing request is a verification request for the data, verification on the data in response to the data processing request, to obtain a verification result; or perform, if the data processing request is an encryption request for the data, encryption on the data in response to the data processing request, to obtain encrypted data.

[00253] The data processing apparatus provided in the foregoing embodiments is illustrated with an example of division in functionality between the above-described functional modules. In some applications, the functions are allocated to and completed by different functional modules according to requirements. For example, the internal structure of the computer device is divided into different functional modules, to implement all or some of the functions described above. In addition, the data processing apparatus provided in the foregoing embodiment and the data processing method embodiment belong to the same idea and concept. For details of an example specific implementation process of the data processing apparatus, reference may be made to the method embodiment. Details are not described herein again.

[00254] An embodiment of the present disclosure further provides a computer device, the computer device including a processor and a memory, at least one computer program being stored in the memory, and the at least one computer program being loaded and executed by the processor, to implement operations performed in the data processing method in the foregoing embodiments.

[00255] In one embodiment, the computer device is provided as a terminal. FIG. 16 shows a schematic structural diagram of a terminal 1600 according to an exemplary embodiment of the present disclosure. The terminal 1600 includes: a processor 1601 and a memory 1602.

[00256] The processor 1601 includes one or more processing cores, for example, a 4-core processor or an 8-core processor. The processor 1601 is implemented in at least one hardware form of a digital signal processor (DSP), a field-programmable gate array (FPGA), and a programmable logic array (PLA). The processor 1601 alternatively includes a main processor and a coprocessor. The main processor is configured to process data in an active state, also referred to as a central processing unit (CPU). The coprocessor is a low-power processor configured to process data in a standby state. In some embodiments, the processor 1601 is integrated with a graphics processing unit (GPU). The GPU is configured to render and draw content that needs to be displayed on a display screen.

[00257] The memory 1602 includes one or more computer-readable storage media. The computer-readable storage medium is non-transient. The memory 1602 further includes a high-speed random access memory and a non-volatile memory, such as one or more magnetic disk storage devices or flash storage devices. In some embodiments, the non-transitory computer-readable storage medium in the memory 1602 is configured to store at least one computer program, and the at least one computer program is configured to be executed by the processor 1601 to implement the data processing method provided in the method embodiments of the present disclosure.

[00258] In some embodiments, the terminal 1600 includes: a peripheral interface 1603 and at least one peripheral. The processor 1601, the memory 1602, and the peripheral interface 1603 are connected through a bus or a signal cable. Each peripheral is connected to the peripheral interface 1603 through a bus, a signal cable, or a circuit board. In one embodiment, the peripheral includes: at least one of a radio frequency (RF) circuit 1604 or a display screen 1605.

[00259] The peripheral interface 1603 may be configured to connect the at least one peripheral related to input/output (I/O) to the processor 1601 and the memory 1602. In some embodiments, the processor 1601, the memory 1602 and the peripheral interface 1603 are integrated on a same chip or circuit board. In some other embodiments, any one or two of the processor 1601, the memory 1602, and the peripheral interface 1603 are implemented on a single chip or circuit board. This is not limited in this embodiment.

[00260] The RF circuit 1604 is configured to receive and transmit an RF signal, also referred to as an electromagnetic signal. The RF circuit 1604 communicates with a communication network and other communication devices through the electromagnetic signal. The RF circuit 1604 converts an electric signal into an electromagnetic signal for transmission, or converts a received electromagnetic signal into an electric signal. In one embodiment, the RF circuit 1604 includes: an antenna system, an RF transceiver, one or more amplifiers, a tuner, an oscillator, a digital signal processor, a codec chip set, a subscriber identity module card, and the like.

[00261] The display screen 1605 is configured to display a user interface (UI). The UI includes a graph, text, an icon, a video, and any combination thereof. When the display screen 1605 is a touch display screen, the display screen 1605 also has a capability of acquiring a touch signal on or above a surface of the display screen 1605. The touch signal is inputted to the processor 1601 as a control signal for processing.

[00262] The structure shown in FIG. 16 are not limiting to elements of the terminal 1600. For example, the terminal 600 includes more or fewer components than those shown in the figure, or some components are combined, or a different component deployment is used.

[00263] In one embodiment, the computer device is provided as a server. FIG. 17 is a schematic structural diagram of a server according to an embodiment of the present disclosure. The server 1700 may vary due to different configurations or performance or requirements, and may include one or more central processing units (CPUs) 1701 and one or more memories 1702. The memory 1702 stores at least one computer program, the at least one computer program being loaded and executed by the CPU 1701 to implement the method provided in the foregoing method embodiments. The server further includes components such as a wired or wireless network

interface, a keyboard, and an I/O interface, to facilitate I/O. The server further includes other components configured to implement a function of a device. Details are not further described herein.

[00264] An embodiment of the present disclosure further provides a computer-readable storage medium, at least one computer program being stored in the computer-readable storage medium, and the at least one computer program being loaded and executed by a processor, to implement operations performed in the data processing method in the foregoing embodiments.

[00265] An embodiment of the present disclosure further provides a computer program product, including a computer program, the computer program being loaded and executed by a processor, to implement operations performed in the data processing method in the foregoing embodiments. In some embodiments, the computer program involved in this embodiment of this application may be deployed to be executed on a computer device, or deployed to be executed on a plurality of computer devices at the same location, or deployed to be executed on a plurality of computer devices that are distributed in a plurality of locations and interconnected by using a communication network. The plurality of computer devices that are distributed in the plurality of locations and interconnected by using the communication network form a blockchain system.

[00266] All or some of the operations of the embodiments are implemented by hardware or a program instructing related hardware. The program is stored in a computer-readable storage medium. The storage medium is a read-only memory, a magnetic disk, or an optical disc.

[00267] The foregoing descriptions provide optional aspects, and are not intended to limit the embodiments of the present disclosure. Any modification, equivalent replacement, or improvement made within the spirit and principle of the disclosure shall fall within the protection scope of the present disclosure.

CLAIMS

What is claimed is:

1. A data processing method, executable by a node device in a blockchain system, the node device storing a smart contract, the method comprising:

obtaining to-be-processed data;

determining that the to-be-processed data is to be processed in an off-chain processing manner, wherein the off-chain processing manner indicates that a computer device outside the blockchain system performs processing;

generating a data processing request for the data in response to determining that the processing manner of the data is the off-chain processing manner;

executing the smart contract and transmitting the data processing request to the computer device, the smart contract being configured to perform information exchange with the computer device in an execution process, and the computer device being provided with a processing resource configured for processing the data;

receiving a data processing result returned by the computer device based on the data processing request; and

performing a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

2. The method according to claim 1, wherein the smart contract comprises a service smart contract and an oracle machine smart contract, and the oracle machine smart contract is enabled to perform information exchange with the computer device in the execution process; and

the executing the smart contract and transmitting the data processing request to the computer device comprises:

transmitting the data processing request to the oracle machine smart contract in an execution process of the service smart contract; and

receiving the data processing request in an execution process of the oracle machine smart contract, and transmitting the data processing request to the computer device.

3. The method according to claim 2, wherein the performing a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result comprises:

performing a consensus on the data processing result based on the consensus mechanism in the execution process of the oracle machine smart contract, to obtain a second consensus processing result, and transmitting the second consensus processing result to the service smart contract; and

receiving the second consensus processing result in the execution process of the service smart contract, and performing a consensus on the second consensus processing result based on the consensus mechanism, to obtain the first consensus processing result.

4. The method according to any one of claims 1 to 3, wherein the method further comprises:

invoking a data prediction model, and performing prediction on the data, to obtain a prediction result, wherein the prediction result is configured to indicate whether the processing manner of the data is the off-chain processing manner.

5. The method according to claim 4, wherein a training process of the data prediction model comprises:

obtaining positive sample data, a first sample label, negative sample data, and a second sample label according to a historical processing record, wherein the first sample label indicates that a processing manner of the positive sample data is the off-chain processing manner, and the second sample label indicates that a processing manner of the negative sample data is not the off-chain processing manner;

invoking the data prediction model, and separately performing prediction on the positive sample data and the negative sample data, to obtain a first prediction result and a second prediction result; and

training the data prediction model based on the first sample label, the first prediction result, the second sample label, and the second prediction result, to obtain an increased similarity between a first prediction result and the first sample label and an increased similarity between a second prediction result and the second sample label by invoking a trained data prediction model.

6. The method according to any one of claims 1 to 5, wherein the method further comprises at least one of the following:

determining, that the processing manner of the data is the off-chain processing manner, upon determining that a computation amount of the data is greater than a first threshold;

determining that the processing manner of the data is the off-chain processing manner, upon determining that a data volume of the data is greater than a second threshold;

determining that the processing manner of the data is the off-chain processing manner, upon

determining that a service party to which the data belongs is a designated service party; and

determining that the processing manner of the data is the off-chain processing manner, upon determining that a data type of the data belongs to a preset data type.

7. The method according to any one of claims 1 to 6, wherein a plurality of computer devices are provided, and the node device receives data processing results returned by the plurality of computer devices;

the performing a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result comprises:

determining a data processing result with a maximum number of times of occurrence among the plurality of data processing results as the first consensus processing result; or

determining a data processing result whose number of times of occurrence reaches a third threshold among the plurality of data processing results as the first consensus processing result; or

performing weighted fusion on the plurality of data processing results to obtain the first consensus processing result, the data processing results being values.

8. The method according to any one of claims 1 to 7, wherein the data processing request comprises the data and a program identifier, and the program identifier indicates a computation program configured for processing the data; and

the executing the smart contract and transmitting the data processing request to the computer device comprises:

executing the smart contract, and transmitting the data processing request to the computer device after determining that the program identifier is registered.

9. The method according to any one of claims 1 to 8, wherein the generating a data processing request for the data upon determining that processing manner of the data is an off-chain processing manner comprises:

querying the program identifier of the computation program for providing the processing manner; and

generating the data processing request based on the data and the program identifier.

10. A data processing method, executable by a computer device outside a blockchain system, the method comprising:

receiving a data processing request for to-be-processed data transmitted by a node device in an

execution process of a smart contract, the node device being located in the blockchain system, the smart contract being configured to perform information exchange with the computer device in the execution process, the computer device being provided with a processing resource configured for processing the data, the data processing request being generated by the node device if a processing manner of the data is an off-chain processing manner, and the off-chain processing manner indicating that the computer device performs processing;

determining a data processing result in response to the data processing request; and

transmitting the data processing result to the node device, the node device being configured to receive the data processing result transmitted by the computer device and perform a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

11. The method according to claim 10, wherein the computer device comprises an oracle machine control device and an oracle machine computing device;

the receiving a data processing request for to-be-processed data transmitted by a node device in an execution process of a smart contract, the node device being located in the blockchain system comprises:

receiving, by the oracle machine control device, the data processing request;

the determining a data processing result in response to the data processing request comprises:

transmitting, by the oracle machine control device, the data processing request to the oracle machine computing device; and

determining, by the oracle machine computing device, the data processing result in response to the data processing request; and

the transmitting the data processing result to the node device comprises:

transmitting, by the oracle machine computing device, the data processing result to the oracle machine control device; and

transmitting, by the oracle machine control device, the data processing result to the node device.

12. The method according to claim 11, wherein the data processing request comprises the data and a program identifier, and the program identifier indicates a computation program configured for processing the data; and

the determining, by the oracle machine computing device, the data processing result in response to the data processing request comprises:

invoking, by the oracle machine computing device, the computation program indicated by the program identifier in response to the data processing request, and processing the data, to obtain the data processing result.

13. The method according to claim 11 or 12, wherein the transmitting, by the oracle machine control device, the data processing result to the node device comprises:

converting, by the oracle machine control device, the data processing result into a format supported by the smart contract; and

transmitting, by the oracle machine control device, the converted data processing result to the node device.

14. The method according to any one of claims 10 to 13, wherein an external processing interface is stored in the computer device, and the external processing interface is provided by another device different from the computer device; and

the determining a data processing result in response to the data processing request comprises:

invoking the external processing interface in response to the data processing request, and performing processing on the data, to obtain the data processing result.

15. The method according to any one of claims 10 to 14, wherein the determining a data processing result in response to the data processing request comprises:

performing, if the data processing request is a hash computation request for the data, hash computation on the data in response to the data processing request, to obtain hash data; or

performing, if the data processing request is a verification request for the data, verification on the data in response to the data processing request, to obtain a verification result; or

performing, if the data processing request is an encryption request for the data, encryption on the data in response to the data processing request, to obtain encrypted data.

16. A data processing system, the data processing system comprising a plurality of node devices in a blockchain system and a computer device outside the blockchain system, a smart contract being stored in the node devices, the smart contract being configured to perform information exchange with the computer device outside the blockchain system in an execution process, and the computer device being provided with a processing resource configured for processing data;

a node device of the plurality of node devices being configured to obtain to-be-processed data, and generate a data processing request for the data after determining that a processing manner of the data is an off-chain processing manner, the off-chain processing manner indicating that a computer device outside the blockchain system performs processing;

the node device being further configured to execute the smart contract and transmit the data processing request to the computer device;

the computer device being configured to determine a data processing result in response to the data processing request and return the data processing result to the node device;

the node device being further configured to receive the data processing result returned by the computer device; and

the node device being further configured to perform a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

17. A data processing apparatus, located in a blockchain system, a smart contract being stored in the apparatus; and the apparatus comprising:

a request transmitting module, configured to obtain to-be-processed data, and generate a data processing request for the data if a processing manner of the data is an off-chain processing manner, the off-chain processing manner indicating that a computer device outside the blockchain system performs processing;

the request transmitting module being further configured to execute the smart contract and transmit the data processing request to the computer device, the smart contract being configured to perform information exchange with the computer device in an execution process, and the computer device being provided with a processing resource configured for processing the data;

a result receiving module, configured to receive a data processing result returned by the computer device based on the data processing request; and

a consensus module, configured to perform a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

18. A data processing apparatus, located outside a blockchain system, the apparatus comprising:

a request receiving module, configured to receive a data processing request for to-be-processed data transmitted by a node device in an execution process of a smart contract, the node device being

located in the blockchain system, the smart contract being configured to perform information exchange with a computer device outside the blockchain system in the execution process, the computer device being provided with a processing resource configured for processing the data, the data processing request being generated by the node device if a processing manner of the data is an off-chain processing manner, and the off-chain processing manner indicating that the computer device performs processing;

a processing module, configured to determine a data processing result in response to the data processing request; and

a result transmitting module, configured to transmit the data processing result to the node device, the node device being configured to receive the data processing result transmitted by the computer device and perform a consensus on the data processing result based on a consensus mechanism of the blockchain system, to obtain a first consensus processing result.

19. A computer device, the computer device comprising a processor and a memory, at least one computer program being stored in the memory, and the at least one computer program being loaded and executed by the processor, to implement the data processing method according to any one of claims 1 to 9 or implement the data processing method according to any one of claims 10 to 15.

20. A computer-readable storage medium, at least one computer program being stored in the computer-readable storage medium, and the at least one computer program being loaded and executed by a processor, to implement the data processing method according to any one of claims 1 to 9 or implement the data processing method according to any one of claims 10 to 15.

21. A computer program product, comprising a computer program, the computer program being loaded and executed by a processor, to implement the data processing method according to any one of claims 1 to 9 or implement the data processing method according to any one of claims 10 to 15