

HIGH SURFACE AREA HEAT SINK

5

FIELD OF THE INVENTION

[0001] The present invention relates generally to the field of heat sinks, and more particularly to the field of high efficiency heat sinks.

10

BACKGROUND OF THE INVENTION

[0002] As modern electronics evolve, they continue to shrink in size, yet increase in power density, and in the amount of heat they generate during operation. In order for these electronic devices to perform properly, their temperature must be strictly controlled within a given temperature range. Often, designers will attach heat sinks to the electronic devices to dissipate this excess heat. Typically heat sinks include fins or pins to increase the surface area of the heat sink within a constrained space and thus correspondingly increase the heat transfer capacity of the heat sink.

15

SUMMARY OF THE INVENTION

[0003] A heat sink is built including a three dimensional array of cylindrical openings for air to flow through instead of fins. By having a larger surface area than heat sinks with fins, this high surface area heat sink results in increased heat transfer to the surrounding air than a similarly sized heat sink with fins. Heat sinks including an array of cylindrical openings may be manufactured through extrusion, stamping, and other common techniques.

20

25

[0004] Other aspects and advantages of the present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

5

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] Figure 1 is a side view of a typical prior art heat sink.

[0006] Figure 2 is a side view of a high surface area heat sink according to the present invention.

10 **[0007]** Figure 3 is a side view of a high surface area heat sink according to the present invention.

[0008] Figure 4 is a side view of a high surface area heat sink according to the present invention.

[0009] Figure 5A is a side view of a sheet of thermally conductive material for use in manufacturing a high surface area heat sink according to the present invention.

15 **[0010]** Figure 5B is a side view of a pair of molds for use in manufacturing a high surface area heat sink according to the present invention.

[0011] Figure 5C is a side view of the pair of molds from Figure 5B and the thermally conductive material from Figure 5A, during manufacturing of a high surface area heat sink according to the present invention.

20 **[0012]** Figure 6 is a side view of a high surface area heat sink manufactured by the process illustrated in Figures 5A to 5C according to the present invention.

[0013] Figure 7 is a side view of a high surface area heat sink according to the present invention.

25 **[0014]** Figure 8 is a flow chart of a method of constructing a high surface area heat sink according to the present invention.

DETAILED DESCRIPTION

[0015] Figure 1 is a side view of a typical prior art heat sink. In this example of a prior art heat sink, the heat sink includes a heat sink body **100**, a heat sink base **102** that is configured to thermally couple with a heat generating electronic device, along with a plurality of heat sink fins **104**. These fins **104** are used to increase the surface area of the heat sink since the heat transfer capability of the heat sink is proportional to surface area. Often fans are used to flow air through the fins **104**, also increasing heat transfer. When fans are used, the heat sink must be aligned with the flow of air, to allow the air to flow between the fins **104** instead of being blocked by the outer fins **104**.

[0016] Figure 2 is a side view of a high surface area heat sink according to the present invention. In this example embodiment of the present invention, a heat sink is constructed including a heat sink body **200** a heat sink base **202** and an array of cylindrical openings **204** within the heat sink body **200**. Note, that not all cylinders have circular cross-sections, and that those shown in this example embodiment of the present invention have square cross-sections. Other embodiments of the present invention may use cylindrical openings **204** with other shapes of cross-sections, all within the scope of the present invention. By eliminating heat sink fins and instead constructing a heat sink including an array of cylindrical openings **204**, the surface area of the heat sink is increased, resulting in improved heat transfer from the heat sink to the atmosphere. Those of skill in the art will recognize that these heat sinks may be manufactured in a wide variety of methods such as extrusion, milling, or other fabrication techniques within the scope of the present invention. While this example embodiment of the present invention includes an array of cylindrical openings **204**,

those of skill in the art will recognize that there is no need for these openings to form an array. In fact, any plurality of openings in any configuration may suffice to increase the surface area of the heat sink.

[0017] Figure 3 is a side view of a high surface area heat sink according to the present

5 invention. The example embodiment shown in Figure 3 is similar to that of Figure 2 with the exception that the cross-section of the cylindrical columns **304** within the heat sink body **300** is now hexagonal instead of square. This example embodiment of the present invention is a heat sink including a heat sink body **300**, a heat sink base **302** configured to thermally couple to a heat generating electronic device, along with
10 an array of cylindrical openings **304** within the heat sink body **300**. Once again these cylindrical openings **304** act to increase the surface area of the heat sink and thus increase its heat transfer capacity.

[0018] Figure 4 is a side view of a high surface area heat sink according to the present

invention. This example embodiment of the present invention is similar to that of
15 Figure 4 with the exception, that some of the heat sink material on the top and sides of the heat sink body **400** have been removed to reduce weight and slightly increase surface area of the heat sink. This example embodiment of the present invention may be more easily manufactured by extrusion than the example shown in Figure 3. This example embodiment of the present invention is a heat sink including a heat sink body
20 **400**, a heat sink base **402** configured to thermally couple to a heat generating electronic device, along with an array of cylindrical openings **404**. Similar honeycomb material suitable for use as a heat sink body **400** may be found in material used in electro-magnetic interference (EMI) applications. This material may then be mechanically and thermally coupled to a heat sink base **402** to create a high surface
25 area heat sink.

[0019] Figure 5A is a side view of a sheet of thermally conductive material for use in manufacturing a high surface area heat sink according to the present invention.

Figures 5A through 5C demonstrate one possible method of manufacturing a high surface area heat sink according to the present invention. Figure 5A shows a side

5 view of a sheet of thermally conductive material **500** for use in manufacturing a high surface area heat sink. This thermally conductive material **500** may be any of a variety of materials such as aluminum or copper within the scope of the present invention.

[0020] Figure 5B is a side view of a pair of molds for use in manufacturing a high surface

10 area heat sink according to the present invention. A top mold **502** and a bottom mold **504** are configured to stamp material into a shape configured to create cylindrical openings when sheets of stamped material are mechanically and thermally coupled together to form a heat sink body.

[0021] Figure 5C is a side view of the pair of molds from Figure 5B and the thermally

15 conductive material from Figure 5A, during manufacturing of a high surface area heat sink according to the present invention. In this example embodiment of the present invention the top mold **502** and the bottom mold **504** have been brought together to stamp the thermally conductive material **500** into a sheet of stamped material **506**.

This stamped material **506** may then be assembled with other sheets of stamped
20 material **506** to form a high surface area heat sink similar to that of Figure 6.

[0022] Figure 6 is a side view of a high surface area heat sink manufactured by the

process illustrated in Figures 5A to 5C according to the present invention. In this example embodiment of the present invention, a plurality of stamped sheets of

thermally conductive material has been assembled into a high surface area heat sink.

25 Those of skill in the art will recognize that the sheets of stamped material **506** may be

mechanically and thermally coupled using a variety of methods such as soldering or welding. This finished heat sink includes a heat sink body **600**, a heat sink base **602** configured to thermally couple with a heat generating electronic device and includes an array of cylindrical openings **604** in the heat sink **600** resulting in a high surface area heat sink.

[0023] Figure 7 is a side view of a high surface area heat sink according to the present invention. This example embodiment of the present invention is a heat sink including a heat sink body **700**, a heat sink base **702** configured to thermally couple with a heat generating electronic device and includes an array of cylindrical openings **704** resulting in a high surface area heat sink. Also, each of the cylindrical openings **704** includes a slight chamfer **706** on one or both ends of the cylinders. This chamfer helps to funnel the air into the cylindrical openings **704** and reduces turbulence in the air flow at the leading face of the heat sink body **700**. This example embodiment is a simple example of the present invention such as may be used as a prototype constructed by milling a block of thermally conductive material such as aluminum or copper. While this example embodiment of the present invention does have a high surface area, it contains more material than other examples and thus may weigh more, and also be more expensive. However, its construction is quite simple compared to the other example embodiments shown previously, and may be used in situations where ease of construction is critical.

[0024] Figure 8 is a flow chart of a method of constructing a high surface area heat sink according to the present invention. In a step **800**, a heat sink base is provided. In a step **802**, a heat sink body is provided. In a step **804**, a plurality of cylindrical openings is created in the heat sink body. In a step **806**, the heat sink body is thermally and mechanically coupled to the heat sink base.

[0025] The foregoing description of the present invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed, and other modifications and variations may be possible in light of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application to thereby enable others skilled in the art to best utilize the invention in various embodiments and various modifications as are suited to the particular use contemplated. It is intended that the appended claims be construed to include other alternative embodiments of the invention except insofar as limited by the prior art.

CLAIMS

What is claimed is:

1. A heat sink comprising:
a heat sink base; and
a heat sink body mechanically and thermally coupled with said heat sink base,
wherein said heat sink body includes a plurality of cylindrical openings; and
wherein said cylindrical openings include chamfers in at least one face of said heat sink body.
2. A heat sink as recited in claim 1,
wherein plurality of cylindrical openings forms an array.
3. A heat sink as recited in claim 1,
wherein said plurality of cylindrical openings have a circular cross-section.
4. A heat sink as recited in claim 1,
wherein said plurality of cylindrical openings have a hexagonal cross-section.
5. A method for constructing a heat sink comprising the steps of:
 - a) providing a heat sink base;
 - b) providing a heat sink body;

- c) creating a plurality of cylindrical openings in said heat sink body,
wherein said cylindrical openings include chamfers in at least
one face of said heat sink body; and
 - d) mechanically and thermally coupling said heat sink body to said heat
sink base.
- 6. A method for constructing a heat sink as recited in claim 5,
wherein plurality of cylindrical openings forms an array.
- 7. A method for constructing a heat sink as recited in claim 5,
wherein said plurality of cylindrical openings have a circular cross-section.
- 8. A method for constructing a heat sink as recited in claim 5,
wherein said plurality of cylindrical openings have a hexagonal cross-
section.