

Description

The invention relates to a display device comprising a substantially evacuated envelope having mainly flat, substantially parallel front and rear walls, a layer of luminescent material along the inner surface of the front wall and means for generating at least one electron beam which moves substantially in a plane parallel to the front and rear walls and which can be selectively deflected in direction toward the layer of luminescent material via first deflection means in a deflection unit, so that each beam scans at least a part of the layer of luminescent material, said means for generating at least one electron beam comprising at least one cathode unit having at least one cathode which can be controlled separately.

The invention also relates to a cathode unit for use in a display device of the type described.

A display device of this type has great advantages because it provides the possibility of realizing thin flat television screens. Research is being done into constructions of such types that the thick glass walls, which are often necessary in connection with the high vacuum, can be avoided as much as possible. Other points of research aim at obtaining a uniform brightness throughout the picture surface, independent of driven pixel and the possibility of integration with control electronics.

A display device of the type described in the opening paragraph is known from Netherlands Patent Application No. 7610521 laid open to public inspection.

In this device electron beams are guided through channels and subsequently they are not only deflected to the phosphor screen, but the beams also perform a scanning movement in the transverse direction of the channel. The latter is effected to simplify the electron gun for such a device. In this case either a source for one beam or a line cathode arranged on or along the end wall of the channels, respectively, is used.

The dimensions of conventional cathodes are such that generated electron beams of two cathodes located at a minimum distance from each other enclose a plurality of pixel columns, thus requiring a horizontal deflection over a plurality of pixels. Moreover, the energy supplied is so high that the solution proposed in the above-cited Patent Application is extremely costly on grounds of energy considerations and extra material costs (horizontal deflection electrodes in the channels).

The use of semiconductor cathodes in different display devices has already been proposed, notably in the Netherlands Patent Application No. 7905470 in the name of the Applicant. However, such cathodes have the drawback that, although they amply meet the requirements imposed on

dimensions for use in a device in accordance with NL 7610521, their efficiency rapidly deteriorates due to an ion bombardment caused by positive ions which are created notably in the high voltage-section of the device.

To prevent this, a display device according to the invention is characterized in that the cathode unit comprises second deflection means for horizontal deflection of the electron beam over at least a part of the width of the layer of luminescent material and in that a row of electron multipliers is arranged in the beam path between the cathode and the deflection unit.

The cathode is preferably a semiconductor cathode in which the main surface of the semiconductor body is preferably substantially perpendicular to the plane in which the electron beams move.

In this case it is not absolutely necessary for the emissive surface to coincide with the main surface of the semiconductor body. For example, the cathode may be in the form of one or more punctiform emitters as described in the Netherlands Patent Application NL 7905470 laid open to public inspection.

The invention is based on the recognition that the assembly of cathode, deflection means and electron multipliers functions, as it were, as an ion trap due to the deflection of the electron beam between the cathode and the electron multipliers.

This ensures a longer lifetime of the cathode. This improvement is all the more effective as the total number of required (semiconductor) cathodes in the entire display device can be reduced, for example, by increasing the number of columns driven by one cathode.

Since horizontal deflection takes place prematurely, the channels as described in the Netherlands Patent Application 7610521 laid open to public inspection can be dispensed with.

However, deviations due to the earth's magnetic field which are largely corrected in conventional tubes by means of electron-optical systems must now be avoided in a different way.

To this end the plane within which the electron beams move parallel to the front and rear walls is substantially entirely surrounded by a magnetic shield whose outer cladding may also function as a high-voltage electrode.

There are various possibilities for the display after the deflection of the electron beam from the plane parallel to the front and rear walls.

For example, the so-called penetration principle may be chosen (for example, in the case of two colours), by which the voltage at the front wall is varied dependent on the colour to be displayed. The so-called index principle may be used alternatively.

However, the display device preferably comprises a shadow mask (which may be provided, if necessary, with deflection electrodes). The shadow mask may form part of the above-mentioned magnetic shield unit. For the display of a picture two (monochrome) or six (colour) line memories are required in this case for displaying the previous picture or storing the next (sub-)picture.

A light valve may also be arranged in front of the front wall, for example, a liquid crystal device successively passing the red, green and blue sub-pictures. In this case the device should be provided with picture memories.

A cathode unit according to the invention comprises at least one cathode, deflection means for one or more electron beams and a row of electron multipliers.

The invention will now be described in greater detail, by way of example, with reference to the accompanying drawing in which

Fig. 1 is a diagrammatic cross-section of a display device according to the invention,

Fig. 2 is a cross-section along a part of the device of Fig. 1, perpendicular to the cross-section shown in Fig. 1,

Fig. 3 is a cross-section of a separate cathode unit.

The drawings are diagrammatic and not to scale; corresponding components usually have the same reference numerals.

Fig. 1 is a diagrammatic cross-section of a display device 1 according to the invention, comprising a substantially evacuated envelope having a front wall 3 and a rear wall 4. Together with the side walls 6, the front wall 3 forms part of a glass lid or tub having an overall height of, for example, 5 cm, whilst the rear wall 4 in this embodiment is in the form of a thin steel wall which may have reinforcement ribs, if necessary. A layer of luminescent material, for example, a phosphor screen 5 is present on the inside of the front wall 3.

The display device 1 also comprises means for generating a plurality of electron beams 14 which move at least substantially in a plane parallel to the front wall 3 and the rear wall 4 before they are deflected in the direction of the phosphor screen 5. The electron beams move not only parallel to the front wall 3 and the rear wall 4 but also substantially perpendicular to the picture lines of the picture to be displayed, because horizontal deflection is effected in the cathode unit 31 before the electron beams reach the deflection unit which is bounded by the walls 3, 4 and the end walls 16, 17. The phosphor parts to be impinged on (in other words, the picture line to be activated) are selected via voltages at deflection electrodes 7 arranged on an insulated carrier 8 in this embodiment. The electron beams 14 are thereby deflected to the phosphor

screen 5.

The electrons are generated by means of semiconductor cathodes 10, which may be controlled separately, and they are subsequently accelerated by electrodes 24, thereby forming electron beams 14, whilst the emissive surface 12 extends perpendicularly to the walls 3, 4 in this embodiment. The electron beams 14 are deflected by means of deflection electrodes 15 directly after the formation of the beam.

According to the invention a row of electron multipliers 20 is arranged between the deflection electrodes 15 and the high-voltage section 21 in which the deflection towards the phosphor screen 5 takes place. Subsequently the electron beam 14 (intensified by the operation of the electron multiplier) moves substantially parallel to the front wall 3 and the rear wall 4 and also perpendicularly to the end walls 16, 17.

The electron multipliers 20 have a dual function. On the one hand electron multiplication is effected so that a picture of greater intensity can be obtained. On the other hand possible positive ions, which are generated by the electrons in the high-voltage section 21 and accelerated by the dominant field in the direction of the cathode unit, are captured by the electron multipliers 20 so that they cannot damage the cathode 10.

In the device as shown in Figs. 1 and 2 the deviation which the beams 14 may acquire with the aid of the deflection electrodes 15 is chosen to be such that each cathode covers, for example, n columns. The cathode unit 31 is thus seemingly split up into a plurality of sub-units denoted by means of broken lines 23. The deflection electrode 15 and the cathodes 10 are now controlled by means of periodical deflection voltages at the deflection electrodes 15 and information from a line register 41 in such a manner that the information associated with the relevant line is presented to the columns 1, $n+1$, $2n+1$... at instant t_1 ; to the columns i , $n+i$, $2n+i$ at instant t_i ($1 < i < n$), and to the columns n , $2n$, $3n$, ..., $2n \dots$ at instant t_n . After the information of the next line to be written is written in the line register 41 and the control of the line electrodes 7 (for example, via a switching element not shown) has been adapted, this procedure is repeated. For electrical connections of the cathodes and other elements the walls 6 have lead-throughs 26 with which possible acceleration electrodes 24 can be controlled and with which the voltage for the electron multiplier is ensured, for example, via contact conductors 25.

The electron beams 14 from the cathodes 10, deflected by the electrodes 15 and intensified in the electron multipliers 20, are subsequently accelerated parallel to the front and rear walls before they reach the actual display section 9. These

electrons may exhibit deviations from their straight path under the influence of the earth's magnetic field, whilst a lateral correction is not possible. For this reason the plane within which the electrons are accelerated and move parallel to the front and rear walls is substantially entirely surrounded by a magnetic shield, formed in this embodiment from a cage-like construction comprising, for example, the carrier 8 for the electrodes 7 whose lower side is to this end provided with a metal layer or metal pattern 18, whilst the device comprises an electrically conducting bush connected thereto having a first wall 16 (also high-voltage grid) and an end wall 17, the assembly being magnetically closed by the shadow mask 19. Other, more open constructions are alternatively possible in which, as in this embodiment, generally known methods of demagnetizing can be used, if necessary. The electrodes 7 can be controlled via control circuits (not shown) which are also arranged, for example, on the carrier 8 and are contacted by means of metal tracks (not shown) projecting outside the side wall 6.

The vacuum space can be built in a protective cabinet 22 leaving free the visible part of the picture and accommodating operating elements as well as control circuit elements 41, 42 arranged on, for example, a printed circuit board 40.

As already described in the opening paragraph, there are various possibilities for the display of the picture after the electron beam 14 has been deflected towards the phosphor screen 5. For example, in the case of colour display the penetration principle may be used, notably when using display tubes with at most two colours, or the so-called index principle may be used.

In the device shown the phosphor screen 5 is split up, for example, into horizontal tracks of luminescent material. The information for each of the three colours is presented during 1/3 of the line period, whereafter the voltages at the deflection electrodes are slightly changed and the information for the adjacent colour track is presented during 1/3 of the line period, etc. Since the (colour) information is simultaneously read in the case of TV display and is then presented serially in accordance with the incoming signal, the colour information is temporarily stored in line memories. Each colour to be displayed requires two line memories, namely one for the line which is being read and a second in which the next line is stored.

Another possibility is the use of so-called light valves in which a monochrome tube is controlled each time during 1/3 of the picture period with the red, the green and the blue picture signal, respectively, whilst light valves, for example, LCDs with red, green or blue colour filters arranged in front of the tube are synchronously switched on. In this case the presence of picture memories is required.

In the device of Fig. 2 the cathodes 10 are secured to a side wall 6 of the envelope 2 of the vacuum space. The cathode unit 31, with cathodes 10, acceleration electrodes 24, deflection electrodes 15 and electron multipliers 20 may of course also be manufactured separately in a glass envelope 11 which is secured to the end of the vacuum space at a later stage of manufacture.

The sub-units denoted by the broken lines 23 may also be manufactured separately as shown in Fig. 3, and may subsequently be secured next to one another. This has the advantage that the separate units can be individually tested and replaced, if necessary. The number of electron multipliers in the device of Fig. 3 may of course also be extended in such a way that all columns of the picture can be covered by means of one cathode 10. If necessary, a thermal cathode instead of a semiconductor cathode may of course be used alternatively.

Claims

1. A display device (1) comprising a substantially evacuated envelope having mainly flat, substantially parallel front (3) and rear walls (4), a layer of luminescent material (5) along the inner surface of the front wall and means (31) for generating at least one electron beam (14) which moves substantially in a plane parallel to the front (3) and rear walls (4) and which can be selectively deflected in the direction toward the layer of luminescent material (5) via first deflection means (7) in a deflection unit (21), so that each beam scans at least a part of the layer of luminescent material (5), said means for generating at least one electron beam comprising at least one cathode unit (31) having at least one cathode (10) which can be controlled separately, characterized in that the cathode unit (31) comprises second deflection means (15) for horizontal deflection of the electron beam over at least a part of the width of the layer of luminescent material and in that a row of electron multipliers (20) is arranged in the beam path between the cathode (10) and the deflection unit (21).
2. A display device as claimed in Claim 1, characterized in that the cathode unit (31) comprises a semiconductor cathode (10).
3. A display device as claimed in Claim 2, characterized in that the main surface (12) of the semiconductor cathode body extends substantially perpendicular to the plane in which the electron beams (14) move.



electrons may exhibit deviations from their straight path under the influence of the earth's magnetic field, whilst a lateral correction is not possible. For this reason the plane within which the electrons are accelerated and move parallel to the front and rear walls is substantially entirely surrounded by a magnetic shield, formed in this embodiment from a cage-like construction comprising, for example, the carrier 8 for the electrodes 7 whose lower side is to this end provided with a metal layer or metal pattern 18, whilst the device comprises an electrically conducting bush connected thereto having a first wall 16 (also high-voltage grid) and an end wall 17, the assembly being magnetically closed by the shadow mask 19. Other, more open constructions are alternatively possible in which, as in this embodiment, generally known methods of demagnetizing can be used, if necessary. The electrodes 7 can be controlled via control circuits (not shown) which are also arranged, for example, on the carrier 8 and are contacted by means of metal tracks (not shown) projecting outside the side wall 6.

The vacuum space can be built in a protective cabinet 22 leaving free the visible part of the picture and accommodating operating elements as well as control circuit elements 41, 42 arranged on, for example, a printed circuit board 40.

As already described in the opening paragraph, there are various possibilities for the display of the picture after the electron beam 14 has been deflected towards the phosphor screen 5. For example, in the case of colour display the penetration principle may be used, notably when using display tubes with at most two colours, or the so-called index principle may be used.

In the device shown the phosphor screen 5 is split up, for example, into horizontal tracks of luminescent material. The information for each of the three colours is presented during 1/3 of the line period, whereafter the voltages at the deflection electrodes are slightly changed and the information for the adjacent colour track is presented during 1/3 of the line period, etc. Since the (colour) information is simultaneously read in the case of TV display and is then presented serially in accordance with the incoming signal, the colour information is temporarily stored in line memories. Each colour to be displayed requires two line memories, namely one for the line which is being read and a second in which the next line is stored.

Another possibility is the use of so-called light valves in which a monochrome tube is controlled each time during 1/3 of the picture period with the red, the green and the blue picture signal, respectively, whilst light valves, for example, LCDs with red, green or blue colour filters arranged in front of the tube are synchronously switched on. In this case the presence of picture memories is required.

In the device of Fig. 2 the cathodes 10 are secured to a side wall 6 of the envelope 2 of the vacuum space. The cathode unit 31, with cathodes 10, acceleration electrodes 24, deflection electrodes 15 and electron multipliers 20 may of course also be manufactured separately in a glass envelope 11 which is secured to the end of the vacuum space at a later stage of manufacture.

The sub-units denoted by the broken lines 23 may also be manufactured separately as shown in Fig. 3, and may subsequently be secured next to one another. This has the advantage that the separate units can be individually tested and replaced, if necessary. The number of electron multipliers in the device of Fig. 3 may of course also be extended in such a way that all columns of the picture can be covered by means of one cathode 10. If necessary, a thermal cathode instead of a semiconductor cathode may of course be used alternatively.

Claims

1. A display device (1) comprising a substantially evacuated envelope having mainly flat, substantially parallel front (3) and rear walls (4), a layer of luminescent material (5) along the inner surface of the front wall and means (31) for generating at least one electron beam (14) which moves substantially in a plane parallel to the front (3) and rear walls (4) and which can be selectively deflected in the direction toward the layer of luminescent material (5) via first deflection means (7) in a deflection unit (21), so that each beam scans at least a part of the layer of luminescent material (5), said means for generating at least one electron beam comprising at least one cathode unit (31) having at least one cathode (10) which can be controlled separately, characterized in that the cathode unit (31) comprises second deflection means (15) for horizontal deflection of the electron beam over at least a part of the width of the layer of luminescent material and in that a row of electron multipliers (20) is arranged in the beam path between the cathode (10) and the deflection unit (21).
2. A display device as claimed in Claim 1, characterized in that the cathode unit (31) comprises a semiconductor cathode (10).
3. A display device as claimed in Claim 2, characterized in that the main surface (12) of the semiconductor cathode body extends substantially perpendicular to the plane in which the electron beams (14) move.



4. A display device as claimed in any one of the preceding Claims, characterized in that the display device has a rear wall (4) of a soft magnetic material.

5. A display device as claimed in Claim 4, characterized in that the display device has a steel rear wall.

6. A display device as claimed in Claim 1, 2 or 3, characterized in that the plane within which the electron beams (14) move parallel to the front and rear walls (3,4) is substantially entirely surrounded by a magnetic shield.

7. A display device as claimed in any one of the preceding Claims, characterized in that the display device comprises a shadow mask (19).

8. A display device as claimed in any one of the preceding Claims, characterized in that the device is provided with a light valve.

9. A display device as claimed in any one of Claim 1 or 2, characterized in that the cathode unit (31) comprises the row of electron multipliers (20).

10. A cathode unit (31) for a display device of the kind defined in claim 1 and comprising at least one cathode (10) for generating at least one electron beam (14) characterized in that the cathode unit (31) comprises a row of electron multipliers (20) and deflection means (15) for deflection of the electron beam (14) over the row of electron multipliers (20).

Patentansprüche

1. Wiedergabeordnung (1) mit einer nahezu luftleeren Hülle mit im wesentlichen flachen, nahezu parallelen Vorder- (3) und Rückwänden (4), mit einer Leuchtstoffschicht (5) auf der Innenfläche der Vorderwand und mit Mitteln (31) zum Erzeugen wenigstens eines Elektronenstrahls (14), der sich nahezu im wesentlichen in einer Ebene parallel zur Vorder- (3) und Rückwand (4) bewegt und in einer Ablenkeinheit (21) über erste Ablenkmittel (7) in Richtung auf die Leuchtstoffschicht (5) selektiv ablenkbar ist, so daß jeder Strahl wenigstens einen Teil der Leuchtstoffschicht (5) abtastet, wobei das Mittel zum Erzeugen wenigstens eines Elektronenstrahls wenigstens eine Kathodeneinheit (31) mit wenigstens einer Kathode (10) enthält, die getrennt ansteuerbar ist, dadurch gekennzeichnet, daß die Kathodeneinheit (31) zweite Ablenkmittel (15) zum horizontalen

Ablenken des Elektronenstrahls über wenigstens einen Teil der Breite der Leuchtstoffschicht, und daß eine Reihe von Elektronenmultiplizierern (20) im Bündelweg zwischen der Kathode (10) und der Ablenkeinheit (21) angeordnet ist.

2. Wiedergabeordnung nach Anspruch 1, dadurch gekennzeichnet, daß die Kathodeneinheit (31) eine Halbleiterkathode (10) enthält.

3. Wiedergabeordnung nach Anspruch 2, dadurch gekennzeichnet, daß die Hauptfläche (12) des Halbleiterkathodenkörpers sich im wesentlichen senkrecht zur Ebene erstreckt, in der sich die Elektronenbündel (14) bewegen.

4. Wiedergabeordnung nach einem oder mehreren der vorangehenden Ansprüche, dadurch gekennzeichnet, daß sie eine Rückwand (4) aus weichmagnetischem Material enthält.

5. Wiedergabeordnung nach Anspruch 4, dadurch gekennzeichnet, daß sie eine Stahl-Rückwand enthält.

6. Wiedergabeordnung nach Anspruch 1, 2 oder 3, dadurch gekennzeichnet, daß die Ebene, in der sich die Elektronenbündel (14) parallel zur Vorderwand (3) und zur Rückwand (4) bewegen, im wesentlichen von einem Magnetschirm vollständig umgeben ist.

7. Wiedergabeordnung nach einem oder mehreren der vorangehenden Ansprüche, dadurch gekennzeichnet, daß sie eine Lochmaske (19) enthält.

8. Wiedergabeordnung nach einem oder mehreren der vorangehenden Ansprüche, dadurch gekennzeichnet, daß sie mit einem Lichtventil versehen ist.

9. Wiedergabeordnung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die Kathodeneinheit (31) die Reihe von Elektronenmultiplizierern (20) enthält.

10. Kathodeneinheit (31) für eine Wiedergabeordnung nach der im Anspruch angegebenen Art mit wenigstens einer Kathode (10) zum Erzeugen wenigstens eines Elektronenstrahls (14), dadurch gekennzeichnet, daß die Kathodeneinheit (31) eine Reihe von Elektronenmultiplizierern (20) und Ablenkmittel (15) zum Ablenken des Elektronenstrahls (14) über die Reihe von Elektronenmultiplizierern (20) enthält.



Revendications

1. Dispositif d'affichage (1) comprenant une enveloppe en substance sous vide comportant des parois antérieure (3) et postérieure (4) en substance parallèles, principalement planes, une couche de matière luminescente (5) le long de la surface intérieure de la paroi antérieure et des moyens (31) pour produire au moins un faisceau d'électrons (14) qui se déplace en substance dans un plan parallèle aux parois antérieure (3) et postérieure (4) et qui peut être dévié sélectivement dans la direction allant vers la couche de matière luminescente (5) via des premiers moyens de déviation (7) dans une unité de déviation (21), de sorte que chaque faisceau balaye au moins une partie de la couche de matière luminescente (5), les moyens destinés à produire au moins un faisceau d'électrons comprenant au moins une unité cathodique (31) comportant au moins une cathode (10) qui peut être commandée séparément, caractérisé en ce que l'unité cathodique (31) comprend des seconds moyens de déviation (15) pour la déviation horizontale du faisceau d'électrons sur au moins une partie de la largeur de la couche de matière luminescente et qu'une rangée de multiplicateurs d'électrons (20) est disposée dans le trajet du faisceau entre la cathode (10) et l'unité de déviation (21). 5 10 15 20 25 30
2. Dispositif d'affichage suivant la revendication 1, caractérisé en ce que l'unité cathodique (31) comprend une cathode semi-conductrice (10). 35
3. Dispositif d'affichage suivant la revendication 2, caractérisé en ce que la surface principale (12) du corps de cathode semi-conductrice s'étend en substance perpendiculairement au plan dans lequel les faisceaux d'électrons (14) se déplacent. 40
4. Dispositif d'affichage suivant l'une quelconque des revendications précédentes, caractérisé en ce qu'il comporte une paroi postérieure (4) en une matière magnétique douce. 45
5. Dispositif d'affichage suivant la revendication 4, caractérisé en ce qu'il comporte une paroi postérieure en acier. 50
6. Dispositif d'affichage suivant la revendication 1, 2 ou 3, caractérisé en ce que le plan dans lequel les faisceaux d'électrons (14) se déplacent parallèlement aux parois antérieure et postérieure (3, 4) est en substance entièrement entouré par un blindage magnétique. 55
7. Dispositif d'affichage suivant l'une quelconque des revendications précédentes, caractérisé en ce qu'il comprend un masque perforé (19).
8. Dispositif d'affichage suivant l'une quelconque des revendications précédentes, caractérisé en ce qu'il est pourvu d'une valve de lumière.
9. Dispositif d'affichage suivant l'une ou l'autre des revendications 1 et 2, caractérisé en ce que l'unité cathodique (31) comprend la rangée de multiplicateurs d'électrons (20).
10. Unité cathodique (31) pour un dispositif d'affichage du type selon la revendication 1, comprenant au moins une cathode (10) pour produire au moins un faisceau d'électrons (14), caractérisée en ce qu'elle comprend une rangée de multiplicateurs d'électrons (20) et des moyens de déviation (15) pour faire dévier le faisceau d'électrons (14) sur la rangée de multiplicateurs d'électrons (20).