

FLOW DETECTION

The invention relates to the detection of flow in a pipe and particularly, but not exclusively, to the detection of clogging of a pipe in which the material conveyed comprises pulverized objects or a slurry.

Related Background Art

In a polyolefin production plant, for example, polyolefin produced in a fluidized bed olefin polymerization reactor is transported to a reactor of a next process, or a reservoir through a transportation pipe.

Temperature at the exit of the fluidized olefin polymerization reactor and in a pipe for the transportation is 60 - 100°C. At this temperature range polyolefin has so high viscosity and solidification that there is a risk that it may clog the transportation pipe.

To avoid such risk in transporting polyolefin from the fluidized bed polyolefin polymerization reactor to a next process, generally a pressure difference of 3 - 25 kg/cm² is generated between the polymerization reactor and the next process to transport the polyolefin at high speed by the pressure difference.

Conventionally the clogging of the transportation pipe is prevented by transporting polyolefin thus at high speed, but still the transportation pipe tends to be clogged. In the fluidized bed olefin

polymerization reactor, for example, sometimes lumps are formed in the reaction process, and the lumps stick to valves of the transportation pipe and clog the pipe.

5 To detect clogging of the transportation pipe, conventionally operators on patrol press a sound scope stick against the transportation pipe and directly listen to vibratory sounds of the transportation pipe caused by the flow of polyolefin to judge occurrence
10 of clogging.

 Thus the detection of clogging of the transportation pipe of the polyolefin depends on human audition. Such detection results sometimes contain personal differences, and there is a risk that
15 clogging may be overlooked.

 Since the patrol is periodic, if the transportation pipe are clogged immediately after a patrol, the operation is continued with the clogging. unremoved, and a clogging state is worsened. When the
20 operation is continued with the clogging state unremoved, the clogging material is solidified, and the transportation pipe sometimes have to be removed and changed.

 But, since the polyolefin is transported through
25 the transportation pipe at a flow rate as high as 10 - 300 m/s, it is very difficult to dispose flow meters and electrodes. The presence of projections, such as flow meters, electrodes, etc., in the transportation pipe can be sources of the clogging and adversely

enhance the clogging.

The above-described problem is not limited to the transportation pipe for polyolefin and arises in transportation pipe for other pulverized materials, slurry, etc.

SUMMARY OF THE INVENTION

In view of the above-described problem this invention has been made. An object of this invention is to provide a pipe clogging detecting device which incessantly monitors states of a pipe through which fluid is flowing, and when clogging occurs, immediately alarms the occurrence to operators.

Another object of this invention is to provide means for removing clogging from a pipe when the clogging is detected.

The above-described objects and other objects of this invention will be apparent from the following description.

Provided according to the present invention is a pipe clogging detecting device comprising a plurality of containers, a pipe interconnecting said containers, said pipe being apt to be clogged with fluid passing through said pipe, a vibration sensor provided on said pipe, said vibration sensor detecting vibrations generated when the fluid passes through said pipe, and detecting means for detecting occurrence of clogging in said pipe, based on output signals from said vibration sensor.

When the pipe is not clogged, fluid flows through

the pipe, and vibrations generated by the flow of the fluid are of higher level. As clogging develops, the level of vibrations is decreasing. Accordingly the clogging state in the pipe can be detected by
5 converting the vibrations into electric signals with a vibration sensor provided on the pipe, and analyzing the electric signals.

Output signals of the vibration sensor contain those of vibrations which are not associated with the fluid through the pipe, i.e., vibrations generated by
10 motors, etc. in the plant. Accordingly it is preferable that only the signals of a frequency band corresponding to vibrations generated by the fluid through the pipe are extracted.

15 When the pipe is clogged, the clogging objects can be forcibly removed by feeding a purge gas of high pressure into the pipe.

The present invention will become more fully understood from the detailed description given
20 hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not to be considered as limiting the present invention.

Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be
25 understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the

spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 is a block diagram of the clogging detecting device according to Embodiment 1 of this invention which is applied to a transportation pipe of a fluidized bed olefin polymerization reactor.

10 Fig. 2 is an electric circuit diagram of one example of a signal processing circuit of the clogging detecting device according to Embodiment 1.

15 Fig. 3 is graph of one example of trend records taken by a computer of the clogging detecting device according to Embodiment 1, (a) indicating actuation signals for the solenoid valves in the transportation pipe line, (b) representing actuation signals for the solenoid valves in a purge gas feed pipe, (c) representing signals from the signal processing circuit.

20 Fig. 4 is a block diagram of the clogging detecting device according to Embodiment 2 applied to a system including a plurality of transportation pipes.

DESCRIPTION OF THE PREFERRED EMBODIMENT

25 This invention will be explained by means of preferred embodiments with reference to the drawings attached hereto.

Embodiment 1

Fig. 1 shows the clogging detecting device 4

according to this invention which is used in a transportation pipe 3 between a fluidized bed olefin polymerization reactor 1 and a product hopper 2. In the fluidized olefin polymerization reactor 1 a mixed phase of a gas and a pulverized body, and it is fluidized by the circulating gas and fresh gas (not shown) fed from below a distribution plate 5. When a catalyst is injected into the mixed phase in this state, a polymerization reaction goes on, and polyolefin is produced. Pressure in the fluidized bed olefin polymerization reactor 1 is about 10 - 30 kg/cm²G, and temperature therein is about 70 - 100°C.

The polyolefin produced in the fluidized bed olefin polymerization reactor 1 is transported to the product hopper 2 through the transportation pipe 3 by means of pressure difference between the reactor 1 and the product hopper 2. A solenoid valve 6 is disposed near the exit of the fluidized olefin polymerization reactor 1 in the transportation pipe 3. A solenoid valve 7 is disposed also near the entrance of the product hopper 2. When the plant is in operation, the solenoid valve 6 is normally opened, and the solenoid valve 7 is periodically opened and closed, so that the polyolefin is intermittently transported. The solenoid valve 7 is opened generally for a short period of time of 10 - 60 seconds.

In the fluidized bed olefin polymerization reactor 1 it sometimes happens that some lumps are formed in the process of the reaction and clog the

transportation pipe 3 itself or the solenoid valves 6, 7, with the result that the polyolefin cannot be taken out of the fluidized bed olefin polymerization reactor 1.

5 To avoid such situation, generally the transportation pipe 3 is connected to a pipe for feeding a purge gas for precluding the clogging and removing the clogging objects. In the shown embodiment, purge gas feed pipes 8, 9 are connected
10 immediately after the solenoid valve 6 and immediately before the solenoid valve 7 respectively. The respective purge gas feed pipes 8, 9 have solenoid valves 10, 11. The solenoid valves 10, 11, and the solenoid valves 6, 7 in the transportation pipe 3 are
15 suitably opened and closed so that a purge gas of higher pressure than the interior of the fluidized olefin polymerization reactor 1 is fed into the transportation pipe 3, and the interior of the transportation pipe 3 is cleaned, or the clogging
20 objects are forcibly removed.

 In the normal plant operation, during the transportation of polyolefin is stopping, by closing the solenoid valve 7 and opening the solenoid valve 11 concurrently, the high pressure purge gas is caused to
25 flow reversely from a feed point B to the fluidized bed olefin polymerization reactor 1 through the transportation pipe 3 to preclude the clogging. During this operation, the solenoid valve 10 in the purge gas feed pipe 8 is closed. The actuation of the

solenoid valves 6, 7, 10, 11 are sequentially controlled by a sequencer 12.

5 The clogging detecting device 4 according to this invention includes a vibration sensor 13. The vibration sensor 13 is mounted on the outer surface of the middle portion of the transportation pipe 3. The vibration sensor 13 converts vibrations caused by the polyolefin or the purge gas flowing through the transportation pipe 3 into electric signals. The vibration sensor 13 is provided by a piezoelectric element or others. The electric signals from the vibration sensor 13 are converted by a converter 14 into signals of a voltage level which is easy to process, and supplied to a signal processing circuit 15.

10 Fig. 2 shows one example of the signal processing circuit 15. The forward half of the signal processing circuit 15 consists of partial circuits 16, 17. The partial circuit 16 includes switches 18 - 20, amplifiers 21 - 23, a low-pass filter 24 and a high-pass filter 25. The partial circuit 17 includes a switch 26, amplifiers 27, 28, a low-pass filter 29 and a high-pass filter 30.

25 The partial circuit 16 detects vibrations caused by the flow of the purge gas. The low-pass filter 24 and the high-pass filter 25 pass only signals of a frequency band (1.5 k - 4 kHz) corresponding to vibrations caused by the flow of the purge gas and cut off other signals corresponding to vibrations caused

by motors, etc. in the plant. The partial circuit 17 detects vibrations caused by the flow of the polyolefin. The low-pass filter 29 and the high-pass filter 30 pass only signals of a frequency band (0.5 k - 1.5 kHz) corresponding to vibrations caused by the flow of the polyolefin.

The switches 18, 19 turn on when the respective solenoid valves 10, 11 are opened. The switch 20 turns on when either of the solenoid valves 10, 11 is opened. The switch 26 turns on when the solenoid valve 7 is opened. These switches 18, 19, 20, 26 are actuated in response to a signal from the sequencer 12. The sequencer 12 is incessantly supplied with actuation signals as answer-back signals from the respective solenoid valves 6, 7, 10, 11.

The thus extracted electric signals of the specific frequency bands by the partial circuits 16, 17 of the signal processing circuit 15 are inputted to the amplifier 34 and amplified to be listened to as flow sounds of the polyolefin or purge gas through the transportation pipe 3 by a speaker 35 as electric-acoustic transducing means disposed in a centralized control room (not shown). It is preferable that the switch 36 is turned on and off so that the speaker 35 timely utters flow sounds.

The signal processing circuit 15 includes an average processing circuit 32 and a peak retaining circuit 33. Electric signals of the specific frequency bands extracted by the partial circuits 16,

17 of the forward stage are rectified by a rectifying circuit 31, and then outputted to the computer (detecting means) 37 through the average processing circuit 32 and the peak retaining circuit 33.

5 The computer 37 is supplied with signals of the vibration sensor 13, and actuation signals of the respective solenoid valves 6, 7, 10, 11 through the sequencer 12 and the signal processing circuit 15, and these signals are recorded as trend records. Fig. 3
10 shows one example of trend records recorded by the computer 37. (a) represents actuation signals of the solenoid valve 7 in the transportation pipe, (b) indicates actuation signals of the solenoid valve 11 in the purge gas feed pipe 9, and c represents output
15 signals from the signal processing circuit.

As shown at (a) and (b) in Fig. 3, the solenoid valves 7, 11 are periodically opened and closed alternately.

When the solenoid valve 7 is opened (sections C₁ -
20 C₅), the solenoid valves 10, 11 are closed. The solenoid valve 6 is normally opened. In this state, the polyolefin is transported from the fluidized bed olefin polymerization reactor 1 to the product hopper through the transportation pipe 3.

25 In this state, the switch 26 is on, the other switches 18, 19, 20 being off. Signals of the vibration sensor 13 through the converter 14 are converted into signals of suitable magnitudes by the amplifier 27, then those of the signals which have

frequencies outside a range of 0.5 k - 1.5 kHz are cut off by the low-pass filter 29 and the high-pass filter 30. The extracted signals are converted into signals of suitable magnitudes by the amplifier 28, and supplied to the speaker 35 and the rectifying circuit 31 and outputted from the signal processing circuit 15.

When the solenoid valve 11 is opened (sections D₁ - D₅), the solenoid valves 7, 10 are closed, and the purge gas is fed into the fluidized bed olefin polymerization reactor 1 through the transportation pipe 3 from the purge gas feed pipe 9.

In this state, the switches 19, 20 are on, the other switches 18, 26 being off. Signals of the vibration sensor 13 are converted into signals of suitable magnitudes by the amplifier 22, then those of the signals which have frequencies outside a range of 1.5 k - 4 kHz are cut off by the low-pass filter 24 and the high-pass filter 25. The extracted signals are converted into signals of suitable magnitudes by the amplifier 23, and supplied to the speaker 35 and the rectifying circuit 31 and outputted from the signal processing circuit 15.

In the sections C₁, C₂, C₃, peak values of signals from the signal processing circuit 15 are above 60% of the maximum peak value, and the transportation pipe 3 is not clogged. It is shown that the polyolefin is being smoothly transported. In the sections D₁, D₂, D₃, D₅ as well, peak values of signals are sufficiently

large. It is shown that the purge gas smoothly flows reversely. But in the sections C_3 , C_4 , and the section D_4 , peak values of signals are so small that it is shown that clogging has take place in the transportation pipe 3.

The computer 37 beforehand stores a set reference level (60% of the maximum value in this embodiment) based on this finding to judge whether or not peak values of signals in the respective sections C, D are above the reference level. When a peak value of the signals are below the set reference level, the computer 37 actuates suitable alarming means, such as an alarm speaker 38 or others to alarm to operators in the centralized control room that the transportation pipe 3 is clogged.

When an alarm is made, the operators interrupt the control of actuating the solenoid valves 6, 7, 10, 11 by the sequencer 12 and instead operate a control board in the centralized control room to remotely open and close the solenoid valves 6, 7, 10, 11 so as to remove the clogging by means of the purge gas. Various modes of the flow of the purge gas can be proposed.

For example, first after all the solenoid valves 6, 7, 10, 11 are closed, the solenoid valve 10 is opened, and next the solenoid valve 6 is opened. Then the solenoid valve 6 is opened to feed the purge gas of a higher pressure than a pressure in the fluidized bed olefin polymerization reactor 1 from the purge gas

feed pipe 8 into the transportation pipe 3 to cause the purge gas to reversely flow into the fluidized bed olefin polymerization reactor 1. Clogging of the transportation pipe 3 between the feed point A and the fluidized bed olefin polymerization reactor 1, and the solenoid valve 6 is removed.

When this operation fails to remove the clogging, after all the solenoid valves 6, 7, 10, 11 are closed, the solenoid valve 11 is opened, and in addition the solenoid valve 6 is opened. And the high-pressure purge gas is fed into the transportation pipe 3 from the purge gas feed pipe 9 to be caused to reversely flow into the fluidized bed olefin polymerization reactor 1.

When clogging has occurred between the feed point B and the product hopper 2, the above-described operations cannot remove the clogging. The next operation is necessary. First all the solenoid valves 6, 7, 10, 11 are closed, and then the solenoid valves 11, 7 are sequentially opened to feed the purge gas from the feed point B into the transportation pipe 3 to be sent under pressure into the product hopper 2.

When this operation cannot remove the clogging, the solenoid valves 11, 6 are closed, the solenoid valves 10, 7 are opened to cause the purge gas to flow from the feed point A to the product hopper 2.

The operators suitably combine the above-described four modes, listening to alarms from the speaker 35. Repetition of combinations of the four

modes by several times can normally remove clogging.

Thus, according to the pipe clogging detecting device according to Embodiment 1 of this invention, operators can detect a clogging state of the pipe in a remote centralized control room or others without going to the pipe, and can quickly take a suitable procedure for removing the clogging state. Accordingly a situation in which clogging objects have solidified, and the transportation pipe has to be dismantled to remove the solidified clogging objects can be precluded.

A detection of clogging can be followed by removal of the clogging, and accordingly manual labour of operators can be decreased.

In addition, this invention can contribute to stable operation of the plant including the pipe, and rationalization of patrols in the plant.

Embodiment 2

Fig. 4 shows a system including a plurality of transportation pipes 3_1 , 3_2 . In this embodiment vibration sensors 13_1 , 13_2 are provided respectively on the transportation pipes 3_1 , 3_2 . A clogging detecting device 4 includes a number of signal processing circuits 15_1 , 15_2 corresponding to a number of the vibration sensors 13_1 , 13_2 . The clogging detecting device 4 also includes change-over switch 39. Each signal processing circuit 15_1 , 15_2 includes low-pass filters, high-pass filters, amplifiers, etc. Frequencies and amplifying ratios are optimumly set

depending on vibration characteristics of the transportation pipes 3₁, 3₂. Operators can listen to sounds corresponding to vibrations of the transportation pipes 3₁, 3₂, changing over output
5 signals of the signal processing circuits 15₁, 15₂ by the switch 39. By following the same procedure as in Embodiment 1, clogging in the transportation pipes 3₁, 3₂ can be removed. The operators can listen to alarms from a speaker 38.

10 With reference to Fig. 4, a system including two transportation pipes 3₁, 3₂, and three reactors 1₁ - 1₃ has been explained. This invention can be applied to large-scale systems including more than two transportation pipes, and more than three reactors in
15 the same way as above.

In Embodiments 1 and 2, the clogging detecting device 4 according to this invention is applied in the transportation pipe 3 from the fluidized olefin polymerization reactor 1, but this invention is not
20 limited to such an application. This invention is applicable to detection of clogging in the general fluid transportation pipes.

From the invention thus described, it will be obvious that the invention may be varied in many ways.
25 Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.



THIS SHEET HAS BEEN
REPLACED

CLAIMS:

1. A pipe clogging detecting device comprising:
a plurality of containers;
a pipe interconnecting said containers, said pipe
5 being apt to be clogged with fluid passing through
said pipe;

a vibration sensor provided on said pipe, said
vibration sensor detecting vibrations generated when
the fluid passes through said pipe; and

10 detecting means for detecting occurrence of
clogging in said pipe, based on output signals from
said vibration sensor.

2. A pipe clogging detecting device according to
claim 1, wherein said detecting means extracts out of
15 output signals of said vibration sensor signals of a
frequency band corresponding to the vibrations
generated by the fluid through said pipe, and judges
that said pipe is clogged when the signals of the
frequency band are below a set reference level.

20 3. A pipe clogging detecting device according to
claim 2, wherein

the fluid through said pipe is polyolefin and a
purge gas for removing clogging in said pipe;

25 there is provided purge gas feeding means for
feeding the purge gas into said pipe;

there is provided valve means for causing one of
the polyolefin and the purge gas to flow through said
pipe; and

the frequency band is 0.5k - 1.5kHz when the

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

fluid admitted to flow through said pipe by said valve means is the polyolefin.

4. A pipe clogging detecting device according to claim 2, wherein

5 the fluid through said pipe is polyolefin and a purge gas for removing clogging in said pipe;

there is provided purge gas feeding means for feeding the purge gas into said pipe;

10 there is provided valve means for causing one of the polyolefin and the purge gas to flow through said pipe; and

the frequency band is 1.5k - 4kHz when the fluid admitted to flow through said pipe by said valve means is the purge gas.

15 5. A pipe clogging detecting device according to claim 1, wherein said detecting means includes an average processing circuit for averaging the output signals of said vibration sensor.

20 6. A pipe clogging detecting device according to claim 1, wherein

the detecting means includes a peak retaining circuit for retaining peak values of the output signals of said vibration sensor.

25 7. A pipe clogging detecting device according to claim 1, comprising alarming means for giving alarms when clogging is detected in said pipe by said detecting means.

8. A pipe clogging detecting device according to claim 1 comprising means for converting the output





THIS SHEET HAS BEEN
REPLACED

signals of said vibration sensor into sounds.

9. A pipe clogging detecting device according to claim 1, wherein the fluid through said pipe includes polyolefin.

5 10. A pipe clogging detecting device according to claim 1, wherein

there are provided a plurality of pipes;

there are provided the same number of vibration sensors as said pipes; and

10 there are provided the same number of detecting means as said vibration sensors.

11. Flow detection apparatus comprising means for sensing vibration generated by a flow of material in a pipe and providing a signal in response to said vibration and processing means for processing said signal and providing an indication of a flow condition in said pipe.

12. Flow detection apparatus substantially as hereinbefore described with reference to the accompanying drawings.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

ABSTRACT OF THE DISCLOSURE

(Figure 1)

5 A pipe clogging detecting device (4) which incessantly monitors states of a pipe through which fluid is flowing, and when clogging occurs, immediately alarms the occurrence to operators. The device comprises a plurality of containers (1,2), a pipe (3) interconnecting the containers, a vibration sensor (13) provided on the pipe, and detecting means for detecting occurrence of clogging in the pipe,
10 based on output signals from the vibration sensor.

This Sheet Has Been Replaced



Fig. 1




Fig. 2






Fig. 3

Fig. 4



THIS SHEET HAS BEEN
REPLACED

REPLACEMENT SHEET
06 AUG 1996

19

FLOW DETECTION

ABSTRACT OF THE DISCLOSURE

(Figure 1)

5 A pipe clogging detecting device (4) which incessantly monitors states of a pipe through which fluid is flowing, and when clogging occurs, immediately alarms the occurrence to operators. The device comprises a plurality of containers (1,2), a pipe (3) interconnecting the containers, a vibration sensor (13) provided on the pipe, and detecting means for detecting occurrence of clogging in the pipe,
10 based on output signals from the vibration sensor.

This Sheet Has Been Replaced






26 DEC 1997

9602047-4

1108

CLAIMS:

1. Apparatus comprising:
 - two containers;
 - a pipe interconnecting said containers, said pipe being liable to be clogged with fluid passing through said pipe from one container to the other;
 - a vibration sensor provided on said pipe, for detecting vibrations generated when the fluid passes through said pipe;
 - detecting means for detecting occurrence of clogging in said pipe, based on output signals from said vibration sensor; and
 - purge gas feeding means for selectively feeding purge gas into said pipe at spaced apart feed locations along the pipe for removing a clog in the pipe.
2. Apparatus according to claim 1 comprising valve means for selectively controlling the flow of fluid from one container to the other through said pipe and the flow of purge gas into said pipe at said feed locations.
3. Apparatus according to claim 2, wherein said valve means comprise a respective valve in said pipe adjacent each of said containers and a respective valve in each of two purge gas feed pipes connected to said pipe at said spaced apart feed locations between



17

said valves in said pipe interconnecting said containers.


4. Apparatus according to claim 1, 2 or 3, wherein said detecting means extracts out of output signals of said vibration sensor signals of a frequency band corresponding to the vibrations generated by the fluid through said pipe, and judges that said pipe is clogged when the signals of the frequency band are below a set reference level.

5. Apparatus according to claim 4, when appended to claim 2 or 3, wherein the fluid to be passed through said pipe is polyolefin and wherein the frequency band is 0.5k - 1.5kHz when the valve means are set to allow flow of polyolefin through said pipe and to prevent flow of purge gas therethrough.

6. Apparatus according to claim 4 when appended to claim 2 or 3, wherein the frequency band is 1.5k - 4kHz when the valve means are set to allow fluid flow of purge gas through said pipe and to prevent flow of polyolefin therethrough.

7. Apparatus according to any one of the preceding claims, wherein said detecting means includes an average processing circuit for averaging the output signals of said vibration sensor.

8. Apparatus according to any one of the preceding claims, wherein the detecting means includes a peak retaining circuit for retaining peak values of the



output signals of said vibration sensor.

9. Apparatus according to any one of the preceding claims, comprising alarm means for giving an alarm when clogging is detected in said pipe by said detecting means.

10. Apparatus according to any one of the preceding claims, comprising means for converting the output signals of said vibration sensor into sounds.

11. Apparatus according to any one of the preceding claims, comprising a plurality of said containers and a plurality of said pipes, each pipe interconnecting two of said containers and being provided with a respective said vibration sensor, each vibration sensor having a respective said detecting means associated therewith, and a respective said purge gas feeding means being provided for selectively feeding purge gas into each said pipe at spaced apart feed locations therealong.

12. Apparatus comprising:

a pipe;

means for sensing vibration generated by a flow of material in a pipe and providing a signal in response to said vibration;

processing means for processing said signal and providing an indication of a flow condition in said pipe; and

purge gas feeding means for selectively feeding



19

REPLACEMENT SHEET

26 DEC 1997

purge gas into said pipe at spaced apart locations along the pipe for removing a clog in the pipe.

13. Apparatus substantially as hereinbefore described with reference to Figures 1 to 3 or Figure 4 of the accompanying drawings.

Flow DetectionAbstract

A pipe clogging detecting device (4) which incessantly monitors states of a pipe through which fluid is flowing, and when clogging occurs, immediately alarms the occurrence to operators. The device comprises a plurality of containers (1,2), a pipe (3) interconnecting the containers, a vibration sensor (13) provided on the pipe, and detecting means for detecting occurrence of clogging in the pipe, based on output signals from the vibration sensor.

Figure 1

