



- (51) International Patent Classification:
C09D 5/16 (2006.01) *C09D 163/00* (2006.01)
- (21) International Application Number:
PCT/DK2014/050069
- (22) International Filing Date:
21 March 2014 (21.03.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13161381.2 27 March 2013 (27.03.2013) EP
- (71) Applicant: **HEMPEL A/S** [DK/DK]; Lundtoftegårdsvej
91, DK-2800 Kgs. Lyngby (DK).
- (72) Inventors: **THORLAKSEN, Peter Christian Weinrich**;
Druemarken 7, DK-2680 Solrød Strand (DK). **PAULSEN,**
Andreas Lundtang; Eskjærvej 2, 1., DK-2720 Vanløse
(DK).
- (74) Agents: **THORSEN, Jesper** et al.; Inspicos A/S, P.O. Box
45, Kogle Allé 2, DK-2970 Hørsholm (DK).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM,
ZW.

- (84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— *of inventorship (Rule 4.17(iv))*

Published:

— *with international search report (Art. 21(3))*

(54) Title: CURING AGENT FOR TIE-COAT COMPOSITION COMPRISING AN AMINO-SILANE ADDUCT

(57) Abstract: A method for applying a fouling-release coating system to a surface, said surface suitably provided with an anticorrosive coat and an article comprising a substrate, said substrate having a surface, preferably an anticorrosive coat on at least a part of the surface of said substrate and a tie-coat on said substrate. A curing agent composition comprising an amino-silane adduct comprising a high molecular weight amine HMWA, and a tie-coat comprising said curing agent composition are also provided

