

MOBILE PAYMENT METHOD, APPARATUS, AND DEVICE

TECHNICAL FIELD

[0001] The present specification relates to the field of information technologies, and in particular, to mobile payment methods, apparatuses, and devices.

5

BACKGROUND

[0002] With the popularity of mobile payment technologies, users can perform mobile payment by using specified applications (such as mobile payment application) installed on terminal devices (such as mobile phone).

10 [0003] Generally, when a mobile phone of a user is in a lock screen mode, if the user needs to perform mobile payment, the user needs to first unlock the screen of the mobile phone through fingerprint verification, password input, etc. to enter an interface of an operating system. Then, only after the user starts a specified application in the interface of the operating system, the user can further trigger a mobile payment interface in an interface of the specified application for mobile
15 payment.

[0004] Based on the existing technology, a more convenient mobile payment method is needed.

SUMMARY

20 [0005] Implementations of the present specification provide mobile payment methods, apparatuses, and devices, to alleviate a problem that existing mobile payment methods are less convenient.

[0006] To alleviate the previous technical problem, the implementations of the present specification are implemented as below:

25 [0007] An implementation of the present specification provides a mobile payment method, including: monitoring, by a terminal device, body movements of a user when the terminal device is in a lock screen mode; displaying a mobile payment interface when it is determined that the monitored body movement satisfies first specified criteria; and executing a mobile payment service based on inputs received through the

mobile payment interface.

[0008] An implementation of the present specification provides a mobile payment apparatus, including: a monitoring module, configured to monitor body movements of a user when the apparatus is in a lock screen mode; a display module, configured to display a mobile payment interface when it is determined that the monitored body movement satisfies first specified criteria; and an execution module, configured to execute a mobile payment service based on inputs received through the mobile payment interface.

[0009] An implementation of the present specification provides a terminal device, including one or more processors and memories, where the memories store programs, and the programs are configured to be executed by the one or more processors to perform the following steps: monitoring, by the terminal device, body movements of a user when the terminal device is in a lock screen mode; displaying a mobile payment interface when it is determined that the monitored body movement satisfies first specified criteria; and executing a mobile payment service based on inputs received through the mobile payment interface.

[0010] It can be seen from the previous technical solutions provided in the implementations of the present specification that, in the implementations of the present specification, a terminal device can monitor body movements of a user when the terminal device is in a lock screen mode; display a mobile payment interface when it is determined that the monitored body movement satisfies first specified criteria; and execute a mobile payment service based on inputs received through the mobile payment interface. According to the implementations of the present specification, the user can trigger the terminal device to display the mobile payment interface for mobile payment by performing only a body movement that satisfies the first specified criteria, without unlocking the screen of the terminal device and then starting a specified application for mobile payment. As such, the user can perform mobile payment more conveniently.

BRIEF DESCRIPTION OF DRAWINGS

[0011] To describe the technical solutions in the implementations of the present specification or in the existing technology more clearly, the following briefly describes the accompanying drawings required for describing the implementations or

the existing technology. Clearly, the accompanying drawings in the following descriptions merely show some implementations of the present specification, and a person of ordinary skill in the art can still derive other drawings from these accompanying drawings without creative efforts.

5 **[0012]** FIG. 1 is a schematic diagram illustrating steps performed by a user when the user operates a mobile phone for mobile payment in the existing technology;

[0013] FIG. 2 is a flowchart illustrating a mobile payment method, according to an implementation of the present specification;

[0014] FIG. 3 is a schematic diagram illustrating a mobile payment method,
10 according to an implementation of the present specification;

[0015] FIG. 4 is a schematic diagram illustrating a mobile payment apparatus, according to an implementation of the present specification;

[0016] FIG. 5 is a schematic diagram illustrating a terminal device, according to an implementation of the present specification.

15 **DESCRIPTION OF IMPLEMENTATIONS**

[0017] FIG. 1 is a schematic diagram illustrating steps performed by a user when the user operates a mobile phone for mobile payment in the existing technology. As shown in FIG. 1, when the user needs to perform mobile payment, the user usually needs to operate the mobile phone to perform the following steps: 1. Unlock the
20 screen of the mobile phone. 2. Find and start a mobile payment application in an application list displayed on the home screen. 3. Click "Scan" button or "QR code" button in an interface of the mobile payment application to trigger a corresponding mobile payment interface for mobile payment.

[0018] It can be seen that in the existing mobile payment method, the user usually
25 can trigger the mobile payment interface only after performing multiple steps, which is inconvenient for the user.

[0019] However, in one or more implementations of the present specification, a terminal device can monitor body movements of a user when the terminal device is in a lock screen mode; and directly display a mobile payment interface for mobile
30 payment when it is determined that the monitored body movement satisfies first specified criteria. It means that the user usually can trigger the mobile payment interface by performing only a body movement that satisfies the first specified

criteria, so that the user can perform mobile payment more conveniently.

[0020] To make a person skilled in the art better understand the technical solutions in the present specification, the following clearly and comprehensively describes the technical solutions in the implementations of the present specification with reference to the accompanying drawings in the one or more implementations of the present specification. Clearly, the described implementations are merely some rather than all of the implementations of the present specification. All other implementations obtained by a person of ordinary skill in the art based on the implementations of the present specification without creative efforts shall fall within the protection scope of the present specification.

[0021] The technical solutions provided in the implementations of the present specification are described in detail below with reference to the accompanying drawings.

[0022] FIG. 2 is a flowchart illustrating a mobile payment method, according to an implementation of the present specification. The method includes the following steps.

[0023] S200. A terminal device monitors body movements of a user when the terminal device is in a lock screen mode.

[0024] The method is executed by the terminal device, and the terminal device can be specifically an intelligent device available for mobile payment, such as a mobile phone or a tablet computer of the user.

[0025] As is known to all, to prevent a user from mistakenly touching a screen or a physical key of a terminal device to mistakenly start an application installed in an operating system, or prevent other unwanted cases, the terminal device usually has a lock screen mode and an unlocked (i.e., home screen) mode. When the terminal device is in the lock screen mode, only after unlocking the screen of the terminal device to enable the terminal device to be in the unlocked mode, the user can be authorized to enter the home screen, and then can further operate an application installed in the operating system.

[0026] For example, in the existing technology, if a terminal device is in a lock screen mode, when a user needs to perform mobile payment, only after unlocking the screen of the terminal device to enter the home screen, the user can start a specified application (which can be specifically a mobile payment application) with a mobile payment function for mobile payment.

[0027] However, in this implementation of the present specification, when the

terminal device is in the lock screen mode, the terminal device can monitor various body movements of the user. For example, the terminal device can monitor body movements of the user, such as blinking, hand raising, hand waving, and head shaking, by using a camera, or can monitor body movements of the user by using a built-in acceleration sensor. It is worthwhile to note that the body movement monitored by the terminal device may be neither a screen unlocking movement performed by the user nor an operation performed by the user on a screen of the terminal device.

[0028] That the terminal device monitors body movements of the user by using the acceleration sensor can be specifically monitoring a body movement (for example, shaking the terminal device) performed by the user when the user holds the terminal device. An acceleration of the terminal device can be generated due to an external force, and the acceleration sensor built in the terminal device can detect an acceleration generated during shaking of the terminal device.

[0029] S202. Display a mobile payment interface when it is determined that the monitored body movement satisfies first specified criteria.

[0030] In this implementation of the present specification, the first specified criteria can be set based on an actual need.

[0031] For example, if the terminal device monitors, by using the built-in acceleration sensor, a body movement that the user shakes the terminal device, when it is determined, by using the acceleration sensor, that an acceleration of the terminal device is greater than a specified threshold, the terminal device determines that the monitored body movement satisfies the first specified criteria.

[0032] Further, the acceleration sensor can be a tri-axis acceleration sensor, and the tri-axis acceleration sensor can be configured to detect accelerations of the terminal device on x, y, and z coordinate axes. In this case, a corresponding threshold can be predetermined for each coordinate axis. When it is determined, by using the acceleration sensor, that an acceleration of the terminal device on each coordinate axis is greater than the corresponding threshold, the terminal device determines that the monitored body movement satisfies the first specified criteria. It is worthwhile to emphasize here that the three coordinate axes can correspond to the same threshold.

[0033] In this implementation of the present specification, the mobile payment interface is an interface used to execute a mobile payment service, and only after triggering the terminal device to display the mobile payment interface, the user can

enable the terminal device to execute the mobile payment service based on inputs received through the mobile payment interface.

[0034] The mobile payment interface can be an interface used to obtain collection information, for example, an interface used to scan a collection identifier (which can be specifically a collection QR code or a collection barcode), and the user can align a scan box displayed in the mobile payment interface with a collection identifier provided by a payee for scanning, to transfer money to the payee.

[0035] Alternatively, the mobile payment interface can be an interface used to display mobile payment information, for example, an interface used to display a mobile payment identifier (which can be specifically a mobile payment QR code or a mobile payment barcode) corresponding to an account of the user, and a payee can scan the mobile payment identifier provided by the user by using a scan device, to deduct money from the account of the user. Certainly, the terminal device can display both the mobile payment interface used to obtain collection information and the mobile payment interface used to display mobile payment information.

[0036] In the existing technology, a mobile payment interface is usually an interface loaded by a specified application, which imposes a need that the user can further trigger the mobile payment interface only after starting the specified application. However, in this implementation of the present specification, the mobile payment interface can be an interface loaded by an operating system of the terminal device. That is, when the terminal device determines that the monitored body movement satisfies the first specified criteria, the terminal device can display the mobile payment interface in the lock screen mode because permission of the operating system of the terminal device is not limited by the lock screen mode. As such, the user can trigger the terminal device to directly display the mobile payment interface without unlocking the screen and starting a specified application.

[0037] In addition, in this implementation of the present specification, when it is determined that the monitored body movement satisfies the first specified criteria, the terminal device can select an interface from predetermined available mobile payment interfaces, and display the interface. For example, the predetermined available mobile payment interfaces can include an interface used to scan a collection QR code, an interface used to display a mobile payment QR code, an interface used to scan a collection barcode, etc.

[0038] Further, after displaying the mobile payment interface, the terminal device

can continue to monitor body movements of the user; and if it is determined that the monitored body movement satisfies second specified criteria, select another interface from the predetermined available mobile payment interfaces, and display the interface. The second specified criteria can be the same as or different from the first specified criteria.

[0039] FIG. 3 is a schematic diagram illustrating a mobile payment method, according to an implementation of the present specification. As shown in FIG. 3, when a mobile phone is in a lock screen mode, a user can shake the mobile phone, so that when it is determined that an acceleration of the mobile phone is greater than a specified threshold, the mobile phone displays a mobile payment interface including a scan box, and the user can align the scan box in the mobile payment interface with a collection QR code provided by a payee. If the user wants to display a mobile payment QR code corresponding to an account of the user for mobile payment, the user can shake the mobile phone again, so that when it is determined again that an acceleration of the mobile phone is greater than the specified threshold, the mobile phone is switched to display a mobile payment interface including the mobile payment QR code corresponding to the account of the user.

[0040] S204. Execute a mobile payment service based on inputs received through the mobile payment interface.

[0041] Still referring to FIG. 3, the terminal device scans, by using the mobile payment interface including the scan box, the collection QR code provided by the payee, to obtain an account identifier of the payee and transfer money to the payee; or the payee can scan, by using a scan device, the mobile payment QR code displayed in the mobile payment interface, to deduct money from the account of the user.

[0042] In this implementation of the present specification, the terminal device can obtain rendering data from a specified application by using an operating system, and display the mobile payment interface based on the obtained rendering data. The rendering data specifically depends on a component layout in the mobile payment interface. No specific limitation is imposed thereto in the present specification.

[0043] After the mobile payment interface is displayed, the terminal device can scan a collection identifier by using the mobile payment interface, parse the scanned collection identifier to obtain payee information, and send the payee information to the specified application for mobile payment by using the operating system; or can perform mobile payment by using a mobile payment identifier displayed in the mobile

payment interface, where the mobile payment identifier is obtained from the specified application by using the operating system.

[0044] Further, in this implementation of the present specification, before executing the mobile payment service based on the inputs received through the mobile payment interface, the terminal device can perform identity verification on the user, and determine that the identity verification on the user succeeds. That is, if the verification succeeds, the terminal device performs the mobile payment service; or if the verification fails, the terminal device refuses to perform the mobile payment service. A specific identity verification method can be password verification, fingerprint verification, etc.

[0045] Specifically, before displaying the mobile payment interface, the terminal device can perform identity verification on the user, and if the verification fails, the terminal device refuses to display the mobile payment interface; or before executing the mobile payment service based on the inputs received through the mobile payment interface, the terminal device can perform identity verification on the user, and if the verification fails, the terminal device refuses to execute the mobile payment service based on the inputs received through the mobile payment interface.

[0046] For example, when the terminal device displays a mobile payment interface used to scan a collection identifier, that the terminal device sends the payee information to the specified application for mobile payment by using the operating system can be specifically: obtaining, by using the operating system, a mobile payment amount entered by the user; performing identity verification on the user by using the operating system; and if the verification succeeds, sending the payee information and the mobile payment amount to the specified application for mobile payment by using the operating system; or if the verification fails, refusing to send the payee information and the mobile payment amount.

[0047] For another example, when the terminal device displays a mobile payment interface used to display a mobile payment identifier, that the terminal device obtains the mobile payment identifier from the specified application by using the operating system can be specifically: performing identity verification on the user by using the operating system; and if the verification succeeds, obtaining the mobile payment identifier from the specified application by using the operating system; or if the verification fails, refusing to obtain the mobile payment identifier.

[0048] According to the mobile payment method shown in FIG. 2, because

permission of the operating system of the terminal device is not limited by the lock screen mode, when the terminal device determines that the monitored body movement satisfies the first specified criteria, even if the terminal device is in the lock screen mode, the terminal device can display the mobile payment interface and execute the mobile payment service based on the inputs received through the mobile payment interface. That is, when the user needs to perform mobile payment, the user can trigger the terminal device to display the mobile payment interface for mobile payment by performing only a body movement that satisfies the first specified criteria, without performing multiple steps, so that the user can perform mobile payment more conveniently.

[0049] Based on the mobile payment method shown in FIG. 2, an implementation of the present specification further correspondingly provides a mobile payment apparatus. As shown in FIG. 4, the mobile payment apparatus includes: a monitoring module 401, configured to monitor body movements of a user when the apparatus is in a lock screen mode; a display module 402, configured to display a mobile payment interface when it is determined that the monitored body movement satisfies first specified criteria; and an execution module 403, configured to execute a mobile payment service based on inputs received through the mobile payment interface.

[0050] The monitoring module 401 is configured to monitor the body movements of the user by using a built-in acceleration sensor; and the display module 402 is configured to: when it is determined, by using the acceleration sensor, that an acceleration of the apparatus is greater than a specified threshold, determine that the monitored body movement satisfies the first specified criteria.

[0051] The display module 402 is configured to display a mobile payment interface used to obtain collection information; and/or display a mobile payment interface used to display mobile payment information.

[0052] The display module 402 is configured to select at least one interface from predetermined available mobile payment interfaces, and display the at least one interface.

[0053] The display module 402 is configured to: after displaying the mobile payment interface, continue to monitor body movements of the user; and if it is determined that the monitored body movement satisfies second specified criteria, reselect an interface from the available mobile payment interfaces, and display the interface.

[0054] The mobile payment interface used to obtain collection information specifically includes an interface used to scan a collection identifier; and the mobile payment interface used to display mobile payment information specifically includes an interface used to display a mobile payment identifier.

5 **[0055]** The display module 402 is configured to obtain rendering data from a specified application by using an operating system, and display the mobile payment interface based on the obtained rendering data; and the execution module 403 is configured to scan a collection identifier by using the mobile payment interface, parse the scanned collection identifier to obtain payee information, and send the payee
10 information to the specified application for mobile payment by using the operating system; and/or perform mobile payment based on a mobile payment identifier displayed in the mobile payment interface, where the mobile payment identifier is determined from the specified application by using the operating system.

[0056] The apparatus further includes: an identity verification module 404,
15 configured to: before the execution module executes the mobile payment service, perform identity verification on the user, and determine that the identity verification on the user succeeds.

[0057] Based on the mobile payment method shown in FIG. 2, an implementation of the present specification further correspondingly provides a terminal device. As
20 shown in FIG. 5, the terminal device includes one or more processors and memories, where the memories store programs, and the programs are configured to be executed by the one or more processors to perform the following steps: monitoring, by the terminal device, body movements of a user when the terminal device is in a lock screen mode; displaying a mobile payment interface when it is determined that the
25 monitored body movement satisfies first specified criteria; and executing a mobile payment service based on inputs received through the mobile payment interface.

[0058] The implementations of the present specification are described in a progressive way. For same or similar parts of the implementations, mutual references can be made to the implementations. Each implementation focuses on a difference
30 from other implementations. Especially, the terminal device shown in FIG. 5 is basically similar to the method implementation, and therefore is described briefly. For related parts, references can be made to some descriptions in the method implementation.

[0059] In the 1990s, whether a technical improvement is a hardware improvement

(for example, an improvement to circuit structures, such as a diode, a transistor, and a switch) or a software improvement (an improvement to a method process) can be clearly distinguished. However, as technologies develop, current improvements to many method processes can be considered as direct improvements to hardware circuit structures. Almost all designers program an improved method process into a hardware circuit, to obtain a corresponding hardware circuit structure. Therefore, a method process can be improved by using a hardware entity module. For example, a programmable logic device (PLD) (for example, a field programmable gate array (FPGA)) is such an integrated circuit, and a logical function of the PLD is determined by a user through device programming. A designer performs programming to "integrate" a digital system into a single PLD, without requiring a chip manufacturer to design and manufacture a dedicated integrated circuit chip. In addition, at present, instead of manually manufacturing an integrated circuit chip, this type of programming is mostly implemented by using "logic compiler" software. The "logic compiler" software is similar to a software compiler used to develop and write a program. Original code needs to be written in a particular programming language before compilation. The language is referred to as a hardware description language (HDL). There are many HDLs, such as the Advanced Boolean Expression Language (ABEL), the Altera Hardware Description Language (AHDL), Confluence, the Cornell University Programming Language (CUPL), HDCal, the Java Hardware Description Language (JHDL), Lava, Lola, MyHDL, PALASM, and the Ruby Hardware Description Language (RHDL). The Very-High-Speed Integrated Circuit Hardware Description Language (VHDL) and Verilog are most commonly used at present. A person skilled in the art should also understand that a hardware circuit that implements a logical method process can be readily obtained provided that the method process is logically programmed by using several of the previous hardware description languages and is programmed into an integrated circuit.

[0060] A controller can be implemented by using any appropriate method. For example, the controller can be in a form a microprocessor or a processor, or a computer readable medium that stores computer readable program code (such as software or firmware) that can be executed by the microprocessor or the processor, a logic gate, a switch, an application-specific integrated circuit (ASIC), a programmable logic controller, or a built-in microprocessor. Examples of the controller include but are not limited to the following microprocessors: ARC 625D, Atmel AT91SAM,

Microchip PIC18F26K20, and Silicone Labs C8051F320. The memory controller can also be implemented as a part of control logic of the memory. A person skilled in the art also knows that, in addition to implementing the controller by using only the computer readable program code, method steps can be logically programmed to allow the controller to implement the same function in a form of a logic gate, a switch, an ASIC, the programmable logic controller, or the built-in microcontroller. Therefore, the controller can be considered as a hardware component, and an apparatus that is included in the controller and configured to implement various functions can also be considered as a structure in the hardware component. Alternatively, the apparatus configured to implement various functions can even be considered as both a software module implementing the method and a structure in the hardware component.

[0061] The system, apparatus, module, or unit illustrated in the previous implementations can be specifically implemented by using a computer chip or an entity, or can be implemented by using a product having a certain function. A typical implementation device is a computer. Specifically, the computer can be, for example, a personal computer, a laptop computer, a cellular phone, a camera phone, a smartphone, a personal digital assistant, a media player, a navigation device, an email device, a game console, a tablet computer, a wearable device, or a combination of any of these devices.

[0062] For ease of description, when the previous apparatus is described, the previous apparatus is divided into various units based on functions for separate description. Certainly, when the present specification is implemented, functions of the units can be implemented in one or more pieces of software and/or hardware.

[0063] A person skilled in the art should understand that an implementation of the present specification can be provided as a method, a system, or a computer program product. Therefore, the present specification can use a form of hardware only implementations, software only implementations, or implementations with a combination of software and hardware. Moreover, the present specification can use a form of a computer program product that is implemented on one or more computer-usable storage media (including but not limited to a magnetic disk memory, a CD-ROM, an optical memory, etc.) that include computer-usable program code.

[0064] The present specification is described with reference to the flowcharts and/or block diagrams of the method, the device (system), and the computer program product according to the implementations of the present specification. It is worthwhile

to understand that computer program instructions can be used to implement each process and/or each block in the flowcharts and/or the block diagrams and a combination of a process and/or a block in the flowcharts and/or the block diagrams. These computer program instructions can be provided for a general-purpose computer, a dedicated computer, an embedded processor, or a processor of another programmable data processing device to generate a machine, so that the instructions executed by a computer or a processor of another programmable data processing device generate an apparatus for implementing a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0065] Alternatively, these computer program instructions can be stored in a computer readable memory that can instruct a computer or another programmable data processing device to work in a specific way, so that the instructions stored in the computer readable memory generate an artifact that includes an instruction apparatus. The instruction apparatus implements a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0066] Alternatively, these computer program instructions can be loaded onto a computer or another programmable data processing device, so that a series of operations and steps are performed on the computer or another programmable device, thereby generating computer-implemented processing. Therefore, the instructions executed on the computer or another programmable device provide steps for implementing a specific function in one or more processes in the flowcharts and/or in one or more blocks in the block diagrams.

[0067] In a typical configuration, a computing device includes one or more processors (CPUs), input/output interfaces, network interfaces, and memories.

[0068] The memory may include a non-persistent memory, a random access memory (RAM), a nonvolatile memory, and/or another form in a computer readable medium, for example, a read-only memory (ROM) or a flash memory (flash RAM). The memory is an example of the computer readable medium.

[0069] The computer readable medium includes persistent, non-persistent, movable, and unmovable media that can store information by using any method or technology. The information can be a computer readable instruction, a data structure, a program module, or other data. Examples of a computer storage medium include but are not limited to: a phase-change RAM (PRAM), a static RAM (SRAM), a dynamic RAM (DRAM), another type of RAM, a ROM, an electrically erasable programmable

read-only memory (EEPROM), a flash memory or another memory technology, a compact disc read-only memory (CD-ROM), a digital versatile disc (DVD) or another optical storage, a magnetic cassette, a magnetic tape/magnetic disk memory or another magnetic storage device, or any other non-transmission medium. The computer storage medium can be configured to store information that can be accessed by a computing device. Based on the definition in the present specification, the computer readable medium does not include computer readable transitory media such as a modulated data signal and carrier.

[0070] It is worthwhile to further note that, the terms "include", "comprise", or their any other variants are intended to cover a non-exclusive inclusion, so that a process, a method, a product, or a device that includes a list of elements not only includes those elements but also includes other elements that are not expressly listed, or further includes elements inherent to such process, method, product, or device. Without more constraints, an element preceded by "includes a ..." does not preclude the existence of additional identical elements in the process, method, product, or device that includes the element.

[0071] A person skilled in the art should understand that an implementation of the present specification can be provided as a method, a system, or a computer program product. Therefore, the present specification can use a form of hardware only implementations, software only implementations, or implementations with a combination of software and hardware. Moreover, the present specification can use a form of a computer program product that is implemented on one or more computer-usable storage media (including but not limited to a magnetic disk memory, a CD-ROM, an optical memory, etc.) that include computer-usable program code.

[0072] The present specification can be described in the general context of computer-executable instructions, for example, a program module. Generally, the program module includes a routine, a program, an object, a component, a data structure, etc. executing a specific task or implementing a specific abstract data type. Alternatively, the present specification can be practiced in distributed computing environments. In these distributed computing environments, tasks are performed by remote processing devices that are connected through a communications network. In a distributed computing environment, the program module can be located in both local and remote computer storage media including storage devices.

CLAIMS

What is claimed is:

1. A mobile payment method, comprising:
monitoring, by a terminal device, body movements of a user when the terminal
5 device is in a lock screen mode;
displaying a mobile payment interface when it is determined that the monitored
body movement satisfies first specified criteria; and
executing a mobile payment service based on inputs received through the mobile
payment interface.
- 10 2. The method according to claim 1, wherein the monitoring body movements of
a user specifically comprises:
monitoring, by the terminal device, the body movements of the user by using a
built-in acceleration sensor; and
that it is determined that the monitored body movement satisfies first specified
15 criteria specifically comprises:
when it is determined, by using the acceleration sensor, that an acceleration of
the terminal device is greater than a specified threshold, it is determined that the
monitored body movement satisfies the first specified criteria.
- 20 3. The method according to claim 1, wherein the displaying a mobile payment
interface specifically comprises:
displaying a mobile payment interface used to obtain collection information;
and/or
displaying a mobile payment interface used to display mobile payment
information.
- 25 4. The method according to claim 1, wherein the displaying a mobile payment
interface specifically comprises:
selecting an interface from predetermined available mobile payment interfaces,
and displaying the interface.
- 30 5. The method according to claim 4, wherein after the displaying a mobile
payment interface, the method further comprises:
continuing to monitor body movements of the user; and
if it is determined that the monitored body movement satisfies second specified

criteria, reselecting an interface from the available mobile payment interfaces, and displaying the interface.

6. The method according to claim 3, wherein the mobile payment interface used to obtain collection information specifically comprises an interface used to scan a

5 collection identifier; and

the mobile payment interface used to display mobile payment information specifically comprises an interface used to display a mobile payment identifier.

7. The method according to claim 6, wherein the displaying a mobile payment interface specifically comprises:

10 obtaining rendering data from a specified application by using an operating system, and displaying the mobile payment interface based on the obtained rendering data; and

the executing a mobile payment service based on inputs received through the mobile payment interface specifically comprises:

15 scanning a collection identifier by using the mobile payment interface, parsing the scanned collection identifier to obtain payee information, and sending the payee information to the specified application for mobile payment by using the operating system; and/or

performing mobile payment by using a mobile payment identifier displayed in
20 the mobile payment interface, wherein the mobile payment identifier is obtained from the specified application by using the operating system.

8. The method according to any one of claims 1 to 7, wherein before the executing a mobile payment service based on inputs received through the mobile payment interface, the method further comprises:

25 performing identity verification on the user, and determining that the identity verification on the user succeeds.

9. A mobile payment apparatus, comprising:

a monitoring module, configured to monitor body movements of a user when the apparatus is in a lock screen mode;

30 a display module, configured to display a mobile payment interface when it is determined that the monitored body movement satisfies first specified criteria; and

an execution module, configured to execute a mobile payment service based on inputs received through the mobile payment interface.

10. The apparatus according to claim 9, wherein the monitoring module is

configured to monitor the body movements of the user by using a built-in acceleration sensor; and

the display module is configured to: when it is determined, by using the acceleration sensor, that an acceleration of the apparatus is greater than a specified threshold, determine that the monitored body movement satisfies the first specified criteria.

11. The apparatus according to claim 9, wherein the display module is configured to display a mobile payment interface used to obtain collection information; and/or display a mobile payment interface used to display mobile payment information.

12. The apparatus according to claim 9, wherein the display module is configured to select at least one interface from predetermined available mobile payment interfaces, and display the at least one interface.

13. The apparatus according to claim 12, wherein the display module is configured to: after displaying the mobile payment interface, continue to monitor body movements of the user; and if it is determined that the monitored body movement satisfies second specified criteria, reselect an interface from the available mobile payment interfaces, and display the interface.

14. The apparatus according to claim 11, wherein the mobile payment interface used to obtain collection information specifically comprises an interface used to scan a collection identifier; and the mobile payment interface used to display mobile payment information specifically comprises an interface used to display a mobile payment identifier.

15. The apparatus according to claim 14, wherein the display module is configured to obtain rendering data from a specified application by using an operating system, and display the mobile payment interface based on the obtained rendering data; and

the execution module is configured to scan a collection identifier by using the mobile payment interface, parse the scanned collection identifier to obtain payee information, and send the payee information to the specified application for mobile payment by using the operating system; and/or perform mobile payment by using a mobile payment identifier displayed in the mobile payment interface, wherein the mobile payment identifier is obtained from the specified application by using the operating system.

16. The apparatus according to any one of claims 9 to 15, wherein the apparatus further comprises:

an identity verification module, configured to: before the execution module executes the mobile payment service, perform identity verification on the user, and
5 determine that the identity verification on the user succeeds.

17. A terminal device, comprising one or more processors and memories, wherein the memories store programs, and the programs are configured to be executed by the one or more processors to perform the following steps:

monitoring, by the terminal device, body movements of a user when the terminal
10 device is in a lock screen mode;

displaying a mobile payment interface when it is determined that the monitored body movement satisfies first specified criteria; and

executing a mobile payment service based on inputs received through the mobile payment interface.