

Claims

1. A method of providing continuous access to a resource, the method comprising:
receiving a first request to access a resource by a process ~~from a requestor~~, wherein
the request is received from a first client in a client cluster;
5 associating a first application instance identifier with the ~~first~~ resource;
granting ~~allowing~~ the first request to access ~~to~~ the resource;
receiving a second request to access ~~for~~ the resource by the process ~~from the~~
~~requestor~~ after loss of connection with the first client ~~recovering from a failure~~, wherein
the second request is received from a second client in the client cluster and the second
10 client is different from the first client;
receiving a second application instance identifier associated with the second
request;
determining that ~~if~~ the first ~~application identifier~~ and ~~the~~ second application
instance identifiers are the same; and
15 ~~when the first and second application identifiers are the same, performing the steps~~
~~comprising:~~
invalidating the first request; ~~and~~, wherein invalidating the first request comprises:
determining that the resource is not located on the first node that receives
the second request;
20 sending a request to a second node to invalidate the resource; and
granting the second request to access the resource on the first node.
2. The method of claim 1, wherein the first application instance identifier is
associated with an application instance of an open request.
3. The method of claim 1, wherein the first application instance identifier is
25 associated with the ~~a~~ process.
4. The method of claim 1, wherein the first application instance identifier is
associated with at least one child process of the process ~~an application~~.
5. The method of claim 1, further comprising storing the first application instance
identifier in a registry.
6. ~~The method of claim 1, wherein associating the first application instance identifier~~
30 ~~comprises receiving the first application instance identifier in a~~
~~NETWORK_APP_INSTANCE_ECP_CONTEXT structure.~~
~~6. A method for providing clustered client failover, the method comprising:~~

~~receiving, at a second client, an application instance identifier for a requestor,
wherein the requestor previously accessed a resource using a first client;
sending, from the second client, a second request to access the resource on behalf
of the requestor;
5 sending, from the second client, the application instance identifier for the
requestor;
receiving an indication that a server granted the second request; and
accessing, by the second client, the resource on behalf of the client.~~

~~7. The method of claim 6, wherein the server granting the second request previously
10 granted a first request to access the resource from the first client on behalf of the requestor.~~

~~8. The method of claim 6, wherein the second client sends the second request in
response to a client failover.~~

7. The method of claim 6, wherein the first application instance identifier in the
15 NETWORK_APP_INSTANCE_ECP_CONTEXT structure is added to an Extra Create
Parameter (ECP) list.

8. The method of claim 1, wherein the process comprises an application.

9. A system for facilitating client failover in a clustered environment, the system
comprising:

at least one server comprising:

20 at least one processor configured to execute a first set of computer
executable instructions;

at least one computer readable storage media storing the first set of
computer executable instructions, wherein the first set of computer executable
instructions, that when executed by the at least one processor comprise instructions
25 for provide:

receiving a first request to access a resource from a first client in a
client cluster, wherein the first client sends the first request on behalf of a
process requestor;

30 associating a first application instance identifier with the first
resource;

allowing the process requestor access to the resource;

receiving a second request for the resource from a second client in
the client cluster on behalf of the process after loss of connection with the
first client, wherein the second client is different from the first client;

receiving a second application instance identifier associated with the second request;

determining ~~that if~~ the first ~~application identifier~~ and the second application instance identifiers are the same; and

~~when the first and second application identifiers are the same, performing the steps comprising:~~

invalidating the first request, wherein invalidating the first request comprises; ~~and~~

determining that the resource is not located on the first node that receives the second request;

sending a request to a second node to invalidate the resource; and

granting the second request to access the resource on the first node.

10. The system of claim ~~9~~¹⁸, wherein the system further comprises: the first client, comprising:

at least one processor configured to execute a second set of computer executable instructions;

at least one computer readable storage media storing the second set of computer executable instructions, wherein the second set of computer executable instructions, that when executed by the at least one processor, comprise instructions for:

sending the first request;

sending the first application instance identifier to ~~the~~^a second client.

11. The system of claim 10, wherein the second client further comprises:

at least one processor configured to execute a third set of computer executable instructions;

at least one computer readable storage media storing the third set of computer executable instructions, wherein the third set of computer executable instructions, when executed by the at least one processor, comprise instructions for:

receiving first the application instance identifier from the first client; and sending the second request to access the resource with the application instance identifier.

12. The system of claim 9, wherein the process comprises an application.

13. The system of claim 9, wherein the first application instance identifier is associated with at least one child process of the process.

14. The system of claim 9, wherein the first application instance identifier is associated with an application instance of an open request.

5 15. The system of claim 9, wherein the first application instance identifier is associated with the process.

16. A computer readable storage media, wherein computer storage media is not a signal, storing computer executable instructions that, when executed by a processor, comprise instructions for:

10 receiving a first request to access a resource from a first client in a client cluster, wherein the first client sends the first request on behalf of a process;

associating a first application instance identifier with the first resource;

allowing the process access to the resource;

15 receiving a second request for the resource from a second client in the client cluster on behalf of the process after loss of connection with the first client, wherein the second client is different from the first client;

receiving a second application instance identifier associated with the second request;

determining that the first and second application instance identifiers are the same;

20 and

invalidating the first request, wherein invalidating the first request comprises:

determining that the resource is not located on the first node that receives the second request;

sending a request to a second node to invalidate the resource; and

25 granting the second request to access the resource on the first node.

17. The computer readable storage media of claim 16, wherein the process comprises an application.

18. The computer readable storage media of claim 16, wherein the first application instance identifier is associated with at least one child process of the process.

30 19. The computer readable storage media of claim 16, wherein the first application instance identifier is associated with an application instance of an open request.

20. The computer readable storage media of claim 16, wherein the first application instance identifier is associated with the process.