

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 January 2002 (17.01.2002)

PCT

(10) International Publication Number
WO 02/04392 A1

(51) International Patent Classification⁷: **C07C 27/10**,
67/00, 67/05, 51/02, 51/16, B01J 23/44, 23/48, 23/56,
23/58

MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL,
TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(21) International Application Number: PCT/US01/21184

(22) International Filing Date: 5 July 2001 (05.07.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/612,159 7 July 2000 (07.07.2000) US

(71) Applicant: **SAUDI BASIC INDUSTRIES CORPORA-
TION** [SA/SA]; P.O. Box 5101, Riyadh 11422 (SA).

(71) Applicant and

(72) Inventor: **KHANMAMEDOVA, Alla, Konstantin**
[AZ/US]; 2006 Summerfield Pl., Sugarland, TX 77478
(US).

(74) Agents: **HEWITT, Lester, L.** et al.; Akin, Gump, Strauss,
Hauer & Feld, L.L.P., Pennzoil Place - South Tower, Suite
1900, 701 Louisiana Street, Houston, TX 77002 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM,
HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX,

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted
a patent (Rule 4.17(ii)) for the following designations AE,
AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH,
CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB,
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP,
KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,
MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA,
ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL,
SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ,
MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE,
DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR),
OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML,
MR, NE, SN, TD, TG)
- as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii)) for all designations

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: HIGHLY SELECTIVE SHELL IMPREGNATED CATALYST OF IMPROVED SPACE TIME YIELD FOR PRODUC-
TION OF VINYL ACETATE

(57) Abstract: A shell impregnated catalyst of Pd-Au produced on a silica support to have a Pd loading of 1.8 g/L of catalyst to about 7.2 g/L and a Au to Pd weight ratio of 0.3 to 2.0 by impregnating the support with aqueous solutions of palladium and gold salts or acids and thereafter precipitating water insoluble compounds of Pd and Au on the with alkali metal silicate or hydroxide solutions, then dried, and the surface precipitated compounds of Pd and Au are then reduced by reaction with ethylene or hydrogen at a temperature of greater than 150 °C up to 310 °C or with hydrogen up to 299 °C until substantially all of the Pd and Au contents are reduced to a free metal state, after which the support is impregnated with potassium acetate to an extent of 6 to 7 weight percent of the weight of the total catalyst. For production of vinyl acetate (VA) such catalyst has a space-time yield (STY) and specific activity (SA) about 20-30 % greater than an otherwise identical catalyst composition that is formed from impregnated support reduced at 150 °C, and in a temperature range of 140 °C to 160 °C at a gas hourly space velocity of 4500/hr will at 120 psig exhibit a VA selectivity of 90 % or greater when operated under reaction conditions that result in a STY of at least 600.