

(51) International Patent Classification:  
H04L 29/06 (2006.01)(21) International Application Number:  
PCT/IB2011/052871(22) International Filing Date:  
30 June 2011 (30.06.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
12/854,084 10 August 2010 (10.08.2010) US

(71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET L M ERICSSON (PUBL) [SE/SE]; S-164 83 Stockholm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): AKIL-PON-NUSWAMY, Namadurai [IN/US]; 1180 Reed Avenue Apt. #65, Sunnyvale, California 94086 (US). CHIN-NASWAMY, Sudhagar [IN/US]; 821 Harmony Place, Milpitas, California 95035 (US).

(74) Agents: YEE, William, K. et al.; 6300 Legacy, MS EVR 1-C-11, Plano, Texas 75024 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: LIMITING RESOURCES CONSUMED BY REJECTED SUBSCRIBER END STATIONS




Figure 2

(57) Abstract: A method performed in a network element coupled between a subscriber end station and an AAA server for avoiding AAA processing by at least temporarily suppressing AAA access-request messages for a rejected subscriber end station. The network element receives subscriber session-request messages from the subscriber end station. Subscriber session-request messages include information for verifying an identity that the network element transmits to the AAA server as AAA access-request messages. The network element receives AAA access-response messages corresponding to the AAA access-request messages. Responsive to an AAA access-response message, the network element determines that additional AAA access-request messages should be, at least temporarily, suppressed with regards to the subscriber end station. Responsive to determining, the network element suppresses any additional AAA access-request messages from being transmitted to the AAA server. The suppression of AAA access-request messages conserves execution resources in the network element and the AAA server.