

19 JAN 2000

0 SUBSYNCHRONOUS RELUCTANCE ELECTRICAL MACHINE

The present invention relates to a new reluctance electric machine and, more particularly, to a rotating or linear subsynchronous reluctance machine.

5 As is known by those of skill in the art, one of the best known and most employed types of reluctance electrical machines is the switched reluctance motor, which presents, as a limiting aspect to the use thereof, the existence of torque and speed oscillations, as well as the difficulty of imposing high variation rates in the electric current.

10 Other drawbacks of this switched reluctance motor relates to the fact that the circuits employed for controlling and feeding them are very complex and expensive, specially in respect of high-power machines.

As an alternative to solve the above mentioned drawbacks, the patent application PI9400880-9, published on 10/24/95 and relating to "Reluctance electrical machine" has been proposed, which provided
15 an electrical machine comprised of a rotor and a stator. Said stator was provided with a core comprised of magnetic plates and provided with longitudinal teeth projecting towards the rotor. Said stator also comprised a plurality of grooves capable of receiving a multi-phase winding, said winding being comprised of a plurality of coils
20 homogeneously surrounding the stator's magnetic material. As a supplementation, said rotor was formed by a core of magnetic plates provided with longitudinal teeth projecting towards the stator. Thus, upon energizing of said coils by a balanced multiphase voltage, a

25 rotating field was generated, which caused a relative movement
between rotor and stator.

However, and even though such machine was capable of overcoming
the drawbacks of the prior art, there is still the fact that the electrical
machine described on patent application PI 9400880-9 has the
particular drawback of a low power factor, and in some cases may
30 increase the cost of the drive system.

It is an object of the present invention to provide a reluctance
electrical machine providing high torque at low speeds,
advantageously replacing the switched reluctance, conventional
electrical machines.

35 It is an object of the present invention to provide a reluctance
electrical machine presenting high torques at low speeds,
advantageously replacing in terms of cost and maintenance the
conventional mechanical reduction machines that multiply the torque
and decrease the speed.

40 It is an object of the present invention to provide a reluctance
electrical machine that allows a large control of the rotation and
torque thereof, without the need of a complex and expensive power
and control circuit.

Another object of the present invention is to provide a reluctance
45 electrical machine that, by reason of its constructive features, does not
present oscillations in the resulting torque and speed.

Another object of the present invention is to provide an improvement

on the reluctance electrical machine as per the above described patent application PI 9400880-9, having characteristics of a high power factor.

These and other objects and advantages of the present invention are achieved by a sub-synchronous reluctance electrical machine comprised of a stator provided with a core composed of magnetically uncoupled or weakly coupled sectors of ferromagnetic plates having longitudinal teeth arranged on the face thereof facing the rotor and provided with grooves to house a winding, the latter being comprised of a plurality of coils surrounding the ferromagnetic material, thereby creating a magnetic field when the winding thus defined is energized.

Said rotor is an integral part of the machine and is in turn provided with a core comprised of ferromagnetic plates having longitudinal teeth arranged uniformly along its face turned towards the stator. In addition, the number of teeth on the rotor is necessarily different from the number of teeth on the stator.

The machine is further provided with a device for monitoring and identifying the relative position between the stator and rotor teeth in order to allow the identification of the region of largest magnetic permeability between the rotor and the stator, in order to allow the proper feeding of the stator coils, thereby obtaining the maximum possible torque.

The present invention has constructive characteristics similar to those of the machine described on patent application PI9400880-9, however

it is fundamentally different therefrom in the following items:

- The stator core is comprised of magnetically uncoupled or weakly coupled sectors, contrary to the machine described on the document
75 PI9400880-9, which employs integral magnetic plates; and

- The coils are individually fed with currents controlled and monitored by devices identifying the relative position between the stator and rotor teeth, whereas on the document PI9400880-9 the coils are multiphase and are energized by balanced multiphase voltages.

80 - These differences allow the machine subject matter of the present invention to possess a high power factor, which means that during the operation thereof the machine absorbs low currents.

Accordingly, it is an object of the present invention to provide a sub-synchronous reluctance electrical machine of the type comprising
85 at least one rotor formed of ferromagnetic plates and provided with a plurality of uniformly distributed teeth and at least a stator provided on the surface thereof facing said rotor with a second plurality of teeth, also uniformly arranged, plus windings, said windings being selectively fed by a current power source, and the at least one stator
90 is formed by a series of magnetically uncoupled or weakly coupled sectors of ferromagnetic plates, each sector comprising at least one winding, the at least one winding of each sector having the power thereof controlled by a monitoring device, and the number of teeth on the stator being different from the number of teeth on the rotor.

95 The scope of the present invention will be best understood in the light

of the following description, made with reference to the appended drawings, shown for illustrative purposes only and not as limitation of the scope of the invention, wherein:

- 100 - Figure 1 is a perspective view in partial section of a sub-synchronous reluctance rotating motor made according to the inventive concept defined for the sub-synchronous electrical machine with one winding on the stator, said stator being external to the rotor;
- 105 - Figure 2 is a section view of the motor shown on Figure 1;
- Figure 2a is an enlarged detailed view of the section of the motor on Figure 2;
- Figure 2b is a view similar to Figure 2a, but with the rotor displaced $1/6$ th from the pitch of the stator teeth;
- 110 - Figure 3 is a perspective view in partial section of a sub-synchronous reluctance rotating motor identical to the one shown on Figure 1, but with the stator internal to the rotor;
- Figure 4 is a section view of the motor shown on Figure 3;
- 115 - Figure 5 is a schematic, perspective representation of a sub-synchronous reluctance linear motor made according to the inventive concept defined for the sub-synchronous reluctance electrical machine.
- Figure 6 is a longitudinal section view of the motor shown on Figure 5;
- Figure 7 is a perspective view of a sub-synchronous reluctance disc

120 motor made according to the inventive concept defined for the sub-synchronous reluctance electrical machine.

- Figure 8 is a cross-section view of the motor on Figure 7;

- Figure 9 is a perspective, partial section view of a motor with two stators and two (inner and outer) sub-synchronous reluctance windings
125 made according to the inventive concept defined for the sub-synchronous electrical machine;

- Figure 10 is an elevation view of the shaft end of any of the motors illustrated above, to which is coupled a device for monitoring and identifying the relative position between the rotor and stator teeth; and

130 - Figures 11-11c illustrate in a schematic manner the movement of a linear motor of the type shown on Figure 5.

In accordance with the above figures, the reluctance electrical machine of the present invention is conceptually defined by a stator 10 provided with a core comprised of magnetically uncoupled or
135 weakly coupled ferromagnetic plate sectors 11 having longitudinal teeth 1 arranged on the face thereof turned towards the rotor 20 and provided with grooves 2 for housing one or more windings 6.

These windings 6 are comprised of a plurality of coils surrounding the magnetic material of stator 10, in order to generate a magnetic field
140 whenever this winding is energized.

As an integral part of the sub-synchronous reluctance electrical machine is said rotor 20 which is in turn provided with a core of ferromagnetic plates having longitudinal teeth 21 uniformly arranged

145 along the face thereof turned towards the stator 10, said teeth 21
being in a number different from the number of teeth 1 of stator 10.
More specifically, Figures 1-2 shown a sub-synchronous rotating
motor the shell of which fixedly houses a stator 10 within which is
arranged a rotor 20 supported by shaft 5.

150 As shown, the stator 10 is formed by a plurality of magnetically
uncoupled or weakly coupled sectors 11, and is formed of
ferromagnetic plates, the surface facing the rotor 20 being provided
with a plurality of teeth 1. In addition, said stator is provided with a
series of grooves 2 within which are arranged the windings 6.

155 In a supplementary manner, rotor 20, formed of ferromagnetic plates,
is provided with a plurality of teeth 21 on the surface thereof facing
the stator 10, the number of teeth 21 of rotor 20 being different from
the number of teeth 1 of stator 10.

160 Figures 3-4 illustrate a motor similar to the one described above,
differing therefrom only in that the stator 10 is internal and supported
by shaft 5, whereas the rotor 20 is attached to the motor shell 3.

165 Figures 5-6 illustrate in a very schematic manner a linear motor
wherein the stator 10 and the rotor 20 face each other by means of
respective teeth 1 and 21. The stator 10 in accordance with the
invention is formed of uncoupled or weakly coupled sectors, and the
windings 6 are housed within each sector.

Figures 7-8 in turn illustrate also in a schematic manner a
sub-synchronous disc motor, wherein rotor 20 is attached to the motor

shaft 5 and faces the stator 10 by means of the respective teeth 21 and 1. The stator 10 is formed of a plurality of uncoupled sectors 11, in this case illustrated by only two sectors 11, each provided with grooves to receive the windings 6. Said windings are maintained within each of the sectors 11 of stator 10, specifically inside the respective grooves 2.

Finally, Figure 9 illustrate a sub-synchronous reluctance motor of two stators 10, 10' and two windings 6, 6', made in accordance with the characteristics of the present invention.

More particularly, said motor is formed of a first, external stator 10 attached to shell 3, which surrounds a rotor 20 attached to shaft 5, in a known manner. Said stator 10 is provided with a series of internal teeth 1 which face a series of external teeth 21 of rotor 20. Said rotor 20 is provided internally thereof with a second series of teeth 21' which face a series of teeth 1' of the second stator 10'. In this case, the stators 10, 10' are fixed and have the respective sectors 11, 11' cooperating in an angular position, as are cooperating the respective windings 6, 6'.

The machine is further provided with a monitoring device 4 for relative identification of the teeth of rotor 20 and the teeth of stator 10, as shown on Figure 10. Such device, of a known type, can be for example a resolver or an encoder, and is capable of determining the relative position between the teeth 1 of stator 10 and teeth 21 of rotor 20.

Alternatively, this monitoring device 4 can be comprised, for example, of a position detector based on Hall effect, properly attached to the stator.

195 For a better understanding of the inventive concept now claimed, the operation of the sub-synchronous reluctance electrical machine will be described in a more detailed manner, taking as reference the linear sub-synchronous motor shown on Figure 5.

200 By means of the monitoring device 4 for identification of the relative position of teeth 1 of stator 10 and teeth 21 of rotor 20, the condition indicated on Figure 11 (teeth 1a and 21a aligned) is identified and the coils 6a and 6b are energized, that is, the magnetic field is always maintained at 90° magnetic degrees from the region of highest permeability, thereby causing a displacement of teeth 21 of rotor 20, 205 until they reach an equilibrium position shown on Figure 22a. In this condition, wherein the stator teeth 1e can be seen in alignment with rotor teeth 21e, the coil 6a is de-energized and the subsequent coil 6c is energized, jointly with coil 6b, thereby causing a new displacement of rotor teeth 21 towards the position shown on Figure 11b. In the 210 same sequence, coil 6b is de-energized, and coils 6c and 6d are energized, thereby obtaining a displacement of rotor 20 towards the position shown on Figure 11c, where teeth 1l is seen aligned with teeth 21l, and so on and so forth.

Accordingly, by successively repeating in a controlled manner the 215 operation of energizing and de-energizing the coils, a controlled

movement of rotor 20 is obtained.

As shown on Figure 11, when the windings 6a and 6b of stator 10 are energized, the region of highest permeability between stator 10 and rotor 20 tends to stay in alignment with the field, so that the latter
220 drags with it said region of highest permeability, thereby causing the relative displacement between rotor 20 and stator 10.

While the winding is successively energized and de-energized, the sequence of movements between rotor 20 and stator 10 takes place, so that, upon completion of 360 electrical degrees of field displacement,
225 the rotor 20 will have traversed only two teeth of stator 10.

In the event that the field is placed out of phase by 90° in the opposite direction, an operation in the four quadrants can be obtained, that is, an acceleration or braking torque can be obtained in either of the machine's directions of rotation (clockwise or counterclockwise).

230 The proper combination of the number of teeth 1 of stator 10 with the number of teeth 21 of rotor 20 allows the achievement of torque and determination of the synchronous speed of the sub-synchronous reluctance electrical machine. As already said, the number of teeth of rotor 20 should differ from the number of teeth 1 of stator 10. By way
235 of example, the practical construction illustrated on Figure 1 shows a stator with 144 teeth and a rotor with 146 teeth.

The speed of rotor 20 is a function of the number of teeth of said rotor 20 and a function of the triggering frequency of the power source (not illustrated), that is, in a more specific manner, the speed

240 of rotor 20 is directly proportional to the triggering speed of the
power source and inversely proportional to the number of teeth 21 of
rotor 20. Accordingly, it can be concluded that with a proper selection
of the number of teeth 21 of rotor 20 it is easy to obtain any rated
rotation or speed, with the variation of the power source switching
245 frequency further allowing the achievement any rotation or speed,
from zero to the rated value.

Even though some constructive models for the sub-synchronous
electrical machine have been described and illustrated, it should be
emphasized that the inventive concept can be applied to any type of
250 configuration or employ any type of power source for the winding 6
of stator 10.

In particular, said power source (not illustrated) should have as a
feature thereof the possibility of being directly or indirectly controlled
by the monitoring device 4, thereby to feed the windings 6 of sectors
255 11, according to the relative position between stator 10 and rotor 20.

In respect of the monitoring device 4, in addition to the preferred
types described above, use could be made of any device capable of
accurately determining the relative position between stator 10 and
rotor 20, and that may control a power source for the windings 6,
260 either directly or through an interface.

On the other hand, the internal position adopted for the winding 6 can
also be modified, such as, for example, by arranging the winding or
windings 6 around the teeth 1 of stator 10. Another alternative is

arranging the winding 6 around each of the sectors 11, thereby
265 completely surrounding each said sector 11. In addition, each sector
may comprise more than one winding 6, each fed separately by a
respective power source.



0

Claims

5

10

1. Sub-synchronous Reluctance Electrical Machine of the type comprising at least one rotor 20 formed of ferromagnetic plates and provided with a plurality of uniformly distributed teeth 21, and at least one stator 10 provided with a second plurality of teeth 1 also uniformly distributed thereon, plus windings 6, said windings 6 being selectively fed by a current power source, characterized in that the at least one stator 10 is formed of a series of magnetically uncoupled or weakly uncoupled sectors 11 of ferromagnetic plates, each sector 11 comprising at least one winding 6, the at least one winding 6 of each sector 11 having the power thereof controlled by a monitoring device 4, the number of teeth 1 of stator 10 being different from the number of teeth 21 of rotor 20.

15

2. Machine in accordance with claim 1, characterized in that each winding 6 is preferentially arranged in a groove 2 of sector 11 of stator 10.

20

3. Machine in accordance with claim 1, characterized in that the current power source for windings 6 is controlled by a device 4 monitoring the relative position between teeth 1 of stator 10 and teeth 21 of rotor 20, said monitoring device 4 being a Hall-type detector.

4. Machine in accordance of claim 3, characterized in that said monitoring device is alternately an encoder or a resolver.

5. Machine in accordance with claim 1, characterized in that it is a sub-synchronous reluctance rotating motor.



- 25 6. Machine in accordance with claim 1, characterized in that it
is a sub-synchronous reluctance linear motor.
7. Machine in accordance with claim 1, characterized in that it
is a sub-synchronous reluctance disc motor.
- 30 8. Machine in accordance with claim 1, characterized in that it
is a motor comprising two or more stators 10, 10' and two or more
sub-synchronous reluctance windings 6.