



- (51) International Patent Classification:
E21B 33/038 (2006.01) *E21B 17/01* (2006.01)
- (21) International Application Number:
PCT/US2011/064582
- (22) International Filing Date:
13 December 2011 (13.12.2011)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/422,506 13 December 2010 (13.12.2010) US
13/102,676 6 May 2011 (06.05.2011) US
- (71) Applicant (for all designated States except US): CAMERON INTERNATIONAL CORPORATION [—US];
1333 West Loop South, Suite 1700, Houston, Texas 77027 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VANDERFORD, Delbert Edwin [US/US]; 12311 Pine Glen Lane, Cypress,

Texas 77429 (US). VAN ADRICHEM, Max [NL/US];
4266 T.C. Jester Blvd., Houston, Texas 77018 (US).

- (74) Agent: ROSE, Collin, A.; Chamberlain Hrdlicka, 1200
Smith Street, 14th Floor, Houston, Texas 77002 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,

[Continued on next page]

- (54) Title: ADJUSTABLE RISER SUSPENSION AND SEALING SYSTEM




FIG. 1

(57) Abstract: An adjustable riser suspension system for suspending a riser under tension including a riser hanger, a mating sleeve rotationally coupled to the riser hanger, a ratchet-latch sleeve located inside the mating sleeve with an external profile configured to engage an internal profile of the mating sleeve and an internal profile configured to engage an externally threaded face of the riser. The riser hanger and mating sleeve are configured to move downward relative to the riser such that the mating sleeve fits over at least a portion of the riser, causing the ratchet-latch device to ratchet over the external threads of the riser. The mating sleeve is configured to rotate relative to the riser, causing the internal and external profiles of ratchet-latch device to lock the riser and the mating sleeve to prevent movement of the riser relative to the mating sleeve.



DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT,
LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE,
SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

27 December 2012