

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 March 2005 (17.03.2005)

PCT

(10) International Publication Number
WO 2005/024485 A1

(51) International Patent Classification⁷: **G02B 17/08**
(21) International Application Number:
PCT/IL2004/000812

(22) International Filing Date:
9 September 2004 (09.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
157836 10 September 2003 (10.09.2003) IL

(71) Applicant (for all designated States except US): **LUMUS LTD.** [IL/IL]; 24B Hess Street, Rehovot 76346 (IL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **AMITAI, Yaakov** [IL/IL]; Sireni Street 36/4, 76229 Rehovot (IL).

(74) Agent: **WOLFF BREGMAN AND GOLLER**; P.O. Box 1352, 91013 Jerusalem (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: OPTICAL DEVICES PARTICULARLY FOR REMOTE VIEWING APPLICATIONS



(57) Abstract: There is provided an optical device for transferring light within a given field-of-view, comprising an input aperture; reflecting surfaces (4, 6), and an output aperture located in spaced-apart relationship from the input aperture such that light waves, located within the field-of-view, that enter the optical device through the input aperture, exit the optical device through the output aperture, wherein the reflecting surfaces are at least one pair of parallel reflecting surfaces (42a, 42b, 44a, 44b) and that part of the light waves located within the field-of-view that enter the input aperture, pass directly to the output aperture without being reflected off the at least one pair of parallel reflecting surfaces, while another part of the light waves within the field-of-view that enters the input aperture, arrives at the output aperture after being twice reflected by the at least one pair of parallel reflecting surfaces.

WO 2005/024485 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.