CLAIMS

1. A patch for relieving lumbago, the patch comprising a backing and an adhesive layer laminated on the backing, wherein

the adhesive layer comprises an adhesive base and 0.70 to 1.50 mg of diclofenac sodium per cm^2 of application area, ~~and~~

the adhesive base comprises at least one selected from the group consisting of a styrene-isoprene-styrene block copolymer and a polyisobutylene, and

the patch is used by applying the patch once a day to a chest region, an abdominal region, a dorsal region, a brachial region, or a femoral region of a human.

2. The patch according to claim 1, wherein the adhesive base comprises ~~at least one selected from the group consisting of a styrene-isoprene-styrene block copolymer and a polyisobutylene.~~

~~3. The patch according to claim 2, wherein the adhesive base comprises~~ the styrene-isoprene-styrene block copolymer and the polyisobutylene.

4~~3~~. The patch according to ~~any one of claims~~ claim 1 ~~to 3~~or 2, wherein the adhesive layer further comprises dimethyl sulfoxide.

5~~4~~. The patch according to any one of claims 1 to 4~~3~~, wherein the adhesive layer comprises an organic acid.

5. The patch according to ~~6. The patch according to~~ claim 5~~4~~, wherein the organic acid is oleic acid.

~~7. The patch according to~~ 6. The patch according to any one of claims 1 to 6~~5~~, wherein the adhesive layer further comprises a tackifier.

~~8~~7. The patch according to claim ~~7~~6, wherein the tackifier is an alicyclic saturated hydrocarbon resin and a hydrogenated rosin glycerol ester.

~~9~~8. The patch according to any one of claims 1 to ~~8~~7, wherein the adhesive layer comprises a plasticizer.

~~10~~9. The patch according to claim ~~9~~8, wherein the plasticizer is liquid paraffin.

10. The patch according to any one of claims 1 to 9, wherein a content of diclofenac sodium is 50 to 100 mg.

11. The patch according to any one of claims 1 to 10, wherein ~~a content~~the number of ~~diclofenac sodium~~patches per application is ~~50~~1 to ~~100 mg~~3.

12. The patch according to any one of claims 1 to 11~~, wherein the number of patches per application is 1 to 3.~~

~~13. The patch according to any one of claims 1 to 12~~, wherein the backing is a polyethylene terephthalate knitted fabric having a water vapor transmission rate of 1000 g/m^2·24 hr or more.

~~14~~13. The patch according to any one of claims 1 to ~~13~~12, wherein an application area is 50 to 150 cm^2.