

This Sheet Has Been Replaced



RECEIVED SHEETS	
✓	1
✓	11
✓	49
✓	12

SEMICONDUCTOR MEMORY STRUCTURES AND PHASE
SHIFTING MASKS THEREFOR

This invention relates to semiconductor memory structures and
5 phase shifting masks therefor. The invention can be applied, for
example, to CMOS memory cells.

The dimensions of semiconductor devices tend to get smaller
and smaller year by year.

In the technology of photolithography employed for the
10 manufacture of miniaturized semiconductor devices, there is known, as
a means for improving the resolution, a phase shifting technique which
causes a phase difference in the light wave transmitted through a
mask. This phase shifting method is disclosed in Japanese laid-open
patent specification 58/173744; and also in Marc D. Levenson et al.,
15 "Improving Resolution in Photolithography with a Phase-Shifting Mask,
IEEE transactions on Electron Devices, Vol. ED-29, No. 12, December
1982, pages 1828 to 1836.

The known phase shifting method will now be described with
reference to Figure 9. In the case of forming a line-and-space
20 pattern, it is usual that, as shown in Figure 9A, a light shielding
region 10 is formed by the use of a light shielding material such as
chromium on a transparent substrate 1 of quartz or the like, and an
arrangement of repeated line-and-space patterns is formed to produce
an exposure mask. The intensity distribution of the light transmitted
25 through such an exposure mask is represented by a curve A1 in Figure
9A, wherein the intensity is zero in the light shielding region 10,
while the light is transmitted through the other portions (light
transmitting portions 12a and 12b). Viewing one light transmitting
portion 12a as an example, the intensity of the light transmitted
30 therethrough and irradiated on a work member to be exposed is
distributed as represented by a curve A2 in Figure 9A, wherein hill-
like maxima exist on both sides due to diffraction of the light and so
forth. The light passed through the light transmitting portion 12b is
represented by a one-dot chain line. When the light rays obtained
35 through the individual light transmitting portions 12a and 12b are
mutually combined, the light intensity distribution is deprived of its
sharpness as indicated by a curve A3, consequently to blur the image



due to diffraction of the light. In contrast therewith, if phase shifting films 11a are provided on the light transmitting portions 12a and 12b of the repeated patterns alternately as shown in Figure 9B, any blur of the image resulting from diffraction of the light is eliminated by inversion of the phase, so achieving transfer of a sharp image, thereby improving the resolution and the focusing tolerance. More particularly, when the phase shifting film 11a is formed on the light transmitting portion 12a as shown in Figure 9B in such a manner as to cause a phase shift of 180° for example, the light passed through the phase shifting film 11a is inverted as represented by a curve B1. Meanwhile the light obtained through the adjacent light transmitting portion 12b is not passed through the phase shifting film 11a, so that no such phase inversion occurs. Therefore, on the work member to be exposed, the mutually phase-inverted light rays cancel each other in the position B2 at the feet of the light intensity distribution, whereby the distribution of the light irradiated on the work member is rendered ideally sharp as represented by a curve B3 in Figure 3B.


In the example mentioned, the greatest advantage is attainable by causing a 180° inversion of the phase to ensure the above-described effect. However, for realizing such a satisfactory result, it is necessary for the phase shifting film 11a to have an adequate thickness

$$d = \frac{\lambda}{2(n-1)}$$

(where n denotes the refractive index of the phase shifting film, and λ denotes the wavelength of the exposure light).

In the process of forming a pattern by exposure, it is customary that a member used for reduced-size projection is termed a reticle, and a member for life-size projection is termed a mask; or a member corresponding to an original sheet is termed a reticle, and a member obtained by duplicating such a reticle is termed a mask. In this specification, any of the masks and reticles classified by such various definitions are included in the term mask.

However, in the known phase shifting exposure mask, there are some difficulties in using it for forming a complicated pattern,



although it is effective for forming a relatively simple pattern with a line-and-space or contact hole arrangement for example.

5 The pattern of a semiconductor memory device such as a CMOS memory cell is generally complicated, as shown in Figure 7. In this diagram, A denotes a diffused layer portion, and B denotes a LOCOS portion. As the design becomes finer from say $0.5\mu\text{m}$ down to 0.3 to $0.35\mu\text{m}$, accurate patterning in a general exposure mask is rendered more difficult, and employment of the phase shifting method is considered necessary. However, in such a complicated pattern as shown
10 in Figure 7, for example, the desired effect is barely attainable by the phase shifting technique. In a case where the minimum line width of the pattern in Figure 7 is $0.3\mu\text{m}$ and the light intensity distribution is calculated with an exposure to the light emitted from a KrF excimer laser, there is hardly any observable difference between
15 the result obtained without (Figure 8A) or with (Figure 8B) the phase shifting technique. In either case, the pattern deviates considerably from the required one. Denoted by C in Figure 8B is a pattern to be formed continuously. In this drawing, the pattern is divided into two parts due to the necessity of causing a phase inversion, and therefore
20 the light intensity distribution becomes as illustrated.

According to the present invention there is provided a semiconductor memory structure comprising:
a pattern layer having a plurality of elemental patterns; and
another pattern layer having, in a single cell or adjacent cells, more
25 than one pair of elemental patterns including mutually proximate parallel portions.

According to the present invention there is also provided a phase shifting mask for use in producing a semiconductor memory device, the mask comprising:
30 a light shielding region, light transmitting portions and phase shifting films on a substrate transparent to the wavelength of exposure light;
wherein said light transmitting portions and said phase shifting films constitute pairs each including mutually proximate parallel portions.

35 A first embodiment of the present invention comprises a pattern layer having a plurality of elemental patterns, and another pattern layer having, in a single cell or adjacent cells, more than



one pair of elemental patterns including mutually proximate parallel portions, thereby achieving effective formation of a desired pattern with a phase shifting mask.

5 A second embodiment of the present invention comprises a phase shifting mask having a light shielding region, light transmitting segments and phase shifting films on a substrate transparent to the wavelength of exposure light, wherein the light transmitting segments and the phase shifting films constitute pairs each including mutually proximate parallel portions. Such an
10 embodiment is effectively utilizable as a mask for patterning a semiconductor memory device which has pairs of elemental patterns each including mutually proximate parallel portions.

The invention will now be described by way of example with reference to the accompanying drawings, throughout which like parts
15 are referred to by like references, and in which:

Figure 1 is view of a phase shifting mask used for a first embodiment of the invention;

Figures 2A and 2B illustrate the phase shifting mask in more detail;

20 Figure 3 shows the light intensity distribution obtained by a known mask;

Figures 5A and 5B show the first embodiment of semiconductor memory structure;

25 Figures 6A and 6B show a second embodiment of semiconductor memory structure;

Figure 7 is a view of a known memory cell pattern;

Figure 8A and 8B show the intensity distributions of exposure light in forming the pattern of Figure 7; and

30 Figures 9A and 9B illustrate the principle of a phase shifting mask.

A semiconductor memory structure comprises a pattern layer having a plurality of elemental patterns, and another pattern layer having, in a single cell or adjacent cells, more than one pair of elemental patterns including mutually proximate parallel portions.

35 In this specification, an "elemental pattern" connotes any of various patterns required for forming a semiconductor memory structure, such as a diffused layer pattern, an element isolating



region, or a wiring pattern.

A "cell" is a general term including at least one semiconductor device which constitutes a memory. In this specification, the concept of a cell connotes one unit having a plurality of elemental patterns. And a pattern layer signifies a layer which comprises such elemental patterns and is existent over two or more cells.

Also in this specification, the requisite of "elemental patterns including mutually proximate parallel portions" is that the elemental patterns themselves are mutually proximate and parallel to each other in the longitudinal direction thereof or at least have mutually proximate and parallel portions such as one side of each pattern. Another requisite is satisfied if at least one pair of elemental patterns having such interrelation exist in the pattern layer. Meanwhile, "proximate" signifies a positional adjacency adequate for attaining at least the effect of the phase shift. For this purpose, it is generally desired that the proximity or adjacency be such as corresponding to the wavelength of exposure light employed.

A phase shifting mask is provided for use in producing a semiconductor memory device and has a light shielding region, light transmitting segments and phase shifting films on a substrate transparent to the wavelength of exposure light, wherein the light transmitting segments and the phase shifting films constitute pairs each including mutually proximate parallel portions.

In this specification, "transparent to the wavelength of exposure light" signifies "capable of passing or transmitting the wavelength of employed exposure light therethrough". The phase shifting film serves to cause a desired shift in the phase of the transmitted light. Generally such a film is composed of a material transparent to the exposure light wavelength and has a thickness adequate for inducing a desired phase shift. The material and the thickness of the film may be so determined selectively as to attain a phase inversion of 180° or any desired amount of phase shift such as 90° or 270° in conformity with each design. For example, in a preferred embodiment of this invention, the film thickness d is given by:



$$d = \frac{\lambda}{2(n-1)}$$

for achieving a phase shift of 180° . In the above equation, n denotes the refractive index of the phase shifting film and is therefore
5 determine by the material of the film, and λ denotes the exposure wavelength which is determined by the exposure light employed.

The light shielding region may be composed of any suitable material such as chromium which is capable of absorbing and thereby shielding the exposure light employed.

10 First Embodiment

This embodiment corresponds to a semiconductor memory device, more specifically to a CMOS memory device obtained by using a phase shifting mask.

15 First a description will be given of the phase shifting mask used in this embodiment.

The phase shifting mask shown in Figure 1 is used for forming a diffused layer in the semiconductor memory structure of this embodiment. As illustrated, the phase shifting mask comprises a light shielding region 10, light transmitting portions 12, 14, 16, 18 and
20 20, and phase shifting films 11, 13, 15, 17 and 19 formed on a substrate 1 transparent to the wavelength of exposure light, wherein the light transmitting portions and the phase shifting films form more than one pair having mutually proximate parallel portions. Denoted in Figure 1 by 11, 12; 13, 14; 15, 16; 17, 18; and 19, 20 are pairs each
25 consisting of one light transmitting portion and one phase shifting film. More specifically, the pairs are arranged to have such a positional relationship that, as illustrated, the rectangular light transmitting portions and the rectangular phase shifting films are disposed parallel with each other in the longitudinal direction.

30 In this embodiment, the substrate 1 is composed of silicon dioxide (SiO_2) or quartz, and the light shielding region 10 is obtained by evaporation of chromium in the shape of a film on the substrate 1. The light transmitting portions 12, 14, 16, 18 and 20 are so formed as to expose the substrate material directly for
35 permitting transmission of the exposure light therethrough. The light transmitting portions 12, 14, 16, 18 and 20 are patterned in such a manner that none of the light shielding region 10 is existent thereat.



The phase shifting films 11, 13, 15, 17 and 19 are so formed as to cause a 180° phase inversion of the exposure light. In this embodiment, such film is composed of silicon dioxide to have a thickness of 500 nm. Some other suitable material may alternatively
5 be selected on condition that it retains a phase shifting effect, and a resist material may also be used to form each phase shifting film.

The semiconductor memory structure of this embodiment is shown in Figure 5A, wherein elemental patterns 31 to 36 exist in a single pattern layer. The pattern layer has, in one cell or mutually
10 adjacent cells (reference numeral 3 denotes a cell unit), more than one pair of elemental patterns each having mutually proximate parallel portions. In the structure of this embodiment, the patterns 31 and 32 of diffused layers form a pair having mutually proximate parallel portions. Similarly the patterns 33 and 34, and the patterns 35 and
15 36 constitute such a pair, respectively. Each pattern is composed of a diffused layer to fabricate a transistor structure. Denoted by 37 and 38 in Figure 5A are gate electrode patterns which are in another pattern layer different from that of the elemental patterns 31 to 36. Figure 5B is a circuit diagram representing the structure of Figure
20 5A. Denoted by Q1 to Q4 and a to d are a transistor structure and a connection structure respectively, which show the relationship of mutual correspondence between the configurations of Figures 5a and 5B. In Figure 5B, W.L. stands for a word line, and B.L. for a bit line.

In this embodiment, the diffused layers of the patterns 31
25 and 32 form a driver transistor and are therefore shaped to be greater than the other diffused layer patterns 33 to 36 as illustrated in Figure 5A.

The semiconductor memory structure of Figure 5A corresponds to the phase shifting mask of Figure 1, and the phase shifting film 11
30 and the light transmitting portion 12 in the phase shifting mask correspond respectively to the diffused layer patterns 31 and 32 of the semiconductor memory structure. Furthermore, the pair 13 and 14 and the pair 15 and 16 in Figure 1 correspond respectively to the pair of patterns 33 and 34 and the pair of patterns 35 and 36 in Figure 5A.

35 Patterns existing in one pattern layer in the structure of Figure 5A can be formed in a satisfactory state by the phase shifting mask of Figure 1, as will be ensured also from the following.



Figure 3 shows the calculated light intensity distribution when the patterns of Figure 5A are formed by using the phase shifting mask of Figure 1 under the conditions including a minimum line width of $0.3\ \mu\text{m}$ and the employment of a KrF excimer laser. In contrast therewith, Figure 4 shows the result of calculating the light intensity distribution when similar patterns are formed under the same conditions as the above by using a known mask without the phase shifting process. It is apparent from a comparison of these two results that an enhanced pattern accuracy can be attained by using the mask of this embodiment.

Particularly in the use of the known mask as shown in Figure 4, the individual rectangular pattern has a rounded elliptical light distribution. It is obvious that the light distribution represented by 121 and 111 in Figure 4 is substantially elliptical, in contrast with the substantially rectangular distribution represented by 120 and 110 in Figure 3. Moreover in the known example of Figure 4, the light distribution of the mutually adjacent patterns are proximate to each other, particularly in the portions 100 thereof, and the patterns obtained actually by exposure and development become coarser than the original light distributions, whereby the patterns are extended consequently to cause a fault that the portions, which are not to be connected, are connected. To prevent such faults, it is necessary further to increase the tolerance, so that eventually the known mask cannot be used for forming extremely fine patterns. Meanwhile in the case of Figure 3, the portions 100 are sufficiently spaced apart from each other, so that adequate patterns can be formed without any problem. The light distributions are substantially parallel and satisfactory in the mutually proximate portions of the patterns 120 and 110 in Figure 3, whereas the distributions in the patterns 121 and 111 in Figure 4 are not mutually parallel, and are so constricted inward of rectangles as to be in the shape of gourds.

Thus, it is rendered possible, by means of such a phase shifting mask, to realize finer patterns than the known ones. Furthermore, when using the same light source and the same stepper (reduced-size exposure projector), the patterns can be made more minute than those obtained by the known mask, hence achieving the structure of Figure 5A in a satisfactory state.



The mask shown in Figure 2A is an example for forming a layer, which is to be in contact with the aforementioned pattern layer, to form gate electrodes 37 and 38 in Figure 5A. In this example, the gate electrodes 37 and 38 can be formed of light transmitting segments 21 and 22 without employing a mask according to the present invention. Since the two light transmitting segments are disposed to be mutually parallel, it is a matter of course that, if they are sufficiently proximate to each other, this example is shapable as a phase shifting mask by adopting a mask according to the present invention. In Figure 2A, there are also shown light transmitting portions 23 and 24 for forming gate electrodes in adjacent cells.

Figure 2B illustrates a structure obtained by superposing the masks of Figures 1 and 2A on each other, wherein gate-forming mask patterns 21 to 24 are represented by broken lines. The structures of Figure 2B substantially corresponds to the entirety of Figure 5A.

In this embodiment where exposure light is emitted from a KrF excimer laser, an excellent result is attainable with the minimum line width diminished to $0.3 \mu\text{m}$.

In the case of employing G rays (wavelength $0.45 \mu\text{m}$) or the like, the space between parallel proximate portions is set to $0.5 \mu\text{m}$ or so.

It is preferred that the space between the mutually proximate parallel segments be substantially equal to the wavelength of the exposure light employed.

Denoted by reference numeral 4 in Figure 5A is silicon dioxide serving for isolation of elements.

In this embodiment, as described above, an improvement is achieved in the complicated elemental patterns of a CMOS memory by adopting the phase shifting method, so that extremely fine patterns can be formed. This permits dimensional reduction of cells as well.

Second Embodiment

Figures 6A and 6B show another exemplary semiconductor memory structure, wherein Figure 6A illustrates its form, and Figure 6B is a circuit diagram corresponding thereto. This embodiment is a modification of the structure shown in Figure 5A, wherein the diffused layers D and D' of adjacent cells (Figure 5A) are connected together



to be common as represented by D", so that the vertical dimension of each cell is diminished. As compared with one cell unit of Figure 5A having a vertical length of $3.8 \mu\text{m}$ and a horizontal length of $2.4 \mu\text{m}$, the corresponding dimensions in this embodiment can be
5 reduced to $3.5 \mu\text{m}$ and $2.1 \mu\text{m}$ respectively.

Figure 6 shows a word line (W.L.), and the same reference numerals and symbols as those used in Figure 5 denotes the same or corresponding components.

In this second embodiment also, the semiconductor memory
10 device can be produced effectively by using a phase shifting mask according to the present invention with corresponding patterns.



(6

CLAIMS

1. A semiconductor memory structure comprising:
a pattern layer having a plurality of elemental patterns; and
5 another pattern layer having, in a single cell or adjacent cells, more
than one pair of elemental patterns including mutually proximate
parallel portions.
2. A phase shifting mask for use in producing a semiconductor
10 memory device, the mask comprising:
a light shielding region (10), light transmitting portions (12) and
phase shifting films (11) on a substrate (1) transparent to the
wavelength of exposure light;
wherein said light transmitting portions (12) and said phase shifting
15 films (11) constitute pairs each including mutually proximate parallel
portions.

