METHOD AND APPARATUS FOR ACHIEVING FLEXIBLE BANDWIDTH USING VARIABLE GUARD BANDS

[0001] The present application claims priority to provisional U.S. Application Serial No. 60/731,028, entitled "A METHOD AND APPARATUS FOR ACHEVING A FLEXIBLE BANDWIDTH USING GUARD CARRIERS," filed October 27, 2005, assigned to the assignee hereof and incorporated herein by reference.

BACKGROUND

I. Field

[0002] The present disclosure relates generally to communication, and more specifically to techniques for data transmission in a wireless communication system.

II. Background

[0003] Wireless communication systems are widely deployed to provide various communication services such as voice, video, packet data, messaging, broadcast, etc. These systems may be multiple-access systems capable of supporting communication for multiple users by sharing the available system resources. Examples of such multiple-access systems include Code Division Multiple Access (CDMA) systems, Time Division Multiple Access (TDMA) systems, Frequency Division Multiple Access (FDMA) systems, Orthogonal FDMA (OFDMA) systems, and Single-Carrier FDMA (SC-FDMA) systems.

[0004] A wireless communication system is typically designed for a specific bandwidth. Various system parameters such as sample rate, frame duration, etc., may be selected based on the system bandwidth to achieve the desired performance. The system may be deployed in different geographic regions where different bandwidths may be available. Different sets of system parameter values may then be selected for use for the different bandwidths. However, the parameter selection may be a difficult task if a large number of bandwidths are possible. Furthermore, there may be constraints on some parameters, which may make selection of other parameters more difficult or impossible.

[0005] There is therefore a need in the art for techniques to flexibly support different bandwidths.

SUMMARY

[0006] Techniques to support different bandwidths in a wireless communication system are described herein. In an aspect, the system supports a configurable operating bandwidth using a fixed design bandwidth and variable guard bands. Values for various parameters such as fast Fourier transform (FFT) size, cyclic prefix length, and sample rate may be selected based on the design bandwidth. The design bandwidth may be associated with K total subcarriers, where $K > 1$. The operating bandwidth may be associated with N usable subcarriers, where $K \geq N > 1$. Different operating bandwidths may be easily supported by selecting different numbers of usable subcarriers. The remaining $K - N$ subcarriers are guard subcarriers that are not used for transmission. A transmitter and a receiver may perform processing for a transmission using the same FFT size, cyclic prefix length, and sample rate regardless of the selected operating bandwidth.

[0007] In another aspect, the system may use different operating bandwidths and/or different parameter values for different portions of a transmission. A first operating bandwidth (or a first set of subcarriers) may be used for a first portion of the transmission. A second operating bandwidth (or a second set of subcarriers) may be used for a second portion of the transmission. The first portion may correspond to a preamble, and the second portion may correspond to a main body of the transmission. The first and second portions may be associated with the same or different design bandwidths. Each design bandwidth may be associated with a specific set of parameter values to use for transmission.

[0008] Various aspects and features of the disclosure are described in further detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 shows a wireless communication system.

[0010] FIG. 2 shows a block diagram of a base station and a terminal.

[0011] FIG. 3 shows an OFDM modulator for a fixed operating bandwidth.

[0012] FIG. 4 illustrates configurable operating bandwidth and variable guard bands.

[0013] FIG. 5A shows a subcarrier structure for a fixed design bandwidth.

[0014] FIG. 5B shows a subcarrier structure for a configurable operating bandwidth.

[0015] FIG. 6 shows an OFDM modulator for configurable operating bandwidth.

[0016] FIG. 7 shows an OFDM demodulator for configurable operating bandwidth

[0017] FIGS. 8 and 9 show a process and an apparatus, respectively, for transmission with configurable operating bandwidth.

[0018] FIG. 10 shows a super-frame structure.

[0019] FIG. 11 shows use of different bandwidths for different portions of a transmission.

[0020] FIGS. 12 and 13 show a process and an apparatus, respectively, for transmission with different bandwidths for different portions.

DETAILED DESCRIPTION

[0021] **FIG. 1** shows a wireless communication system 100 with multiple base stations 110. A base station is generally a fixed station that communicates with the terminals and may also be referred to as an access point, a Node B, an enhanced Node B (eNode B), etc. Each base station 110 provides communication coverage for a particular geographic area. The term "cell" can refer to a base station and/or its coverage area depending on the context in which the term is used. To improve system capacity, a base station coverage area may be partitioned into multiple smaller areas, e.g., three smaller areas. Each smaller area may be served by a respective base transceiver subsystem (BTS). The term "sector" can refer to a BTS and/or its coverage area depending on the context in which the term is used. For a sectorized cell, the BTSs for all sectors of that cell are typically co-located within the base station for the cell.

[0022] Terminals 120 may be dispersed throughout the system. A terminal may be stationary or mobile and may also be referred to as an access terminal, a mobile station, a user equipment, a mobile equipment, a station, etc. A terminal may be a cellular phone, a personal digital assistant (PDA), a wireless modem, a wireless communication device, a handheld device, a subscriber unit, etc. A terminal may communicate with one or more base stations via the downlink and uplink. The downlink (or forward link) refers to the communication link from the base stations to the terminals, and the uplink

(or reverse link) refers to the communication link from the terminals to the base stations.

[0023] A system controller 130 may couple to base stations 110 and provide coordination and control for these base stations. System controller 130 may be a single network entity or a collection of network entities. System controller 130 may comprise a Radio Network Controller (RNC), a Mobile Switching Center (MSC), etc.

[0024] The techniques described herein may be used for various communication systems such as multiple-access systems (e.g., CDMA, FDMA, TDMA, OFDMA, and SC-FDMA systems), broadcast systems, wireless local area networks (WLANs), etc. The terms "systems" and "networks" are often used interchangeably. OFDMA systems and some broadcast systems utilize Orthogonal Frequency Division Multiplexing (OFDM). SC-FDMA systems utilize Single-Carrier Frequency Division Multiplexing (SC-FDM). OFDM and SC-FDM partition the system bandwidth into multiple (K) orthogonal subcarriers, which are also commonly referred to as tones, subbands, bins, etc. Each subcarrier may be modulated with data. OFDM sends modulation symbols in the frequency domain on the subcarriers whereas SC-FDM sends modulation symbols in the time domain on the subcarriers. For clarity, the techniques are described below for an OFDM-based system, which is a system that utilizes OFDM. An OFDM-based system may be an OFDMA system, a broadcast system, a system utilizing multiple radio technologies (e.g., OFDM on the downlink and CDMA on the uplink), etc.

[0025] **FIG. 2** shows a block diagram of a base station 110 and a terminal 120, which are one of the base stations and one of the terminals in FIG. 1. At base station 110, a transmit (TX) data processor 210 receives different types of data such as, e.g., traffic data from a data source (not shown) and signaling from a controller/processor 240. As used herein, "data" generically refers to any type of data such as, e.g., traffic data, signaling, overhead data, control data, pilot, broadcast data, messages, etc. Processor 210 processes (e.g., formats, encodes, interleaves, and symbol maps) the different types of data and provides modulation symbols. An OFDM modulator 220 processes the modulation symbols for OFDM and provides output samples or chips. A transmitter (TMTR) 222 processes (e.g., converts to analog, amplifies, filters, and frequency upconverts) the output samples and generates a downlink signal, which is transmitted via an antenna 224.

[0026] At terminal 120, an antenna 252 receives the downlink signals from base station 110 and possibly other base stations and provides a received signal to a receiver (RCVR) 254. Receiver 254 conditions (e.g., filters, amplifies, frequency downconverts, and digitizes) the received signal and provides received samples. An OFDM demodulator (Demod) 260 processes the received samples for OFDM and provides received symbols. A receive (RX) data processor 270 processes (e.g., detects, symbol demaps, deinterleaves, and decodes) the received symbols and provides decoded data for terminal 120.

[0027] On the uplink, at terminal 120, data is processed by a TX data processor 290, modulated by an OFDM modulator 292, conditioned by a transmitter 294, and transmitted via antenna 252. At base station 110, the uplink signals from terminal 120 and other terminals are received by antenna 224, conditioned by a receiver 230, demodulated by an OFDM demodulator 232, and processed by an RX data processor 234 to recover data sent by the terminals. In general, the processing for uplink transmission may be similar to or different from the processing for downlink transmission.

[0028] Controllers 240 and 280 direct the operations at base station 110 and terminal 120, respectively. Memories 242 and 282 store data and program codes for base station 110 and terminal 120, respectively.

[0029] An OFDM-based system typically partitions a total bandwidth of W Hertz into K total subcarriers. K is typically a power of two in order to enable faster processing by using fast Fourier transform (FFT) and inverse FFT (IFFT) operations. K modulation symbols may be sent on the K total subcarriers, one modulation symbol per subcarrier, in each OFDM symbol period.

[0030] **FIG. 3** shows a block diagram of an OFDM modulator 220a, which may be used for OFDM modulators 220 and 292 in FIG. 2. Within OFDM modulator 220a, a serial-to-parallel converter 320 receives modulation symbols for data (e.g., traffic data, signaling, pilot, etc.) and maps these modulation symbols to the K total subcarriers. The mapped modulation symbols are denoted as $V(k)$, where k is an index for subcarriers. An IFFT unit 324 receives K modulation symbols for the K total subcarriers in each OFDM symbol period, transforms the K modulation symbols to the time domain with a K-point IFFT, and provides a transformed symbol containing K time-domain samples.

Each time-domain sample is a complex value to be transmitted in one sample period. A parallel-to-serial converter 326 serializes the K samples of each transformed symbol.

[0031] A cyclic prefix generator 328 cyclically/circularly repeats a portion (or C samples) of each transformed symbol to form an OFDM symbol containing $K+C$ samples. The repeated portion is referred to as a cyclic prefix or a guard interval, and C is the cyclic prefix length. The cyclic prefix is used to combat inter-symbol interference (ISI) caused by frequency selective fading, which is a frequency response that varies across the system bandwidth.

[0032] A filter 330 performs pulse shaping or windowing on the OFDM symbols from cyclic prefix generator 328. Filter 330 cyclically repeats L samples in front and L samples in back of each OFDM symbol. Filter 330 then filters each extended OFDM symbol in accordance with a desired impulse response to obtain filtered samples for the OFDM symbol. The pulse shaping ensures that the filtered samples conform to a spectral emission mask imposed on the system. Filter 330 then overlaps the pulse-shaped OFDM symbols such that the last L filtered samples of each OFDM symbol overlap the first L filtered samples of the next OFDM symbol. Filter 330 then sums the filtered samples for each sample period and provides the output samples, which are denoted as $y(n)$ where n is an index for sample period. Because of the overlap-and-add operation, each OFDM symbol after pulse shaping contains $K+C+L$ samples. An OFDM symbol period is the duration of one OFDM symbol and is equal to $K+C+L$ sample periods.

[0033] As shown in FIG. 3, a transmitter may send K modulation symbols in the frequency domain on the K total subcarriers in each OFDM symbol period. The transmitter may convert the K modulation symbols to the time-domain with an IFFT to generate K time-domain samples. A cyclic prefix of length C and a window of length L may also be appended. This digital sequence of $K+C+L$ samples may then be converted to an analog waveform with a digital-to-analog converter (DAC). The DAC may be operated at a sample rate of W, and the spacing between samples may be 1/W seconds. A receiver may obtain digital samples by sampling an analog received signal every 1/W seconds.

[0034] The duration of an OFDM symbol is denoted as T_{OFDM} and may be given as:

$$T_{OFDM} = (K+C+L)/W \ . \qquad \text{Eq (1)}$$

Since an OFDM symbol is a basic unit of transmission in an OFDM-based system, time intervals in the system are typically given in units of T_{OFDM}. For example, a data packet may be encoded and sent in a frame spanning N_{FRAME} OFDM symbols. The transmission time for this packet would be at least $N_{FRAME} \cdot T_{OFDM}$ seconds. The time interval between the start of transmission of a data packet and the end of reception of that data packet is often referred to as latency. It is easy to see that latencies in an OFDM-based system depend directly on T_{OFDM}.

[0035] As shown in equation (1), T_{OFDM} is typically a function of bandwidth W. Therefore, OFDM-based systems designed for different bandwidths may have different latencies. This may not be desirable since some applications have strict latency requirements that do not depend on bandwidth. In order to ensure similar latencies for different bandwidths, certain system parameters such as FFT size, frame duration, etc., may be defined as a function of bandwidth. However, this parameter selection may be a difficult task, especially if there is a large number of possible bandwidth allocations. Furthermore, there may be constraints on FFT sizes, frame durations, etc., which may make the parameter selection more difficult or impossible.

[0036] The sample rate at a receiver is typically equal to an integer multiple of the bandwidth W. Different sample rates may be used for different bandwidths. This may be disadvantageous since hardware (e.g., analog-to-digital converters) may need to be designed to support different sample rates.

[0037] In an aspect, an OFDM-based system flexibly supports different bandwidths by using a fixed design bandwidth and variable guard bands. This allows the system to use the same sample rate and offer similar latencies for all supported bandwidths.

[0038] **FIG. 4** illustrates the use of variable guard bands to support different bandwidths. The OFDM-based system is designed for a fixed bandwidth of W Hertz. The system supports a configurable operating bandwidth of B Hertz by using one or more guard bands at one or both ends of the operating bandwidth. The operating bandwidth B may be any bandwidth that is less than or equal to the design bandwidth W, or $B \leq W$.

[0039] **FIG. 5A** shows a subcarrier structure for the design bandwidth W. The design bandwidth is partitioned into K total subcarriers, which may be assigned indices

of 1 through K. Since the design bandwidth is fixed, the total number of subcarriers is also fixed.

[0040] **FIG. 5B** shows a subcarrier structure for the operating bandwidth B. The operating bandwidth may occupy all or a portion of the design bandwidth. The subcarriers within the operating bandwidth are referred to as usable subcarriers, and the subcarriers outside of the operating bandwidth are referred to as guard subcarriers. A usable subcarrier is a subcarrier that may be modulated with data. A guard subcarrier is a subcarrier that is modulated with a signal value of zero, so that no power is transmitted on the guard subcarrier. The number of usable subcarriers, N, may be given as follows:

$$N = K \cdot B / W \ . \qquad \text{Eq (2)}$$

The number of guard subcarriers, G, may be given as $G = K - N$.

[0041] As shown in FIGS. 4 and 5B, the OFDM-based system can support different bandwidths up to W Hertz by using variable guard bands/subcarriers. For example, the system may be designed for a bandwidth of 10 MHz. The system may be deployed with an operating bandwidth of 8 MHz by using 1 MHz guard band on each of the two sides of the 8 MHz operating bandwidth. In general, the left and right guard bands may be selected based on the operating bandwidth B and the design bandwidth W. The left and right guard bands may or may not have equal lengths.

[0042] Using variable guard bands/subcarriers, the OFDM-based system can support different bandwidths with a single sample rate and offer similar latencies for all supported bandwidths. A sample rate of 1/W may be used for the system, and the OFDM symbol duration may be given as shown in equation (1). The quantities on the right hand side of equation (1) are independent of the operating bandwidth B. Hence, the OFDM symbol period T_{OFDM} and latencies are independent of the operating bandwidth B.

[0043] **FIG. 6** shows a block diagram of a design of an OFDM modulator 220b for configurable operating bandwidth. OFDM modulator 220b may also be used for OFDM modulators 220 and 292 in FIG. 2. Within OFDM modulator 220b, a serial-to-parallel converter 620 receives modulation symbols for data (e.g., traffic data, signaling, pilot, etc.) and maps these modulation symbols to the N usable subcarriers. The

mapped modulation symbols are denoted as $U(k)$. A zero insertion unit 622 inserts a zero symbol on each guard subcarrier and provides K transmit symbols in each OFDM symbol period. A zero symbol is a signal value of zero. Each transmit symbol may be a modulation symbol for data or a zero symbol. The transmit symbols are denoted as $V(k)$. The mapping to N usable subcarriers by unit 620 and the zero insertion by unit 622 may be performed based on the operating bandwidth B.

[0044] An IFFT unit 624 receives K transmit symbols for the K total subcarriers in each OFDM symbol period, transforms the K transmit symbols to the time domain with a K-point IFFT, and provides K time-domain samples. The K samples of each transformed symbol are serialized by a parallel-to-serial converter 626, appended with a cyclic prefix by a cyclic prefix generator 628, and filtered by a pulse-shaping filter 630 to generate a pulse-shaped OFDM symbol.

[0045] **FIG. 7** shows a block diagram of a design of an OFDM demodulator 260a for configurable operating bandwidth. OFDM demodulator 260a may be used for OFDM demodulators 260 and 232 in FIG. 2. Within OFDM demodulator 260a, a cyclic prefix removal unit 710 obtains K+C+L received samples in each OFDM symbol period, removes C samples for the cyclic prefix and L samples for the pulse shaping window, and provides K received samples for the OFDM symbol period. A serial-to-parallel converter 712 provides the K received samples in parallel form. An FFT unit 714 transforms the K received samples to the frequency domain with a K-point FFT and provides K received symbols for the K total subcarriers. The received symbols from FFT unit 714 are denoted as $Y(k)$.

[0046] A zero removal unit 716 obtains K received symbols in each OFDM symbol period, removes the received symbols from the G guard subcarriers, and provides N received symbols from the N usable subcarriers. The received symbols from unit 716 are denoted as $R(k)$. A parallel-to-serial converter 728 serializes the N received symbols of each OFDM symbol from unit 716. The zero removal by unit 716 and the parallel-to-serial conversion by unit 718 may be performed based on the operating bandwidth B.

[0047] An OFDM-based system may have a single design bandwidth W and may use specific values for parameters such as FFT size K, cyclic prefix length C, window

length L, and sample rate W. Different operating bandwidths up to W may be supported using these fixed parameter values for K, C, L and sample rate.

[0048] An OFDM-based system may also have more than one design bandwidth and may use a specific set of values for K, C, L, and sample rate for each design bandwidth. Different sets of parameter values may be selected for different design bandwidths, e.g., to achieve the same or similar latencies for all design bandwidths. For example, an OFDM-based system may be designed for bandwidths of 5 MHz and 10 MHz using FFT sizes of 512 and 1024, respectively. The 5 MHz design bandwidth may be used to support operating bandwidths up to 5 MHz, or $B \leq 5$ MHz. The 10 MHz design bandwidth may be used to support operating bandwidths from 5 to 10 MHz, or 5 MHz $< B \leq 10$ MHz. In general, any number of design bandwidths may be supported, and any set of parameter values may be used for each design bandwidth. Each design bandwidth may support an associated range of operating bandwidths up to that design bandwidth.

[0049] Variable guard bands may be used to support different operating bandwidths, as described above. Variable guard bands may also be used to support different spectral emission masks. A spectral emission mask specifies the allowed output power levels at different frequencies. A more stringent spectral emission mask may require the output power level to be attenuated more at certain frequencies. The impulse response of the pulse-shaping filter is typically fixed to simplify the transmitter design. More guard subcarriers may be used in order to meet more stringent spectral emission mask requirements.

[0050] Variable guard bands may also be used to avoid interference from other transmitters. For example, a base station in an OFDM-based system may observe high levels of interference from other transmitters in other systems. The base station may adjust its operating bandwidth in order to avoid using subcarriers with high levels of interference. These subcarriers may be made guard subcarriers and not used for transmission.

[0051] **FIG. 8** shows a process 800 for transmission with configurable operating bandwidth. Process 800 may be performed by a transmitter (e.g., a base station for downlink transmission) or a receiver (e.g., a terminal for downlink transmission). Usable subcarriers and guard subcarriers are determined based on a configurable operating bandwidth for a wireless communication system (block 812). The operating

bandwidth may be selected based on, e.g., the bandwidth available for the system, a spectral emission mask for the system, etc. The determination in block 812 may be made based on signaling, control registers, hardwired logic, software commands, etc. The system may be associated with a design bandwidth corresponding to K total subcarriers. The operating bandwidth may correspond to N usable subcarriers, where $K \geq N > 1$. The N usable subcarriers may be centered among the K total subcarriers, and the guard subcarriers may be evenly distributed on both sides of the operating bandwidth. Other arrangements of usable and guard subcarriers are also possible. Processing is performed for a transmission sent on the usable subcarriers (block 814). The transmission may comprise traffic data, signaling, pilot, etc.

[0052] Process 800 may be performed by a transmitter. In this case, for block 814, modulation symbols may be mapped to the usable subcarriers, and zero symbols may be mapped to the guard subcarriers. OFDM symbols may be generated based on the mapped modulation symbols and zero symbols. The OFDM symbols may be generated further based on an FFT size and a cyclic prefix length that may be independent of the operating bandwidth. Output samples may be generated at a sample rate that may be independent of the operating bandwidth.

[0053] Process 800 may also be performed by a receiver. In this case, for block 814, received samples may be obtained at a sample rate that may be independent of the operating bandwidth and processed (e.g., OFDM demodulated) to obtain received symbols for the K total subcarriers. Received symbols from the usable subcarriers may be retained, and received symbol from the guard subcarriers may be discarded. The received symbols from the usable subcarriers may be processed (e.g., symbol demapped, deinterleaved, and decoded) to recover data sent in the transmission.

[0054] The operating bandwidth may be selected from multiple bandwidths associated with different numbers of guard subcarriers and a fixed OFDM symbol duration. OFDM symbols for different operating bandwidths may be generated by keeping the same OFDM symbol duration but changing the number of guard subcarriers.

[0055] The system may be associated with a single design bandwidth. The operating bandwidth may be selected from a range of bandwidths supported by the design bandwidth. The processing in block 814 may be performed based on a set of

parameter values for the design bandwidth. Alternatively, the system may be associated with multiple design bandwidths. Each design bandwidth may support a respective range of operating bandwidths. The processing in block 814 may be performed based on a set of parameter values for a design bandwidth supporting the operating bandwidth selected for use.

[0056] **FIG. 9** shows a design of an apparatus 900 for transmission with configurable operating bandwidth. Apparatus 900 includes means for determining usable subcarriers and guard subcarriers based on a configurable operating bandwidth for a wireless communication system (for example module 912), and means for performing processing for a transmission sent on the usable subcarriers (for example module 914). Modules 912 and 914 may comprise processors, electronics devices, hardware devices, electronics components, logical circuits, memories, etc., or any combination thereof.

[0057] In another aspect, an OFDM-based system may use different operating bandwidths and/or different parameter values for different portions of a transmission. The system may employ a preamble comprising one or more OFDM symbols and a main body comprising any number of OFDM symbols. The preamble may carry information used to demodulate and decode the transmission sent in the main body. The main body may carry traffic data and/or other types of data. Different operating bandwidths and/or parameter values may be used for the preamble and main body.

[0058] **FIG. 10** shows a super-frame structure 1000 that may be used for an OFDM-based system. The timeline for transmission in the system may be divided into super-frames. Each super-frame may have a predetermined time duration. A super-frame may also be referred to as a frame, a slot, or some other terminology. In the design shown in FIG. 10, each super-frame includes a preamble 1010 and a main body 1020. Preamble 1010 includes a pilot field 1012 and an overhead field 1014.

[0059] Pilot field 1012 may carry pilot and/or other signals used for various purposes such as system detection, time and frequency acquisition, channel estimation, etc. Overhead field 1014 may carry information regarding how data is sent in main body 1020, system information, etc. For example, overhead field 1014 may carry information for parameters such as the operating bandwidth, FFT size, cyclic prefix length, window length, frequency hop sequence, etc., used for main body 1020. Main body 1020 may carry data, e.g., traffic data, signaling, pilot, etc. The three fields 1012,

1014 and 1020 may be time division multiplexed in each super-frame as shown in FIG. 10 in order to facilitate synchronization and data recovery. Pilot field 1012 may be sent first in each super-frame and may be used for detection of overhead field 1014. Information obtained from overhead field 1014 may be used to recover the data sent in main body 1020.

[0060] **FIG. 11** shows a design of a structure 1100 with different design bandwidths and different operating bandwidths for different fields. In structure 1100, one design bandwidth W_P and one FFT size K_P may be used for the preamble. Another design bandwidth W_M and another FFT size K_M may be used for the main body. The operating bandwidth B_P and the N_P usable subcarriers for the preamble may be selected based on the design bandwidth W_P and the K_P total subcarriers for the preamble. The operating bandwidth B_M and the N_M usable subcarriers for the main body may be selected based on the design bandwidth W_M and the K_M total subcarriers for the main body. The parameters may be selected, e.g., as follows:

$$W_P \le W_M, \quad B_P \le B_M, \text{ and } \quad K_P \le K_M. \qquad \text{Eq (3)}$$

Different design bandwidths, operating bandwidths, FFT sizes, etc. may also be used for the pilot and overhead fields of the preamble.

[0061] Alternatively, one design bandwidth W and one FFT size K may be used for all fields, and different operating bandwidths may be used for different fields. An operating bandwidth of B_{pilot} may be used for the pilot field, an operating bandwidth of $B_{overhead}$ may be used for the overhead field, and an operating bandwidth of B_{main} may be used for the main body. The bandwidths for the various fields may be selected, e.g., as follows:

$$B_{pilot} \le B_{overhead} \le B_{main} \le W. \qquad \text{Eq (4)}$$

[0062] The bandwidths for different fields may be conveyed in various manners. In one design, the design bandwidths and operating bandwidths for the pilot field, overhead field, and main body are fixed and known to the terminals *a priori*.

[0063] In another design, the design bandwidths for the pilot field, overhead field, and main body are fixed, and the operating bandwidths for the pilot field, overhead field, and/or main body are configurable. The parameter values for each configurable

field may be sent in another field. For example, the operating bandwidth and parameter values for the overhead field may be conveyed in the pilot field. The operating bandwidth and parameter values for the main body may be conveyed in the overhead field. A terminal may recover the overhead field based on parameter values known to the terminal *a priori* or conveyed via the pilot field. The terminal may then recover the transmission sent in the main body based on the parameter values obtained from the overhead field.

[0064] In yet another design, a small number of predetermined sets of parameter values may be used for a given field, e.g., the pilot field, overhead field, or main body. The terminals have knowledge of the predetermined sets of parameters and may attempt to recover the transmission on this field based on the predetermined parameter sets.

[0065] A combination of the above designs may also be used for different fields. For example, a known set of parameter values may be used for the pilot field, a small number of predetermined sets of parameter values may be used for the overhead field, and a configurable set of parameter values may be used for the main body and conveyed in the overhead field. A terminal may recover the pilot based on the known set of parameter values. The terminal may recover the overhead based on the predetermined sets of parameter values and obtain the configurable set of parameter values for the main body. The terminal may then recover the transmission sent in the main body based on the configurable set of parameter values.

[0066] **FIG. 12** shows a design of a process 1200 that may be performed by a transmitter or a receiver. Processing is performed for a first portion of a transmission sent using a first operating bandwidth (block 1212). Processing is performed for a second portion of the transmission sent using a second operating bandwidth (block 1214). The first portion may correspond to a preamble, and the second portion may correspond to a main body of the transmission.

[0067] Process 1200 may be performed by a transmitter. In this case, signaling may be sent on the first set of subcarriers used for the first portion of the transmission and determined based on the first operating bandwidth. Data may be sent on the second set of subcarriers used for the second portion of the transmission and determined based on the second operating bandwidth. The signaling may comprise information for parameters for the second portion of the transmission. The parameters may comprise

the second operating bandwidth, an FFT size, a cyclic prefix length, a frequency hopping sequence, etc.

[0068] Process 1200 may also be performed by a receiver. In this case, signaling may be received from the first set of subcarriers, and data may be received from the second set of subcarriers. The signaling may be processed to obtain information for parameters for the second portion of the transmission. The second portion of the transmission may be processed based on the information obtained from the signaling.

[0069] In one design, the first and second operating bandwidths are selected from a set of operating bandwidths available for both the first and second portions. In another design, the first operating bandwidth is selected from a first set of operating bandwidths available for the first portion. The second operating bandwidth is selected from a second set of operating bandwidths available for the second portion.

[0070] In one design, the first and second portions are associated with one design bandwidth. The processing for the first and second portions may be based on a set of parameter values for this design bandwidth. In another design, the first and second portions are associated with first and second design bandwidths, respectively. The processing for the first portion may be based on a first set of parameter values for the first design bandwidth. The processing for the second portion may be based on a second set of parameter values for the second design bandwidth. A first set of design bandwidths may be applicable for the first portion, and a second set of design bandwidths may be applicable for the second portion. The first and second design bandwidths may be selected from the first and second sets, respectively.

[0071] The first portion may be associated with fewer design bandwidths and/or fewer operating bandwidths than the second portion. This may reduce the number of hypotheses to evaluate to recover the transmission sent in the first portion.

[0072] **FIG. 13** shows a design of an apparatus 1300 for transmission. Apparatus 1300 includes means for performing processing for a first portion of a transmission sent using a first operating bandwidth (for example module 1312), and means for performing processing for a second portion of the transmission sent using a second operating bandwidth (for example module 1314). Modules 1312 and 1314 may comprise processors, electronics devices, hardware devices, electronics components, logical circuits, memories, etc., or any combination thereof.

[0073] The transmission techniques described herein may be implemented by various means. For example, the techniques may be implemented in hardware, firmware, software, or a combination thereof. For a hardware implementation, the processing units at an entity (e.g., a base station or a terminal) may be implemented within one or more application specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, micro-controllers, microprocessors, electronic devices, other electronic units designed to perform the functions described herein, or a combination thereof.

[0074] For a firmware and/or software implementation, the techniques may be implemented with modules (e.g., procedures, functions, and so on) that perform the functions described herein. The firmware and/or software codes may be stored in a memory (e.g., memory 242 or 282 in FIG. 2) and executed by a processor (e.g., processor 240 or 280). The memory may be implemented within the processor or external to the processor.

[0075] The previous description of the disclosure is provided to enable any person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the spirit or scope of the disclosure. Thus, the disclosure is not intended to be limited to the examples described herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

CLAIMS

1. An apparatus comprising:

a processor configured to determine usable subcarriers and guard subcarriers based on a configurable operating bandwidth for a wireless communication system, and to perform processing for a transmission sent on the usable subcarriers; and

a memory coupled to the processor.

2. The apparatus of claim 1, wherein the processor is configured to map modulation symbols to the usable subcarriers, to map zero symbols to the guard subcarriers, and to generate Orthogonal Frequency Division Multiplexing (OFDM) symbols based on the mapped modulation symbols and zero symbols.

3. The apparatus of claim 2, wherein the processor is configured to generate the OFDM symbols based on a fast Fourier transform (FFT) size and a cyclic prefix length that are independent of the operating bandwidth.

4. The apparatus of claim 1, wherein the processor is configured to generate output samples at a sample rate that is independent of the operating bandwidth.

5. The apparatus of claim 1, wherein the processor is configured to obtain received symbols from the usable subcarriers, to discard received symbol from the guard subcarriers, and to process the received symbols from the usable subcarriers to recover data sent in the transmission.

6. The apparatus of claim 5, wherein the processor is configured to obtain received samples at a sample rate that is independent of the operating bandwidth, and to process the received samples to obtain the received symbols for the usable and guard subcarriers.

7. The apparatus of claim 1, wherein the wireless communication system is associated with a design bandwidth corresponding to K total subcarriers, and wherein the operating bandwidth corresponds to N usable subcarriers, where $K \geq N > 1$.

8. The apparatus of claim 7, wherein the N usable subcarriers are centered among the K total subcarriers.

9. The apparatus of claim 1, wherein the guard subcarriers are evenly distributed on both sides of the operating bandwidth.

10. The apparatus of claim 1, wherein the wireless communication system is associated with a single design bandwidth and the operating bandwidth is selected from a range of bandwidths supported by the design bandwidth, and wherein the processor is configured to perform processing for the transmission based on a set of parameter values for the design bandwidth.

11. The apparatus of claim 1, wherein the wireless communication system is associated with multiple design bandwidths, each design bandwidth supporting a respective range of bandwidths, and wherein the processor is configured to perform processing for the transmission based on a set of parameter values for a design bandwidth supporting the operating bandwidth.

12. The apparatus of claim 1, wherein the wireless communication system is associated with first and second design bandwidths, and wherein the processor is configured to perform processing for the transmission based on a first set of parameter values for the first design bandwidth if the operating bandwidth is within a first range, and to perform processing for the transmission based on a second set of parameter values for the second design bandwidth if the operating bandwidth is within a second range that is lower than the first range.

13. The apparatus of claim 1, wherein the operating bandwidth is determined based on frequency bandwidth available for the wireless communication system.

14. The apparatus of claim 1, wherein the operating bandwidth is determined based on a spectral emission mask for the wireless communication system.

15. The apparatus of claim 1, wherein the operating bandwidth is selected from a plurality of bandwidths associated with different numbers of guard subcarriers and a fixed Orthogonal Frequency Division Multiplexing (OFDM) symbol duration.

16. A method comprising:

determining usable subcarriers and guard subcarriers based on a configurable operating bandwidth for a wireless communication system; and

performing processing for a transmission sent on the usable subcarriers.

17. The method of claim 16, wherein the performing processing for the transmission comprises

mapping modulation symbols to the usable subcarriers,

mapping zero symbols to the guard subcarriers, and

generating Orthogonal Frequency Division Multiplexing (OFDM) symbols based on the mapped modulation symbols and zero symbols.

18. The method of claim 16, wherein the performing processing for the transmission comprises

obtaining received symbols from the usable subcarriers,

discarding received symbol from the guard subcarriers, and

processing the received symbols from the usable subcarriers to recover data sent in the transmission.

19. An apparatus comprising:

means for determining usable subcarriers and guard subcarriers based on a configurable operating bandwidth for a wireless communication system; and

means for performing processing for a transmission sent on the usable subcarriers.

20. The apparatus of claim 19, wherein the means for performing processing for the transmission comprises

means for mapping modulation symbols to the usable subcarriers,

means for mapping zero symbols to the guard subcarriers, and

means for generating Orthogonal Frequency Division Multiplexing (OFDM) symbols based on the mapped modulation symbols and zero symbols.

21. The apparatus of claim 19, wherein the means for performing processing for the transmission comprises

means for obtaining received symbols from the usable subcarriers,

means for discarding received symbol from the guard subcarriers, and

means for processing the received symbols from the usable subcarriers to recover data sent in the transmission.

22. An apparatus comprising:

a processor configured to determine usable subcarriers and guard subcarriers based on a configurable operating bandwidth for a wireless communication system, the operating bandwidth selected from a plurality of bandwidths associated with different numbers of guard subcarriers and a fixed Orthogonal Frequency Division Multiplexing (OFDM) symbol duration, and to perform processing for a transmission sent on the usable subcarriers, the transmission comprising OFDM symbols having the fixed duration; and

a memory coupled to the processor.

23. An apparatus comprising:

a processor configured to perform processing for a first portion of a transmission sent using a first operating bandwidth, and to perform processing for a second portion of the transmission sent using a second operating bandwidth; and

a memory coupled to the processor.

24. The apparatus of claim 23, wherein the first portion corresponds to a preamble and the second portion corresponds to a main body of the transmission.

25. The apparatus of claim 24, wherein the first operating bandwidth is smaller than the second operating bandwidth.

26. The apparatus of claim 23, wherein the processor is configured to send signaling on a first set of subcarriers used for the first portion of the transmission and determined based on the first operating bandwidth, and to send data on a second set of subcarriers used for the second portion of the transmission and determined based on the second operating bandwidth.

27. The apparatus of claim 26, wherein the signaling comprises information for parameters for the second portion of the transmission.

28. The apparatus of claim 27, wherein the parameters comprise the second operating bandwidth, a fast Fourier transform (FFT) size, a cyclic prefix length, a frequency hopping sequence, or a combination thereof.

29. The apparatus of claim 23, wherein the processor is configured to receive signaling from a first set of subcarriers used for the first portion of the transmission and determined based on the first operating bandwidth, and to receive data from a second set of subcarriers used for the second portion of the transmission and determined based on the second operating bandwidth.

30. The apparatus of claim 29, wherein the processor is configured to process the signaling to obtain information for parameters for the second portion of the transmission, and to process the second portion of the transmission based on the information obtained from the signaling.

31. The apparatus of claim 23, wherein the processor is configured to perform processing for the first portion of the transmission based on a first set of parameter values for a first design bandwidth applicable to the first portion, and to perform processing for the second portion of the transmission based on a second set of parameter values for a second design bandwidth applicable to the second portion.

32. The apparatus of claim 31, wherein the first design bandwidth is in a first set of design bandwidths applicable for the first portion and the second design bandwidth is in a second set of design bandwidths applicable for the second portion, the first set including fewer design bandwidths than the second set.

33. The apparatus of claim 23, wherein the processor is configured to perform processing for the first and second portions of the transmission based on a set of parameter values for a design bandwidth applicable to the first and second portions.

34. The apparatus of claim 23, wherein the first operating bandwidth is selected from a first set of operating bandwidths available for the first portion, and wherein the second operating bandwidth is selected from a second set of operating bandwidths available for the second portion.

35. The apparatus of claim 34, wherein the first set includes fewer operating bandwidths than the second set.

36. A method comprising:

performing processing for a first portion of a transmission sent using a first operating bandwidth; and

performing processing for a second portion of the transmission sent using a second operating bandwidth.

37. The method of claim 36, further comprising:

sending signaling on a first set of subcarriers used for the first portion of the transmission and determined based on the first operating bandwidth; and

sending data on a second set of subcarriers used for the second portion of the transmission and determined based on the second operating bandwidth.

38. The method of claim 36, further comprising:

receiving signaling from a first set of subcarriers used for the first portion of the transmission and determined based on the first operating bandwidth; and

receiving data from a second set of subcarriers used for the second portion of the transmission and determined based on the second operating bandwidth.

39. The method of claim 38, wherein the performing processing for the first portion comprises processing the signaling to obtain information for parameters for the second portion of the transmission, and wherein the performing processing for the second portion comprises processing the second portion of the transmission based on the information obtained from the signaling.

40. An apparatus comprising:

means for performing processing for a first portion of a transmission sent using a first operating bandwidth; and

means for performing processing for a second portion of the transmission sent using a second operating bandwidth.

41. The apparatus of claim 40, further comprising:

means for sending signaling on a first set of subcarriers used for the first portion of the transmission and determined based on the first operating bandwidth; and

means for sending data on a second set of subcarriers used for the second portion of the transmission and determined based on the second operating bandwidth.

42. The apparatus of claim 40, further comprising:

means for receiving signaling from a first set of subcarriers used for the first portion of the transmission and determined based on the first operating bandwidth; and

means for receiving data from a second set of subcarriers used for the second portion of the transmission and determined based on the second operating bandwidth.

43. The apparatus of claim 42, wherein the means for performing processing for the first portion comprises means for processing the signaling to obtain information for parameters for the second portion of the transmission, and wherein the means for performing processing for the second portion comprises means for processing the second portion of the transmission based on the information obtained from the signaling.