

## DESCRIPTION

### RELAY COMMUNICATION SYSTEM AND FIRST RELAY SERVER

#### Technical Field

[0001]

The present invention relates to a relay communication system that enables client terminals connected to local area networks (LANs) to make communication with one another beyond a wide area network (WAN).

#### Background Art

[0002]

By using a virtual private network (VPN), a client terminal can communicate with another client terminal remotely located beyond a WAN. However, it is difficult for the VPN to construct a network having expandability and flexibility.

[0003]

A relay communication system disclosed in Patent Document 1 can construct a network looking as if remote LANs were directly connected to one another in a similar way to the VPN. This relay communication system is superior in expandability and flexibility to the general VPN in that it is possible to dynamically change a group relationship among the LANs, and so on.

#### Prior Art Document

Patent Document

[0004]

[Patent Document 1] Japanese Patent Laid-Open Publication No.  
2008-129991

Summary of the Invention

Problems to be Solved by the Invention

[0005]

In the relay communication system disclosed in Patent Document 1, the respective relay servers share identification information of the client terminals connected to the respective LANs, thus enabling communication among the client terminals. Specifically, association information between identification information of the relay servers and identification information of the client terminals is shared by the whole of the network, thus making it possible for the relay servers to relay communication packets among the client terminals.

[0006]

It is an object of the present invention to provide a communication method excellent in flexibility and expandability in the event of constructing the communication system in which the client terminals communicate with one another through the WAN.

Means for Solving the Problems

[0007]

A relay communication system according to an aspect of the present invention is a relay communication system in which a first relay server

connected to a first LAN and a second relay server connected to a second LAN are connected to each other. Each of the first relay server and the second relay server includes: a relay server information sharing unit; a routing group information sharing unit; a routing control unit. The relay server information sharing unit shares relay server information between the first relay server and the second relay server, the relay server information including activation information of the first relay server and the second relay server, and activation/registration information of client terminals connected to the first relay server and the second relay server. The routing group information sharing unit shares routing group information with a first routing device that executes routing control for the first LAN and a second routing device that executes routing control for the second LAN, the routing group information including a network address of the first LAN, a network address of the second LAN, first specifying information that specifies either a relay server or a client terminal, which is the first routing device, and second specifying information that specifies either a relay server or a client terminal, which is the second routing device. Upon receiving a start request of routing control, the routing control unit specifies the first routing device and the second routing device from the first specifying information and the second specifying information, which are included in the routing group information, establishes a routing session between the first routing device and the second routing device based on the relay server information, executes routing control for a communication packet between the first LAN and the second LAN through the routing session, and, upon receiving an instruction to end the routing control, disconnects the routing

session, and ends the routing control for the communication packet between the first LAN and the second LAN. When a first communication packet destined for a destination address of an IP address belonging to the second LAN is sent out from a communication terminal connected to the first LAN, the first routing device refers to the routing group information to decide that routing of the first communication packet to the second LAN is possible, and transfers the first communication packet by using the established routing session.

[0008]

Preferably, a plurality of relay servers including the first relay server and the second relay server are connected to one another through a wide area network, and the routing group information includes network addresses of LANs to which the relay servers connect, and information that specifies routing devices executing routing control for LANs to which the relay servers connect.

[0009]

Preferably, the first routing device is a client terminal connected to the first relay server, and is capable of performing communication with the second relay server through the first relay server.

[0010]

Preferably, the second routing device is the second relay server.

[0011]

Preferably, the first relay server and the second relay server are a same device, the first routing device is a first client terminal connected to the first relay server, and the second routing device is a second client

terminal connected to the first relay server.

[0012]

Preferably, the routing group information includes permitted terminal information in which an address of the communication terminal connected to the first LAN is registered, and in a case where a transmission source address of the first communication packet is registered in the permitted terminal information, the first routing device permits routing of the first communication packet.

[0013]

Preferably, the routing group information includes permitted terminal information in which an address of the communication terminal connected to the second LAN is registered, and in a case where a destination address of the first communication packet is registered in the permitted terminal information, the first routing device permits routing of the first communication packet.

[0014]

A relay communication system according to another aspect of the present invention is a relay communication system in which a first relay server connected to a first LAN and a second relay server connected to a second LAN are connected to each other. The first relay server includes: a relay server information sharing unit; an acquisition unit; a request unit; and a routing setting information creation unit. The relay server information sharing unit shares relay server information with the second relay server, the relay server information including activation information of the first relay server and the second relay server, and activation/registration

information of client terminals connected to the first relay server and the second relay server. The acquisition unit acquires first specifying information specifying either a relay server or a client terminal, which is a first routing device executing routing control for the first LAN based on a network address of the first LAN. The request unit requests the second relay server for second specifying information specifying either a relay server or a client terminal, which is a second routing device executing routing control for the second LAN based on a network address of the second LAN. The routing setting information creation unit creates routing setting information based on the first specifying information and the second specifying information, the routing setting information including information in which the network address of the first LAN and the first routing device are associated with each other, and information in which the network address of the second LAN and the second routing device are associated with each other. The second relay server includes: a response unit that, in response to a request from the request unit, acquires the second specifying information, and transmits the second specifying information to the first relay server. Each of the first relay server and the second relay server includes: a sharing unit; and a routing control unit. The sharing unit shares the routing setting information. Upon receiving a start request of routing control, the routing control unit specifies the first routing device and the second routing device based on the routing setting information, establishes a routing session between the first routing device and the second routing device based on the relay server information, executes routing control for a communication packet between the first LAN

and the second LAN through the routing session, and, upon receiving an instruction to end the routing control, disconnects the routing session, and ends the routing control for the communication packet between the first LAN and the second LAN. When a communication packet destined for a destination address as an IP address belonging to the second LAN is sent out from a communication terminal connected to the first LAN, the first routing device refers to the routing setting information to decide that routing of the communication packet to the second LAN is possible, and transfers the communication packet by using the established routing session.

[0015]

Preferably, the first relay server further includes: a list creation unit that searches LANs capable of routing control, and creates a list of the LANs; and a selection unit that selects the network address of the first LAN and the network address of the second LAN by using the list.

[0016]

Preferably, the first routing device is a client terminal connected to the first relay server, and is capable of performing communication with the second relay server through the first relay server, and the client terminal shares the routing setting information with the first relay server and the second relay server.

[0017]

Preferably, the second routing device is the second relay server.

[0018]

A first relay server according to still another aspect of the present

invention is a first relay server for use in a relay communication system in which the first relay server connected to a first LAN and a second relay server connected to a second LAN are connected to each other, the first relay server including: a relay server information sharing unit; a routing group information sharing unit; and a routing control unit. The relay server information sharing unit shares relay server information with the second relay server, the relay server information including activation information of the first relay server and the second relay server, and activation/registration information of client terminals connected to the first relay server and the second relay server. The routing group information sharing unit shares routing group information with a first routing device that executes routing control for the first LAN and a second routing device that executes routing control for the second LAN, the routing group information including a network address of the first LAN, a network address of the second LAN, first specifying information that specifies either a relay server or a client terminal, which is the first routing device, and second specifying information that specifies either a relay server or a client terminal, which is the second routing device. Upon receiving a start request of the routing control, the routing control unit specifies the first routing device and the second routing device from the first specifying information and the second specifying information, which are included in the routing group information, establishes a routing session between the first routing device and the second routing device based on the relay server information, executes routing control for a communication packet between the first LAN and the second LAN through the routing session, and, upon receiving an instruction to end

the routing control, disconnects the routing session, and ends the routing control for the communication packet between the first LAN and the second LAN. When a first communication packet destined for a destination address of an IP address belonging to the second LAN is sent out from a communication terminal connected to the first LAN, the first routing device refers to the routing group information to decide that routing of the first communication packet to the second LAN is possible, and transfers the first communication packet by using the established routing session.

[0019]

A first relay server according to still another aspect of the present invention is used for a relay communication system in which the first relay server connected to a first LAN and a second relay server connected to a second LAN are connected to each other, and includes: a relay server information sharing unit; an acquisition unit; a request unit; a routing setting information creation unit; a sharing unit; and a routing control unit. The relay server information sharing unit shares relay server information with the second relay server, the relay server information including activation information of the first relay server and the second relay server, and activation/registration information of client terminals connected to the first relay server and the second relay server. The acquisition unit acquires first specifying information specifying either a relay server or a client terminal, which is a first routing device executing routing control for the first LAN based on a network address of the first LAN. The request unit requests the second relay server for second specifying information specifying either of a relay server or a client terminal, which is a second routing device

executing routing control for the second LAN based on a network address of the second LAN. The routing setting information creation unit creates routing setting information based on the first specifying information and the second specifying information, the routing setting information including information in which the network address of the first LAN and the first routing device are associated with each other, and information in which the network address of the second LAN and the second routing device are associated with each other. The sharing unit shares the routing setting information with the second relay server. Upon receiving a start request of routing control, the routing control unit specifies the first routing device and the second routing device based on the routing setting information, establishes a routing session between the first routing device and the second routing device based on the relay server information, executes routing control for a communication packet between the first LAN and the second LAN through the routing session, and upon receiving an instruction to end the routing control, disconnects the routing session, and ends the routing control for the communication packet between the first LAN and the second LAN. When a communication packet destined for a destination address of an IP address belonging to the second LAN is sent out from a communication terminal connected to the first LAN, the first routing device refers to the routing setting information to decide that routing of the communication packet to the second LAN is possible, and transfers the communication packet by using the established routing session.

Effects of the Invention

[0020]

The relay communication system according to an aspect of the present invention establishes the routing session between the routing devices based on the routing group information including the network addresses of the LANs and the information regarding the client terminals or the relay servers, which function as the routing devices. By using the routing session, the routing devices execute the routing control for the communication packets transmitted from communication terminals connected to the LAN. By using the routing group information, the client terminals or the relay servers can function as the routing devices, and accordingly, it becomes possible to flexibly execute the routing control.

[0021]

In the relay communication system according to another aspect of the present invention, the routing devices establish the routing session based on the routing setting information. And by using the routing session, the routing devices execute the routing control for the communication packets transmitted from communication terminals connected to the LAN. A route information is created by specifying the routing devices which handle the routing for the LANs and by associating the network addresses of the LANs and the routing devices with each other.

[0022]

In such a way, the creation of the routing setting information necessary to validate the routing function of the relay communication system can be simplified. At the time when the configuration of the relay communication system is changed, and so on, it becomes easy to update the

route information, and accordingly, it becomes easy to manage the routing function using the relay communication system. Moreover, the relay communication system can search the LAN that can be used for the routing , and based on the search result, can designate the LAN as the routing target. Accordingly, the creation of the routing setting information can be further simplified.

#### Brief Description of the Drawings

[0023]

FIG. 1 is a schematic view of an entire configuration of a relay communication system.

FIG. 2 is a diagram showing a configuration of a relay server.

FIG. 3 is a diagram showing a configuration of a client terminal.

FIG. 4 is a view showing a flow of registration processing for the relay servers and the client terminals.

FIG. 5 is a view showing information created in response to processing of Step S9.

FIG. 6 is a view showing information created in response to processing of Step S10.

FIG. 7 is a view showing information created in response to processing of Step S12.

FIG. 8 is a view showing information created in response to processing of Step S13.

FIG. 9 is a view showing information created in response to processing of Step S14.

FIG. 10 is a view showing a flow of processing regarding construction of a relay group.

FIG. 11 is a view showing information created in response to an instruction to construct the relay group.

FIG. 12 is a view showing information created up to processing of Step S20.

FIG. 13 is a view showing a flow of processing regarding the construction of the relay group.

FIG. 14 is a view showing information created up to processing of Step S24.

FIG. 15 is a view showing information created up to processing of Step S28.

FIG. 16 is a diagram showing detailed configurations of the respective LANs.

FIG. 17 is a view showing a flow until a first routing session is established.

FIG. 18 is a view showing routing group information.

FIG. 19 is a view showing a flow of establishing a second routing session.

FIG. 20 is a view showing a flow of establishing a third routing session.

FIG. 21 is a view showing a flow of transferring a communication packet by using the first to third routing sessions.

FIG. 22 is a view showing routing group information.

FIG. 23 is a view showing a flow of establishing a fourth routing

session and of transferring the communication packet by using the fourth routing session.

FIG. 24 is a view showing a flow of ending routing processing.

FIG. 25 is a view showing routing group information.

FIG. 26 is a view showing a flow of processing that follows a change of the routing group information.

FIG. 27 is a view showing a flow of establishing fifth and sixth routing sessions.

FIG. 28 is a view showing a flow of transferring the communication packet by using the fifth and sixth routing sessions.

FIG. 29 is a flowchart showing a flow of creating the routing group information.

FIG. 30 is a flowchart showing a flow of ending the routing processing.

FIG. 31 is a flowchart showing operations of the client terminal that is executing the routing processing.

FIG. 32 is a chart showing a flow of network search processing.

FIG. 33 is a view showing network search information.

FIG. 34 is a view showing network search information.

FIG. 35 is a view showing network search information.

FIG. 36 is a table showing network search results displayed on a monitor of the client terminal.

FIG. 37 is a flowchart showing operations of the client terminal instructed to search a network.

FIG. 38 is a flowchart showing operations of the relay server at a

time of receiving a network search command.

FIG. 39 is a chart showing a flow of route search processing.

FIG. 40 is a view showing route search information.

FIG. 41 is a flowchart showing operations of the client terminal instructed to search a route.

FIG. 42 is a flowchart showing operations of the relay server that has received the route search command.

FIG. 43 is a chart showing a flow of starting routing.

FIG. 44 is a view showing routing group information.

FIG. 45 is a chart showing a flow of routing control for the communication packet.

## Best Modes for Carrying out the Invention

[0024]

### <1. Entire configuration of relay communication system>

A description will be made below of embodiments of the present invention while referring to the drawings. FIG. 1 is a schematic view showing an entire configuration of a relay communication system. The relay communication system is composed of LANs 1, 2 and 3 and a wide area network (WAN) 100. The WAN 100 is a wide area network such as the Internet.

[0025]

Client terminals 11 and 12 and a relay server 13 are connected to the LAN 1. A client terminal 21 and a relay server 22 are connected to the LAN 2. Client terminals 31 and 32 and a relay server 33 are connected to

the LAN 3. A session initiation protocol (SIP) server 101 is connected to the WAN 100.

[0026]

The client terminals individually connected to the LANs 1 to 3 are personal computers and the like. The relay servers 13, 22 and 33 relay communication between the client terminals respectively connected to two different LANs. The SIP server 101 relays communication among the relay servers. In this embodiment, each of the relay servers uses SIP at the time of communicating with the other relay server; however, protocols other than the SIP may be used.

[0027]

<2. Configuration of relay server>

FIG. 2 is a block diagram showing a configuration of the relay server 13. The relay server 13 includes an interface unit 131, a control unit 132, and a database storage unit 133. Configurations of the relay servers 22 and 33 are similar to that of the relay server 13.

[0028]

The interface unit 131 performs communication with the client terminals 11 and 12 by using private internet protocol (IP) addresses. The interface unit 131 performs communication with the SIP server 101 by using a global IP address.

[0029]

The control unit 132 manages a variety of databases stored in the database storage unit 133. The database storage unit 133 is composed of a relay group information storage unit 134, a relay server information storage

unit 135, a client terminal information storage unit 136, and a routing group information storage unit 137. Moreover, the control unit 132 has a similar configuration to that of a control unit 112 of the client terminal 11 to be described later.

[0030]

### <3. Configuration of client terminal>

FIG. 3 is a diagram showing the configuration of the client terminal 11. The client terminal 11 includes an interface unit 111, a control unit 112, an operation unit 113, a monitor 114, and a database storage unit 115. Note that configurations of the client terminals 12, 21, 31 and 32 are similar to that of the client terminal 11.

[0031]

The interface unit 111 performs communication with the relay server 13 by using the private IP address.

[0032]

The control unit 112 includes a LAN driver 191, a LAN-side IP packet processing unit 192, a WAN-side IP packet processing unit 193, a routing control unit 194, a routing session processing unit 195, and a routing session X unit 196.

[0033]

The LAN driver 191 is a driver software that controls the interface unit 111. The LAN-side IP packet processing unit 192 processes a communication packet received from the client terminal 12 or the like, and outputs the communication packet to the routing control unit 194. The routing control unit 194 decides a routing destination of the communication

packet based on information stored in the database storage unit 115. Based on the information stored in the database storage unit 115, the routing session processing unit 195 decides a routing session to relay the communication packet, and outputs the routing session to the routing session X unit 196. The routing session X is a media session to be established between the client terminal 11 and a specific relay server or client terminal. The routing session X unit 196 outputs the communication packet to the WAN-side IP packet processing unit 193. The WAN-side IP packet processing unit 193 transmits and receives the communication packet through the routing session X.

[0034]

The operation unit 113 is a keyboard, a mouse or the like, and receives an instruction to the client terminal 11. The monitor 114 is a liquid crystal display or the like.

[0035]

The database storage unit 115 is composed of a relay group information storage unit 117, a relay server information storage unit 118, and a routing group information storage unit 119.

[0036]

A description will be made below of a flow of processing of the relay communication system shown in FIG. 1, in the order from construction of a relay group to the routing processing.

[0037]

#### <4. Construction of relay group>

FIG. 4 is a chart showing a flow of processing for registering the

relay servers and the client terminals, which participate in the relay group. The respective administrators of the relay servers 13, 22 and 33 agree and decide to construct a group of the relay communication system among the LANs 1, 2 and 3.

[0038]

#### <4.1. Registration of relay servers and client terminals>

First, the administrator of the relay server 13 registers identification information and global IP address of the relay server 13 in the SIP server 101 (Step S1). In a similar way, the respective administrators of the relay servers 22 and 33 register identification information and global IP addresses of the relay servers 22 and 33 in the SIP server 101, respectively (Steps S2, S3).

[0039]

The SIP server 101 manages the identification information and global IP address of each of the relay servers in association with each other. In such a way, the SIP server 101 becomes capable of relaying the communication among the relay servers by using the global IP addresses of the respective relay servers.

[0040]

Next, accounts of the respective client terminals are created (Steps S4 to S8). Specifically, the administrator of the relay server 13 creates the account for the user of the client terminal 11 (Step S4), and creates the account for the user of the client terminal 12 (Step S5). The relay server 13 creates relay server information 51-1, which indicates details of the relay server 13, and client terminal information 61, which indicates details of the

client terminals 11 and 12. The relay server information 51-1 and the client terminal information 61 are stored in the relay server information storage unit 135 and the client terminal information storage unit 136, respectively.

[0041]

In a similar way, the administrator of the relay server 22 creates the account for the user of the client terminal 21 (Step S6). The relay server 22 creates relay server information 51-2, which indicates details of the relay server 22, and client terminal information 71, which indicates details of the client terminal 21.

[0042]

The administrator of the relay server 33 creates the account for the user of the client terminal 31 (Step S7), and creates the account for the user of the client terminal 32 (Step S8). The relay server 33 creates relay server information 51-3, which indicates details of the relay server 33, and client terminal information 81, which indicates details of the client terminals 31 and 32.

[0043]

#### <4.2. Logon processing of client terminals>

After the accounts for the users of the client terminals have been created, the client terminals log on to the respective relay servers (Steps S9 to S15). Note that the order in which the respective client terminals log on does not have to be the order described below.

[0044]

First, a description will be made of the logon (Steps S9 to S11) of the

client terminals 11 and 12. The user of the client terminal 11 inputs the identification information and password of the client terminal 11, and logs on to the relay server 13 (Step S9). In response to the logon of the client terminal 11, the relay server information 51-1 and the client terminal information 61 are updated. The client terminal 11 receives the relay server information 51-1 as a response to the logon to the relay server 13.

[0045]

FIG. 5 is a view showing information held by the relay server 13 after processing indicated in Step S9. The relay server information 51-1 is composed of upper information 511-1 regarding the relay server 13 and lower information 512-1 regarding the client terminals 11 and 12.

[0046]

In the upper information 511-1, “id” and “name” indicate the identification information and the name of the relay server 13. In “id”, the identification information “relay-server-1@abc.net” of the relay server 13 is set. In activation information 513-1, “active” is set, indicating that the relay server 13 has been activated.

[0047]

In the lower information 512-1, two node tags, which correspond to the client terminals 11 and 12, respectively, are created. In each of the node tags, “div”, “id” and “name” indicate a name of a division where the client terminal is installed, the identification information of the client terminal, and the name thereof. These pieces of information are set at the time of creating the client terminal information 61. “group” indicates the relay group in which the client terminals participate. Site information

514-1 indicates the identification information of the relay servers as logon destinations of the client terminals.

[0048]

“group” of each of the node tags in the lower information 512-1 is blank since the relay group has not been constructed at this point of time. The upper node tag of the lower information 512-1 corresponds to the client terminal 11, in which, as “id”, the identification information “client-11@relay-server-1.abc.net” of the client terminal 11 is set. In the site information 514-1, the identification information of the relay server 13 is set following the logon of the client terminal 11.

[0049]

The lower node tag of the lower information 512-1 corresponds to the client terminal 12, in which, as “id”, the identification information “client-12@relay-server-1.abc.net” of the client terminal 12 is set. The site information 514-1 is blank since the client terminal 12 has not logged on.

[0050]

In the client terminal information 61, two node tags, which correspond to the client terminals 11 and 12, respectively, are created. In each of the node tags, “div”, “id”, “name” and “pass” indicate the name of the division where the client terminal is installed, the identification information of the client terminal, the name thereof and the password thereof, respectively. These pieces of information are set at the time of creating the client terminal information 61. “group” indicates the relay group in which the client terminals participate. Address information 611, expiration period information 612 and port information 613 indicate the IP address of

the client terminal, a registration expiration period thereof, and a port number thereof, respectively, and are set at the time when each of the client terminals logs on.

[0051]

In the client terminal information 61, “group” of each of the node tags is blank since the relay group has not been constructed. The upper node tag of the client terminal information 61 corresponds to the client terminal 11, in which, as “id”, the identification information of the client terminal 11 is set. The client terminal 11 logs on (Step S9), whereby “192.168.1.11”, “1213” and “5070” are set in the address information 611, the expiration period information 612 and the port information 613, respectively.

[0052]

The lower node tag of the client terminal information 61 corresponds to the client terminal 12, in which, as “id”, the identification information of the client terminal 12 is set. The client terminal 12 has not logged on to the relay server 13 at the point of time in Step S9, and accordingly, the address information 611 is blank. Moreover, “0” is set in the expiration period information 612 and the port information 613.

[0053]

After the logon (Step S9) of the client terminal 11, the user of the client terminal 12 inputs the identification information and password of the client terminal 12, and logs on to the relay server 13 (Step S10).

[0054]

Following the logon of the client terminal 12, the relay server 13

updates the relay server information 51-1 and the client terminal information 61 to relay server information 52-1 and client terminal information 62, respectively. The client terminal 12 receives the relay server information 52-1 as a response to the logon to the relay server 13.

[0055]

FIG. 6 is a view showing information held by the relay server 13 after processing indicated in Step S10. Fields updated following the logon of the client terminal 12 are underlined.

[0056]

Due to the logon of the client terminal 12, the identification information of the relay server 13 is set in site information 524-1 in a lower node tag of lower information 522-1. In a lower node tag of the client terminal information 62, "192.168.2.22", "1213" and "5070" are set in address information 621, expiration period information 622 and site information 623, respectively.

[0057]

After the logon of the client terminal 12, the relay server 13 transmits the relay server information 52-1 to the client terminal 11 (Step S11). In such a way, the relay server information 51-1 held by the client terminal 11 is updated to the relay server information 52-1.

[0058]

Next, a description will be made of the logon (Step S12) of the client terminal 21. The user of the client terminal 21 inputs the identification information and password of the client terminal 21, and logs on to the relay server 22 (Step S12). Following the logon of the client terminal 21, the

relay server 22 updates the relay server information 51-2 and the client terminal information 71. The client terminal 21 receives the relay server information 51-2 as a response to the logon to the relay server 22.

[0059]

FIG. 7 is a view showing information held by the relay server 22 after processing of Step S12. The relay server information 51-2 is composed of upper information 511-2 and lower information 512-2. In "id" of the upper information 511-2, identification information "relay-server-2@abc.net" of the relay server 22 is registered. In activation information 513-2, "active" is set, indicating that the relay server 22 has been activated.

[0060]

"group" of each of the node tags in the lower information 512-2 and the client terminal information 71 is blank since the relay group has not been constructed.

[0061]

In the node tag of the lower information 512-2, the information regarding the client terminal 21 is registered. In "id", identification information "client-21@relay-server-2.abc.net" of the client terminal 21 is registered. Following the logon of the client terminal 21, the identification information of the relay server 22 is set in site information 514-2.

[0062]

In the client terminal information 71, the node tag corresponds to the client terminal 21, and as "id", the identification information of the client terminal 21 is set. Following the logon of the client terminal 21,

“172.16.1.21”, “1213” and “5070” are registered in address information 711, expiration period information 712 and port information 713, respectively.

[0063]

Next, a description will be made of the logon processing (Steps S13 to S15) of the client terminals 31 and 32. The user of the client terminal 31 inputs the identification information and password of the client terminal 31, and logs on to the relay server 33 (Step S13). In response to the logon of the client terminal 31, the relay server information 51-3 and the client terminal information 81 are updated. The client terminal 31 receives the relay server information 51-3 as a response to Step S13, and stores the relay server information 51-3 in a relay server information storage unit 318.

[0064]

FIG. 8 is a view showing information held by the relay server 33 after processing of Step S13. The relay server information 51-3 is composed of upper information 511-3 and lower information 512-3. In the upper information 511-3, as “id”, identification information “relay-server-3@abc.net” of the relay server 33 is registered. In activation information 513-3, “active” is set, indicating that the relay server 33 has been activated.

[0065]

“group” of each of the node tags in the lower information 512-3 and the client terminal information 81 is blank since the relay group has not been constructed.

[0066]

The upper node tag of the lower information 512-3 corresponds to

the client terminal 31, and as “id”, identification information “client-31@relay-server-3.abc.net” of the client terminal 31 is set. Due to the log on of the client terminal 31, the identification information of the relay server 33 is set in site information 514-3.

[0067]

The lower node tag of the lower information 512-3 corresponds to the client terminal 32, in which, as “id”, the identification information “client-32@relay-server-3.abc.net” of the client terminal 32 is set. The site information 514-3 is blank since the client terminal 32 has not logged on.

[0068]

The upper node tag of the client terminal information 81 corresponds to the client terminal 31, in which the identification information of the client terminal 31 is set as “id”. Following the logon of the client terminal 31, “200.1.2.31”, “1213” and “5070” are set in address information 811, expiration period information 812 and port information 813, respectively.

[0069]

The lower node tag of the client terminal information 81 corresponds to the client terminal 32, in which, as “id”, the identification information of the client terminal 32 is set. The address information 811 is blank since the client terminal 32 has not logged on. Moreover, “0” is set in the expiration period information 812 and the port information 813.

[0070]

After the logon (Step S13) of the client terminal 31, the user of the client terminal 32 inputs the identification information and password of the

client terminal 32, and logs on to the relay server 33 (Step S14).

[0071]

Following the logon of client terminal 32, the relay server 33 updates the relay server information 51-3 and the client terminal information 81 to relay server information 52-3 and client terminal information 82, respectively. The client terminal 32 receives the relay server information 52-3 as a response to Step S14.

[0072]

FIG. 9 is a view showing information held by the relay server 33 after processing of Step S14. Fields updated following the logon of the client terminal 32 are underlined.

[0073]

In site information 524-3 of a lower node tag of lower information 522-3, the identification information of the relay server 33 is set. Moreover, in a lower node tag of the client terminal information 82, "200.1.3.132", "1213" and "5070" are set in address information 821, expiration period information 822 and site information 823, respectively.

[0074]

After the logon of the client terminal 32, the relay server 33 transmits the relay server information 52-3 to the client terminal 31 (Step S15). The client terminal 31 updates the relay server information 51-3, which is stored in the relay server information storage unit 318, to the relay server information 52-3.

[0075]

<4.3. Creation of relay group information>

FIG. 10 is a chart showing a flow of processing regarding construction of the relay group. In FIG. 10, the client terminals 22 and 33 are not shown.

[0076]

After the processing of Step S15, the administrator of the relay server 13 inputs the identification information of the relay servers 13, 22 and 33, and instructs the relay server 13 to construct the relay group. The relay server 13 newly creates relay group information 41, and stores the relay group information 41 in the relay group information storage unit 134.

[0077]

FIG. 11 is a view showing information held by the relay server 13 after the construction of the relay group is instructed. The relay server information 52-1 and the client terminal information 62 are not changed from those in FIG. 6.

[0078]

The relay group information 41 is composed of upper information 411 regarding the relay group and lower information 412 regarding the relay servers which participate in the relay group. In the upper information 411, in “id”, identification information “group-a@relay-server-1.abc.net” of the relay group is set. “lastmod” and “name” indicate a latest update time of the relay group information 41 and a name of the relay group. Moreover, in the respective site tags of the lower information 412, the identification information of the relay servers 13, 22 and 33 are set.

[0079]

Through the SIP server 101, the relay server 13 requests the relay server 22 to construct the relay group in which the relay servers 13, 22 and 33 participate (Steps S16, S16.1). In a similar way, through the SIP server 101, the relay server 13 requests the relay server 33 to construct the relay group (Steps S17, S17.1). At the time of requesting the construction of the relay group, the relay group information 41 is transmitted to the relay servers 22 and 33.

[0080]

#### <4.4. Synthesis of relay server information>

Next, through the SIP server 101, the relay server 13 requests the relay server 22 for the relay server information 51-2 (Steps S18, S18.1), and requests the relay server 33 for the relay server information 52-3 (Steps S19, S19.1). The relay server 13 synthesizes the relay server information 52-1, 51-2 and 52-3, and creates relay server information 53. The client terminal information 62 is updated to client terminal information 63. In the relay server information storage unit 135, the relay server information 52-1 and 53 are stored.

[0081]

FIG. 12 is a view showing information held by the relay server 13 after processing of Step S19. Fields updated following the processing of Step S18 are underlined.

[0082]

In the relay server information 53, upper information 531-1 and lower information 532-1 correspond to the upper information 521-1 and the lower information 522-1, which are shown in FIG. 6, respectively. In a

similar way, upper information 531-2 and lower information 532-2 correspond to the upper information 511-2 and the lower information 512-2, which are shown in FIG. 7, respectively. Upper information 531-3 and lower information 532-3 correspond to the upper information 521-3 and the lower information 522-3, which are shown in FIG. 9, respectively.

[0083]

Following the construction of the relay group, identification information of the relay group is set in “group” of each of the node tags of the lower information 532-1, 532-2 and 532-3 and “group” of each of the node tags of the client terminal information 63.

[0084]

By referring to the client terminal information 63, the relay server 13 confirms that the client terminals 11 and 12 are logged on. The relay group information 41 and the relay server information 53 are transmitted to the client terminals 11 and 12 (Steps S20, S21).

[0085]

FIG. 13 is a chart showing a flow of processing during and after Step 22 in the construction of the relay group. In FIG. 13, the client terminals 11 and 12 are not shown.

[0086]

Through the SIP server 101, the relay server 22 requests the relay server 13 for the relay server information 52-1 (Steps S22, S22.1), and requests the relay server 33 for the relay server information 52-3 (Steps S23, S23.1). The relay server 22 synthesizes the relay server information 52-1, 51-2 and 52-3, and creates the relay server information 53. The client

terminal information 71 is updated to client terminal information 72. The relay server 22 continues to hold the relay server information 51-2.

[0087]

FIG. 14 is a view showing information held by the relay server 22 after processing of Step S23. Fields changed following the processing of Step S23 are underlined. The identification information of the relay group is newly set in “group” of the client terminal information 72.

[0088]

By referring to the client terminal information 72, the relay server 22 confirms that the client terminal 21 is logged on. The relay group information 41 and the relay server information 53 are transmitted to the client terminal 21 (Step S24).

[0089]

Next, through the SIP server 101, the relay server 33 requests the relay server 13 for the relay server information 52-1 (Steps S25, S25.1), and requests the relay server 22 for the relay server information 51-2 (Steps S26, S26.1). The relay server 33 synthesizes the relay server information 52-1, 51-2 and 52-3, and creates relay server information 53. The client terminal information 82 is updated to client terminal information 83.

[0090]

FIG. 15 is a view showing information held by the relay server 33 after processing of Step S26. Fields changed following the processing of Step S26 are underlined. The identification information of the relay group is newly set in “group” of each of the node tags of the client terminal information 83.

[0091]

By referring to the client terminal information 83, the relay server 33 confirms that the client terminals 31 and 32 are logged on. The relay group information 41 and the relay server information 53 are transmitted to both the client terminals 31 and 32 (Steps S27, S28).

[0092]

As a result of the processing up to this point, the relay group is constructed in which the client terminals 11, 12, 21, 31 and 32 and the relay servers 13, 22 and 33 participate. The computers which participate in the relay group can confirm the configuration of the relay group, operation states of the individual computers, and the like, by referring to the relay group information 41 and the relay server information 53.

[0093]

#### <5. Flow of routing processing (first embodiment) >

A description will be made of routing processing according to a first embodiment in the relay communication system shown in FIG. 1.

[0094]

##### <5.1. Detailed configuration of LAN>

FIG. 16 is a diagram showing detailed configurations of the LANs 1 to 3. In FIG. 16, the SIP server 101 is not shown. General terminals are connected to the LANs 1 to 3 as personal computers that do not function as client terminals.

[0095]

The LAN 1 has a configuration in which a LAN 10-1 and a LAN 10-2 are connected to each other through a general-purpose router 14. The

client terminal 11, the relay server 13 and a general terminal 15 are connected to the LAN 10-1. The client terminal 12 and a general terminal 16 are connected to the LAN 10-2. Network addresses of the LANs 10-1 and 10-2 are "192.168.1.0/24" and "192.168.2.0/24" (24 at the end is a subnet mask).

[0096]

A general terminal 23 is connected to the LAN 2, in addition to the client terminal 21 and the relay server 22. The network address of the LAN 2 is "192.100.1.0/24".

[0097]

The LAN 3 has a configuration, in which a LAN 30-1 and a LAN 30-2 are connected to each other through a general-purpose router 34, and the LAN 30-1 and a LAN 30-3 are connected to each other through a general-purpose router 35. The relay server 33 is connected to the LAN 30-1. The client terminal 31 and a general terminal 36 are connected to the LAN 30-2. The client terminal 32 and a general terminal 37 are connected to the LAN 30-3. Network addresses of the LANs 30-2 and 30-3 are "200.1.2.0/24" and "200.1.3.0/24".

[0098]

#### <5.2. Sharing routing group information>

A description will be made of sharing of routing group information for use in the routing processing according to this embodiment.

[0099]

FIG. 17 is referred to. The user of the client terminal 11 instructs construction of a first routing group. The client terminal 11 stores routing

group information 91, which is created in response to the instruction of the user, in the routing group information storage unit 119. The client terminal 11 transmits the routing group information 91 to the relay server 13 (Step S31), and issues a notice to the relay server 13 of the construction of the first routing group. The relay server 13 stores the received routing group information 91 in the routing group information storage unit 137.

[0100]

FIG. 18 is a view showing the routing group information 91. The routing group information 91 is composed of body information 911, routing target information 912, routing permission information 913, and session information 914.

[0101]

The body information 911 is information regarding the routing group information 91 itself. “group” indicates identification information of the relay group. “id”, “lastmod”, “name” and “owner” indicate identification information, latest update time, name and creation source of the routing group information 91.

[0102]

The routing target information 912 is information regarding a network that serves as a routing target, and is composed of network information 912-1 to 912-3. In each network information, “addr” indicates the network address of the network that serves as the routing target. “router” indicates a client terminal that routes an IP packet from the network set in “addr”.

[0103]

In the network information 912-1, the network address of the LAN 10-2 is set as “addr”, and the identification information of the client terminal 11 is set as “router”. In the network information 912-2, the network address of the LAN 2 is set as “addr”, and the identification information of the client terminal 21 is set as “router”. In the network information 912-3, the network address of the LAN 30-2 is set as “addr”, and the identification information of the client terminal 31 is set as “router”. That is to say, the client terminals 11, 21 and 31 are set so as to function as routing devices.

[0104]

The routing permission information 913 indicates communication terminals capable of using the routing function of the relay communication system, and is composed of permitted terminal information 913-1 to 913-3. Here, “communication terminals” refer to all of the relay servers, the client terminals and the general terminals, which are individually connected to the LANs 1 to 3. For example, in the LAN 1, the client terminals 11 and 12, the relay server 13, and the general terminals 15 and 16 all correspond to the communication terminals. Accordingly, even the general terminals which do not compose the relay communication system can use the routing function of the relay communication system.

[0105]

In each of the permitted terminal information, “name” and “addr” indicate the name and IP address of the communication terminal capable of using the routing function. The permitted terminal information 913-1 corresponds to the general terminal 16, in which “192.168.2.150” is set as

“addr”. The permitted terminal information 913-2 corresponds to the general terminal 23, in which “192.100.1.150” is set as “addr”. In the permitted terminal information 913-3, as “addr”, “200.1.2.\*” is set, which indicates that all of the communication terminals connected to the LAN 30-2 can use the routing function. Note that, though the identification information of the general terminal is set in the permitted terminal information 913-1 and 913-2, the identification information of the client terminals and the relay servers may be set therein.

[0106]

The session information 914 is composed of point information 914-1 to 914-3 regarding routing sessions for use in the routing of the communication packet. “start” and “end” of each of the point information indicate a start point and an end point of the routing session.

[0107]

Since the point information 914-1 to 914-3 have been created, three routing sessions are established in the first routing group. The point information 914-1 corresponds to a first routing session, in which the identification information of the client terminals 11 and 21 are set in “start” and “end”. The point information 914-2 corresponds to a second routing session, in which the identification information of the client terminals 11 and 31 are set in “start” and “end”. The point information 914-3 corresponds to a third routing session, in which the identification information of the client terminals 21 and 31 are set in “start” and “end”.

[0108]

FIG. 17 is referred to one more time. The relay server 13 issues a

notice of the construction of the first routing group to the client terminals 21 and 31 which function as the routing devices. Specifically, the relay server 13 transmits the routing group information 91 to the client terminal 21 through the SIP server 101 and the relay server 22 (Steps S32, S32.1 and S32.1.1). In a similar way, the routing group information 91 is transmitted to the client terminal 31 through the SIP server 101 and the relay server 33 (Steps S33, S33.1 and S33.1.1). In such a way, the relay servers 13, 22 and 33, and the client terminals 11, 21 and 31 which function as the routing devices share the routing group information 91.

[0109]

#### <5.3. Establishment of routing session>

Next, first to third routing sessions are established. The client terminal 11 refers to the point information 914-1 and 914-2, and confirms that the terminal itself has been set at the start points of the first and second routing sessions.

[0110]

In order to establish the first routing session between the client terminals 11 and 21, the client terminal 11 transmits an establishment request of the first routing session to the relay server 13 (Step S34). In response to a response from the relay server 13, the client terminal 11 transmits an ACK to the relay server 13 (Step S35). In response to the ACK, the relay server 13 establishes a media session between the client terminal 11 and the relay server 13 (Step S36).

[0111]

After step S36, the relay server 13 transmits the establishment

request of the first routing session to the relay server 22 through the SIP server 101 (Steps S37, S37.1). In response to a response from the relay server 22, the relay server 13 transmits an ACK to the relay server 22 through the SIP server 101 (Steps S38, S38.1). In response to the ACK, the relay server 22 establishes a media session between the relay servers 13 and 22 (Step S39).

[0112]

After Step S39, a media session is established between the client terminal 21 and the relay server 22 (Steps S40, S41 and S42). The processing is similar to those of Steps S34 to S36.

[0113]

The first routing session is composed based on the three media sessions established in Steps S36, S39 and S42.

[0114]

FIG. 19 is referred to. In a similar way to the establishment of the first routing session, the second routing session is established between the client terminals 11 and 31. A media session is established between the client terminal 11 and the relay server 13 (Steps S43, S44 and S45). A media session is established between the relay servers 13 and 33 (Steps S46, S46.1, S47, S47.1 and S48). A media session is established between the client terminal 31 and the relay server 33 (Steps S49, S50 and S51). The second routing session is composed of the three media sessions established in Steps S45, S48 and S51.

[0115]

The client terminal 21 refers to the point information 914-3, and

confirms that the terminal itself has been set at the start point of the third routing session. Then, the third routing session is established between the client terminals 21 and 31.

[0116]

A media session is established between the client terminal 21 and the relay server 22. A media session is established between the relay servers 22 and 33. A media session is established between the client terminal 31 and the relay server 33. The third routing session is composed of the three media sessions established.

[0117]

#### <5.4. Routing control of communication packet>

The communication terminals set in the permitted terminal information 913-1 to 913-3 can perform communication, in which IP addresses are directly designated, with one another through the first to third routing sessions.

[0118]

FIG. 21 is referred to. The general terminal 16 sends out a first communication packet destined for the general terminal 23 (Step S61). When having received the first communication packet, the client terminal 11 refers to the routing group information 91, and determines whether or not it is possible to route the first communication packet.

[0119]

First, based on the routing target information 912, the client

terminal 11 determines whether or not the first communication packet can be routed. An IP address “192.100.1.150” of the destination (general terminal 23) of the first communication packet corresponds to the network address of the LAN 2 set in the network information 912-2. An IP address “192.168.2.150” of the transmission source (general terminal 16) corresponds to the network address of the LAN 10-2 set in the network information 912-1. Therefore, the client terminal 11 determines that the first communication packet can be routed.

[0120]

Next, the client terminal 11 refers to the routing permission information 913, and confirms whether or not the routing of the first communication packet is permitted. The IP address of the transmission source (general terminal 16) of the first communication packet is set in the permitted terminal information 913-1, and the IP address of the destination (general terminal 23) of the first communication packet is set in the permitted terminal information 913-2. Therefore, the client terminal 11 determines that the routing of the first communication packet is permitted. Note that the determination as to whether or not such routing is possible may also be performed based on just one of the IP address of the transmission source of the first communication packet and the IP address of the destination of the same.

[0121]

Since the identification information of the client terminal 21 is set in the network information 912-2 and the point information 914-1, the client terminal 11 decides to use the first routing session for the routing of the

first communication packet. Then, the first communication packet is sent out by using the first routing session (Steps S62, S62.1 and S62.1.1). The client terminal 21 transfers the first communication packet, which has been received through the first routing session, to the general terminal 23 (Step S63).

[0122]

The first communication packet is encapsulated at the time of being transferred using the first routing session, and accordingly, the general terminals 16 and 23 can communicate with each other without being conscious of the route of the network from the client terminal 11 to the client terminal 21. That is to say, the general terminals 16 and 23 can communicate with each other through the WAN 100 by using the private IP addresses.

[0123]

Next, the general terminal 16 sends out a second communication packet destined for the general terminal 36 (Step S64). The destination of the second communication packet corresponds to the network information 912-3, and the transmission source of the second communication packet corresponds to the network information 912-1. Accordingly, the client terminal 11 determines that the second communication packet can be routed. Moreover, the IP address “200.1.2.150” of the destination (general terminal 36) of the second communication packet corresponds to “200.1.2.\*” set in the permitted terminal information 913-3, and the transmission source of the same corresponds to the permitted terminal information 913-1. Therefore, the client terminal 11 determines that the routing of the second

communication packet is permitted, and sends out the second communication packet by using the second routing session (Steps S65, S65.1 and S65.1.1). The client terminal 31 transfers the second communication packet to the general terminal 36 (Step S66).

[0124]

Next, the general terminal 23 sends out a third communication packet destined for the general terminal 36 (Step S67). The destination of the third communication packet corresponds to the network information 912-3, and the transmission source of the third communication packet corresponds to the network information 912-2. Moreover, the destination of the third communication packet corresponds to the permitted terminal information 913-3, and the transmission source of the same corresponds to the permitted terminal information 913-2. Therefore, the client terminal 21 determines that it is possible to route the received third communication packet, and sends out the third communication packet by using the third routing session (Steps S68, S68.1 and S68.1.1). The client terminal 31 transmits the third communication packet to the general terminal 36 (Step S69).

[0125]

As described above, the routing function according to this embodiment is validated by sharing the routing group information among the client terminals which can communicate with one another. Then, by using the first to third routing sessions established for the routing, the routing control for the IP packets is performed based on the function of the relay communication system. Accordingly, the routing validated in this

embodiment is executed in the application layer, and differs from the usual IP routing.

[0126]

Moreover, in this embodiment, in addition to the terms “client terminal” and “general terminal”, the term “communication terminal” is used on purpose. The “client terminals” are terminals capable of logging on to the relay servers, the “general terminals” are terminals incapable of logging on to the relay servers, and meanwhile, the “communication terminals” represent all of the terminals including the “relay servers”, the “client terminals” and the “general terminals”. This is because, by using the above-described routing sessions, routing is possible for the “communication terminals” which are connected to the LANs 1 to 3 and are registered in the permitted terminal information without being limited to the relay servers and the client terminals which are logged on to the relay servers.

[0127]

As described above, by using the routing group information 91, the relay communication system of this embodiment can allow the client terminals to function as the routing devices. Hence, the routing control using the relay communication system can be executed flexibly.

[0128]

Moreover, by registering the communication terminals which can use the routing function in the routing permission information 913, the communication packets to be routed can be restricted. Therefore, it becomes easy to manage the communication terminals which can use the

routing function of the relay communication system.

[0129]

<6. Flow of routing control (second embodiment)>

A description will be made of routing control according to a second embodiment. Configurations of LANs 1 to 3 are similar to the configurations shown in FIG. 16.

[0130]

This embodiment is different from the above-described first embodiment in that the relay server 13 functions as the routing device, and that ending processing for the routing control is performed. A description will be mainly made below of points different from the above-described first embodiment.

[0131]

The relay server 13 creates the routing group information 92 in response to the instruction to construct the second routing group. Note that the control unit 132 of the relay server 13 has a similar configuration to that of the control unit 112 of the client terminal 11.

[0132]

FIG. 22 is a view showing the routing group information 92. In network information 922-1 of routing target information 922, the network address of the LAN 10-1 is set as "addr", and the identification information of the relay server 13 is set as "router". In network address information 922-2 of the routing target information 922, the network address of the LAN 30-3 is set as "addr", and the identification information of the client terminal 32 is set as "router".

[0133]

In permitted terminal information 923-1 of routing permission information 923, an IP address “192.168.1.150” of the general terminal 15 is set. In permitted terminal information 923-2, “200.1.3.\*” indicating all of the communication terminals connected to the LAN 30-3 is set. Point information 924-1 of session information 924 corresponds to a fourth routing session, in which the identification information of the relay server 13 and the client terminal 32 are set in “start” and “end”.

[0134]

FIG. 23 is referred to below. The routing group information 92 is transferred to the client terminal 32 through the SIP server 101 and the relay server 33 (Steps S70, S70.1 and S70.1.1). In such a way, the relay server 33, and the relay server 13 and the client terminal 32, which serve as the routing devices, share the routing group information 92.

[0135]

Based on the routing group information 92, the fourth routing session is established between the relay server 13 and the client terminal 32. A media session is established between the relay servers 13 and 33 (Steps S71 and S71.1 and Steps S72, S72.1 and S73). A media session is established between the client terminal 32 and the relay server 33 (Steps S74, S75 and S76). The fourth routing session is composed of the two media sessions established in Steps S73 and S76.

[0136]

Next, the general terminal 15 sends out a fourth communication packet destined for the general terminal 37 (Step S77). The destination of

the fourth communication packet corresponds to the network information 922-2, and the transmission source of the fourth communication packet corresponds to the network information 922-1. Moreover, the destination of the fourth communication packet corresponds to the permitted terminal information 923-2, and the transmission source corresponds to the permitted terminal information 923-1. Therefore, the relay server 13 determines that it is possible to route the received fourth communication packet, and transfers the fourth communication packet to the client terminal 32 by using the fourth routing session (Steps S78, S78.1). The client terminal 32 transfers the fourth communication packet to the general terminal 37 (Steps S79).

[0137]

With reference to FIG. 24, a description will be made of a flow for ending the routing. In response to an instruction to end the routing, which is based on the routing group information 92, the client terminal 32 deletes the routing group information 92. Such an end instruction is transmitted to the relay server 13 through the relay server 33 and the SIP server 101 (Steps S80, S80.1 and S80.1.1.). Based on the end instruction, the relay server 13 deletes the routing group information 92.

[0138]

When having received a response to the end instruction, the client terminal 32 transmits a disconnection request of the fourth routing session to the relay server 33 (Step S81). Based on the disconnection request, the media session between the client terminal 32 and the relay server 33 in the fourth routing session is disconnected. The relay server 33 transmits the

disconnection request of the fourth routing session to the relay server 13 through the SIP server 101 (Steps S82 and S82.1). Based on the disconnection request, the media session between the relay servers 13 and 33 in the fourth routing session is disconnected. In such a way, the routing processing based on the routing group information 92 is ended.

[0139]

Following the end of the routing processing, the communication between the general terminals 15 and 37 becomes impossible. Even if the general terminal 15 sends out the fourth communication packet (Step S83), the relay server 13 cannot recognize the destination of the received fourth communication packet since the relay server 13 does not hold the routing group information 92. Therefore, the relay server 13 notifies the general terminal 15 that the fourth communication packet cannot reach the destination.

[0140]

As described above, in this embodiment, the relay server 13 can function as the routing device. Moreover, in response to the end instruction, the fourth routing session is disconnected, and accordingly, it becomes easier to manage the routing function of the relay communication system.

[0141]

#### <7. Flow of routing processing (third embodiment)>

A description will be made of routing processing according to a third embodiment. Configurations of LANs 1 to 3 are similar to the configurations shown in FIG. 16. In this embodiment, the configuration of

the routing sessions is changed following the change of the routing group information. A description will be mainly made below of points different from the above-described first and second embodiments.

[0142]

First, in response to an instruction of the user, the client terminal 31 updates the routing group information 91 to routing group information 93.

[0143]

FIG. 25 is a view showing the routing group information 93. Fields changed from the routing group information 91 are underlined. A latest update time is changed in body information 931 and in tags in which “lastmod” had been set.

[0144]

In routing target information 932, the network information 912-1 and 912-3 are not changed. In place of the network information 912-2, network information 932-1 is set, in which the network address of the LAN 30-3 is set in “addr” and the identification information of the client terminal 32 is registered in “router”.

[0145]

In routing permission information 933, “lastmod” is changed in the permitted terminal information 913-1 and 913-3. In place of the permitted terminal information 913-2, permitted terminal information 933-1 is registered, in which “200.1.3.\*” is set in “addr”, indicating all of the communication terminals in the LAN 30-3.

[0146]

In session information 934, the point information 914-2 is not

changed. In place of the point information 914-1, point information 934-1 is set, which corresponds to a fifth routing session, and in which the identification information of the client terminals 11 and 32 are registered in “start” and “end”. In place of the point information 913-3, point information 934-2 is set, which corresponds to a sixth routing session, and in which the identification information of the client terminals 31 and 32 are registered in “start” and “end”.

[0147]

FIG. 26 is referred to. As a notice of change of the routing group information 92, the client terminal 31 transmits the routing group information 93 to the relay server 33 (Step S83). The relay server 33 transfers the routing group information 93 as the notice of change to the client terminals whose identification information are set in “router” of the network information 912 and 932. The routing group information 93 is transmitted to the client terminal 11 through the SIP server 101 and the relay server 13 (Steps S83.1, S83.1.1 and S83.1.1.1). The routing group information 93 is transferred to the client terminal 21 from the SIP server 101 through the relay server 22 (Steps S83.1.2, and S83.1.2.1). Moreover, the relay server 33 transmits the routing group information 93 to the client terminal 32 (Step S83.2).

[0148]

A description will be made of the disconnection of the first and third routing sessions, which is based on the update to the routing group information 93. The client terminal 11 refers to the routing group information 93, and confirms that the point information 914-1

corresponding to the first routing session has been deleted. Then, the first routing session is disconnected (Steps S84, S85, S85.1 and S86). The client terminal 21 refers to the routing group information 93, and confirms that the terminal itself is not registered in the routing target information 932. Then, the third routing session is disconnected (Steps S87, S88, S88.1 and S89).

[0149]

Note that the point information 914-2 is in a state of having been set in the routing group information 93, and accordingly, the second routing session established between the client terminals 11 and 31 is maintained.

[0150]

FIG. 27 is referred to. In order to establish the fifth routing session between the client terminals 11 and 32, a media session is established between the client terminal 11 and the relay server 13 (Steps S90, S91 and S92). A media session is established between the relay servers 13 and 33 (Steps S93, S93.1, S94, S94.1 and S95). A media session is established between the client terminals 32 and the relay server 33 (S96, S97 and S98). The three media sessions established in Steps S92, S95 and S98 compose the fifth routing session.

[0151]

Next, in order to establish the sixth routing session between the client terminals 31 and 32, a media session is established between the client terminal 31 and the relay server 33 (Steps S99, S100 and S101) and a media session is established between the client terminal 32 and the relay server 33 (S102, S103 and S104). The two media sessions established in Steps S101

and S104 compose the sixth routing session.

[0152]

With reference to FIG. 28, a description will be made of routing processing using the fifth and sixth routing sessions. The general terminal 37 sends out a fifth communication packet destined for the general terminal 16 (Step S105). The destination of the fifth communication packet corresponds to the network information 912-1, and the transmission source of the fifth communication packet corresponds to the network information 932-1. Moreover, the destination of the fifth communication packet corresponds to the permitted terminal information 913-1, and an IP address “200.1.3.250” of the transmission source (general terminal 37) corresponds to “200.1.3.\*” set in the permitted terminal information 933-1. Therefore, the client terminal 32 determines that it is possible to route the received fifth communication packet, and transfers the fifth communication packet to the client terminal 11 by using the fifth routing session (Steps S106, S106.1 and S106.1.1). The client terminal 11 transfers the fifth communication packet to the general terminal 16 (Step S107).

[0153]

Next, the general terminal 36 sends out a sixth communication packet destined for the general terminal 37 (Step S108). The destination of the sixth communication packet corresponds to the network information 932-1, and the transmission source of the sixth communication packet corresponds to the network information 912-3. Moreover, the destination of the sixth communication packet corresponds to the permitted terminal information 933-1, and the transmission source of the same corresponds to

the permitted terminal information 913-3. Therefore, the client terminal 31 determines that it is possible to route the received sixth communication packet, and transfers the sixth communication packet to the client terminal 32 by using the sixth routing session (Steps S109 and S109.1). The client terminal 32 transfers the sixth communication packet to the general terminal 37 (Step S110).

[0154]

As described above, the relay communication system according to this embodiment changes the routing group information 92 to the routing group information 93, thereby can dynamically change the configurations of the routing sessions.

[0155]

#### <8. Operations of client terminal>

Here, by referring to FIGS. 29 to 31, a description will be made of operations of the client terminal that functions as the routing device. The following description is also applied to the relay server 13.

[0156]

##### <8.1. Start of routing processing>

FIG. 29 is a flowchart showing a flow of starting the routing processing. Here, the description will be made using the client terminal 11 as an example.

[0157]

The client terminal 11 newly creates the routing group information 91 in response to the instruction to construct the first routing group (Step S201). At this point, the network information, the permitted terminal

information and the point information are not set in the routing group information 91.

[0158]

In the case where the network address of the LAN and the identification information of the client terminal that functions as the routing device are set (Yes in Step S202), the network information is added to the routing group information 91 (Step S203). In the case where the communication terminal permitted to use the routing function is set, (Yes in Step S204), the permitted terminal information is added to the routing group information 91 (Step S205).

[0159]

In the case where the end of the setting has been instructed (Yes in Step S206), the client terminals registered in each of the network information are set as the start point and the end point, whereby the point information is created (Step S207), and is added to the routing group information 91.

[0160]

In such a way, the routing group information 91 turns into the state shown in FIG. 18. In order to issue a notice of the construction of the first routing group, the routing group information 91 is transmitted to the relay server 13 (Step S208). This processing corresponds to Step S31 (refer to FIG. 17).

[0161]

Next, the client terminal 11 transmits a routing command that requests for the establishment of the routing session (Step S209), and, as a

result, the routing session is established (Step S210). The processing of Steps S209 and S210 are repeated based on the number of point information, whereby the first to third routing sessions are established. The processing of Step S209 corresponds to Steps S31 to S33 (refer to FIG. 17) and the like, and the processing of Step S210 corresponds to Steps S34 to S42 (refer to FIG. 17) and the like. The client terminal 11 starts routing using the routing sessions (Step S211).

[0162]

#### <8.2. End of routing processing>

FIG. 30 is a flowchart showing operations of the client terminal at the time of ending the routing processing. Here, a description will be made of the operations using, as an example, the client terminal 32 that is executing the routing processing (second embodiment) based on the second routing group.

[0163]

First, the user instructs the client terminal 32 to end the routing processing, which is based on the routing group information 92. Since the routing group information 92 is selected as an end target (Yes in Step S301), the client terminal 32 stops the routing processing which uses the fourth routing session (Step S302).

[0164]

The client terminal 32 transmits a deletion command of the routing group information 92 to the relay server 13 registered in the network information 922·2 (Step S303). This processing corresponds to Steps S80 to S80.1.1. (refer to FIG. 24). The client terminal 32 deletes the routing group

information 92 (Step S304). Then, the fourth routing session is disconnected (Step S305). This processing corresponds to Steps S81 to S82.1 (refer to FIG. 24).

[0165]

### <8.3. Packet receiving processing>

FIG. 31 is a flowchart showing operations of the client terminal in a state in which the routing session has been established. Here, a description will be made of the operations using the client terminal 11 as an example.

[0166]

When having received the communication packet, the client terminal 11 analyzes the communication packet (Step S401), and determines whether or not the communication packet is a routing packet (Step S402). If the communication packet is not the routing packet (No in Step S402), the client terminal 11 performs normal packet receiving processing (Step S403).

[0167]

If the communication packet is the routing packet (Yes in Step S402), the client terminal 11 detects the destination IP address and transmission source IP address of the communication packet (Step S404). When not holding the routing group information 91 (No in Step S405), the client terminal 11 notifies the transmission source of the communication packet that the communication packet cannot reach the destination (Step S406).

[0168]

When holding the routing group information 91 (Yes in Step S405),

the client terminal 11 reads the routing group information 91 (Step S407), and confirms whether or not the communication packet matches the routing conditions (Step S408).

[0169]

In the case where the communication packet satisfies the following first condition and second condition, it is determined that the communication packet satisfies the routing conditions. The first condition is that the destination IP address and transmission source IP address of the communication packet have been set in any of the network information 912-1 to 912-3. The second condition is that the destination IP address and transmission source IP address of the communication packet correspond to any of the permitted terminal information 913-1 to 913-3.

[0170]

If the communication packet satisfies the routing conditions (Yes in Step S408), the client terminal 11 selects the routing session to transfer the communication packet (Step S409), and sends out the communication packet to the selected routing session (Step S410). Meanwhile, in the case where the communication packet does not satisfy the routing conditions (No in Step S408), the client terminal 11 notifies the transmission source that the communication packet cannot reach the destination (Step S406).

[0171]

As described above, the relay communication system according to the present invention routes the communication packet among the communication terminals through the WAN 100 based on the routing group information regarding the routing sessions required for the routing. The

client terminals, which function as the routing devices, and the relay servers can establish the routing sessions based on the routing group information. Accordingly, it becomes easy to manage the routing function of the relay communication system.

[0172]

Moreover, whether or not the communication packet is to be routed is determined based on the IP addresses set in the permitted terminal information of the routing group information and on the transmission source IP address and destination IP address of the communication packet. Hence, the communication terminals capable of using the routing function of the relay communication system can be managed easily.

[0173]

#### <9. Flow of routing processing (fourth embodiment)>

A description will be made of a flow of routing processing using the relay communication system shown in FIG. 1.

[0174]

##### <9.1. Detailed configuration of LANs>

Detailed configurations of LANs are similar to those of FIG. 16, and accordingly, a description thereof is omitted here.

Note that, in this embodiment, a description thereof is made on the assumption that, unlike other client terminals, the client terminal 12 does not have the routing control function of the communication packet.

[0175]

##### <9.2. Flow of processing of network search>

FIG. 32 is a chart showing a flow of search processing for the

network capable of routing the communication packet using the relay communication system. The user of the client terminal 11 inputs an instruction to search the network capable of such routing using the relay communication system (Step S131). In response, the client terminal 11 transmits a network search command to the relay server 13 (Step S132). [0176]

The relay server 13 refers to relay group information 141, and thereby specifies the relay servers 22 and 33, which compose the relay group, as transfer destinations of the network search command. First, the relay server 13 transmits the network search command to the relay server 22 through the SIP server 101 (Steps S133 and S133.1). The relay server 22 refers to the client terminal information 71, and transmits the network search command to the client terminal 21 that is logged on (Step S133.1.1). [0177]

The client terminal 21 has the routing function, and is capable of performing routing for the LAN 2, and accordingly, transmits the network address of the LAN 2 to the relay server 22. The relay server 22 creates network search information 191 based on a response of the client terminal 21, and transmits the network search information 191 as a response to the network search command to the relay server 13. [0178]

FIG. 33 is a view showing the network search information 191. In the network search information 191, body information 1911 is information regarding the network search information 191 itself. In “name”, “IP routing map” is set, which indicates that the network search information

191 is the response to the network search command, and in “owner”, the identification information of the relay server 22 is set as a creation source of the network search information 191.

[0179]

Network search list information 1912 is a list of responses from the relay servers and the client terminals that have the routing function. In routing device response information 1912-1, in “addr”, the network address of the LAN 2 is set as the network capable of the routing, and in “router” the identification information of the client terminal 21 is set. In routing device response information 1912-2, the network address of the LAN 2 and the identification information of the relay server 22 are set. This is because the relay server 22 can function as the routing device of the LAN 2.

[0180]

Next, the relay server 13 transmits the network search command to the relay server 33 through the SIP server 101 (Steps S134 and S134.1). The relay server 33 transfers the network search command to the client terminals 31 and 32 (Steps S134.1.1 and S134.1.2). The client terminals 31 and 32 having the routing function respectively transmit, to the relay server 33, the network addresses of the LANs 30-2 and 30-3 capable of the routing. The relay server 33 creates network search information 192 based on responses of the client terminals 31 and 32, and transmits the network search information 192 to the relay server 13.

[0181]

FIG. 34 is a view showing the network search information 192. In “owner” of body information 1921, the identification information of the relay

server 33 is set. In routing device response information 1922-1 of network search list information 1922, the network address of the LAN 30-2 and the identification information of the client terminal 31 are set. In routing device response information 1922-2, the network address of the LAN 30-3 and the identification information of the client terminal 32 are set. The relay server 33 that does not have the routing function is not registered in the network search information 192.

[0182]

FIG. 32 is referred to one more time. The relay server 13 transmits a network search command to the client terminal 12 (Step S135). Since the client terminal 12 does not have the routing function, the client terminal 12 does not transmit, as a response to the network search command, the network address of the LAN capable of the routing.

[0183]

The relay server 13 synthesizes the received network search information 191 and 192, thereby creates network search information 193. As a response to the network search command, the network search information 193 is transmitted to the client terminal 11.

[0184]

The client terminal 11 has the routing function, and is capable of routing for the LAN 10-2, and accordingly, updates the network search information 193 to network search information 194. Then, based on the network search information 194, the client terminal 11 displays a search result of the network on a monitor (Step S136).

[0185]

FIG. 35 is a view showing the network search information 194. In “owner” of body information 1941, the identification information of the client terminal 11 is set. Network search list information 1942 is a list of the network addresses of the LANs capable of the routing in the relay communication system.

[0186]

Routing device response information 1932-1 is information added at the time when the network search information 191 and 192 are synthesized and the network search information 193 is created. In the routing device response information 1932-1, the network address of the LAN 10-1 for the relay server 13 is capable of routing, and the identification information of the relay server 13 are set.

[0187]

Routing device response information 1942-1 is added when the network search information 193 is updated to the network search information 194. In routing device response information 1942-1, the network address of the LAN 10-2 for the client terminal 11 is capable of routing, and the identification information of the client terminal 11 are set.

[0188]

FIG. 36 is a list of the LANs displayed as a result of the network search on the monitor of the client terminal 11 based on the network search information 194. As shown in FIG. 36, the network addresses of the LANs capable of the routing and the relay servers or the client terminals, which are capable of the routing control for the respective LANs, are displayed in association with each other. The user of the client terminal 11 refers to the

list shown in FIG. 36, and can confirm the LANs capable of the routing in the relay communication system.

[0189]

Note that, in the network search processing, since only networks capable of using the routing function of the relay communication system need to be searched, it is not necessary to set the identification information of the client terminal or the relay server in each piece of the routing device response information.

[0190]

FIG. 37 is a flowchart showing operations of the client terminal 11 that executes the network search. Processing shown in FIG. 37 corresponds to Steps S131 and S132 (refer to FIG. 32). In the case where the client terminal 11 has been instructed to perform the network search (Yes in Step S1101), the client terminal 11 transmits the network search command to the relay server 13, to which the client terminal 11 is logged on, based on the relay server information 53 (refer to FIG. 12) (Step S1102). When having received network search information 193 as a response to the network search command (Yes in Step S1103), the client terminal 11 updates the network search information 193 to the network search information 194. Then, the list shown in FIG. 36 is displayed on the monitor of the client terminal 11 based on the network search information 194 (Step S1104).

[0191]

FIG. 38 is a flowchart showing operations of the relay server 13 that has received the network search command. When having received the

network search command from the client terminal 11 (Yes in Step S1151), the relay server 13 refers to the relay group information 141 (Step S1152). In the case where the network search command has not been transmitted to all of the relay servers registered in the relay group information 141 (No in Step S1153), the network search command is transmitted to the relay servers specified in the relay group information 141 (Step S1154). This processing corresponds to the processing of Steps S133 and S133.1 and the like (refer to FIG. 32). When having received a response to the network search command (Yes in Step S1155), the relay server 13 updates the network search information based on the received response (Step S1156), and returns to Step S1153.

[0192]

In the case where the network search command has been transmitted to all of the relay servers (Yes in Step S1153), the relay server 13 refers to the client terminal information 63 (refer to FIG. 12) (Step S1157). In the case where the network search command has not been transmitted to all of the client terminals which are logged on (No in Step S1158), the relay server 13 specifies the client terminals, which are logged on, from the client terminal information 63 (refer to FIG. 12). The network search command is transmitted from the relay server 13 to the specified client terminals (Step S1159). This processing corresponds to the processing of Step S135 (refer to FIG. 32). When having received a response to the network search command (Yes in Step S1160), the relay server 13 updates the network search information based on the received response (Step S1161), and returns to Step S1158.

[0193]

In the case where the network search command has been transmitted to all of the client terminals which are logged on (Yes in Step S1158), the relay server 13 transmits the network search information to the client terminal as the transmission source of the network search command (Step S1162). In such a way, the processing of the relay server 13 that has received the network search command is ended.

[0194]

### <9.3. Flow of route search processing>

FIG. 39 is a chart showing a flow of route search processing. The user of the client terminal 11 refers to the network search information 194, and issues an instruction on route search of the LANs 10-1 and 30-3 as targets of the routing control (Step S137). A route search command is a command to issue an instruction to search a routing route for routing for the LAN designated by the user. The client terminal 11 transmits a route search command, in which the network addresses of the LANs 10-1 and 30-3 are set, to the relay server 13 to which the client terminal 11 are logged on (Step S138).

[0195]

In response to receiving the route search command, the relay server 13 newly creates response information to the route search command. In a similar way to the transfer of the network search command, the relay server 13 transmits the route search command to the relay servers 22 and 33 based on the relay group information 141. First, the route search command is transmitted from the relay server 13 to the client terminal 21 through the

SIP server 101 and the relay server 22 (Steps S139, S139.1, and S139.1.1). The client terminal 21 and the relay server 22 cannot handle the routing of the LANs 10-1 and 30-3. Therefore, the client terminal 21 notifies the relay server 22 that the routing is impossible (NO ROUTE), and the relay server 22 notifies the relay server 13 that the routing is impossible.

[0196]

Next, the route search command is transmitted from the relay server 13 to the client terminals 31 and 32 through the SIP server 101 and the relay server 33 (Steps S140, S140.1, S240.1.1 and S140.1.2).

[0197]

The client terminal 31 cannot handle the routing of the LANs 10-1 and 30-3, and accordingly, issues a notice that the routing is impossible. The client terminal 32 is connected to the LAN 30-3, and has the routing function. Therefore, the client terminal 32 transmits the identification information of itself and the network address of the LAN 30-3 to the relay server 33, and issues a notice thereto that the routing is possible. Moreover, the relay server 33 does not have the routing function. As a result, the relay server 33 creates specifying information that specifies the client terminal 32, which is capable of operating as a routing point of the LAN 30-3, and transmits the specifying information to the relay server 13. In the specifying information, the identification information of the client terminal 32 and the network address of the LAN 30-3 are associated with each other. The relay server 13 adds the specifying information to response information 195 to the route search command.

[0198]

Next, the relay server 13 transmits the route search command to the client terminal 12 (Step S141). The client terminal 12 does not have the routing function, and accordingly, notifies the relay server 13 that the routing is impossible.

[0199]

The relay server 13 has the routing function, and is capable of routing for the LAN 10-1. Therefore, the relay server 13 adds, to the response information to the route search command, specifying information in which the identification information of the relay server 13 and the network address of the LAN 10-1 are associated with each other. Then, the response information to the route search command is transmitted from the relay server 13 to the client terminal 11. The client terminal 11 displays, as a result of the route search, the route search information 195 created based on the response information to the route search command (Step S142).

[0200]

FIG. 40 is a view showing the route search information 195. In body information 1951, "IP routing group 1" assigned by the user at the time of issuing the instruction of the route search is set in "name", and the identification information of the client terminal 11 is set in "owner".

[0201]

Routing target information 1952 is route information for use in the routing control for the LANs 10-1 and 30-3. Network information 1952-1 and 1952-2 correspond to the above-mentioned specifying information. Since the network address of the LAN 10-1 has been set, and the

identification information of the relay server 13 has been set, the network information 1952-1 indicates that the relay server 13 is executing the routing control for the LAN 10-1. In a similar way, the network information 1952-2 indicates that the client terminal 32 is executing the routing control for the LAN 30-3.

[0202]

Note that the pieces of network search list information included in the network search information 191 to 194 have a similar configuration to that of the routing target information 1952. As mentioned above, the routing target information 1952 indicates that the routing control for the LANs 10-1 and 30-3 is performed by the relay server 13 and the client terminal 32. On the other hand, however, the network search list information is the list of the LANs capable of the routing. Hence, there is no relationship between the routing target information 1952 and the network search list information 1912.

[0203]

As described above, the user of the client terminal 11 designates the network address serving as the target of the routing control, and issues the instruction on the route search, thereby can acquire the route search information 195. Therefore, when validating the routing function of the relay communication system, it is not necessary to confirm the relay servers, the client terminals and the like which have the routing function.

[0204]

FIG. 41 is a flowchart showing operations of the client terminal 11 instructed to perform the route search. When having been instructed to

perform the route search (Yes in Step S1201), the client terminal 11 asks the user to confirm whether or not the network address serving as the target of the route search is to be designated (Step S1202). In the case where the network address is designated (Yes in Step S1202), the user of the client terminal 11 inputs the network address (Step S1203). Then, when the start of the route search is instructed (Yes in Step S1204), the client terminal 11 creates a route search command in which the inputted network address is set (Step S1205). In the case where a network address is further designated (Yes in Step S1206), the client terminal 11 adds the designated network address to an argument of the route search command (Step S1207). In the case where no network address is further added (No in Step S1206), the client terminal 11 transmits the route search command to the relay server 13 (Step S1208).

[0205]

When having received the response to the route search command (Yes in Step S1209), the client terminal 11 confirms the response. In the case where the specifying information corresponding to the designated LAN is not included in the response, the client terminal 11 determines that there is no routing route (No in Step S1210). Then, the client terminal 11 issues a notice of an error, indicating that a routing route of the designated LAN could not be found (Step S1211). Meanwhile, in the case where the client terminal 11 determines that there is a routing route (Yes in Step S1210), the client terminal 11 creates the route search information 195 based on the received response, and displays candidates of the routing route on the monitor (Step S1212).

[0206]

The user of the client terminal 11 selects the routing route from the results of the route search, which are displayed on the monitor. In the case where an instruction is issued on the start of the routing control through the route selected by the user (Yes in Step S1213), the client terminal 11 transmits the routing start command to the relay server 13 (Step S1214). A description will be made later of the start processing for the routing control.

[0207]

FIG. 42 is a flowchart showing operations of the relay server 13 that has received the route search command. When having received the route search command (Yes in Step S1301), the relay server 13 refers to the relay group information 141 (Step S1302). In the case where the route search command has not been transmitted to all of the relay servers registered in the relay group information 141 (No in Step S1303), the route search command is transferred to a relay server specified in the relay group information 141 (Step S1304). This processing corresponds to processing in Steps S139, S139.1 and the like (refer to FIG. 39).

[0208]

When having received the response to the route search command (Yes in Step S1305), the relay server 13 confirms the response (Step S1306). In the case where the specifying information is not included in the response (No in Step S1306), the operation of the relay server 13 returns to Step S1303. In the case where the specifying information is included in the response (Yes in Step S1306), the relay server 13 adds the specifying

information to the response information to the route search command (Step S1307), and the operation returns to Step S1303. Moreover, in the case where the relay server 13 is able to route for the LAN designated in the route search command, the relay server 13 adds specifying information which corresponds to the relay server 13 to the response information to the route search command.

[0209]

In the case where the route search command has been transmitted to all of the relay servers (Yes in Step S1303), the relay server 13 refers to the client terminal information 63 (refer to FIG. 12) (Step S1308).

[0210]

In the case where the route search command has not been transmitted to all of the client terminals (excluding the transmission source of the route search command) registered in the client terminal information 63 (No in Step S1309), the transfer destination of the route search command is specified based on the client terminal information 63. Then, the relay server 13 transmits the route search command to the specified transfer destination (Step S1310). This processing corresponds to Step S141 (refer to FIG. 39).

[0211]

Processing of Steps S1311, S1312 and S1313 is similar to the processing of Steps S1305 to S1307. Then, in the case where the route search command has been transmitted to all of the client terminals (Yes in Step S1309), the relay server 13 transmits the response information to the

route search command to the client terminal 11 (Step S1314).

[0212]

#### <5.4. Flow of routing start processing>

FIG. 43 is a chart showing a flow of the start processing for the routing control using the relay communication system.

[0213]

The user of the client terminal 11 designates the relay server 13 and the client terminal 32 as routing points based on the route search result displayed on the monitor, and issues the instruction to start the routing control (Step S143). To the relay server 13, the client terminal 11 transmits the routing start command in addition to the network information 1952-1 and 1952-2 (Step S144). Steps S143 and S144 correspond to Steps S1213 and S1214 shown in FIG. 41.

[0214]

Based on the received routing start command, the relay server 13 creates routing group information 196 from the route search information 195. The routing group information 196 is routing setting information for executing the routing control using the relay communication system, and is stored in the routing group information storage unit 137.

[0215]

FIG. 44 is a view showing the routing group information 196. The routing group information 196 is created through adding routing permission information 1963 and session information 1964 to the route search information 195.

[0216]

The routing permission information 1963 indicates the communication terminals capable of using the routing function of the relay communication system, and is composed of permitted terminal information 1963-1 and 1963-2. Here, in addition to the terms “client terminal” and “general terminal”, the term “communication terminal” is used on purpose. The “client terminals” are terminals capable of logging on to the relay servers, the “general terminals” are terminals incapable of logging on to the relay servers, and meanwhile, the “communication terminals” represent all of the terminals including the “relay servers”, the “client terminals” and the “general terminals”. This is because, by using the routing function of the relay communication system, routing is possible for the “communication terminals” which are connected to the LANs 1 to 3 and are registered in the permitted terminal information without being limited to the relay servers and the client terminals which are logged on to the relay servers.

[0217]

In each of the permitted terminal information, “name” and “addr” indicate the name and IP address of the communication terminal or the LAN, which is capable of using the routing function. In the permitted terminal information 1963-1, “192.168.1.\*” is set, indicating all of the communication terminals connected to the LAN 10-1. In the permitted terminal information 1963-2, “200.1.3.\*” is set, indicating all of the communication terminals connected to the LAN 30-3.

[0218]

Note that, at the time of the start instruction of the routing (Step S143), the user of the client terminal 11 may designate the client terminals,

the relay servers, the general terminals and the like, which are registered in the permitted terminal information. In this case, the route search information 195 added with the routing permission information 1963 is transmitted to the relay server 13 (Step S144).

[0219]

The session information 1964 has point information 1964-1 regarding the routing session. The routing session is a media session which the relay server 13 and the client terminal 32 use for the routing control of the communication packet. "start" of the point information 1964-1 indicates a start point of the routing session, in which the identification information of the relay server 13 is set. "end" indicates an end point of the routing session, in which the identification information of the client terminal 32 is set.

[0220]

FIG. 44 is referred to one more time. The relay server 13 transmits the routing group information 196 to the client terminal 32 through the SIP server 101 and the relay server 33 (Steps S145, S145.1, S145.1.1). In such a way, the relay server 13 and the client terminal 32, which function as the routing devices, share the routing group information 196.

[0221]

Next, the routing session is established between the relay server 13 and the client terminal 32. The relay server 13 refers to the point information 1964-1, and confirms that the device itself is set at the start point of the routing session.

[0222]

The relay server 13 transmits an establishment request of the routing session to the relay server 33 through the SIP server 101 (Steps S146 and S146.1). In response to a response from the relay server 33, the relay server 13 transmits an ACK to the relay server 33 through the SIP server 101 (Steps S147 and S147.1). In response to the ACK, the relay server 33 establishes a media session between the relay servers 13 and 33 (Step S148). Moreover, a media session is established between the relay server 33 and the client terminal 32 (Steps S149, S150 and S151). This processing is similar to Steps S146 to S148 except that the media session is established without passing through the SIP server 101. The routing session is composed of the two media sessions established in Steps S148 and S151.

[0223]

#### <5.5. Routing control of communication packet>

FIG. 45 is a chart showing a flow of the routing control using the routing session established between the relay server 13 and the client terminal 32.

[0224]

The general terminal 15 sends out a communication packet destined for the general terminal 37 (Step S152). Based on the routing group information 196, the relay server 13 determines whether or not it is possible to route the received communication packet.

[0225]

First, based on the routing target information 1952, the relay server 13 determines whether or not the communication packet can be routed. An

IP address “200.1.3.250” of the destination (general terminal 37) of the communication packet corresponds to the network address of the LAN 30-3 set in the network information 1952-2. An IP address “192.168.1.150” of the transmission source (general terminal 15) corresponds to the network address of the LAN 10-1 set in the network information 1952-1. Therefore, the relay server 13 determines that the received communication packet can be routed.

[0226]

Next, the relay server 13 refers to the routing permission information 1963, and confirms whether or not the routing of the communication packet is permitted. The IP address of the destination (general terminal 37) of the communication packet corresponds to “200.1.3.\*” set in the permitted terminal information 1963-2. Moreover, the IP address of the transmission source (general terminal 15) of the communication packet corresponds to “192.168.1.\*” set in the permitted terminal information 1963-1. Therefore, the relay server 13 determines that the routing of the communication packet is permitted.

[0227]

The relay server 13 sends out the communication packet, for which the routing is permitted, by using the routing session (Steps S153 and S153.1). The client terminal 32 transfers, to the general terminal 37, the communication packet received through the routing session (Step S154). The communication packet is encapsulated at the time of being transferred using the routing session, and accordingly, the general terminal 15 and 37 can communicate with each other without being conscious of the presence of

the WAN 100. That is to say, the general terminals 15 and 37 can communicate with each other through the WAN 100 by using the private IP addresses.

[0228]

As described above, the routing function according to this embodiment is validated by sharing the routing group information 196 between the relay server 13 and the client terminal 32, which can communicate with each other. Then, by using the routing session established for the routing, the routing control for the IP packet is performed based on the function of the relay communication system. Accordingly, the routing validated in this embodiment is executed in the application layer, and differs from the usual IP routing.

[0229]

Next, a description will be made of a flow of the end of the routing. In response to an instruction to end the routing, which is based on the routing group information 196, the client terminal 32 deletes the routing group information 196. Such an end instruction is transmitted to the relay server 13 through the relay server 33 and the SIP server 101 (Steps S155, S155.1 and S155.1.1). Based on the end instruction, the relay server 13 deletes the routing group information 196.

[0230]

When having received a response to the end instruction, the client terminal 32 transmits a disconnection request of the routing session to the relay server 33 (Step S156). Based on the disconnection request, the media session between the client terminal 32 and the relay server 33 in the routing

session is disconnected. In a similar way, in the routing session, the media session between the relay servers 13 and 33 is disconnected (Steps S157 and S157.1). In such a way, the routing processing that is based on the routing group information 196 is ended.

[0231]

Following the end of the routing processing, the communication between the general terminals 15 and 37 becomes impossible. Even if the general terminal 15 sends out a communication packet destined for the general terminal 37 (Step S158), the relay server 13 cannot recognize the destination of the received communication packet since the relay server 13 does not hold the routing group information 196. Therefore, the relay server 13 notifies the general terminal 15 that the communication packet cannot reach the destination.

[0232]

As described above, the relay communication system of this embodiment automatically creates the routing setting information in which the network address of the designated LAN and the relay server or the client terminal, which functions as the routing device, are associated with each other. Therefore, the creation of the routing setting information used as the route information in the routing using the relay communication system can be simplified. Moreover, even if the configuration of the relay communication system is changed, it is easy to create routing setting information corresponding to the configuration of the relay communication system.

## Explanation of Reference Numerals

[0233]

1, 2, 3 LAN

11, 21, 21, 31, 32 CLIENT TERMINAL

15, 16, 23, 36, 37 GENERAL TERMINAL

13, 22, 33 RELAY SERVER

100 WAN

101 SIP SERVER

131 INTERFACE UNIT

132 CONTROL UNIT

115, 133 DATABASE STORAGE UNIT

117, 134 RELAY GROUP INFORMATION STORAGE UNIT

118, 135 RELAY SERVER INFORMATION STORAGE UNIT

119, 137 ROUTING GROUP INFORMATION STORAGE UNIT

136 CLIENT TERMINAL INFORMATION STORAGE UNIT

## CLAIMS

1. A relay communication system in which a first relay server connected to a first LAN and a second relay server connected to a second LAN are connected to each other,
  - each of the first relay server and the second relay server includes:
    - a relay server information sharing unit configured to share relay server information between the first relay server and the second relay server, the relay server information including activation information of the first relay server and the second relay server, and activation/registration information of client terminals connected to the first relay server and the second relay server;
    - a routing group information sharing unit configured to share routing group information with a first routing device that executes routing control for the first LAN and a second routing device that executes routing control for the second LAN, the routing group information including a network address of the first LAN, a network address of the second LAN, first specifying information that specifies either a relay server or a client terminal, which is the first routing device, and second specifying information that specifies either a relay server or a client terminal, which is the second routing device; and
    - a routing control unit configured to, upon receiving a start request of routing control, specify the first routing device and the second routing device from the first specifying information and the second specifying information, which are included in the routing group information, establish

a routing session between the first routing device and the second routing device based on the relay server information, execute routing control for a communication packet between the first LAN and the second LAN through the routing session, and, based on an instruction to end the routing control, disconnect the routing session, and end the routing control for the communication packet between the first LAN and the second LAN, wherein

when a first communication packet destined for a destination address of an IP address belonging to the second LAN is sent out from a communication terminal connected to the first LAN, the first routing device refers to the routing group information to decide that routing of the first communication packet to the second LAN is possible, and transfers the first communication packet by using the established routing session.

2. The relay communication system according to claim 1,

wherein a plurality of relay servers including the first relay server and the second relay server are connected to one another through a wide area network, and

the routing group information includes network addresses of LANs to which the relay servers connect, and information that specifies routing devices executing routing control for LANs to which the relay servers connect.

3. The relay communication system according to claim 1 or 2,

wherein the first routing device is a client terminal connected to the first relay server, and is capable of performing communication with the

second relay server through the first relay server.

4. The relay communication system according to any one of claims 1 to 3,

wherein the second routing device is the second relay server.

5. The relay communication system according to claim 1 or 2,  
wherein the first relay server and the second relay server are a same device,

the first routing device is a first client terminal connected to the first relay server, and

the second routing device is a second client terminal connected to the first relay server.

6. The relay communication system according to any one of claims 1 to 5,

wherein the routing group information includes permitted terminal information, in which an address of the communication terminal connected to the first LAN is registered, and

in a case where a transmission source address of the first communication packet is registered in the permitted terminal information, the first routing device permits routing of the first communication packet.

7. The relay communication system according to any one of claims 1 to 5,

wherein the routing group information includes permitted terminal information, in which an address of the communication terminal connected to the second LAN is registered, and

in a case where a destination address of the first communication packet is registered in the permitted terminal information, the first routing device permits routing of the first communication packet.

8. A relay communication system in which a first relay server connected to a first LAN and a second relay server connected to a second LAN are connected to each other,

the first relay server includes:

a relay server information sharing unit configured to share relay server information with the second relay server, the relay server information including activation information of the first relay server and the second relay server, and activation/registration information of client terminals connected to the first relay server and the second relay server;

an acquisition unit configured to acquire first specifying information specifying either a relay server or a client terminal, which is a first routing device executing routing control for the first LAN based on a network address of the first LAN;

a request unit configured to request the second relay server for second specifying information specifying either a relay server or a client terminal, which is a second routing device executing routing control for the second LAN based on a network address of the second LAN; and

a routing setting information creation unit configured to create

routing setting information based on the first specifying information and the second specifying information, the routing setting information including information in which the network address of the first LAN and the first routing device are associated with each other, and information in which the network address of the second LAN and the second routing device are associated with each other,

the second relay server includes:

a response unit configured to, in response to a request from the request unit, acquire the second specifying information, and transmit the second specifying information to the first relay server,

each of the first relay server and the second relay server includes:

a sharing unit configured to share the routing setting information;

and

a routing control unit configured to, upon receiving a start request of routing control, specify the first routing device and the second routing device based on the routing setting information, establish a routing session between the first routing device and the second routing device based on the relay server information, execute routing control for a communication packet between the first LAN and the second LAN through the routing session, and, upon receiving an instruction to end the routing control, disconnect the routing session, and end the routing control for the communication packet between the first LAN and the second LAN, wherein

when a communication packet destined for a destination address of an IP address belonging to the second LAN is sent out from a communication terminal connected to the first LAN, the first routing device

refers to the routing setting information to decide that routing of the communication packet to the second LAN is possible, and transfers the communication packet by using the established routing session.

9. The relay communication system according to claim 8,  
wherein the first relay server further includes:  
a list creation unit configured to search for LANs capable of routing control, and create a list of the LANs; and  
a selection unit configured to select the network address of the first LAN and the network address of the second LAN by using the list.

10. The relay communication system according to claim 8 or 9,  
wherein the first routing device is a client terminal connected to the first relay server, and is capable of performing communication with the second relay server through the first relay server, and  
the client terminal shares the routing setting information with the first relay server and the second relay server.

11. The relay communication system according to any one of claims 8 to 10,  
wherein the second routing device is the second relay server.

12. A first relay server for use in a relay communication system in which the first relay server connected to a first LAN and a second relay server connected to a second LAN are connected to each other, the first relay server

comprising:

a relay server information sharing unit configured to share relay server information with the second relay server, the relay server information including activation information of the first relay server and the second relay server, and activation/registration information of client terminals connected to the first relay server and the second relay server;

a routing group information sharing unit configured to share routing group information with a first routing device that executes routing control for the first LAN and a second routing device that executes routing control for the second LAN, the routing group information including a network address of the first LAN, a network address of the second LAN, first specifying information that specifies either a relay server or a client terminal, which is the first routing device, and second specifying information that specifies either a relay server or a client terminal, which is the second routing device; and

a routing control unit configured to, upon receiving a start request of the routing control, specify the first routing device and the second routing device from the first specifying information and the second specifying information, which are included in the routing group information, establish a routing session between the first routing device and the second routing device based on the relay server information, execute routing control for a communication packet between the first LAN and the second LAN through the routing session, and, upon receiving an instruction to end the routing control, disconnect the routing session, and end the routing control for the communication packet between the first LAN and the second LAN, wherein

when a first communication packet destined for a destination address of an IP address belonging to the second LAN is sent out from a communication terminal connected to the first LAN, the first routing device refers to the routing group information to decide that routing of the first communication packet to the second LAN is possible, and transfers the first communication packet by using the established routing session.

13. A first relay server for use in a relay communication system in which the first relay server connected to a first LAN and a second relay server connected to a second LAN are connected to each other, the first relay server comprising:

- a relay server information sharing unit configured to share relay server information with the second relay server, the relay server information including activation information of the first relay server and the second relay server, and activation/registration information of client terminals connected to the first relay server and the second relay server;

- an acquisition unit configured to acquire first specifying information specifying either a relay server or a client terminal, which is a first routing device executing routing control for the first LAN based on a network address of the first LAN;

- a request unit configured to request the second relay server for second specifying information specifying either a relay server or a client terminal, which is a second routing device executing routing control for the second LAN based on a network address of the second LAN;

- a routing setting information creation unit configured to create

routing setting information based on the first specifying information and the second specifying information, the routing setting information including information in which the network address of the first LAN and the first routing device are associated with each other, and information in which the network address of the second LAN and the second routing device are associated with each other;

a sharing unit configured to share the routing setting information with the second relay server; and

a routing control unit configured to, upon receiving a start request of routing control, specify the first routing device and the second routing device based on the routing setting information, establish a routing session between the first routing device and the second routing device based on the relay server information, execute routing control for a communication packet between the first LAN and the second LAN through the routing session, and, upon receiving an instruction to end the routing control, disconnect the routing session, and end the routing control for the communication packet between the first LAN and the second LAN, wherein

when a communication packet destined for a destination address of an IP address belonging to the second LAN is sent out from a communication terminal connected to the first LAN, the first routing device refers to the routing setting information to decide that routing of the communication packet to the second LAN is possible, and transfers the communication packet by using the established routing session.