

DESCRIPTION

[Title of Invention] CEILING CONVEYANCE VEHICLE AND CEILING
CONVEYANCE VEHICLE SYSTEM

Technical Field

[0001]

The present invention relates to a ceiling conveyance vehicle and a ceiling conveyance vehicle system.

Background Art

[0002]

In semiconductor manufacturing factories or the like, a ceiling conveyance vehicle system conveying articles such as front opening unified pods (FOUPs) housing semiconductor wafers or reticle pods housing reticles is being used, for example. As a ceiling conveyance vehicle used in this ceiling conveyance vehicle system, a configuration having a traveling wheel rolling on a track including a first track extending in a first direction and a second track extending in a second direction different from the first direction and a main body placed below the track and coupled to the traveling vehicle is known (refer to Patent Literature 1, for example). In this ceiling conveyance vehicle, the main body includes a direction changer switching between a first state in which the traveling wheel rolls on the first track and a second state in which the traveling wheel rolls on the second track, with an orientation of the main body with respect to the track maintained, an article holder capable of holding an article, a hoisting-and-lowering driver hoisting and lowering the article holder, and a lateral slider slidably moving the hoisting-and-lowering driver in a linear direction on a horizontal plane.

Citation List

Patent Literature

[0003]

[Patent Literature 1] International Publication No.
2018/037762

Technical Problem

[0004]

In the ceiling conveyance vehicle described in Patent Literature 1, the configuration switches a traveling direction of the main body with the orientation of the main body with respect to the track maintained, and thus the orientation of the main body is maintained unchanged even when the traveling direction is switched between the first track and the second track. Consequently, when a direction of sliding movement by the lateral slider matches the traveling direction of the main body, there arises a problem in that the article holder cannot be moved in a direction other than the traveling direction (a direction orthogonal to the traveling direction, for example), and a transfer position of an article cannot be adjusted.

[0005]

An object of the present invention is to provide a ceiling conveyance vehicle and a ceiling conveyance vehicle system that can easily adjust a transfer position of an article by slidingly moving a lateral slider in a desired direction.

Solution to Problem

[0006]

A ceiling conveyance vehicle according to an aspect of the present invention is a ceiling conveyance vehicle having a traveling wheel rolling on a track including a first track extending in a first direction and a second track extending in a second direction different from the first direction and a main body placed below the track and coupled to the traveling wheel, the ceiling conveyance vehicle including a direction changer switching between a

first state in which the traveling wheel rolls on the first track and a second state in which the traveling wheel rolls on the second track, with an orientation of the main body with respect to the track maintained, an article holder capable of holding an article, a hoisting-and-lowering driver hoisting and lowering the article holder, a lateral slider slidably moving the hoisting-and-lowering driver in a horizontal, linear direction, and a first rotational driver rotationally driving the lateral slider around a first perpendicular axis with respect to the main body.

[0007]

A second rotationally driver rotationally driving the article holder or the hoisting-and-lowering driver around a second perpendicular axis with respect to the lateral slider may be included. The second rotationally driver may rotate the article holder or the hoisting-and-lowering driver in a range of at least 180 degrees around the second perpendicular axis on the basis of the linear direction. The track may be a grid-like track in which the first direction and the second direction are orthogonal to each other, the lateral slider may one-sidedly slidably move the hoisting-and-lowering driver in one direction in the linear direction, and the first rotational driver may rotate the lateral slider in a range of 270 degrees around the first perpendicular axis from a state in which a direction of one-sided sliding movement of the lateral slider is aligned with the first direction or the second direction.

[0008]

A controller driving the first rotational driver to rotate the lateral slider around the first perpendicular axis while going toward a transfer position to perform transfer of an article with respect to a transfer

destination may be included. The controller may set a rotational position of the lateral slider such that the linear direction in which the lateral slider slidingly moves and the transfer destination overlap with each other in a plan view when the main body has stopped at the transfer position.

[0009]

A ceiling conveyance vehicle system according to an aspect of the present invention is a ceiling conveyance vehicle system including a track including a first track extending in a first direction and a second track extending in a second direction different from the first direction and a ceiling conveyance vehicle traveling along the track, the ceiling conveyance vehicle being the ceiling conveyance vehicle.

[0010]

With the ceiling conveyance vehicle and the ceiling conveyance vehicle system, the lateral slider is rotatable around the first perpendicular axis with respect to the main body, and thus the lateral slider can be slidingly moved in a desired direction when the traveling direction of the main body is any one of the first track and the second track. Consequently, even when the direction of the sliding movement by the lateral slider and the traveling direction of the main body match, the article holder can be moved in a direction other than the traveling direction such as a direction orthogonal to the traveling direction, and the transfer position of the article can easily be adjusted.

[0011]

In the configuration in which the second rotationally driver rotationally driving the article holder or the hoisting-and-lowering driver around a second perpendicular

axis with respect to the lateral slider is included, the orientation of the article held by the hoisting-and-lowering driver can be changed, and even a case in which the orientation of the article is specified at a transfer destination can be coped with. In the configuration in which the second rotationally driver rotates the article holder or the hoisting-and-lowering driver in a range of at least 180 degrees around the second perpendicular axis on the basis of the linear direction, the article held by the article holder can be directed to an opposite direction around the second perpendicular axis. In the configuration in which the track is a grid-like track in which the first direction and the second direction are orthogonal to each other, the lateral slider one-sidedly slidably moves the hoisting-and-lowering driver in one direction in the linear direction, and the first rotational driver rotates the lateral slider in a range of 270 degrees around the first perpendicular axis from a state in which a direction of one-sided sliding movement of the lateral slider is aligned with the first direction or the second direction, when the lateral slider is one-sided sliding movement, the article holder can be slidably moved in any direction of the first direction and the second direction from the main body stationary on the grid-like track.

[0012]

In the configuration in which the controller driving the first rotational driver to rotate the lateral slider around the first perpendicular axis while going toward a transfer position to perform transfer of an article with respect to a transfer destination is included, the lateral slider is rotated while the main body is traveling, and thus the time required for the transfer of the article M can be reduced. In the configuration in which the

controller sets a rotational position of the lateral slider such that the linear direction in which the lateral slider slidably moves and the transfer destination overlap with each other in a plan view when the main body has stopped at the transfer position, a transfer operation for the article can quickly be performed after the main body has reached the transfer position.

Brief Description of the Drawings

[0013]

Fig. 1 is a side view illustrating an example of a ceiling conveyance vehicle according to a first embodiment.

Fig. 2 is a perspective view of the ceiling conveyance vehicle illustrated in Fig. 1.

Fig. 3 is a perspective view illustrating an example of a ceiling conveyance vehicle system according to the present embodiment.

Fig. 4 is a diagram schematically illustrating a state in which a main body is viewed from above.

Figs. 5(A) and 5(B) are plan views illustrating an example of a relation between a traveling direction of the main body and a sliding movement direction of a lateral slider.

Figs. 6(A) and 6(B) are plan views illustrating another example of the relation between the traveling direction of the main body and the sliding movement direction of the lateral slider.

Figs. 7(A) and 7(B) are plan views illustrating an example of a relation between the sliding movement direction of the lateral slider and an orientation of an article.

Figs. 8(A) and 8(B) are plan views illustrating another example of the relation between the sliding movement direction of the lateral slider and the

orientation of the article.

Figs. 9(A) and 9(B) are plan views illustrating another example of the relation between the sliding movement direction of the lateral slider and the orientation of the article.

Figs. 10(A) and 10(B) are plan views illustrating another example of the relation between the sliding movement direction of the lateral slider and the orientation of the article.

Fig. 11 is a plan view illustrating another example of the relation between the sliding movement direction of the lateral slider and the orientation of the article.

Fig. 12 is a side view illustrating an example of a ceiling traveling vehicle according to a second embodiment.

Figs. 13(A) and 13(B) are plan views illustrating an example in which the lateral slider is rotated when the main body is traveling.

Description of Embodiments

[0014]

The following describes embodiments of the present invention with reference to the accompanying drawings. However, the present invention is not limited to the aspects described below. To describe the embodiment, the drawings are represented with a scale changed as appropriate such as in a partially enlarged or emphasized manner. In the drawings below, directions in the drawings are described using an XYZ coordinate system. In this XYZ coordinate system, a plane parallel to a horizontal plane is defined as an XY plane. A linear direction along this XY plane is denoted by an X direction, whereas a direction orthogonal to the X direction is denoted by a Y direction. A traveling direction of a ceiling conveyance vehicle 100 can be changed from the state illustrated in the drawings

below to another direction, and the ceiling conveyance vehicle 100 may travel in a curvilinear direction, for example. A direction perpendicular to the XY plane is denoted by a Z direction. Each of the X direction, the Y direction, and the Z direction is described with the direction indicated by the arrow in the drawings as a + direction and with the opposite direction as a - direction. A rotational direction around a Z axis is denoted by a θZ direction.

[0015]

<First Embodiment>

Fig. 1 is a side view illustrating an example of a ceiling conveyance vehicle 100 according to a first embodiment. Fig. 2 is a perspective view of the ceiling conveyance vehicle 100 illustrated in Fig. 1. Fig. 3 is a perspective view illustrating an example of a ceiling conveyance vehicle system SYS according to the present embodiment. As illustrated in Fig. 1 to Fig. 3, the ceiling conveyance vehicle 100 moves along a track R of the ceiling conveyance vehicle system SYS to convey an article M such as a front opening unified pod (FOUP) housing semiconductor wafers or a reticle pod housing reticles. The ceiling conveyance vehicle 100 travels near the ceiling of a building and may thus be referred to as a ceiling traveling vehicle.

[0016]

The ceiling conveyance vehicle system SYS is a system to convey the article M by the ceiling conveyance vehicle 100 in a clean room of a semiconductor manufacturing factory, for example. In the ceiling conveyance vehicle system SYS, a plurality of ceiling conveyance vehicles 100 may be used, for example. The ceiling conveyance vehicles 100 convey the article M, thereby enabling high-density

conveyance, and the conveyance efficiency of the article M can be improved.

[0017]

The track R is one aspect of a track. The track R is laid on the ceiling of the building such as a clean room or near the ceiling. The track R is a grid-like track having a first track R1, a second track R2, and a connection track R3 (refer to Fig. 3). Hereinafter, the track R is referred to as a grid-like track R. The first track R1 is provided along the X direction (a first direction D1). The second track R2 is provided along the Y direction (a second direction D2). In the present embodiment, the first direction D1 and the second direction D2 are orthogonal to each other, and a plurality of first tracks R1 and a plurality of second tracks R2 are provided along directions orthogonal to each other but are provided so as not to directly cross each other. The connection track R3 is placed at a crossing part between the first track R1 and the second track R2. The first tracks R1 and the second tracks R2 are provided along the directions orthogonal to each other, whereby the grid-like track R is in a state in which a plurality of cells C (sections) are adjacent to each other in a plan view. Fig. 3 illustrates part of the grid-like track R, and in the grid-like track R, a similar configuration is continuously formed in the first direction D1 (the X direction) and the second direction D2 (the Y direction) from the illustrated configuration.

[0018]

The first track R1, the second track R2, and the connection track R3 are hung on the ceiling (not illustrated) with a hanging member H (refer to Fig. 3). The hanging member H has a first part H1 to hang the first track R1, a second part H2 to hang the second track R2, and

a third part H3 to hang the connection track R3. First parts H1 and second parts H2 are each provided at two places across the third part H3.

[0019]

The first track R1, the second track R2, and the connection track R3 have traveling faces R1a, R2a, and R3a, respectively, on which a traveling wheel 21 described below of the ceiling conveyance vehicles 100 travels. A gap D is formed between the first track R1 and the connection track R3 and between the second track R2 and the connection track R3. The gap D is a part over which a coupler 30 described below as part of the ceiling conveyance vehicles 100 passes when the ceiling conveyance vehicles 100 travels along the first track R1 to cross the second track R2 or when the ceiling conveyance vehicles 100 travels along the second track R2 to cross the first track R1. Consequently, the gap D is provided in a width enabling the coupler 30 to pass thereover. The first track R1, the second track R2, and the connection track R3 are provided along the same or substantially the same horizontal plane. In the present embodiment, the first track R1, the second track R2, and the connection track R3 place the traveling faces R1a, R2a, and R3a on the same or substantially the same horizontal plane.

[0020]

As illustrated in Fig. 1 and Fig. 2, the ceiling conveyance vehicle 100 has a main body 10, travelers 20, couplers 30, and a controller 50. The controller 50 collectively controls operations of the respective parts of the ceiling conveyance vehicle 100. Although the controller 50 is provided in the main body 10, it may be provided outside the main body 10. The main body 10 is placed below (on the -Z side of) the grid-like track R.

The main body 10 is formed in a rectangular shape, for example, in a plan view. The main body 10 is formed in dimensions housed in one cell C in the track R in a plan view. Thus, space in which one ceiling conveyance vehicle 100 passes another ceiling conveyance vehicle 100 traveling along an adjacent first track R1 or second track R2 is ensured.

[0021]

The main body 10 includes an upper unit 17 and a transfer apparatus 18. The upper unit 17 is hung on the travelers 20 via the couplers 30. The upper unit 17 is rectangular in a plan view, for example, and has four corner parts in an upper face 17a. The main body 10 has the traveling wheel 21, the coupler 30, and a direction changer 34 in each of the four corner parts.

[0022]

The transfer apparatus 18 is provided below the upper unit 17. The transfer apparatus 18 can rotate around a first perpendicular axis AX1 in a vertical direction. The transfer apparatus 18 has an article holder 13 holding the article M, a hoisting-and-lowering driver 14 hoisting and lowering the article holder 13 in the vertical direction, a lateral slider 11 slidably moving the hoisting-and-lowering driver 14, a rotator 12 holding the lateral slider 11, a first rotational driver 15 rotationally driving the lateral slider 11 around the first perpendicular axis AX1 with respect to the main body 10, and a second rotational driver 16 rotationally driving the hoisting-and-lowering driver 14 around a second perpendicular axis AX2 with respect to the lateral slider 11.

[0023]

The lateral slider 11 has a plurality of movable plates placed stacked in the Z direction, for example. The

movable plates are movable in the Y direction. The second rotational driver 16 is mounted on a lowermost movable plate. The lateral slider 11 moves the movable plates by a drive apparatus (not illustrated) and can thus one-sidedly slidably move the hoisting-and-lowering driver 14 mounted on the lowermost movable plate and the article holder 13 in one direction with respect to the traveling direction, that is, in one direction in a linear direction. The rotator 12 is mounted on the first rotational driver 15 between the lateral slider 11 and the upper unit 17 to hold the lateral slider 11.

[0024]

The article holder 13 grasps a flange part Ma of the article M to hang and hold the article M. The article holder 13 is a chuck having a horizontally movable hook part 13a, for example, causes the hook part 13a to enter below the flange part Ma of the article M, and hoists the article holder 13 to hold the article M. The article holder 13 is connected to a hanging member 13b such as a wire or a belt.

[0025] The hoisting-and-lowering driver 14 is mounted on the second rotational driver 16. The hoisting-and-lowering driver 14 is a hoist, for example, draws out the hanging member 13b to lower the article holder 13, and winds up the hanging member 13b to hoist the article holder 13. The hoisting-and-lowering driver 14 is controlled by the controller 50 to lower or hoist the article holder 13 at a certain speed. The hoisting-and-lowering driver 14 is controlled by the controller 50 to hold the article holder 13 at a target height.

[0026]

The first rotational driver 15, for which an electric motor or the like is used, rotates the rotator 12 around

the first perpendicular axis AX1. The first rotational driver 15 can rotate the lateral slider 11 around the first perpendicular axis AX1 together with the rotation of the rotator 12. When the first rotational driver 15 rotates the lateral slider 11 around the first perpendicular axis AX1, the second rotational driver 16, the hoisting-and-lowering driver 14, and the article holder 13 mounted on a lower side of the lateral slider 11 integrally rotate around the first perpendicular axis AX1. The second rotational driver 16, for which an electric motor or the like is used, rotates the hoisting-and-lowering driver 14 around the second perpendicular axis AX2.

[0027]

Fig. 4 is a diagram schematically illustrating a state in which the main body 10 is viewed from above. Fig. 4 illustrates an example of rotational movement of the lateral slider 11 and the hoisting-and-lowering driver 14. As illustrated in Fig. 4, the first rotational driver 15 can rotate the lateral slider 11 in a range of 270 degrees around the first perpendicular axis AX1 from a state in which a direction of one-sided sliding movement of the lateral slider 11 is aligned with the first direction D1 or the second direction D2. Thus, the direction of the one-sided sliding movement of the lateral slider 11 rotates by an angle by which the lateral slider 11 has rotated. In this case, the article holder 13 can be one-sidedly slidably moved in any direction of the first direction D1 and the second direction D2 from the main body 10 stationary on the grid-like track R. The rotation range is limited to 270 degrees, not 360 degrees, whereby a mechanical stopper for the first rotational driver 15 can easily be installed. Damage that wiring (not illustrated) connected to the first rotational driver 15 receives during

rotation can be reduced.

[0028]

The lateral slider 11 may be able to slidably move the hoisting-and-lowering driver 14 and the article holder 13 in both directions in the linear direction. In this configuration, the first rotational driver 15 may rotate the lateral slider 11 in a range of 90 degrees around the first perpendicular axis AX1 from the state in which the direction of the sliding movement of the lateral slider 11 is aligned with the first direction D1 or the second direction D2. In this case, the article holder 13 can be slidably moved in any direction of the first direction D1 and the second direction D2 from the main body 10 stationary on the grid-like track R.

[0029]

The transfer apparatus 18 drives the lateral slider 11 to enable the hoisting-and-lowering driver 14 and the article holder 13 to protrude from a transfer position P1 below the upper unit 17 to any of protruding positions P2a, P2b, P2c, and P2d. The protruding position P2a is a protruding position when the hoisting-and-lowering driver 14 and the article holder 13 are slidably moved in the +Y direction by the lateral slider 11. The protruding position P2b is a protruding position when the lateral slider 11 is rotated by 90 degrees (clockwise 90 degrees, for example) around the first perpendicular axis AX1 by the first rotational driver 15, and the hoisting-and-lowering driver 14 and the article holder 13 are slidably moved in the +X direction by the lateral slider 11. The protruding position P2c is a protruding position when the lateral slider 11 is rotated by 180 degrees around the first perpendicular axis AX1 by the first rotational driver 15, and the hoisting-and-lowering driver 14 and the article

holder 13 are slidingly moved in the -Y direction by the lateral slider 11. The protruding position P2d is a protruding position when the lateral slider 11 is rotated by 270 degrees around the first perpendicular axis AX1 by the first rotational driver 15, and the hoisting-and-lowering driver 14 and the article holder 13 are slidingly moved in the -X direction by the lateral slider 11.

[0030]

Thus, although the lateral slider 11 one-sidedly slidingly moves the hoisting-and-lowering driver 14 and the article holder 13 in one direction in the linear direction, the first rotational driver 15 is driven to set a rotational position of the lateral slider 11 at 90-degree intervals to enable the hoisting-and-lowering driver 14 and the article holder 13 to be slidingly moved in each of four directions, namely the +X direction (the first direction D1), the +Y direction (the second direction D2), the -X direction (the first direction D1), and the -Y direction (the second direction D2).

[0031]

The second rotational driver 16, for which an electric motor or the like is used, rotates the hoisting-and-lowering driver 14 (the article holder 13) at least in a range of 180 degrees around the second perpendicular axis AX2 on the basis of the linear direction in which the one-sided sliding movement is performed by the lateral slider 11. Although Fig. 4 illustrates an aspect in which the hoisting-and-lowering driver 14 (the article holder 13) can be rotated by 180 degrees around the second perpendicular axis AX2 in a range of a direction indicated by the dotted dashed line passing through the second perpendicular axis AX2 (a direction orthogonal to the linear direction), this aspect is not limiting. The direction indicated by the

dotted dashed line in Fig. 4 may match the linear direction in which the one-sided sliding movement is performed by the lateral slider 11, for example. According to the aspect illustrated in Fig. 4, the second rotational driver 16 is driven, whereby a state in which the front side of the article M is directed to the +X direction is rotated by 180 degrees around the second perpendicular axis AX2, whereby the front side of the article M can be directed to the -X direction (that is, the opposite direction), for example. The hoisting-and-lowering driver 14 (the article holder 13) is rotated by 90 degrees by the second rotational driver 16, whereby the state in which the front side of the article M is directed to the +X direction can be made to a state in which the front side of the article M is directed to the +Y direction or the -Y direction.

[0032]

As illustrated in Fig. 1 and Fig. 2, a traveler 20 has the traveling wheel 21 and auxiliary wheels 22. Traveling wheels 21 are placed at the four respective corner parts of the upper face 17a of the upper unit 17 (the main body 10). Each of the traveling wheels 21 is mounted on a wheel shaft (not illustrated) provided in the coupler 30. The wheel shaft is provided parallel or substantially parallel to the XY plane. Each of the traveling wheels 21 is rotationally driven by the driving force of a traveling driver 33 described below. Each of the traveling wheels 21 rolls on the traveling faces R1a, R2a, and R3a of the first track R1, the second track R2, and the connection track R3, respectively, in the grid-like track R to cause the ceiling conveyance vehicle 100 to travel. Without being limited to rotationally driving all the four traveling wheels 21 by the driving force of the traveling driver 33, part of the four traveling wheels 21 may be rotationally driven.

[0033]

The traveling wheel 21 is provided turnably in the θZ direction around a turning axis AX3. The traveling wheel 21 turns in the θZ direction by the direction changer 34 described below and can consequently change the traveling direction of the ceiling conveyance vehicle 100. One auxiliary wheel 22 is placed on each of the front and rear in the traveling direction of the traveling wheel 21. Each of the auxiliary wheels 22, like the traveling wheel 21, is rotatable in the θZ direction. A lower end of the auxiliary wheels 22 is set to be higher than a lower end of the traveling wheel 21. Consequently, when the traveling wheel 21 is traveling on the traveling faces R1a, R2a, and R3a, the auxiliary wheels 22 are not in contact with the traveling faces R1a, R2a, and R3a. When the traveling wheel 21 passes over the gap D (refer to Fig. 3), the auxiliary wheels 22 come into contact with the traveling faces R1a, R2a, and R3a to prevent the traveling wheel 21 from falling. Without being limited to providing two auxiliary wheels 22 for one traveling wheel 21, one auxiliary wheel 22 may be provided for one traveling wheel 21, or no auxiliary wheels 22 may be provided, for example.

[0034]

As illustrated in Fig. 1 and Fig. 2, the ceiling conveyance vehicle 100 may be provided with a cover W so as to surround the transfer apparatus 18 and the article M held by the transfer apparatus 18. The cover W has a tubular shape with a lower end open with a part through which the movable plates of the lateral slider 11 protrude (a part through which they slidably move) notched. The cover W, the upper end of which is mounted on the rotator 12, rotates around the first perpendicular axis AX1 along with the rotation of the rotator 12.

[0035]

The couplers 30 couple the upper unit 17 of the main body 10 and the travelers 20 to each other. The couplers 30 are provided at the four respective corner parts of the upper face 17a of the upper unit 17 (the main body 10). The main body 10 is made to a hung state by these couplers 30 to be placed below the grid-like track R. The coupler 30 has a support member 31 and a connection member 32. The support member 31 rotatably supports a rotation axis of the traveling wheel 21 and rotation axes of the auxiliary wheels 22. The support member 31 holds a relative position among the traveling wheel 21 and the auxiliary wheels 22. The support member 31 is formed in a plate shape, for example, and is formed to have a thickness capable of passing over the gap D.

[0036]

The connection member 32 extends downward from the support member 31 to be coupled to the upper face 17a of the upper unit 17 and to hold the upper unit 17. The connection member 32 includes a transmitter transmitting the driving force of the traveling driver 33 described below to the traveling wheel 21 therewithin. For this transmitter, a chain or a belt may be used, or a gear train may be used. The connection member 32 is provided rotatably in the θZ direction around the turning axis AX3. This connection member 32 rotates around the turning axis AX3, thereby enabling the traveling wheel 21 to turn in the θZ direction.

[0037]

The coupler 30 is provided with the traveling driver 33 and the direction changer 34. The traveling driver 33 is mounted on the connection member 32. The traveling driver 33 is a driving source driving the traveling wheel

21, and an electric motor or the like is used therefor, for example. The four traveling wheels 21 are each driven by the traveling driver 33 to serve as the drive wheels. The four traveling wheels 21 are controlled by the controller 50 so as to have the same or substantially the same number of rotations. When any of the four traveling wheels 21 is not used as the drive wheel, the traveling driver 33 is not mounted on its connection member 32.

[0038]

The direction changer 34 turns the connection member 32 of the coupler 30 around the turning axis AX3 with respect to the main body 10 to turn the traveling wheel 21 in the θZ direction. The traveling wheel 21 is turned in the θZ direction, whereby a first state in which the traveling direction of the ceiling conveyance vehicle 100 is the first direction D1 can be switched to a second state in which the traveling direction is the second direction D2, or the second state, in which the traveling direction is the second direction D2, can be switched to the first state, in which the traveling direction is the first direction D1.

[0039]

The direction changer 34 has a driving source 35, a pinion gear 36, and a rack 37. The driving source 35 is mounted on a side face of the traveling driver 33 separate from the turning axis AX3. For the driving source 35, an electric motor or the like is used, for example. The pinion gear 36 is mounted on a lower face side of the driving source 35 and is rotationally driven in the θZ direction through driving force generated by the driving source 35. The pinion gear 36 is circular in a plan view and has a plurality of teeth in a circumferential direction on its perimeter. The rack 37 is fixed to the upper face 17a of the upper unit 17. Racks 37 are provided at the

four respective corner parts of the upper face 17a of the upper unit 17 and are each provided in an arc shape (a fan shape) around the turning axis AX3 of the traveling wheel 21. The rack 37 has a plurality of teeth meshing with the teeth of the pinion gear 36 in a circumferential direction on its perimeter.

[0040]

The pinion gear 36 and the rack 37 are placed with the mutual teeth meshing with each other. The pinion gear 36 rotates in the θZ direction, whereby the pinion gear 36 moves in a circumferential direction around the turning axis AX3 so as to follow the perimeter of the rack 37. With this movement of the pinion gear 36, the connection member 32 turns, and the traveling driver 33 and the direction changer 34 turn in the circumferential direction around the turning axis AX3 together with the pinion gear 36.

[0041]

By the turning of the direction changer 34, the traveling wheels 21 and the auxiliary wheels 22 placed at the four respective corner parts of the upper face 17a turn in a range of 90 degrees in the θZ direction around the turning axis AX3. The drive of the direction changer 34 is controlled by the controller 50. The controller 50 may instruct to perform turning operations of the four traveling wheels 21 at the same time or instruct to perform them at different times. The traveling wheels 21 and the auxiliary wheels 22 are turned, whereby a state in which the traveling wheels 21 are in contact with one of the first track R1 and the second track R2 shifts to a state in which the traveling wheels 21 are in contact with the other. Thus, the first state, in which the traveling direction of the ceiling conveyance vehicle 100 is the first direction

D1 (the X direction), and the second state, in which the traveling direction is the second direction D2 (the Y direction), can be switched to each other.

[0042]

Fig. 5 and Fig. 6 are plan views illustrating examples of a relation between the traveling direction of the main body 10 and a sliding movement direction of the lateral slider 11. In Fig. 5 and Fig. 6, the first track R1, the second track R2, and the connection track R3 are illustrated in a simplified manner. Fig. 5 illustrates an example of a case in which the main body 10 moves in the first direction D1. Fig. 6 illustrates an example of a case in which the main body 10 moves in the second direction D2. In Fig. 5 and Fig. 6, the article M is placed deviated from a central part of an area surrounded by the first track R1 and the second track R2 in a plan view (refer to the cell C in Fig. 3). The article M being deviated from the central part of the cell C in a plan view includes a case in which although the article M is at substantially the center of the cell C, it is placed only a little deviated to one rail. That is, a case in which the article M can be received and delivered by hoisting and lowering the article holder 13 with the ceiling conveyance vehicle 100 stopped at a position at which the central part of the main body 10 matches the central part of the cell C is a state in which the article M is at the central part of the cell C (the article M is not deviated from the central part); in other cases, when the article M is received and delivered by hoisting and lowering the article holder 13, sliding movement of the lateral slider 11 is required, and they are included in a state in which the article M is deviated from the central part of the cell C in a plan view.

[0043]

In Fig. 5 and Fig. 6, a side of the article M is illustrated in a curved manner. In the article M, this curved part indicates a rear side of the article M, whereas the side facing the curved part indicates a front side. As illustrated in Fig. 5(A), the article M is placed on a load port LP of a processing apparatus PA. The load port LP is an example of a transfer destination of the article M. The processing apparatus PA and the load port LP are placed below the grid-like track R. The processing apparatus PA and the load port LP are denoted in Fig. 5(A), whereas they are omitted in the other drawings.

[0044]

As illustrated in Fig. 5(A), the ceiling conveyance vehicle 100 is in a state in which the main body 10 is traveling in the first direction D1 (the +X direction) toward a transfer position P11 in order to receive the article M. When reaching the transfer position P1, the main body 10 stops traveling. The same holds true for a case in which the main body 10 travels in the -X direction toward the transfer position P11. In the present embodiment, the transfer position is a stopping position of the ceiling conveyance vehicle 100 to transfer the article M. In a state in which the main body 10 has stopped traveling at the transfer position P11, the article M is at a position corresponding to the central part of the main body 10 for the first direction D1 and deviated to the +Y side with respect to the central part of the main body 10 for the second direction D2. Consequently, the main body 10 rotates the lateral slider 11 by the first rotational driver 15 so as to enable the lateral slider 11 to slidably move toward the +Y side from the transfer position P11.

[0045]

After the lateral slider 11 is rotated, as illustrated in Fig. 5(B), the main body 10 slidably moves the lateral slider 11 toward the +Y side to cause the hoisting-and-lowering driver 14 to be placed above (on the +Z side of) the article M. In this state, the main body 10 lowers the article holder 13 by the hoisting-and-lowering driver 14 to cause the article holder 13 to hold the article M. The main body 10 then hoists the article holder 13 and slidably moves the lateral slider 11 toward the -Y side and can thereby house the hoisting-and-lowering driver 14, the article holder 13, and the article M.

[0046]

As illustrated in Fig. 6(A), the ceiling conveyance vehicle 100 is in a state in which the main body 10 is traveling in the second direction D2 (the -Y direction) toward a transfer position P12 in order to receive the article M. When reaching the transfer position P12, the main body 10 stops traveling. The same holds true for a case in which the main body 10 travels in the +Y direction toward the transfer position P12. In a state in which the main body 10 has stopped traveling at the transfer position P12, the article M is at a position corresponding to the central part of the main body 10 for the second direction D2 and deviated to the -X side with respect to the central part of the main body 10 for the first direction D1. The main body 10 rotates the lateral slider 11 by the first rotational driver 15 so as to enable the lateral slider 11 to slidably move toward the -X side from the transfer position P12.

[0047]

After rotating the lateral slider 11, as illustrated in Fig. 6(B), the main body 10 slidably moves the lateral slider 11 toward the -X side to cause the hoisting-and-

lowering driver 14 to be placed above (on the +Z side of) the article M. In this state, the main body 10 lowers the article holder 13 by the hoisting-and-lowering driver 14 to cause the article holder 13 to hold the article M. The main body 10 then hoists the article holder 13 to slidably move the lateral slider 11 toward the +X side and can thereby house the hoisting-and-lowering driver 14, the article holder 13, and the article M.

[0048]

Thus, the main body 10 rotates the lateral slider 11 by the first rotational driver 15, whereby for the article M placed deviated from the central part of the cell C in a plan view, reception and delivery from and to the load port LP as the transfer destination of the article M are enabled in both a case in which the first track R1 is the transfer position P11 and a case in which the second track R2 is the transfer position P12. Consequently, either the transfer position P11 or the transfer position P12 may be selected depending on a direction in which the ceiling conveyance vehicle 100 approaches the article M, and the time required for the transfer of the article M is reduced, whereby article conveyance efficiency can be improved. When the article M is delivered to the transfer destination (the load port LP), an operation opposite to the operation described above is performed.

[0049]

In a configuration in which the lateral slider 11 cannot be rotated in the ceiling conveyance vehicle 100, when the sliding movement direction of the lateral slider 11 is the first direction D1 in the configuration in Fig. 5(A), for example, in a state traveling along the first track R1, the ceiling conveyance vehicle 100 cannot receive or deliver the article M and cannot receive or deliver the

article M unless the traveling direction is switched from the first track R1 to the second track R2, then a state in which the ceiling conveyance vehicle 100 travels along the second track R2 is given, and then the lateral slider 11 is slidably moved in the first direction D1. Thus, when switching of the traveling direction of the ceiling conveyance vehicle 100 is required during the transfer of the article M, it takes time for the switching, leading to a reduction in the conveyance efficiency of the article M.

[0050]

Fig. 7 to Fig. 11 are plan views illustrating relations between the direction of the sliding movement of the lateral slider 11 and the orientation of the article M. In Fig. 7 to Fig. 11, the first track R1, the second track R2, and the connection track R3 are illustrated in a simplified manner. Fig. 7 to Fig. 11 illustrate examples in which the article M is delivered to a transfer destination deviated from the central part of the area surrounded by the first track R1 and the second track R2 in a plan view (refer to the cell C in Fig. 3). In the article M illustrated in Fig. 7 to Fig. 11, like the above, the curved part is the rear side of the article M, whereas the side facing the curved part is the front side.

[0051]

In the examples illustrated in Figs. 7(A) and 7(B), the article M is placed at a position deviated to the +X side and the +Y side from the central part of the cell C in a plan view. At the transfer destination illustrated in Fig. 7(A) (the load port LP of the processing apparatus PA, for example), it is designated in advance that the article M is placed with the front side of the article M directed to the -X side, whereas at the transfer destination illustrated in Fig. 7(B) (the load port LP of the

processing apparatus PA, for example), it is designated in advance that the article M is placed with the front side of the article M directed to the +X side.

[0052]

In the example illustrated in Fig. 7(A), after traveling along the second track R2 and stopping traveling at a transfer position P13, the main body 10 rotates the lateral slider 11 around the first perpendicular axis AX1 by the first rotational driver 15 (refer to Fig. 1) so as to enable the lateral slider 11 to slidingly move toward the +X side, and then slidingly moves the lateral slider 11 toward the +X side. In this case, the front side of the article M held by the article holder 13 is directed to the -X direction (refer to the left drawing in Fig. 7(A)), and thus the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the transfer destination with the front side of the article M directed to the -X direction.

[0053]

In the example illustrated in Fig. 7(B), the main body 10, like Fig. 7(A), rotates the lateral slider 11 around the first perpendicular axis AX1 at the transfer position P13, and then slidingly moves the lateral slider 11 toward the +X side. In this case, the front side of the article M held by the article holder 13 is directed to the -X direction (refer to the left drawing in Fig. 7(B)), whereas it is designated that the front side of the article M is directed to the +X direction at the transfer destination. Consequently, the hoisting-and-lowering driver 14 (the article holder 13) is rotated by 180 degrees around the second perpendicular axis AX2 by the second rotational driver 16 (refer to Fig. 1), whereby the front side of the article M is directed to the +X direction. Subsequently,

the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the transfer destination with the front side of the article M directed to the +X direction.

[0054]

In the examples illustrated in Figs. 8(A) and 8(B), the article M is placed at a position deviated to the -X side and the +Y side from the central part of the cell C in a plan view. At the transfer destination illustrated in Fig. 8(A) (the load port LP of the processing apparatus PA, for example), it is designated in advance that the article M is placed with the front side of the article M directed to the +X side, whereas at the transfer destination illustrated in Fig. 8(B) (the load port LP of the processing apparatus PA, for example), it is designated in advance that the article M is placed with the front side of the article M directed to the -X side.

[0055]

In the example illustrated in Fig. 8(A), after traveling along the second track R2 and stopping traveling at the transfer position P13, the main body 10 rotates the lateral slider 11 around the first perpendicular axis AX1 by the first rotational driver 15 (refer to Fig. 1) so as to enable the lateral slider 11 to slidingly move toward the -X side, and then slidingly moves the lateral slider 11 toward the -X side. In this case, the front side of the article M held by the article holder 13 is directed to the +X direction (refer to the left drawing in Fig. 8(A)), and thus the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the transfer destination with the front side of the article M directed to the +X direction.

[0056]

In the example illustrated in Fig. 8(B), the main body 10, like Fig. 8(A), rotates the lateral slider 11 around the first perpendicular axis AX1 at the transfer position P13, and then slidably moves the lateral slider 11 toward the -X side. In this case, the front side of the article M held by the article holder 13 is directed to the +X direction (refer to the left drawing in Fig. 8(B)), whereas it is designated that the front side of the article M is directed to the -X direction at the transfer destination. Consequently, the hoisting-and-lowering driver 14 (the article holder 13) is rotated by 180 degrees around the second perpendicular axis AX2 by the second rotational driver 16 (refer to Fig. 1), whereby the front side of the article M is directed to the -X direction. Subsequently, the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the transfer destination with the front side of the article M directed to the -X direction.

[0057]

In the examples illustrated in Figs. 9(A) and 9(B), the article M is placed at a position deviated to the +X side and the +Y side from the central part of the cell C in a plan view. At the transfer destination illustrated in Fig. 9(A) (the load port LP of the processing apparatus PA, for example), it is designated in advance that the article M is placed with the front side of the article M directed to the +Y side, whereas at the transfer destination illustrated in Fig. 9(B) (the load port LP of the processing apparatus PA, for example), it is designated in advance that the article M is placed with the front side of the article M directed to the -Y side.

[0058]

In the example illustrated in Fig. 9(A), after

traveling along the first track R1 and stopping traveling at a transfer position P14, the main body 10 rotates the lateral slider 11 around the first perpendicular axis AX1 by the first rotational driver 15 (refer to Fig. 1) so as to enable the lateral slider 11 to slidingly move toward the +Y side, and then slidingly moves the lateral slider 11 toward the +Y side. In this case, the front side of the article M held by the article holder 13 is directed to the +Y direction (refer to the left drawing in Fig. 9(A)), and thus the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the transfer destination with the front side of the article M directed to the +Y direction.

[0059]

In the example illustrated in Fig. 9(B), the main body 10, like Fig. 9(A), rotates the lateral slider 11 around the first perpendicular axis AX1 at the transfer position P14, and then slidingly moves the lateral slider 11 toward the +Y side. In this case, the front side of the article M held by the article holder 13 is directed to the +Y direction (refer to the left drawing in Fig. 9(B)), whereas it is designated that the front side of the article M is directed to the -Y direction at the transfer destination. Consequently, the hoisting-and-lowering driver 14 (the article holder 13) is rotated by 180 degrees around the second perpendicular axis AX2 by the second rotational driver 16 (refer to Fig. 1), whereby the front side of the article M is directed to the -Y direction. Subsequently, the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the transfer destination with the front side of the article M directed to the -Y direction.

[0060]

In the examples illustrated in Figs. 10(A) and 10(B), the article M is placed at a position deviated to the +X side and the -Y side from the central part of the cell C in a plan view. At the transfer destination illustrated in Fig. 10(A) (the load port LP of the processing apparatus PA, for example), it is designated in advance that the article M is placed with the front side of the article M directed to the -Y side, whereas at the transfer destination illustrated in Fig. 10(B) (the load port LP of the processing apparatus PA, for example), it is designated in advance that the article M is placed with the front side of the article M directed to the +Y side.

[0061]

In the example illustrated in Fig. 10(A), after traveling along the first track R1 and stopping traveling at the transfer position P14, the main body 10 rotates the lateral slider 11 around the first perpendicular axis AX1 by the first rotational driver 15 (refer to Fig. 1) so as to enable the lateral slider 11 to slidingly move toward the -Y side, and then slidingly moves the lateral slider 11 toward the -Y side. In this case, the front side of the article M held by the article holder 13 is directed to the -Y direction (refer to the left drawing in Fig. 10(A)), and thus the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the transfer destination with the front side of the article M directed to the -Y direction.

[0062]

In the example illustrated in Fig. 10(B), the main body 10, like Fig. 10(A), rotates the lateral slider 11 around the first perpendicular axis AX1 at the transfer position P14, and then slidingly moves the lateral slider 11 toward the -Y side. In this case, the front side of the

article M held by the article holder 13 is directed to the -Y direction (refer to the left drawing in Fig. 10(B)), whereas it is designated that the front side of the article M is directed to the +Y direction at the transfer destination. Consequently, the hoisting-and-lowering driver 14 (the article holder 13) is rotated by 180 degrees around the second perpendicular axis AX2 by the second rotational driver 16 (refer to Fig. 1), whereby the front side of the article M is directed to the +Y direction. Subsequently, the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the transfer destination with the front side of the article M directed to the +Y direction.

[0063]

In the example illustrated in Fig. 11, the article M is placed at a position deviated to the +X side and the -Y side from the central part of the cell C (the cell C at the lower left of the drawing) in a plan view. In Fig. 11, the processing apparatus PA is placed inclined with respect to the first direction D1 or the second direction D2, and the load port LP of this processing apparatus PA is also inclined with respect to the first direction D1 or the second direction D2. The load port LP is like the above in that it is designated in advance that the article M is placed with the front side of the article M directed to the processing apparatus PA.

[0064]

As illustrated in Fig. 11, after traveling along the second track R2 and stopping traveling at a transfer position P15, the main body 10 rotates the lateral slider 11 around the first perpendicular axis AX1 by the first rotational driver 15 (refer to Fig. 1) so as to enable the lateral slider 11 to slidingly move toward the -X side and

the +Y side above the load port LP, and then slidingly moves the lateral slider 11 toward the -X side and the +Y side. In this case, the front side of the article M held by the article holder 13 is deviated from the orientation designated at the load port LP illustrated in Fig. 11. Consequently, the hoisting-and-lowering driver 14 (the article holder 13) is rotated around the second perpendicular axis AX2 by the second rotational driver 16 (refer to Fig. 1), whereby the front side of the article M is directed to the processing apparatus PA. Subsequently, the article holder 13 is lowered by the hoisting-and-lowering driver 14, whereby the article M can be placed at the load port LP with the front side of the article M directed to the processing apparatus PA.

[0065]

Although in the example illustrated in Fig. 11 the orientation of the article M is aligned with the orientation of the load port LP using both the rotation of the lateral slider 11 by the first rotational driver 15 and the rotation of the hoisting-and-lowering driver 14 by the second rotational driver 16, this aspect is not limiting. At the load port LP illustrated in Fig. 11, the transfer position P15 at which the main body 10 stops is adjusted, whereby the orientation of the article M may be able to be aligned with the orientation of the load port LP using only the rotation of the lateral slider 11 by the first rotational driver 15, for example. In Fig. 11, the transfer position P15 of the main body 10 is shifted toward the +Y side from the position illustrated in Fig. 11, and the direction of the sliding movement of the lateral slider 11 and the orientation of the article M designated at the load port LP are aligned, whereby the article M may be able to be placed at the load port LP without rotating the

hoisting-and-lowering driver 14, for example.

[0066]

Fig. 7 to Fig. 11 illustrate examples in which the article M can be placed at the transfer destination with the orientation of the article M aligned with the orientation designated by the transfer destination, and the same holds true for cases not illustrated. That is, rotating the lateral slider 11 around the first perpendicular axis AX1 by the first rotational driver 15 and rotating the hoisting-and-lowering driver 14 (the article holder 13) around the second perpendicular axis AX2 by the second rotational driver 16 can place the article M with the orientation designated by the transfer destination deviated from the central part of the cell C in a plan view. Consequently, according to the present embodiment, the degree of freedom of the relative position between the grid-like track R (the track) and the load port LP (the processing apparatus PA) can be improved, and in addition, the degree of freedom for a position and a direction at which and in which the processing apparatus PA is installed (the position and the direction of the load port LP) can also be improved. That is, when the orientation of the article M to be placed at the load port LP is determined in advance like the processing apparatus PA, the position and the orientation of the load port LP as the transfer destination of the article M (the position and the orientation of the processing apparatus PA) can be set relatively freely with respect to the grid-like track R, and thus space efficiency can be improved, including relaxation of limitations on installation of the processing apparatus PA on the surface of a floor.

[0067]

In the embodiment, a time at which the hoisting-and-

lowering driver 14 (the article holder 13) is rotated by the second rotational driver 16 may be the time during which the main body 10 is traveling along the grid-like track R or the lateral slider 11 is slidably moving. Another example of a time at which the lateral slider 11 is rotated by the first rotational driver 15 will be described below.

[0068]

Thus, according to the ceiling conveyance vehicle 100 and the ceiling conveyance vehicle system SYS according to the present embodiment, the lateral slider 11 is rotatable around the first perpendicular axis AX1 with respect to the main body 10, and thus the lateral slider 11 can be slidably moved in a desired direction when the traveling direction of the main body 10 is any one of the first track R1 and the second track R2. Consequently, even when the direction of the sliding movement by the lateral slider 11 and the traveling direction of the main body 10 match, the article holder 13 can be moved in a direction other than the traveling direction such as a direction orthogonal to the traveling direction, and the transfer position of the article M can easily be adjusted.

[0069]

<Second Embodiment>

Fig. 12 is a side view illustrating an example of a ceiling conveyance vehicle 200 according to a second embodiment. Although the first embodiment describes a case in which the hoisting-and-lowering driver 14 is rotated around the second perpendicular axis AX2 by the second rotational driver 16 as an example, this aspect is not limiting; the article holder 13 may be rotated. As illustrated in Fig. 11, in the ceiling conveyance vehicle 200 according to the second embodiment, the main body 10

has a second rotational driver 116 rotating the article holder 13 around the second perpendicular axis AX2. In the ceiling conveyance vehicle 200, components similar to those of the ceiling conveyance vehicle 100 of the first embodiment are denoted by the same symbols, and descriptions thereof are omitted or simplified.

[0070]

The second rotational driver 116 is connected to the lowermost part of the hanging member 13b and is placed on the article holder 13. The second rotational driver 116, for which an electric motor or the like is used, for example, rotates the article holder 13 in a range of at least 180 degrees around the second perpendicular axis AX2 from one direction out of directions orthogonal to the linear direction in which the lateral slider 11 slidingly moves. Consequently, the article M held by the article holder 13 can be rotated in a range of 180 degrees around the second perpendicular axis AX2 to direct the front side of the article M to an opposite direction.

[0071]

With the ceiling conveyance vehicle 200 of the present embodiment, like the ceiling conveyance vehicle 100, the transfer position of the article M can easily be adjusted. The second rotational driver 116 rotates the article holder 13 around the second perpendicular axis AX2, and thus the rotation path of the article M is shorter than that of a case in which the hoisting-and-lowering driver 14 is rotated, and thus when the article M is rotated after the article holder 13 has been lowered in particular, the responsiveness of the rotation of the article M during the drive of the second rotational driver 116 is high, and the orientation of the article M can be adjusted in a short time.

[0072]

Although the first and second embodiments describe an example in which the main body 10 has stopped at the transfer position, and then the sliding movement of the lateral slider 11 is performed, this operation is not limiting. Fig. 13 is a plan view illustrating an example of timing between the traveling of the main body 10 and the sliding movement of the lateral slider 11. As illustrated in Fig. 13(A), while the main body 10 is traveling along the grid-like track (the track) R toward a transfer position P16 in order to transfer the article M to a transfer destination P, the controller 50 may drive the first rotational driver 15 to rotate the lateral slider 11 around the first perpendicular axis AX1.

[0073]

When acquiring information on the transfer position P16, the controller 50 acquires information on the transfer destination P from a host controller or the like. After stopping at the transfer position P16, the controller 50 acquires the direction of the sliding movement by the lateral slider 11 from the information on the transfer destination P. Consequently, the controller 50 rotates the lateral slider 11 while the main body 10 is traveling, and can thereby start the sliding movement of the lateral slider 11 in a short time after the stopping of the main body 10 or at the same time with the stopping and reduce the time required for the transfer of the article M. When the lateral slider 11 employs one-sided sliding movement in particular, the lateral slider 11 is rotated in a range of 270 degrees, and thus rotation of the lateral slider 11 is executed while the main body 10 is traveling, whereby a reduction in the transfer time of the article M can be achieved.

[0074]

The controller 50 need not correctly acquire the direction of the sliding movement by the lateral slider 11. The controller 50 may roughly calculate the direction of the sliding movement from the coordinates of the transfer position P16 and the transfer destination P and rotate the lateral slider 11 toward the direction, for example. Also in this case, adjustment of a rotational position of the lateral slider 11 is completed in a short time after the stopping at the transfer position P16, and thus the time required for the transfer of the article M can be reduced. The controller 50 may set the rotational position of the lateral slider 11 such that the linear direction in which the lateral slider 11 slidingly moves and the transfer destination P overlap with each other in a plan view when the main body 10 has stopped at the transfer position P16. In this configuration, as illustrated in Fig. 13(B), after the main body 10 has reached the transfer position P16, the sliding movement (the one-sided sliding movement) by the lateral slider 11 can immediately be started, and a transfer operation for the article M can quickly be performed after the main body 10 has reached the transfer position P16.

[0075]

Although the embodiments have been described, the present invention is not limited to the description described above, and various modifications can be made to the extent not departing from the gist of the present invention. Although the embodiments described above describe a configuration in which the main body 10 includes the second rotational driver 16 or 116 as an example, this configuration is not limiting. The main body 10 may not necessarily include the second rotational driver 16 or 116.

When the article M has no directivity (when the article bears a similar aspect regardless of the orientation thereof) or when the orientation of the article M is not designated in a transfer destination, for example, even the ceiling conveyance vehicle 100 not including the second rotational driver 16 or 116 can easily adjust the transfer position of the article M like the embodiments.

[0076]

Although the embodiments describe a configuration in which the direction changer 34 rotates the coupler 30 around the turning axis AX3 with respect to the main body 10 to switch between the first state, in which the traveling wheel 21 travels along the first track R1, and the second state, in which the traveling wheel 21 travels along the second track R2, as an example, this configuration is not limiting. A first traveling wheel traveling along the first track R1 and a second traveling wheel traveling along the second track R2 may separately be provided, and the first traveling wheel and the second traveling wheel may be used in a switching manner in accordance with the traveling direction of the main body 10, for example.

[0077]

Although the embodiments describe the grid-like track R in which the first track R1 (the first direction D1) and the second track R2 (the second direction D2) are orthogonal to each other as an example, this configuration is not limiting. The track R may be an aspect in which the first track R1 and the second track R2 are not orthogonal to each other, for example. Without being limited to the aspect being the grid-like track R in which the first track R1 and the second track R2 cross each other, the track R may be an aspect in which the second track R2 is placed

bent from an end of the first track R1, for example. To the extent permitted by law, the contents of Japanese Patent Application No. 2018-203024 as a Japanese patent application and all the literature cited in the present specification are hereby incorporated herein by reference.

Description of Reference Signs

[0078]

AX1: FIRST PERPENDICULAR AXIS
AX2: SECOND PERPENDICULAR AXIS
SYS: CEILING CONVEYANCE VEHICLE SYSTEM
D1: FIRST DIRECTION
D2: SECOND DIRECTION
M: ARTICLE
P: TRANSFER DESTINATION
P1, P11, P12, P13, P14, P15, P16: TRANSFER POSITION
R: TRACK
R1: FIRST TRACK
R2: SECOND TRACK
R3: CONNECTION TRACK
10: MAIN BODY
11: LATERAL SLIDER
13: ARTICLE HOLDER
14: HOISTING-AND-LOWERING DRIVER
15: FIRST ROTATIONAL DRIVER
16, 116: SECOND ROTATIONAL DRIVER
21: TRAVELING WHEEL
34: DIRECTION CHANGER
50: CONTROLLER
100, 200: CEILING CONVEYANCE VEHICLE

CLAIMS

1. A ceiling conveyance vehicle that includes a traveling wheel rolling on a track including a first track extending in a first direction and a second track extending in a second direction different from the first direction, and a main body placed below the track and coupled to the traveling wheel, the ceiling conveyance vehicle comprising:

- a direction changer switching between a first state in which the traveling wheel rolls on the first track and a second state in which the traveling wheel rolls on the second track, with an orientation of the main body with respect to the track maintained;

- an article holder capable of holding an article;

- a hoisting-and-lowering driver hoisting and lowering the article holder;

- a lateral slider slidably moving the hoisting-and-lowering driver in a horizontal, linear direction; and

- a first rotational driver rotationally driving the lateral slider around a first perpendicular axis with respect to the main body.

2. The ceiling conveyance vehicle according to claim 1, comprising a second rotationally driver rotationally driving the article holder or the hoisting-and-lowering driver around a second perpendicular axis with respect to the lateral slider.

3. The ceiling conveyance vehicle according to claim 2, wherein the second rotationally driver rotates the article holder or the hoisting-and-lowering driver in a range of at least 180 degrees around the second perpendicular axis on the basis of the linear direction.

4. The ceiling conveyance vehicle according to any one of claims 1 to 3, wherein

the track is a grid-like track in which the first direction and the second direction are orthogonal to each other,

the lateral slider one-sidedly slidably moves the hoisting-and-lowering driver in one direction in the linear direction, and

the first rotational driver rotates the lateral slider in a range of 270 degrees around the first perpendicular axis from a state in which a direction of one-sided sliding movement of the lateral slider is aligned with the first direction or the second direction.

5. The ceiling conveyance vehicle according to any one of claims 1 to 4, comprising a controller driving the first rotational driver to rotate the lateral slider around the first perpendicular axis while going toward a transfer position to perform transfer of an article with respect to a transfer destination.

6. The ceiling conveyance vehicle according to claim 5, wherein the controller sets a rotational position of the lateral slider such that the linear direction in which the lateral slider slidably moves and the transfer destination overlap with each other in a plan view when the main body has stopped at the transfer position.

7. A ceiling conveyance vehicle system comprising:

a track including a first track extending in a first direction and a second track extending in a second direction different from the first direction; and

a ceiling conveyance vehicle traveling along the track,
the ceiling conveyance vehicle being the ceiling
conveyance vehicle according to any one of claims 1 to 6.