

**Capsule and method for preparing a beverage such as coffee
from said capsule**

The present invention relates to a capsule and a method for
5 preparing a beverage such as a coffee extract from a
single-use capsule containing a beverage ingredient (e.g.,
roast and ground coffee) inserted in a beverage producing
beverage.

A successful method for preparing a beverage from capsules
10 containing a beverage ingredient is described in EP0468570.
The principles consists in inserting a capsule containing
coffee powder and extracting a coffee liquid by tearing a
delivery membrane of the capsule under the effect of
pressure against a capsule holder comprising a network of
15 small truncated pyramids. The truncated pyramids create
controlled orifices in the membrane and filter the coffee
extract that is discharged through the capsule holder then
down to a discharge duct.

Other patent publications relate to providing a sealing
20 member at the capsule for improving liquid tightness
between the capsule and the pressurized water injection
system such as EP1654966, EP1702543, EP1700548, EP1816936
and WO 2009/115474.

Certain consumers prefer coffees that have not too strong
25 taste or aroma characteristics that are typically
obtainable by the high pressure extraction method of the
prior art. For certain coffees like lungo, the method may
also produce over-extraction of compounds that provide
undesired bitterness to the coffee extract.

30 Therefore, it would be advantageous to deliver a coffee
beverage of lighter strength or taste, or less dense coffee
crema, while maintaining the effectiveness of the prior art

extraction principle which can deliver on demand coffee beverages which are intimately extracted with a high aroma intensity and thick crema.

One object of the present invention is to provide a
5 solution to this need by proposing a method which principle is to create a water bypass to dilute the coffee extract which is extracted through the capsule with hot water from the device.

More particularly, the invention relates to a method for
10 the preparation of a beverage, preferably coffee, using a capsule containing a dose of beverage ingredient, preferably ground coffee, by insertion of the capsule in a beverage preparation unit comprising a capsule holder and a water injection enclosing member; comprising the operations
15 of:

- inserting the capsule between the capsule holder and the water injection enclosing member while pressing the sealing rim against the capsule holder by a grooved pressing surface of the water injection enclosing member,
- 20 - injecting water under pressure in the volume between the capsule and water injection enclosing member and in the capsule,

wherein a bypass of water is provided at the beginning of the water injection operation between the pressing
25 surface comprising radial grooves and the capsule,

wherein such water bypass is stopped or at least reduced when further carrying on the water injection step,

wherein liquid extract is forced to flow from the interior of the capsule through the delivery wall, through
30 the capsule holder and to a discharge duct and,

wherein the water bypass is collected and also guided to said discharge duct.

In the preferred mode, the water bypass is stopped or at least reduced during water injection by softening the material of the rim under the effect of hot liquid injected between the capsule and the enclosing member and the
5 mechanical pressure exerted by the injection enclosing member on the rim.

In a first mode, the material of the rim is preferably a semicrystalline polymer material chosen in a grade having a
10 Vicat softening point (ISO 10350) between about 30 and 100°C, preferably between 40 and 90°C, most preferably between 40°C and 80°C.

Preferably, the semicrystalline material comprises
15 thermoplastic polymer of the group of polyolefins.

More preferably, the material is selected amongst the group of:

- polyethylene in particular high density polyethylene,
20 medium density polyethylene, low linear density polyethylene,

- a blend of:

- a) a polymer chosen amongst polyethylene (PE) or polypropylene (PP) and,

- 25 b) at least one copolymer chosen amongst the group consisting of: ethylene copolymer(s) or terpolymer(s) of ethylene and combinations thereof.

Most preferably, said copolymer of the list b) is chosen
30 amongst the group consisting of:

- b1) EVA (ethylene vinyl acetate), EMA (ethylene glycol monobutyl monomer ether acetate), EBA (poly(ethylene-co-butyl acrylate) and combinations thereof, or

b2) a polyolefin elastomer or plastomer, preferably EPDM (ethylene propylene diene monomer), or combinations thereof.

5 In particular, said polymer a (i.e., PE or PP) provides the mechanical properties to the capsule, in particular, its resistance against buckling during perforation by the injection needles. It also compensates for the lower heat resistance of the second polymer or
10 functional polyolefins (i.e., EVA, EMA EBA, etc.).

 Instead of or in addition to low heat resistant polyolefins, a rubber elastomer (TPEs) or plastomer can be added to the first polymer to provide similar functions.
15
Therefore, preferably, the ratio of polymer(s) and copolymer(s) a:b, is comprised between 10:0.1 and 10:5, more preferably 10:0.2 to 10:3, most preferably 10:0.3 to 10:1.

20
Additional charges and/or specific additives can also be added into the material such as in copolymer(s) of the list b, such as calcium carbonate, titanium dioxide, fibres, glass beads and combinations thereof.

25
In another mode, the material constituting at least part of the rim is an (e.g., thermoplastic) polymer chosen in a grade having a glass transition temperature (T_g) between 30 and 80°C, preferably between 40 and 60°C. When the glass
30 transition temperature of the material has been reached, because of the hot injected liquid, the material behaves like rubber. This causes the grooves of the pressing surface of the injection enclosing member to become clogged

by the material and, consequently, the bypass of water to stop.

Preferably, the polymer material which constitutes at least
5 part of the rim is a biodegradable polyester. This polyester is also preferably an agro-resource-based polyester.

Preferably, the polymer material which constitutes at least
10 part of the rim is chosen amongst the group consisting of: polyester such as crystallized or semi-crystallized PET (cPET), crystallized or semicrystallized polylactic acid (cPLA) PET (polyethylene terephthalate), PLA (polylactic acid) and combinations thereof.

15 At least partially crystallized PLA or PET is preferred to non-crystallized PLA or PET since it provides a higher temperature and pressure resistance during extraction.

20 In one mode, the PLA polyester is a blend or copolymer of PLLA (poly-L-lactide) and PDLA (poly-D-lactide). The ratio of PLLA:PDLA can be varied depending on the degree of crystallinity, mechanical properties and temperature resistance desired.

25 According to the present invention, the synergy between the behaviour properties of the material of the capsule, in particular its rim, and the configuration of the device provides a certain dilution ratio of the final beverage.

30 The dilution ratio can be controlled by choosing the proper material of the capsule and dimensioning the grooved pressing surface of the device accordingly.

The extraction is carried out in basically two steps; a first step during which a certain water bypass is provided along the rim and a second step during which the beverage is essentially extracted through the capsule and the bypass
5 reduced or stopped. This result in a weaker, lower-crema coffee compared to typical coffee bar beverages (espresso/lungo) obtained by prior art capsule systems providing no bypass effect.

10 The delivery wall of the capsule preferably tears under pressure against protrusions provided on the capsule holder during water injection. In particular, the delivery wall is an aluminium membrane of thickness comprised between 10 and 120 microns, preferably between 20 and 100 microns. The
15 membrane is allowed to tear only when a threshold of pressure is reached in the capsule according to the principle described in EP0468570. This enables to provide a higher interaction of coffee and hot water in the capsule. It also promotes the bypass of water in the first part of
20 the extraction. However, a compromise should be reached to ensure that the bypass is not too large which would prevent pressure from increasing sufficiently in the capsule and thereby the membrane from tearing against the capsule holder. Such control can be obtained by choosing the
25 material of the rim, as well as the thickness of the rim. For this, the rim has preferably a thickness comprised between 0.5 and 1.2 mm, most preferably 0.7 to 1.1 mm.

In an alternative, the delivery wall can be a porous wall.
30 The advantage is a lower pressure building in the capsule and potentially weaker extraction results (i.e., lower total solids (Tc) in cup).

The present invention further relates to a capsule for the preparation of a beverage in a beverage preparation device comprising:

- 5 a cup-shaped body comprising a cavity containing a beverage ingredient and a flange-like rim extending outwardly from the base of said body,
 - a delivery wall connected to the flange-like rim,
 - characterized in that the flange-like rim is formed of a polymer material chosen in a grade having a Vicat
 - 10 softening point (ISO 10350) between about 30 and 100°C, preferably between 40 and 90°C, most preferably between 40 and 80°C or an polymer chosen in a grade having a glass transition temperature (Tg) between 30 and 80°C, preferably between 40 and 60°C.

15

Although the capsule of the invention is preferably utilized for carrying out the method of the invention, it is not limited to this method.

- 20 In a mode, the polymer material is an agro-resource based polyester.

- In a mode, the polymer material is selected amongst the group consisting of: polyester such as crystallized or
- 25 semi-crystallized PET (cPET), crystallized or semicrystallized polylactic acid (cPLA) PET (polyethylene terephthalate), PLA (polylactic acid) and combinations thereof.

- 30 In one mode, the PLA polyester is a blend or copolymer of PLLA (i.e., poly-L-lactide) and PDLA (i.e., poly-D-lactide). The ratio of PLLA:PDLA can be varied depending on the degree of crystallinity, mechanical properties and

temperature resistance desired. The ratio of PLLA to PDLA may range of from 99:1 to 40:60, more preferably 95:5 to 50:50.

- 5 In a mode, the delivery wall is a membrane configured for being at least partially torn under pressure against protrusions provided on the capsule holder during water injection.
- 10 In a mode, the delivery wall is configured with filtering apertures. The filtering apertures preferably have a diameter of less than 300 microns, more preferably, less than 200, most preferably less than 100 microns.
- 15 The rim preferably has a thickness between 0.5 and 1.2 mm.

In a mode, the flange-like rim has a thickness which comprises at least a portion which is of greater thickness than the thickness of the sidewall of the body. This
- 20 increase of thickness ensures sufficient material can be softened and pressed by the grooved pressing surface of the water injection member to provide a final liquid-tight engagement.
- 25 In a mode, the flange-like rim comprises the flange-like rim comprises at least one lip forming a local increase of thickness protruding from the rim in a direction opposite to the membrane. Again, this configuration ensures that sufficient material of the rim can be softened and pressed
- 30 by the grooved pressing surface of the water injection member to provide a final liquid-tight engagement while maintaining a light, eco-friendly structure for the capsule.

In a mode, the membrane is an aluminium or aluminium alloy membrane.

In another mode, the membrane is made of the same material
5 as the polymer material of the body.

The invention also relates to a system for the preparation of a beverage comprising a capsule as aforementioned and a beverage preparation unit wherein the unit comprises a
10 capsule holder and an enclosing member for receiving the capsule; said enclosing member comprising an annular pressing surface comprising radial grooves; said pressing surface being configured for compressing the flange-like rim of the capsule wherein the material of the flange-like
15 rim is configured during water injection for clogging the grooves of the pressing surface thereby providing a liquid-tight engagement between the capsule and the enclosing member.

20 The invention will be better understood in relation to the figures attached which are given as a preferred embodiment.
Figure 1 shows the operation of insertion of the capsule in the beverage preparation device according to the method of the invention,

25 Figure 2 shows the operation of water injection at the start of the coffee extraction in the closed device,

Figure 3 shows the operation of water injection water injection during coffee extraction,

Figure 4 shows the operation of insertion of the capsule in
30 the beverage preparation device according to a second embodiment of the capsule,

Figure 5 shows the operation of insertion of the capsule in the beverage preparation device according to a third embodiment of the capsule.

In the method of the present invention, a beverage
5 preparation device 1 is provided into which is inserted a capsule 2. The device 1 comprises a capsule holder 3, a water injection enclosing member 4 and a collector 5.

The capsule holder 3 is formed of a support member comprising protrusions such as truncated pyramids 6,
10 channels 7 between the protrusions and orifices 8 provided through the holder 3 for draining liquid extract through the capsule holder.

The water injection enclosing member 4 has the shape of a bell with an internal cavity 9, an injection conduit 10 and
15 blades 16 enabling to perforate water inlets in the inlet face of the capsule 2. At the free end of the enclosing member 4 is provided a pressing surface 17 comprising a plurality of radial grooves 15 as described in WO
2009/115474 herein enclosed by reference. In the present
20 invention, the grooves are utilized here to control a temporary bypass of water between the capsule and the enclosing member, until a liquid-tight sealing is obtained by clogging of the grooves with the material of the capsule as will be explained.

25 Downstream of the capsule holder is provided a collector 5 for collecting the liquid extract as well as water leaking from the device. The collector is designed to guide liquid to a common discharge liquid duct 11. Therefore, the collector is large enough to encompass the periphery of the
30 capsule holder. For example, the collector can be designed as described in WO 2009/115474. It should be noted that the device may be oriented differently, for instance, with the

enclosing member 4 and capsule holder being substantially horizontal rather than vertical (i.e., said holder 3 below said member 4) as represented here.

The capsule 2 according to the invention has a cup-shaped
5 body 12 containing a dose beverage ingredient, e.g., roast and ground coffee, and a delivery wall 13 sealed onto the rim 14 of the body.

The delivery wall 13 can be of various configurations.

In a preferred configuration, the delivery wall is a thin
10 membrane which tears under the pressure of extraction building up in the capsule against the protrusions 6, e.g., aluminium membrane of between 20-120 microns, as described in EP0468570. "Aluminium" also encompasses here any suitable kind of aluminium alloys. The thin membrane may
15 comprise means for reducing the resistance of the membrane such as weakening lines or cuts or means for reducing the opening pressure of the membrane in the capsule such as a limited number of tiny pre-perforated holes.

In a second configuration, the delivery wall is formed of a
20 porous wall that does not tear or tears only partially under the pressure against the capsule holder.

The body of the capsule is preferably formed integrally with the flange-like rim 14. The material for the rim is preferably at least partially made of or at least covered
25 by a sealing material that softens under contact with the hot pressurized liquid. Preferably, the entire body is made integrally of this material.

As aforementioned, the material is formed of a polymer material having a Vicat softening point (ISO 10350) between
30 about 30 and 100°C, preferably between 40 and 90°C.

As known per se, the Vicat softening temperature is the temperature at which a flat-ended needle penetrates the specimen to the depth of 1 mm under a specific load (50N).

- 5 In a first mode, the polymer material can be a thermoplastic polymer, preferably polyolefins. In the preferred mode, the polymer is polyethylene such as high density polyethylene (HDPE), medium density polyethylene (MDPE), or low linear density polyethylene (LLDPE) wherein
10 the grade of the polyethylene material is chosen to meet the Vicat softening point within the defined range.

In a second mode the polymer material is a blend of:

- a1- a polymer chosen amongst polyethylene (PE) or
15 polypropylene (PP) and,
b1- at least one second copolymer of ethylene copolymer or terpolymer of ethylene, most preferably chosen amongst EVA (Ethylene vinyl acetate), EMA (ethylene glycol monobutyl monomer ether acetate), EBA (poly(ethylene-co-
20 butyl acrylate) and combinations thereof.

The ratio of a:b1 is preferably comprised between 10:0.1 and 10:5, more preferably 10:0.2 to 10:3, most preferably 10:0.3 to 10:1.

- 25 In a third mode, the polymer is a blend of:

- a- a polymer chosen amongst polyethylene (PE) or polypropylene (PP) and
b2- a rubber elastomer or plastomer.

- The polymer b2 can be EPDM (ethylene propylene diene
30 monomer) or a blend of EPDM and metallocene plastomer.
The ratio of a:b2 is preferably comprised between 10:0.1 and 10:5, more preferably 10:0.2 to 10:3, most preferably 10:0.3 to 10:1.

In another mode, the polymer material may also be chosen amongst polymer(s) chosen in a grade comprising a glass transition temperature (T_g) between 30 and 80°C, preferably
5 between 40 and 60°C.

The polymer material can be chosen amongst agro-resources-based polyesters.

10 Therefore, in a fourth mode, the material is selected amongst the group consisting of: polyester such as crystallized or semi-crystallized PET (cPET), crystallized or semicrystallized polylactic acid (cPLA) PET (polyethylene terephthalate), PLA (polylactic acid) and
15 combinations thereof.

Poly(lactic acid) (i.e., PLA) can be produced in different ways: chemical or biological, such as by fermentation of carbohydrate from lactobaccilus. The PLA comprises
20 different enantiomeric monomers (PLLA or PDLA) are polycondensed via its cyclic dimmer (lactide) by ring-opening polymerisation to a high molecular weight polymer. The heat properties and crystallinity of PLA is related to the ratio between the two mesoforms D and L. For the
25 invention, the ratio of PLLA:PDLA preferably varies of from 95:5 to 40:60. The PLA may be further plasticized by oligomeric lactic acid (OLA), citrate ester, low molecular weight polyethylene-glycol (PEG) and combinations thereof.

30 As illustrated in figure 2, the device is closed onto the capsule by application of a mechanical and/or hydraulic pressure of the pressing surface of the enclosing member 4 onto the rim of the capsule. A closure obtained by

combination of mechanical and hydraulic means is described, for example, in WO 2008/037642 herein incorporated by reference.

The method comprises an operation of injection of hot water
5 through the injection enclosing member 4 in the cavity
after closing as shown in figure 2. In the early phase of
this operation (figure 2), the material of the rim is not
yet softened by the pressurized liquid. Thereby the grooves
15 remain at least partially opened forming water bypassing
10 through-holes in the enclosing member 4. The pump of the
device, e.g., a piston pump (not illustrated) forces water
under pressure in the cavity. The rising pressure thereby
causes water to flow through the restriction formed by the
grooves which are not yet clogged by the material of the
15 rim. This leakage provides a bypass 18 for the flow of
water which is collected by the collector 5 and drains
through the discharge duct 11 to fill the receptacle (e.g.,
the coffee cup) placed underneath. During this phase, the
pressure loss created in the capsule (e.g., by the coffee
20 bed and delivery wall) may be higher than the pressure loss
created outside the capsule, i.e., by the flow restriction
caused by the grooves 15. As a result, essentially water is
drained at the interface between the rim and the enclosing
member. During this phase, the membrane does not perforate
25 yet against the capsule holder 3 or perforates only
partially thereby causing some liquid extract to start
being dispensed from the capsule. Water or resulting
mixture (i.e., water and some liquid extract) is collected
by the collector 5 and into the receptacle.

30 In the next phase of the method of the invention,
pressurized hot water has softened the rim sufficiently
that the enclosing member penetrates further into the rim
due to the mechanical/hydraulic pressure causing the

grooves 15 to become clogged by the material of the rim. As a result, the water bypass 18 stops or is at least significantly reduced which causes the pressure in the capsule to further rise significantly. Interaction between
5 coffee powder and water is normally obtained at a higher pressure than in the first extraction phase. When the delivery wall is a tear membrane, it can perforate against the protrusions (or be further torn)) and the liquid extract is released, as illustrated, at least a higher flow
10 rate than in the first phase.

When the delivery wall is a porous member, the liquid extract overcomes the back-pressure of the wall and discharges through the capsule holder.

Figure 4 illustrates a variant of the invention in which
15 the capsule 2 comprises a flange-like rim 14 which comprises a lip 19 forming a local increase of thickness protruding in a direction opposite to the delivery wall 13. The lip is configured on the flange-like rim to be deformed by the pressing surface 17 of the enclosing member 4 to
20 fill the grooves 15 after sufficient softening by hot water under pressure pressing outwardly at the external surface of the body. One or more than one lip can extend from the base portion of the rim, such as a series of two or three concentric annular lips.

25 The lip can be made so that it is more flexible and/or thinner than the transversal annular wall of the rim. As a result, the lip softens more rapidly while the rest of the rim becomes remains rigid.

The lip preferably comprises a cross section that decreases
30 from its base to its free end, e.g., forming a conical, pyramidal or rounded section.

Figure 5 illustrates another variant in which the capsule 2 comprises a flange-like rim 14 which is thicker than at least a wall portion of the body 12 outside the rim. In particular, the body comprises three portions, a flange-like rim 14, a sidewall 20 and a bottom wall 21. The thickness (t1) of the flange-like rim 14 is dimensioned to be thicker than the thickness (t2) of the sidewall 20 or than the thickness (t3) of the bottom wall 21. Preferably, the thickness (t2) of the sidewall 20 is equal or higher than the thickness (t3) of the bottom wall. The bottom wall 21 is preferably made thinner to provide a lesser resistance to perforation by the perforating elements 16 whereas the flange-like rim is made thicker to ensure a sufficient amount of material for sealing purpose. Of course, the flange-like rim 14 could also be made as thick as the sidewall 20 and only the bottom wall is made thinner. Also, the flange-like rim could also be as in the embodiment of figure 4, i.e., with a lip protruding from the base portion of the rim.

In a possible mode, the sealing means (e.g. lip 19 or increase thickness) provides a liquid-tight engagement with the pressing surface which is effective from the beginning of the water injection operation without creating a bypass as aforementioned. In particular, a tight-engagement can be desired to ensure higher pressure conditions in the capsule, for example, when extracting a short and/or stronger coffee such as espresso or ristretto types.

CLAIMS:

1. Capsule for the preparation of a beverage in a beverage preparation device comprising:

5 a cup-shaped body (12) comprising a cavity containing a beverage ingredient and a flange-like rim (14) extending outwardly from the base of said body,

 a beverage delivery wall (13) connected to the flange-like rim,

10 characterized in that the flange-like rim is formed of a polymer material chosen in a grade having a Vicat softening point according to ISO 10350 being between about 30 and 100°C, preferably between 40 and 90°C or a polymer chosen in a grade comprising a glass transition temperature
15 (T_g) between 30 and 80°C, preferably between 40 and 60°C.

2. Capsule according to claim 1, wherein the polymer material is selected amongst the group of:

 - polyethylene in particular HPDE, MDPE or LLDPE,

20 - a blend of:

 a) a polymer chosen amongst polyethylene (PE) or polypropylene (PP) and,

 at least one polymer chosen amongst the group of:

 b) ethylene copolymers and terpolymers and
25 combinations thereof.

3. Capsule according to claim 2, wherein said at least one copolymer is chosen amongst the group consisting of:

 b1) Ethylene vinyl acetate (EVA), ethylene glycol
30 monobutyl monomer ether acetate (EMA), polyethylene-co-butyl acrylate (EBA) and combinations thereof, or

 b2) a rubber elastomer or plastomer, preferably ethylene propylene diene monomer (EDPM)

and combinations thereof.

4. Capsule according to claim 1, wherein the polymer material is an agro-resource based polyester.

5

5. Capsule according to claims 1 or 4, wherein said polymer material is selected amongst the group consisting of:

polyester such as crystallized or semi-crystallized PET (cPET), crystallized or semicrystallized polylactic acid

10 (cPLA), polyethylene terephthalate (PET), polylactic acid (PLA) and combinations thereof.

6. Capsule according to any of claims 1 to 5, wherein the delivery wall is a membrane configured for being at least

15 partially torn under pressure against protrusions provided on the capsule holder during water injection.

7. Capsule according to any of claims 1 to 5, wherein the delivery wall is configured with filtering apertures.

20

8. Capsule according to claim 7, wherein the filtering apertures have a diameter of less than 300 microns.

9. Capsule according to any of the preceding claims,

25 wherein the flange-like rim has a thickness which comprises at least a portion which is of greater thickness than the thickness of at least one of the other walls, i.e. the sidewall and/or bottom wall of the body.

30 10. Capsule according to any of claims 6 to 9, wherein the flange-like rim comprises at least one lip forming a local increase of thickness protruding from the rim in a direction opposite to the membrane.

11. Capsule according to any of the claims 6 to 10,
wherein the membrane is an aluminium or aluminium alloy
membrane.

5

12. Capsule according to any of the preceding claims 6 to
10, wherein the membrane is made of the same material as
the polymer material of the body.

10 13. Capsule according to any of the preceding claims,
wherein the rim has a thickness between 0.5 and 1.2 mm.

14. System for the preparation of a beverage comprising a
capsule according to any of the preceding claims and a
15 beverage preparation unit wherein the unit comprises a
capsule holder and an enclosing member for receiving the
capsule; said enclosing member comprising an annular
pressing surface (17) comprising radial grooves (15); said
pressing surface being configured for compressing the
20 flange-like rim of the capsule wherein the material of the
flange-like rim is configured during water injection for
clogging the grooves (15) of the pressing surface thereby
providing a liquid-tight engagement between the capsule and
the enclosing member.

25

15. Method for the preparation of a beverage, preferably
coffee, using a capsule according to any of claims 1 to 13
by insertion of the capsule (2) in a beverage preparation
unit (1) comprising a capsule holder (3) and a water
30 injection enclosing member (4); comprising the operations
of:

- inserting the capsule between the capsule holder and
the water injection enclosing member while pressing the

flange-like rim (14) of the capsule against the capsule holder by a grooved pressing surface (17) of the water injection enclosing member,

- injecting hot water under pressure in the volume
5 between the capsule and the water injection enclosing member and in the capsule,

wherein a bypass of water (18) is provided at the beginning of the water injection operation between radial grooves (15) of the said pressing surface (17) and the
10 capsule (2) whereby the water bypass (18) is collected and discharged through a discharge duct (11),

wherein the said water bypass (18) is stopped or reduced when further carrying on the water injection step by softening the polymer material of the flange-like rim
15 (14) of the capsule under the effect of the injected hot liquid, and

wherein liquid extract is forced to flow from the interior of the capsule through the beverage delivery wall, and apertures (8) of the capsule holder to the discharge
20 duct (11).

25

30