

SPECIFICATION

ELECTRICAL CONNECTOR FOR FLAT CIRCUITRY

Field of the Invention

5 This invention generally relates to the art of electrical connectors and, particularly, to connectors for electrically interconnecting flat electrical circuitry such as flat flexible circuitry.

Background of the Invention

10 A flat flexible electrical circuit conventionally includes an elongated flat flexible dielectric substrate having laterally spaced strips of conductors on one or both sides thereof. The conductors may be covered with a thin, flexible protective layer on one or both sides of the circuit. If protective layers are used, cutouts are formed
15 therein to expose the underlying conductors at desired contact locations where the conductors are to engage the conductors of a complementary mating connecting device which may be a second flat flexible circuit, a printed circuit board or the terminals of a mating connector.

20 A wide variety of zero insertion force electrical connectors have been designed particularly adapted for terminating flat circuits, such as flat flexible circuits, flexible printed circuit boards and the like. These electrical connectors conventionally have a housing
25 mounting a plurality of terminals in a generally parallel array spaced along an elongated opening or slot for receiving an end of the flat circuit. Typically, these connectors use actuators to push the flat circuits, flexible printed circuit boards or the like against
30 resilient contact portions of the terminals.

The actuators of these flat circuit connectors typically are movable between a first position allowing free insertion of the flat circuit into the elongated




opening or slot in the housing, and a second position wherein a pressure plate portion of the actuator biases the circuit against the contact portions of the terminals. For instance, the pressure plate biases the exposed conductors of a flat circuit against the contact portions of the terminals.

Major problems continue to plague such connectors, particularly in the areas of cost, size, operability and reliability. With the ever-increasing miniaturization of electronic circuitry, it has become desirable to provide connectors for flat circuits as thin as possible. It is desirable to provide some form of temporary holding means on the connectors for preliminarily holding the flat circuit. It also is desirable to provide some sort of means to hold the actuator in one or both of its positions on the connector housing. Providing these features or means are difficult with extremely small or miniaturized connectors. The present invention is directed to solving one or more of these problems and satisfying such needs.

Summary of the Invention

An object, therefore, of the invention is to provide a new and improved electrical connector for receiving a flat electrical circuit.

In the exemplary embodiment of the invention, the connector includes an elongated dielectric housing defining a slot for receiving the flat electrical circuit. A plurality of terminals are mounted on the housing, with contact portions spaced along the slot. A metal actuator is mounted on the housing and includes a pressure plate portion for biasing the flat electrical circuit against the contact portions of the terminals. A flexible elongated strip portion is spaced forwardly of the pressure plate portion and extends longitudinally of the housing to define a preliminary circuit holding means at a mouth of the slot.



The pressure plate portion is separated from the elongated strip portion at opposite ends thereof by open areas to, thereby, isolate the flexibility of the elongated strip portion from that of the pressure plate portion.

5 As disclosed herein, the open areas between the pressure plate portion and the elongated strip portion are formed by elongated slots extending transverse to the longitudinal direction of the elongated strip portion. The flexible pressure plate portion comprises a plurality of
10 flexible fingers. Each finger has a width to cover on the order of two contact portions of two terminals.

 The elongated strip portion in the preferred embodiment is formed by a cross portion between a pair of legs of a U-shaped section of the metal actuator. The rear
15 ends of the legs are joined to a rear area of the pressure plate portion of the actuator. The pressure plate portion projects forwardly into the U-shaped section and is separated from the legs by the aforementioned opened areas. The elongated strip portion is flexible enough to allow for
20 the easy insertion of the flat circuitry while preventing easy withdrawal until the actuator is moved to its final holding position.

 Other objects, features and advantages of the invention will be apparent from the following detailed
25 description taken in connection with the accompanying drawings.

This Sheet Has Been Replaced



Brief Description of the Drawings

The features of this invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements in the figures and in which:

FIGURE 1 is a top plan view of a flat circuit connector according to a first embodiment;

FIGURE 2 is an enlarged vertical section taken generally along line 2-2 of Figure 1;

FIGURE 3 is a front elevational view of the connector of Figure 1;

FIGURE 4 is a bottom plan view of the connector of Figure 1;

FIGURE 5 is a view similar to that of Figure 2, with the connector temporarily holding the flat circuit;

FIGURE 6 is a view similar to that of Figure 5, with the actuator moved to complete the termination of the flat circuit;

FIGURE 7 is an enlarged end elevational view, looking toward the right-hand end of Figure 1;

FIGURE 8 is a perspective view of a connector for a flat circuit according to a second embodiment;

FIGURE 9 is an enlarged vertical section taken generally along lines 9-9 of Figure 8, with the connector terminating a flat circuit;

FIGURE 10 is a bottom plan view of the connector of Figure 8;

FIGURE 11 is a front elevational view of the connector of Figure 8;

FIGURE 12 is an end elevational view of the connector of Figure 8, with the actuator shown in phantom in its preliminary position;



FIGURE 13 is a top perspective view of the connector of Figure 8, with the actuator removed;

FIGURE 14 is a bottom perspective view of the connector of Figure 8, with the actuator removed;

5 FIGURE 15 is a top plan view of the actuator of the connector of Figure 8;

FIGURE 16 is a front elevational view of the actuator;

10 FIGURE 17 is an end elevational view of the actuator;

FIGURE 18 is a vertical section taken generally along line 18-18 of Figure 15;

15 FIGURE 19 is a view similar to that of Figure 9, with the actuator in its first position and the flat circuit removed; and

FIGURE 20 is a view similar to that of Figure 18, but of an alternate embodiment of the actuator.

This Sheet Has Been Replaced



Detailed Description of the Preferred Embodiments

Referring to the drawings in greater detail, Figures 1-7 show a first embodiment of an electrical connector, generally designated 1, for receiving or terminating a flat electrical circuit, such as a flat flexible circuit, a printed circuit board or the like. Figures 8-20 show a second embodiment of an electrical connector, generally designated 41, also for receiving or terminating a flat electrical circuit.

Turning first to Figures 1-7, connector 1 includes an elongated dielectric housing 3 mounting a plurality of terminals 2 mounted on the housing in a parallel arrangement at regularly spaced intervals longitudinally of the housing. A generally U-shaped actuator, generally designated 4, is mounted on the housing for movement between a first position allowing free insertion of a flat electrical circuit into the connector and a second position biasing the circuit against the terminals, as will be seen hereinafter. A metal fixing member 5 is insert-molded in housing 3 at each opposite end thereof.

As best seen in Figures 2 and 5, each terminal 2 is stamped and formed from sheet metal material and includes a contact portion 6 having a raised contact projection 6a intermediate its opposite ends. The contact portion is joined to a horizontal solder tail 7 by an integral oblique joint section 8. The terminals are insert-molded in housing 3 so that the opposite ends of contact portion 6 are overmolded by the housing. Therefore, at least the opposite ends of the contact portion are rigid or fixed against movement relative to the housing. In most prior art connectors for flat circuits, the contact portions of the terminals are cantilevered and flexible. Therefore, the connector housings must be enlarged or made thicker to accommodate the flexing movement of the contact portions. With the entire contact



portion or the opposite ends of the terminals fixed against movement relative to the housing the movement of the contact portion relative to the housing is eliminated or greatly reduced allowing for a thinner housing. By
5 providing an actuator, as described in detail below, having portions located above and below the contact portion, the portion of the housing under the terminal contact portion may be thin and somewhat flexible and still will be able to provide the force needed to make a good electrical
10 engagement between the contact portion and a conductor on the flat circuit 30.

Elongated dielectric housing 3 is a one-piece structure unitarily molded of plastic material or the like. Therefore, the housing can be overmolded about portions of
15 terminals 2 and fixing members 5 by an appropriate insert-molding process. The housing has a generally rectangular plate-like configuration defining a slot 9 at the top/front thereof for receiving a flat circuit 30. The housing has a relatively thick rear section 10 which facilitates
20 mounting actuator 4 thereon. Contact portions 6 of the terminals are generally flush with a floor 9a of slot 9, and solder tails 7 of the terminals extend forwardly along a bottom surface 3b of the housing and project slightly forwardly of the front of the housing as seen best in
25 Figures 2 and 5. Contact portions 6 and oblique joint sections 8 of terminals 2 are embedded in housing 3, with the upper surfaces of contact portions 6 exposed in floor 9a of slot 9, and with contact projections 6a projecting into the slot.

30 Dielectric housing 3 also has upper guide walls 11 extending the width of the housing at opposite ends thereof and projecting upwardly from a top surface 3a of the housing. Bottom guide walls 13 extend the width of the housing at opposite ends thereof and project downwardly
35 from bottom surface 3b of the housing and define a longitudinal recess 18 within which actuator 4 is slidably



mounted. As best seen in Figure 4, the housing has a plurality of guide ribs 19 which project into a corresponding plurality of guide grooves or notches 19a in the actuator.

5 Each fixing member 5 is stamped and formed of sheet metal material and includes a plurality of plate portions 5a. Portions of the fixing members are overmolded by housing 3, and plate portions 5a are exposed for connection, as by soldering, to appropriate mounting pads
10 on a printed circuit board. Therefore, fixing members 5 function to mount the housing and, thereby, the connector to the printed circuit board. The bottom surfaces of plate portions 5a are coplanar with the bottom surfaces of solder
15 tails 7 of terminals 2 as seen in Figures 2, 5 and 6. The plate portions of the fixing members and the solder tails of the terminals can be soldered simultaneously to the printed circuit board.

As seen in Figure 1, each fixing member 5 has a latch tab 20 which projects into a recess 21 in the top of
20 housing 3. The latch tabs have upwardly projecting stops 20a. As best seen in Figure 4, each fixing member 5 has first and second stop shoulders 5b and 5c, respectively, projecting from the bottom of the housing.


Actuator 4 is stamped and formed of sheet metal
25 material, such as stainless steel or the like, into a generally U-shaped configuration to define a top plate 4a and a bottom plate 4b. A preliminary circuit holding strip 22 is disposed forwardly of top plate 4a. Preliminary holding strip 22 forms a cross portion between a pair of
30 legs 23 of a U-shaped section of metal actuator 4. The rear ends of legs 23 are joined, as at 24, to a rear area of top plate 4a. In essence, top plate 4a forms a pressure plate portion of actuator 4 and includes a plurality of forwardly projecting fingers 25 separated by slots 26. The
35 fingers are used to bias flat circuit 30 against contact projections 6a of terminals 7, as will be seen hereinafter.



Each finger has a width to cover the contact projections of an adjacent pair of terminals. By separating the fingers by slots 26, any dirt that might accumulate on the contact projections can be swept to the side into the slots during use. Finally in referring to Figure 1, a latch tab 27 is formed at each front corner of preliminary holding strip 22. The preliminary holding strip is of a double-thickness by folding the metal material of the actuator back onto itself as seen in Figures 2, 5 and 6.

Referring to Figure 4, a flexible latch arm 28 is provided at each end of actuator 4 at the bottom thereof. Each latch arm terminates in an outwardly projecting latch hook 28a.

Metal actuator 4 is movable on housing 3 from a first position shown in Figures 2 and 5 to a second position shown in Figure 6. In the first position, flat circuit 30 is free to be inserted into slot 9 of the housing. In the second position, fingers 25 of the actuator bias the circuit against the contact portions of terminals 2. When the actuator is in its first position, latch hooks 28a of latch arms 28 seat behind first stop shoulders 5b of fixing members 5 as seen in Figure 4. When the actuator is moved from its first position (Figs. 2 and 5) to its second position (Fig. 6), latch hooks 28a (Fig. 4) are biased inwardly by oblique surfaces 5d of fixing members 5 until the latch hooks snap back outwardly into engagement behind second stop shoulders 5c of the fixing members. This holds the actuator in its final circuit-terminating position. In addition, referring back to Figure 1, latch tabs 27 at the top of the actuator and at opposite ends of preliminary holding strip 22 slide under stops 20a of latch tabs 20 of the fixing members when the actuator is moved to its final circuit-terminating position locking the preliminary holding strip against the flat circuit 30 further helping to hold the flat circuit in the connector housing. Therefore, metal-to-metal engagements



are provided at both the top and bottom of the connector between the metal actuator and the metal fixing members.

5 In connecting or terminating flat circuit 30 to connector 1, the circuit is inserted into slot 9 of housing 3 with actuator 4 in its first position as shown in Figure 2. The circuit is inserted freely and rotated downwardly in the direction of arrow 31 until a front end 30a of the circuit is fully inserted into slot 9 as shown in Figure 5. In this position, and with actuator 4 still in its first or inoperative position, preliminary holding strip 22 temporarily holds the circuit as seen in Figure 5. The actuator then is pushed forwardly in the direction of arrow "A" (Fig. 6) until pressure fingers 25 of top plate or pressure plate 4a of the housing biases the flat circuit against contact projections 6a of contact portions 6 of terminals 2. Legs 23 which are connected to preliminary holding strip 22 are separated from pressure fingers 25 and pressure plate 4a by open areas or elongated slots 29. Consequently, the flexibility of preliminary holding strip 22 is totally independent or isolated from the flexibility of fingers 25. If desired, the temporary holding forces of preliminary holding strip 22 can be made less than the connecting forces provided by fingers 25. Therefore, the preliminary holding strip can be raised easily by the flat circuit which may be a very small flexible circuit, while fingers 25 apply a stronger connecting force of the circuit against the contact projections of the terminals. When it is desired to remove the circuit from the connector, actuator 4 simply is pulled back rearwardly opposite the direction of arrow "A" (Fig. 6) to its first or inoperative position shown in Figures 2 and 5.

Referring to the second embodiment of Figures 8-19, connector 41 includes a plurality of terminals 42 for connection to a flat circuit 43, the terminals being insert-molded in a housing 44. Like the first embodiment, the housing is a generally rectangular plate-like



structure. A generally U-shaped actuator 45 is mounted on the housing for movement between a first position shown in Figure 19 allowing free insertion of flat circuit 43 into a slot 46 of the housing and a second position biasing the
5 circuit against contact portions of the terminals.

More particularly, as best seen in Figures 9 and 19, each terminal 42 has an intermediate section 42a overmolded by housing 44, leaving a contact portion 47 and a solder tail portion 48 exposed outside the housing. The
10 contact portion is cantilevered into an opening 44c in housing 44, with a contact projection 47a at a distal end of the contact portion projecting into slot 46.

As best seen in the top perspective view of Figure 13, housing 44 has a lateral shelf 50 adjacent the
15 free ends of contact portions 47 of the terminals. The housing has a flat U-shaped stepped surface 51 recessed from a top surface 44a of the housing equal to the thickness of a top plate 45A of actuator 45 so that the top of the actuator is substantially flush with top surface 44a
20 of the housing. A flat surface 51a defines the bottom of a mouth 52 (Fig. 9) for receiving flat circuit 43 inserted into slot 46. Surface 51a is substantially at the same level as shelf 50. Guide walls 53 are formed at opposite ends of stepped surface 51, and stop walls 54 are formed at
25 opposite ends of the circuit-receiving mouth.

Referring to the bottom perspective view of Figure 14, housing 14 further has a flattened, U-shaped stepped surface 55 recessed inwardly of a bottom surface
30 44b of the housing. Stepped surface 55 is recessed from bottom surface 44b a distance substantially equal to the thickness of a bottom plate 45b of actuator 45 so that the bottom surface of the actuator is substantially flush with the bottom surface of the housing. Stop walls 56 and inclined latch projections 57 also are formed on the bottom
35 of the housing.

This Sheet Has Been Replaced



As seen in both Figures 13 and 14, a pair of fixing members 49 are insert molded in opposite ends of housing 44 and include exposed tab portions 49a for solder connection to appropriate mounting pads on a printed circuit board.

Referring to Figures 15-18, actuator 45 is stamped and formed of sheet metal material, such as aluminum or the like. At least the areas of the actuator which engage contact portions 47 of terminals 42 are coated with a dielectric material 58 (Fig. 9), such as an insulating resin. For simplicity purposes, the entire sheet metal material of the actuator can be coated with the insulating material.

Actuator 45 is formed in a generally U-shaped configuration to define top plate 45a and bottom plate 45b. The top plate has notched corners 59 at the front thereof to abut stop walls 54 (Fig. 13) on the top of housing 44. A preliminary holding strip 67, similar to preliminary holding strip 22 of the first embodiment, extends between notched corners 59. The preliminary holding strip is disposed above surface 51a (Fig. 13) to define a mouth therebetween for receiving the flat circuit. The preliminary holding strip forms a cross portion between a pair of legs 67a of a U-shaped section of the metal actuator. The rear ends of legs 67a are joined to a rear area of top plate 45a of the actuator. A pair of pressure-applying fingers 62, separated by a slot 61, project forwardly into the U-shaped section and are separated from legs 67a by open areas 60. Therefore, like the first embodiment, the flexibility of preliminary holding strip 67 is independent of or isolated from the flexibility of fingers 62. As best seen in Figure 17, the free ends 62a of fingers 62 are inclined downwardly or inwardly.

Bottom plate 45b of actuator 45 is generally flat and has rectangular projections 63 at the front corners thereof. These projections are captured between stop walls



56 (Fig. 14) and inclined latch projections 57 of the housing when the actuator is mounted on the housing. This can be seen best in Figure 12 and allows for movement of the actuator between its inoperative and operative positions.

5 In operation of the second embodiment, U-shaped actuator 45 is mounted about the rear of housing 44 as best seen in Figure 19, with the actuator in a first position as shown therein. In this position, flat circuit 43 can be
10 inserted freely into slot 64 of the housing. The actuator then is moved forwardly in the direction of arrow "B" (Fig. 9) to a second position whereat fingers 62 bias a free end 43a of flat circuit 43 against contact projections 47a of
15 contact portions 47 of terminals 42. At the same time, bottom plate 45b of the actuator abuts against the bottoms of contact portions 47 of the terminals, as at 70. With the actuator coated with insulating material, the bottom plate does not short the terminals. Therefore, it can be
20 seen that actuator 45 performs dual functions of (1) biasing flat circuit 43 against the contact portions of the terminals and (2) also providing reinforcing support for the contact portions. In addition, preliminary holding strip 67 provides a means for temporarily holding the flat
25 circuit while an operator manually manipulates the actuator. When the actuator is in its final or second position, notched corners 59 (Fig. 15) of the actuator engage stop walls 54 (Fig. 13) of the housing, as seen in Figure 8.

30 By fixing contact portions 6 of terminals 7 in the first embodiment, and by reinforcing contact portions 47 of terminals 42 in the second embodiment, the overall profile of the connectors can be made thinner because the flexibility required to maintain a positive contact between the flat circuit and the terminals is provided by the
35 pressure plate portions or fingers of the actuators.



5 Lastly, Figure 20 shows an alternate embodiment
of an actuator 45 which does not include a separated
preliminary holding strip. In this embodiment, bulged
areas 65 have downwardly formed projections 65a which
10 oppose contact projections 47a of contact portions 47 of
terminals 42 when the actuator is moved to its connecting
or terminating position. Projections 65a of the actuator
bias the flat circuit against projections 47a of the
terminals. Nevertheless, this actuator also performs the
15 dual functions of biasing the circuit against the contact
portions of the terminals and also providing reinforcing
support for the contact portions.

It will be understood that the invention may be
embodied in other specific forms without departing from the
15 spirit or central characteristics thereof. The present
examples and embodiments, therefore, are to be considered
in all respects as illustrative and not restrictive, and
the invention is not to be limited to the details given
herein.

This Sheet Has Been Replaced





CLAIMS

1. An electrical connector (1,41) for receiving a flat electrical circuit (30,43), comprising:
- 5 an elongated dielectric housing (3,44) defining a slot (9,46) for receiving the flat electrical circuit;
- a plurality of terminals (2,42) mounted on the housing with contact portions (6,47) spaced along the slot; and
- 10 a metal actuator (4,45) mounted on the housing and including a pressure plate portion (25,62) for biasing the flat electrical circuit against the contact portions of the terminals, a flexible elongated strip portion (22,67) spaced forwardly of the pressure plate portion and extending longitudinally of the housing to define a
- 15 preliminary flat circuit holding means at a mouth of the slot, and the pressure plate portion (25,62) being separated from the elongated strip portion (22,67) at opposite ends thereof by open areas (29,60) to, thereby, isolate the flexibility of the elongated strip portion from
- 20 that of the pressure plate portion.
2. The electrical connector of claim 1 wherein said open areas comprise elongated slots (29,60) extending transverse to the longitudinal direction of the elongated strip portion (22,67).
- 25 3. The electrical connector of claim 1 wherein said flexible plate portion of the actuator (4,45) comprises a plurality of flexible fingers (25,62).

This Sheet Has Been Replaced





Patent
99-001 SG

4. The electrical connector of claim 3 wherein each of said flexible fingers (25) has a width to cover on the order of two contact portions (6) of two terminals (2).

5 5. The electrical connector of claim 1 wherein
said elongated strip portion (22,67) comprises a cross
portion between a pair of legs (23,67a) of a U-shaped
section of the metal actuator (4,45), with rear ends of the
legs being joined to a rear area of the pressure plate
portion (25,62) of the actuator, the pressure plate portion
10 projecting forwardly into the U-shaped section and being
separated from the legs by said open areas (29,60).

15 6. The electrical connector of claim 1 including
complementary interengaging locking means (27,20) between
a metal fixing member (5) mounted on the housing for
securing the connector to an appropriate mounting pad on a
printed circuit board and the metal actuator (4) to lock
the elongated strip portion (22) against the flat
electrical circuit.

This Sheet Has Been Replaced





7. An electrical connector (1,41) for receiving a flat electrical circuit (30,43), comprising:

an elongated dielectric housing (3,44) defining a slot (9,46) for receiving the flat electrical circuit;

5 a plurality of terminals (2,42) mounted on the housing with contact portions (6,47) spaced along the slot; and

a metal actuator (4,45) mounted on the housing and including a pressure plate portion (4a,45a) having a plurality of flexible fingers (25,62) for biasing the flat electrical circuit against the contact portions of the terminals, the actuator including a U-shaped section defining an elongated flexible strip portion (22,67) extending between a pair of legs (23,67a) of the U-shaped configuration, the rear ends of the legs being joined to a rear area of the pressure plate portion (25,62), the flexible fingers (25,62) projecting forwardly into the U-shaped section and being separated from the legs by open areas (29,60), and the elongated flexible strip portion (22,67) being spaced forwardly from the flexible fingers (25,62) to define a preliminary flat circuit holding means at a mouth of the slot, with said open areas (29,60) being effective to isolate the flexibility of the elongated strip portion from that of the flexible fingers.

25 8. The electrical connector of claim 7 wherein each of said flexible fingers (25) has a width to cover on the order of two contact portions (6) of two terminals (2).

This Sheet Has Been Replaced





9. An electrical connector (1,41) for receiving a flat electrical circuit (30,43), comprising:

an elongated dielectric housing (3,44) defining a slot (9,46) for receiving the flat electrical circuit;

5 a plurality of terminals (2,42) mounted on the housing with contact portions (6,47) spaced along the slot; and

10 a metal actuator (4,45) mounted on the housing for movement between a first position allowing free insertion of the flat electrical circuit (30,43) into the slot (9,46) and a second position wherein a pressure plate portion (25,62) of the actuator biases the circuit against the resilient contact portions (6,47) of the terminals (2,42), the actuator including a flexible elongated strip portion (22,67) spaced forwardly of the pressure plate portion and extending longitudinally of the housing to define a preliminary flat circuit holding means at a mouth of the slot, and the pressure plate portion (25,62) being separated from the elongated strip portion (22,67) at
15 opposite ends thereof by open areas (29,60) to, thereby, isolate the flexibility of the elongated strip portion from that of the pressure plate portion.

10. The electrical connector of claim 9 wherein said open areas comprise elongated slots (29,60) extending transverse to the longitudinal direction of the elongated strip portion (22,67).
25

11. The electrical connector of claim 9 wherein said flexible plate portion of the actuator (4,45) comprises a plurality of flexible fingers (25,62).

This Sheet Has Been Replaced





Patent
99-001 SG

12. The electrical connector of claim 11 wherein each of said flexible fingers (25) has a width to cover on the order of two contact portions (6) of two terminals (2).

5 13. The electrical connector of claim 10 wherein said elongated strip portion (22,67) comprises a cross portion between a pair of legs (23,67a) of a U-shaped section of the metal actuator (4,45), with rear ends of the legs being joined to a rear area of the pressure plate portion (25,62) of the actuator, the pressure plate portion
10 projecting forwardly into the U-shaped section and being separated from the legs by said open areas (29,60).

14. The electrical connector of claim 9 including complementary interengaging locking means (27,20) between a metal fixing member (5) mounted on the housing
15 for securing the connector to an appropriate mounting pad on a printed circuit board and the metal actuator (4) to lock the elongated strip portion (22) against the flat electrical circuit.

This Sheet Has Been Replaced

