



159159

1

Device for delivering soap solution in a dispenser

The present invention relates to a device according to the preamble of claim 1.

Known soap and foam dispensers (inter alia EP-B1- 0 019 582) have supply bottles for a soap solution (emulsion, dispersion, etc.) which are placed upside down in an intermediate container which maintains a relatively constant level of liquid in the manner of a birds' drinking vessel in order to feed a downstream metering device.

It has been found that during the operation of such a dispenser the intermediate container is contaminated by impurities in the atmosphere and that after more or less long use such a dispenser has a high germ count and therefore, instead of serving to clean hands, it also contaminates them.

The above-mentioned problems represent a great risk owing to the increasing number of infectious diseases, especially in factories and organisations that manufacture and/or distribute foodstuffs, or in the health sector (hospitals, etc.).

It has also been found to be disadvantageous that known dispensers - in the often very limited lighting conditions of wash-rooms - have an inadequate filling-level indicator, so that such dispensers are often without a continuous flow of soap solution which of course also greatly impairs hygiene conditions.

Furthermore, an empty intermediate container is a receiving reservoir for countless germs which remain in the system or



G00002

multiply therein even when a fresh supply container is subsequently inserted.

In addition, the market offers various qualities of soap which, depending on their purpose, are suitable only for specific dispensers and places of use. For example, soap solutions that are used in sectors requiring a high level of hygiene contain anti-bacterial additives and soap solutions that are used in other sectors contain fat-replenishing active substances and/or perfumes. Furthermore, foam dispensers require soap solutions having different physical properties, especially a higher viscosity, from those necessary, for example, in soap dispensers.

In the past, therefore, dispensers were often equipped with unsuitable soap solutions or supply bottles that were intended for other dispensers and/or places of use.

object

The problem of the invention is to remove those disadvantages and to avoid the risks indicated, that is to say, the hygiene conditions in the dispenser are to be improved and the supply containers are not to be confused.

At the same time, indication of the necessity to replace the supply container is to be improved so that a dispenser which is running dry is recognised in good time. The reserve is also to be sufficiently large to prevent any interruption in operation.

object

A further problem is to provide a device which prevents appliances from becoming contaminated before their first use, for example during despatch or storage.

The problem is solved by the features of patent claim 1; claim 1 characterises the operating state.

The device according to the invention prevents the use of unsuitable supply containers, that is to say, such containers cannot even be opened by the dispenser because the piercing sleeve does not project into the region of the diaphragm of a container that does not fit.

The resiliently supported closing plug prevents the penetration of impurities into the intermediate container, on the one hand, before the insertion of a supply bottle and, on the other hand, also when that bottle is exchanged or removed, because the closing plug recloses the inlet to the intermediate container without delay.

In addition, a liquid level having a relatively large surface is established in the intermediate container, as a result of which a very narrow labyrinthine edge opening to the surrounding atmosphere is quite sufficient to obtain the effect of a "birds' drinking vessel".

Developments of the subject-matter of the invention are described in the following dependent claims.

A form of keying according to claim 2 is economical because it can also be produced for a standard bottle in numerous non-confusable variants.

The construction of the keying members in the form of ring segments is favourable from the point of view of production technology.

The form according to claim 4 is space-saving and requires only a small amount of material, that is to say, the closing cover carrying it can be very thin-walled. Furthermore, a raised edge facilitates the insertion of a keyed neck of a bottle.

The use of webs and recesses increases the possible combinations considerably.

Especially in the case of more highly viscous soap solutions, the form according to claim 6 ensures a defined position and a corresponding opening angle of the closing plug.

A labyrinthine air inlet prevents the penetration of germs and lets in only as much air as the amount of liquid removed.

The form of the filling-level indicator according to claim 8 gives very good optical conditions and permits the favourable arrangement thereof at the dispenser housing.

A float can be guided by an upright guide strip in an especially simple and operationally reliable manner.

Lateral guide strips according to claim 10 prevent the float from tilting.

Figure 1 shows a dispenser represented in a simplified manner having an intermediate container for soap solution with an adapter and associated supply bottle,

Figure 2 shows the complete dispenser according to Figure 1 in a partly sectional view and in its functioning state,

Figure 3a shows a push-on member for the neck of the supply container in Figure 1 in plan view,

Figure 3b is a view of the push-on member of Figure 3a in vertical section,

Figure 4a shows the form of a closing member in the dispenser of Figure 1 and Figure 2 in plan view,

Figure 4b shows the closing member of Figure 4a viewed from the side,

Figure 5 shows the form of a float of a filling-level indicator in the dispenser according to Figures 1 and 2,

Figure 6 is an enlarged sectional view of the intermediate container of Figure 1, at the beginning of the fitting of a supply bottle and

Figure 7 is a view analogous to Figure 6 during the fitting of the supply bottle.

In Figure 1, 1 denotes a soap dispenser which has a supply container 2 known per se for a soap solution. A recess 2' which provides space for a system for locking the dispenser is provided in the upper portion of the rear lateral face of the container 2; keying members 4 and 5 are provided on the bottle neck 3 of the supply container 2.

Underneath, and drawn at a distance from the supply bottle 2 for reasons connected with draughtsmanship, is an intermediate soap solution container 6 which is used, likewise in a manner known per se, as a reservoir for the soap solution and permits a smooth exchange of the container 2 without interruptions in operation. The intermediate container 6 has a modular structure and has a closing cover 7 with an adapter 8 which is closed centrally by a resiliently arranged closing plug 50, as long as a supply container 2 has not been fitted.

In order to prevent the use of unsuitable supply containers 2, for example those which contain a special soap solution suitable only for foam dispensers, a keying edge 10 is provided here. The edge 10 acts as a receiving negative with respect to the keying members 4, 5 and is adapted to the members 4 and 5, while maintaining a suitable play, so that the correct supply container 2 can be readily inserted into the adapter 8 and locked. An unsuitable container 2 cannot be used.

The intermediate container 6 also has, on its closing cover 7, clamping and locking members 11 which are used for the insertion and holding thereof in the dispenser housing which is shown here only in simplified form. In order to prevent the intermediate container 6 from rotating, the container also has a lateral guide 12 constructed in the form of a recess. Arranged below the container 6 is a pump support 13 with a spring member 15 which is arranged in one piece thereon and which has a sectional end member which is likewise used for holding in the dispenser housing. The pump support 13 contains a hose pump 18 having an outlet 17 in the form of a rubber lip for the delivery of liquid soap in portions. A projecting upright member 19 in which an

indicator flag for the filling level of the soap solution is held can be seen at the front of the intermediate container 6.

The sectional view of Figure 2 shows the subject-matter according to Figure 1 installed in a soap dispenser 1 for mounting on a wall W. The soap dispenser 1 is secured in a well-known manner with its rear wall 30 against the wall W. At the lower end of the rear wall 30 is an articulation 31 (film hinge) for a hood 20, which is partially illustrated here. A locking cam 33 which is used to close the hood 20 can be seen at the upper end of the rear wall 30. Below the cam are support ribs 32 which are used for the vertical positioning of the supply container 2. A cut-open diaphragm 52 projects upwards in the bottle neck 3 of the container 2 and is held in that position, which allows soap solution to flow through, by the piercing sleeve 9.

It can be seen that a member projecting from the bottle neck 3 holds the hemi-spherical closing plug 50 in the open position shown; soap can therefore flow between the closing plug 50 and its valve seat 51, as a result of which the liquid level illustrated to the right of the bottle neck 3 is maintained and an air space is formed above it which is replenished through an extremely small edge gap between the closing cover 7 and the actual container 6.

In addition, a guide strip 47 on which a float 22 having a short top-side flag 22' slides vertically upwards can be seen in the intermediate container 6. Thus, the illustrated position corresponds to a state with an almost empty intermediate container and contradicts the level of the soap solution.

According to Figure 2 the hose pump 18 which is closed by a flap valve 44, which is a non-return valve, is inserted in the lower base of the intermediate container 6.

An operating lever 24, having an operating ring 23, and the soap outlet 17 project from the hood 20.

Figure 3a and Figure 3b show that the bottle neck 3 is a member fitted to the outlet of the container 2 and is connected to that outlet (not shown) in a positive-locking and liquid-tight manner.

The plan view according to Figure 3a shows the two keying members 4 and 5 having recessed grooves 4' and 5', and a projection 28. The diaphragm 52 described in Figure 2 is located in the centre, but in the closed state.

Figure 3b is a horizontally arranged vertical section through the bottle neck 3 of Figure 3a. It shows the thin-walled dimensioning and a depression 14 which is closed by the diaphragm 52. The height of the projection 28, a centring edge 16 for positioning the container outlet, and a lower recess 27 are also shown.

The recess 27 corresponds to a raised portion (not shown) at the outlet of the container 2, so that a standard supply container, depending on what it has been filled with, can be equipped with corresponding attachments according to Figure 3a and Figure 3b used for identification and keying.

The detailed form of the closing plug 50 with its spring leaf 48 and the mounting pins 49 can be seen in Figure 4a. In conjunction with Figure 4b that Figure shows in the closing plug 50 a notch 53 into which extends the projection

28 which is at the same time used for the parallel guiding of the container 2 during insertion into the adapter 8, see Figure 2.

The form of the float 22 can be seen in Figure 5 which shows a sectional guide member 26 provided with grooves; the actual float body 25 is constructed as a hollow body in known manner.

The operation of fitting a soap-filled supply bottle 2 to the adapter 8 of the closing cover 7 is shown in Figure 6 in an enlarged view.

Figure 7 shows the piercing of the diaphragm 52 in the bottle neck 3, in which position the closing plug 50 still abuts the valve seat 51.

The lower position of the bottle neck 3 corresponds to the operating position and has been described in detail in connection with Figure 2.

The subject-matter of the invention permits a hygienically excellent delivery of soap solutions for metering in a soap or foam dispenser without contaminated atmosphere and/or other influences affecting the quality of the solution and the dispenser.

The device can be manufactured by conventional plastics technology and can be readily integrated in existing dispenser structures.

The exchange of a supply container does not require instructions; either a container fits into a dispenser or the dispenser requires another type of container.

It will be appreciated that the subject-matter of the invention is not restricted to what has been presented; for example, functional members which have been drawn separately can be constructed in one piece, which is advantageous, in particular, in the case of components manufactured in large piece numbers. The keying can be integrated into and/or injection-moulded onto, inter alia, the bottle neck of the supply container.

Patent claims

1. Device for the reliable delivery of soap solution from an inverted supply container into an intermediate container of a dispenser, a bottle-neck-like outlet having a pierceable diaphragm being provided on the container and an adapter having a piercing sleeve being provided on the intermediate container, characterised in that at least one keying member (4, 5) projects from the bottle neck (3) and is positioned in the adapter (8) in an analogously keyed cylindrical surface (10), and in that there is provided, in the region below the piercing sleeve (9), a valve seat (51) on which a resiliently supported closing plug (50) is pushed through the bottle neck (3) into a through-flow position, the tip of the piercing sleeve (9) being supported lower down than the upper edge of the adapter.

2. Device according to claim 1, characterised in that the bottle neck (3) has a push-on member to which at least two keying members (4, 5) are fitted.

3. Device according to claim 1 or 2, characterised in that the keying members (4, 5) are ring segments.

4. Device according to claim 1, characterised in that the keyed cylindrical surface (10) has a raised edge.

5. Device according to claim 4, characterised in that the keyed cylindrical surface (10) has webs and recesses.

6. Device according to claim 1, characterised in that there is provided on the bottle neck (3) and parallel therewith a projection (28) which extends peripherally relative to the piercing sleeve (9) through a closing cover (7) of

the intermediate container (6) and presses on a notch (53) in the closing plug (50) and holds the plug in the through-flow position.

7. Device according to claim 1, characterised in that the closing cover (7) has edge gaps opposite the upper portion of the intermediate container (6), which gaps are in the form of labyrinthine air inlets to the air space (L) in the intermediate container.

8. Device according to claim 1, characterised in that a filling-level indicator having a float (22) is arranged in a projection (19) in the intermediate container (6).

9. Device according to claim 1, characterised in that an upright guide strip (47) on which the float (22) is guided is provided behind a projection (19) in the intermediate container (6).

10. Device according to claims 8 and 9, characterised in that the float (22) has lateral grooves (26) through which guide strips (47) extend.