

- 1 -

AIMING DEVICE AND METHOD FOR GUNS

Field of the invention

This invention relates to devices for aiming hand-held guns, such as pistols and revolvers, and in general fire arms, including short range rifles. The devices of the invention permit particularly quick and accurate aiming of the fire arm and substantially eliminate subjective aiming errors. The invention also comprises a corresponding aiming method.

Background of the invention

Fire arms, particularly hand-held fire arms are conventionally aimed by aligning a front sight with a rear sight and pointing the front sight to the target point. The term "short range", as used herein, includes ranges which are up to about 30 m for pistols and about 50 m for other types of firearms. By "target" is meant the object or person that the shooter intends to hit, and by "target point" is meant the point of the target at which the shooter aims the projectile.

Generally the projectiles may hit any point within an area about the target point, but if the shooting is good, said area will be limited. When the front and the rear sight are aligned, they define a line that will be called "the aim line", and when said aim line passes through the shooter's aiming eye, the axis of the fire arm barrel should be directed to the target point.

The conventional system of aiming involves certain inherent errors: a) the aim line is spaced by a few millimeters from the barrel axis, whereby the point of impact of the projectile, assuming that there are no other errors, will be equally spaced from the point at which the shooter aimed (this may be called "the parallax error"; b) an attempted compensation of the resulting error by structuring the sights so as to slant the aim line slightly

- 2 -

towards to the barrel axis, is effective only if the target is located at the distance at which the aim line and the barrel axis meet, and if it is not, said error will remain and may even be increased; c) the fire arm's sights mask, to some extent, the target; d) gun users that are not too experienced require some time to aim by aligning the two sights; e) the alignment of the sights is not objective and its accuracy depends on the skill of the gun user.

USP 6,604,315 B1 discloses and claims an aiming apparatus which comprises a first and a second lenticular element, orthogonal to one another, both mounted on the barrel of the gun, wherein the first lenticular element receives a first image when the shooter's aiming eye is in proper alignment with said barrel in elevation and a second image when the shooter's aiming eye is not in proper alignment in elevation, and the second lenticular element receives a third image when the shooter's aiming eye is in proper alignment with said barrel in azimuth and a fourth image when the shooter's aiming eye is not in proper alignment in azimuth. The first and third image are of a first matching color, typically green, and second and fourth image are of a second matching color, typically red. Said apparatus is not fully satisfactory, firstly because it comprises two lenticular elements and is therefore somewhat complicated and costly; secondly, because its user has to rely on the accurate perception of colors that may not be quite distinctive to him and anyway are not easy to distinguish in dark or sharply colored environments; and thirdly, because it requires the user to correct the alignment of the gun barrel by moving it in two orthogonal directions, elevation and azimuth, a requirement which slows down the aiming and renders it uncertain, since a correction in elevation may be accompanied by a displacement in azimuth, and vice versa.

- 3 -

Co-pending patent application No. 155993, the contents of which are incorporated herein by reference, describes and claims an aiming device for short range guns, which comprises an aiming sight for directing the aim to the target, mounted on the barrel near its forward end, and an angle indicator, for signaling when the aim line is at a predetermined angle, preferably parallel, to the axis of the gun barrel. The angle indicator, which typically comprises two like elements symmetrically positioned about the aiming sight, comprises one or more figures lying on a plane that makes a given angle to the gun barrel axis and some means for determining when the aim line passing from the gun user's eye and the aiming sight makes said given angle to the plane of said figure, or forms with said plane a predetermined, compensation angle. Typically, said figures lie on a plane perpendicular to the axis of the gun barrel and acquire a distinctive appearance when viewed along an aim line perpendicular to said plane.

The said co-pending application also describes and claims an aiming method for short range guns provided with said aiming device, wherein the gun user firstly brings the tip of the aiming sight in the appropriate position with respect to the target point, which can be called a coarse aiming step, and thereafter completes the aiming by gun to by bringing the aim line to a predetermined angle to the axis of the gun barrel while keeping the aiming sight in the said appropriate position, which can be called a fine aiming step.

Types of images or figures forming part of the angle indicator include figures, preferably colored, and which may be transparent, which look deformed in some way from a basic shape when seen at an angle; images which change according to the angle under which they are seen, e.g. by changing color or showing or hiding predetermined shapes or details; and

- 4 -

composite figures, including at least two parts of different colors, wherein one part is seen as larger and the other as smaller, depending on the angle at which the figure is seen.

While the aiming device of said co-pending application constitutes an important improvement over the prior art, it still comprises two components – the aiming sight and the angle indicator – and requires two aiming steps – a coarse and a fine one. Because of this, on the one hand, the aiming is not as easy and immediate as might be desired, and subjective errors are not completely eliminated.

It is therefore a purpose of this invention to provide an aiming device for guns, particularly, but not exclusively, short range hand-held guns, for instance pistols and revolvers, that is extremely simple and reliable.

It is another purpose to provide such an aiming device which consists of a single structural element.

It is a further purpose to provide such an aiming device which substantially eliminates subjective errors.

It is a still further purpose to provide such an aiming device which does not define nor require two displacements in two directions to render the aiming line parallel to the gun barrel axis.

It is a still further purpose to provide an aiming method which permits very accurate aiming with extreme rapidity.

It is a still further purpose to provide an aiming method which is completed in a single step.

- 5 -

It is a still further purpose to provide an aiming method which does not require to establish an optical correlation between different structural element, but only requires the observation of a single element.

Other purposes and advantages of the invention will appear as the description proceeds.

Summary of the Invention

The present invention is directed to an aiming device for guns, such as firearms, toy guns, PaintBall guns and any gun that is intended to shoot a real, dummy or virtual projectile of any shape to a target.

The aiming device comprises transparent plate, which shows to person aiming the gun (hereinafter, "the user" or "the shooter") an image that has a critical optical appearance (hereinafter, "the critical image") when a plane associated with said plate has a predetermined orientation, and shows a different image (hereinafter, "the deformed image") when said plate has any other different orientation; wherein said transparent plate is so mounted in said indicator and said indicator is so mounted on the gun to be aimed that said critical image is seen by the user when and only when the axis of the gun barrel is parallel to the line of sight passing through the user's eye and the center of said transparent plate.

The term "plate", as used herein, does not necessarily mean a planar element. The plate may be curved, and the "plane associated with said plate" may be defined in any way, e.g. may be the plane tangent to the center of the plate or the plane on which lies the periphery of the plate. Hereinafter, for brevity's sake, the plate will be assumed to be planar, but no limitation is intended by this, and what is said about the plate will be

- 6 -

applicable, if said plate is not planar, to said plane associated with said plate. In the following description and claims, the term "plate" will be used, for brevity's sake, to include, where appropriate, the plane associated with the plate.

The aiming device will generally comprise, in addition to the transparent plate, a support for said plate, through which the plate is mounted on the gun with the appropriate orientation. The transparent plate, whether planar or not, is preferably, though not necessarily, circular, and in that case, said support is ring-like or comprises a ring-like frame portion.

Preferably, the structure of the plate support, the way in which the plate is mounted therein, and the way in which said support is mounted on the gun, generally but not necessarily on the gun barrel, are such the plate is perpendicular to the axis of the gun barrel, and the image shown by the plate to the user is the critical image when the line of sight from the user's eye to said image is perpendicular to said plate. Therefore, when the user sees the critical image, he knows that the gun barrel is parallel to his line of sight, and if his line of sight passes through the target point, the gun is properly aimed.

The aiming method, when the aiming device of the invention is used, is a single step one. The user points the gun in such a way that he sees the critical image and the target point at the center of the transparent plate. In preferred embodiments, the critical image covers the entire surface of the transparent plate, and therefore the center of the transparent plate is also the center of the critical image. Since both the plate and the image are small, having, if circular, a diameter from 3 to 10 mm and preferably from 4 to 6 mm, accurately placing the target point at their center is very easy. Of course, it is also possible to mark the center of the plate by an insert, or

- 7 -

by a preferably black dot, or by other marks examples of which will be given hereinafter.

The invention, therefore, also includes an aiming method which consists in generating the critical image and bringing the target point to the center of said image.

Examples of colored materials that can be used in the transparent plate of the invention are, for instance: phosphorus materials, fluorescent materials organic or biological luminous materials (such as luminous materials produced by insects, e.g., fireflies, by underwater creatures, or by plants), radioactive luminous materials, e.g., Tritium (see USP 5,359,800, USP 5,065,519, and night sights made by Trijicon Inc., Farmington Hills, Mich., U.S.A.), and lenticular indicia sets (described, for example, in "Lenticular Imaging, Part I", Screen Graphics, Sep/Oct 1999, pp 37-42 and in "Lenticular Imaging, Part II", Screen Graphics, Jan/Feb 2000, pp 30-35, in "Lenticular Imaging, Part III", Screen Graphics, Mar/Apr 2000, pp 30-36). It should be understood, however, that in the broad definition of the invention, are comprised the passage of the image shown by the transparent plate from a colorless to a colored condition or vice versa, and therefore, in this invention, the term "color" may comprise the colorless state.

Brief description of the drawings

Figs. 1A and 1B schematically illustrate the conventional aiming devices and procedure;

Figs. 2A is a schematic perspective illustration of an embodiment of the invention in the aiming of a gun shown as a pistol, but which may be a revolver, a rifle or any other gun; and Figs. 2B and 2C are vertical views

- 8 -

from the rear of the transparent plate of said gun, wherein in Fig. 2B the gun is properly aimed and in Fig. 2C the gun is not properly aimed; and Figs. 3A to 3D show various different embodiments of the transparent plate according to embodiments of the invention.

Detailed Description of Preferred Embodiments

Fig. 1 schematically shows in perspective view a conventional prior art aiming device and method. A hand-held gun 10 is represented as a pistol. Numeral 18 generally indicates the eye of the gun user. It is well known that even if a shooter aims with both eyes, his brain selects one eye as the aiming one and therefore it is permitted in this description to refer to the shooter's eye in singular. The aiming device comprises a front sight 11 and a rear sight 12. Numeral 16 symbolically indicates a target, wherein 14 is the target point. The aim line of sight 15 passes from the shooter's eye 18 through sights 11 and 12, and, when the gun is aimed, impacts on the target point 14. Actually, as has been said, an experienced shooter will correct for the distance between the line passing through sights 11 and 12 and the gun barrel axis, and therefore he will so aim that the aim line 15 impacts the target slightly above the target point 14. Of course, the actual trajectory of the projectile curves downwards, because of the gravity effect, and therefore, if the resulting deviation of the projectile from the aim line 15 is significant, an experienced shooter will know it and will correct for it, this correction being sometimes more substantial than that required by the distance between the aim line and the gun barrel axis. This correction is illustrated in Fig. 1B.

In both of the prior art cases of Fig. 1A and Fig. 1B, the physical arrangement of the front and rear sights is familiar to all skilled persons and need not be described. In general, the rear sight is fork-shaped and the front sight is brought, when aiming, to the central part of the fork and

- 9 -

ideally in the middle, for lateral aiming, and at the same height as the rear sight, for vertical aiming.

Figs. 2A to 2C illustrate a first embodiment of the invention. The target is again indicated at 16, the target point at 14, and the gun user's aiming eye at 18, as they will be in the following figures. The gun is illustrated as a pistol 30, but this embodiment of the invention, like all embodiments of the invention, is equally applicable to all kinds of, particularly but not exclusively short range hand-held guns, including in particular short-range rifles. Gun 30 is provided with an aiming device 31. No rear sight is provided.

A preferred embodiment of the aiming device is shown in Fig. 2B, in which said device is shown as the user sees it when correctly aiming the gun, viz. is seen in vertical view from the rear. Numeral 32 indicates a transparent plate, which in this embodiment is planar and round. The plate is seen as colored and to represent this it is shown as gray in the drawing, but in reality it may have any chosen color, for instance red or blue, said color being preferably pale not to interfere with a clear view of the target. 33 is the target point, and it is seen at the center of the transparent plate. 34 indicates a support in which plate 32 is mounted, which support or frame is mounted on the gun barrel, of which only a broken off portion 35 is shown in the drawings. The support 34 in this embodiment comprises a round central frame 36 and is so structured that it holds the plate 32 perpendicular to the gun barrel axis. Therefore in the position shown in Fig. 2B the gun barrel axis is parallel to the line of sight from the user's eye to the target point.

The aiming device 31 is shown in Fig. 2C as it appears to the user when the gun is not correctly aimed. It is seen that colored shape 37, which may

- 10 -

be called the "deformed shape", which has the same color as in Fig. 2B and is equally shown in the drawing as gray, does not occupy the whole round area of transparent plate 32 but only a portion of it, and therefore the gun barrel axis is not parallel to the line of sight from the user's eye to the target point and the gun is not correctly aimed. The user will shift the gun until the situation of Fig. 2B is produced.

The deformed shape is shown in Fig. 2C as being oval and set at one side of the transparent plate. However, this is only an example and the deformed shape may have any form and size, and be set at any zone of the transparent plate, as long as it is easily, and preferably immediately, recognizable by the user. Generally, it would be sufficient, to render it recognizable, that it should cover only a part of the transparent plate as seen, for example, in Fig. 2C. Any deformed shape, therefore, is included in this invention.

In Figs. 2B and 2C the user judges when the target point is seen at the center of the transparent plate. This is easy, since said plate has a small size. However, it is possible within the scope of the invention to mark precisely or approximately the center of the plate. Figs. 3A to D, which are vertical views like Figs. 2B and 2C, show various ways of marking said center.

In Fig. 3A the center 40 of the transparent plate is indicated by a mark, which in this example is a dot, generally as black dot. In Fig. 3B a figure 41, similar to a conventional front sight, indicates said center by its tip 42. In Fig. 3C two arrows 43-44 are aligned with said center and leave only a small space between them, said center being located in said small space. In Fig. 3D a very small circle 45 is marked, the center 40 of the transparent plate being the center of said circle. Other ways to facilitate the

- 11 -

identification of the center of the transparent plate can easily be devised by skilled persons.

It will be apparent that, while the transparent plates that have been illustrated are planar and round, this is not necessary. Other structures of transparent plates could be adopted in all embodiments of the invention, but they should always be such that it will be readily apparent when the images which they show are seen properly and when they are seen deformed. Particularly, the deformation may consist in the disappearance or appearance of images or of portions of images. Thus, in the examples described the transparent plate appears wholly and equally colored when the line of sight from the user's eye to the target point is parallel to the gun barrel axis, and only partly colored when said line of sight is not so parallel, but the opposite could be true, viz. a total or partial coloration might be generally seen by the user and disappear only when the line of sight from the user's eye to the target point is parallel to the gun barrel axis. Further, the deformation of the images seen by the user looking at the transparent plate could consist in partial or total changes of color. Generally, whatever such deformation, it is sufficient that it should be easily, and preferably immediately, recognizable by the user. The optical art provides many possibilities and varieties of such changes, and all of them are comprised in the scope of the invention. For instance, means are known for printing figures which change their color or their apparent shape, or show or hide various geometrical figures, or become translucent, or show a network of lines, and so on. Any one of these optical means can be used in carrying out the invention. It should be understood that the term "image", as used herein, does not imply figures having a meaning or representing definite objects, but includes any shape of any kind whatsoever, including meaningless and convoluted shapes. Various kinds, shapes and sizes of support could also be used. For example, the element

- 12 -

that is shown as a circular frame 36 in Fig. 2B could be cylindrical and of significant length to exclude any optical interference from the outside with the transparent plate, or, on the contrary, could be very thin and even reduced to a small number of circumferential points. It might also be such as to permit the substitution of the transparent plate, since different transparent plates might be preferable under different environmental conditions, or the plate might become damaged and have to be replaced.

The transparent plate may also be implemented as a combination of an air layer and a circular object, e.g., a dye layer. Such combination can be inserted into a narrow through bore, formed in the support, so that anyone looking through it will only see an object that is comprised in a small area around the axis of the bore. In a preferred embodiment, the bore may be circular and the object which is to be seen through it be also circular and with the same diameter as the bore. The relation between the bore depth and the bore diameter determines the sharpness of the transition from a desired orientation with no deformation of the critical image to an undesired orientation with a deformed image.

In order to allow the shooter seeing the image clearly, the dye layer may be an illuminating layer (e.g., a phosphorous material), having a distal wall that is sufficiently immersed in the bore, such that said distal wall is actually the distal wall of the support and is exposed to ambient light when the shooter aims the firearm. During the short time period until shooting, the illuminating layer absorbs ambient light and the dye layer can be well seen by the shooter, both during daytime and nighttime. More illumination toward the shooter's eye can be obtained by using a bore with reflecting walls.

- 13 -

The dye layer may also be self illuminating, by using, for example, electric light source or Tritium.

While embodiments of the invention have been described by way of illustration, it will be apparent that the invention can be carried into practice by persons skilled in the art with many modifications, for example, implementing the aiming device proposed by the present invention for guns that are not firearms, such as toy guns, PaintBall guns and any gun that is intended to shoot a real, dummy or virtual projectile of any shape to a target, variations and adaptations, without departing from the spirit of the invention or exceeding the scope of the claims.

- 14 -

CLAIMS

1. Aiming device for guns, which comprises a transparent plate which shows to the user a critical image when said plate has a predetermined orientation, and shows a deformed image when said plate has any other different orientation; wherein said transparent plate is so mounted in said device and said device is so mounted on the gun that said critical image is seen by the user when and only when the axis of the gun barrel is parallel to the line of sight passing through the user's eye and the center of said transparent plate.
2. Aiming device according to claim 1, wherein the transparent plate is so mounted in said device and said device is so mounted on the gun that said transparent plate is set at a right angle to the gun barrel axis.
3. Aiming device according to claim 1, wherein the transparent plate is planar.
4. Aiming device according to claim 1, wherein the transparent plate is curved and the orientation of said plate is defined by a plane associated with it.
5. Aiming device according to claim 3, wherein the plane associated with the transparent plate is the plane tangent to the center of said plate.
6. Aiming device according to claim 3, wherein the plane associated with the transparent plate is the plane on which lies the periphery of said plate.

- 15 -

7. Aiming device according to claim 1, further comprising a support for the transparent plate, through which said plate is mounted on the gun at the appropriate orientation.
8. Aiming device according to claim 3, wherein the transparent plate is circular.
9. Aiming device according to claim 7, wherein the plate support comprises a ring-like portion.
10. Aiming device according to claim 1, which has such a structure and in which the plate is mounted in such a way that said plate is perpendicular to the axis of the gun barrel, and the image shown by the plate to the user is the critical image when the line of sight from the user's eye to said image is perpendicular to said plate.
11. Aiming device according to claim 1, wherein the transparent plate has a diameter from 3 to 10 mm.
12. Aiming device according to claim 1, wherein the transparent plate has a diameter from 4 to 6 mm.
13. Aiming device according to claim 1, wherein the gun is a hand-held gun.
14. Aiming device according to claim 1, wherein the difference between the critical image and the deformed image consists in the disappearance or appearance of figures or of portions of figures.

- 16 -

15. Aiming device according to claim 1, wherein the difference between the critical image and the deformed image consists in partial or total changes of color.

16. Aiming method for guns, which consists in pointing the gun so as to generate the critical image and bringing the target point to the center of said image.

17. Aiming device according to claim 1, wherein gun that is selected from the group consisting of:

- toy guns;
- PaintBall guns; and
- A gun that is intended to shoot a real, dummy or virtual projectile of any shape to a target.