

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number
WO 2005/048170 A1

(51) International Patent Classification⁷: **G06K 7/08**,
G08B 13/24

(21) International Application Number:
PCT/US2004/032538

(22) International Filing Date: 4 October 2004 (04.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/705,733 10 November 2003 (10.11.2003) US

(71) Applicant (for all designated States except US): **3M INNOVATIVE PROPERTIES COMPANY** [US/US]; 3M Center, Post Office Box 33427, Saint Paul, MN 55133-3427 (US).

(72) Inventors: **MERCER, Thomas C.**; 3M Center, Post Office Box 33427, Saint Paul, MN 55133-3427 (US).

JESME, Ronald D.; 3M Center, Post Office Box 33427, Saint Paul, MN 55133-3427 (US). **GOFF, Edward D.**; 3M Center, Post Office Box 33427, Saint Paul, MN 55133-3427 (US).


(74) Agents: **BUSS, Melissa E.**, et al.; Post Office Box 33427, Saint Paul, MN 55133-3427 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: ALGORITHM FOR RFID SECURITY



(57) Abstract: Techniques for detecting radio-frequency identification (RFID) tags are disclosed. For example, an exit control system is described that detects unauthorized removal of articles from a protected facility. A series of antennas are setup to produce interrogation corridors located near the exit of the protected area. RFID tags are attached to the articles to be protected. Each tag includes information that uniquely identifies the article to which it is affixed and status information as to whether the articles removal from the facility is authorized. The RF reader outputs RF signals through the antennas to create electromagnetic fields within the interrogation corridors. The reader outputs RF power from a single port to the multiple antennas via a splitter/combiner. In this way, a single RF reader with only one transmitter/receiver port simultaneously interrogates multiple antennas. A variety of techniques are described by which the reader can detect the removal of an unauthorized article.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.