




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04B 7/185, H04M 1/02, 1/72, H01Q 1/28		A1	(11) International Publication Number: WO 98/38754
			(43) International Publication Date: 3 September 1998 (03.09.98)
(21) International Application Number: PCT/JP98/00765			
(22) International Filing Date: 25 February 1998 (25.02.98)			
(30) Priority Data:			
9/61909	28 February 1997 (28.02.97)	JP	
9/81988	14 March 1997 (14.03.97)	JP	
9/116165	18 April 1997 (18.04.97)	JP	
(71) Applicant (for all designated States except US): KYOCERA CORPORATION [JP/JP]; 5-22, Kitainoue-cho, Higashino, Yamashina-ku, Kyoto-shi, Kyoto 607-8555 (JP).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): KIUCHI, Kazuya [JP/JP]; Kyocera Corporation, Yokohama Office, 1-1, Kagahara 2-chome, Tsuzuki-ku, Yokohama-shi, Kanagawa 224-8502 (JP). MASUDA, Yuzuru [JP/JP]; Kyocera Corporation, Yokohama Office, 1-1, Kagahara 2-chome, Tsuzuki-ku, Yokohama-shi, Kanagawa 224-8502 (JP). OOKITA, Hideto [JP/JP]; Kyocera Corporation, Yokohama Office, 1-1, Kagahara 2-chome, Tsuzuki-ku, Yokohama-shi, Kanagawa 224-8502 (JP). NAGAMACHI, Kazuo [JP/JP]; Kyocera Corporation, Yokohama Office, 1-1, Kagahara 2-chome, Tsuzuki-ku, Yokohama-shi, Kanagawa 224-8502 (JP). SASAKI, Yoshio [JP/JP];			
		(74) Agent: TAKAHASHI, Masahisa; Ambassador Roppongi Buildings, Room 1003, 16-13, Roppongi 3-chome, Minato-ku, Tokyo 106-0032 (JP).	
		(81) Designated States: AU, BR, CA, CN, ID, IL, KR, MX, NO, NZ, PL, SG, TR, UA, US, Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: DUAL-MODE SATELLITE/TERRESTRIAL MOBILE COMMUNICATION UNIT



(57) Abstract

The present invention seeks to provide a dual mode mobile satellite communication unit, which requires low communication cost and very little battery power, does not require always carrying a large unit frame and does not always provide great weight burden on the user. A terrestrial communication portable unit (B) is detachably mounted in the mobile satellite communication unit (A). The mobile satellite communication unit (A) as base unit does not include a key operating section, a display section and a speech transducer section having a microphone and a loudspeaker, and utilizes those mechanically assembled on the portable unit (B) side for keying and other operations. In an interlocked relation to the removal of the portable unit, the stand-by state of the base unit is turned off. It is thus possible to avoid wasteful battery power consumption on the base unit side.