

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
22 March 2001 (22.03.2001)

PCT

(10) International Publication Number
WO 01/20214 A1

(51) International Patent Classification⁷: F16L 19/065,
19/00

(21) International Application Number: PCT/US00/24900

(22) International Filing Date:
12 September 2000 (12.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/395,386 13 September 1999 (13.09.1999) US
60/159,965 18 October 1999 (18.10.1999) US

(71) Applicant (for all designated States except US):
SWAGELOK COMPANY [US/US]; 29500 Solon
Road, Solon, OH 44139 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): WILLIAMS, Peter,
C. [US/US]; 3495 Edison Road, Cleveland Heights, OH
44121 (US). JOHNSTON, Lonnie, E. [US/US]; 77915
Riverside Drive, Aurora, OH 44202 (US). KARKOSIAK,

John, D. [US/US]; 7985 Twin Oaks Drive, Broadview Hts.,
OH 44147 (US). BABUDER, Gerald, A. [US/US]; 8807
Yorkwood Court, Mentor, OH 44060 (US). MOGHE, San-
jeev, S. [—/US]; 7489 Dorwick Drive, Northfield Center,
OH 44067 (US). SCHEFFEL, Gary, W. [US/US]; 8384
State Route 43, Streetsboro, OH 44240 (US).


(74) Agent: GUTT, Ronald, D.; Calfee, Halter & Griswold
LLP, Suite 1400, 800 Superior Avenue, Cleveland, OH
44114 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: TUBE FITTING WITH INDICATING MEANS



162162

WO 01/20214 A1

(57) Abstract: An intrinsic gauging device for a ferrule type tube fitting (10) of the type having a coupling nut (14), a coupling body (12) and at least one ferrule (32), includes a precisely formed marking on the coupling body that is visually perceptible when the coupling is in a finger tight position, and that is covered or visually imperceptible or otherwise has a predetermined relationship with the coupling nut when the fitting has been initially pulled-up. In a preferred form, the marking is realized as a precision groove (50) or recess machined into a surface of the coupling body. The groove can be made more easily visually perceptible such as by roughening or knurling the surface, or coloring the surface, for example. The groove defines an edge (50b) at a precise position that corresponds to a predetermined axial displacement of the nut relative to the body for initial pull-up. The marking may also be formed with a precise dimension such as an axial length to provide a second edge that corresponds to a predetermined axial displacement of the nut relative to the body beyond initial pull-up for fitting assemblies that are remade.

WO 01/20214 A1

Published:

- *With international search report.*
- *Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette