



(51) International Patent Classification:
B65D 51/20 (2006.01)

(21) International Application Number:
PCT/IL2011/000783

(22) International Filing Date:
6 October 2011 (06.10.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
29/394,407 16 June 2011 (16.06.2011) US
61/391,101 8 August 2011 (08.08.2011) US

(72) Inventors; and

(71) Applicants : **AGASSI, Or** [IL/IL]; 5 Lincoln street, Tel Aviv 65220 (IL). **MARKO, Reuven** [IL/IL]; 1 YLG Street, 42240 Netanya (IL).

(74) Agent: **HESKIA-HACMUN LAW FIRM**; 6 Kaufman Street, 68012 Tel Aviv (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: A SEALABLE POURER

(57) Abstract: A sealable pourer for mounting on a bottle. The sealable pourer includes a cap to ensure that the pouring nozzle and air tube outlet are sealed, or otherwise closed, when in a first position of the cap and allow free flow of the liquid content of the bottle when in a second position. In one embodiment, the cap is rotated about a symmetry axis of the nozzle to achieve sealing of both the air passage and the pouring nozzle.



WO 2012/172534 A1