



- (51) **International Patent Classification:**
B01J 8/06 (2006.01) *C07C 51/215* (2006.01)
C07C 45/33 (2006.01)
- (21) **International Application Number:**
PCT/US2011/063652
- (22) **International Filing Date:**
7 December 2011 (07.12.2011)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/428,056 29 December 2010 (29.12.2010) US
- (71) **Applicant (for all designated States except US):** **ROHM AND HAAS COMPANY** [US/US]; 100 Independence Mall West, Philadelphia, PA 19106 (US).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** **HAN, Scott** [US/US]; 39 Easton Court, Lawrenceville, NJ 08648 (US). **FRICK, Christopher** [US/US]; 573 Kline Avenue, Pottstown, PA 19465 (US). **MARTENAK, Daniel, J.** [US/US]; 39 Direthorn Drive, Perkasio, PA 18944 (US).
- (74) **Agent:** **PLOTECHER, Gary, R.**; Whyte Hirschboeck Dudek S.c., 555 East Wells Street, Suite 1900, Milwaukee, WI 53202 (US).

- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) **Title:** REACTOR AND PROCESS FOR PROPANE OXIDATION

(57) **Abstract:** The amount of propionic acid produced in the process of oxidizing propane to acrylic acid is reduced by using a reactor with a length/diameter ratio >10 and/or maintaining the difference between the target reaction temperature and the peak temperature within the reactor to less than 20°C.

