

Data Transmission Method, Network Device and Terminal Device

Technical Field

Embodiments of the present invention relate to the communication field, and more particularly, to a data transmission method, a network device, and a terminal device.

Background

At present, in a discussion about a New Radio (NR)/5-Generation (5G) mobile communication technology, there are two following types of approaches supported by solutions that multiple Transmission Reception Points (TRPs) or multiple Antenna panels or multiple beams simultaneously provide transmission for a terminal device. Specifically, a first approach is that the terminal device only receives one Physical Downlink Control Channel (PDCCH) indicating relevant indication information about data transmitted through multiple TRPs/beams. A second approach is that the terminal device receives different NR-PDCCHs from different TRPs/beams, and each control channel indicates relevant indication information about one corresponding data transmission.

However, for the second approach, the terminal device needs to simultaneously detect multiple PDCCHs/Physical Downlink Shared Channels (PDSCHs) on the same carrier, and needs to send uplink information on uplinks corresponding to multiple downlinks, causing too high complexity and power consumption of the terminal device.

Summary

Provided are a data transmission method, a network device, and a terminal device, which can effectively reduce requirements for a terminal device and further reduce complexity and power consumption of the terminal device.

In a first aspect, there is provided a data transmission method. The data transmission method includes: generating first indication information, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or

the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels; and sending the first indication information to the terminal device.

The uplink signal transmission method provided by the embodiment of the invention can effectively reduce too high complexity and power consumption of the terminal device by indicating a transmission mode of uplink signals for the terminal device by the network device.

In some possible implementations, generating the first indication information includes: generating the first indication information according to at least one piece of the following information: interaction capabilities between multiple Transmission Reception Points (TRPs) corresponding to the multiple downlinks, interaction capabilities between multiple beams corresponding to the multiple downlinks, interaction capabilities between multiple cells to which the multiple TRPs belong, interaction capabilities between multiple cells to which the multiple beams belong, report information of the terminal device, service information of the multiple downlinks, and network load information.

In some possible implementations, the report information includes at least one piece of the following information: capability information indicating whether the terminal device supports to send the multiple pieces of uplink information on the multiple uplink channels, information about a Multiple-Input Multiple-Output (MIMO) capability of the terminal device, level information of the terminal device, and a Power Headroom Report (PHR) of the terminal device.

In some possible implementations, sending the first indication information to the terminal device includes: sending a Radio Resource Control (RRC) signaling to the terminal device, wherein the RRC signaling includes the first indication information; or, sending a Media Access Control (MAC) Control Element (CE) to the terminal device, wherein the MAC CE includes the first indication information.

In some possible implementations, sending the first indication information to the terminal device includes: sending first Downlink Control Information (DCI) to the terminal device, wherein the first DCI includes the first indication information.

In some possible implementations, sending the first Downlink Control Information (DCI) to the terminal device includes: sending the first DCI to the terminal device on a control channel corresponding to each downlink in the multiple downlinks; or sending the first DCI to the terminal device on a control channel corresponding to a first downlink of the multiple

downlinks.

In some possible implementations, the method further includes: receiving the multiple pieces of uplink information sent by the terminal device.

5 In some possible implementations, receiving the multiple pieces of uplink information sent by the terminal device includes: when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, receiving the multiple pieces of uplink information sent by the terminal device on a Physical Uplink Control Channel (PUCCH), wherein the multiple pieces of uplink information includes acknowledgement/non-acknowledgement information
10 corresponding to each downlink in the multiple downlinks, and/or Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

In some possible implementations, receiving the multiple pieces of uplink information sent by the terminal device includes: when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of
15 the multiple uplink channels, receiving the multiple pieces of uplink information sent by the terminal device on a Physical Uplink Shared Channel (PUSCH), wherein the multiple pieces of uplink information includes uplink data, or the multiple pieces of uplink information includes the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information corresponding to each downlink in the
20 multiple downlinks, and Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

In some possible implementations, before receiving the multiple pieces of uplink information sent by the terminal device, the method further includes: sending an uplink (UL) grant message of the uplink data to the terminal device.

25 In some possible implementations, sending the uplink grant message of the uplink data to the terminal device includes: sending second Downlink Control Information (DCI) to the terminal device, wherein the second DCI includes the UL grant message.

In some possible implementations, sending the second Downlink Control Information (DCI) to the terminal device includes: sending the second DCI to the terminal device on a
30 control channel corresponding to the each downlink in the multiple downlinks; or sending the second DCI to the terminal device on a control channel corresponding to a second downlink of the multiple downlinks.

The method in the embodiment of the present invention can effectively improve a success rate of detection of the terminal device by sending the second DCI to the terminal device on the control channel corresponding to each downlink in the multiple downlinks. Or, the method in the embodiment of the present invention can effectively reduce signaling overhead by sending the second DCI to the terminal device on the control channel corresponding to the second downlink in the multiple downlinks.

In some possible implementations, sending the second Downlink Control Information (DCI) to the terminal device includes: selecting at least one downlink in the multiple downlinks; and sending the second DCI to the terminal device on the at least one downlink.

In some possible implementations, before sending the second Downlink Control Information (DCI) to the terminal device, the method further includes: generating second indication information, wherein the second indication information is used for indicating the terminal device to receive the second DCI on the at least one downlink; and sending the second indication information to the terminal device.

The method in the embodiment of the present invention can effectively improve a success rate of detection of the terminal device.

In some possible implementations, selecting the at least one downlink in the multiple downlinks includes: selecting the at least one downlink in the multiple downlinks according to quality information and/or load information of the multiple downlinks.

In a second aspect, there is provided a data transmission method. The data transmission method includes: receiving first indication information sent by a network device, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels; and sending the multiple pieces of uplink information to the network device according to the first indication information.

In some possible implementations, receiving the first indication information sent by the network device includes: receiving a Radio Resource Control (RRC) signaling sent by the network device, wherein the RRC signaling includes the first indication information; or

receiving a Media Access Control (MAC) Control Cell (CE) sent by the network device, wherein the MAC CE includes the first indication information.

5 In some possible implementations, receiving the first indication information sent by the network device includes: receiving first Downlink Control Information (DCI) sent by the network device, wherein the first DCI includes the first indication information.

10 In some possible implementations, receiving the first Downlink Control Information (DCI) sent by the network device includes: receiving the first DCI sent by the network device on a control channel corresponding to any downlink of the multiple downlinks; or receiving the first DCI sent by the network device on a control channel corresponding to a first downlink of the multiple downlinks.

15 In some possible implementations, sending the multiple pieces of uplink information to the network device according to the first indication information includes: when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, sending the multiple pieces of uplink information to the network device on a Physical Uplink Control Channel (PUCCH), wherein the multiple pieces of uplink information includes acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and/or Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

20 In some possible implementations, sending the multiple pieces of uplink information to the network device according to the first indication information includes: when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, sending the multiple pieces of uplink information to the network device on a Physical Uplink Shared Channel (PUSCH), wherein the multiple pieces of uplink information includes uplink data, or the multiple pieces of uplink information includes the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

30 In some possible implementations, before sending the multiple pieces of uplink information to the network device according to the first indication information, the method further includes: receiving an uplink (UL) grant message of the uplink data sent by the network device; wherein sending the multiple pieces of uplink information to the network device

according to the first indication information includes: sending the multiple pieces of uplink information to the network device according to the first indication information and the UL grant message.

5 In some possible implementations, receiving the uplink (UL) grant message of the uplink data sent by the network device includes: receiving second Downlink Control Information (DCI) sent by the network device, wherein the second DCI includes the UL grant message.

10 In some possible implementations, receiving the second Downlink Control Information (DCI) sent by the network device includes: receiving the second DCI sent by the network device on a control channel corresponding to any downlink of the multiple downlinks; or receiving the second DCI sent by the network device on a control channel corresponding to a second downlink of the multiple downlinks; or receiving the second DCI sent by the network device on a control channel corresponding to each downlink in the multiple downlinks.

15 In some possible implementations, receiving the second Downlink Control Information (DCI) sent by the network device includes: receiving the second DCI sent by the network device on a control channel corresponding to at least one downlink of the multiple downlinks.

20 In some possible implementations, before receiving the second Downlink Control Information (DCI) sent by the network device, the method further includes: receiving second indication information sent by the network device, wherein the second indication information is used for indicating the terminal device to receive the second DCI sent by the network device on the at least one downlink, and the at least one downlink is a downlink selected by the network device in the multiple downlinks; wherein receiving the second DCI sent by the network device on the control channel corresponding to the at least one downlink of the multiple downlinks includes: receiving the second DCI sent by the network device on the control channel corresponding to the at least one downlink according to the second indication information.

25 In some possible implementations, before receiving the Downlink Control Information (DCI) sent by the network device, the method further includes: selecting the at least one downlink in the multiple downlinks.

30 In some possible implementations, selecting the at least one downlink in the multiple downlinks includes: selecting the at least one downlink in the multiple downlinks according to quality information and/or load information of the multiple downlinks.

In a third aspect, there is provided a network device. The network device includes a generating unit and a transceiving unit.

The generating unit is used for generating first indication information, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels.

The transceiving unit is used for sending the first indication information to the terminal device.

In a fourth aspect, there is provided a network device. The network device includes a processor and a transceiver.

The processor is used for generating first indication information, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels.

The transceiver is used for sending the first indication information to the terminal device.

In a fifth aspect, there is provided a terminal device. The terminal device includes a receiving unit and a sending unit.

The receiving unit is used for receiving first indication information sent by a network device, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels.

The sending unit is used for sending the multiple pieces of uplink information to the network device according to the first indication information.

In a sixth aspect, there is provided a terminal device including a transceiver. The

transceiver is used for receiving first indication information sent by a network device, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels; and sending the multiple pieces of uplink information to the network device according to the first indication information.

In a seventh aspect, there is provided a computer readable medium for storing a computer program. The computer program includes instructions used for executing the method embodiments of the first aspect or the second aspect.

In an eighth aspect, there is provided a computer chip. The computer chip includes an input interface, an output interface, at least one processor, and a memory. The at least one processor is used for executing codes in the memory. When the codes are executed, the processor may implement various processes executed by the network device in the data transmission method of the first aspect and various implementations thereof.

In a ninth aspect, there is provided a computer chip. The computer chip includes an input interface, an output interface, at least one processor, and a memory. The at least one processor is used for executing codes in the memory. When the codes are executed, the processor may implement various processes executed by the terminal device in the data transmission method of the first aspect and various implementations thereof.

In a tenth aspect, a communication system is provided, including the above network device and the above terminal device.

Brief Description of Drawings

FIG. 1 is an example of an application scenario according to an embodiment of the present invention.

FIG. 2 is an example of an application scenario according to an embodiment of the present invention.

FIG. 3 is a schematic flowchart of a data transmission method according to an embodiment of the present invention.

FIG. 4 is a schematic block diagram of a network device according to an embodiment of the present invention.

FIG. 5 is another schematic block diagram of a network device according to an embodiment of the present invention.

5 FIG. 6 is a schematic block diagram of a terminal device according to an embodiment of the present invention.

FIG. 7 is another schematic block diagram of a terminal device according to an embodiment of the present invention.

10 Detailed Description

Technical solutions in the embodiments of the present invention will be described with reference to the accompanying drawings.

FIG. 1 is an example diagram of a 5G communication system 100 according to an embodiment of the present invention.

15 As shown in FIG. 1, the communication system 100 may include a terminal device 110, a first TRP 121 and a second TRP 122. The first TRP 121 and the second TRP 122 may respectively communicate with the terminal device 110 through air interfaces. Specifically, the first TRP 121 and the second TRP 122 may independently schedule one terminal device 110 for data transmission.

20 For example, the terminal device 110 detects PDCCHs from the first TRP 121 and the second TRP 122 respectively within one time slot to schedule multiple independent uplink data transmissions, and these independent uplink transmissions may be just scheduled into the same time slot.

25 However, under the communication system shown in FIG. 1, there may be multiple communication scenarios.

For example, the first TRP 121 and the second TRP 122 belong to the same cell, and a connection (backhaul) between the first TRP 121 and the second TRP 122 is ideal, that is, information interaction may be rapidly and dynamically performed.

30 For another example, the first TRP 121 and the second TRP 122 belong to the same cell, and the connection between the first TRP 121 and the second TRP 122 is non-ideal, that is, information interaction between the first TRP 121 and the second TRP 122 cannot be quickly

performed, and relatively slow data interaction can only be performed.

For another example, the first TRP 121 and the second TRP 122 belong to different cells, and the connection between the first TRP 121 and the second TRP 122 is ideal.

For still another example, the first TRP 121 and the second TRP 122 belong to different
5 cells, and the connection between the first TRP 121 and the second TRP 122 is non-ideal.

Since a network device may send different NR-PDCCHs/NR-PDSCHs from multiple TRPs to a terminal device, that is, the terminal device receives downlink information through multiple downlinks. Herein, each downlink has corresponding uplink information to be transmitted, and the uplink information includes at least one piece of the following information
10 signals: acknowledgement/non-acknowledgement (ACK/NACK) corresponding to each downlink, report information such as Channel State Information (CSI) corresponding to each downlink, and uplink data.

It can be seen that if the terminal device 110 further needs to send uplink information on uplinks corresponding to multiple downlinks, too high complexity and power consumption of
15 the terminal device will be caused.

Aiming at the above problems, an embodiment of the present invention provides an uplink signal transmission method, which can effectively reduce too high complexity and power consumption of the terminal device through indicating a transmission mode of uplink signals for the terminal device by the network device.

It should be understood that the 5G communication system 100 is taken as an example for
20 exemplarily describing the embodiment of the present invention. However, the embodiments of the present invention are not limited thereto. In other words, the technical solutions of the embodiment of the present invention may be applied to any communication system in which multiple network devices can independently schedule a terminal to transmit data. For example,
25 if TRPs in FIG. 1 correspond to beams, accordingly an example of an application scenario as shown in FIG. 2 may be obtained. The scenario includes a terminal device 130 and a network device 140, wherein there are multiple beams between the terminal device 130 and the network device 140.

For example, a Global System of Mobile Communication (GSM) system, a Code Division
30 Multiple Access (CDMA) system, a Wideband Code Division Multiple Access (WCDMA) system, a General Packet Radio Service (GPRS), a Long Term Evolution (LTE) system, an LTE Time Division Duplex (TDD) system, and a Universal Mobile Telecommunication System

(UMTS) system.

The present invention describes various embodiments in combination with a network device and a terminal device.

5 The network device 120 may refer to any entity at a network side for sending or receiving signals. For example, it may be a user device for machine type communication (MTC), a Base Transceiver Station (BTS) in a GSM or CDMA, a NodeB in a WCDMA, an Evolutional Node B (eNB or eNodeB) in an LTE, a base station device in a 5G network, etc.

10 In addition, the terminal device 110 may be any terminal device. Specifically, the terminal device 110 may communicate with one or more core networks through a radio access network (RAN), and may be referred to as an access terminal, a User Equipment (UE), a subscriber unit, a subscriber station, a mobile station, a mobile platform, a remote station, a remote terminal, a mobile device, a user terminal, a terminal, a wireless communication device, a user agent, or a user device. For example, the terminal device may be a cellular phone, a cordless phone, a Session Initiation Protocol (SIP) phone, a Wireless Local Loop (WLL) station, a Personal
15 Digital Assistant (PDA), a handheld device with a wireless communication function, a computing device or another processing device connected to a wireless modem, an on-board device, a wearable device, a terminal device in a 5G network or the like.

FIG. 3 is a schematic flowchart of a data transmission method according to an embodiment of the present invention.

20 As shown in FIG. 3, the method includes the following acts 210, 220, and 230.

In 210, a network device generates first indication information.

In 220, the network device sends the first indication information to a terminal device.

In 230, the terminal device sends multiple pieces of uplink information to the network device according to the first indication information.

25 Specifically, the network device generates the first indication information, wherein the first indication information is used for indicating the terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on multiple uplink channels in a time division
30 multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels. The network device sends the first indication information to the terminal device.

In the embodiment of the present invention, the multiple uplink channels are uplink channels corresponding to the multiple downlinks, the multiple downlinks are links for a terminal to receive downlink information, and each downlink has corresponding uplink information to be transmitted. It can be understood that the first indication information indicates the terminal device to simultaneously send upload information corresponding to each downlink on multiple independent uplink channels; or, the first indication information indicates the terminal device to send upload information corresponding to each downlink in a time division multiplexing (TDM) mode on multiple independent uplink channels; or, the first indication information indicates the terminal device to transmit upload information corresponding multiple downlinks in a combination way by using a uplink channel.

In other words, after receiving the first indication information sent by the network device, the terminal device sends the multiple pieces of uplink information to the network device according to the first indication information.

A method for the network device to generate the first indication information in the embodiment of the present invention is described exemplarily below.

Optionally, the network device may generate the first indication information according to at least one piece of the following information: interaction capabilities between multiple Transmission Reception Points (TRPs) corresponding to the multiple downlinks, interaction capabilities between multiple beams corresponding to the multiple downlinks, interaction capabilities between multiple cells to which the multiple TRPs belong, interaction capabilities between multiple cells to which the multiple beams belong, report information of the terminal device, service information of the multiple downlinks, and network load information.

Herein, the report information may include at least one piece of the following information: capability information indicating whether the terminal device supports to send the multiple pieces of uplink information on the multiple uplink channels, information about a Multiple-Input Multiple-Output (MIMO) capability of the terminal device, level information of the terminal device, and a Power Headroom Report (PHR) of the terminal device.

An implementation for the network device to send the first indication information to the terminal device is described below.

As one embodiment, exemplarily, the network device may send a Radio Resource Control (RRC) signaling to the terminal device, wherein the RRC signaling includes the first indication information; or, the network device may send a Media Access Control (MAC) Control cell (CE)

to the terminal device, wherein the MAC CE includes the first indication information. In other words, the terminal device may obtain the first indication information through the RRC signaling or the MAC CE.

As another embodiment, exemplarily, the network device may send first Downlink Control Information (DCI) to the terminal device, wherein the first DCI includes the first indication information. In other words, the terminal device may obtain the first indication information through the first DCI.

In the embodiment of the present invention, when the network device sends the first indication information through the first DCI, the terminal device may only receive one NR-PDCCH indicating relevant indication information about data transmitted on multiple TRPs/beams, or the terminal device may receive different NR-PDCCHs from different TRPs/beams, wherein each control channel indicates relevant indication information about data transmitted on multiple TRPs/beams.

In other words, the network device may send the first DCI to the terminal device on a control channel corresponding to each downlink in the multiple downlinks; or, the network device may send the first DCI to the terminal device on a control channel corresponding to a first downlink of the multiple downlinks.

For example, when the network device sends the first DCI to the terminal device on the control channel corresponding to each downlink in the multiple downlinks, the terminal device may receive the first DCI sent by the network device on a control channel corresponding to any downlink in the multiple downlinks.

For another example, when the network device sends the first DCI to the terminal device on the control channel corresponding to the first downlink of the multiple downlinks, the terminal device may receive the first DCI sent by the network device on the control channel corresponding to the first downlink.

In the embodiment of the present invention, after receiving the first indication information, the terminal device may send the multiple pieces of uplink information to the network device according to the first indication information.

From the perspective of the terminal device, an implementation by which the terminal device sends the multiple pieces of uplink information to the network device after receiving the first indication information will be described below.

As one embodiment, exemplarily, when the first indication information is used for

indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels, the multiple pieces of uplink information are sent to the network device on a Physical Uplink Control Channel (PUCCH), wherein the multiple pieces of uplink information includes acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and/or Channel State Information (CSI) corresponding to each downlink in the multiple downlinks.

In other words, when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, the network device may receive the multiple pieces of uplink information sent by the terminal device on the PUCCH, wherein the multiple pieces of uplink information include acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and/or CSI corresponding to each downlink in the multiple downlinks.

As another embodiment, exemplarily, when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, the multiple pieces of uplink information are sent to the network device on a Physical Uplink Shared Channel (PUSCH), wherein the multiple pieces of uplink information includes uplink data, or the multiple pieces of uplink information includes the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and Channel State Information (CSI) corresponding to each downlink in the multiple downlinks.

In other words, when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, the network device may receive the multiple pieces of uplink information sent by the terminal device on the PUCCH, wherein the multiple pieces of uplink information include uplink data, or the multiple pieces of uplink information include the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and CSI corresponding to each downlink in the multiple downlinks.

It should be understood that in the embodiment of the present invention, if the terminal device needs to send uplink data to the network device, that is, when uplink data needs to be included in the multiple pieces of uplink information, the terminal device further needs to

receive an uplink (UL) grant message of the uplink data sent by the network device before sending the multiple pieces of uplink information to the network device.

Specifically, before sending the multiple pieces of uplink information to the network device, the terminal device receives the UL grant message of the uplink data sent by the network device, and then according to the first indication information and the UL grant message, sends the multiple pieces of uplink information to the network device.

Optionally, the terminal device receives a second DCI sent by the network device, wherein the second DCI includes the UL grant message. That is, the network device may carry the UL grant message in the second DCI to send to the terminal device.

As one embodiment, exemplarily, the network device may send the second DCI to the terminal device on a control channel corresponding to each downlink in the multiple downlinks; or, may send the second DCI to the terminal device on a control channel corresponding to a second downlink of the multiple downlinks.

For example, when the network device sends the second DCI to the terminal device on the control channel corresponding to each downlink in the multiple downlinks, the terminal device may receive the second DCI sent by the network device on a control channel corresponding to any downlink in the multiple downlinks. The method in the embodiment of the present invention can effectively improve a success rate of detection of the terminal device.

For another example, when the network device sends the second DCI to the terminal device on the control channel corresponding to the second downlink of the multiple downlinks, the terminal device may receive the second DCI sent by the network device on the control channel corresponding to the second downlink of the multiple downlinks; that is, the network device and the terminal device transmit the second DCI by default on the control channel corresponding to the second downlink. The method in the embodiment of the present invention can effectively reduce signaling overhead.

For another example, when the network device sends the second DCI to the terminal device on the control channel corresponding to any downlink in the multiple downlinks, the terminal device may receive the second DCI sent by the network device on a control channel corresponding to each downlink in the multiple downlinks. That is, the terminal device receives the second DCI sent by the network device through blind detection on control channels corresponding to the multiple downlinks. The method in the embodiment of the present invention can effectively reduce signaling overhead.

As another embodiment, exemplarily, the network device may select at least one downlink in the multiple downlinks; and then sends the second DCI to the terminal device on the at least one downlink.

For example, before sending the second DCI to the terminal device, the network device
5 generates second indication information for indicating the terminal device to receive the second DCI on the at least one downlink; and sends the second indication information to the terminal device. At this time, the terminal device may receive the second DCI sent by the network device on a control channel corresponding to the at least one downlink according to the second indication information. The method in the embodiment of the present invention can further
10 reduce the complexity of the terminal device.

For another example, the network device may select the at least one downlink in the multiple downlinks according to quality information and/or load information of the multiple downlinks. At this time, the terminal device may also select the at least one downlink in the multiple downlinks according to the quality information and/or load information of the multiple
15 downlinks, and then receive the second DCI sent by the network device on a control channel corresponding to the at least one downlink. The method in the embodiment of the present invention can effectively improve a success rate of detection of the terminal device.

It should be understood that the method for the network device to send the UL grant message to the terminal device is only described exemplarily, and the embodiment of the
20 present invention is not limited thereto. For example, the network device may determine a downlink for sending the second DCI through negotiation with the terminal device.

FIG. 4 is a schematic diagram of a network device 300 according to an embodiment of the present invention.

As shown in FIG. 4, the network device 300 includes a generating unit 310 and a
25 transceiving unit 320.

The generating unit 310 is used for generating first indication information, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send
30 the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink

channels.

The transceiving unit 320 is used for sending the first indication information to the terminal device.

Optionally, the generating unit 310 is specifically used for generating the first indication
 5 information according to at least one piece of the following information: interaction capabilities
 between multiple Transmission Reception Points (TRPs) corresponding to the multiple
 downlinks, interaction capabilities between multiple beams corresponding to the multiple
 downlinks, interaction capabilities between multiple cells to which the multiple TRPs belong,
 interaction capabilities between multiple cells to which the multiple beams belong, report
 10 information of the terminal device, service information of the multiple downlinks, and network
 load information.

Optionally, the report information includes at least one piece of the following information:

capability information indicating whether the terminal device supports to send the multiple
 pieces of uplink information on the multiple uplink channels, information about a
 15 Multiple-Input Multiple-Output (MIMO) capability of the terminal device, level information of
 the terminal device, and a Power Headroom Report (PHR) of the terminal device.

Optionally, the transceiving unit 320 is specifically used for sending a Radio Resource
 Control (RRC) signaling to the terminal device, wherein the RRC signaling includes the first
 indication information; or, sending a Media Access Control (MAC) Control Cell (CE) to the
 20 terminal device, wherein the MAC CE includes the first indication information.

Optionally, the transceiving unit 320 is specifically used for sending first Downlink
 Control Information (DCI) to the terminal device, wherein the first DCI includes the first
 indication information.

Optionally, the transceiving unit 320 is further specifically used for sending the first DCI
 25 to the terminal device on a control channel corresponding to each downlink in the multiple
 downlinks; or, sending the first DCI to the terminal device on a control channel corresponding
 to a first downlink in the multiple downlinks.

Optionally, the transceiving unit 320 is further used for receiving the multiple pieces of
 uplink information sent by the terminal device.

30 Optionally, the transceiving unit 320 is specifically used for, when the first indication
 information is used for indicating the terminal device to send the multiple pieces of uplink
 information on the first uplink channel of the multiple uplink channels, receiving the multiple

pieces of uplink information sent by the terminal device on a PUCCH, wherein the multiple pieces of uplink information include acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and/or CSI corresponding to each downlink in the multiple downlinks.

5 Optionally, the transceiving unit 320 is specifically used for, when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, receiving the multiple pieces of uplink information sent by the terminal device on a PUSCH, wherein the multiple pieces of uplink information include uplink data, or the multiple pieces of uplink information
10 include the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and CSI corresponding to each downlink in the multiple downlinks.

15 Optionally, the transceiving unit 320 is further used for, before receiving the multiple pieces of uplink information sent by the terminal device, sending an uplink (UL) grant message of uplink data to the terminal device.

Optionally, sending the UL grant message of uplink data to the terminal device includes: sending second Downlink Control Information (DCI) to the terminal device, wherein the second DCI includes the UL grant message.

20 Optionally, the transceiving unit 320 is specifically used for sending the second DCI to the terminal device on a control channel corresponding to each downlink in the multiple downlinks; or, sending the second DCI to the terminal device on a control channel corresponding to a second downlink of the multiple downlinks.

25 Optionally, the transceiving unit 320 is specifically used for selecting at least one downlink in the multiple downlinks; and sending the second DCI to the terminal device on the at least one downlink.

30 Optionally, the generating unit 310 is further used for, before sending the second Downlink Control Information (DCI) to the terminal device, generating second indication information, wherein the second indication information is used for indicating the terminal device to receive the second DCI on the at least one downlink; and the transceiving unit 320 is further used for sending the second indication information to the terminal device.

Optionally, the transceiving unit 320 is specifically used for selecting the at least one downlink in the multiple downlinks according to quality information and/or load information of

the multiple downlinks.

It should be noted that in the embodiment of the present invention, the generating unit 310 may be implemented by a processor, and the transceiving unit 320 may be implemented by a transceiver. As shown in FIG. 5, a network device 400 may include a processor 410, a transceiver 420, and a memory 430. The memory 430 may be used for storing indication information, and may be further used for storing codes, instructions, etc., executed by the processor 410. Various components in the network device 400 are connected by a bus system. The bus system includes a power bus, a control bus and a status signal bus in addition to a data bus.

The network device 400 shown in FIG. 5 can implement the various processes implemented by the network device in the method embodiment of FIG. 3 described above. In order to avoid duplication, the details will not be repeated here.

FIG. 6 is a schematic block diagram of a terminal device 500 according to an embodiment of the present invention.

As shown in FIG. 6, the terminal device 500 includes a receiving unit 510 and a sending unit 520.

The receiving unit 510 is used for receiving first indication information sent by the network device, wherein the first indication information is used for indicating the terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels.

The sending unit 520 is used for sending the multiple pieces of uplink information to the network device according to the first indication information.

Optionally, the receiving unit 510 is specifically used for receiving a Radio Resource Control (RRC) signaling sent by the network device, wherein the RRC signaling includes the first indication information; or, receiving a Media Access Control (MAC) Control Element (CE) sent by the network device, wherein the MAC CE includes the first indication information.

Optionally, the receiving unit 510 is specifically used for receiving first Downlink Control Information (DCI) sent by the network device, wherein the first DCI includes the first

indication information.

Optionally, the receiving unit 510 is specifically used for receiving the first DCI sent by the network device on a control channel corresponding to any downlink of the multiple downlinks; or, receiving the first DCI sent by the network device on a control channel
5 corresponding to a first downlink of the multiple downlinks.

Optionally, the sending unit 520 is specifically used for, when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, sending the multiple pieces of uplink information to the network device on a PUCCH, wherein the multiple pieces of
10 uplink information include acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and/or CSI corresponding to each downlink in the multiple downlinks.

Optionally, the sending unit 520 is specifically used for, when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, sending the multiple pieces of uplink information to the network device on a PUSCH, wherein the multiple pieces of
15 uplink information include uplink data, or the multiple pieces of uplink information include the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and CSI corresponding to each downlink in the multiple downlinks.
20

Optionally, the receiving unit 510 is further used for, before sending the multiple pieces of uplink information to the network device according to the first indication information, receiving an uplink (UL) grant message of uplink data sent by the network device; wherein the sending unit 520 is further used for sending the multiple pieces of uplink information to the network
25 device according to the first indication information and the UL grant message.

Optionally, the receiving unit 510 is specifically used for receiving second Downlink Control Information (DCI) sent by the network device, wherein the second DCI includes the UL grant message.

Optionally, the receiving unit 510 is specifically used for receiving the second DCI sent by
30 the network device on a control channel corresponding to any downlink of the multiple downlinks; or, receiving the second DCI sent by the network device on a control channel corresponding to a second downlink of the multiple downlinks; or, receiving the second DCI

sent by the network device on a control channel corresponding to each downlink in the multiple downlinks.

Optionally, the receiving unit 510 is specifically used for receiving the second DCI sent by the network device on a control channel corresponding to at least one downlink of the multiple downlinks.

Optionally, the receiving unit 510 is further used for, before receiving the second Downlink Control Information (DCI) sent by the network device, receiving second indication information sent by the network device, wherein the second indication information is used for indicating the terminal device to receive the second DCI sent by the network device on the at least one downlink, and the at least one downlink is a downlink selected by the network device in the multiple downlinks; and receiving the second DCI sent by the network device on a control channel corresponding to the at least one downlink according to the second indication information.

Optionally, the receiving unit 510 is further used for, before receiving the Downlink Control Information (DCI) sent by the network device, selecting the at least one downlink in the multiple downlinks.

Optionally, the receiving unit 510 is specifically used for selecting the at least one downlink in the multiple downlinks according to quality information and/or load information of the multiple downlinks.

It should be noted that in the embodiment of the present invention, both the receiving unit 510 and the sending unit 520 may be implemented by a transceiver. As shown in FIG. 7, a terminal device 600 may include a processor 610, a transceiver 620, and a memory 630. The memory 630 may be used for storing indication information, and may be further used for storing codes, instructions, etc., executed by the processor 610. Various components in the terminal device 600 are connected by a bus system. The bus system includes a power bus, a control bus and a status signal bus in addition to a data bus.

The terminal device 600 shown in FIG. 7 can implement the various processes implemented by the terminal device in the method embodiment of FIG. 3 described above. In order to avoid duplication, the details will not be repeated here.

That is, method embodiments in the embodiments of the present invention may be applied to or implemented by a processor. The processor may be an integrated circuit chip with a signal processing capability. In the implementation process, the actions of the method embodiments

described above may be completed by integrated logic circuits of hardware in the processor or instructions in the form of software. The above processor may be a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic devices, a transistor logic device, or a discrete hardware component. The processor may implement or execute the disclosed methods, acts and logical block diagrams in the embodiments of the present invention. The general purpose processor may be a microprocessor or the processor may be any conventional processor or the like. The acts of the methods disclosed in combination with the embodiments of the present invention may be directly embodied as to be executed and accomplished by a hardware decoding processor or by a combination of hardware and software modules in a decoding processor. Software modules may be located in a typical storage medium in the art, such as, a random access memory (RAM), a flash memory, a read-only memory, a programmable read-only memory, an electrical erasable programmable memory, or a register. The storage medium is located in a memory, and the processor reads information in the memory and completes the actions of the above method in combination with its hardware.

It should be understood that the memory in the embodiment of the present invention may be a transitory memory or a non-transitory memory, or it may include both transitory and non-transitory memory. The non-transitory memory may be a read-only memory (ROM), a programmable ROM (PROM), an erasable PROM (EPROM), an electrically erasable EPROM (EEPROM), or a flash memory. The transitory memory may be a Random Access Memory (RAM) which serves as an external cache. As an example, but not as a limitation, many forms of RAMs are available, such as a static random access memory (SRAM), a dynamic random access memory (DRAM), a synchronous dynamic random access memory (SDRAM), a double data rate SDRAM (DDR SDRAM), an enhanced SDRAM (ESDRAM), a Synch link DRAM (SLDRAM), and a Direct Rambus RAM (DR RAM). It should be noted that memories of the systems and methods described herein are intended to include, but are not limited to, these and any other suitable types of memories.

Finally, it should be noted that the terms used in the embodiments of the present invention and the appended claims are for the purpose of describing specific embodiments only and are not intended to limit the embodiments of the present invention.

For example, the singular forms “a”, “said”, and “the” used in the embodiments of the present invention and the appended claims are intended to include the plural forms unless the context clearly indicates other meanings.

For another example, the terms “first type cell group” and “second type cell group” may be used in the embodiments of the present invention, but these type cell groups should not be limited to these terms. These terms are only used for distinguishing type cell groups from each other.

5 For another example, depending on the context, the word “when” as used herein may be interpreted as “if” or “whether” or “while” or “in response to a determination of/that” or “in response to a detection of/that”. Similarly, depending on the context, the phrase “if it is determined that” or “if it is detected that (a stated condition or event)” may be interpreted as “when ... is determined” or “in response to a determination of/that” or “when (stated condition
10 or event) is detected” or “in response to a detection of/that (stated condition or event)”.

Those of ordinary skill in the art will recognize that the example units and algorithm acts described in connection with the embodiments disclosed herein may be implemented in electronic hardware, or a combination of computer software and electronic hardware. Whether these functions are implemented in hardware or software depends on a specific application and
15 design constraint of technical solutions. One skilled in the art may use different methods to implement the described functions for each particular application, but such implementation should not be considered to be beyond the scope of embodiments of the present invention.

Those skilled in the art may clearly understand that for convenience and conciseness of description, the specific working processes of the systems, apparatuses and units described
20 above may refer to the corresponding processes in the aforementioned method embodiments, and details are not described herein again.

In several embodiments provided by the present application, it should be understood that the disclosed systems, apparatuses and methods may be implemented in other ways. For example, the apparatus embodiments described above are only illustrative, for example, the
25 division of the units is only a logical function division, and there may be other division modes in actual implementations, for example, multiple units or components may be combined or integrated into another system, or some features may be ignored or not executed. On the other hand, the mutual coupling or direct coupling or communication connection shown or discussed may be indirect coupling or communication connection through some interfaces, apparatuses or
30 units, and may be in electrical, mechanical or other forms.

The units described as separated components may or may not be physically separated, and components shown as units may or may not be physical units, i.e., they may be located in one place or may be allocated over multiple network units. Parts or all of the units can be selected

according to actual needs to achieve the purpose of the embodiments of the present invention.

In addition, various functional units in the embodiments of the present invention may be integrated in one processing unit, or the various units may be presented separately in a physical way, or two or more units may be integrated in one unit.

5 Function units may be stored in a computer readable storage medium if realized in a form of software functional units and sold or used as a separate product. Based on this understanding, the technical solutions of the embodiments of the present invention, in essence, or the part contributing to the related art, or the part of the technical solutions, may be embodied in the form of a software product stored in a storage medium, including several instructions for
10 causing a computer device (which may be a personal computer, a server, or a network device, etc.) to perform all or parts of the acts of the methods described in various embodiments of the present invention. The aforementioned storage medium includes a medium capable of storing program codes, such as, a U disk, a mobile hard disk, a read-only memory (ROM), a magnetic disk or an optical disk, etc.

15 What are described above are merely specific implementations of the embodiments of the present invention, but the protection scope of the embodiments of the present invention is not limited thereto. Any modification or substitution that can be easily conceived by a person skilled in the art within the technical scope disclosed by the embodiments of the present invention shall be included within the protection scope of the embodiments of the present
20 invention. Therefore, the scope of protection of the embodiments of the present invention should be subject to the scope of protection of the claims.

Claims:

1. A data transmission method, comprising:

generating first indication information, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels; and

sending the first indication information to the terminal device.

2. The method according to claim 1, wherein generating the first indication information comprises:

generating the first indication information according to at least one piece of the following information:

interaction capabilities between multiple Transmission Reception Points (TRPs) corresponding to the multiple downlinks, interaction capabilities between multiple beams corresponding to the multiple downlinks, interaction capabilities between multiple cells to which the multiple TRPs belong, interaction capabilities between multiple cells to which the multiple beams belong, report information of the terminal device, service information of the multiple downlinks, and network load information.

3. The method according to claim 2, wherein the report information comprises at least one piece of the following information:

capability information indicating whether the terminal device supports to send the multiple pieces of uplink information on the multiple uplink channels, information about a Multiple-Input Multiple-Output (MIMO) capability of the terminal device, level information of the terminal device, and a Power Headroom Report (PHR) of the terminal device.

4. The method according to any one of claims 1-3, wherein sending the first indication information to the terminal device comprises:

sending a Radio Resource Control (RRC) signaling to the terminal device, wherein the RRC signaling comprises the first indication information; or, sending a Media Access Control (MAC) Control Element (CE) to the terminal device, wherein the MAC CE comprises the first

indication information.

5. The method according to any one of claims 1-3, wherein sending the first indication information to the terminal device comprises:

5 sending first Downlink Control Information (DCI) to the terminal device, wherein the first DCI comprises the first indication information.

6. The method according to claim 5, wherein sending the first Downlink Control Information (DCI) to the terminal device comprises:

10 sending the first DCI to the terminal device on a control channel corresponding to each downlink in the multiple downlinks; or sending the first DCI to the terminal device on a control channel corresponding to a first downlink in the multiple downlinks.

7. The method according to any one of claims 1-6, wherein the method further comprises:

receiving the multiple pieces of uplink information sent by the terminal device.

8. The method according to claim 7, wherein receiving the multiple pieces of uplink information sent by the terminal device comprises:

15 when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, receiving the multiple pieces of uplink information sent by the terminal device on a Physical Uplink Control Channel (PUCCH), wherein the multiple pieces of uplink information comprises acknowledgement/non-acknowledgement information corresponding to each
20 downlink in the multiple downlinks, and/or Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

9. The method according to claim 7, wherein receiving the multiple pieces of uplink information sent by the terminal device comprises:

25 when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, receiving the multiple pieces of uplink information sent by the terminal device on a Physical Uplink Shared Channel (PUSCH), wherein the multiple pieces of uplink information comprises uplink data, or the multiple pieces of uplink information comprises the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information
30 corresponding to each downlink in the multiple downlinks, and Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

10. The method according to claim 9, wherein before receiving the multiple pieces of uplink information sent by the terminal device, the method further comprises:

sending an uplink (UL) grant message of the uplink data to the terminal device.

11. The method according to claim 10, wherein sending the uplink (UL) grant message of the uplink data to the terminal device comprises:

sending second Downlink Control Information (DCI) to the terminal device, wherein the second DCI comprises the UL grant message.

12. The method according to claim 11, wherein sending the second Downlink Control Information (DCI) to the terminal device comprises:

10 sending the second DCI to the terminal device on a control channel corresponding to the each downlink in the multiple downlinks; or sending the second DCI to the terminal device on a control channel corresponding to a second downlink of the multiple downlinks.

13. The method according to claim 11, wherein sending the second Downlink Control Information (DCI) to the terminal device comprises:

15 selecting at least one downlink in the multiple downlinks; and
sending the second DCI to the terminal device on the at least one downlink.

14. The method according to claim 13, wherein before sending the second DCI to the terminal device, the method further comprises:

20 generating second indication information, wherein the second indication information is used for indicating the terminal device to receive the second DCI on the at least one downlink; and

sending the second indication information to the terminal device.

15. The method according to claim 13 or 14, wherein selecting at least one downlink in the multiple downlinks comprises:

25 selecting the at least one downlink in the multiple downlinks according to quality information and/or load information of the multiple downlinks.

16. A data transmission method, comprising:

30 receiving first indication information sent by a network device, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the

first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels; and

5 sending the multiple pieces of uplink information to the network device according to the first indication information.

17. The method according to claim 16, wherein receiving the first indication information sent by the network device comprises:

10 receiving a Radio Resource Control (RRC) signaling sent by the network device, wherein the RRC signaling comprises the first indication information; or, receiving a Media Access Control (MAC) Control Cell (CE) sent by the network device, wherein the MAC CE comprises the first indication information.

18. The method according to claim 17, wherein receiving first indication information sent by the network device comprises:

15 receiving first Downlink Control Information (DCI) sent by the network device, wherein the first DCI comprises the first indication information.

19. The method according to claim 18, wherein receiving the first Downlink Control Information (DCI) sent by the network device comprises:

20 receiving the first DCI sent by the network device on a control channel corresponding to any downlink of the multiple downlinks; or receiving the first DCI sent by the network device on a control channel corresponding to a first downlink of the multiple downlinks.

20. The method according to any one of claims 16-19, wherein sending the multiple pieces of uplink information to the network device according to the first indication information comprises:

25 when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, sending the multiple pieces of uplink information to the network device on a Physical Uplink Control Channel (PUCCH), wherein the multiple pieces of uplink information comprises acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and/or Channel State Information (CSI) corresponding to the each
30 downlink in the multiple downlinks.

21. The method according to any one of claims 16-19, wherein sending the multiple pieces of uplink information to the network device according to the first indication information comprises:

5 when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, sending the multiple pieces of uplink information to the network device on a Physical Uplink Shared Channel (PUSCH), wherein the multiple pieces of uplink information comprises uplink data, or the multiple pieces of uplink information comprises the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information
10 corresponding to each downlink in the multiple downlinks, and Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

22. The method according to claim 21, wherein before sending the multiple pieces of uplink information to the network device according to the first indication information, the method further comprises:

15 receiving an uplink (UL) grant message of the uplink data sent by the network device;

wherein sending the multiple pieces of uplink information to the network device according to the first indication information comprises:

sending the multiple pieces of uplink information to the network device according to the first indication information and the UL grant message.

20 23. The method according to claim 22, wherein receiving the UL grant message of the uplink data sent by the network device comprises:

receiving second Downlink Control Information (DCI) sent by the network device, wherein the second DCI comprises the UL grant message.

24. The method according to claim 23, wherein receiving the second DCI sent by the
25 network device comprises:

receiving the second DCI sent by the network device on a control channel corresponding to any downlink of the multiple downlinks; or receiving the second DCI sent by the network device on a control channel corresponding to a second downlink of the multiple downlinks; or receiving the second DCI sent by the network device on a control channel corresponding to
30 each downlink in the multiple downlinks.

25. The method according to claim 23, wherein receiving the second DCI sent by the

network device comprises:

receiving the second DCI sent by the network device on a control channel corresponding to at least one downlink of the multiple downlinks.

26. The method according to claim 25, wherein before receiving the second DCI sent by the network device, the method further comprises:

receiving second indication information sent by the network device, wherein the second indication information is used for indicating the terminal device to receive the second DCI sent by the network device on the at least one downlink, and the at least one downlink is a downlink selected by the network device in the multiple downlinks;

10 wherein receiving the second DCI sent by the network device on the control channel corresponding to the at least one downlink of the multiple downlinks comprises:

receiving the second DCI sent by the network device on a control channel corresponding to the at least one downlink according to the second indication information.

27. The method according to claim 25, wherein before receiving the DCI sent by the network device, the method further comprises:

selecting the at least one downlink in the multiple downlinks.

28. The method according to claim 27, wherein selecting the at least one downlink in the multiple downlinks comprises:

20 selecting the at least one downlink in the multiple downlinks according to quality information and/or load information of the multiple downlinks.

29. A network device, comprising:

a generating unit, configured to generate first indication information, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels; and

30 a transceiving unit, configured to send the first indication information to the terminal device.

30. The network device according to claim 29, wherein the generating unit is specifically configured to:

generate the first indication information according to at least one piece of the following information:

5 interaction capabilities between multiple Transmission Reception Points (TRPs) corresponding to the multiple downlinks, interaction capabilities between multiple beams corresponding to the multiple downlinks, interaction capabilities between multiple cells to which the multiple TRPs belong, interaction capabilities between multiple cells to which the multiple beams belong, report information of the terminal device, service information of the
10 multiple downlinks, and network load information.

31. The network device according to claim 30, wherein the report information comprises at least one piece of the following information:

capability information indicating whether the terminal device supports to send the multiple pieces of uplink information on the multiple uplink channels, information about a
15 Multiple-Input Multiple-Output (MIMO) capability of the terminal device, level information of the terminal device, and a Power Headroom Report (PHR) of the terminal device.

32. The network device according to any one of claims 29-31, wherein the transceiving unit is specifically configured to:

20 send a Radio Resource Control (RRC) signaling to the terminal device, wherein the RRC signaling comprises the first indication information; or, send a Media Access Control (MAC) Control Cell (CE) to the terminal device, wherein the MAC CE comprises the first indication information.

33. The network device according to any one of claims 29-31, wherein the transceiving unit is specifically configured to:

25 send first Downlink Control Information (DCI) to the terminal device, wherein the first DCI comprises the first indication information.

34. The network device according to claim 33, wherein the transceiving unit is further specifically configured to:

30 send the first DCI to the terminal device on a control channel corresponding to each downlink in the multiple downlinks; or send the first DCI to the terminal device on a control channel corresponding to a first downlink of the multiple downlinks.

35. The network device according to any one of claims 29-34, wherein the transceiving unit is further configured to:

receive the multiple pieces of uplink information sent by the terminal device.

36. The network device according to claim 35, wherein the transceiving unit is specifically
5 configured to:

when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, receive the multiple pieces of uplink information sent by the terminal device on a Physical Uplink Control Channel (PUCCH), wherein the multiple pieces of uplink information
10 comprises acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and/or Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

37. The network device according to claim 35, wherein the transceiving unit is specifically configured to:

15 when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, receive the multiple pieces of uplink information sent by the terminal device on a Physical Uplink Shared Channel (PUSCH), wherein the multiple pieces of uplink information comprises uplink data, or the multiple pieces of uplink information comprises the uplink data and at least
20 one piece of the following information: acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

38. The network device according to claim 37, wherein the transceiving unit is further configured to:

25 before receiving the multiple pieces of uplink information sent by the terminal device, send an uplink (UL) grant message of uplink data to the terminal device.

39. The network device according to claim 38, wherein sending the UL grant message of the uplink data to the terminal device comprises:

30 sending second Downlink Control Information (DCI) to the terminal device, wherein the second DCI comprises the UL grant message.

40. The network device according to claim 39, wherein the transceiving unit is specifically

configured to:

send the second DCI to the terminal device on a control channel corresponding to the each downlink in the multiple downlinks; or send the second DCI to the terminal device on a control channel corresponding to a second downlink of the multiple downlinks.

5 41. The network device according to claim 40, wherein the transceiving unit is specifically configured to:

select at least one downlink in the multiple downlinks; and

send the second DCI to the terminal device on the at least one downlink.

10 42. The network device according to claim 41, wherein the generating unit is further configured to:

before sending the second Downlink Control Information (DCI) to the terminal device, generate second indication information, wherein the second indication information is used for indicating the terminal device to receive the second DCI on the at least one downlink; and the transceiving unit is further configured to:

15 send the second indication information to the terminal device.

43. The network device according to claim 41 or 42, wherein the transceiving unit is specifically configured to:

select the at least one downlink in the multiple downlinks according to quality information and/or load information of the multiple downlinks.

20 44. A terminal device, comprising:

a receiving unit, configured to receive first indication information sent by a network device, wherein the first indication information is used for indicating a terminal device to simultaneously send multiple pieces of uplink information corresponding to multiple downlinks on multiple uplink channels, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the multiple uplink channels in a time division multiplexing mode, or the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on a first uplink channel of the multiple uplink channels; and

25

a sending unit, configured to send the multiple pieces of uplink information to the network device according to the first indication information.

30

45. The terminal device according to claim 44, wherein the receiving unit is specifically

configured to:

receive a Radio Resource Control (RRC) signaling sent by the network device, wherein the RRC signaling comprises the first indication information; or receive a Media Access Control (MAC) Control Cell (CE) sent by the network device, wherein the MAC CE comprises the first indication information.

46. The terminal device according to claim 44, wherein the receiving unit is specifically configured to:

receive first Downlink Control Information (DCI) sent by the network device, wherein the first DCI comprises the first indication information.

47. The terminal device according to claim 46, wherein the receiving unit is specifically configured to:

receive the first DCI sent by the network device on a control channel corresponding to any downlink of the multiple downlinks; or receive the first DCI sent by the network device on a control channel corresponding to a first downlink of the multiple downlinks.

48. The terminal device according to any one of claims 44-47, wherein the sending unit is specifically configured to:

when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, send the multiple pieces of uplink information to the network device on a Physical Uplink Control Channel (PUCCH), wherein the multiple pieces of uplink information comprises acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and/or Channel State Information (CSI) corresponding to the each downlink in the multiple downlinks.

49. The terminal device according to any one of claims 44-47, wherein the sending unit is specifically configured to:

when the first indication information is used for indicating the terminal device to send the multiple pieces of uplink information on the first uplink channel of the multiple uplink channels, send the multiple pieces of uplink information to the network device on a Physical Uplink Shared Channel (PUSCH), wherein the multiple pieces of uplink information comprises uplink data, or the multiple pieces of uplink information comprises the uplink data and at least one piece of the following information: acknowledgement/non-acknowledgement information corresponding to each downlink in the multiple downlinks, and Channel State Information (CSI)

corresponding to the each downlink in the multiple downlinks.

50. The terminal device according to claim 49, wherein the receiving unit is further configured to:

5 before sending the multiple pieces of uplink information to the network device according to the first indication information, receive an uplink (UL) grant message of uplink data sent by the network device;

wherein the sending unit is further configured to:

send the multiple pieces of uplink information to the network device according to the first indication information and the UL grant message.

10 51. The terminal device according to claim 50, wherein the receiving unit is specifically configured to:

receive second Downlink Control Information (DCI) sent by the network device, wherein the second DCI comprises the UL grant message.

15 52. The terminal device according to claim 51, wherein the receiving unit is specifically configured to:

20 receive the second DCI sent by the network device on a control channel corresponding to any downlink of the multiple downlinks; or receive the second DCI sent by the network device on a control channel corresponding to a second downlink of the multiple downlinks; or receive the second DCI sent by the network device on a control channel corresponding to each downlink in the multiple downlinks.

53. The terminal device according to claim 51, wherein the receiving unit is specifically configured to:

receive the second DCI sent by the network device on a control channel corresponding to at least one downlink of the multiple downlinks.

25 54. The terminal device according to claim 53, wherein the receiving unit is further configured to:

30 before receiving the second Downlink Control Information (DCI) sent by the network device, receive second indication information sent by the network device, wherein the second indication information is used for indicating the terminal device to receive the second DCI sent by the network device on the at least one downlink, and the at least one downlink is a downlink selected by the network device in the multiple downlinks; and

receive the second DCI sent by the network device on a control channel corresponding to the at least one downlink according to the second indication information.

55. The terminal device according to claim 53, wherein the receiving unit is further configured to:

5 before receiving the Downlink Control Information (DCI) sent by the network device, select the at least one downlink in the multiple downlinks.

56. The terminal device according to claim 55, wherein the receiving unit is specifically configured to:

10 select the at least one downlink in the multiple downlinks according to quality information and/or load information of the multiple downlinks.