

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 October 2005 (27.10.2005)


PCT

(10) International Publication Number
WO 2005/099949 A1

- (51) International Patent Classification⁷: **B23C 5/08, 5/22** (74) Agent: **ISCAR LTD., PATENT DEPARTMENT**; P.O. Box 11, 24959 Tefen (IL).
- (21) International Application Number: PCT/IL2005/000307 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 17 March 2005 (17.03.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 161373 14 April 2004 (14.04.2004) IL
- (71) Applicant (for all designated States except US): **ISCAR LTD.** [IL/IL]; P.O. Box 11, 24959 Tefen (IL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **HECHT, Gil** [IL/IL]; 30/18 Ahad Ha'am Street, 22443 Nahariya (IL).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: CUTTING TOOL AND CUTTING INSERT THEREFOR



(57) Abstract: A cutting insert (14) comprising a cutting portion (24) and a locating portion (26), the cutting portion (24) comprising a cutting edge (28) formed at the intersection of a rake surface (30) and a relief surface (32); an upper surface (34), a lower surface (36) and a peripheral side surface therebetween, the peripheral side surface comprising opposing forward and rear surfaces (38, 40) and opposing side surfaces (42) extending between the forward and rear surfaces (38, 40); the relief surface (32) being located in the forward surface (38) and the rake surface (30) being located in the upper surface (34); the locating portion (26) extends downwardly from the cutting portion (24) away from the upper surface (34); the locating portion (26) comprising opposing forward and rear locating surfaces (44, 46), the rear locating surface (46) being located in the rear surface (40) and the forward locating surface (44) being located in the lower surface (36); and a lower locating surface (48) located in the lower surface (36) and opposing the upper surface (34), and extending between the forward surface (38) and the forward locating surface (44). A cutting tool (10; 20) with such a cutting insert.



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*