



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶ :

B04B 1/14, 1/18, 11/04

A1

(11) International Publication Number:

WO 96/41683

(43) International Publication Date: 27 December 1996 (27.12.96)

(21) International Application Number: PCT/SE96/00672

(22) International Filing Date: 24 May 1996 (24.05.96)

(30) Priority Data:

9502098-8

8 June 1995 (08.06.95)

SE

(71) Applicant (for all designated States except US): TETRA
LAVAL HOLDINGS & FINANCE S.A. [CH/CH]; 70,
avenue Général-Guisan, CH-1009 Pully (CH).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BODELSON, Berth
[SE/SE]; Plåtslagarvägen 103, S-146 00 Tullinge (SE).
KLINTENSTEDT, Kjell [SE/SE]; Sjöängsvägen 16,
S-132 34 Saltsjö-Boo (SE). SALMI, Toini [SE/SE]; PL
3901, S-148 97 Sorunda (SE). OHLSON, Nils-Gunnar
[SE/SE]; Kristinedalsvägen 52, S-131 46 Nacka (SE).
SETTERBERG, Jan [SE/SE]; Hällebergsvägen 26, S-141
41 Huddinge (SE). HOLM, Staffan [SE/SE]; Målarstigen
35, S-144 33 RÖNNINGE (SE).(74) Agent: CLIVEMO, Ingemar, Alfa Laval AB, S-147 80 Tumba
(SE).(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY,
CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS,
JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD,
MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD,
SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN,
ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent
(AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,
MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

86 9700 843-7

(54) Title: A CENTRIFUGAL ROTOR AND A SLIDE FOR SUCH A ROTOR

(57) Abstract

In the rotor of a centrifugal separator there is an annular slide (6) for opening and closing of a periphery outlet (12, 13) from a separation chamber (9). The slide (6) at its radially inner edge is connected with and axially fixed relative to the rotor body (1, 2) but has a radially outer edge portion (11) which is axially movable relative to the rotor body (1, 2). This is possible because a portion of the slide, having a substantial radial extension, is flexible.

