

Boring machine comprising a variable-geometry cutting device

Technical Field

5 This invention relates to the field of soil excavation. In particular, it has the subject of a boring machine equipped with a variable-geometry milling device.

Prior Art

10 To make an excavation in soil, for example a trench, it is known to use a machine, commonly known as a "hydromill", which includes a frame suspended from the mast of a carrier, the lower end of the frame bearing a milling device which is generally equipped with one or two rotary milling drums. The rotary drums, also known as milling drums, include cutting tools disposed on the periphery of the milling drum or drums.

15 Such a boring machine is in particular described in the document FR2211027.

The cross-section of the trench, considered in a horizontal plane, which is obtained using such a machine is substantially constant over the entire depth of the trench.

20 The excavation operations can however require an increase in the cross-section of the trench, for example locally on the trench floor.

To do this, the document US2006/0032096 makes provision for a boring machine equipped with two milling drums, each drum being mounted on a support which can pivot with respect to the frame. This
25 makes it possible to vary the distance between the axes of rotation of the drums.

The pivoting of the supports is obtained using an actuating mechanism composed of two small articulated levers, attached to the supports pivotably and to the end of a hydraulic cylinder, which is itself
30 attached to the lower end of the frame.

The structure of this actuating mechanism is fragile and nonetheless does not make it possible to exert a significant torque on the supports. In some cases, it can therefore be difficult to deploy the milling drums.

35

Summary of the invention

An aim of the invention is to make provision for a boring machine equipped with a variable-geometry milling device having an alternative structure which is more robust and particularly makes it possible to supply a greater pivoting torque than in the prior machine.

5 To do this, the invention relates to a boring machine including:

a frame bearing at least one milling drum, the frame having a body extending along a longitudinal direction;

at least a first motor to drive the first milling drum in rotation about a first axis of rotation;

10 at least a first arm having a lower end part, the first arm being movable with respect to the body;

at least a first support bearing the first milling drum and the first motor, the first support being connected to the lower end part of the first arm while being movable with respect to the body of the frame,

15 an actuating device connected to the body to displace at least the first arm with respect to the body.

Characteristically, the body further includes:

20 a translational guiding device extending along the longitudinal direction,

the boring machine further comprising a movable member disposed in the body above the first support and interacting with the translational guiding device such that the movable member is displaceable with respect to the body along the longitudinal direction while being guided by the translational guiding device, the first arm being mounted pivotably on the movable member.

25 Unlike the prior boring machine wherein the actuating device is composed of a small hydraulic cylinder disposed outside the frame, the arrangement according to the invention makes it possible to mount a more powerful actuating device in the body of the frame.

30 Furthermore, the translational guiding device, which has the function of guiding the translational displacement of the movable member, also makes it possible to guide and stabilize the displacement of the first arm.

35 This arrangement makes it possible to transfer more force between the actuating device and the first support than in the prior mechanism.

This has the effect of obtaining a pivoting torque of the first support which is substantially greater than in the machine of the aforementioned prior document.

5 The longitudinal direction is preferably vertical. The first axis of rotation is preferably perpendicular to the longitudinal direction.

It will moreover be understood that the translational guiding device is separate from the actuating device.

10 Advantageously, the movable member is housed in the translational guiding device such as to form together a sliding coupling. Preferably, the movable member is movable inside the guiding device. Still preferably, the translational guiding device and the movable member are located in the frame.

Advantageously, the translational guiding device is integrated into the frame and the movable member is disposed in the frame.

15 Advantageously, the actuating device is attached to the body above the translational guiding device.

The translational guiding device preferably includes two parallel rails extending along the longitudinal direction of the body and together delimiting a passage for the movable member.

20 According to an advantageous embodiment, the first support is attached to the body pivotably about a first pivoting axis, and is attached to the lower end part of the first arm pivotably about a first axis of pivot, whereby the actuating of the actuating device has the effect of making the first milling drum pivot with respect to the body about the first
25 pivoting axis.

Preferably, considered along the longitudinal direction, the axis of pivot is disposed above the first pivoting axis.

30 Furthermore, considered along a transverse direction perpendicular to the longitudinal direction and perpendicular to the first pivoting axis, the first axis of rotation is preferably located between the first axis of pivot and the first pivoting axis when the boring machine is in the retracted position.

This arrangement makes it possible to install a first arm which is greater and more robust than the small levers of the prior boring machine.

35 Advantageously, the frame further includes a second arm which is connected to the movable member, the second arm having a lower end

part, the first and second arms being pivotable with respect to one another, the actuating device being configured to displace the second arm with respect to the body, said boring machine further including:

5 a second milling drum and a second motor to drive the second milling drum in rotation about a second axis of rotation; and
 a second support which is movable with respect to the body, the second milling drum and the second motor being mounted on the second support, the second support being connected to the lower end part of the second arm.

10 Preferably, the second support is attached to the body pivotably about a second pivoting axis, and is attached to the lower end part of the second arm pivotably about a second axis of pivot, whereby the actuating of the actuating device has the effect of making the second milling drum pivot with respect to the body about the second pivoting axis.

15 The second pivoting axis is preferably parallel to the second axis of pivot and to the second axis of rotation.

 Still preferably, the first and second axes of pivoting are parallel.

 Without departing from the scope of this invention, the first and second axes of pivoting can be colinear.

20 In an advantageous arrangement, the first and second axes of pivot are located above the first and second axes of pivoting.

 Preferably, the first and second milling drums can be pivoted about their respective axes of pivoting independently of one another. The pivoting amplitude is preferably between 0° and 60° . Preferably, the
 25 pivoting amplitude of the milling drums about the axes of pivoting is the same for both drums. Without departing from the scope of this invention, the two milling drums can have different deployment amplitudes.

 Advantageously, considered along a transverse direction perpendicular to the longitudinal direction and to the first pivoting axis,
 30 the first and second axes of pivoting are located between the first and second axes of pivot.

 Advantageously, the boring machine has a retracted position wherein the separation between the first and second milling drums is minimal, the boring machine further including a stop device in order to
 35 maintain the minimum separation between the first and second milling drums when the boring machine is in the retracted position.

It will be understood that the transition between the retracted position and a deployed position is made by actuating the actuating device.

5 The boring machine described in the document US2006/0032096 also has the drawback that the milling drums can come into contact with one another if the cylinder is too retracted or badly adjusted, which will of necessity lead to damage or breakage of the milling drums.

10 Owing to the invention, the stop device contrariwise makes it possible to avoid the first and second milling drums coming into contact with one another when they are brought closer to one another, in such a way as to preserve a minimum separation, for example of a few centimeters, between the two milling drums.

15 Preferably, the first and second supports are shaped to come into contact with one another when the boring machine is in the retracted position, the stop device consisting of stop faces disposed face-to-face on each of the first and second supports.

20 According to a preferred embodiment, the actuating device includes a first actuator which is connected to the body and to the first arm to displace the first arm with respect to the body, and a second actuator which is connected to the body and to the second arm to displace the second arm with respect to the body. The first and second actuators are preferably attached to the body pivotably. Still preferably, the first and second actuators are connected to the body above the translational guiding device.

25 Without departing from the scope of this invention, the actuating device may comprise a main actuator attached to the body on the one hand and to the movable member on the other. In this embodiment the actuating of the main actuator has the effect of displacing the movable member in translation, the displacement of the movable member causing
30 the pivoting of the first and second arms.

To quickly remove the boring machine from the suspension device, the frame further includes a swivel joint which is connected to the body by way of a removable element.

35 One benefit is to be able to quickly replace the frame of the boring machine according to the invention with another frame, for example a grab frame, while keeping the same carrier.

Brief description of the drawings

5 The invention will be better understood on reading the following description of an embodiment of the invention given by way of non-limiting example, with reference to the appended drawings, wherein:

[Fig.1] Figure **1** is a front view of an embodiment of the boring machine according to the invention, the milling drums being in the retracted position;

10 [Fig.2] Figure **2** is a front view of the boring machine of figure **1**, the milling drums being in the deployed position;

[Fig.3] Figure **3** illustrates an example of use of the boring machine of figure **1** to make cavities at different depths in two adjacent soil portions;

15 [Fig.4] Figure **4** shows an example of use of the boring machine of figure **1** illustrating a step during which the milling device overcuts the vertical edges of two adjacent panels;

[Fig.5] Figure **5** is a view taken in a horizontal plane, illustrating the overcut area during the step of figure **4** ; and

20 [Fig.6] Figure **6** illustrates a variant of figure **5**, wherein the panels are overcut over a fraction of their thickness such as to create a paving notch joint.

Detailed description

25 Using figures **1** and **2**, a description will now follow of a boring machine **10** in accordance with this invention.

The boring machine **10** includes a frame **12** which is attached to the end of a suspending element **14**, the latter being connected to a mast
30 of a carrier not illustrated here.

In accordance with the invention, the frame includes a body **16** extending along a longitudinal direction **L** between an upper end part **16a** and a lower end part **16b**.

35 In this non-limiting example, the frame **12** includes a swivel joint **18** which is attached to the upper end part **16a** of the body **16** by way of a removable element **20**. The swivel joint is moreover connected to the

suspending element **14**. The removable element **20** makes it possible to easily replace the frame **12** with another frame for example bearing another type of boring device, for example a grab frame.

In this example, the frame further includes a first guiding element **22** and a second guiding element **24** which are disposed on either side of the body **16**.

These guiding elements extend along a longitudinal direction **L** and are intended to bear against the walls of the trench to guide the vertical displacement of the boring machine **10** through the soil.

The body **16** further includes a translation guiding device **30** which extends along the longitudinal direction **L**. In this example, the translational guiding device **30** includes a first rail **32** and a second rail **34** which are parallel to one another while extending along the longitudinal direction **L**, the first and second rails **32**, **34** together delimiting a passage **36** the usefulness of which will be detailed below.

The frame moreover includes a first arm **40** which has an upper end part **40a** and a lower end part **40b**.

In this example, the frame further includes a second arm **42** having an upper end part **42a** and a lower end part **42b**.

As can be seen in figure **1**, the upper end parts **40a**, **42a** of the first and second arms are connected to a movable member **44** which takes the form of a roller housed in the aforementioned passage **36** of the translational guiding device **30**. The movable member is therefore housed in the translational guiding device **30** and is guided in translation along the longitudinal direction by the first and second rails. In other words, the movable member **44** is housed in the translational guiding device **30** such as to form together a sliding coupling oriented along the longitudinal direction **L**. In this example, the translational guiding device **30** is integrated into the frame **12**, and the movable member **44** is disposed in the frame **12**.

More precisely, in this non-limiting example, the first and second arms are pivotable with respect to one another about a coupling axis **X** which is perpendicular to the longitudinal direction **L**.

More precisely, each of the first and second arms **40**, **42** is pivotable with respect to the movable member **44** about the coupling axis **X**.

It will therefore be understood that the first and second arms **40**, **42** are movable with respect to the body **16**.

The boring machine **10** according to the invention moreover includes an actuating device **50** which, in the embodiment described in figures **1** and **2**, includes a first actuator **52**, consisting of a hydraulic cylinder, and a second actuator **54**, also consisting of a hydraulic cylinder. It will be understood that the actuating device **50** is connected to the body **16** to displace the first arm and the second arm **42** with respect to the body **16**. In this example, the translational guiding device **30** is separate from the actuating device **50**.

In this non-limiting example, the first actuator **52** includes an upper end **52a** which is mounted on the body **16** pivotably about an axis **Y1**. The first actuator **52** is moreover connected to the lower end part **40b** of the first arm **40** pivotably about an axis **Y2** which is parallel to the axis **Y1**.

Similarly, the second actuator **54** has an upper end **54a** which is attached to the body **16** pivotably about an axis **Y3**, parallel to the axis **Y1**. The second actuator **54** also includes a lower end **54b** which is connected to the lower end **42b** of the second arm **42** pivotably about an axis **Y4**, which is parallel to the axis **Y3**.

It can be seen in this example that the upper ends of the first and second actuators **52**, **54** are attached above the translational guiding device **30**.

It will be understood that the actuating of the first and/or second actuators **52**, **54** has the effect of displacing the first and second arms **40**, **42** with respect to the body **16**.

In this example, the displacement of the first and second arms **40**, **42** with respect to the body **16** is a combination of a rotation about the coupling axis **X** and of a translation along the longitudinal direction **L**.

It can be seen that the upper end of the actuating device **50** is attached to the upper end part **16a** of the body **16**.

In this example, the upper ends of the first and second actuators **52**, **54** are attached to the upper end part **16a** of the body **16**.

In accordance with the invention, the frame bears a first milling drum **60** and, in this example, the frame moreover bears a second milling drum **62**. The first milling drum **60** is rotary about a first axis of rotation

A1, perpendicular to the longitudinal direction **L**, while the second milling drum **62** is rotary about a second axis of rotation **A2** which, in this example, is parallel to the first axis of rotation **A1**.

5 The boring machine **10** moreover includes a first motor to drive the first milling drum **60** in rotation about the first axis of rotation **A1**, and a second motor to drive the second milling drum **62** about the second axis of rotation **A2**.

10 The first and second motors are housed in the first and second milling drums **60**, **62**. This arrangement is moreover known, and will not be described in further detail here. Without departing from the scope of this invention, the first and second motors can alternatively be disposed above the first and second milling drums, in a structure which is also known.

15 In accordance with the invention, the boring machine **10** further comprises a first support **64** bearing the first milling drum **60** and the first motor. As can be seen in figure **1**, the first support **64** is connected to the lower end part **40b** of the first arm **40**. The first support **64** is also movable with respect to the body **16** of the frame.

20 More precisely, in this example the first support **64** is attached to the body **16** pivotably about a first pivoting axis **B1**.

Moreover, the first support **64** is attached to the lower end part **40b** of the first arm **40** pivotably about a first axis of pivot **C1**.

25 It will therefore be understood that the actuating of the actuating device **50**, and more precisely the actuating of the first actuator **52**, has the effect of pivoting the first milling drum **60** with respect to the body **16** about the first pivoting axis **B1**.

It can also be seen that the first pivoting axis **B1** is parallel to the first axis of pivot **C1**, these axes being – in this example – also parallel to the first axis of rotation **A1**.

30 Note moreover that the first pivot **C1** is disposed above the first pivoting axis **B1**.

In this example, it will be understood that the actuating of the first actuator **52** has the effect of making the first milling drum **60** pivot with respect to the body **16** about the first pivoting axis **B1**.

35 In this example, the boring machine further includes a second support **66** which is movable with respect to the body **16**. Moreover, the

second milling drum **62** and the second motor are mounted on the second support, the latter being connected to the lower end part **42b** of the second arm **42**.

As can be seen in figures **1** and **2**, in the exemplary embodiment described here, the second support **66** is attached to the body **16** pivotably about a second pivoting axis **B2**. The second support **66** is moreover attached to the lower end part **42b** of the second arm **42** pivotably about a second pivoting axis **C2**.

It will be understood that the actuating of the actuating device **50**, and more precisely the actuating of the second actuator **54** has the effect of making the second milling drum **62** pivot with respect to the body **16** about the second pivoting axis **B2**.

Considered in projection in a horizontal plane, it will be understood that the actuating of the first and second actuators **52**, **54** has the effect of modifying the distance between the first and second axes of rotation **A1** and **A2** of the first and second milling drums **60**, **62**, which makes it possible to make the first and second milling drums transition between a retracted position, illustrated in figure **1**, and a deployed position, illustrated in figure **2**. The amplitude of pivoting of each of the first and second supports is preferably between 0° and 60°.

In this example, the first and second axes of pivoting **B1**, **B2** are parallel. Without departing from the scope of this invention, the first and second axes of pivoting **B1**, **B2** could be colinear.

Note moreover that the first and second axes of pivot **C1**, **C2** are disposed above the first and second axes of pivoting **B1**, **B2**, while the first axes of rotation **A1** and **A2** are disposed below first and second axes of pivoting **B1**, **B2**.

Moreover, considered along a transverse direction **T**, which is perpendicular to the longitudinal direction **L** on the one hand and to the first pivoting axis **B1** on the other, it should be noted that the first and second axes of pivoting are located between the first and second axes of pivot.

Moreover, when the boring machine **10** is in the retracted position, the separation between the first and second milling drums **60**, **62** is minimal. The boring machine further includes a stop device **70** in order to

maintain the minimum separation between the first and second milling drums when the boring machine is in the retracted position.

In this example, the first and second supports **64**, **66** are shaped to come into contact with one another when the boring machine is in the retracted position, as illustrated in figure **1**. The stop device **70** is here formed by stop faces **72**, **74** disposed face-to-face on each of the first and second supports. It will be understood that, in the retracted position, the stop faces **72**, **74** come into contact with one another.

The first portion **64** includes a first hydraulic junction box **82** connected to the first motor and to hydraulic hoses (not illustrated here) to supply the first motor with hydraulic power. Similarly, the second support **66** includes a second hydraulic unit **84**, connected to the second motor, as well as to hydraulic hoses to supply the second motor with hydraulic power.

Figure **3** illustrates the boring machine **10** according to the invention in which the boring machine with variable geometry is in the deployed position, which makes it possible to excavate cavities **E** in the soil **S** on either side of the trench being excavated.

In figure **4**, the boring machine **10** is used to overcut the vertical edges **300a,302a** of two primary panels **300**, **302** disposed on either side of the machine. After excavating a trench between the two primary panels using the boring machine **10**, the milling device then being in the retracted position, the milling device is brought into the deployed position and the boring machine **10** is raised such as to overcut the primary panels over a depth **p**, this depth being considered along a horizontal direction.

In figure **5**, which illustrates a horizontal section of the boring, the vertical edges **300a,300b** of the panels are overcut over the entire thickness **e** of the panels. The overcut areas are referenced **304,306**.

In figure **6**, which illustrates a variant of the boring illustrated in figure **5**, the vertical edges **300a,300b** of the panels are overcut over a fraction of the thickness **e** of the panels. The overcut areas are referenced **306,308**, and form a paving notch. To do this, the width of the milling drums will be adapted to the desired width of the paving notches.

CLAIMS

1. A boring machine (10) including:

a frame (12) bearing at least a first milling drum, the frame
5 having a body extending along a longitudinal direction;

at least a first motor to drive the milling drum (60) in
rotation about a first axis of rotation (A1);

at least a first arm (40) having a lower end part (40b), the
first arm being movable with respect to the body (16);

10 at least a first support (64) bearing the first milling drum
(60) and the first motor, the first support (64) being connected to
the lower end part (40b) of the first arm (40) while being movable
with respect to the body (16) of the frame,

an actuating device (50) connected to the body (16) to
15 displace at least the first arm (40) with respect to the body (16);

said boring machine being characterized in that the body
further includes:

a translational guiding device (30) extending along the
longitudinal direction,

20 the boring machine further comprising a movable member
(34) disposed in the body above the first support and interacting
with the translational guiding device (30) such that the movable
member is displaceable with respect to the body along the
longitudinal direction while being guided by the translational
25 guiding device (30), the first arm (40) being mounted pivotably on
the movable member (34).

2. The boring machine as claimed in claim 1, wherein:

the first support (64) is attached to the body (16) pivotably
30 about a first pivoting axis (B1), and is attached to the lower end
part (40b) of the first arm (40) pivotably about a first axis of pivot
(C1),

whereby the actuating of the actuating device (50) has the
effect of making the first milling drum (60) pivot with respect to the
35 body (16) about the first pivoting axis (B1).

3. The boring machine as claimed in claim 2, wherein the first axis of pivot (C1) is disposed above the first pivoting axis (B1).
- 5 4. The boring machine as claimed in any of claims 1 to 3, wherein the frame further includes a second arm (42) which is connected to the movable member (34), the second arm (42) having a lower end part (42b), the first and second arms being pivoting with respect to one another, the
10 actuating device (50) being configured to displace the second arm with respect to the body, said boring machine further including:
 - 15 a second milling drum (62) and a second motor to drive the second milling drum in rotation about a second axis of rotation (A2); and
 - 20 a second support (66) which is movable with respect to the body (16), the second milling drum (62) and the second motor being mounted on the second support, the second support being connected to the lower end part (42b)
25 of the second arm (42).
5. The boring machine as claimed in claim 4, wherein:
 - 25 the second support (66) is attached to the body (16) pivotably about a second pivoting axis (B1), and is attached to the lower end part (42b) of the second arm (42) pivotably about a second axis of pivot (C1),
 - 30 whereby the actuating of the actuating device (50) has the effect of making the second milling drum (62) pivot with respect to the body (16) about the second pivoting axis (B1).
6. The boring machine as claimed in claim 5, wherein the first and second axes of pivoting (B1, B2) are parallel.

7. The boring machine as claimed in claim 5 or 6, wherein the first and second axes of pivot (C1, C2) are located above the first and second axes of pivoting (B1, B2).
- 5 8. The boring machine as claimed in any of claims 5 to 7, wherein, considered along a transverse direction (T) perpendicular to the longitudinal direction and to the first pivoting axis, the first and second axes of pivoting (B1,B2) are located between the first and second axes of pivot
10 (C1,C2).
9. The boring machine as claimed in any of claims 4 to 8, wherein the boring machine has a retracted position wherein the separation between the first and second milling
15 drums (60, 62) is minimal, the boring machine further including a stop device (70) in order to maintain the minimum separation between the first and second milling drums when the boring machine is in the retracted position.
- 20 10. The boring machine as claimed in claim 9, wherein the first and second supports (64, 62) are shaped to come into contact with one another when the boring machine is in the retracted position, the stop device (70) consisting of stop
25 faces (72, 74) disposed face-to-face on each of the first and second supports.
11. The boring machine as claimed in any of claims 4 to 10, wherein the actuating device (50) includes a first actuator (52) which is connected to the body and to the first arm to
30 displace the first arm with respect to the body, and a second actuator (54) which is connected to the body and to the second arm to displace the second arm with respect to the body.
- 35 12. The boring machine as claimed in any of the preceding claims, wherein the first motor is hydraulic.

- 5 13. The boring machine as claimed in any of the preceding claims, wherein the frame further includes a swivel joint (18) which is connected to the body by way of a removable element (20).
- 10 14. The boring machine as claimed in any of the preceding claims, wherein the movable member (44) is housed in the translational guiding device (30) such as to form together a sliding coupling.
- 15 15. The boring machine as claimed in any of the preceding claims, wherein the translational guiding device (30) includes two parallel rails extending along the longitudinal direction of the body and together delimiting a passage for the movable member.
- 20 16. The boring machine as claimed in any of the preceding claims, wherein the translational guiding device (30) is separate from the actuating device.
- 25 17. The boring machine as claimed in any of the preceding claims, wherein the translational guiding device (30) is integrated into the frame (12), and the movable member is disposed in the frame (12).