

- 1 -

Method of, and apparatus for, producing a newspaper

The invention relates to a method of producing a newspaper as claimed in claim 1 and to an apparatus for
5 implementing the method as claimed in claim 11.

A classic newspaper is typically composed of a plurality of sections which are positioned one inside the other, are folded once in the center all together
10 and, in turn, comprise individual sheets which are positioned one upon the other and folded one inside the other. A section, also referred to as a bundle, typically contains from two to ten sheets, depending on the amount of printing. A section may also contain
15 half-sheets which are not folded to produce the section. The newspaper is formed from a plurality of sections which are again folded one inside the other. In the case of a typical daily newspaper, for example the outermost, first section contains the front page
20 and the international part, the second section contains the regional part, the third section contains the financial part, etc. The reader finds all the sections in the correct order when he/she opens up the newspaper for the first time. The individual sheets or pages are
25 likewise arranged in the correct order when the sections are opened up. The known, always identical basic composition of a certain newspaper makes it possible for the regular reader to find quickly the parts which interest him/her.

30

In exceptional cases, it is also possible for the newspaper to comprise just one section. This section comprises, for example, a plurality of sheets which are folded one inside the other twice.

35

In the case of conventional printing methods for producing a newspaper, for example letter press printing, offset printing and gravure printing, a rotary printing machine is used for one or more paper

webs to be printed at the same time in a plurality of printing units and to be folded to form the end product or newspaper. This printing method is static in the sense that a certain number of identical newspapers are
5 printed by first of all all of the first, second and further pages being printed and, following completion of the printing, being joined together to form a section or to form a complete newspaper. In order to print a product with different contents, the printing
10 machine is stopped, the printing formes, e.g. plates, blocks, cylinders, are changed and the printing machine is restarted.

Such static printing methods are only economically
15 viable for very large print jobs. For this reason, even national daily newspapers are printed in only one center or in a small number of centers and distributed from there, it often being the case that long distances have to be covered precisely when the newspapers are
20 shipped abroad. The topicality of the newspaper contents suffers as a result of the transporting time necessary for this purpose. The transportation itself involves high outlay in terms of personnel and energy.

25 Digital printing machines, e.g. laser printers or ink-jet printers, in which a plurality of different pages can be printed sequentially, i.e. one after the other, without the printing machine having to be stopped (dynamic printing method), are known. Digital printing
30 machines are used, at present, to produce end products with an end format of typically DIN A4 and less, said end products comprising a plurality of sheets which are not folded or are folded once and, once printing has been completed are collected and connected to one
35 another, e.g. by wire stapling or gluing. Previously known digitally printed products are not comparable in terms of their composition and appearance, with the current, conventionally produced newspapers.

The object of the invention is to specify a method of producing a newspaper which can be implemented straightforwardly and cost-effectively, even in a decentralized manner, and in the case of which the newspaper does not differ in appearance from a conventionally printed newspaper. The intention is also to specify an apparatus for implementing the method.

The invention is achieved by a method of producing a newspaper having the features of claim 1, and also by an apparatus for implementing the method having the features of claim 11. Advantageous developments of the method and of the apparatus are described in the dependent claims, the description and the drawing.

In the case of the method according to the invention, the sheets printed in a digital printing machine are processed to form a newspaper in one operation in that the sheets belonging to a newspaper or a section, which are printed in sequence one after the other, are collected and formed into a section by being folded one inside the other, and further sections are printed in sequence, collected, folded and formed into a newspaper by all the sections being folded one inside the other again. The newspaper is produced according to the invention in the following steps: the continuously printed sheets are fed continuously one by one to a first collecting station. Sheets which are assigned to one common section are positioned one above the other (collected) to form a sheet stack or a not yet folded section. Once all of the sheets of a section have been collected, the finished sheet stack is conveyed away from the first collector station. In this case, a first sheet of a further section, which is continuously produced by the printing machine and supplied to the collecting station, is fed to the collecting station while the preceding sheet stack is conveyed away from the first collecting station or once it has been conveyed away therefrom. It is thus possible for the

printing machine to run continuously without interruption. A finished sheet stack or a section which is finished apart from the center fold is then folded in the center in order to complete the section. The
5 section is deposited in a second collecting station such that it comes to rest on an, if appropriate, already deposited section which is assigned to the same newspaper. The steps of feeding, collecting, conveying away and folding are repeated, if appropriate, until
10 all the sections of the newspaper have been completed and positioned one upon the other to form a section stack. This section stack is then preferably folded in the center again. The method is preferably continued without interruption with the production of the next
15 newspaper.

It is advantageous for sheets which are intended for forming individual sections of a newspaper to be printed sequentially by a digital printing machine in a
20 previous method step. Sequentially means that, first of all, all of the sheets which form a copy of a newspaper are printed one after the other, each sheet bearing different printing. Thereafter, the sheets for the next newspaper copy are printed. This is not possible using
25 conventional printing machines.

The invention makes it possible to print just the precise number of complete newspapers in the typical newspaper format as has to be available at the printing
30 location. The expensive operation of exchanging printing formes is done away with altogether if a digital printer is used; the printed contents are changed electronically. It is also the case here, in contrast to known static printing methods, that it is
35 not necessary to keep any supply of printed pages between the individual printing operations. All the sheets of a complete newspaper are preferably printed one after the other, and the sheets of a further newspaper are printed thereafter, etc. It is also

possible for one or more sections to be printed
beforehand and for the newspaper only to be completed
just prior to distribution by virtue of the as yet
absent sections with topical and/or local information
5 being printed.

An apparatus according to the invention for
implementing the method has a first collecting station
which is intended for collecting sheets and comprises a
10 feed and depositing apparatus, for feeding individual
sheets and depositing the same to form a sheet stack,
and a removal apparatus for conveying sheet stacks
away. A digital printing machine for the sequential
printing of sheets intended for forming the newspaper,
15 a first folding arrangement for folding a finished
sheet stack, a second collecting station for collecting
complete sections, and a second folding arrangement for
folding the complete newspaper are preferably provided.
The correct method sequence is preferably controlled,
20 by means of software, by a control unit or by timing
marks.

On account of a digital printing machine being used,
the apparatus is more cost-effective and
25 straightforward to operate and to maintain than a
conventional set-up for producing newspapers using a
conventional printing machine. The amount of space
required is also reduced. It is thus possible, instead
of using a central set-up, for a number of such
30 apparatuses with the corresponding printing machines to
be decentralized, the distribution-related distances
being shortened as a result. The printed contents can
be transferred electronically to the production sites.
It is also possible, in principle, for a newspaper only
35 to be produced in accordance with actual demand. It is
further possible for the newspaper to be put together
in a customer-specific manner, e.g. for certain
sections to be left out or to be included in a
locality-specific manner.

In an advantageous development of the method, at least one further printed product, e.g. a prefabricated section or a prefabricated advertising supplement, is fed to the second collecting station by a feed arrangement and positioned on a section deposited there. The point in time at which the further printed product is deposited is preferably selected such that it comes to rest on a predetermined section, if appropriate at a predetermined location of the section. It is thus possible for the position of a supplement within the newspaper to be adapted thematically to the section contents.

A further advantage of the invention is that it is easily possible to produce sections which optionally comprise whole sheets and half-sheets. The digital printing machine and the following cross-cutters are capable of producing different sheet lengths dynamically. The first collecting apparatus according to the invention is configured such that it is possible, in any desired sequence, for both whole sheets and half-sheets to be collected in a disruption-free manner and stacked with straight edges. For example, suckers or grippers grip the fed sheets along the entire width of the leading sheet edge, as seen in the conveying direction, with the result that even a half-sheet is transported and deposited in a precisely aligned manner.

An example of the invention is described hereinbelow and illustrated in the drawing, in which, purely schematically:

Figure 1 shows the sequence of the method according to the invention;

Figure 2 shows a side view of a first collection station; and

Figure 3 shows the sequence of the method according to the invention in the region of the second collecting station.

- 5 Individual sheets 1 are printed in a digital printing machine, sheet-fed or web-fed printing machine (not shown here), cross-cut if appropriate and collected in a first collecting station 10 to form a sheet stack 2 made of individual sheets 1. It is possible for
10 printing to take place both in the forward direction, from A to Z, or in the rearward direction, from Z to A. In the first collector station 10, the sheets 1 are received, transported and deposited precisely one upon the other. The finished sheet stack 2 is folded in a
15 first folding arrangement 11 to form a section 3. The section 3 is positioned, in a second collecting station 12, on a section stack 15 comprising already printed and folded sections 4, 5. A feed arrangement 14 for supplements may be used to position a previously
20 produced supplement 6 at a predetermined location on one of the sections 3, 4, 5 in the second collecting station 12. Once all of the sections 3, 4, 5 of a newspaper 7 have been collected, the section stack 15 is folded in the center in a second folding station 13.
25 The thus completed newspapers 7, 8, 9 are deposited in an ordered manner, e.g. in an imbricated formation or on a stack, and transported away by a removal arrangement 16.
- 30 Figure 2 shows an example of a first collecting station 10 according to the invention with a following folding station 11. The first collecting station 10 is suitable specifically for large-format digital printing and is made up of a feed and depositing apparatus 17, for
35 feeding the individual sheets 1 and depositing them to form a sheet stack 2, and of a removal apparatus 20 for quickly transporting a finished sheet stack 2 away to the following operating process, i.e. to the folding station 11, without the individual sheets 1 in the

sheet stack 2 being displaced in relation to one another.

A transporting system 17 with suitable receiving
5 elements 19, e.g. grippers or suckers, receives individual sheets 1 from the previous process, e.g. the printing machine or the cross-cutters, and guides the sheets 1 into a first depositing position 24. In this case, the speed of the sheet 1 in the first collecting
10 station 10 is not uniform: the receiving element 19, which moves along a continuous circulatory path 25, rectilinear at least in one segment 25a, initially runs at a speed v_A which is essentially identical to that of the previous process. Depending on the printing system
15 v_A is between 50 and 150 m/min, preferably between 50 and 80 m/min. An incoming sheet 1 is thus received by the receiving elements 19 at approximately the same speed. Once it has left the previous process, the sheet is accelerated to a speed v_B , in order to acquire a
20 lead over the following sheet. v_B is approximately two to three times the speed v_A , preferably between 150 and 200 m/min. Finally, the sheet is deposited in the depositing position 24 at reduced speed v_C , in order for the sheet 1 to be deposited carefully, and in the
25 correct position, without the edges of the thin paper of the newspaper being damaged in the process. v_C is preferably from approximately 120 to 150 m/min. The variable conveying speed makes it possible for large sheets, typically in a format of larger than DIN A 2
30 (width typically between 420 and 508 mm; length between 580 and 760 mm), of thin newspaper paper to be transported quickly, but carefully, and to be stacked with accurate edge alignment. The non-uniform speed of the receiving element 19 along its circulatory path can
35 be realized, for example, by a servo drive.

A plurality of sheets 1 positioned one upon the other form a sheet stack 2. For transporting the latter away into the following operating process, i.e. into the

first folding station 11, the finished sheet stack 2 is transported away from the first collecting station 10 immediately after the last sheet 1 of a sheet stack 2 has arrived. The transporting-away speed here is preferably higher than the previously described speed v_A , in order that the first-arriving sheet of a further sheet stack and the outgoing sheet stack do not disrupt one another in the first collecting station 10. A removal arrangement 20 transports the entire sheet stack out of the first collecting apparatus 10 at a speed v_D . The removal arrangement 20 here comprises two transporting belts or conveying belts 20a, 20b, which form between them a gap for receiving the sheet stack 2. Alternatively, it is also possible to use grippers.

Immediately before the transportation by the removal arrangement 20, 20', or during said transportation, the individual sheets 1 of the sheet stack 2 are preferably connected to one another temporarily in order that they cannot be displaced during the transportation to the folding station 11. This temporary connection preferably takes place by electrostatic charging by means of a charging apparatus 21. The charging is dissipated again in an extremely short period of time during or after the folding operation. It is alternatively possible, for being transported together, for all the sheets of a sheet stack to be pierced by needles ("crimping"). In order for the sheet stack to be transferred to the following folding unit without the sheets being displaced in relation to one another, the first folding station 11 is preferably arranged directly at the outlet of the first collecting station 10. Alternatively, it is also possible for the folding station 11 to be integrated in the first collecting station 10, preferably by the entire sheet stack located in the depositing position 24 being folded directly in situ by a knife folding arrangement, arranged centrally in relation to the sheet stack, and thereby also conveyed out of the depositing position 24, e.g. in the downward or upward direction.

The first folding station 11 comprises, for example, a buckle, vacuum or knife folding unit, it also being possible for the first two units to be integrated in the first collecting station 10. In this case, the
5 collected sheets are folded for the first time in the first collecting station 10 and leave the first collecting station 10 in the folded state.

Figure 3 shows the sequence of a method according to
10 the invention in the region of the second collecting station 12. Sections 3 coming from the first folding apparatus 11 are deposited on a section stack 15 in the second collecting station 12. Prefabricated supplements 6, 6', which are present as individual sheets or
15 likewise in the form of sections, e.g. previously printed sections or advertising literature, may be supplied to the section stack 15 in a controlled manner. The finished section stack 15 comprises all the sections 3, 4, 5 of the newspaper and all the
20 supplements 6, 6' envisaged therefor. In a second folding apparatus 13, it is folded once in the center in a direction perpendicular to the folds of the individual sections 3, 4, 5. The finished newspaper 7 may then be transported away.



Patent claims

1. A method of producing a newspaper (7, 8, 9) which comprises at least one section (3, 4, 5) which is
5 formed at least from one centrally folded printed sheet (1), having the following steps:

a) individual sequentially printed sheets (1), which are intended for forming the individual sections (3, 4,
10 5) of the newspaper (7, 8, 9), are fed continuously to a first collecting station, and sheets (1) which are assigned to one common section (3, 4, 5) are positioned one above the other (collected) to form a sheet stack (2);

15

b) a finished sheet stack (2) is conveyed away from the first collecting station (10), a first sheet (1) of a further section (3, 4, 5) being fed to the first collecting station (10) while the preceding sheet stack
20 (2) is being conveyed away from the first collecting station (10) or once it has been conveyed away therefrom;

c) the finished sheet stack (2) is folded in order to
25 produce a section (3, 4, 5);

d) the section (3, 4, 5) is deposited in a second collecting station (12) such that it comes to rest on, if appropriate, an already deposited section (3, 4, 5);

30

e) the steps a) to d) are repeated, if appropriate, until all the sections (3, 4, 5) of the newspaper (7, 8, 9) have been completed and positioned one upon the other to form a section stack (15).

35

2. The method as claimed in claim 1, wherein the sheets intended for forming the individual sections (3, 4, 5) of the newspaper (7, 8, 9) are printed sequentially by



- 12 -

a digital printing machine and fed to the first collecting station (10).

3. The method as claimed in claim 1 or 2, wherein a
5 finished section stack (15) is folded in the center.

4. The method as claimed in claim 1, 2 or 3, wherein
sheets (1) of a sheet stack (2) are releaseably
connected to one another, preferably by means of
10 staples, by piercing with needles, or by means of
electrostatic charging, in order to be conveyed away.

5. The method as claimed in one of the preceding
claims, wherein at least one further printed product
15 (6, 7') is fed to the second collecting station (12)
and positioned on a section (3, 4, 5) deposited there.

6. The method as claimed in claim 5, wherein the at
least one further printed product (6, 6') is fed such
20 that it comes to rest on a predetermined section (3, 4,
5).

7. The method as claimed in one of the preceding
claims, wherein sheets (1) of a width of from 420 to
25 508 cm and of a length of from 580 to 760 cm are
processed.

8. The method as claimed in one of the preceding
claims, wherein a finished sheet stack (2) is conveyed
30 away from the first collecting station (10) at a speed
which is greater than the speed of the sheets (1) fed
to the first collecting station (10).

9. The method as claimed in one of the preceding
35 claims, wherein a sheet (1) is braked before being
deposited in the first collecting station (10).

10. The method as claimed in one of the preceding
claims, wherein a finished sheet stack (2) is folded as



it is conveyed out of the first collecting station (10).

11. An apparatus for implementing the method according
5 to one of the preceding claims, having a first
collecting station (10) which is intended for
collecting sheets (1) and comprises a feed and
depositing apparatus (17), for feeding individual
10 sheets (1) and depositing the same to form a sheet
stack (2), and a removal apparatus (20) for conveying
sheet stacks (2) away.

12. The apparatus as claimed in claim 11, which
comprises a digital printing machine for the sequential
15 printing of sheets (1) intended for forming the
newspaper (7, 8, 9).

13. The apparatus as claimed in claim 11 or 12, which
comprises a first folding arrangement (11) for folding
20 a finished sheet stack (2) in order to form a section
(3, 4, 5).

14. The apparatus as claimed in claim 13, wherein the
first folding arrangement (11) is integrated in the
25 first collecting station.

15. The apparatus as claimed in one of claims 11 to 14,
which comprises a second collecting station (12), for
collecting sections (3, 4, 5), and a second folding
30 station (13) for folding a section stack (15).

16. The apparatus as claimed in one of claims 11 to 15,
wherein the feed and depositing apparatus (17)
comprises at least one receiving element (19) which is
35 moved at non-uniform speed along a continuous
circulatory path (25), rectilinear in at least one
segment (25a), is preferably in the form of a gripper
or sucker and is capable of receiving an incoming sheet
(1), the speed of the receiving element (19) at that

end of the segment (25a) which is directed toward the digital printing machine corresponding essentially to the speed of the incoming sheet (1), being greater than this in the downstream region and being reduced again
5 in the region in which the sheet (1) is deposited in the first collection station (10).

17. Use of a digital printing machine for printing a newspaper (7, 8, 9) which comprises at least one
10 section (3, 4, 5) which is formed at least from one centrally folded printed sheet (1).

