

Data Transmission Method, Terminal Device, and Network Device

Technical Field

Embodiments of the present application relate to the field of wireless communication, and
5 more particularly, relate to a data transmission method, a terminal device, and a network device.

Background

In a Long Term Evolution (LTE) system, frequency domain resources for transmitting data are allocated in the whole system bandwidth. However, in a 5G New Radio (NR) system, a
10 transmission bandwidth of a terminal device may only occupy a part of the system bandwidth due to greatly increased system bandwidth. For example, a network device divides the system bandwidth into a plurality of transmission bands, each transmission band is called a Bandwidth Part (BWP), and the terminal device only needs to perform data transmission in its corresponding bandwidth part.

15 In the 5G system, when the terminal device performs a Radio Resource Management (RRM) measurement, signals from different cells, such as Synchronization Signal Blocks (SS Blocks), may be located in different frequency positions, so the terminal device needs to measure signals from different cells in different frequency positions. If the different frequency positions of SS Blocks from different cells differ greatly in the frequency domain, the terminal
20 needs to adopt a large reception bandwidth to receive the SS Blocks of all cells simultaneously. In such case, BWP configured for data transmission by the network device to the terminal device may not meet requirements for the terminal device to perform the RRM measurement.

Summary

25 Embodiments of the present application provide a data transmission method, a terminal device and a network device. The terminal device may effectively perform data transmission in its corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

In a first aspect, there is provided a data transmission method. The data transmission
30 method includes: a terminal device determines a first bandwidth part and a second bandwidth part; and the terminal device performs data transmission and a radio resource management

(RRM) measurement on a specific time domain resource by using the first bandwidth part, and performs the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

Therefore, the terminal device determines two different transmission bandwidths, and uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

In one possible implementation, determining, by the terminal device, the first bandwidth part and the second bandwidth part, includes: the terminal device receives first configuration information and second configuration information sent by a network device, wherein the first configuration information includes bandwidth information about the first bandwidth part, and the second configuration information includes bandwidth information about the second bandwidth part; and the terminal device determines the first bandwidth part according to the first configuration information and determines the second bandwidth part according to the second configuration information.

In one possible implementation, determining, by the terminal device, the first bandwidth part and the second bandwidth part, includes: the terminal device receives second configuration information and third configuration information sent by a network device, wherein the second configuration information includes bandwidth information about the second bandwidth part, and the third configuration information includes information about a frequency band occupied by at least one signal to be measured by the terminal device in the RRM measurement; the terminal device determines the second bandwidth part according to the second configuration information, and determines a third bandwidth part according to the third configuration information, the third bandwidth part includes the frequency band occupied by the at least one signal; and the terminal device determines the first bandwidth part according to the second bandwidth part and the third bandwidth part.

In one possible implementation, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

In one possible implementation, the first bandwidth part includes a whole system bandwidth.

In one possible implementation, the bandwidth information includes at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

In one possible implementation, the specific time domain resource includes a plurality of time domain resources distributed according to a time periodicity.

5 In one possible implementation, the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

In one possible implementation, the at least one signal to be measured by the terminal device in the RRM measurement includes a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

10 In a second aspect, there is provided a data transmission method. The data transmission method includes: a network device sends first configuration information or third configuration information to a terminal device, wherein the first configuration information includes bandwidth information about a first bandwidth part, the third configuration information includes information about a frequency band occupied by at least one signal to be sent for the
15 terminal device to perform a radio resource management (RRM) measurement, and the first configuration information and the third configuration information are used for the terminal device to determine the first bandwidth part so that the terminal device performs data transmission and the RRM measurement on a specific time domain resource by using the first bandwidth part; the network device sends second configuration information to the terminal
20 device, wherein the second configuration information includes bandwidth information about the second bandwidth part, so that the terminal device performs the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

Therefore, the network device configures two different bandwidth parts for the terminal device based on different requirements for the terminal device to perform the data transmission
25 and the RRM measurement, so that the terminal device uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

30 In one possible implementation, if the network device sends the first configuration information to the terminal device, the method further includes: the network device determines a third bandwidth part according to the information about the frequency band occupied by the at

least one signal to be sent for the terminal device to perform the RRM measurement, wherein the third bandwidth part includes the frequency band occupied by the at least one signal; and the network device determines the first bandwidth part according to the second bandwidth part and the third bandwidth part.

5 In one possible implementation, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

In one possible implementation, the first bandwidth part includes a whole system bandwidth.

10 In one possible implementation, the bandwidth information includes at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

In one possible implementation, the specific time domain resource includes a plurality of time domain resources distributed according to a time periodicity.

15 In one possible implementation, the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

In one possible implementation, the at least one signal to be sent for the terminal device to perform the RRM measurement includes a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

20 In a third aspect, there is provided a terminal device that may perform operations of the terminal device in the first aspect or any optional implementation of the first aspect. Specifically, the terminal device may include modules used for performing operations of the terminal device in the first aspect or any possible implementation of the first aspect.

25 In a fourth aspect, there is provided a network device that may perform operations of the network device in the second aspect or any optional implementation of the second aspect. Specifically, the network device may include modules used for performing operations of the network device in the second aspect or any possible implementation of the second aspect.

30 In a fifth aspect, there is provided a terminal device. The terminal device includes: a processor, a transceiver, and a memory. The processor, the transceiver, and the memory communicate with each other through an internal connection path. The memory is used for storing instructions, and the processor is used for executing the instructions stored in the memory. When the processor executes the instructions stored in the memory, the execution causes the terminal device to execute the method in the first aspect or any possible

implementation of the first aspect, or the execution causes the terminal device to implement the terminal device provided in the third aspect.

5 In a sixth aspect, there is provided a network device. The network device includes: a processor, a transceiver, and a memory. The processor, the transceiver, and the memory communicate with each other through an internal connection path. The memory is used for storing instructions, and the processor is used for executing the instructions stored in the memory. When the processor executes the instructions stored in the memory, the execution causes the network device to execute the method in the second aspect or any possible implementation of the second aspect, or the execution causes the network device to implement
10 the network device provided in the fourth aspect.

In a seventh aspect, there is provided a computer-readable storage medium storing a program that causes a terminal device to perform any data transmission method in the first aspect and various implementations thereof.

15 In an eighth aspect, there is provided a computer-readable storage medium storing a program that causes a network device to perform any data transmission method in the second aspect and various implementations thereof.

In a ninth aspect, there is provided a system chip, which includes an input interface, an output interface, a processor, and a memory, wherein the processor is used for executing instructions stored in the memory, and when the instructions are executed, the processor may
20 implement the method in the first aspect or any possible implementation thereof.

In a tenth aspect, there is provided a system chip, which includes an input interface, an output interface, a processor, and a memory, wherein the processor is used for executing instructions stored in the memory, and when the instructions are executed, the processor may implement methods in the second aspect and any possible implementation thereof.

25 In an eleventh aspect, a computer program product containing instructions is provided. When the computer program product is run on a computer, the computer is caused to perform the method in the first aspect or any possible implementation thereof.

In a twelfth aspect, a computer program product containing instructions is provided. When the computer program product is run on a computer, the computer is caused to perform the
30 method in the second aspect or any possible implementation thereof.

Brief Description of Drawings

FIG. 1 is a schematic architecture diagram of an application scenario according to an embodiment of the present application.

5 Fig. 2 is a schematic diagram of frequency domain positions of SS Blocks of different cells.

FIG. 3 is a schematic flowchart of a data transmission method according to an embodiment of the present application.

Fig. 4 is a schematic diagram of bandwidth parts according to an embodiment of the present application.

10 Fig. 5 is a schematic flowchart of an approach for determining a bandwidth part according to an embodiment of the present application.

Fig. 6 is a schematic flowchart of an approach for determining a bandwidth part according to an embodiment of the present application.

15 Fig. 7 is a schematic diagram of bandwidth parts according to an embodiment of the present application.

Fig. 8 is a schematic diagram of bandwidth parts according to an embodiment of the present application.

FIG. 9 is a schematic flowchart of a data transmission method according to an embodiment of the present application.

20 FIG. 10 is a schematic block diagram of a terminal device according to an embodiment of the present application.

FIG. 11 is a schematic block diagram of a network device according to an embodiment of the present application.

25 FIG. 12 is a schematic structural diagram of a terminal device according to an embodiment of the present application.

FIG. 13 is a schematic structural diagram of a network device according to an embodiment of the present application.

FIG. 14 is a schematic structural diagram of a system chip according to an embodiment of the present application.

30

Detailed Description

Hereinafter, technical solutions in the embodiments of the present application will be described with reference to the accompanying drawings.

It should be understood that the technical solutions of the embodiments of the present application may be applied to various communication systems, such as a Global System of Mobile Communication (GSM) system, a Code Division Multiple Access (CDMA) system, a Wideband Code Division Multiple Access (WCDMA) system, a Long Term Evolution (LTE) system, a LTE Frequency Division Duplex (FDD) system, a LTE Time Division Duplex (TDD) system, a Universal Mobile Telecommunication System (UMTS), and a future 5G communication system.

Various embodiments are described herein in connection with terminal devices in the present application. The terminal device may also refer to a User Equipment (UE), an access terminal, a subscriber unit, a subscriber station, a mobile station, a mobile platform, a remote station, a remote terminal, a mobile device, a user terminal, a terminal, a wireless communication device, a user agent, or a user apparatus. The access terminal may be a cellular phone, a cordless phone, a Session Initiation Protocol (SIP) phone, a Wireless Local Loop (WLL) station, a Personal Digital Assistant (PDA), a handheld device with a wireless communication function, a computing device or other processing device connected to a wireless modem, an on-board device, a wearable device, a terminal device in a future 5G network, or a terminal device in a future evolving Public Land Mobile Network (PLMN), etc.

Various embodiments are described herein in connection with network devices in the present application. A network device may be a device for communicating with a terminal device, such as a Base Transceiver Station (BTS) in a GSM system or CDMA, a NodeB (NB) in a WCDMA system, or an Evolutional Node B (eNB or eNodeB) in a LTE system, or the network device may be a relay station, an access point, a vehicle-mounted device, a wearable device, a network side device in a future 5G network, or a network side device in a future evolved PLMN network, etc.

FIG. 1 is a schematic diagram of an application scenario according to an embodiment of the present application. The communication system in FIG. 1 may include a network device 10 and a terminal device 20. The network device 10 is used for providing communication services for the terminal device 20 and is connected to a core network. The terminal device 20 may access the network by searching for a synchronization signal, or a broadcast signal, etc., sent by

the network device 10, to communicate with the network. Arrows shown in FIG. 1 may represent uplink/downlink transmission through cellular links between the terminal device 20 and the network device 10.

The network in the embodiment of the present application may refer to a Public Land Mobile Network (PLMN) or a Device-to-Device (D2D) network or a Machine-to-Machine/man (M2M) network or other networks. FIG. 1 is a simplified schematic diagram of an example, and other terminal devices may be included in the network and are not shown in FIG. 1.

In a 5G New Radio (NR) system, the system bandwidth may reach hundreds of MHz or even several GHz. However, when the terminal device works, it does not always need such a large bandwidth. For example, when transmitting at a low data rate, the terminal device only needs to adopt a small working bandwidth. Therefore, a concept of Bandwidth Part (BWP) is proposed. After a network device configures a BWP to a terminal device, the terminal device only needs to send and receive data within the BWP, thus effectively reducing power consumption of the terminal device during low data rate transmission.

A synchronization channel in the 5G system is transmitted in a form of a Synchronization Signal (SS) Block, and each SS Block includes a Primary Synchronization Signal (PSS), a Secondary Synchronization Signal (SSS), a Physical Broadcast Channel (PBCH) signal, etc. In a LTE system, PSS, SSS and PBCH are always located in a central position of the system bandwidth. But in the 5G system, the position of the SS Block in the system bandwidth is not fixed, but is flexibly configured by the network device according to deployment requirements. It brings about a problem, for example, when a terminal device performs a Radio Resource Management (RRM) measurement, signals from different cells, such as the SS Blocks, may be located in different frequency positions, so the terminal device needs to measure signals from different cells in different frequency positions. If the different frequency positions of signals from different cells differ greatly in the frequency domain, for example, as shown in FIG. 2, SS Blocks of different cells (e.g., cell 1, cell 2, cell 3, and cell 4) are located in different frequency positions respectively, the terminal needs to adopt a large reception bandwidth to receive the SS Blocks of all cells simultaneously. In such case, BWP configured for data transmission by the network device to the terminal device may not meet requirements for the terminal device to perform the RRM measurement.

According to the embodiment of the present application, two different bandwidth parts are respectively configured for the terminal device based on different requirements for the terminal device to perform the data transmission and the RRM measurement, and the terminal device

uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

FIG. 3 is a schematic flowchart of a data transmission method according to an embodiment of the present application. The method shown in the FIG. 3 may be performed by a terminal device which may be, for example, the terminal device 20 shown in FIG. 1. As shown in FIG. 3, the data transmission method includes the following acts 310 and 320.

In 310, a terminal device determines a first bandwidth part and a second bandwidth part.

In 320, the terminal device performs data transmission and a radio resource management (RRM) measurement on a specific time domain resource by using the first bandwidth part, and performs the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

Specifically, the first bandwidth part (first BWP) and the second bandwidth part (second BWP) are both bandwidth parts for data transmission performed by the terminal device, and the first bandwidth part is further used for the terminal device to perform the RRM measurement, for example, measurement is performed on an SS block and/or a reference signal from a cell to be measured, and the reference signal may be, e.g., a channel state indication reference signal (CSI-RS). After determining the first bandwidth part and the second bandwidth part, the terminal device may perform the data transmission and the RRM measurement on the specific time domain resource by using the first bandwidth part, and perform the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

Optionally, the specific time domain resource includes a plurality of time domain resources distributed according to a time periodicity.

Further, optionally, the time periodicity is a time periodicity for the terminal device to perform the RRM measurement. That is, the terminal device may perform the RRM measurement according to the time periodicity.

For example, as shown in FIG. 4, the terminal device performs the data transmission and the RRM measurement on the plurality of time domain resources distributed according to the time periodicity by using the first bandwidth part, and performs the data transmission on other

time domain resources by using the second bandwidth part.

Therefore, the terminal device determines two different transmission bandwidths, and uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

It should be understood that in the embodiment of the present application, when the terminal device performs data transmission with the network device on the first bandwidth part and the second bandwidth part, the transmitted data may include service data, signaling data or other types of data, which are not limited here. The data transmission may include receiving by the terminal device the data sent by the network device or sending by the terminal device the data to the network device.

In 310, specifically the terminal device may determine the first bandwidth part and the second bandwidth part in the following two modes.

Mode 1

Optionally, as shown in FIG. 5, act 310 may include acts 311 and 312.

In 311, the terminal device receives first configuration information and second configuration information sent by a network device.

Herein the first configuration information includes bandwidth information about the first bandwidth part, and the second configuration information includes bandwidth information about the second bandwidth part.

In 312, the terminal device determines the first bandwidth part according to the first configuration information, and determines the second bandwidth part according to the second configuration information.

Specifically, the first configuration information and the second configuration information are configured by the network device and indicated to the terminal device through the first configuration information and the second configuration information. The terminal device may determine the first bandwidth part according to the received first configuration information and determine the second bandwidth part according to the received second configuration information.

Mode 2

Optionally, as shown in FIG. 6, act 310 may include acts 313 to 315.

In 313, the terminal device receives second configuration information and third configuration information sent by a network device.

5 Herein, the second configuration information includes bandwidth information about the second bandwidth part, and the third configuration information includes information about a frequency band occupied by at least one signal to be measured by the terminal device in the RRM measurement.

10 In 314, the terminal device determines the second bandwidth part according to the second configuration information, and determines a third bandwidth part according to the third configuration information, wherein the third bandwidth part includes the frequency band occupied by the at least one signal.

In 315, the terminal device determines the first bandwidth part according to the second bandwidth part and the third bandwidth part.

15 Specifically, the network device may send the second configuration information to the terminal device, so that the terminal device determines the second bandwidth part according to the second configuration information. In this case, the network device may send third configuration information to the terminal device, wherein the third configuration information includes information about the frequency band occupied by the at least one signal to be
20 measured by the terminal device in the RRM measurement process, so that the terminal device determines the third bandwidth part including the frequency band occupied by the at least one signal according to the third configuration information. The at least one signal may include, for example, an SS Block and/or CSI-RS of at least one cell to be measured by the terminal device. The terminal device ultimately determines the first bandwidth part according to the second
25 bandwidth part and the third bandwidth part jointly.

Optionally, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the second bandwidth part may at least partially overlap with the third bandwidth part, or may not overlap with the third bandwidth part.

30 For example, if the second bandwidth part is within the third bandwidth part, that is, the third bandwidth part includes the second bandwidth part, then the third bandwidth part may be determined as the first bandwidth part, e.g., the schematic diagram of the bandwidth parts shown in FIG. 7. Taking cell 1, cell 2, cell 3 and cell 4 as an example, SS blocks sent by

different cells are located in different frequency bands respectively. The third bandwidth part is a continuous frequency domain resource and includes frequency bands occupied by the SS blocks sent by the four cells, and the second bandwidth part configured by the network device for data transmission of the terminal device is located within a range of the third bandwidth part, then the terminal device may determine the third bandwidth part as the first bandwidth part.

For example, if the second bandwidth part does not overlap with the third bandwidth part, then the first bandwidth part should at least include the second bandwidth part and the third bandwidth part, e.g., the schematic diagram of the bandwidth parts shown in FIG. 8. Taking cell 1, cell 2, cell 3 and cell 4 as an example, SS blocks sent by different cells are located in different frequency bands respectively, and the second bandwidth part and the third bandwidth part do not overlap at all, then a range of the first bandwidth part spans the second bandwidth part and the third bandwidth part, that is, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the first bandwidth part is a continuous domain frequency resource.

Of course, the first bandwidth part may include a discontinuous frequency domain resource, for example, the first bandwidth part may only include the second bandwidth part and the third bandwidth part shown in FIG. 8.

It is assumed in the above that the terminal device can acquire information about the frequency band occupied by at least one signal to be measured, so that the terminal device determines the first bandwidth part according to the third bandwidth part and the second bandwidth part. However, if the terminal device cannot accurately acquire the information about the frequency band occupied by the at least one signal to be measured, then, optionally, the terminal device may take the whole system bandwidth as the first bandwidth part, thus ensuring that the signals of all cells to be measured can be effectively measured.

Optionally, the above bandwidth information may include at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

For example, the terminal device may determine the center frequency, the bandwidth size, the subcarrier spacing, etc. of the first bandwidth part according to the bandwidth information about the first bandwidth part. The terminal device may determine the center frequency, the bandwidth size, the subcarrier spacing, etc. of the second bandwidth part according to the bandwidth information about the second bandwidth part.

It should be understood that the Bandwidth Part (BWP) in the embodiment of the present

application may also be referred to as a transmission bandwidth, bandwidth segment, bandwidth configuration, etc., and the system bandwidth may include a plurality of BWPs. Different bandwidth parts may have different bandwidth sizes and/or center frequencies, and numerologies for data transmission, such as subcarrier spacing, in different bandwidth parts
 5 may also be different.

FIG. 9 is a schematic flowchart of a data transmission method according to an embodiment of the present application. The method shown in the FIG. 9 may be performed by a network device which may be, for example, the network device 10 shown in the FIG. 1. As shown in FIG. 9, the data transmission method includes the following acts 910 and 920.

10 In 910, a network device sends first configuration information or third configuration information to a terminal device, wherein the first configuration information includes bandwidth information about a first bandwidth part, the third configuration information includes information about a frequency band occupied by at least one signal to be sent for the terminal device to perform a radio resource management (RRM) measurement, and the first
 15 configuration information and the third configuration information are used for the terminal device to determine the first bandwidth part, so that the terminal device performs data transmission and the RRM measurement on a specific time domain resource by using the first bandwidth part.

In 920, the network device sends second configuration information to the terminal device,
 20 wherein the second configuration information includes bandwidth information about the second bandwidth part, so that the terminal device performs the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

That is, the network device may configure different second bandwidth parts for different terminal devices according to deployment requirements, and indicate the second bandwidth
 25 parts to the terminal devices through the second configuration information. In this case, the network device may further determine a third bandwidth part according to a frequency band occupied by at least one signal sent by a plurality of cells for the terminal device to perform the RRM measurement, and finally the network device determines the first bandwidth part according to the second bandwidth part and the third bandwidth part jointly, and indicates the
 30 first bandwidth part to the terminal device through the first configuration information. Optionally, the network device may not send the first configuration information, but indicate the information about the frequency band occupied by the at least one signal to the terminal device through the third configuration information, so that the terminal device itself determines

the first bandwidth part according to the third configuration information and the second configuration information.

Therefore, the network device configures two different bandwidth parts for the terminal device based on different requirements for the terminal device to perform the data transmission and the RRM measurement, so that the terminal device uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

Optionally, if the network device sends the first configuration information to the terminal device, the method further includes: the network device determines a third bandwidth part according to the information about the frequency band occupied by the at least one signal to be sent for the terminal device to perform the RRM measurement, wherein the third bandwidth part includes the frequency band occupied by the at least one signal; and the network device determines the first bandwidth part according to the second bandwidth part and the third bandwidth part.

Optionally, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

Optionally, the first bandwidth part includes a whole system bandwidth.

Optionally, the bandwidth information includes at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

Optionally, the specific time domain resource includes a plurality of time domain resources distributed according to a time periodicity.

Optionally, the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

Optionally, the at least one signal to be sent for the terminal device to perform the RRM measurement includes a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

It should be understood that a detailed process for the network device to determine the first bandwidth part and the second bandwidth part may refer to the relevant descriptions of the terminal device in FIG. 3 to 8, and will not be described repeatedly here for the sake of brevity.

It should be understood that in various embodiments of the present invention, values of sequence numbers in the processes described above do not indicate an order of execution, and the order of execution of various processes should be determined by their functions and internal logics, and should not constitute any limitation on implementation processes of embodiments of the present application.

FIG. 10 is a schematic block diagram of a terminal device 1000 according to an embodiment of the present application. As shown in FIG. 10, the terminal device 1000 includes a determination unit 1010 and a transceiving unit 1020.

Herein, the determination unit 1010 is used for determining a first bandwidth part and a second bandwidth part.

The transceiving unit 1020 is used for performing data transmission and a radio resource management (RRM) measurement on a specific time domain resource by using the first bandwidth part, and performing the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

Therefore, the terminal device determines two different transmission bandwidths, and uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

Optionally, the transceiving unit 1020 is further used for receiving first configuration information and second configuration information sent by a network device, wherein the first configuration information includes bandwidth information about the first bandwidth part, and the second configuration information includes bandwidth information about the second bandwidth part.

The determining unit 1010 is specifically used for determining the first bandwidth part according to the first configuration information, and determining the second bandwidth part according to the second configuration information.

Optionally, the transceiving unit 1020 is further used for receiving second configuration information and third configuration information sent by a network device, wherein the second configuration information includes bandwidth information about the second bandwidth part, and the third configuration information includes information about a frequency band occupied

by at least one signal to be measured by the terminal device in the RRM measurement.

The determining unit 1010 is specifically used for determining the second bandwidth part according to the second configuration information, and determining a third bandwidth part according to the third configuration information, wherein the third bandwidth part includes the frequency band occupied by the at least one signal; and determining the first bandwidth part according to the second bandwidth part and the third bandwidth part.

Optionally, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

Optionally, the first bandwidth part includes a whole system bandwidth.

Optionally, the bandwidth information includes at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

Optionally, the specific time domain resource includes a plurality of time domain resources distributed according to a time periodicity.

Optionally, the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

Optionally, the at least one signal to be measured by the terminal device in the RRM measurement includes a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

FIG. 11 is a schematic block diagram of a network device 1100 according to an embodiment of the present application. As shown in FIG. 11, the network device 1100 includes a transceiving unit 1110, used for: sending first configuration information or third configuration information to a terminal device, wherein the first configuration information includes bandwidth information about a first bandwidth part, the third configuration information includes information about a frequency band occupied by at least one signal to be sent for the terminal device to perform a radio resource management (RRM) measurement, and the first configuration information and the third configuration information are used for the terminal device to determine the first bandwidth part, so that the terminal device performs data transmission and the RRM measurement on a specific time domain resource by using the first bandwidth part; and sending second configuration information to the terminal device, wherein the second configuration information includes bandwidth information about the second bandwidth part, so that the terminal device performs the data transmission on other time domain

resources than the specific time domain resource by using the second bandwidth part.

Therefore, the network device configures two different bandwidth parts for the terminal device based on different requirements for the terminal device to perform the data transmission and the RRM measurement, so that the terminal device uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

Optionally, the network device further includes a determination unit 1120, used for determining a third bandwidth part according to the information about the frequency band occupied by the at least one signal to be sent for the terminal device to perform the RRM measurement, wherein the third bandwidth part includes the frequency band occupied by the at least one signal; and determining the first bandwidth part according to the second bandwidth part and the third bandwidth part.

Optionally, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

Optionally, the first bandwidth part includes a whole system bandwidth.

Optionally, the bandwidth information includes at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

Optionally, the specific time domain resource includes a plurality of time domain resources distributed according to a time periodicity.

Optionally, the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

Optionally, the at least one signal to be sent for the terminal device to perform the RRM measurement includes a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

FIG. 12 is a schematic structural diagram of a terminal device 1200 according to an embodiment of the present application. As shown in FIG. 12, the terminal device includes a processor 1210, a transceiver 1220, and a memory 1230, wherein the processor 1210, the transceiver 1220, and the memory 1230 communicate with each other through an internal connection path. The memory 1230 is used for storing instructions, and the processor 1210 is

used for executing instructions stored in the memory 1230 to control the transceiver 1220 to send or receive signals.

Herein, the processor 1210 is used for determining a first bandwidth part and a second bandwidth part.

5 The transceiver 1220 is used for performing data transmission and a radio resource management (RRM) measurement on a specific time domain resource by using the first bandwidth part, and performing the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

10 Therefore, the terminal device determines two different transmission bandwidths, and uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part and simultaneously meet the requirement of the RRM measurement.

15 Optionally, the transceiver 1220 is further used for receiving first configuration information and second configuration information sent by a network device, wherein the first configuration information includes bandwidth information about the first bandwidth part, and the second configuration information includes bandwidth information about the second bandwidth part.

20 The processor 1210 is specifically used for determining the first bandwidth part according to the first configuration information, and determining the second bandwidth part according to the second configuration information.

25 Optionally, the transceiver 1220 is further used for receiving second configuration information and third configuration information sent by a network device, wherein the second configuration information includes bandwidth information about the second bandwidth part, and the third configuration information includes information about a frequency band occupied by at least one signal to be measured by the terminal device in the RRM measurement.

30 The processor 1210 is specifically used for determining the second bandwidth part according to the second configuration information, and determining a third bandwidth part according to the third configuration information, wherein the third bandwidth part includes the frequency band occupied by the at least one signal; and determining the first bandwidth part according to the second bandwidth part and the third bandwidth part.

Optionally, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

Optionally, the first bandwidth part includes a whole system bandwidth.

5 Optionally, the bandwidth information includes at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

Optionally, the specific time domain resource includes a plurality of time domain resources distributed according to a time periodicity.

10 Optionally, the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

Optionally, the at least one signal to be measured by the terminal device in the RRM measurement includes a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

15 It should be understood that, in an embodiment of the present application, the processor 1210 may be a central processing unit (CPU), or the processor 1210 may be other general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, a discrete gate or a transistor logic device, or a discrete hardware component, etc. The general purpose processor may be a microprocessor, or the processor may be any conventional
20 processor or the like.

The memory 1230 may include a read only memory and a random access memory, and provide instructions and data to the processor 1210. A portion of the memory 1230 may include a non-volatile random access memory.

25 In an implementation process, the acts of the methods described above may be accomplished by integrated logic circuits of hardware in the processor 1210 or instructions in a form of software. The acts of the positioning method disclosed in the embodiment of the present application may be directly accomplished by an execution of a hardware processor or accomplished by a combination of hardware and software modules in the processor 1210. The software modules may be located in a storage medium commonly used in the art, such as a
30 random access memory, flash memory, read-only memory, programmable read-only memory or electrically erasable programmable memory, or register. The storage medium is located in the memory 1230, and the processor 1210 reads the information in the memory 1230 and

accomplishes the acts of the above method in combination with its hardware. In order to avoid repetition, it will not be described in detail here.

The terminal device 1200 according to the embodiment of the present application may correspond to the terminal device for executing the method 300 in the method 300 and the terminal device 1000 according to the embodiment of the present application, and various units or modules in the terminal device 1200 are respectively used for executing various actions or processing processes executed by the terminal device in the method 300. Here, in order to avoid redundancy, detailed description thereof is omitted.

FIG. 13 is a schematic structural diagram of a network device 1300 according to an embodiment of the present application. As shown in FIG. 13, the network device includes a processor 1310, a transceiver 1320, and a memory 1330, wherein the processor 1310, the transceiver 1320, and the memory 1330 communicate with each other through an internal connection path. The memory 1330 is used for storing instructions, and the processor 1310 is used for executing instructions stored in the memory 1330 to control the transceiver 1320 to send or receive signals.

The transceiver 1320 is used for sending first configuration information or third configuration information to a terminal device, wherein the first configuration information includes bandwidth information about a first bandwidth part, the third configuration information includes information about a frequency band occupied by at least one signal to be sent for the terminal device to perform a radio resource management (RRM) measurement, and the first configuration information and the third configuration information are used for the terminal device to determine the first bandwidth part, so that the terminal device performs data transmission and the RRM measurement on a specific time domain resource by using the first bandwidth part; and sending second configuration information to the terminal device, wherein the second configuration information includes bandwidth information about the second bandwidth part, so that the terminal device performs the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

Therefore, the network device configures two different bandwidth parts for the terminal device based on different requirements for the terminal device to perform the data transmission and the RRM measurement, so that the terminal device uses different bandwidth parts when performing different operations. Since the bandwidth part used for the data transmission and RRM measurement is different from the bandwidth part used for data transmission only, the terminal device can effectively perform data transmission in the corresponding bandwidth part

and simultaneously meet the requirement of the RRM measurement.

Optionally, the processor 1310 is used for determining a third bandwidth part according to the information about the frequency band occupied by the at least one signal to be sent for the terminal device to perform the RRM measurement, wherein the third bandwidth part includes the frequency band occupied by the at least one signal; and determining the first bandwidth part according to the second bandwidth part and the third bandwidth part.

Optionally, the first bandwidth part includes the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

Optionally, the first bandwidth part includes a whole system bandwidth.

Optionally, the bandwidth information includes at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

Optionally, the specific time domain resource includes a plurality of time domain resources distributed according to a time periodicity.

Optionally, the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

Optionally, the at least one signal to be sent for the terminal device to perform the RRM measurement includes a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

It should be understood that in the embodiment of the present application, the processor 1310 may be a central processing unit (CPU), or the processor 1310 may be other general purpose processor, a digital signal processors (DSP), an application specific integrated circuit (ASIC), a field programmable gate arrays (FPGA) or other programmable logic device, discrete gate or transistor logic device, a discrete hardware component, etc. The general purpose processor may be a microprocessor or the processor may be any conventional processor or the like.

The memory 1330 may include a read only memory and a random access memory, and provide instructions and data to the processor 1310. A portion of memory 1330 may include a non-volatile random access memory. In an implementation process, the acts of the methods described above may be accomplished by integrated logic circuits of hardware in the processor 1310 or instructions in a form of software. The acts of the positioning method disclosed in the embodiment of the present application may be directly accomplished by an execution of a

hardware processor or accomplished by a combination of hardware and software modules in the processor 1310. The software modules may be located in a storage medium commonly used in the art, such as a random access memory, flash memory, read-only memory, programmable read-only memory or electrically erasable programmable memory, or register. The storage
5 medium is located in the memory 1330, and the processor 1310 reads the information in the memory 1330 and accomplishes the acts of the above method in combination with its hardware. In order to avoid repetition, it will not be described in detail here.

The network device 1300 according to the embodiment of the present application may correspond to the network device for executing the method 900 in the method 900 and the
10 network device 1100 according to the embodiment of the present application, and various units or modules in the network device 1300 are respectively used for executing various actions or processing processes executed by the network device in the method 900. Here, in order to avoid redundancy, detailed description thereof is omitted.

FIG. 14 is a schematic structural diagram of a system chip according to an embodiment of
15 the present application. The system chip 1400 of FIG. 14 includes an input interface 1401, an output interface 1402, at least one processor 1403, and a memory 1404. The input interface 1401, the output interface 1402, the processor 1403, and the memory 1404 are connected to each other through an internal connection path. The processor 1403 is used for executing codes in the memory 1404.

20 Optionally, the processor 1403 may implement the method 400 executed by the terminal device in the method embodiment when the codes are executed. For the sake of brevity, it will not be repeated here.

Optionally, the processor 1403 may implement the method 900 executed by the network
25 device in the method embodiment when the codes are executed. For the sake of brevity, it will not be repeated here.

Those of ordinary skill in the art will recognize that the exemplary units and algorithm acts described in connection with the embodiments disclosed herein may be implemented in electronic hardware, or a combination of computer software and electronic hardware. Whether these functions are implemented in hardware or software depends on a specific application and
30 design constraint of the technical solution. Skilled in the art may use different manners to realize the described functions for each particular application, but such realization should not be considered to be beyond the scope of the present application.

Those skilled in the art may clearly understand that for convenience and conciseness of description, the specific working process of the system, device and unit described above may refer to the corresponding process in the aforementioned embodiments of methods, and details are not described herein again.

5 In several embodiments provided by the present application, it should be understood that the disclosed systems, apparatuses and methods may be implemented in other ways. For example, the apparatus embodiment described above is only illustrative, for example, the division of the unit is only a logical function division, and there may be other ways of division in actual implementation, for example, multiple units or components may be combined or
10 integrated into another system, or some features may be ignored or not executed. On the other hand, the mutual coupling or direct coupling or communication connection shown or discussed may be indirect coupling or communication connection through some interfaces, devices or units, and may be in electrical, mechanical or other forms.

15 The unit described as a separate component may or may not be physically separated, and the component shown as a unit may or may not be a physical unit, i.e., may be located in one place or may be distributed over multiple network units. Some or all of the units may be selected according to practical needs to achieve a purpose of the solution of the embodiments.

20 In addition, various functional units in various embodiments of the present application may be integrated in one monitoring unit, or various units may be physically present separately, or two or more units may be integrated in one unit.

25 The functions may be stored in a computer readable storage medium if implemented in a form of software functional units and sold or used as a separate product. Based on this understanding, the technical solution of the present application, in essence, or the part contributing to the existing art, or the part of the technical solution, may be embodied in the form of a software product stored in a storage medium, including several instructions for causing a computer device (which may be a personal computer, a server, or a network device, etc.) to perform all or part of the acts of the methods described in various embodiments of the present application. The aforementioned storage medium includes various media capable of
30 storing program codes, such as a U disk, a mobile hard disk, a read-only memory (ROM), a random access memory (RAM), a magnetic disk, or an optical disk.

What are described above are merely exemplary embodiments of the present application, but the protection scope of the present application is not limited thereto. Any variation or substitution that may be easily conceived by a person skilled in the art within the technical

scope disclosed by the present application shall be included within the protection scope of the present application. Therefore, the protection scope of the embodiments of the present application should be based on the protection scope of the claims.

Claims:

1. A data transmission method, comprising:

determining, by a terminal device, a first bandwidth part and a second bandwidth part;

performing, by the terminal device, data transmission and a radio resource management (RRM) measurement on a specific time domain resource by using the first bandwidth part, and performing the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

2. The method according to claim 1, wherein determining, by the terminal device, the first bandwidth part and the second bandwidth part, comprises:

receiving, by the terminal device, first configuration information and second configuration information sent by a network device, wherein the first configuration information comprises bandwidth information about the first bandwidth part, and the second configuration information comprises bandwidth information about the second bandwidth part;

determining, by the terminal device, the first bandwidth part according to the first configuration information, and determining the second bandwidth part according to the second configuration information.

3. The method according to claim 1, wherein determining, by the terminal device, the first bandwidth part and the second bandwidth part, comprises:

receiving, by the terminal device, second configuration information and third configuration information sent by a network device, wherein the second configuration information comprises bandwidth information about the second bandwidth part, and the third configuration information comprises information about a frequency band occupied by at least one signal to be measured by the terminal device in the RRM measurement;

determining, by the terminal device, the second bandwidth part according to the second configuration information, and determining a third bandwidth part according to the third configuration information, wherein the third bandwidth part comprises the frequency band occupied by the at least one signal;

determining, by the terminal device, the first bandwidth part according to the second bandwidth part and the third bandwidth part.

4. The method according to claim 3, wherein the first bandwidth part comprises the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially

overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

5. The method according to any one of claims 1-4, wherein the first bandwidth part comprises a whole system bandwidth.

6. The method according to any one of claims 1-5, wherein the bandwidth information
5 comprises at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

7. The method according to any one of claims 1-6, wherein the specific time domain resource comprises a plurality of time domain resources distributed according to a time periodicity.

8. The method according to claim 7, wherein the time periodicity is a time periodicity for
10 the terminal device to perform the RRM measurement.

9. The method according to any one of claims 1-8, wherein at least one signal to be measured by the terminal device in the RRM measurement comprises a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

15 10. A data transmission method, comprising:

sending, by a network device, first configuration information or third configuration information to a terminal device, wherein the first configuration information comprises bandwidth information about a first bandwidth part, the third configuration information comprises information about a frequency band occupied by at least one signal to be sent for the
20 terminal device to perform a radio resource management (RRM) measurement, and the first configuration information and the third configuration information are used for the terminal device to determine the first bandwidth part to enable the terminal device to perform data transmission and the RRM measurement on a specific time domain resource by using the first bandwidth part;

25 sending, by the network device, second configuration information to the terminal device, wherein the second configuration information comprises bandwidth information about a second bandwidth part, to enable the terminal device to perform the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

11. The method according to claim 10, wherein if the network device sends the first
30 configuration information to the terminal device, the method further comprises:

determining, by the network device, a third bandwidth part according to the information

about the frequency band occupied by the at least one signal to be sent for the terminal device to perform the RRM measurement, wherein the third bandwidth part comprises the frequency band occupied by the at least one signal;

5 determining, by the network device, the first bandwidth part according to the second bandwidth part and the third bandwidth part.

12. The method according to claim 11, wherein the first bandwidth part comprises the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

10 13. The method according to any one of claims 10-12, wherein the first bandwidth part comprises a whole system bandwidth.

14. The method according to any one of claims 10-13, wherein the bandwidth information comprises at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

15 15. The method according to any one of claims 10-14, wherein the specific time domain resource comprises a plurality of time domain resources distributed according to a time periodicity.

16. The method according to claim 15, wherein the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

20 17. The method according to any one of claims 10-16, wherein the at least one signal to be sent for the terminal device to perform the RRM measurement comprises a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

18. A terminal device, comprising:

25 a determination unit, used for determining a first bandwidth part and a second bandwidth part;

a transceiving unit, used for performing data transmission and a radio resource management (RRM) measurement on a specific time domain resource by using the first bandwidth part, and performing the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

30 19. The terminal device according to claim 18, wherein the transceiving unit is further used for:

receiving first configuration information and second configuration information sent by a network device, wherein the first configuration information comprises bandwidth information about the first bandwidth part, and the second configuration information comprises bandwidth information about the second bandwidth part;

5 wherein the determination unit is specifically used for:

determining the first bandwidth part according to the first configuration information, and determining the second bandwidth part according to the second configuration information.

20. The terminal device according to claim 18, wherein the transceiving unit is further used for:

10 receiving second configuration information and third configuration information sent by a network device, wherein the second configuration information comprises bandwidth information about the second bandwidth part, and the third configuration information comprises information about a frequency band occupied by at least one signal to be measured by the terminal device in the RRM measurement;

15 wherein the determination unit is specifically used for:

determining the second bandwidth part according to the second configuration information, and determining a third bandwidth part according to the third configuration information, wherein the third bandwidth part comprises the frequency band occupied by the at least one signal;

20 determining the first bandwidth part according to the second bandwidth part and the third bandwidth part.

21. The terminal device according to claim 20, wherein the first bandwidth part comprises the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth
25 part.

22. The terminal device according to any one of claims 18-21, wherein the first bandwidth part comprises a whole system bandwidth.

23. The terminal device according to any one of claims 18-22, wherein the bandwidth information comprises at least one of: a center frequency, a bandwidth size, and a subcarrier
30 spacing.

24. The terminal device according to any one of claims 18-23, wherein the specific time

domain resource comprises a plurality of time domain resources distributed according to a time periodicity.

25. The terminal device according to claim 24, wherein the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

5 26. The terminal device according to any one of claims 18-25, wherein at least one signal to be measured by the terminal device in the RRM measurement comprises a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.

27. A network device, comprising:

10 a transceiving unit, used for sending first configuration information or third configuration information to a terminal device, wherein the first configuration information comprises bandwidth information about a first bandwidth part, the third configuration information comprises information about a frequency band occupied by at least one signal to be sent for the terminal device to perform a radio resource management (RRM) measurement, and the first
15 configuration information and the third configuration information are used for the terminal device to determine the first bandwidth part to enable the terminal device to perform data transmission and the RRM measurement on a specific time domain resource by using the first bandwidth part;

20 wherein the transceiving unit is further used for sending second configuration information to the terminal device, wherein the second configuration information comprises bandwidth information about the second bandwidth part, to enable the terminal device to perform the data transmission on other time domain resources than the specific time domain resource by using the second bandwidth part.

25 28. The network device according to claim 27, further comprising a determination unit, used for:

determining a third bandwidth part according to the information about the frequency band occupied by the at least one signal to be sent for the terminal device to perform the RRM measurement, wherein the third bandwidth part comprises the frequency band occupied by the at least one signal;

30 determining the first bandwidth part according to the second bandwidth part and the third bandwidth part.

29. The network device according to claim 28, wherein the first bandwidth part comprises

the second bandwidth part and the third bandwidth part, and the second bandwidth part at least partially overlaps with the third bandwidth part, or does not overlap with the third bandwidth part.

5 30. The network device according to any one of claims 27-29, wherein the first bandwidth part comprises a whole system bandwidth.

31. The network device according to any one of claims 27-30, wherein the bandwidth information comprises at least one of: a center frequency, a bandwidth size, and a subcarrier spacing.

10 32. The network device according to any one of claims 27-31, wherein the specific time domain resource comprises a plurality of time domain resources distributed according to a time periodicity.

33. The network device according to claim 32, wherein the time periodicity is a time periodicity for the terminal device to perform the RRM measurement.

15 34. The network device according to any one of claims 27-33, wherein the at least one signal to be sent for the terminal device to perform the RRM measurement comprises a synchronization signal (SS) block and/or a channel state indication reference signal (CSI-RS) of at least one cell to be measured.