

DESCRIPTION

OPTICAL DEVICE

TECHNICAL FIELD

[0001] The present invention relates to an optical device,
5 and more particularly to an optical device that includes a
lightguide.

BACKGROUND ART

[0002] Currently, there are high production costs for the
production tools for large-sized lightguides of about 0.5 to
10 1 m^2 (square meters) or larger, and their associated light
distribution structures. The cost per master fabrication
tool item (approximately 1 m^2 of surface coverage) is beyond
acceptable levels. When one takes into account having to
form patterns on the entire surface of the lightguide through
15 molding or the like, and mass production thereof, the process
is challenging. For this reason, highly efficient and
advanced optical solutions that provide higher optical power,
lower power consumption, and improved performance have not
been realized.

20 [0003] One of the fundamental problems that occur when
light is in-coupled to a lightguide is a loss of light when
the angle of incidence is smaller than the critical angle of

the medium, i.e., at an angle that does not result in total reflection (angle of out-coupling). Light entering the interface between the lightguide and one or more adhesive layers at an angle smaller than the critical angle is not
5 controlled by any optical control structure provided in the lightguide. In this case, 5 to 15% of the light in-coupled to the lightguide passes through the adhesion layer, but such leakage of light is undesirable.

[0004] An example application of lightguides is the
10 application to transparent illumination devices. Transparent illumination devices are becoming an important solution in a variety of products, such as general illumination, window/facade illumination, reflection type/transmissive type display illumination, street signboards, and traffic signs.
15 The main challenges in realizing transparent solutions are (1) open structure of the surface relief optical pattern, (2) management of light distribution, (3) stray light control, and (4) high transparency. Among them, (1) open structure exposing the surface optical pattern is not realistic for
20 practical industrial applications because of the risk of soiling, physical defects, etc. Regarding (2), depending on the optical requirements and specifications, the light distribution must be controlled without additional optical sheets, such as brightness-enhanced films, etc. In
25 transparent devices, an efficient light extraction

configuration is desirable because the insertion of an extra sheet may compromise transparency.

[0005] Regarding (3), in surface illumination for use in signboards (signage), displays involved with visual performances, etc., stray light in the direction of the line of sight must be minimized, to avoid a decrease in contrast. However, the optical pattern itself is a source of stray light due to light leakage and Fresnel reflections. Non-laminated devices also produce Fresnel-type stray light on the outer surface.

[0006] Regarding (4), optical transparency always depends on the shape and characteristics of the optical pattern and the visibility based on the presence or absence of ambient light. The larger the optical pattern, the easier it is to see; however, even small patterns become visible when the device is illuminated. In particular, when the pattern density is small, a bright spot is formed that produces stray light at the viewing angle.

[0007] Some of the above four challenges can be addressed by providing an antireflection (AR) film on the outer surface of the protection cover, but not all of them are solved; thus, this may not be a reliable solution for some applications. Cavity optical elements for transparent illumination have also been proposed, but no consideration

has been given to leakage of light (or stray light) control to ensure final quality and performance.

[0008] A configuration is known in which a layer alternating low-refractive index regions and high-refractive index regions is inserted between a light guide element and a reflective scatterer (see, for example, Patent Document 1).

CITATION LIST

PATENT LITERATURE

[0009]

Patent Document 1: Japanese National Phase PCT Laid-Open Publication No. 2015-534100 (International Publication No. 2014/031726)

SUMMARY OF INVENTION

TECHNICAL PROBLEM

[0010] In surface illumination for use in signboards (signage), displays involved with visual performances, etc., it is necessary to suppress a decrease in contrast, or improve visibility.

[0011] With respect to optical devices in general, if fingerprints, soil, or the like has adhered to the surface cover, light does not permeate over to the end of the light guiding layer due to scattering or loss of light, and sufficient light cannot be extracted in the direction of the

viewer's line of sight. As a result, contrast is reduced and visibility is reduced. A configuration is desired that can efficiently extract light and increase contrast or visibility while allowing light to permeate the entire light guiding
5 layer with a simple structure.

[0012] It is an objective of the present invention to provide an optical device that provides sufficient contrast or visibility in a simple configuration.

SOLUTION TO PROBLEM

10 [0013] In one implementation of the present invention, an optical device includes:

a light guiding layer;

a first optically functional layer provided on a first principal face of the light guiding layer;

15 a second optically functional layer provided on a second principal face of the light guiding layer that is on an opposite side to the first principal face; and

an optical medium layer provided on a surface of the second optically functional layer that is on an opposite side
20 to the light guiding layer, wherein

a refractive index of the first optically functional layer is lower than a refractive index of the light guiding layer.

ADVANTAGEOUS EFFECTS OF INVENTION

[0014] With the aforementioned configuration and approach, an optical device with high visibility is realized.

BRIEF DESCRIPTION OF DRAWINGS

[0015]

5 [FIG. 1A] A diagram illustrating the basic concept of an optical device according to an embodiment.

[FIG. 1B] A diagram illustrating the basic concept of an optical device according to an embodiment.

10 [FIG. 2A] A diagram showing an example configuration of an optical device according to a first embodiment.

[FIG. 2B] A diagram showing another example configuration of an optical device according to the first embodiment.

[FIG. 2C] A diagram showing another example configuration of an optical device according to the first embodiment.

15 [FIG. 2D] A diagram showing the effect of an optical device according to the first embodiment.

[FIG. 2E] A diagram showing an example application of an optical device according to the first embodiment.

20 [FIG. 2F] A diagram showing an example configuration of an optical device for the example application of FIG. 2E.

[FIG. 3A] A diagram describing problems to be solved by a second embodiment.

[FIG. 3B] A diagram showing an example configuration of an optical device according to the second embodiment.

[FIG. 3C] A diagram showing another example configuration of an optical device according to the second embodiment.

5 [FIG. 4] A diagram showing a method of forming a low-refractive index pattern on the lightguide surface.

[FIG. 5] A diagram showing a method of forming a low-refractive index pattern on the lightguide surface.

[FIG. 6A] An image of an optical device from which a low-
10 refractive index cladding is removed by laser ablation.

[FIG. 6B] An image of an optical device from which a low-refractive index cladding is removed by laser ablation.

[FIG. 7] A diagram showing the concept of a lightguide structure in which a light distribution filter (Light
15 Directing (Distributing) Filter; LDF) is used, and main functions of light control by the light distribution filter.

[FIG. 8A] A diagram showing an example configuration of a lightguide structure using a light distribution filter.

[FIG. 8B] A diagram showing an example configuration of a
20 lightguide structure using a light distribution filter.

[FIG. 9A] A diagram showing a hybrid pattern for light control in two directions.

[FIG. 9B] A diagram showing a hybrid pattern for light control in two directions.

[FIG. **10**] A diagram showing an optical pattern for two-directional light control.

[FIG. **11**] A diagram showing a hybrid pattern and a linear pattern, as examples of the pattern on the lightguide.

5 [FIG. **12**] A diagram showing simulation results for light distribution filter films.

[FIG. **13**] A diagram showing the concept of a signal lightguide for a sensor such as a finger sensor or a fingerprint sensor.

10 [FIG. **14**] A diagram showing the concept of a signal lightguide for a sensor such as a finger sensor or a fingerprint sensor.

[FIG. **15A**] A diagram showing a result of a fingerprint simulation at nine points.

15 [FIG. **15B**] A diagram showing a result of a fingerprint simulation at nine points.

[FIG. **16**] A diagram showing simulation results for different setups.

[FIG. **17A**] A diagram describing problems to be solved by a
20 third embodiment.

[FIG. **17B**] Shows an example configuration of an optical device including an in-coupling element according to the third embodiment.

[FIG. **17C**] A diagram showing another example configuration of an optical device including an in-coupling element according to the third embodiment.

[FIG. **17D**] A diagram showing an internal intensity
5 distribution of a lightguide integrated with an in-coupling element according to the third embodiment.

[FIG. **17E**] A diagram showing an internal intensity distribution of an optical device according to a comparative example.

10 [FIG. **17F**] A diagram showing an internal intensity distribution of an optical device according to another comparative example.

[FIG. **17G**] A diagram comparing conventional configurations and optical devices according to comparative examples and the
15 third embodiment with respect to their characteristics.

[FIG. **17H**] A diagram showing uniformity of transverse luminance when the in-coupling optics according to the third embodiment are used.

[FIG. **17I**] A diagram showing an example configuration
20 incorporating in-coupling cavities.

[FIG. **18A**] A diagram showing an example of a master fabrication process.

[FIG. **18B**] A diagram showing an example of a master fabrication process.

[FIG. **18C**] A diagram showing an example of a master fabrication process.

[FIG. **18D**] A diagram showing an example of a master fabrication process.

5 [FIG. **18E**] A diagram showing an example of a master fabrication process.

[FIG. **19**] A diagram showing an example solution for improving transparency of cavity optics.

[FIG. **20**] A diagram showing an example solution for improving
10 transparency of cavity optics.

[FIG. **21A**] A diagram showing an example of cavity lamination.

[FIG. **21B**] A diagram showing an example of cavity lamination.

[FIG. **22A**] An example air cavity configuration for stray light suppression.

15 [FIG. **22B**] An example air cavity configuration for stray light suppression.

[FIG. **22C**] An example air cavity configuration for stray light suppression.

[FIG. **22D**] An example air cavity configuration for stray
20 light suppression.

[FIG. **22E**] An example air cavity configuration for stray light suppression.

[FIG. **22F**] An example air cavity configuration for stray light suppression.

[FIG. **22G**] An example air cavity configuration for stray light suppression.

[FIG. **22H**] An example air cavity configuration for stray light suppression.

5 [FIG. **22I**] An example air cavity configuration for stray light suppression.

[FIG. **22J**] An example air cavity configuration for stray light suppression.

[FIG. **23**] A diagram describing the effect of stray light
10 suppression based on an antireflection film.

[FIG. **24**] A diagram describing the effect of stray light suppression based on an optical adhesive.

[FIG. **25**] A diagram showing the effect of stray light reduction based on air cavities.

15 [FIG. **26**] A diagram showing influences of stray light in a conventional configuration.

[FIG. **27**] A diagram showing the concept of window illumination with an antireflection film.

[FIG. **28**] A diagram showing the concept of window
20 illumination with an antireflection film.

[FIG. **29**] A diagram showing an example configuration of a detachable optical device.

[FIG. **30**] A diagram showing an example configuration of a detachable optical device.

DESCRIPTION OF EMBODIMENTS

[0016] According to embodiments, an optical device with an enhanced contrast or visibility is provided at a low cost and with a simple configuration. This optical device is applicable to frontlights, backlights, window/facade
5 illumination, signage, signal illumination, solar applications, decorative illumination, light shields, light masks, public/general illumination such as roof lighting, and the like.

[0017] In the following description, the term "optical
10 filter" refers to a device or a material used to change the spectral intensity distribution or the state of polarization of electromagnetic radiation that is incident thereupon. The filter may be involved in performing a variety of optical functions, selected from: transmission, reflection,
15 absorption, refraction, interference, diffraction, scattering, and polarization.

[0018] The expression "a number of" refers to any positive integer starting from 1, whereas the expression "a plurality of" refers to any positive integer starting from two 2.

20 [0019] The terms "first" and "second" are not intended to denote any order, quantity, or importance, but rather are used to merely distinguish one element from another.

[0020] The terms "optical" and "light" are largely utilized as synonyms unless explicitly stated otherwise, and

refer to electromagnetic radiation within a certain portion of the electromagnetic spectrum, preferably, but not limited to, visible light.

[0021] The term "carrier substrate" or "carrier element" generally refers to a flat, planar member composed of a substrate material generally constituting a layered structure.

[0022] In one implementation, an optical device incorporating an optically functional layer(s) is provided. An optically functional layer allows light to permeate over to the end of the light guiding layer, and efficiently extracts light in the direction of the line of sight. In the following description, depending on the situation where it is applied, an optically functional layer may also be referred to as a "light distribution filter (LDF)", an "optical filter layer", "orientation element", or the like. The optical functions of an optically functional layer include at least one of reflection, transmission, polarization, and refraction.

[0023] The optically functional layer is used to efficiently in-couple light to the inside of the light guiding layer, and may be realized in various forms, such as a low-refractive index layer, an air cavity, an antireflection film, a microlens, or the like.

[0024] The light guiding layer, i.e., a lightguide, is made of an optical polymer, a glass, or the like. The optically functional layer, which is formed on at least one surface or both surfaces of the lightguide, may be a transparent low-refractive index (R_i) filter, a total internal reflection (TIR) filter, or the like. These optical filters may be a) provided directly on a flat surface, b) laminated with an adhesive layer, or c) bonded by chemical surface treatment such as VUV (vacuum UV), atmospheric plasma treatment, or microwave assisted bonding, for example.

[0025] The thickness (h) of the optical filter is typically greater than the used wavelength ($h > \lambda$), e.g. 1 μ to 10 μ m. In one example configuration, the optical filter layer is made of a material having a lower refractive index (n_2) than the refractive index (n_1) of the material composing the light guiding layer. The range of the low-refractive index (n_2) value may be appropriately selected according to the application, e.g., not less than 1.05 and not more than 1.45, between 1.14 and 1.41, not more than 1.2, and so on. The optical filter may contain a nano-silica material in a mesoporous film. In that case, in order to maintain the refractive index value of the low R_i cladding, a low-(out) gassing material may be used to cover in between phases, to laminate, or to bond.

[0026] The optical filter may be implemented as a total internal reflection (TIR) solution based on available materials, such as TiO_2 , BaSO_4 , SiO_2 , Al_2O_3 , Al, Ag, dielectrics, high reflection (HR) coating materials, or the
5 like.

[0027] An optical device incorporating an optically functional layer(s) (or optical filter(s)) according to an embodiment may be fixedly attached to an optical medium including a poster, a reflection type display, an electronic
10 paper, a window glass, and the like (fixed type), or detachably attached to constitute signage, decorative displays, or the like (non-fixed type).

[0028] <basic concept>

FIG. **1A** and FIG. **1B** are schematic cross-sectional views
15 illustrating the basic concept of an optical device according to an embodiment. This basic concept is applicable to all embodiments to be described in detail below. In an optical device **100A** in FIG. **1A**, an optical medium layer **11**, an optical adhesion layer **19**, a low-refractive index layer **13** in
20 which optical apertures are made, a lightguide **14**, an uninterruptedly-extending low-refractive index layer **15**, an optical adhesion layer **16**, and a cover **17** are layered in this order. In this example, the low-refractive index layer **13** with apertures and the uninterruptedly-extending low-

refractive index layer **15** correspond to optically functional layers.

[0029] In this example, the optical medium layer **11** is an image-presenting body, such as a poster, a reflection type display, or an electronic paper, or a transparent window or transparent wall, etc.

[0030] The lightguide **14** is a light guiding layer, such that light which is output from a light source **21** (e.g., an LED) that is located on an end face of the optical device **100A** propagates through the lightguide **14**. In an embodiment, at least one of the optically functional layer **13** and the optically functional layer **15** allows light to be guided to an end face of the optical device **100A** on the opposite side to the light source **21**. The lightguide **14** is composed of e.g. PMMA or PCR, in which case its refractive index is about 1.49.

[0031] The low-refractive index layer **13** with apertures and the uninterruptedly-extending low-refractive index layer **15** may be made of the same material or different materials; however, the refractive index n_2 of these layers is smaller than the refractive index n_1 of the lightguide **14**. The refractive index n_2 of the low-refractive index layers **13** and **15** is 1.30 or less, and preferably 1.20 or less.

[0032] The refractive indices of the optical adhesion layers **19** and **16** and the cover **17** are desirably approximately

equal to, but may be slightly different from, that of the lightguide **14**.

[0033] In the configuration of FIG. **1A**, the viewer observes the optical device **100A** from the direction of the cover **17**. Therefore, the more light is extracted through the cover **17** toward the viewer, the more preferable it is. The light propagating in the lightguide **14** passes through the apertures **131** or **132** of the low-refractive index layer **13**, and is reflected by the optical medium layer **11** and transmitted through the apertures **131** or **132** or the low-refractive index layer **13**, so as to be emitted through the cover **17** toward the viewer.

[0034] When its angle of incidence on the low-refractive index layer **15** is greater than the critical angle (i.e., when incident at a small angle), the light propagating in the lightguide **14** satisfies the conditions for total reflection, and is reflected toward the optical medium layer **11**. Herein, by using the refractive index n_1 of the lightguide **14**, and the refractive index n_2 of the low-refractive index layers **13** and **15**, the critical angle θ_c is expressed as:

$$\theta_c = \theta_i = \arcsin(n_2/n_1).$$

θ_i is the angle of incidence (i.e., the angle from the normal).

[0035] The light which is reflected by the optical medium layer **11** is transmitted through the low-refractive index

layer **13**, the lightguide **14**, and the low-refractive index layer **15**, and is emitted through the cover **17**. The pattern of apertures **131** or **132** in the low-refractive index layer **13** is designed so as to allow the light which has been totally
5 reflected by the low-refractive index layer **15** to be efficiently guided toward the optical medium layer **11**, and to allow reflected light from the optical medium layer **11** to be efficiently extracted toward the cover **17**.

[0036] The apertures **131** are formed by removing portions
10 of the low-refractive index layer **131** through cladding removal, for example. The apertures **132** are formed in a high-density pattern such that the removed portions of the low-refractive index layer **131** are buried with a layer of another optical material, for example. The material to bury
15 the apertures **132** has a refractive index which is equal or similar to the refractive index of the lightguide **14** and the optical adhesion layer **19**.

[0037] If the low-refractive index layer **15** did not exist on the surface of the lightguide **14** at the light-extracting
20 side (which in this example is the upper surface along the direction of layering), light which is output from the light source **21** and heads directly toward the cover **17** would be transmitted intact through the optical adhesion layer **16** and the cover **17**, thus causing a loss of light. Adopting the
25 configuration of FIG. **1A** minimizes the loss of light during

guiding, thus allowing it to be efficiently guided to the end of the lightguide **14**, and also allows the light which is reflected by the optical medium layer **11** to be efficiently emitted through the cover **17**. As a result, light of a sufficient amount and intensity is output toward the viewer, whereby contrast and visibility are maintained.

[0038] The low-refractive index layer **13** having apertures, and the low-refractive index layer **15** which is a continuous film (i.e., a low-refractive index layer uninterruptedly constituting a uniform surface with a low-refractive index material), function as optical filters to control the traveling path of light which propagates in the lightguide **14**. As will be described later, besides refractive indices, antireflection coating structure, optical density, optical constant, etc., may also be adjusted, whereby various functions can be conferred.

[0039] The distribution of light to be achieved by the apertures **131** or **132** of the low-refractive index layer **13** may be uniform, non-uniform, or discrete. As a result, a uniform, non-uniform, or discrete image or signal can be formed. The main function of the apertures **131** or **132** is to control the amount of incident light which propagates from the lightguide **14** toward the optical medium layer **11**, without out-coupling the light (i.e., by utilizing the conditions for total reflection).

[0040] Through adjustments of their dimensions, shape, etc., the apertures **131** and **132** may be produced so as to exhibit other functions, such as scattering, refraction, reflection, or the like. Some of the apertures **131** or **132** may be formed so as to out-couple light, i.e., so as to allow light which has been reflected by the optical medium layer **11** to be transmitted through the cover **17**. The apertures **131** or **132** may be formed in shapes such as circles, ellipses, polygons, rectangles, etc., and their size or diameter may be e.g. 1 μm to 100 μm , preferably to be adjusted within the range from 1 μm to 30 μm .

[0041] FIG. **1B** is a schematic cross-sectional view of an optical device **100B**. The fundamental principles of the optical device **100B** are the same as in FIG. **1A**. In the optical device **100B**, an air layer is used as a low-refractive index layer covering the entire surface of the lightguide **14**. Air has a smaller refractive index than that n_1 of the lightguide **14**, and light which is output from the light source **21** so as to be incident on the interface between the lightguide **14** and the air layer satisfies the conditions for total reflection and thus is reflected into the lightguide **14**, and passes through the apertures of the low-refractive index layer **13** to be reflected by the optical medium layer **11**. Light carrying information of the optical medium layer **11** is emitted through the surface of the lightguide **14**.

[0042] With the configuration of FIG. **1B**, too, light can be propagated to the end of the lightguide **14** on the opposite side to the light source **21** without waste, and light can be allowed to efficiently proceed to the optical medium layer
5 **11**, whereby reflected light can be efficiently extracted.

[0043] FIG. **1A** presents a frontlight solution in which the lightguide **14** is disposed (e.g., laminated) between layers. FIG. **1B** presents a frontlight solution in which the lightguide **14** serves as a top layer. In order to prevent
10 light leakage due to contamination or defects on the outer surface of the lightguide **14**, the outermost surface of the lightguide **14** may be provided with a hard coating having a low refractive index value.

[0044] The lightguides **14** of FIG. **1A** and FIG. **1B** lack any
15 optical patterns such as a light out-coupling pattern. This novel non-patterned lightguide **14** provides illumination on a target such as a display surface, through lamination on the surface/interfaces with the optically functional layers. An interface lamination can direct light onto a target surface
20 such as a display surface, for illumination or light displaying purposes. In order to control passage of light and its direction, both interfaces may be laminated, and refractive index matching may be utilized for the control.

[0045] Table 1 shows results of improvement on the light extraction efficiency of the lightguide structure in which the optical apertures **131** or **132** are provided.

[0046]

5 [Table 1]

	silicone-laminated, patterned PMMA FL	acrylic-laminated, low Ri PMMA FL with apertures	improvement in light extraction efficiency
luminous flux (lumens)	2.768	3.424	23.50%
illuminance (lux)	250	390	

In Table 1, the upper row shows luminous flux (lumen), and the lower row shows illuminance (lux), of extracted light. In a comparison between the low-refractive index and apertured PMMA lightguide which is laminated with acrylic and a surface-patterned PMMA lightguide which is laminated with silicone, the light extraction efficiency is improved by as much as 23.5% in a frontlight solution, because the lightguide **14** is laminated with the low-refractive index layer **13** with apertures.

[0047] Light extraction efficiency depends on the refractive index of the lightguide **14** and the refractive

indices of the bonded or laminated layer, cladding, coating material, etc. Since the frontlight solution of the embodiment does not have any optical pattern formed on the surface of the lightguide, stray light is minimized and transparency is enhanced, thereby improving the contrast and light extraction efficiency.

[0048] <first embodiment>

FIG. **2A** through FIG. **2F** show optical devices according to a first embodiment and example applications thereof. In the first embodiment, while relying on the configuration and performance according to FIG. **1A** and FIG. **1B**, cavity optical elements may be optionally utilized to improve transparency. In particular, transparency of the lightguide in ON/OFF modes of illumination is improved, and stray light is suppressed so as to allow light to be emitted (or out-coupled) at desired angles. Even if fingerprints, dust, or other soil has adhered to the cover surface, at least one of improvement in the transparency of the lightguide and suppression of stray light is realized, whereby sufficient light is extracted toward the viewer for better visibility.

[0049] FIG. **2A** is a schematic cross-sectional view of an optical device **10A** according to the first embodiment. The optical device **10A** includes an optical medium layer **11**, an optically functional layer **13A** having air cavities **134**, a lightguide **14**, a low-refractive index layer **15** which is

uninterruptedly provided, an optical adhesion layer **16**, and a cover **17**, which are layered in this order.

[0050] The cover **17** is intended to protect the optical device **10A**; the more transparent it is, the better. It may
5 be made of glass, plastic, etc. and may have a UV-absorbing effect. It is desirably high in strength in terms of a protective layer, but it may also be a thin and flexible layer.

[0051] The uninterruptedly-extending low-refractive index
10 layer **15** and the optically functional layer **13A** with air cavities **134** are other examples of the optically functional layer **13** which has been described with reference to FIG. **1A** and FIG. **1B**. The low-refractive index layer **15** allows the light which is emitted from the light source **21** and which
15 enters inside the lightguide **14** from an end face of the lightguide **14** to be sufficiently guided to the end face on the opposite side to the light source **21**.

[0052] The optically functional layer **13A** allows the light which has been totally reflected by the low-refractive index
20 layer **15** or the light which directly enters from the light source **21** to be efficiently guided in the direction of the optical medium layer **11**, and out-couples the light which has been reflected by the optical medium layer **11** toward the cover **17**.

[0053] The optically functional layer **13A** includes optical bumps, e.g., microlens-type, lenticular lens-type, and a triangular prism- or ridge-shaped lenses. In pattern **(a)**, as viewed in the direction of layering, an optically functional
5 layer **13A₁** is provided on the lower surface of the lightguide **14**, and includes optical protrusions **133** of microlens type which are convex toward the optical medium layer **11**. Air cavities **134** exist between the optical protrusions **133** and the optical medium layer **11**.

10 [0054] In pattern **(b)**, an optically functional layer **13A₂** is provided on the lower surface of the lightguide **14** as viewed in the direction of layering, and includes optical protrusions **135** which are triangular prism- or ridge-shaped and which protrude toward the optical medium layer **11**. Air
15 cavities **134** exist between the optical protrusions **135** and the optical medium layer **11**.

[0055] The refractive indices of the optical protrusions **133** and **135** are equal or close to the refractive index n_1 of the lightguide **14**. The refractive index n_2 of the air
20 cavities **134** is the refractive index of air, which is smaller than the refractive index n_1 ($n_2 < n_1$).

[0056] An optical layer having formed thereon a concave pattern of grooves, dots, etc., instead of convex lenses, may be bonded to the bottom surface of the lightguide. In this
25 case, air cavities based on grooves or recesses constitute a

low-refractive index pattern, which, as in the case of convex lenses, efficiently refracts incident light in the direction of the optical medium layer **11**.

[0057] Shapes are transferred via vacuum pressing onto the
5 optically functional layer **13A** with air cavities **134** by using a mold, a first portion of whose acrylic plate has desired shapes formed thereon, for example. A solution of a low-refractive index is applied onto a second portion of the plate, which is modified with the transferred pattern,
10 whereby the above is formed.

[0058] The optically functional layer **13A** may be adhesively bonded to the bottom surface of the lightguide **14** by using an optical adhesive of a refractive index equal or close to that of the lightguide **14**.

15 [0059] Similarly to the aforementioned optical device **100A**, the low-refractive index layer **15** refracts the light which directly enters from the light source **21** in the direction of the optical layer **13**. The light which has been reflected by the low-refractive index layer **15**, or the light
20 which directly enters from the light source **21**, is refracted at the interface of an optical protrusion **133** or **135** and an air cavity, so as to be guided toward the optical medium layer **11**. At the surface of the optical medium layer **11**, the light is reflected in the direction of the cover **17**. This
25 reflected light does not satisfy the conditions for total

reflection at the interface with the low-refractive index layer **15**, and thus is emitted intact through the cover **17**.

[0060] With this configuration, the light which is emitted from the light source **21** sufficiently propagates toward the
5 end face of the lightguide **14** on the opposite side, and the light which has been reflected by the optical medium layer **11** can be sufficiently extracted for output.

[0061] In mobile terminals such as smartphones, fingerprints, sweat, or other soil are likely to adhere to
10 the display screen, especially in the outer peripheral region. If the low-refractive index layer **15** were not present, the light which has been emitted from the light source **21** in the direction of the cover **17** would be scattered by soil, thus resulting in a large loss of light. By
15 combining the low-refractive index layer **15** and the optically functional layer **13A** having air cavities **134**, loss of light during guiding can be suppressed, and light can be efficiently extracted from the optical device **10A**.

[0062] FIG. **2B** is a schematic cross-sectional view of
20 another optical device **10B** according to the first embodiment. The optical device **10B** includes an optical medium layer **11**, an optical adhesion layer **19**, a low-refractive index layer **13B**, a lightguide **14B**, a low-refractive index layer **14**, an optical adhesion layer **16**, and a cover **17**, which are layered
25 in this order.

[0063] In this example, the low-refractive index layer **13B** is a continuous film (i.e., a low-refractive index layer uninterruptedly constituting a uniform surface with a low-refractive index material). The refractive index n_2 of the
5 low-refractive index layer **13B** and the low-refractive index layer **15n** is lower than the refractive index n_1 of the lightguide **14**. Together with the low-refractive index layer **15**, the low-refractive index layer **13B** allows the light which is emitted from the light source **21** and which has entered at
10 an end face of the optical device **10B** to sufficiently propagate to the end face of the lightguide **14** on the opposite side.

[0064] The lightguide **14B** includes optical cavities inside. The inside of the optical cavities may be filled
15 with a gas such as air. The optical cavities have shapes which allow the light propagating in the lightguide **14B** to be efficiently directed in the direction of the optical medium layer **11**. Moreover, they are designed so that stray light or leakage light will not occur due to refraction at the
20 interfaces of the optical cavities.

[0065] So long as stray light or leakage light can be suppressed, the optical cavities may be designed in any appropriate shape, (e.g., optical cavities **141a** with a rectangular cross-sectional shape, triangular-shaped optical
25 cavities **141b**, etc.). Specific shapes of the optical

cavities will be discussed later with reference to FIG. **22A** through FIG. **22J**.

[0066] In the configuration of FIG. **2B**, the low-refractive index layer **13B**, the lightguide **14B**, and the low-refractive index layer **15** serves as optically functional layers, thus creating optical filters. With these optical filters, while sufficiently guiding light toward the end of the lightguide **14B**, a necessary amount of light can be guided in the direction of the optical medium layer **11**, and reflected light from the optical medium layer **11** can be efficiently extracted to the outside of the cover **17**.

[0067] FIG. **2C** is a schematic cross-sectional view of another optical device **10C** according to the first embodiment. The optical device **10C** has a similar configuration to that of FIG. **1A**, and includes a low-refractive index layer **15** which is a continuous film (i.e., a low-refractive index layer uninterruptedly constituting a uniform surface with a low-refractive index material) at the surface of the lightguide **14** on the light-extracting side (i.e., the upper surface along the direction of layering), and includes a low-refractive index layer **13C** having an optical aperture pattern on the bottom surface of the lightguide **14**. The low-refractive index layer **13C** and the low-refractive index layer **15** serve as optically functional layers.

[0068] The aperture pattern in the low-refractive index layer **13C** is formed so that increasingly greater aperture ratios exist farther down the direction of light propagation in the lightguide **14**.

5 [0069] In regions of the lightguide **14** near the light source **21**, there are large light amounts so that, even if the aperture ratio is small, a sufficient amount of light can still be guided toward the optical medium layer **11**. Although the amount of light decreases as it propagates in the
10 lightguide **14**, a similar amount of light to that in the neighborhood of the light source **21** is supplied to the optical medium layer **11**, thus ensuring that the intensity of reflected light from the optical medium layer **11** is uniform.

[0070] As in the case of the optical devices **10A** and **10B**,
15 the low-refractive index layer **15** allows light to sufficiently permeate over to the end of the lightguide **14**, and also the aperture pattern allows light to be efficiently incident on the optical medium layer **11**, whereby reflected light is extracted. With the configuration of FIG. **2C**, light
20 extraction from the optical device **10C** becomes efficient and uniform, whereby visibility further improves.

[0071] The configurations of FIG. **2A** through FIG. **2C** may be mutually combined at least in part. For example, the lightguide **14B** of FIG. **2B** may be combined with the optical

layer **13** with air cavities in FIG. **2A**, or the low-refractive index layer **13C** with apertures in FIG. **2C**.

[0072] FIG. **2D** is a diagram showing the effect of providing the low-refractive index layer **15** on the surface of the lightguide **14** on the light-extracting side. As Comparative Example, a configuration in which the low-refractive index layer **15** is not provided on the surface of the lightguide **14** on the light-extracting side is shown in **(b)**.

10 [0073] As in **(b)** of FIG. **2D**, when the low-refractive index layer **15** does not exist on the light-extracting side of the lightguide **14**, when fingerprints, sweat, dust, or other soil have adhered to the surface of the cover **17**, within the light which has entered the lightguide **14** from the light source **21**,
15 the light heading directly to the cover **17** will scatter without being guided by the optical medium layer **11**, thus resulting in a loss of light.

[0074] On the other hand, as in **(a)** of FIG. **2D**, providing the low-refractive index layer **15** on the light-extracting
20 side of the lightguide **14** can prevent light from scattering without entering the optical medium layer **11**. Furthermore, by utilizing the total internal reflection in the low-refractive index layer **15**, while allowing light to propagate to the end of the lightguide **14**, light is allowed to enter
25 the optical medium layer **11** by air cavities **134** or other low-

refraction members. By efficiently extracting reflected light from the optical medium layer **11**, high contrast and visibility can be realized.

[0075] FIG. **2E** shows example applications of the optical devices **10A** through **10C** to signage **190**. In signs, signboards, facade illumination, marketing illumination, indication illumination, and the like, in order to efficiently illuminate a two-dimensional plane, at least one of the aforementioned aperture pattern and air cavities is used to guide light within the lightguide, thus extracting a sufficient amount of light.

[0076] Public, signs, displays for marketing, etc., may be a passive type or an active type, depending on the type of display or poster. Although backlight solutions are generally utilized, the trend in recent years has been to use frontlights and to illuminate a reflection type display only when needed.

[0077] In the example of FIG. **2E**, the above-described optical device **10** may be applied to one surface or both surfaces of the signage **190**. In the case where the signage **190** is a both-surface solution, an optical device **10D** of both-surface type may be adopted.

[0078] FIG. **2F** is a schematic cross-sectional view of the optical device **10D**. The optical device **10D** includes a pair of optical devices **10-1** and **10-2** which are attached back to

back on the optical medium layer **11** side. Although optical devices **10C** of FIG. **2C** are attached together in this example, optical devices **10A** or optical devices **10B** may be attached together. So long as light can be sufficiently guided and
5 light can be sufficiently extracted from the optical medium layer **11**, it is not necessary to use optical devices **10** of an identical configuration on both surfaces.

[0079] On respective end faces of the optical devices **10-1** and **10-2**, a light source **21-1** and a light source **21-2** are
10 disposed, so that light enters the lightguide from the end face, and is guided. With the optical function of the aperture pattern or air cavities, light is guided to the optical medium layer **11** so as to be emitted through both surfaces.

15 [0080] In case an advertisement stand, in particular a poster or the like, is to be replaced, it is preferable that the optical medium layer **11** is detachable from the optical device **10**. This will be described later with reference to FIG. **29** and FIG. **30**.

20 [0081] In the case of solid-state displays, a permanent lamination is appropriate. Preferably, a rigid or elastic optical material may be used to ensure an optical contact between the lightguide **14** and the optical media layer **11** (display/sign/poster, etc.).

[0082] Whether it is a fixed type or a replaceable type, it is important to ensure (optical) contact with the surface being illuminated in order to minimize stray light and maintain a high contrast ratio.

5 [0083] When the lightguide **14** or **14B** is used for purposes other than illumination, it is in a passive mode and requires visual transparency throughout the device. Under natural light, such as sunlight, reflective displays do not require illumination, but when the lightguide is in the uppermost
10 layer of the display, as in the frontlight type, sufficient transparency is required to ensure that the visual characteristics of the display are not degraded.

[0084] In an active mode, illumination light is emitted through one surface or both surfaces of the transparent
15 lightguide. Depending on the use of the illumination light, appropriate light distribution is made within the range of the viewing angle, especially for illumination for use with displays, thus minimizing stray light.

(A) Criteria in the passive mode (for purposes other than
20 illumination) are: (a) minimization of fogging and suppression of scattering and color shift, (b) minimization of Fresnel reflection, (c) invisibility of the optical pattern/features, and (d) invisibility of changes in pattern density.

(B) Criteria in the active mode are: (a) stray light due to the pattern, (b) Fresnel reflection due to the interface (external reflection), (c) Fresnel reflection due to the pattern itself, and (d) quality of light extraction with
5 suppressed scattering.

[0085] The optical device of the embodiment is compatible with either mode, depending on the product and the application. In particular, leakage of light at the surface and stray light due to internal Fresnel reflections can be
10 addressed by at least one of the internal cavities and the antireflection.

[0086] FIG. **22A** through FIG. **22J** show example configurations of the optical pattern. The optical pattern is a pattern that is created, within a medium of the
15 refractive index n_1 , with a material ($n_2 < n_1$) of the low-refractive index n_2 . When the material of the refractive index n_2 is air, it is air cavities.

[0087] In FIG. **22A**, incident light at the arrow undergoes total reflection (TIA) at the interface of the optical
20 pattern, whereby light is extracted to the outside.

[0088] In FIG. **22B**, light is transmitted through the optical pattern, and stray light L_{stray} due to Fresnel reflection is reflected by the second surface on the outgoing side of the optical pattern, again reflected by the first

surface on the incident side, so as to be transmitted through the optical pattern.

[0089] In FIG. **22C**, light is transmitted through the optical pattern, and through direction control of Fresnel
5 reflection at the second surface, stray light L_{stray} is minimized.

[0090] In FIG. **22D**, an AR film **145** is provided on the first surface of the optical pattern. Light is transmitted through the optical pattern, and the AR film **145** provided on
10 the first surface minimizes stray light L_{stray} .

[0091] In FIG. **22E**, through refraction at the second surface of the optical pattern, light is transmitted through the optical pattern together with the stray light L_{stray} .

[0092] In FIG. **22F**, by restricting the angle of incidence
15 with respect to the first surface of the optical pattern, the stray light L_{stray} is minimized before being transmitted through the optical pattern.

[0093] In FIG. **22G**, the optical pattern presents a cross-sectional shape of a convex lens. Light undergoes total
20 reflection (TIR) at the surface of the optical pattern, so as to be extracted to the outside.

[0094] In FIG. **22H**, light enters at the first surface of the optical pattern and is transmitted through the second surface. The stray light L_{stray} is reflected by the second

surface and the first surface, and thereafter is transmitted through the second surface.

[0095] In FIG. **22I**, an AR film **145** is formed on the second surface of the optical pattern. Light enters at the first surface, and is transmitted through the second surface. The
5 stray light, indicated by a dashed arrow, is minimized by the AR film.

[0096] In FIG. **22J**, the optical pattern is provided on the lightguide **14**. The optical pattern is formed by attaching an
10 optical material together with a lightguide having the pattern formed thereon (the interface I/F of attaching together is indicated by a dotted line). Providing an AR film at the interface I/F results in the AR film being present at the bottom surface of the optical pattern.

15 [0097] FIG. **23** is a diagram describing the effect of stray light suppression due to an antireflection film. As in region **A**, where one-surface irradiation occurs, an AR film **145** is provided on the light-extracting surface of the lightguide **14**. Light propagating in the lightguide **14** is
20 refracted toward the light-extracting surface by the optical cavities **141** having a lower refractive index than that of the lightguide **14**.

[0098] In region **B**, some of the light that has been refracted by the optical cavities **141** is reflected by the
25 light-extracting surface, thus becoming stray light L_{stray} to

be emitted through the surface of the lightguide **14** on the opposite side. In the case of both-surface irradiation, stray light L_{stray} may be utilized, without providing the AR film **145**.

5 [0099] FIG. **24** is a diagram describing the effect of stray light suppression due to an optical adhesive **191**. As in a tablet terminal, in the case where the display **110** is lit with a backlight, the space between the lightguide **14** and the display unit (into which the display **110** and the optical
10 adhesion layer **19** are integrated) may be filled with an optical adhesive **191**, thereby suppressing stray light L_{stray} (region **A**). As in region **B**, where an air layer exists at the interface, some of the light that has been refracted by the optical cavities **141** toward the display **110** is reflected by
15 the air layer, thus becoming stray light L_{stray} to leak outside. By filling the interface with the optical adhesive **191**, stray light L_{stray} can be suppressed.

[0100] All of the aforementioned optical means (optical patterns such as apertures or air cavities, AR films, optical
20 adhesives, etc.) are designed so as to suppress stray light. In particular, by combining two or more of the features described below, an optimum solution can be obtained.

1) By using an optical cavity pattern, via total internal reflection (TIR) or refraction, essentially all light is
25 extracted through the surface of the optical device (out-

coupled), and not allowed to scatter into the cavity (see FIG. **22A** and FIG. **22G**), thereby minimizing stray light and Fresnel reflection. With a light source, or at least with light in-coupling collimation in the vertical direction, the angle of incidence with respect to the lightguide may be restricted.

2) At the first surface of the optical cavity pattern, most light is out-coupled to the light-extracting surface, while partially transmitted light is redirected into the cavity from the interface of the cavity so as to be guided to the second surface, thus suppressing leakage light or stray light (see FIG. **22E**, FIG. **22F**). This configuration is a combined solution, where the first surface of the pattern profile is designed with a limited angle of incidence (a critical angle that can avoid leakage light or stray light). The angle of incidence can be restricted by using an optical collimation element (or, when the angle is large, by using a light absorption layer).

3) When an asymmetric optical cavity pattern is used, the first surface serves as a light extraction/out-coupling surface, while the second surface serves as a surface for transmission or redirection, without allowing out-coupling. This prevents unwanted Fresnel reflection from directly out-coupling to the outside from the lightguide. When a periodic pattern is used, the second surface works in cooperation with

the next surface in the pattern so as to improve light orientation, light extraction/out-coupling, and other performances.

4) When a symmetric optical cavity pattern is used, the first surface serves as a light extraction/out-coupling surface, while the second surface is dedicated to transmission or redirection without allowing out-coupling, thus minimizing Fresnel reflection in any undesirable direction (see FIG. **22C**).

5) When an optical cavity pattern is used, an antireflection coating or an antireflection coating structure may be adopted for the first surface and/or the second surface. In order to minimize Fresnel reflection, an AR pattern or multilayer coating, or a low-refractive index coating may be used to provide wide-range AR (see FIG. **22D**, FIG. **22I**). An optical cavity pattern and an AR structure/coating may together provide a multi-functional hybrid configuration.

6) When a profile of the optical cavity pattern is created, an AR coating or an AR pattern may be provided on the second surface having a flat surface. Such optical cavities can be formed by attaching together a first film having cavity shapes formed on one surface and a second film having an AR coating formed on one face. The optical cavities do not have any interface of attaching together, and thus an active AR surface is obtained.

7) When an optical cavity pattern is formed on the lightguide through one-surface irradiation, undesirable Fresnel reflection can be minimized by providing an AR layer (an AR coating or an AR pattern) on the light-extracting surface.

5 In the case of both-surface light extraction, the AR layer may be omitted (see FIG. **23**).

8) In the case where an optical cavity pattern is to be formed on a lightguide one of whose surfaces serves as a light-extracting surface for the display surface, an optical

10 adhesive is injected at the contact surface with the display unit, thus minimizing undesirable Fresnel reflection (see FIG. **24**).

9) In the case where one surface serves as a light filtering surface without forming an optical pattern thereon, light is

15 transmitted through the optical apertures, and desired illumination light is supplied to the display surface through optical bonding. The light filtering surface may be implemented as a low-refractive index cladding having a light-transmitting surface (see FIG. **1A**, FIG. **1B**, FIG. **2C**).

20 [0101] Transparent lightguides and transparent cavity optics have a variety of applications, and the optical pattern itself is designed and optimized accordingly depending on the application, manner of application, and other factors. For example, at least one optical pattern

25 provided on the optically functional layer may be formed as a

relief selected from grooves, dents, dots, pixels, etc. The relief may be a pattern having, for example, a local (in the film thickness direction) concave or convex surface and may be selected from binary, blazed, slanted, prismatic, trapezoidal, hemispherical, or other shapes. Alternatively, the relief may be a long shape, e.g., linear, curved, waved, or sinusoidal.

[0102] In the case of transparent illumination, it is desirable to use a high performance optical material with low color shift and scattering for the optically functional layer. In particular, it is desirable to use good optical materials in the lightguide, OCA (optically clear adhesive), and low-refractive index layer. Desirably, scattering and stray light are suppressed in the low-refractive index layer with optical apertures. Since physical apertures in the stack laminated along with other refractive index materials can cause light scattering, fogging, and a decrease in the contrast ratio, a low-refractive index layer with optical apertures based on local changes in the refractive index, as shown in FIG. **1A**, FIG. **1B**, and FIG. **2C**, may be one effective configuration. A low-refractive index layer with optical apertures can be formed by inkjet printing, inverted offset printing, laser and electron beam processing.

[0103] The configurations of FIG. **1A** and FIG. **2A** through FIG. **2C** are also effective as frontlight solutions. On at

least the light-extracting surface of the lightguide, the low-refractive index layer **15** is provided, so as to guide light over to the end on the opposite side to the light source **21**. As shown in FIG. **1B**, a frontlight solution in which the light-extracting surface of the lightguide **14** is the uppermost layer is also effective, but in order to prevent leakage of light due to soil or defects on the outermost surface, preferably a hard coating of a low refractive index value may be deposited.

[0104] In the case where the optically functional layer includes an optical pattern, the optical pattern density may be constant, or the pattern density may have a gradient as shown in FIG. **2C**. An optically functional layer including an optical pattern can be designed for applications such as transparent backlights, frontlights, illumination panels, and the like. The light extraction pattern can be designed for a narrow range of light distribution, a wide range of light distribution, elliptical, symmetric, asymmetric, or other light distributions. The light extraction efficiency can be maximized by continuous periodic profiles or local profiles such as pixels. In the case of transparent solutions, the light extraction efficiency can be maximized by minimizing fogginess and stray light. A continuous and efficient 3D optical pattern may be provided. In this case, it can be used for a plurality of applications, reducing master

fabrication and product costs and allowing for larger product sizes.

[0105] As the basic optical profile to be provided on the optically functional layer, either a surface relief pattern or a cavity optical pattern may be used. In the case of a cavity optical pattern, the optical cavities may be filled with a gas, fluid, or solid material, preferably air, to confer a total internal reflection effect to the optical surface. The optical pattern can be given different profiles, e.g., binary, slanted, blazed, prisms, or microlenses, based on diffraction or refraction optics.

[0106] The lightguide is formed by using a coating layer, a film on a substrate material, a light-guiding substance, etc. A light distribution/extraction film with light filtering apertures may be applied to the flat surface of a substrate material that lacks a pattern. Using a functional film allows the lightguide to be designed to be either thin or thick, by using different materials such as PMMA, glass, etc. All optical functions may be integrated on an "all-in-one" film. The main optical functions are: control of uniformity by filter apertures; and out-coupling with a light distribution which is determined by the optical cavity pattern. These two main functions may be realized separately as two different phases. Additional functional layers, such as a diffuser, may also be incorporated.

[0107] An optical filter with a low-refractive index layer may be adopted directly to the surface of the substrate material in order to form apertures, and a functional film having an optical pattern for light extraction may be adopted
5 over the optical filter. This configuration may reduce the number of layering or assembly steps. The layered structure of an optical filter and a functional film may be adopted on one surface or both surfaces of the lightguide.

[0108] The distribution and extraction of light is based
10 on a film concept, such as at least one optical pattern layer, surface reliefs, a cavity pattern, etc. A plurality of optical patterns may be adopted to form a single film, into which at least one cavity optical layer may be integrated. By utilizing cavity optical elements such as air
15 cavities, a plurality of layers can be bonded to each other. In the case of not employing surface reliefs such as a concave-convex pattern, the film can be completely integrated, and the interfaces can be adhesively bonded to each other. The integrated light filter cladding may be
20 gathered within a single film having an optical pattern.

[0109] The optical pattern can be formed on the optically functional layer in various forms. For example, it may be air cavity optics embedded within the layer (an optically functional layer having optical cavities within the layer),
25 or it may be formed as an alternating pattern of optical

bodies and cavities placed at an interface with a transparent laminate layer, a reflective laminate layer, a colored laminate layer, etc.

[0110] A lightguide **14B** with an optical pattern (e.g., air
5 cavities) for light refraction/extraction inside may be used
as a light filter, as shown in FIG. **2B**, without using
apertures. A continuous film of uniform low-refractive index
material is provided on both surfaces of the lightguide **14B**.
The optical pattern is integrated inside the lightguide **14B**.
10 As the optical pattern, microlenses, a blazed pattern, a
slanted pattern, a discrete pattern, a pixel pattern, etc.,
may be arranged in the form of a periodic or diffraction
grating. A lightguide with uniform low-refractive index
layers formed on both surfaces may be adhesively bonded to
15 the other layers with an optically clear adhesive (OCA). The
OCA has a higher refractive index than that of the low-
refractive index layer, preferably having the same refractive
index as that of the lightguide.

[0111] When the optically functional pattern is formed as
20 cavities embedded in a matrix layer, the matrix and the
functional cavities are disposed alternately. In this case,
the optical function is set by at least one of the
dimensions, shape, period and cross-sectional arrangement of
the optically functional cavities. As mentioned above, the

cavities may be filled with air or may be filled with other gases, fluids, liquids or solids.

[0112] The lightguide of the embodiment may be combined with a commonly-used polarizer, such as a wire grid polarizer. The polarizer can be directly adhesively bonded or layered onto the flat surface of the optically functional layer. When the optical pattern provided on the optically functional layer is configured to functionally cooperate with the wire grid polarizer, luminance can be increased.

10 [0113] The optical device of the embodiment can be applied to signage, signboards, facades, marketing, indicator lights, etc., as described above. In this application, with or without an aperture or cavity pattern, the low-refractive index layer can be used to light the whole area, a discrete regions, any arbitrary two-dimensional shape, etc. As an example, with or without a coupling pattern, the aperture layer can be integrated into a color film or figured film to form a layered film. By cutting the layered film into a desired shape and laminating it on the light-guiding sheet, 15 the configurations of FIG. **2A** through FIG. **2C** can be obtained. The stacked body including the optically functional layer and the lightguide can be adhesively bonded, in a fixed (permanent) or a detachable manner, to the optical medium layer **11**, such as a poster, a display, etc. 20

[0114] When a convex optical pattern is present on the contact surface with the optical medium layer **11**, as shown in FIG. **2A**, the optical pattern may be formed with an elastic, transparent optical material. In particular, when it is adhesively bonded to the optical medium layer **11** in a detachable manner, it is preferably an elastic pattern. When the optical medium layer **11** is a replaceable poster or the like, the optical pattern is desirably made of an elastic material that is durable and reliable enough to withstand multiple removals and re-bonding.

[0115] In the first embodiment, a uniform low-refractive index film **15** without apertures is provided on a surface of the lightguide **14** at the light-extracting side, whereas an optically functional layer **13** having an optical pattern is disposed on the surface of the lightguide **14** on the opposite side to the light-extracting surface. The optical pattern may be designed so as to out-couple incident light from the lightguide **14** at a negative angle, and out-couple reflected light from the optical medium layer **11** at a positive angle. The optical pattern is designed so that light is incident at a smaller angle than the critical angle. As a result, while light which has been totally reflected by the low-refractive index layer **15** is distributed to the end of the lightguide **14**, light can be efficiently guided in the direction of the optical medium layer **11** serving as a bottom reflector (i.e.,

coupled), and light can be efficiently extracted (i.e., out-coupled).

[0116] <second embodiment>

FIG. **3A** is a diagram describing problems to be solved by
5 a second embodiment. FIG. **3B** and FIG. **3C** are schematic cross-sectional views of an optical device according to the second embodiment. These diagrams show example configurations.

[0117] When a low-refractive index layer is provided on at
10 least one surface of the lightguide **14**, too, there are rays of light (shown by the dashed lines) that enter the low-refractive index layer **23** or **15** at an angle of incidence smaller than the critical angle, as shown by dashed arrows, in the vicinity of the light source **21**. Rays that do not
15 reach the critical angle and are not totally reflected are not controlled by the aperture pattern or other optical functions, but are transmitted through the low-refractive index layer **23** or **15** intact, resulting in a loss of light.

[0118] Also when a proper alignment with the light source
20 **21** (e.g., an LED) is not made, it is impossible to couple all of the emitted light to the lightguide **14**, and unwanted light is transmitted inside the optical adhesion layer **16** or **19**, or other layers. Light entering at an angle smaller than the critical angle with respect to the interface should be
25 avoided.

[0119] FIG. **3B** shows an example configuration of an optical device **30A** that solves the aforementioned leakage of light. The optical device **30A** includes a lightguide **14**, and on both surfaces of the lightguide **14**, low-refractive index
5 layers **15** and **23** are provided as optically functional layers.

[0120] The optical device **30** includes a light absorption layer **31** and a light absorption layer **32** in its end region at the light source **21** side. The light absorption layers **31** and **32** may be, for example, thin layers (such as black tape)
10 having a light-absorbing property. The light absorption layers **31** and **32** may be directly adhesively bonded to the surface of the end region at the light source **21** side, or adhesively bonded through chemical surface treatment.

[0121] As is exemplified by the light-extracting side of the lightguide **14** in FIG. **3B**, when another layer (such as the optical adhesion layer **18**) exists at the outermost surface at the end, a light absorption layer **31** may be provided on the surface of that other layer (optical adhesion layer **18**) in layer form, e.g., tape. Alternatively, as exemplified by the
20 bottom surface side of the lightguide **14**, an optically functional layer such as the low-refractive index layer **23** may be integrated, with a light absorption function.

[0122] When incident light to the low-refractive index layers **15** and **23** has a smaller angle of incidence than the
25 critical angle of total reflection (as indicated by dashed

arrows), light that is not controlled by the low-refractive index layers **15** and **23** is absorbed by the light absorption layers **31** and **32**.

[0123] FIG. **3C** shows another example configuration for loss-of-light prevention. Instead of the light absorption layers **31** and **32**, the optical device **30B** employs redirecting layers **33** and **34**. As the redirecting layers **33** and **34**, for example, films or tapes having optical directivity may be used. The redirecting layers **33** and **34** change the angle of incidence of light which is output from the light source **21** so as to exceed the critical angle and satisfy the conditions for total reflection, thus keeping the light inside the lightguide **14**.

[0124] As is exemplified by the light-extracting side of the lightguide **14** in FIG. **3C**, when another layer (such as the optical adhesion layer **18**) exists at the outermost surface at the end, a redirecting layer **33** may be provided on the surface of that other layer (optical adhesion layer **18**) in layer form, e.g., tape. Alternatively, as exemplified by the bottom surface side of the lightguide **14**, an optically functional layer such as the low-refractive index layer **23** may be integrated, with a redirecting function.

[0125] The redirecting layers **33** and **34** may be implemented as embedded-type apertures or cavity optical elements, which respectively cooperate with the low-refractive index layers

15 and **23** to confer directivity to light. The redirecting layer having embedded-type apertures or cavity optical elements can be produced by laminating a second film onto a transparent first film having a pattern of apertures or
5 cavities, for example. The second film may be transparent or non-transparent, and may have Lambert reflection, specular reflection, or reflection characteristics between two different colors (e.g., white and black).

[0126] Misalignment of the light source **21** along the
10 light-guiding direction is not so problematic in the case where the overlying (i.e., being on the light-extracting side) optical adhesion layer **18** does not provide cover over to the end of the lightguide **14**. The optical adhesion layer **18** may be disposed somewhat away from the edge of the
15 lightguide **14**, and the redirecting layer **33** supports propagation of light into the lightguide **14**. Usually, the low-refractive index layers **15** and **23** are very thin, and essentially all rays are reflected toward the high-refractive index side (i.e., the lightguide side), without creating
20 fogging, color shift, or other problems in the couple and propagation of light in the lightguide **14**.

[0127] The configuration of the second embodiment suppresses loss of light at the end on the light source **21** side, and while guiding light toward the end of the
25 lightguide on the opposite side, allows a sufficient amount

of light to be extracted through the light-extracting surface.

[0128] <third embodiment>

FIG. **17A** is a diagram describing problems to be solved
5 by a third embodiment. FIG. **17B** and FIG. **17C** show example configurations for solving the problems.

[0129] In FIG. **17A**, when light enters from a light source
21 to an end face at the light-incident side of a
corresponding lightguide **1001**, if the incident end face has
10 not been treated at all, incident light will be visible as
lines of light. The incident end face is usually modified by
forming ruggednesses etc., but this cannot sufficiently
control directionality of light, and luminance may be
degraded through scattering in unwanted directions,
15 misalignments, or the like. Accordingly, a reflector **1002**
having a reflective sheet **1003** may be provided between the
light source **21** and the incident end face of the lightguide
1001, thus to collimate light at the end face of the
lightguide **1001**.

20 [0130] However, this will result in an increased number of
parts, and high assembly costs and a long time. A new
configuration that is low cost, easy to assemble, and has
high in-coupling efficiency to the lightguide is desired.

[0131] FIG. **17B** shows one solution. An optical device **40A**
25 includes in-coupling optics **170** provided at an end face **175**

on the incident side of the lightguide **174**. FIG. **17B** shows the shape within an xy plane, where the light-guiding direction of the lightguide **174** is defined as y, the thickness direction as z, and the width direction as x.

5 [0132] The in-coupling optics **170** include optical elements **171** of hemispherical, prismatic, rod-, or other shapes, and air cavities **173** created between the optical elements **171** and the end face **175** of the lightguide **174**. The optical elements **171** efficiently output the light which is emitted from the
10 light source **21** toward the end face **175** of the lightguide **174**. The air cavities **173** function as in-coupling elements for efficiently inputting light which has been output from the optical elements **171** to the end face **175** of the lightguide **174**. With the optical elements **171** and the air
15 cavities **173**, light from the light source **21** can be collimated, and efficiently coupled to the end face **175** of the lightguide **174**.

[0133] In the example of FIG. **17B**, the in-coupling optics **170**, in which as many optical elements **171** as there are light
20 source **21** are arranged along the transverse direction (x direction), are adhesively bonded, via an optical adhesion layer **176**, to the end face **175** of the lightguide **174** (the incident edge face **175** of the light guiding layer **174** that defines a uniform plane). Apices of the plurality of convex
25 optical elements **171** are disposed in contact with the edge or

the end face **175** of the lightguide **174** defining a uniform plane. The convex optical elements **171** are aligned with the end face **175** so that their apices are in contact with the end face **175** of the lightguide **174** defining a uniform plane,
5 thereby creating a pattern of air cavities **173** (optical cavity pattern). Each optical element **171** and each air cavity **173** allow light which is output from the light source **21** to be coupled to the corresponding lightguide region.

[0134] As a preferable example configuration, although not
10 shown, an optical sheet with a plurality of optical elements **171** arranged in a row may be used. The shape of each optical element **171** is not limited to a hemispherical shape, and may be lenticular, rod-like, etc., so long as the air cavities **173** can be formed. In the optical sheet, a light source **21**
15 such as an LED or the like may be fixed in advance to the bottom surface of each optical element **171**. The optical sheet can be easily made at a low cost by extrusion, punching, molding inserts, or the like. According to this configuration, by simply attaching the optical sheet to the
20 flat end face **175** of the lightguide **174**, the light source **21** and the end face **175** of the corresponding lightguide region are self-aligned.

[0135] After the optical sheet is attached, light is refracted at the interfaces between the optical elements **171**
25 and the air cavities **173**, so as to be optically coupled to

the end face **175** of the lightguide **174** efficiently. Essentially all of the emitted light from the light sources **21** is utilized.

[0136] FIG. **17C** shows an optical device **40B** according to another example configuration. In the optical device **40B**, instead of using an optical adhesion layer **176**, the in-coupling optics **170** and the lightguide **174** are formed integrally. The integrated optical device **40B** can be easily produced by molding, die-cutting, or other methods.

[0137] In FIG. **17B** and FIG. **17C**, each optical element **171** may be molded as a flat ball lens which collimates light at an angle within $\pm 10^\circ$ of the transverse direction (the x axis direction), for example. This configuration is suitable to the case where a plurality of light sources **21** are used, as in an LED strip. The design of the optics, including the optical elements **171**, is optimized to achieve a uniformity of 70% or more along the x direction (transverse direction) light distribution inside the lightguide **174**, thereby normalizing the effect of "point light sources".

[0138] In FIG. **17B** and FIG. **17C**, the plurality of light sources **21** are disposed on a continuous plane at the non-bumpy side (i.e., the opposite side to the bumps of the optical elements) of the optical elements **171**. Disposing the light sources **21** on the plane, which is at the opposite side to the bumps of the optical elements **171**, facilitates

alignment of the plurality of light sources correspondingly to the plurality of bumps.

[0139] FIG. **17D** shows an optical intensity distribution inside a lightguide **174** according to a third embodiment, in which collimation is achieved along the transverse direction. In the model of FIG. **17D**, through a combination of in-coupling optics **170** having a collimating function and a linear blazed-type grating **35**, a uniform light distribution is obtained on the incident end face (i.e., the bottom surface in the figure). The grating **35** is disposed so that its protrusions face the lightguide. The luminous flux along the transverse direction is normalized by the in-coupling optics **170**, which facilitates optimization of the fill factor of the grating **35** at the lightguide. The FWHM of the longitudinal luminance distribution in this model is 30° and the FWHM of the transverse luminance distribution is 50°, indicative of good collimation.

[0140] FIG. **17E** shows an intensity distribution according to Comparative Example 1. The configuration of Comparative Example 1 uses the same light source **21** and the same size lightguide **174** as in FIG. **17D**, but without the in-coupling optics **170**. For out-coupling, a linear blazed grating **36** is used, as in FIG. **17D**, but the protrusions are disposed toward the light source **21**. A large number of light fringes from the light source are observed at the incident end of the

lightguide, and uniformity of the light distribution at the bottom of the lightguide is not good. The FWHM of the luminance distribution along the longitudinal direction is 30°, but the collimation along the transverse direction is inadequate, and the FWHM of the luminance distribution along the transverse direction is as wide as 82°.

[0141] FIG. **17F** shows an intensity distribution according to Comparative Example 2. Comparative Example 2 uses the same light source **21** and the same-sized lightguide **174** as in FIG. **17D**, with a curve-shaped grating **37**. No in-coupling optics **170** are provided. The light distribution at the bottom surface of the lightguide is essentially uniform. The FWHM of the longitudinal luminance distribution is 29°, but collimation along the transverse direction is insufficient, and the FWHM of the transverse luminance distribution is as wide as 78°.

[0142] FIG. **17G** is a table comparing the models of FIG. **17D** through FIG. **17F** with the conventional model. The conventional model is a microlens-type backlight unit (BLU) with a brightness enhancement film. Comparative Example 1 is an air-cavity type BLU of the linear grating configuration shown in FIG. **17E**. Comparative Example 2 is an air-cavity type BLU of the curved grating configuration of FIG. **17F**. In Comparative Example 1 and Comparative Example 2, the in-coupling optics **170** are not used. The configuration of the

embodiment is based on the model of FIG. **17D**, and uses the in-coupling optics **170** and the linear grating configuration, such that the protrusions of the grating face the lightguide.

[0143] The parameters for comparison are: luminance
5 (luminance), relative values against the luminance of the conventional configuration defined as 100%; FWHM; uniformity of the intensity distribution at the incident end face (bottom surface); and the presence/absence of in-coupling.

[0144] The model of the embodiment, which uses in-coupling
10 optics and a linear grating, achieves an efficiency improvement of over 90% as compared to the conventional lightguide configuration. All other performances, such as uniformity of the intensity distribution at the bottom surface and the luminance distribution, are also improved.
15 All of the above performance parameters can be adjusted to optimize the final target value. For example, by optimizing the in-coupling optics with the out-coupling optics, the light distribution angle can be narrowed or widened.

[0145] In the case of light collimated in the transverse
20 direction by the in-coupling optics **170**, a linear-structured grating **35** can be used as an out-coupling pattern. The master and manufacturing tools for the linear grating **35** can be produced by drum cutting or other direct tool methods, which makes the fabrication of the entire structure and the
25 master cheaper and easier.

[0146] In the case of a thin film, the air cavities **173** or optical elements **171** of the in-coupling optics **170** can be produced by die cutting, especially a heated blade method. The shape of the in-coupling optics **170** can be formed by the
5 same process as cutting the lightguide out of a large-sized base film, thus making the process cheaper and easier. The optical elements **171** or air cavities **173** of the in-coupling optics **170** can be covered with a reflector film, e.g., diffuse reflection or specular reflection, or a redirection
10 film, thereby realizing a configuration which utilizes all of the light. A reflector film may be provided on both surfaces of the cavities of the in-coupling optics **170**. In this case, the reflector film may be directly adhesively bonded to the surface of the lightguide with a transparent low-refractive
15 index adhesive. If the surface of the lightguide has a transparent coating with a low refractive index value, the reflector may be adhesively bonded to such a surface layer.

[0147] In the case of a thick sheet, flat ball lens type cavities can be formed by laser cutting. Alternatively, an
20 optical sheet **178** or strip with optical elements **171** having contact points at the edge of the lightguide, as shown in **(b)** of FIG. **17B**, may be used. The optical sheet **178** and a transparent optical adhesive can be laminated onto the edge of a relatively thick (e.g., 1 to 5 mm) lightguide. This is
25 a simple method, and alignment is easy because of the large

thickness of the lightguide. Again, the air cavities **173** or the optical cavities may be covered on one surface or both surfaces with a reflector(s), a diffuser(s), a redirection film (s), etc., to maximize efficiency.

5 [0148] In the case of collimation in the vertical direction, round edges or ball lenses may be used for integration with the lightguide. The in-coupling optics **170** may be integrated as shown in FIG. **17C**. The shape of the air cavities **173** or optical elements **171** in the in-coupling
10 optics **170** is not limited to the above example, but can be designed in any shape that allows light from the light source **21** to be efficiently coupled to the edge on the incident side of the lightguide **174**.

[0149] This configuration can increase the efficiency of
15 light incidence to the lightguide and the luminance, and make the intensity distribution uniform.

[0150] FIG. **17H** illustrates the uniformity of transverse luminance when using the third embodiment of the in-coupling optics **170**. The simulation is based on a model using the in-
20 coupling optics **170** and three LEDs. As mentioned above, the in-coupling optics **170** have a collimating function in the transverse direction, and the uniformity of the transverse luminance distribution in the lightguide reaches 80%. In order to achieve the final desired illumination performance,
25 especially uniform illumination near the edge on the light

source side, the transverse luminance or luminous flux is an important factor in considering the out-coupling design of the lightguide. The configuration of the third embodiment achieves a uniform luminance distribution along the
5 transverse direction.

[0151] FIG. **17I** shows an example configuration incorporating in-coupling cavities at the incident end of a lightguide. Configuration **(a)** is an example of incorporating integrated in-coupling cavities, as the in-coupling optics
10 **170**, into a commonly-used lightguide configuration with a surface relief pattern. In this case, even if light from the LED is efficiently coupled to the lightguide by the in-coupling cavities, the light is refracted because of the light entering the slope of the relief pattern at an angle
15 smaller than the critical angle, and the light cannot be sufficiently guided to the end face of the lightguide on the opposite side.

[0152] Configuration **(b)** is an example configuration in which in-coupling cavities are incorporated into a lightguide
20 **174b** having embedded-type cavities **172** as shown in FIG. **2B**. In this configuration, the light heading toward the bottom surface of the lightguide **174b** satisfies the conditions for total reflection and propagates sufficiently to the opposite side of the lightguide **174b**, and is reflected by the cavities
25 **172** to the light-extracting side.

[0153] In configuration **(c)**, a low-refractive index layer **13** having apertures is provided on the light-extracting side of a non-patterned lightguide **174**, and a pattern layer **177** having embedded cavities **179** is disposed on the low-
5 refractive index layer **13**. In this configuration, the light efficiently coupled to the lightguide **174** by the in-coupling optics **170** propagates between the bottom surface of the lightguide **174** and the low-refractive index layer **13** while undergoing total reflection, and the light transmitted
10 through the apertures is refracted toward the light-extracting side by the embedded cavities **179**. This allows for a uniform luminance distribution and improved light extraction efficiency.

<other embodiments>

15 The embodiments described below are applicable to any one of the basic concept (FIG. **1A** and FIG. **1B**), the first embodiment, the second embodiment, and the third embodiment. Moreover, the basic concept, the first embodiment, the second embodiment, and the third embodiment can be combined with one
20 another.

[0154] The optical patterns of embodiments (including optical apertures, air cavities, etc.) are produced by a variety of methods. For example, laser patterning, direct laser imaging, laser drilling, and laser or electron beam
25 irradiation with or without a mask are used. The optical

material and refractive index values may be modified by printing, inkjet printing, screen printing, or other methods to impart individual characteristics. They can also be produced by micro/nanodispensing, dosing, direct "writing",
5 discrete laser sintering, micro electrical discharge machining (micro EDM), micromachining, micro forming, imprinting, embossing, and the like. The formation of the optical apertures may be completed by direct contact methods, where a low-refractive index layer or a total internal
10 reflection (TIR) layer is directly attached together.

[0155] Formation of the apertures may be completed through indirect contact, for example, by being processed through a medium such as a carrier substrate or lightguide, via laser ablation. As the cladding is removed by ablation, apertures
15 of the desired size and shape are formed in the same manner as by direct contact. Preferably, the laser beam spot profile is shaped like a flat silk hat. This spot profile does not generate excessive heat and does not damage the carrier substrate or the lightguides. The laser wavelength
20 is selected accordingly based on the cladding absorption curve, hole edge quality, beam shaping optics, thickness/height, processing cost, or like standpoints.

[0156] FIG. 4 and FIG. 5 illustrate an example of using a laser **140** to create apertures **281**. In FIG. 4, by using a
25 roll-to-roll method, a substrate material **41** on which a low-

refractive index coating **28** is formed is rolled up from a roll **R1** to a roll **R2**. The low-refractive index coating **28** is ablated/removed by the laser **140** at a rate of 1 m to 20 m/minute to consecutively form apertures **281** which are
5 sized about 5 to 20 μm . The substrate material **41** is a film of optical plastic or optical glass, which is also applicable to a sheet method. After the apertures **281** are formed, OCA **42** is fed by a roll **R3** to form a stack of the substrate material **41**, the low-refractive index coating **28** with the
10 apertures **281**, and OCA **42**. This approach can be performed as a roll-to-roll or roll-to-sheet method of a continual or stop-and-repeat type. Discontinuous films can also be produced using the film-by-sheet or sheet-by-sheet method. As shown in FIG. **5**, multiple scanning heads can be used to
15 produce wide webs up to 1.5 m in width.

[0157] FIG. **5** shows aperture formation using a multi-head **240** that includes a plurality of scanners/lasers **241** to **243**. In this example, a line width of 1.0 m to 1.5 m can be achieved. For uniform light distribution in the lightguide,
20 apertures **281** are formed in the low-refractive index coating **28** on the substrate material **41**. The formation of gradually changing or constant apertures allows for uniform lightguide design for all kinds of sizes. This eliminates the need for a customized 3D production process for each product. After

the completion of the formation of the apertures **281**, the stacked film can be cut into sheets of a specific size.

[0158] FIG. **6A** and FIG. **6B** show images of apertures which are created by laser ablation. In FIG. **6A**, a laser beam with
5 a silk hat-type profile is used, and in FIG. **6B**, a laser beam with a Gaussian type profile is used.

[0159] Large-sized lightguides are very expensive and difficult to be patterned across the entire surface by molding, thus making mass production difficult. The optical
10 device of each embodiment described above are based on film lamination, which is a flexible and cost-effective configuration for producing lightguides in various sizes and, in particular, for producing large-sized lightguides. The configuration and concept of the embodiment allows for
15 application to mass production by roll-to-roll, roll-to-sheet or sheet-to-sheet methods. The final production speed can be appropriately set between 0.5 m to 30 m/minute, although depending on the selected production method. Also, it is applicable to either a continual or a stop-and-repeat
20 approach. The production of the optical device is based on a thin film process. Apertures are formed in the film that is formed thin to become the lightguide. Alternatively, an apertured optical pattern film may be directly laminated or bonded onto the lightguide so that the thin film forms a
25 solid lightguide without any optical pattern. The latter

type makes production flexible and cost-effective. The underlying cladding film or coating film can be produced in large quantities and stored in rolls. Subsequently, the apertures may be produced by an iterative and consecutive
5 method and finally, they may be stored again in rolls, or cut into sheets.

[0160] Preferably, the light source for the aforementioned optical device may be implemented as: one or more LEDs (light emitting diodes); one or more laser diodes; one or more LED
10 bars; one or more organic LED strips; one or more microchip LED strips; one or more cold cathode tubes; or the like. In the case of transparent lightguide solutions, control of the light distribution by the light source is important. Typically, LED light has a Gaussian distribution. In the
15 case of a low-refractive index cladding, the critical angle at which total reflection occurs in the lightguide is defined by Snell's law. When the angle of incidence to the interface is greater than the critical angle, the direction of refraction of the light is controlled by the dimensions and
20 shapes of the apertures formed in the low-refractive index cladding. For light with an angle of incidence smaller than the critical angle of incidence, measures need to be taken to prevent its transmission through the low-refractive index cladding, as has been described in the second embodiment. As
25 explained with reference to FIG. **3B** and FIG. **3C**, a thin

absorber, e.g., a tape (in particular, a black tape), which absorbs light in undesirable incidence ranges, is desirably disposed near the edge on the LED side and above the cladding of the lightguide. Instead of an absorber, a light
5 refraction layer having an aperture pattern, e.g., an optical pattern tape, may be used such that light in undesirable incidence ranges is redirected into a direction where an angle greater than the critical angle is obtained, and also that the redirected light is placed back in the useful light
10 incidence range.

[0161] If low-refractive index films are provided on both surfaces of the lightguide, as illustrated in FIG. **3B** and FIG. **3C**, light incidence below the critical angle must be addressed by absorbers or by redirection on both surfaces.

15 [0162] Further, as in the third embodiment described above, in-coupling optics may be used to restrict the light incidence to between a high critical angle and a low critical angle, as in the third embodiment described above. This allows all light radiated from the light source to be
20 efficiently used. The in-coupling optics may be formed integrally with the lightguide (FIG. **17C**), or may be formed as a separate element from the lightguide and then adhesively bonded to the lightguide (FIG. **17B**). In the latter configuration, optical rods having a diameter equal to the
25 diameter of the radiation aperture of the light source can be

used. Plastic or glass rods can provide optical collimation in two dimensions. Similar light control can be achieved by edge profiles with ball lenses, barrel lenses, hemispherical or prismatic lenses, etc.

5 [0163] A lightguide with integrated apertures can be used as a separate element. Alternatively, it may be laminated onto the substrate on one surface or both surfaces. In the case of frontlight elements, they are generally laminated on both sides. In the backlight concept, two or more laminated
10 lightguides are used. In both the backlight type and the frontlight type, multiple layers with apertures control the light in each layer or each medium.

[0164] In the case of optically transparent claddings, coatings, or films, the lightguide configuration according to
15 the embodiment is used for frontlights, backlights, window or facade illumination, signage and signal lighting, solar applications, decorative illumination, light shields, masking, roof lighting, or other public or general illumination.

20 [0165] In other embodiments, the light distribution element/lightguide element includes at least one optically functional layer with an optically functional pattern that at least has a light out-coupling function. The lightguide is implemented with optical filter apertures and with an optical
25 pattern such as an out-coupling pattern. Such a lightguide

may include a base medium for propagating the in-coupled light, an optical filter solution which is apertures with controlled uniformity, and an optical pattern layer for light out-coupling and distribution control thereof. The optical
5 pattern layer is a thin medium having an optical profile, whose functionality is based on an angle of incidence that is equal to or greater than the critical angle ($\geq \theta_c$) within the medium. The optical pattern, which is preferably uniform, may be formed with a constant density, and formed
10 across the whole area or in discrete manners. For the desired purpose of illumination or signal displaying, the optical pattern may be designed to vary in density of placement. Depending on the optical filter and apertures, the optical pattern layer may be adopted on one surface or
15 both surfaces of the out-coupling surface of the lightguide. The optical pattern layer is typically provided on a flat surface in a whole or partial surface area. The optical pattern layer may include a plurality of layers, each layer creating a different optical function, such as diffusion,
20 light coupling, polarization (wire grid), signal displaying, etc.

[0166] The optical functional layer(s) with an optical pattern may be designed to be application-specific, for example: opaque backlights, illumination and indicator panels
25 with a high fill factor (generally a constant fill factor)

and maximum coupling efficiency; transparent backlights, frontlights, and illumination panels with lower fill factor and optimized efficiency; and so on. The light distribution can be designed in various ways, e.g., narrow distribution, 5 wide distribution, elliptical, symmetric, asymmetric, etc. Maximum efficiency can be achieved by a continuous periodic profile. In a transparent solution, the maximum fill factor can be optimized with respect to transparency, fogging, and stray light. It is of great benefit to include a continuous 10 and efficient three-dimensional optical pattern that can be used for multiple applications. Such a three-dimensional optical pattern reduces master fabrication costs and product costs and allows for the production of large-size elements.

[0167] For light control in two directions, a hybrid 15 pattern may be used. In this case, an optically functional pattern configured as a hybrid pattern with a plurality of discrete or continuous profiles is provided in the light distribution/lightguide element.

[0168] The hybrid pattern has a three-dimensional optical 20 shape for two-directional light distribution control and are applicable to various illumination purposes. The hybrid pattern is based on discrete pixels, profiles, continuous or partially continuous profiles. The pattern profile is formed by at least partially linear, curved or sinusoidal 25 arrangements, zigzag arrangements, random or quasi-random

arrangements, etc. Combinations of different profiles, including variations in height, may be used. The angular profile of the pattern wall is formed with a constant angle throughout the region or at a symmetric or asymmetric angle with angular changes. A hybrid pattern with a sinusoidal orientation affects the light distribution along the x-y axes, with the optimized angle and period, amplitude and frequency of the pattern wall.

[0169] Pattern profiles can be designed in various ways and can have a variety of shapes and profiles, such as different blazed profile angles for longitudinal light distribution control, for example. The pattern profile can be optimized for different purposes and aims, and thus composite patterns can be based on many different pattern variations.

[0170] Hybrid solutions, realized as films, improve uniformity performance by avoiding the light streaks that linear patterns usually produce. It is also possible to avoid moiré effects with a non-linear pattern solution. In addition, the high fill factor allows to cover optical defects on the lightguides.

[0171] A hybrid pattern with a single film can replace two conventional brightness enhancement prism films and even two laminated prism sheets. The hybrid film provided herein may

have an air cavity pattern while having flat surfaces on the top and bottom surfaces for lamination.

[0172] The function of the hybrid pattern film is typically based on total reflection at an incident light angle greater than the critical angle of the medium. This differs from conventional prism sheets based on light out-coupled at an incident light angle smaller than the critical angle of the medium.

[0173] Hybrid patterns are produced by various methods including lithography, micromachining, or a combination thereof. The master tool is typically a drum tool used in roll-to-roll production for mass production purposes.

[0174] The at least one optical pattern on the optically functional layer may be formed by concave and convex parts selected from grooves, recesses, dots, pixels, and the like. These concave and convex parts have a cross-sectional concave-convex profile selected from rectangular waves, a blazed diffraction grating, slanted, prismatic, trapezoidal, hemispherical, and the like. The longitudinal shape is selected from linear, curved, waved, sinusoidal, and the like.

[0175] FIG. 7 shows: **(A)** a lightguide stack with a light distributing (directing) Filter (LDF); **(B)** a low-refractive index layer with apertures **131**, and **(C)** a pattern of optical cavities **141**. In the lightguide **14** stack **(A)**, optical

cavities **141** are formed in the lightguide **14**. A low-refractive index layer **15** is provided on the light-extracting surface of the lightguide **14**, and a low-refractive index layer **13C** with an aperture pattern is provided on the surface
5 at the opposite side. This is an example of a hybrid configuration.

[0176] FIG. **8A** shows an example configuration of a lightguide structure using a light distribution filter. In FIG. **8A**, **(a)** shows an intensity distribution when using a
10 hybrid prism with internal air cavities **83**, and **(b)** shows an intensity distribution when using a hybrid prism with a surface pattern.

[0177] In configuration **(a)**, a reflector **81** is provided on the rear surface of the lightguide **14**, where no pattern is
15 formed. On the light-extracting side of the lightguide **14**, a low-refractive index **88** having a gradient in its distribution density, a hybrid prism film **85** having a uniform air cavity pattern, and a diffuser **82** are layered in this order. The light distribution in the X-Y plane is controlled by the air
20 cavities **83** formed inside the hybrid prism film **85**.

[0178] In configuration **(b)**, a reflector **81** is provided on the rear surface of a non-patterned lightguide **14**. On the light-extracting side of the lightguide **14**, a low-refractive index **88** having a gradient in its distribution density, a
25 hybrid prism film **86** with a uniform pattern, and a diffuser

82 are layered in this order. The pattern of the hybrid prism film **86** controls the light distribution in the X-Y plane.

[0179] FIG. **8B** shows an example configuration of a lightguide structure using a light distribution filter. In FIG. **8B**, **(a)** shows an intensity distribution when using a hybrid prism with internal air cavities as the uppermost layer, and **(b)** in FIG. **8A** shows an intensity distribution when using a hybrid prism with a surface pattern as the uppermost layer.

[0180] In configuration **(a)**, an optically functional layer **13A** and a reflector **81** are provided on the bottom surface side of the lightguide; and on the upper surface, an optically functional layer **15**, a diffuser **82**, and a hybrid prism film **85** with cavities are provided in this order. As has been described in the first embodiment, the optically functional layer **13A** includes air cavities that are created by optical elements which are convex downwards in the figure. By air cavities **83** created inside the hybrid prism film **85**, the light distribution in the X-Y plane is controlled.

[0181] In configuration **(b)**, an optically functional layer **13A** and a reflector **81** are provided on the bottom surface side of the lightguide; and on the upper surface, an optically functional layer **15**, a diffuser **82**, and a hybrid prism film **86** with a surface pattern are provided in this

order. As has been described in the first embodiment, the optically functional layer **13A** includes air cavities that are created by optical elements which are convex downwards in the figure. By the optical pattern formed on the surface of the hybrid prism film **86**, the light distribution in the X-Y plane is controlled.

[0182] FIG. **9A** shows a hybrid pattern **90A** for light control in two directions. The hybrid pattern **90A** has a hybrid pattern profile in which individual hybrid pattern pixels **91A** are linked continuously.

[0183] FIG. **9B** shows a hybrid pattern **90B** for light control in two directions. The hybrid pattern **90B** is composed of a continuous hybrid pattern film, where the individual grating in the hybrid pattern **91B** is denser than in FIG. **9A**.

[0184] FIG. **10** shows another example optical pattern for two-directional light control. In FIG. **10**, **(A)** shows a general formula for the 3D shape of the hybrid pattern **90**. In FIG. **10**, **(B)** shows a cross-sectional profile of the hybrid pattern **90**. In FIG. **10**, **(C)** shows a cross-sectional shape and dimensions of the hybrid pattern **90**. In FIG. **10**, **(D)** is a side view showing the period of the hybrid pattern **90**.

[0185] FIG. **11** shows a hybrid pattern and a linear pattern, as examples of the pattern on the lightguide. In the linear pattern **(B)**, streaks of light are observed; in

hybrid pattern **(A)**, however, no streaks of light are observed.

[0186] FIG. **12** shows simulation results for light distribution filter films. All of them are within the concept of a hybrid pattern for light control in two directions, using a small PMMA lightguide with 20 LEDs and a diffuser, and using a low-refractive index and apertured backlight model. However, different prisms are used so as to result in different air cavity pattern profiles.

10 [0187] FIG. **13** illustrates the concept of a signal lightguide for a finger sensor or a fingerprint sensor. The LDF configuration without the optical pattern described above can be used as a single lightguide for a sensor. A narrow signal distribution angle can be achieved when processing a sensor signal from a finger, a fingerprint, etc. The signal distribution angle can be tuned on the top glass by combining low-refractive index layers with different refractive index values. For example, by varying the refractive index of the upper cladding (R_i : 1.18) and the refractive index of the lower cladding (R_i : 1.25) of the lightguide, it is ensured that patterns such as interference fringes are not visible or observed on the lightguide. Light scattering is suppressed and contrast is maintained at a high level.

FIG. **14** shows an example configuration of a signal lightguide. It is combined with a refractive index (R_i) in

the range of 1.18 to 1.25, but is not limited to this example; other combinations are also possible. This configuration can be applied to both single LED configurations and multi-LED configurations. The
5 multidirectional crosstalk is low even when thick glass plates **(G)** are used. Given that glass has a refractive index of 1.51, only 2.7% of all LED light enters the top glass.

[0188] FIG. **15A** and FIG. **15B** show results of fingerprint simulations at nine points. In FIG. **15A**, in general, the
10 optical power gradually decreases along the lightguide path due to light extraction from the lightguide. In the absence of multidirectional crosstalk, as shown in FIG. **15B**, no ghost image is formed and a clear and spatially accurate signal can be obtained, as shown in FIG. **15B**.

15 [0189] FIG. **16** shows simulation results for different setups with different fingerprints and LEDs. In FIG. **16**, **(A)** is calculated for a model with three LEDs and a fingerprint on a corner away from the center. The signal intensity is 20 Nits or less. The beam is slightly skewed.

20 [0190] In FIG. **16**, **(B)** is calculated on a model with three LEDs and fingerprints at a side edge. The signal intensity is 40 Nits or less. Ghosting is observed, although very slight. This could be an effect of ray tracing.

[0191] In FIG. **16**, **(C)** is calculated on a model with a single LED and a fingerprint in the center. The intensity of the signal is 30 Nits or less. A clear signal is observed.

[0192] In FIG. **16**, there is no multidirectional crosstalk
5 and no substantial ghost image is formed, as in the case of FIG. **15**.

[0193] The directivity of the signal is precisely controlled so that there is essentially zero (0)% of light that is incident on the sensor or display without being
10 reflected by a finger or other item. By narrowing the signal distribution, multidirectional crosstalk is small, even on a thick glass plate. In addition, ghosting is minimum. The signal source may be a single LED, multiple LEDs, or a laser component.

15 [0194] In the case of optical patterns, the signal can be collimated in two directions (X-Y) if necessary. Uniformity over 90% can be achieved if necessary.

[0195] The aforementioned signal lightguides can be designed in sizes from 500 mm to 1000 m, and its size is
20 generally adjusted on a roll-to-roll production line. In this case, a uniform and continuous structural piece can be cut into size as respectively required.

[0196] <master fabrication>

The fabrication of an optical master is costly and
25 difficult, especially in large sizes. The fabrication of

masters and rules for advanced lightguide optics, regardless of their size, is extremely difficult and incurs a high cost.

[0197] Therefore, the present invention proposes to produce large-sized master rolls by diamond cutting or lithography techniques and to mass produce a basic pattern film by the roll-to-roll method. The basic pattern film can be produced by applying a resist on the pattern and mask lithography exposure and development. The mask pattern is replicated by forming a metal film by electroplating in the apertures formed. For example, nickel shims can be used as a tool to produce optical films and sheets.

[0198] FIG. **18A** to FIG. **18E** illustrate an example of a master fabrication process. In FIG. **8A**, a submaster **189**, whose surface pattern is shaped by cutting with a diamond shaper, is used to transfer the pattern to a base plastic substrate **181** by using the imprinting technique. The width of the submaster **189** can be enlarged to a size of 1 m or more.

[0199] In FIG. **8B**, photoresist **185** is applied to the base plastic substrate **181** with a transfer pattern **182**. In FIG. **8C**, exposure through a mask or direct exposure is performed, followed by a development, whereby desired portions of the photoresist **185** are removed so as to partially expose the transfer pattern **182**.

[0200] In FIG. **8D**, for example, by performing nickel plating and detaching the base plastic substrate **181**, a nickel stamper **180** for lightguide replication is obtained, as shown in FIG. **8E**. This nickel stamper **180** has, as an example, a random dot pattern for a periodic blazed profile.

[0201] FIG. **19** shows an example application of the structural piece of the embodiment to window illumination. By attaching (laminating) a stacked body **201A** including an optically functional layer **202** to a window **200**, sunlight and illumination light can be effectively captured on the opposite side (e.g., indoors) to the incident side. The stacked body **201A** includes the optically functional layer **202** having air cavities **203A** and a transparent optical adhesion layer **204**. The optically functional layer **202** can be formed of a polymer, a glass film, or the like. With the optical adhesion layer **204**, the optically functional layer **202** can be affixed to either surface of the window **200**, to increase the amount of light intake.

[0202] FIG. **20** shows a stacked body **201B** that includes an optically functional layer **202** having a different pattern of air cavities **203B**. Such a cavity pattern can also be used effectively.

[0203] FIG. **21A** illustrates a method of producing the optically functional layer **202** of FIG. **19**. FIG. **21** is an adhesive-free lamination method. A non-patterned first film

211 and a second film **212** with a desired pattern **214** on the surface are attached together adhesive-free (e.g., by microwave surface treatment). The first film **211** and the second film are formed of polymethyl methacrylate (PMMA),
5 polycarbonate (PC), etc. Through the attaching-together, cavities **213** are formed.

[0204] FIG. **21B** shows another method of making the optically functional layer **201A** of FIG. **19**. In FIG. **22**, the two films are adhesively bonded with an adhesion layer **216**.
10 The thickness of the adhesion layer is about 1 to 3 μm . Air cavities **213** are created by the second film **212** and the adhesion layer **216**. It is ensured that the pre-cured adhesive will not enter the cavity pattern during the attaching-together.

[0205] The method of attaching-together may be any method that does not affect the shape of the air cavities. For example, a chemical bond can be obtained by pretreating the laminate surface by using a VUV light (vacuum ultraviolet) source or APP (atmospheric plasma) and then laminating it
20 under constant pressure. This method can achieve good mechanical strength.

[0206] FIG. **25** illustrates the effect of stray light suppression by using the lightguide **14** in an embodiment with optical cavities **141a** being formed. As a model, a first
25 portion **251** including a lightguide **14** with microlens-type

optical cavities **141a** inside and a second portion **252** including a lightguide **14** with microlens-type optical cavities **141b** inside are used. The bumps of the optical cavities **141a** and the optical cavities **141b** are oriented in
5 the same direction of light extraction (i.e., upwards in the plane of the figure). The bottom side of the optical cavities **141a** and the bottom side of the optical cavities **141b** are the sides that allow stray light to escape.

[0207] A low-refractive index light absorption layer **254**
10 is adhesively bonded to the bottom surface of the first portion **251** with an optical adhesive **253**, and a low-refractive index light absorption layer **254** is adhesively bonded to the upper surface of the second portion **252** with the optical adhesive **253**. By placing the light absorption
15 layers **254** so as to face each other, the intensity of light extraction from the upper surface of the first portion **251** and the intensity of stray light from the bottom surface of the second portion **252** are calculated.

[0208] The contrast ratio is as high as 44, where contrast
20 is defined as the ratio of the intensity of the extracted light to the intensity of stray light intensity ($I_{\text{ext}}/I_{\text{stray}}$).

[0209] FIG. **26** shows, as Comparative Example, a simulation result on the contrast ratio of a conventional lightguide **340** with a pattern formed on its surface. As in FIG. **25**, a low-
25 refractive index light absorption layer **254** is adhesively

bonded with an optical adhesive **253** to each part, but with the light absorption layers **254** serving as the outermost layers, the light of interest and the stray light are emitted between the two light absorption layers **254**.

5 [0210] This configuration has a contrast ratio of 3, and visibility is very poor compared to the configuration of FIG. **25**. It can be seen that by using a lightguide with internal air cavities in the embodiment, the contrast or visibility can be greatly improved.

10 [0211] FIG. **27** and FIG. **28** illustrate the concept of window illumination with an antireflection film. In both figures, an AR film **145** is provided on the light-extracting surface. In FIG. **27**, the AR film **145** is provided on the light-extracting surface of a lightguide **271** made of a
15 polymer, and an optically functional layer **273** is provided on the surface at the opposite side, with an optical adhesion layer **272**. The optically functional layer **273** allows the light which is output from the light source **21** and incident from the edge of the lightguide **271** to be efficiently
20 redirected in the direction of the AR film **145**. Stray light is suppressed by the AR film, while light of interest is sufficiently extracted in the direction of the arrow. The optical pattern that the optically functional layer **273** has may be a constant pattern or a pattern with a gradient in
25 density or occupancy.

[0212] In FIG. **28**, a glass cover **17** is layered on the light-extracting surface of the lightguide **271** of FIG. **27**, and an AR film **145** is provided on the surface of the cover **17**. In this configuration, too, the optically functional layer **273** efficiently redirects the incident light to the lightguide **271**, in the direction of the AR film **145**. Both of the configurations of FIG. **27** and FIG. **28** can be extended to both-surface illumination.

[0213] FIG. **29** and FIG. **30** show examples of detachable optical device configurations. In FIG. **29**, a stacked body of the configuration of FIG. **27** is adhesively bonded, detachably, to an optical medium layer **11** (e.g., a display) with a removable optical adhesion layer **276**. A low-refractive index layer **275** is inserted between the lightguide **271** and the optical adhesion layer **276**.

[0214] In FIG. **30**, the stacked body in the configuration of FIG. **28** is adhesively bonded, detachably, to an optical medium layer **11** (e.g., a display) with a removable optical adhesion layer **276**. The configurations of FIG. **29** and FIG. **30** are optimum for displaying posters, posters, and other objects that are intended to be replaced.

[0215] Although embodiments have been described based on specific example configurations, a variety of modifications and application examples are possible. Transparent solutions using lightguides with embedded cavities have a variety of

applications, such as signage, transparent mobile electronic terminals or tablets, transparent VR displays, marketing windows, etc.

[0216] In an optical device according to an embodiment,
5 light is extracted/out-coupled at a first surface; and a second surface allows light to be propagated or directed without out-coupling, but does not leak undesirable Fresnel reflection or stray light from the lightguide. When a periodic pattern is used for the optically functional layer,
10 this optically functional layer and the second surface work in cooperation to improve light redirection and extraction (out-coupling).

[0217] Alternatively, light is extracted/out-coupled at the first surface; and the second surface allows light to be
15 propagated or directed without out-coupling, while minimizing Fresnel reflection in undesirable directions.

[0218] In order to minimize Fresnel reflection, an AR pattern, a multilayer coating, an AR coating having a wide-range antireflection effect based on low-refractive index
20 coating, or an antireflection coating structure may be provided on at least one of the first surface and the second surface.

[0219] The profile or pattern shape of the optical pattern may be appropriately designed, e.g., rectangular waves, a
25 blazed diffraction grating, slanted, microlenses, or

trapezoidal. When the optical pattern is air cavities, an AR coating, an AR pattern, etc., may be provided at the interfaces of the air cavities. In the case where the air cavities are created by lamination of two films, an AR
5 coating or an AR pattern may be previously formed on one of the films that is not patterned.

[0220] The size of the optical pattern should be small enough not to be visible to the human eye (e.g., 20 μm or less in size along the direction of layering). When the size
10 is larger than this, it may be used in conjunction with an AR coating or AR pattern to prevent it from being visible.

[0221] This application incorporates the entire disclosure of US Provisional Application No. 62/646461, filed with the U.S. Patent and Trademark Office on March 22, 2018.

15

REFERENCE SIGNS LIST

[0222]

10, 10A-10D, 30A, 30B, 40A, 40B, 100A, 100B optical device
11 optical medium layer
13, 23 low-refractive index layer (second optically
20 functional layer)
131, 132 aperture
13A optical layer (second optically functional layer)
133, 135 optical protrusion
134 air cavity

14, 174, 274 lightguide

141 optical cavities

15 low-refractive index layer (first optically functional layer)

5 **21** light source

31, 32 light absorption layer

33, 34 redirecting layer

170 in-coupling optics

171 optical element

10 **173** air cavity

CLAIMS

[claim 1]

An optical device comprising:

5 a light guiding layer;

a first optically functional layer provided on a first principal face of the light guiding layer;

a second optically functional layer provided on a second principal face of the light guiding layer that is on an opposite side to the first principal face; and

an optical medium layer provided on a surface of the second optically functional layer that is on an opposite side to the light guiding layer, wherein

a refractive index of the first optically functional layer is lower than a refractive index of the light guiding layer.

[claim 2]

The optical device of claim 1, wherein,

the first principal face is a light-extracting surface of the light guiding layer; and

the first optically functional layer is a uniform layer that is formed uninterruptedly of a low-refractive index material.

[claim 3]

25 The optical device of claim 1 or 2, wherein

the second optically functional layer includes an optical element that is convex toward the optical medium layer.

[claim 4]

5 The optical device of claim 3, wherein
an air cavity is created between the optical element and the optical medium layer.

[claim 5]

10 The optical device of claim 1 or 2, wherein
the second optically functional layer is a layer of low-refractive index material that includes a plurality of apertures disposed at an interface with the light guiding layer.

[claim 6]

15 The optical device of claim 5, wherein,
occupancy of the apertures in the interface has a gradient along an optical axis direction of the light guiding layer.

[claim 7]

20 The optical device of claim 6, wherein
occupancy of the apertures in the interface increases along the optical axis direction.

[claim 8]

The optical device of claim 1 or 2, wherein,

the second optically functional layer is a uniform layer that is formed uninterruptedly of a low-refractive index material; and

the light guiding layer includes an air cavity.

5 [claim 9]

The optical device of claim 8, wherein

the air cavity includes an incident surface at which light propagating in the light guiding layer enters and an outgoing surface through which light entering the air cavity
10 is emitted from the air cavity, and an antireflection film is provided on at least one of the incident surface and the outgoing surface.

[claim 10]

The optical device of any of claims 1 to 9, wherein

15 the second optically functional layer or the light guiding layer is adhesively bonded, detachably, to a layer at least including the optical medium layer.

[claim 11]

The optical device of any of claims 1 to 9, wherein,

20 the second optically functional layer, the light guiding layer, and the first optically functional layer constitute a first stacked body;

the optical device comprises a second stacked body at a surface of the optical medium layer that is on an opposite

side to the first stacked body, the second stacked body at least including a second light guiding layer; and

at least one of the first stacked body and the second stacked body is adhesively bonded, detachably, to the optical
5 medium layer.

[claim 12]

The optical device of any of claims 1 to 11, wherein
at least one of the first optically functional layer and the second optically functional layer has a function selected
10 from reflection, transmission, polarization, and refraction.

[claim 13]

The optical device of any of claims 1 to 12, wherein
the first optically functional layer is a total reflection film with respect to light propagating in the
15 light guiding layer.

[claim 14]

The optical device of any of claims 1 to 13, wherein
the first optically functional layer and the second optically functional layer have different refractive index
20 values.

[claim 15]

The optical device of any of claims 1 to 14, further comprising a third functional layer through which light is extracted to the outside from the light guiding layer.

25 [claim 16]

The optical device of claim 15, wherein
the third functional layer has an optical pattern
including a plurality of discrete profiles, or including a
plurality of profiles which are at least partially
5 continuous.