

**SYSTEM FOR DETECTING AND LOCATING SUBMERGED OBJECTS
HAVING NEUTRAL BUOYANCY SUCH AS MOORED MINES AND
ASSOCIATED METHOD**

5 The invention disclosed herein relates to a system
for detecting and locating underwater objects having
neutral buoyancy, comprising a sonar making it possible
to detect the underwater objects having returned sonar
echoes, that is to say returned echoes following the
10 emission of an acoustic pulse (or acoustic ping) by the
sonar.

 Moored mines are mines of neutral buoyancy being
attached by a cable, called tether, to an anchor,
called sinker, resting on the seabed. The sonars are
15 mounted either on a surface ship, or on a fish towed by
a surface ship or on a self-propelled underwater
vehicle.

 One of the problems in detecting objects having
neutral buoyancy is being able to detect mines over a
20 wide swath so as to monitor an area of the marine
environment that is as wide as possible in a minimum
time. Another problem is being able to locate the
detected mines with a sufficiently great accuracy in
the three dimensions of space. In other words, another
25 problem is producing a system for detecting underwater
objects that exhibits a sufficient locating accuracy in
the three dimensions of space of the order of a few
meters.

 One existing solution consists in using front
30 looking sonars which insonify the water column in front
of the carrier and which form a plurality of contiguous
directional channels in reception terms. One drawback
with this solution is that, to cover a wide swath at
right angles to the axis of the carrier and locate

underwater targets having neutral buoyancy with a good accuracy in terms of relative bearing, arrays that are of large dimensions, are bulky and consume a lot of electrical energy are needed. This drawback is
5 incompatible with the trend in mine warfare which is to distance man from the threat. Technical solutions are sought for mounting the sonars on autonomous carriers, on board which a limited energy is stored, rather than on ships of mine hunter type. Another drawback with
10 front looking sonars is that they do not make it possible to locate the mines with a good accuracy in terms of elevation without an array that is directional in elevation and which therefore adds bulk and energy consumption.

15 Another solution is described in patent application US5506812; it consists in using cylindrical emission and reception arrays that make it possible to insonify a toroidal zone surrounding the carrier in a single acoustic ping, that is to say a single acoustic
20 pulse. This solution presents the drawbacks of requiring a high emission power to transmit an acoustic pulse over 360° and of being very bulky since it uses an array with 120 reception channels. Moreover, the processing of the multiple reception channels to detect
25 objects in the water column and locate them can prove complex.

The aim of the invention is to remedy at least one of the abovementioned drawbacks.

To this end, the subject of the invention is a
30 system for detecting and locating submerged underwater objects having neutral buoyancy, comprising at least one mechanically steered sonar with a single channel, the mechanically steered sonar being a sonar with a single emission channel making it possible to perform

the insonification of a first individual sector in a first pointing direction by means of a single first pulse and forming a single reception channel suitable for acquiring a first acoustic signal resulting from
5 said insonification, the mechanically steered sonar being mounted on a carrier intended to advance in a main direction, such that the first pointing direction is substantially lateral to the carrier and that the first individual sector exhibits a wide relative
10 bearing aperture and a narrower elevation aperture, the scanning sonar comprising a pointing device intended to tilt the pointing direction about an axis of rotation substantially parallel to the main direction allowing the sonar to acquire first acoustic signals resulting
15 from insonifications performed in different pointing directions. The system according to the invention advantageously comprises a processing unit configured to locate underwater objects having neutral buoyancy from first acoustic signals.

20 This system based on a mechanically steered sonar offers the advantage of being inexpensive, small and a low energy consumer compared to a multi-beam sonar (with a plurality of reception channels) which would require a powerful and bulky transmitter and a probably
25 curved reception array with at least fifty or so channels. It also makes it possible, by configuring it shrewdly and by shrewd processing operations, to detect marine objects and locate them with a good accuracy in the three dimensions of space of the order of that
30 obtained by means of a side-scan sonar for the detection of underwater objects placed on the seabed. It notably makes it possible to obtain position measurements exhibiting a good location accuracy in the three dimensions from a sonar having a poor horizontal

resolution since it is a sonar with a single emission and reception channel exhibiting a poor resolution in relative bearing terms.

5 This system also makes it possible to detect short moored mines (situated at a low height relative to the seabed) which are difficult to detect with a side-scan sonar, particularly in proximity to the maximum observation range.

10 Advantageously, the system comprises a processing unit configured to locate underwater objects having neutral buoyancy from at least one first acoustic signal.

15 In a particular embodiment, the system comprises a plurality of mechanically steered sonars spaced apart in the main direction and the oriented pointing directions of which are directed toward the same side of a vertical plane passing through the main direction.

20 Advantageously, the system comprises at least one side-scan sonar intended to image the seabed in a second pointing direction in a second individual sector exhibiting a wide relative bearing aperture and a narrow elevation aperture, the side-scan sonar forming a plurality of relative bearing reception channels and being mounted on the carrier such that the second
25 pointing direction is oriented substantially laterally to the carrier on the same side of the carrier, in relation to the vertical plane passing through the main direction, as the first pointing direction, the system further comprising a human-machine interface comprising
30 a display device intended to simultaneously display a first sonar image representing first acoustic signals and a second sonar image representing second acoustic signals acquired during a same period of acquisition by the mechanically steered sonar and respectively by the

side-scan sonar with the human-machine interface being configured such that, when the first and second images are displayed simultaneously, an operator can, when they visually identify, on the first image, a first
5 echo created by a submerged object having neutral buoyancy, visually identify instantaneously, on the second image, if a second echo has been reflected by an object placed on the seabed substantially directly below the submerged object.

10 This feature allows an operator to classify the detected underwater objects and notably classify them according to whether they are moored mines or free objects having neutral buoyancy. In effect, both the mine and the sinker return intense echoes which are
15 represented by bright zones on the sonar images. If, at the moment when a first bright echo is obtained by means of the scanning sonar, a second bright echo is also obtained by means of the side-scan sonar around the position of the first echo, there is a high
20 probability that this second echo has been formed by a sinker and that the first echo has been formed by a moored mine. This allows an operator to confirm a detection of a moored mine in the volume. It is thus possible to distinguish moored mines from free objects
25 such as shoals of fishes or mammals.

In a particular embodiment, the display device is configured such that the first image and the second image displayed have substantially identical sizes and such that an echo included in the first image and an
30 echo included in the second image reflected by respective objects situated at a same distance from the mechanically steered sonar and respectively from the side-scan sonar and generated following a first and a second simultaneous insonification step are represented

substantially at a same abscissa and at a same ordinate on the first image and on the second image.

In a preferred embodiment, the human-machine interface comprises tracking means allowing an operator
5 to simultaneously move two cursors displayed by the display device, one on the first image and the other on the second image, the display device being configured such that the two cursors occupy, on the first and the second image, positions corresponding to a same
10 geographic position in a terrestrial reference frame.

Advantageously, the cursor displayed on the first image is provided with a curve representing a set of the possible positions on the first image of echoes originating from an object having created an echo
15 represented at the position pointed to by the cursor.

Advantageously, which the first image and the second image represent the first and second acoustic signals in instant mode of emission of the acoustic pulse originating the signals/distance separating, in
20 the horizontal plane, the objects originating the echoes, and being included in said signals, from a fixed point in relation to said sonars.

Advantageously, the system comprises a processing unit suitable for identifying, in first signals, first
25 effective echoes effectively created by effectively submerged effective objects having neutral buoyancy, the display device being configured so as to display, superimposed with the first image and/or the second image, symbols at the effective positions considered as
30 being effectively occupied by the effective objects.

Advantageously, said human-machine interface comprises a classification unit configured so as to allow an operator to classify first echoes visible on the first image or first effective echoes identified,

by a processing unit in first signals, as being created by effectively submerged effective objects having neutral buoyancy visible in a first class taken from a plurality of classes comprising a moored mine class and
5 a free floating object class.

The invention relates also to a method for detecting and locating underwater objects having neutral buoyancy, using a system according to the invention, the method comprising a scanning step in
10 which the mechanically steered sonar scans, a plurality of times, a sector to be imaged open in a plane substantially at right angles to the main direction, in which the mechanically steered sonar performs successive sonar acquisition steps in which the
15 pointing device points the first pointing direction in successive pointed directions included in the sector to be imaged, and, for each pointed direction, transmits a first acoustic pulse at a first insonification instant and acquires a first acoustic signal resulting from the
20 first acoustic pulse.

Advantageously, the method comprises a detection step for detecting first potential echoes created by submerged objects having neutral buoyancy by means of first signals, comprising unitary detection steps, each
25 unitary detection step comprising an identification step for identifying first potential echoes, considered as having been created by respective potential floating objects in response to a first acoustic pulse, the first potential echoes being parts of first signals
30 satisfying a predetermined selection criterion.

Advantageously, the identification step comprises a step of thresholding of the contrasts of first signals.

Advantageously, the mechanically steered sonar is configured, given the speed of the carrier, so as to acquire, in the scanning step, more than once, echoes from a one-off object fixed in the terrestrial reference frame and located at a depth lying between a predetermined minimum depth and a predetermined maximum depth, and located at right angles to the main direction in a horizontal plane, at a distance from the mechanically steered sonar greater than a predetermined minimum range and less than a predetermined maximum range, the method comprising a step of locating effective submerged objects having neutral buoyancy from the first acoustic signals acquired in the scanning step and from the first potential echoes.

Advantageously, the method comprises a step of locating submerged objects having neutral buoyancy, comprising:

- a step of determination of potential positions of the potential floating objects comprising, for each first potential echo, a step of determination of a set of potential positions, that the corresponding potential object is likely to occupy, from the position of the sonar at the first instant of emission of the first acoustic pulse originating the first potential echo,
- an accumulation step in which positions that are fixed in the terrestrial reference frame are assigned respective probabilities of occupancy corresponding to probabilities of being actually occupied by an object, said respective probabilities of occupancy being initialized at the start of the accumulation step and incremented each time the respective fixed positions are

determined as being potential positions in the step of determination of potential positions,
- a step of identification of effective positions effectively occupied by effective submerged
5 objects having neutral buoyancy from fixed positions assigned a probability of occupancy above a predetermined threshold.

Advantageously, the set of potential positions of a potential object is a circular arc, of radius equal
10 to the distance separating the potential object from the mechanically steered sonar computed from the difference between the first instant of emission and the instant of reception of the first potential echo created by the potential object, the center of which is
15 the position of the sonar at the first instant of emission and the aperture of which is equal to the aperture of the first individual sector, the first individual sector corresponding to the sector in which is transmitted the portion of the main lobe of the
20 first acoustic pulse attenuated to the maximum of 3dB, or equal to the aperture of the first individual sector plus a predetermined tolerance aperture.

Advantageously, the method is implemented by means of a system according to the invention, comprising a
25 step of imaging of the seabed concurrent with the scanning step, the step of imaging of the seabed consisting in imaging the seabed by means of the side-scan sonar by transmitting second successive acoustic pulses at second successive insonification instants,
30 and by conducting the acquisition of the second successive acoustic signals deriving from the second successive pulses, the method further comprising a step of simultaneous display of a first image representing first acoustic signals and of a second image

representing second acoustic signals acquired during a same period of acquisition by the mechanically steered sonar and respectively by the side-scan sonar.

Advantageously, the method comprises a step of
5 classification, by an operator by means of a classification unit, of at least one first echo visible on the first image in a class taken from a plurality of classes comprising a moored mine class and a free floating object class.

10 The invention relates also to a system for detecting and locating submerged underwater objects having neutral buoyancy suitable for implementing the method according to the invention, comprising a processing unit configured so as to implement the step
15 of identification of the first potential echoes.

Advantageously, the system comprises a positioning unit, such as an inertial navigation system, configured so as to determine the position of the carrier as a function of time, in which the processing unit is
20 configured so as to implement the location step, the positioning unit or the processing unit being configured so as to determine the position of the mechanically steered sonar.

Other features and advantages of the invention
25 will become apparent on reading the following detailed description, given as a nonlimiting example and with reference to the attached drawings in which:

- figure 1 schematically represents, in
side view, a carrier equipped
30 with elements of a detection system according to the invention, the equipment items represented in broken lines are equipment items installed

- inside the carrier, and remote equipment items are also represented in this figure,
- 5 - figure 2 schematically represents, in plan view, a carrier equipped with elements of a detection system according to the invention,
- 10 - figure 3 schematically represents a transverse cross section of a carrier equipped with elements of a detection system according to the invention,
- 15 - figure 4 represents a flow diagram of the method according to the invention,
- 20 - figure 5 represents, on the same transverse cross section, successive pointed directions of the scanning step,
- 25 - figure 6 schematically represents the limits of a zone of the marine environment imaged by the mechanically steered sonar,
- 30 - figure 7 schematically represents potential positions occupied by objects creating first echoes received by the mechanically steered sonar in two imaging steps according to pointed directions exhibiting a same elevation angle,
- figure 8 schematically represents potential positions occupied

5 by the first individual sector
in successive imaging steps
separated by a scanning period
according to pointed
directions exhibiting a same
elevation angle,

10 - figure 9 schematically represents an
exemplary display according to
the invention of the
representations of first
echoes and of second echoes
received by the mechanically
steered sonar and respectively
by the side-scan sonar.

15 From one figure to another, the same elements are
identified by the same references.

Figure 1 shows elements of a system for detecting
underwater objects according to the invention.

20 The detection system comprises an imaging system
comprising a first sonar 2, called mechanically steered
sonar, intended to image the water column. This
mechanically steered sonar 2 is mounted on a carrier 1.
The carrier 1 can be a ship, a towed or autonomous
underwater vessel. It is intended to advance in a main
25 direction of advance D considered as being
substantially horizontal. The direction D is an
oriented direction. The main direction D is the
longitudinal direction of the carrier 1 and is oriented
toward the front of the carrier. The carrier 1
30 advantageously comprises stabilizers, such as rudders
that are not represented, making it possible to keep
the bank angle of the carrier constant (that is to say
to limit the roll) and possibly limit the yaw and pitch
such that the depth of the sonar or of the sonars

embedded on board the carrier is constant with constant depth of the carrier when the direction of advance is substantially horizontal in the terrestrial reference frame.

5 The mechanically steered sonar 2 is a sonar with a single transmit channel and a single reception channel. It is mounted on one of the flanks of the carrier 1. As can be seen in figure 2, the detection system advantageously comprises two mechanically steered
10 sonars 2, 2' mounted on the respective flanks 1a, 1b of the carrier 1. Only the sonar 2 will be described in the patent application, the other sonar 2' being configured and arranged in the same way.

 The mechanically steered sonar 2 is intended to
15 conduct a sonar acquisition of a first individual sector SE1 by transmitting a single first acoustic pulse and by conducting the acquisition of the first acoustic signals thus obtained. The first individual sector SE1 is the sector at -3dB in which is emitted
20 the main lobe of an acoustic pulse emitted by the sonar 2. A first oriented pointing direction PA1 is defined, visible in figure 2, corresponding to the direction in which the maximum acoustic energy is sent when the sonar transmits a first acoustic pulse. The
25 mechanically steered sonar 2 is mounted on the carrier 1 such that the first pointing direction PA1 is substantially lateral to the carrier 1. In other words, the first pointing direction PA1 extends in a substantially vertical plane forming, in a horizontal
30 plane in the terrestrial reference frame, a non-zero angle with the main direction D. This plane is advantageously substantially at right angles to the main direction D. The mechanically steered sonar 2 is also mounted on the carrier 1 such that the first

individual sector SE1 exhibits a wide relative bearing aperture $2\theta_{3H}$ (in the horizontal plane) and a narrow elevation aperture $2\theta_{3V}$ (in the vertical plane), visible in figure 3, so as to obtain the desired angular resolution according to the elevation. The narrow elevation aperture makes it possible to limit the effect of reverberation from the surface of the water and locate the objects having neutral buoyancy with a good accuracy. The first pointing direction PA1 divides the first individual sector SE1 into two equal parts in these two planes.

The mechanically steered sonar 2 comprises a mechanical pointing device 3 intended to tilt the first pointing direction PA1 about an axis of rotation x substantially parallel to the main direction D. In other words, the pointing device 3 allows the sonar 1 to perform a vertical scan. This device is, for example, a device that makes it possible to tilt the emission and reception arrays of the sonar about the axis x. In other words, it mechanically tilts the pointing direction about the axis x.

The system according to the invention advantageously comprises a processing unit 5 making it possible to locate and possibly detect, prior to the locating, underwater objects having neutral buoyancy from at least one first acoustic signal.

The mechanically steered sonar 2 is not bulky, and a low electrical energy consumer. Moreover, the first acoustic signals obtained by means of this sonar are easy to process notably to proceed to detect underwater objects, and locate them. It makes it possible, by configuring it and by processing the acoustic signals obtained shrewdly, to locate, accurately and with little complexity, underwater objects detected in the

three directions of space over a swath comparable to that of a side-scan sonar.

Advantageously, the system according to the invention comprises a plurality of mechanically steered
5 sonars spaced apart in the main direction and the oriented pointing directions of which are directed toward a same side of the carrier, that is to say on the same side of a vertical plane passing through the main direction D. The directions pointed to by the
10 adjacent sonars at a given instant are offset by an appropriate angle. They are for example offset by half of the angular aperture of the sector to be imaged such that each sonar scans only half of the sector to be imaged or else offset by half of the tilt step. The
15 tilt step and the sector to be imaged are defined subsequently. The processing unit 5 is then configured to locate and possibly detect underwater objects having neutral buoyancy from at least one first acoustic signal from at least one scanning sonar. This
20 configuration makes it possible, for a same spatial resolution, to increase the maximum speed of the carrier, and/or increase the vertical resolution of the moored mine detection system, and/or refine the directionality in the vertical plane in order to
25 improve detection efficiency, particularly in the directions close to the interfaces (surface, bed) and location efficiency in the vertical plane while keeping a scanning speed compatible with a minimum number of target hits (> 3), and/or to increase the scanning
30 speed in order to multiply the number of target hits, and/or to increase the width of the vertical sector covered.

The invention relates also to a method for detecting objects in the volume of water, that is to say underwater objects having neutral buoyancy.

This method comprises a scanning step 20 in which
5 the mechanically steered sonar 2 scans, a plurality of times, a sector to be imaged SI that is open in elevation, that is to say in a plane at right angles to the main direction D. This sector to be imaged SI is delimited by a minimum direction $D_{\min}$ and a maximum
10 direction $D_{\max}$ respectively exhibiting a minimum elevation angle $\theta_{\min}$ and a maximum elevation angle $\theta_{\max}$ greater than the minimum elevation angle. The elevation angles are defined relative to the horizontal plane P passing through the sonar 2 represented by dotted lines
15 in figure 3, the elevation angle of an oriented direction being counted as positive when it is directed to a point situated above the horizontal plane P.

As can be seen in figures 4 and 5, in the scanning step 20, the mechanically steered sonar 2 performs
20 successive sonar acquisition steps 20i, of index i with $i = 1$ to N (where N is the number of sonar acquisition steps performed in the scanning step equal to 7 in figure 5), in which the pointing device 3 points the first pointing direction PA1 in respective pointed
25 directions P_i of index or of serial number i. The directions P_i are included in the sector to be imaged SI and have elevation angles of respective indices θ_i by tilting the first pointing direction PA1 about the axis of rotation x. In each sonar acquisition step 20i, the
30 pointing device 3 points, in a step 21i, the first pointing direction PA1 in a pointed direction P_i , insonifies, in a step 22i, the first individual sector SE1, that is to say transmits a first acoustic pulse I_i at a first instant of insonification t_i and acquires 23i

a first acoustic signal sl_i corresponding to an acoustic intensity as a function of time. The method also comprises a step of storage 24i, in a memory 4, of the first acoustic signal sl_i and of the insonification
5 instant t_i .

By pointing the mechanically steered sonar 2 laterally to the carrier 1 and by having it perform a vertical scan (by rotation of the pointing direction about an axis of rotation substantially parallel to the
10 axis of the underwater vehicle), it is possible to detect underwater objects having neutral buoyancy over a swath comparable to that of a side-scan sonar imaging the seabed that can range from 20 to 300 meters.

The fact that the mechanically steered sonar
15 points laterally makes it possible to obtain images laterally relative to the direction of the carrier. In this way, the detection of objects in the water column such as moored mines can be performed simultaneously with the imaging of the seabed, by a side-scan sonar,
20 directly below the zone imaged by the mechanically steered sonar. It is consequently possible to rapidly image a wide zone, both the seabed and the water column, without having to pass over the same point several times.

25 The successive pointed directions P_i are chosen so as to totally insonify the sector to be imaged SI, that is to say such that the first individual sector SE1 covers contiguous successive zones, the set of the contiguous zones forming the sector to be imaged. In
30 other words, the angle θ formed between two consecutive pointed directions is advantageously substantially equal to or less than $2\theta_{3H}$ and preferably less than $2\theta_{3H}/2$.

The scanning is advantageously performed, as represented in figure 5, where $N=7$, by conducting consecutive two-way sweeps of the sector to be imaged SI, that is to say by scanning the sector to be imaged alternately in a first direction then in a second direction opposite to the first direction. Advantageously, the scanning is performed at a constant speed (that is to say that the time to switch from one pointed direction to the next is constant) and with a constant step, called tilt step $\delta\theta$, between two consecutive a pointed directions.

The scanning in two-way sweeps makes it possible to have a high probability of imaging a fixed object more than once upon the movement of the carrier and also makes it possible to perform a rapid imaging of a zone to be imaged. A scanning period is therefore the time needed to conduct a two-way sweep, that is to say the time needed to scan the sector to be imaged SI once by starting from a pointed direction exhibiting an elevation angle and by returning to a pointed direction exhibiting the same elevation angle. It would be possible, less advantageously, to scan the sector to be imaged only in one direction by starting from the minimum (or maximum) direction, by pointing the first pointing direction in consecutive pointed directions within the sector as far as the maximum (or minimum) direction, by returning to the initial direction and by repeating the scan in the same direction.

The carrier 1 moves throughout the scanning step in relation to the terrestrial reference frame. It follows a substantially rectilinear and preferably uniform trajectory at a substantially constant speed and at substantially constant altitude H_{mp} in relation to the seabed 7.

As can be seen in figure 6, the minimum $\theta_{\min}$ and maximum $\theta_{\max}$ elevation angles are defined so as to image a water column extending horizontally and transversally (that is to say at right angles to the main direction D) between a predefined minimum range $R_{\min}$ (defined by the direction $D_{\max}$) and a predefined maximum range $R_{\max}$ (defined by the direction $D_{\min}$) and, vertically, between a predefined minimum depth $I_{\min}$ and a predefined maximum depth $I_{\max}$. The depth of an object is the vertical distance separating this object from the surface level of the water. The minimum elevation angle $\theta_{\min}$ and the maximum elevation angle $\theta_{\max}$ depend on the depth I_{ms_i} of the mechanically steered sonar 2 at constant altitude H_{s_i} in relation to the seabed 7, and also on $R_{\min}$, $R_{\max}$, $I_{\min}$ and $I_{\max}$. The maximum depth $I_{\max}$ is chosen so as to be less than the depth I_{fm} of the seabed and the minimum depth must be greater than 0 to be below the surface of the water 8. The directions $D_{\min}$ and $D_{\max}$ can exhibit positive or negative elevation angles $\theta_{\min}$ and $\theta_{\max}$, the condition being that, for the depth of the sonar 2, the volume imaged when the pointing direction points in these directions in the volume defined between $R_{\min}$ and $R_{\max}$, $I_{\min}$ and $I_{\max}$ is a volume of water and not the seabed. In other words, between the minimum and maximum range distances and the minimum and maximum depths the sonar 2 images the volume of water in which it is dipped. In the embodiment of figures 3 and 6, the elevation angles are positive, the pointed directions are always pointed upward.

The processing unit 5 is embedded on board the carrier 1. This processing unit 5 can comprise one or more computers or can be a computation function of a computer. It can as a variant be partially remotely sited away from the carrier, for example on a ship, on

land or on board an aircraft, and partially on board the carrier. It can also be entirely remotely sited.

The processing unit 5 is advantageously configured so as to calculate the minimum and the maximum $\theta_{\min}$, $\theta_{\max}$ angles during the mission, for example at regular time intervals as a function of the depth Imp of the carrier 1, of the position of the sonar 2 on the carrier, and possibly as a function of its attitude, notably of its list. The depth of the carrier Imp is advantageously supplied to the processing unit by a positioning unit 6 configured so as to determine the position and possibly the attitude of the carrier 1 at regular time intervals, for example, at the first successive insonification instants and to supply them to the processing unit 5. In other words, the positioning unit 6 is configured to supply the processing unit 5 with the space-time trajectory of the carrier 1 and possibly its attitude as a function of time. It can be an acoustic and/or inertial positioning device or any other type of positioning device. This device is advantageously embedded on board the carrier 1.

The processing unit 5 supplies these angles $\theta_{\min}$, $\theta_{\max}$ to the scanning sonar 2, possibly together with a scanning speed, an angular tilt step $\delta\theta$ and a scanning mode (two-way or one-way, for example). As a variant, the depth of the carrier 1 is assumed predefined and these data are supplied to the sonar 2 before the mission, notably the angles $\theta_{\min}$, $\theta_{\max}$ are computed before the mission.

In one embodiment, the method comprises a detection step 30, performed by the processing unit, consisting in detecting first potential echoes having been created by objects of neutral buoyancy floating mid-water by means of first signals. This step

comprises unitary detection steps 30i from respective first signals $s1_i$. A unitary detection step 30i associated with a sonar acquisition step 20i consists in determining first potential echoes $E1_{ij}$ considered as
5 having been created by potential floating objects Op_{ij} of indices I and j with $j = 1$ to M_i where M_i is the number of potential objects detected for the sonar acquisition step 20i, from the first acoustic signal $s1_i$ acquired by the sonar 2 in the sonar acquisition step
10 20i of the same index. A first potential object Op_{ij} is considered to have created a first echo when the latter satisfies a predefined selection criterion. In other words, a first potential echo is a part of the first acoustic signal satisfying a predetermined selection
15 criterion.

The unitary detection step 30i advantageously comprises an identification step 32i in which there are identified, by a method of thresholding of the contrast of the first signal, the first potential echoes $E1_{i1}$ 1 =
20 1 to L included in the first signal and exhibiting a contrast, that is to say a signal-to-noise ratio above a predetermined contrast threshold where L is the number of echoes exhibiting a contrast above the contrast threshold.

25 This contrast threshold can be fixed. It can be a function of the time separating the instant of emission of the acoustic pulse and the instant of reception on the first signal, that is to say the function of the distance separating an echo from the sonar.

30 The contrast threshold can be computed dynamically to obtain a constant false alarm rate, that is to say a constant rate of detections of potential objects which are not real objects relative to the detections of potential objects which are real objects. The detection

threshold can, for example, be fixed to obtain on average a constant detection density over the entire swath.

5 The identification step 32i is possibly preceded by a step of normalization 31i of the intensity of the first signal sl_i as a function of the duration separating the instant of emission of the acoustic pulse and the instant of reception to allow for the application of a constant contrast threshold.

10 The unitary detection step 30i advantageously comprises an elimination step 33i, in which the first potential echoes El_{i1} created by potential objects Op_{i1} deriving from the surface reverberation and/or potential objects deriving from the seabed and/or
15 potential objects situated outside the zone of interest included between the minimum and maximum ranges R_{min} , R_{max} , are eliminated. In this case, the selection criterion is a dual criterion of position and of intensity (or of contrast). First potential echoes El_{ij}
20 are then obtained.

The elimination step 33i consists, for example, in eliminating the first potential echoes El_{i1} situated at a distance from the mechanically steered sonar 2 that does not lie within a distance interval. The
25 elimination step uses the elevation angle of the pointed direction P_i in the insonification step 22i and the instant of insonification 22i and of the instant of reception of the first associated potential echo El_{i1} as well as the depth of the sonar 2. The distance interval
30 is advantageously the distance interval outside of which the potential objects detected are situated at a depth greater than the maximum depth I_{max} or at a depth less than the minimum depth I_{min} and/or at a horizontal distance from the sonar less than the minimum range R_{min}

or greater than the maximum range $R_{\max}$. The method according to the invention therefore makes it possible to very simply reject the potential objects deriving from reverberation from the surface or from the bottom
5 when the pointing direction is directed respectively toward the surface or toward the bottom.

On completion of the unitary detection step 30i, an uncertainty remains as to the position of the potential objects Op_{ij} because of the relative bearing
10 aperture of the individual sector. It is known how to compute the slant range r_{ij} (that is to say the distance) separating the potential object Op_{ij} and the sonar 2, the horizontal distance R_{ij} separating the object from the sonar (from the elevation angle θ_i of
15 the pointed direction P_i at the moment of insonification 22i, of the slant range r_{ij} and possibly the attitude of the carrier if it is not fixed), as well as its depth Im_{ij} (from the elevation angle θ_i , the pointed direction P_i at the instant t_i of insonification 22i, the depth
20 Im_{si} of the carrier at the instant of insonification and possibly from its attitude).

The depth Im_{ij} of the object is given by the following formula:

$$Im_{ij} = Im - r_{ij} \sin (\theta_{ij}) \quad [1]$$

25 The horizontal distance R_{ij} is given by the following formula:

$$R_{ij} = \sin (\theta_{ij}) * r_{ij} \quad [2]$$

On the other hand, it is not possible to accurately know the position of the potential object in
30 the horizontal plane. This object can occupy a set of potential positions corresponding to a circular arc, the center of which is the position of the sonar 2 at the instant of emission of the acoustic pulse and the radius of which is the slant range r_{ij} . That is

represented in figure 7. This figure shows the trajectory of the sonar 2, the positions Ps_i , Ps_{i+k} of the carrier 1 at the first instants of insonification of indices i and $i+k$ which are successive instants of
5 insonification according to the pointed directions exhibiting a same elevation angle and separated by a scanning period. The set of positions potentially occupied by a potential object O_{pij} , $O_{pi+kj'}$ having generated a first echo deriving from the insonification
10 step $22i$, respectively $22i+k$, and being situated at the slant range r_{ij} , respectively $r_{i+kj'}$, of the carrier is a circular arc C_{ij} , respectively $C_{i+kj'}$, of radius r_{ij} , respectively $r_{i+kj'}$, the center of which is the position Ps_i , respectively Ps_{i+k} and symmetrical relative to the
15 vertical plane in which the pointed direction Pi , $Pi+k$ is located. In the embodiment of figure 7, the angular apertures of these circular arcs α_{ij} , and respectively $\alpha_{i+kj'}$ equal to $2\theta_{3H}$. It will be seen that the angular apertures can be greater than $2\theta_{3H}$.

20 Another drawback is that the detections can exhibit a not inconsiderable number of false alarms.

Advantageously, the scanning is performed in such a way as to image more than once a one-off object fixed in the terrestrial reference frame and located at right
25 angles to the direction D , at a horizontal distance from the sonar at least equal to the minimum range R_{min} and less than the maximum range R_{max} of the sonar 2 and between the minimum I_{min} and maximum I_{max} depths, when the carrier advances at a predetermined speed V_{avg} by
30 rectilinear movement. It is stated that the system is configured so as to produce a number of target hits. Thus, a number of first echoes are acquired that originate from the object in the scanning step and these echoes are used to locate neutral buoyancy

objects effectively floating mid-water from the first potential echoes created by the potential objects. This feature makes it possible to limit the chances of not detecting a target.

5 In other words, the scanning speed, the scanning angle θ and the sector to be imaged are chosen so as to image more than once an object situated in the space defined by $R_{\min}$, $R_{\max}$, $I_{\min}$, $I_{\max}$ by means of the first individual sector SE1 at -3dB of the sonar during the
10 scanning step.

 This can be done by configuring the sonar system in such a way that an object fixed in the terrestrial reference frame and located, at right angles to the direction D, at a distance at least equal to a minimum
15 overlap, is located more than once within the individual sector SE1 during an imaging step, when the carrier advances at a speed v_{avg} .

 Figure 8 gives a different representation of the different positions $PSE1_i$, $PSE1_{i+k}$, $PSE1_{i+2k}$ occupied by
20 the first individual sector SE1 as well as the respective positions occupied by the sonar Ps_i , Ps_{i+k} , Ps_{i+2k} , in three insonification steps $22i$, $22i+k$, $22i+2k$, separated in pairs by the scanning period, in which the respective pointed directions P_i , P_{i+k} , P_{i+2k} exhibit the
25 same elevation angle. In other words, in these insonification steps, the first individual sector SE1 occupies the same position in relation to the carrier, that is to say the same orientation in the vertical plane.

30 These fixed one-off objects are imaged at least three times within the first individual sector when the scanning sonar scans the first individual sector more than once at constant scanning speed if they are situated at a horizontal distance at right angles to

the direction D at least equal to a first threshold distance R_{hole} .

$$R_{hole} = \frac{D_{avg}}{\tan\left(\frac{2\theta_{3H}}{2}\right)} \quad [3]$$

in which $2\theta_{3H}$ is the horizontal aperture of -3dB of the transmit pattern of the scanning sonar 2, and in which
5 D_{avg} is the average distance travelled by the carrier during the scanning time. The value of the average distance is given by the following equation:

10 $D_{avg} = V_{avg} * T_{scan} \quad [4]$

In which V_{avg} is the average speed of the carrier during the scanning step and in which T_{scan} is the scanning time.

15 It must be noted that the first echoes received by the mechanically steered sonar 2 are not derived solely from the objects situated within the first individual sector at the time when they are imaged, they can also be derived from objects situated in the rest of the
20 main lobe or outside of this sector. The acoustic pulse in effect exhibits a transmit pattern in $\sin \theta/\theta$ form exhibiting a maximum at the level of the pointed direction. The sonar can therefore receive echoes from objects situated within secondary lobes of the
25 transmitted acoustic signal. The objects situated close to the sonar, for example, at a distance from the sonar less than D_{hole} , will return an echo exhibiting a significant intensity or contrast, which makes it possible to detect them in the individual detection
30 step by thresholding even if they are situated outside of the individual sector at -3dB. They will therefore also be able to be detected a number of times when the sonar advances.

This means that the second threshold distance R_{hole} can be greater than the minimum range R_{min} for the method according to the invention to work or that the radius of the circular arc retained to represent the set of potential positions can be a circular arc exhibiting an aperture greater than the horizontal aperture at -3dB (relative bearing aperture SE1) but, for example, an aperture equal to the horizontal aperture at -10dB or at -20dB.

10 Advantageously, the scanning is performed so as to produce at least three target hits. That makes it possible to guarantee a certain positioning accuracy.

 The method according to the invention advantageously profits from the plurality of target hits to reduce the false alarm rate and accurately locate, in the three dimensions of space, the potential objects.

 To this end, the method advantageously comprises a step of determination of potential positions 40 comprising, for each first potential echo E_{1ij} , a step of determination 41_{ij} of a set of potential positions $PO_{p_{ij}}$ that the potential object which has created the first potential echo is likely to occupy. These potential positions are determined from the position of the sonar 2 at the instant of emission of the acoustic pulse originating from said first potential echo E_{1ij} . The position of the sonar 2 is advantageously computed by the processing unit 5 from the position of the sonar in relation to the carrier and from the position of the carrier. As a variant, the positioning unit 6 directly supplies the position of the sonar to the processing unit 5.

 These potential positions $PO_{p_{ij}}$, can be two-dimensional positions in the horizontal plane. In this

case, as explained previously with reference to figure 8, the set of potential positions that a potential object Op_{ij} can occupy is the projection, in a horizontal plane, of a circular arc C_{ij} , the center of which is the position Ps_i , which is symmetrical in relation to the vertical plane in which the pointing direction P_i is located and the radius of which is the slant range r_{ij} separating the potential object from the sonar 2. These circular arcs C_{ij} can exhibit an angular aperture equal to the relative bearing aperture of the first individual sector SE1 or equal to the relative bearing aperture of the first individual sector plus a predetermined tolerance aperture corresponding to a fraction of the aperture of the first individual sector so as to take account of objects detected outside of the first individual sector. As stated previously, the angular aperture of the circular arc can for example be equal to the horizontal aperture at -10dB or at -20dB.

The method also comprises an accumulation step 50 in which fixed positions P_f in the terrestrial reference frame are assigned respective probabilities of occupancy corresponding to probabilities of being actually occupied by an object. These probabilities are initialized, for example at 0, in a step 51 at the start of the accumulation step and incremented 52ij each time that said fixed positions are identified as being potential positions in the step of determination of the sets of potential positions 40. The fixed positions P_f assigned probabilities are cells of a grid 10 represented in figure 7.

In the case where the potential positions are two-dimensional positions in the horizontal plane, the fixed positions assigned probabilities are cells of a

two-dimensional grid, the sides of which are parallel and at right angles to the direction D.

The method comprises a step of identification 60 of effective positions which are positions effectively occupied by an object out of the fixed positions, the effective positions being obtained from fixed positions assigned a probability of occupancy above a predetermined probability threshold. This step makes it possible to select only the objects seen a sufficient number of times. On completion of this step, the non-relevant potential objects (not seen a sufficient number of times by the method) have been eliminated. It has notably been possible to eliminate fish in motion contrary to the moored mines occupying positions that are substantially fixed and other false alarms.

The effective positions correspond to the two-dimensional positions which are assigned the maximum probability in a circle of radius less than a predetermined threshold (local maximum).

In the case of figure 7, the fixed positions are all either assigned a probability equal to 1 for the fixed positions (or cells) over which a circular arc extends, or a probability equal to 0 for the fixed positions over which a circular arc does not extend, or a probability equal to 2 only for the fixed position situated at the intersection of the two circular arcs.

The increments can be fixed. As a variant, the increment is all the greater when the contrast of the first echo created by the potential object is great. That makes it possible to grant greater credit to a strong echo, that is to say an echo with a significant contrast.

The step of location of the objects comprises a step of computation 70 of the vertical co-ordinates effectively occupied in the vertical plane from

elevation angles of the pointed directions in emissions of the acoustic pulses originating the first potential echoes created by the potential objects occupying potential positions corresponding to the positions
5 assigned probabilities above the probability threshold and from the distances separating the potential objects and the mechanically steered sonar. This value can be obtained from an average or from a median of the elevation angles of the pointed directions in the
10 insonification steps originating first potential echoes considered.

In other words, the step of location of the objects comprises a step of computation 70 of the vertical co-ordinates effectively occupied in the
15 vertical plane from the depths of the potential objects occupying potential positions corresponding to the positions assigned probabilities above the probability threshold and from the distances separating the potential objects and the sonar. The depth of a
20 potential object is defined by the formula [1]. This method described previously makes it possible to locate the object with a good accuracy in the three dimensions of space. The resolution in the vertical direction is defined by the elevation aperture of the first
25 individual sector.

As a variant, the fixed positions are three-dimensional geographic positions. They are for example cells of a three-dimensional grid, the height of which corresponds to the aperture of the first individual
30 sector plus a possible predefined elevation tolerance (variable as a function of the horizontal distance separating a cell from the sonar 2). The method therefore makes it possible to obtain a vertical resolution corresponding to the elevation aperture of
35 the first individual sector.

In this case, the step of location of the objects having neutral buoyancy corresponds to the step of selection 60 of the effective positions.

Advantageously, the system according to the invention comprises, as can be seen in figure 1, at least one side-scan sonar 9 intended to image the seabed 7 in a second oriented pointing direction PA2 visible in figure 3, in a second individual sector SE2 exhibiting a wide relative bearing aperture and a narrow elevation aperture, the side-scan sonar 9 forming a plurality of reception channels in relative bearing terms and being mounted on the carrier 1 such that the second pointing direction PA2 is oriented substantially laterally to the carrier 1, preferably substantially at right angles to the main direction D, on the same side of the carrier 1 in relation to the vertical plane passing through the main direction D as the first pointing direction PA1. The sonar can be a synthetic aperture side-scan sonar.

In a seabed imaging step 100 concurrent with the scanning step 20, the side-scan sonar transmits, in steps $100t$ (with $t = 1$ to N for example), second successive acoustic pulses at second successive instants of insonification and acquires, in steps $101t$, second successive acoustic signals $si2$ resulting from the respective second acoustic pulses. Advantageously, the second successive instants of insonification are the same instants as the first successive instants of insonification. In other words, the sonars are synchronized. That makes it possible to avoid having the sonars interfere with each other. Consequently, the sonars have the same pulse repetition rate and therefore the same range. Advantageously, the emission frequency bands of the two sonars are not superposed.

The system further comprises a human-machine interface 10, arranged, for example, on a surface ship, comprising a display device 11 intended to display, in a step 110, simultaneously, as represented in figure 9, a first sonar image I1 representing first acoustic signals and a second sonar image I2 representing second acoustic signals acquired during a same period of

acquisition by the mechanically steered sonar and respectively by the side-scan sonar. In other words, the display device comprises means for generating the sonar images from the first and second acoustic
5 signals. The echoes originating from objects are visible on the images and represent significant intensities.

The human-machine interface is configured such that, when the first and second images are displayed
10 simultaneously, an operator can, when they visually identify, on the first image, a first echo created by a submerged object having neutral buoyancy, visually identify instantaneously, on the second image, if a second echo has been reflected by an object placed on
15 the seabed substantially directly below the submerged object.

In other words, the human-machine interface is configured such that an operator can visually simultaneously locate, instantaneously on the two
20 images, first and second echoes situated substantially directly above and below one another. In other words, the human-machine interface is configured such that an operator can simultaneously visually locate first echoes and second echoes from substantially a same
25 geographic co-ordinate, in a terrestrial reference frame, on the two images. This feature makes it possible to eliminate false alarms notably by allowing an operator to distinguish first echoes from free floating objects such as fish from moored mines linked
30 to an object placed on the seabed 7. In the embodiment of figure 9, the first image I1 and the second image I2 are displayed simultaneously. These respective images I1, I2 represent the intensities of the echoes included in the first and second signals. The display device is
35 configured such that the first image and the second image displayed are of substantially identical sizes and that a first echo and a second echo from objects situated at a same distance, that is to say slant

range, from the mechanically steered sonar and respectively from the side-scan sonar are represented substantially at a same abscissa and that a first echo and a second echo generated following a first and
5 respectively a second simultaneous pulse are situated at a same ordinate on the two images I1 and I2. The two images are said to be geographically synchronized. As a variant, the first images can be superposed while being distinguished by two symbologies. The first and second
10 echoes can, for example, be represented by two different colors.

Advantageously, in the embodiment of figure 9, the first image I1 and the second image I2 comprise first echoes E1a, E1b, E1c, E1e, E1f, E1g and second echoes
15 E2a, E2b that are very intense according to a same system of co-ordinates. Figure 9 does not show the echoes originating from objects situated outside the respective observation zones of the two sonars, for example, from reverberation from the surface of the
20 water. These echoes are advantageously attenuated or eliminated before the display step 110. The background noise is represented in white and a bright echo on a sonar image is here represented in black. In this figure, the display mode is an instant mode t of
25 emission of the acoustic pulse originating the echo included in the acoustic signal (on ordinate)/distance d (on abscissa) separating the object having created the echo from a predetermined point that is fixed in relation to the sonars. The fixed point is, for
30 example, the position of the sonars which are substantially in line with one another. This distance is computed by the processing unit. The instant of emission of the acoustic pulse is representative of the position of the object according to the main direction
35 D with uncertainties substantially corresponding to the relative bearing apertures of the individual sectors at -3dB of the two sonars.

In other words, the first image I1 represents the intensities of the first acoustic signals as a function of the first instants of emission of the first acoustic pulses, on ordinate, and, on abscissa, as a function of the distance separating an object having created an echo included in the signal from the mechanically steered sonar, that is to say as a function of the acquisition instant. The second image represents the intensities of the second acoustic signals as a function of the second instants of emission of the second acoustic pulses, that is to say as a function of the acquisition instant on ordinate, and, on abscissa, as a function of the distance separating an object having created an echo included in the signal from the side-scan sonar. The display device is configured such that the echoes from identical instants of emission are displayed at the same ordinate on the window or the display screen 17 and the distance scale and the origin of the range of distances displayed are the same for the two images.

On the first image I1, two triplets of first successive echoes E1a, E1b, E1c and successive echoes E1e, E1f, E1g are distinguished. This is due to the fact that the mechanically steered sonar 2 is configured to produce at least three target hits. A floating object will therefore be detected three times by the sonar in the scanning step while the carrier is moving in the direction D during three imaging steps in which the pointed directions exhibit a same elevation angle (that is to say separated in time by the scanning period). The slant range separating the echo from the sonar 2 increases between the echo E1a and the echo E1b and decreases between the echo E1b and the echo E1c. This is due to the fact that, in its movement, the carrier approaches the fixed floating object and then moves away therefrom. The same applies for the triplet of points E1d, E1f, E1g.

In the second image, a second echo E2a is from a second emission simultaneous with the first emission from which the echo E1b is derived because they are situated substantially at the same ordinate. Moreover, these echoes, being situated substantially at the same abscissa, are situated at the same distance from the two sonars 2, 9. There are therefore high probabilities that the object which has created the echoes E1a, E1b and E1c is a moored mine even though there are no second echoes visible on the second image I2 in the vicinity of the echoes E1e, E1f, E1g. These first echoes are probably from a free floating object. The same applies for the echo E2b which, not having any corresponding first echo in its vicinity, is probably from an object placed on the seabed.

The display as described previously therefore allows an operator to classify the echoes or to confirm detections of effective objects obtained by the processing unit. Advantageously, the human-machine interface 10 comprises a classification unit 12 allowing an operator to classify, in a step 120, first echoes visible on the first image (in the case of a manual detection), or first effective echoes identified by the processing unit 5, as being effectively from a submerged object having neutral buoyancy (in the case of an automatic detection) in a first class taken from a plurality of classes comprising a moored mine class and a free floating object class.

The processing unit 5 can also be configured to locate only the first echoes classified in the moored mines class by the operator. The locating is then performed simply by means of the pointed direction for the acquisition of the echo concerned and of the instant of reception of this echo.

Advantageously, the human-machine interface comprises tracking means 13 allowing an operator to simultaneously move a first cursor 51 and a second cursor 52. These cursors are displayed by the display

device. The first cursor 51 is displayed on the first image I1. The second cursor 52 is displayed on the second image I2. In other words, the cursors 51, 52 are superimposed on the respective images I1 and I2. The display device is configured such that the two cursors occupy, on the two images, respective positions corresponding to a same geographic position in a terrestrial reference frame, called pointed position. Otherwise, the co-ordinates occupied by the two cursors on the two images correspond to identical geographic positions in the terrestrial reference frame. With this cursor, it is not essential to provide images of the same size in figure 9. The tracking means comprise, for example, a mouse, a set of keys allowing an operator to direct the cursor in different directions, or even a touch zone.

Advantageously, as can be seen in figure 9, the cursor 51 displayed on the first image I1 is provided with a curve 53 computed dynamically by the processing unit or the display device. The curve 53 depends on the position pointed to by the cursor. It extends around the position pointed to by the cursor and is configured so as to represent a set of possible positions, on the first image, of echoes created by an object having created an echo represented at the position pointed to by the cursor on the image. Thus, if the cursor is placed at E1b, the associated curve will pass through the points E1c and E1a. This cursor makes it possible to visualize the expected position of successive echoes of an immobile object in the volume of water and thus assists the operator in identifying the possible echoes from contacts of interest. This curve is computed approximately as follows:

When the cursor points to a position having the co-ordinates t_i and r_i where t_i corresponds to an instant of insonification t_i originating an echo and r_i represents an slant range between an object originating the echo and the volume scanning sonar, the position

r_{i+k} of the curve on the distance axis situated on the time axis at the instant t_{i+k} is thus computed:

$$r_{i+k} = \sqrt{r_i^2 + (D_{avg} \times k)^2}$$

5 $r_{i-k} = r_{i+k}$. The curve 53 is preferably centered around the position i along the time axis t .

Advantageously, as represented in figure 9, the display device is configured to display superimposed on the first image and/or the second image, symbols SE at
10 effective positions considered as being effectively occupied by the echoes detected by the processing unit 5. That allows an operator to concentrate on the zones where first effective echoes have already been detected so as to speed up and improve the relevance of the
15 classification. In figure 9, a symbol SE corresponding to the effective position identified by the processing unit from the three first echoes $E1a$, $E1b$, $E1c$ is displayed only on the first image. The symbol SE is a square in the nonlimiting example of figure 9.

20 Advantageously, as represented in figure 3, the side-scan sonar is configured so as to image the seabed 7 in a zone of observation delimited by a minimum observation range RI_{min} and a maximum observation range RI_{max} defined by the respective directions DI_{min} and DI_{max}
25 delimiting the second individual sector SE2 corresponding to the horizontal distances at right angles to the direction D close to the height of water between the bottom and the side-scan sonar and respectively beyond which the echo becomes too weak.

30 Advantageously, the minimum and maximum observation ranges DI_{min} and DI_{max} are substantially equal to the minimum and maximum ranges R_{min} and R_{max} of the mechanically steered sonar 2. This configuration makes it possible to carry out the search for moored
35 mines and mines placed on the seabed simultaneously over a same sweep and in a same zone which makes it possible to optimize the trajectory of the carrier and

therefore the time taken to inspect a wider zone to be inspected.

5 The mechanical scanning and side-scan sonars operate at frequencies ranging from several tens to several hundreds of kHz to exhibit an angular resolution compatible with the size of the mines. Advantageously, the first and second acoustic pulses exhibit a bandwidth of at least equal to 50 kHz. This feature makes it possible to limit the echoes deriving from the reverberation from the surface of the water and increase the contrast of the objects to be detected.

10 In the embodiment of the figures, the system according to the invention comprises two side-scan sonars and two mechanically steered sonars arranged on the two flanks of the carrier, that is to say on either side of the direction D, and configured so as to image the seabed and the marine environment laterally to the carrier on both sides of a vertical plane passing through the direction D symmetrically in relation to this plane as represented in figure 3 which shows the other first and second individual sectors SE1', SE2' transmitted by the other scanning 2' and lateral 9' sonars symmetrical to the scanning sonar 2 and respectively to the side-scan sonar 9 in relation to the vertical plane passing through D. A different number of side-scan sonars and mechanically steered sonars can be envisaged.

30

CLAIMS

1. A system for detecting and locating submerged
underwater objects having neutral buoyancy comprising
5 at least one mechanically steered sonar (2) intended to
image a water column, the system comprising at least
one mechanically steered sonar (2) with a single
emission channel, making it possible to perform the
insonification of a first individual sector (SE1) in a
10 first pointing direction (PA1) by means of a single
first acoustic pulse, said sonar (2) forming a single
reception channel suitable for acquiring a first
acoustic signal resulting from said insonification, the
mechanically steered sonar (2) being mounted on a
15 carrier (1) intended to advance in a main direction
(D), such that the first pointing direction (PA1) is
substantially lateral to the carrier (1) and that the
first individual sector (SE1) exhibits a wide relative
bearing aperture and a narrower elevation aperture, the
20 mechanically steered sonar (2) comprising a mechanical
pointing device (3) intended to tilt the first pointing
direction (PA1) about an axis of rotation (x)
substantially parallel to the main direction (D)
allowing the sonar to acquire first acoustic signals
25 resulting from insonifications performed in different
pointing directions.

2. The system as claimed in the preceding claim,
comprising a processing unit (5) configured to locate
30 underwater objects having neutral buoyancy from at
least one first acoustic signal.

3. The system as claimed in either one of the
preceding claims, comprising a plurality of

mechanically steered sonars spaced apart in the main direction and the oriented pointing directions of which are directed toward the same side of a vertical plane passing through the main direction (D).

5

4. The system as claimed in any one of the preceding claims, comprising at least one side-scan sonar (9) intended to image the seabed (7) in a second pointing direction (PA2) in a second individual sector (SE2) exhibiting a wide relative bearing aperture and a narrow elevation aperture, the side-scan sonar (9) forming a plurality of relative bearing reception channels and being mounted on the carrier (1) such that the second pointing direction (PA2) is oriented substantially laterally to the carrier (1) on the same side of the carrier (1) in relation to the vertical plane passing through the main direction (D) as the first pointing direction (PA1), the system further comprising a human-machine interface (10) comprising a display device (11) intended to simultaneously display a first sonar image (I1) representing first acoustic signals and a second sonar image (I2) representing second acoustic signals acquired during a same period of acquisition by the mechanically steered sonar (2) and respectively by the side-scan sonar (9), the human-machine interface being configured such that, when the first and second images are displayed simultaneously, an operator can, when they visually identify, on the first image, a first echo created by a submerged object having neutral buoyancy, visually identify instantaneously on the second image, if a second echo has been reflected by an object placed on the seabed substantially directly below the submerged object.

10

15

20

25

30

5. The system as claimed in the pcrereceding claim, in which the display device (11) is configured such that the first image and the second image displayed have substantially identical sizes and such that an
5 echo included in the first image and an echo included in the second image created by respective objects situated at a same distance from the mechanically steered sonar and respectively from the side-scan sonar and generated following a first and a second
10 simultaneous insonification step are represented substantially at a same abscissa and at a same ordinate on the first image and on the second image.

6. The system as claimed in either one of claims 4
15 and 5, in which the human-machine interface (10) comprises tracking means allowing an operator to simultaneously move two cursors displayed by the display device, one on the first image and the other on the second image, the display device being configured
20 such that the two cursors occupy, on the first and the second image, positions corresponding to a same geographic position in a terrestrial reference frame.

7. The system as claimed in the preceding claim, in
25 which the cursor displayed on the first image is provided with a curve (53) representing a set of the possible positions on the first image of echoes originating from an object having created an echo represented at the position pointed to by the cursor.

30

8. The system as claimed in any one of claims 4 to 7, in which the first image and the second image represent the first and second acoustic signals in instant mode of emission of the acoustic pulse originating the

signals/distance separating, in the horizontal plane, the objects originating the echoes, and being included in said signals, from a fixed point in relation to said sonars.

5

9. The system as claimed in any one of claims 4 to 8, comprising a processing unit (5) suitable for identifying, in first signals, first effective echoes effectively created by effectively submerged effective objects having neutral buoyancy, the display device (11) being configured so as to display, superimposed with the first image and/or the second image, symbols (SE) at the effective positions considered as being effectively occupied by the effective objects.

15

10. The system as claimed in any one of claims 4 to 9, in which said human-machine interface (10) comprises a classification unit (12) configured so as to allow an operator to classify first echoes visible on the first image or first effective echoes identified, by a processing unit (5), in first signals, as being created by effectively submerged effective objects having neutral buoyancy visible in a first class taken from a plurality of classes comprising a moored mine class and a free floating object class.

25

11. A method for detecting and locating underwater objects having neutral buoyancy, using a system as claimed in any one of the preceding claims, the method comprising a scanning step (20) in which the mechanically steered sonar (2) scans, a plurality of times, a sector to be imaged (SI) open in a plane substantially at right angles to the main direction (D), in which the mechanically steered sonar (2)

30

performs successive sonar acquisition steps (20i) in which the pointing device (3) points (21i) the first pointing direction in successive pointed directions included in the sector to be imaged (SI), and, for each
5 direction pointed, transmits a first acoustic pulse (22i) at a first insonification instant and acquires (23i) a first acoustic signal resulting from the first acoustic pulse.

10 12. The method as claimed in the preceding claim, comprising a detection step (30) for detecting first potential echoes created by submerged objects having neutral buoyancy by means of first signals, comprising unitary detection steps (30i), each unitary detection
15 step (30i) comprising an identification step (32i) for identifying first potential echoes, considered as having been created by respective potential neutral-buoyancy objects in response to a first acoustic pulse, the first potential echoes being parts of first signals
20 satisfying a predetermined selection criterion.

13. The method as claimed in the preceding claim, in which the identification step (32i) comprises a step of thresholding of the contrasts of first signals.

25

14. The method as claimed in either one of claims 12 and 13, in which the mechanically steered sonar (2) is configured, given the speed of the carrier, so as to acquire, in the scanning step (20), more than once,
30 echoes from a one-off object fixed in the terrestrial reference frame, said fixed one-off object being located at a depth lying between a predetermined minimum depth and a predetermined maximum depth, and being located at right angles to the main direction D

in a horizontal plane at a distance from the mechanically steered sonar (2) greater than a predetermined minimum range and less than a predetermined maximum range, the method comprising a
5 step of locating effective submerged objects having neutral buoyancy from the first acoustic signals acquired in the scanning step and from the first potential echoes.

10 15. The method as claimed in the preceding claim, comprising a step of locating submerged objects having neutral buoyancy, comprising:

- 15 - a step of determination (40) of potential positions of the potential floating objects comprising, for each first potential echo, a step of determination of a set of potential positions (41ij), that the corresponding potential object is likely to occupy, from the position of the sonar at the first instant of
20 emission of the first acoustic pulse originating the first potential echo,
- an accumulation step (50) in which positions that are fixed in the terrestrial reference frame are assigned respective probabilities of
25 occupancy corresponding to probabilities of being actually occupied by an object, said respective probabilities of occupancy being initialized (51) at the start of the accumulation step (50) and incremented (52ij)
30 each time the respective fixed positions are determined as being potential positions in the step of determination of potential positions,
- a step of identification (60) of effective positions effectively occupied by effective

submerged objects having neutral buoyancy from fixed positions assigned a probability of occupancy above a predetermined threshold.

5 16. The method as claimed in the preceding claim, in which the set of potential positions of a potential object is a circular arc of radius equal to the distance separating the potential object from the mechanically steered sonar (2) computed
10 from the difference between the first instant of emission and the instant of reception of the first potential echo created by the potential object, the center of which is the position of the sonar at the first instant of emission and the aperture of which is equal to the aperture of the first
15 individual sector, the first individual sector corresponding to the sector in which is transmitted the portion of the main lobe of the first acoustic pulse attenuated to the maximum of 3dB, or equal to the aperture of the first
20 individual sector plus a predetermined tolerance aperture.

17. The method as claimed in any one of claims 11 to
25 16, implemented by means of a system as claimed in any one of claims 4 to 10, comprising a step of imaging of the seabed (100) concurrent with the scanning step, the step of imaging of the seabed (100) consisting in imaging the seabed by means of
30 the side-scan sonar (9) by transmitting second successive acoustic pulses at second successive insonification instants, and by conducting the acquisition of the second successive acoustic signals deriving from the second successive

pulses, the method further comprising a step (110) of simultaneous display of a first image representing first acoustic signals and of a second image representing second acoustic signals acquired during a same period of acquisition by the mechanically steered sonar (2) and respectively by the side-scan sonar (9).

18. The method as claimed in the preceding claim, comprising a step of classification by an operator by means of a classification unit of at least one first echo visible on the first image in a class taken from a plurality of classes comprising a moored mine class and a free floating object class.

19. A system for detecting and locating submerged underwater objects having neutral buoyancy as claimed in any one of claims 1 to 10 suitable for implementing the method as claimed in any one of claims 11 to 18, comprising a processing unit (5) configured so as to implement the step of identification of the first potential echoes.

20. The system as claimed in the preceding claim, dependent on claims 14 to 18, comprising a positioning unit (6) configured so as to determine the position of the carrier as a function of time, in which the processing unit (5) is configured so as to implement the location step, the positioning unit or the processing unit being configured so as to determine the position of the mechanically steered sonar (2).