



(51) International Patent Classification:
C08G 59/50 (2006.01) **C08L 63/00** (2006.01)

(21) International Application Number:
PCT/EP2010/062504

(22) International Filing Date:
26 August 2010 (26.08.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09170006.2 11 September 2009 (11.09.2009) EP

(71) Applicant (for all designated States except US): **ELAN-TAS GMBH** [DE/DE]; Abelstr. 43, 46483 Wesel (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LIENERT, Klaus** [DE/DE]; Bernadottestr. 54, 22763 Hamburg (DE). **BUSI, Marco** [IT/IT]; Via Attilio Mori, 34/B, I-46100 Mantova (IT). **COLOMBI, Nataly** [IT/IT]; Via Vittorio Emanuele II, No. 11, I-43038 Sala Breganza (Parma) (IT). **PEDERZANI, Alberto** [IT/IT]; Via Ancona, 1, I-43100 Parma (IT). **GHERARDI, Paola** [IT/IT]; Stradello Goya, 10, I-43100 Parma (IT).

(74) Agent: **FITZNER, Uwe**; Hauser Ring 10, 40878 Ratingen (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: EPOXY RESIN CURING INDICATOR COMPOSITION

(57) Abstract: Compositions comprising at least one epoxy resin and/or reactive diluents, at least one hardener for the at least one epoxy resin, at least one curing indicator, wherein the colour of the composition changes depending on the curing degree, a process for determining sufficient cure of a composition comprising providing a composition comprising at least one epoxy resin and a hardener for the epoxy resin, adding a curing indicator, applying curing conditions to the coloured composition until the composition changes its colour and use of polymeric colourants as curing degree indicator, wherein the curing indicator is a polymeric colourant consisting of chromophores which are chemically bound to polymers having reactive groups.

