

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶:

A62C 35/00 // 35/58

A1

(11) International Publication Number:

WO 99/38573

(43) International Publication Date:

5 August 1999 (05.08.99)

(21) International Application Number: PCT/FI99/00068

(22) International Filing Date: 1 February 1999 (01.02.99)

(30) Priority Data:

980232	2 February 1998 (02.02.98)	FI
980705	27 March 1998 (27.03.98)	FI
980772	3 April 1998 (03.04.98)	FI

(71)(72) Applicant and Inventor: SUNDHOLM, Göran [FI/FI];
Ilmari Kiannon kuja 3, FIN-04310 Tuusula (FI).(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box
148, FIN-00121 Helsinki (FI).

(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: DRIVE SOURCE FOR FEEDING EXTINGUISHING MEDIUM INTO SPRAY HEAD FOR EXTINGUISHING FIRE

(57) Abstract

The invention relates to a drive force for feeding extinguishing medium into at least one spray head (2, 3) for extinguishing fire, the drive source comprising a liquid source (5) including liquid and a gas source (9) including gas, mixing means for mixing the liquid of the liquid source (5) and the gas of the gas source (9), and transportation means (1) for leading the liquid and the gas to the spray head in such a manner that an extinguishing medium including a liquid component and a gas component is led to the spray head. In order for the drive source to enable a controlled dosage of gas to be obtained in the liquid and preferably a substantially even and small droplet size for a substantially long time during the extinguishing process, the drive source is characterized in that the mixing means comprise a cylinder piston apparatus (50) including a first piston (12) arranged in a first cylinder (10) and a second piston (13) arranged in a second cylinder (11), the cylinder piston apparatus being arranged at each stroke to simultaneously provide both liquid and gas to the transportation means (1).

