

Description

This invention relates to an optical fibre back plane for telephone exchange equipment such as transmission, switching and/or distribution equipment.

Exchange equipment of this type has a plurality of vertically-spaced shelves, each of which contains a plurality of vertically-positioned cards carrying electronic components. A back plane is positioned behind the cards of each shelf, the back planes being provided with connectors for interfacing the cards with other cards and with external cabling. Typically, external cabling is housed within vertical channels positioned at the sides of the shelves.

Conventionally, external cabling is co-axial, and this is generally satisfactory for exchange transmission equipment, that is to any transmission equipment for multiplexing bit streams for transmission over trunk and junction networks. Nowadays, however, it is envisaged that such transmission equipment will incorporate switching equipment, and this leads to problems in making interconnections with the back planes. Basically, these problems arise from the size of the connectors which are required for co-axial cable. Moreover, the problem is exacerbated by the requirements for such equipment to cope with increased bit transmission rates.

One known way of alleviating these problems is to use optical fibre cables instead of co-axial cables. Apart from their increased bandwidth, the advantage of using optical fibres is that they are physically much smaller than co-axial cable, and so are easier to connect to the back planes of exchange equipment. Unfortunately, in conventional optical technology, incoming optical fibres are exposed, and so must be ruggedised. This leads to an increase in effective fibre size, and also to an approximately tenfold cost increase. DE-3116869A describes exchange equipment for handling optical fibre cables according to the precharacterising portion of claim 1.

The aim of the invention is to provide an optical fibre back plane for feeding optical fibres to exchange equipment without requiring such optical fibres to be ruggedised.

The present invention provides an optical fibre back plane for connecting incoming optical fibres to exchange equipment, the optical fibre back plane comprising a support member, attachment means for attaching the support member to the exchange equipment and allowing pivotal movement of the support member about an axis, and optical interface means for connecting the incoming optical fibres to on-board optical fibres, characterised in that the optical fibre back plane is provided with fibre support means for supporting the incoming optical fibres, the fibre support means extending parallel, and closely adjacent, to said axis, so as to support said incoming optical fi-

bres parallel, and closely adjacent, to said axis (9).

Advantageously, the back plane is provided with second optical interface means for connecting on-board optical fibres to optical fibres leading to the exchange equipment.

In a preferred embodiment, a first fibre storage area is formed on the support member, the first fibre storage area being provided for storing spare incoming optical fibres, and a second fibre storage area is formed on the support member, the second fibre storage area being provided for storing spare on-board optical fibres. The fibre storage areas may be positioned on opposite sides of the support member. Conveniently, the or each fibre storage area is provided with at least one generally cylindrical boss whose radius of curvature is at least equal to the minimum bend radius for the optical fibres stored in that area.

Preferably, the fibre support means is constituted by a tube extending part way along the support member adjacent to one edge thereof, said one edge being adjacent to a hinge which constitutes the attachment means. The incoming optical fibres exiting the tube may be guided towards the first fibre storage area by a curved channel whose radius of curvature is at least equal to the minimum bend radius for the incoming optical fibres. Advantageously, the first fibre storage area is positioned on the opposite side of the support member to the tube, the incoming optical fibres passing from the curved channel to the first fibre storage area via a slot formed in the support member.

The first-mentioned optical interface means may be positioned within the first fibre storage area. Conveniently, the on-board optical fibres pass from the first fibre storage area to the second fibre storage area via said slot and via a second curved channel formed adjacent to the second fibre storage area, the radius of curvature of the second curved channel being at least equal to the minimum bend radius for the on-board optical fibres.

Advantageously, the support member is provided with optical components such as couplers, switches, WDM devices or filters. These optical components may be positioned within a fibre storage area.

Each of the on-board optical fibres may be guided towards a respective optical connector by a respective guide means, the optical connectors constituting the second optical interface means. Preferably, each of said guide means is constituted by first and second curved guide surfaces, the first guide surfaces being constituted by individual guide surfaces, and the second guide surfaces being constituted by a common guide surface, each of said guide surfaces having a radius of curvature which is at least equal to the minimum bend radius for the on-board optical fibres. Advantageously, the first guide surfaces are formed in a guide block made of machined aluminium or ABS.

In a preferred embodiment, the support member

is made of a vacuum-formed plastics material such as polystyrene, the support member is fixed to a chassis made of steel, and the optical connectors are fixed to the chassis.

Exchange equipment incorporating optical fibre back planes constructed in accordance with the invention will now be described, by way of example, with reference to the accompanying drawings, in which: -

Fig. 1 is a schematic perspective view of the exchange equipment, and shows one optical fibre back plane;

Fig. 2 is a perspective view of the optical fibre back plane of Fig. 1;

Fig. 3 is perspective view of the optical fibre back plane of Fig. 1 looking in the direction of the arrow III of Fig. 2; and

Fig. 4 is a perspective view of the support plate of the optical fibre back plane.

Referring to the drawings, Fig. 1 is a schematic representation of exchange equipment having both transmission and switching capabilities. The exchange equipment has five shelves 1 (only one of which is shown) which are slidable into, and out of, the framework of the exchange equipment on guides (not shown). Each shelf 1 has an electronic back plane 2 and a plurality of cards 3 (only one of which is shown). Each of the cards 3 carries a plurality of electronic components for carrying out transmission and/or switching functions. The electronic back plane 2 of each shelf 1 co-operates, in a manner described below, with a respective optical fibre back plane 4 (only one of which is shown in Fig. 1).

As the optical fibre back planes 4 are identical, only one of them will be described in detail. Thus, referring to Fig. 2, the optical fibre back plane 4 is constituted by a main support member 5 made of a vacuum-formed plastics material such as polystyrene, a steel chassis (support plate) 6, and a fibre guide member 7 made of machined aluminium or ABS. The main support member 5 is fixed to the chassis 6 by means of double-sided adhesive tape or any other suitable adhesive. The chassis 6 is pivotally attached to the framework of the exchange equipment by means of a hinge 8, the pivotal axis 9 (see Fig. 1) of which is generally horizontal and positioned at the lower long edge of the optical fibre back plane 4. This pivotal mounting of the optical fibre back plane 4, permits the back plane to be pivoted down from its normal operating position (shown in Fig. 1) through 90° to facilitate access to the components associated with the back plane.

Optical fibres are fed to the optical fibre back planes 4 via a vertical cable run 10 provided at one side of the exchange equipment. Each back plane 4 is associated with a plurality of incoming optical fibres 11 (only one of which is shown in Fig. 2). These fibres 11 are guided from the cable run 10 to the back plane

4 by a tube 12 which is fixed to the back of the main support member 5. The tube 12 extends about half way along the lower edge of the back plane 4, and is parallel to (and closely spaced from) the axis 9. Thus, when the back plane 4 is pivoted between its normal operating position (vertical) and its "access" position (horizontal), the optical fibres 11 do not undergo any stress. After the fibres 11 leave the tube 12, they are guided through a curved channel 13 and a slot 14 to the front side of the back plane 4. The curved channel 13 has a radius of curvature of 35 mm, that is to say the minimum bend radius of optical fibres.

The front side of the back plane 4 (see Fig. 3) includes a fibre storage area 15 and a pair of generally cylindrical bosses 16. The bosses 16 each have a radius of curvature of 35 mm. The area 15 is used for spare fibre storage of incoming optical fibres (that is to say the optical fibres 11). The area 15 also constitutes an optical interface for interconnecting incoming fibres 11 with on-board optical fibres (not shown).

The optical interface may be constituted by any known means for interconnecting optical fibres (for example single fibre or mass fusion splices, single or multiple fibre connectors, or single or multiple fibre mechanical splices). The bosses 16, being of minimum bend radius, are used to guide the optical fibres to and from the optical interface, as well as to guide the incoming fibres 11 from the slot 14, and to guide outgoing on-board fibres back through the slot. These outgoing fibres pass through the slot 14 and round a curved channel 17 (see Fig. 2) formed in the back of the support member 5. This channel 17 also has a radius of curvature of 35 mm.

The outgoing fibres then pass into a fibre storage area 18, which is used for spare fibre storage of on-board optical fibres. The fibre storage area 18 includes a pair of generally cylindrical bosses 19 which are used to guide the on-board optical fibres around this storage area. Once again, the bosses have a radius of curvature of 35 mm. The fibre storage area 18 may also house optical components and devices (not shown), such as couplers, switches, WDM devices or filters.

The on-board optical fibres exit the storage area 18 via a curved channel 20 having a radius curvature of 35 mm. The curved channel 20 leads to the fibre guide member 7 which is formed with eleven fibre guides 21, each of which has a curved guide surface 21a. The curved guide surfaces 21a each have a radius of curvature of 35 mm. Each guide surface 21a leads to a respective connector (not shown) fixed to a top edge portion 6a of the chassis 6. The optical fibres exiting the guide surfaces 21a are guided to the associated connectors by a curved guide member 22 whose radius of curvature is 35 mm. Each of the connectors projects from the portion 6a of the chassis 6 for connection to a complementary connector (not shown) associated with a respective card 3 of the cor-

responding shelf 1. Cut-outs 2a are formed in the associated electrical back plane 2 to permit the complementary connectors to make contact.

It will be apparent that this type of optical fibre back plane 4 will normally reside behind its electronic component shelf 1 in a sterile environment, that is to say the fibre and components it houses are inaccessible when the back plane is in its normal (vertical) operating position. This permits the use of secondary or primary coated fibres throughout the equipment housing. In particular, there is no need for the incoming optical fibres to be ruggedised, so there is a substantial cost saving over prior art optically-cabled exchange equipment.

Another advantage of the optical fibre back plane 4 is that its three-dimensional moulding allows minimum bend radius of fibre (35 mm approximately) to be maintained from the fibre entry region to the exit connectors, via the storage areas 15 and 18 and all intermediate regions. Moreover, by pivotally mounting the optical fibre back plane 4 on its hinge 8, access for maintenance and installation purposes is facilitated. Furthermore, because the incoming fibres enter the back plane 4 substantially along the hinge axis 9, this pivoting can occur without the fibres being terminated on the back plane undergoing any stress as a result of the pivoting movement of the back plane.

The optical fibre back plane 4 can be manufactured on the bench, or in the factory, to any given specification. No field installation work is required, except for connection to the incoming optical fibres via the optical interface. Installation of optical fibre inputs to exchange equipment is, therefore, simplified. Moreover, the optical fibre back plane can be a standard item which can be used in many different types of exchange equipment; the back plane being adaptable to different situations by the incorporation of different optical components and devices, and by using different numbers of exit connectors.

It will be apparent that the optical fibre back plane described above would be modified in a number of ways. For example, the entire back plane (including the fibre guide member 7 and the chassis 6) could be moulded in one piece from a suitable plastics material. Also, the optical interface between the incoming fibres and the on-board fibres could be positioned in any convenient site on either side of the back plane. Similarly, the optical interface between the on-board fibres and the cards need not be in the form of complementary optical connectors, but would take the form of pigtails, in which case ruggedised optical fibres would be used. In a further modification, the optical components (such as couplers, switches, WDM devices or filters) could be stored in a dedicated storage area instead of in the storage area 18. In this case, the back plane moulding would be appropriately modified to form this dedicated storage area.

In a particularly advantageous modified embodiment,

the optical fibre back plane could be enhanced by the inclusion of a free space optical waveguide mounted in such a manner as to allow clock and/or data distribution between the cards 3. In this case optical signals could be transmitted from the waveguide to a receiver on an associated card 3 via a perspex rod fixed to the card. One end of the perspex rod would be aligned with the receiver, the other end passing through a cut-out in the optical fibre back plane and being in alignment with the waveguide. In practice, the waveguide runs at right-angles to the receiver, so that the perspex rod must deflect the light it carries through 90°. This can be done by cutting the waveguide and surface of the rod at 45° and polishing this cut surface to form a transparent surface. The rod then acts as a 'periscope' to reflect incoming light through 90°.

Claims

1. An optical fibre back plane (4) for connecting incoming optical fibres (11) to exchange equipment, the optical fibre back plane (4) comprising a support member (5), attachment means (8) for attaching the support member (5) to the exchange equipment and allowing pivotal movement of the support member (5) about an axis (9), and optical interface means for connecting the incoming optical fibres (11) to on-board optical fibres, characterised in that the optical fibre back plane (4) is provided with fibre support means (12) for supporting the incoming optical fibres, the support means extending parallel, and closely adjacent, to said axis (9), so as to support said incoming optical fibres parallel, and closely adjacent, to said axis (9).
2. A back plane as claimed in claim 1, wherein the back plane (4) is provided with second optical interface means for connecting on-board optical fibres to optical fibres leading to the exchange equipment.
3. A back plane as claimed in claim 1 or claim 2, wherein a first fibre storage area (15) is formed on the support member (5), the first fibre storage area (15) being provided for storing spare incoming optical fibres (11).
4. A back plane as claimed in any one of claims 1 to 3, wherein a second fibre storage area (18) is formed on the support member (5), the second fibre storage area (11) being provide for storing spare on-board optical fibres.
5. A back plane as claimed in claim 4 when appendant to claim 3, wherein the first and second fibre

responding shelf 1. Cut-outs 2a are formed in the associated electrical back plane 2 to permit the complementary connectors to make contact.

It will be apparent that this type of optical fibre back plane 4 will normally reside behind its electronic component shelf 1 in a sterile environment, that is to say the fibre and components it houses are inaccessible when the back plane is in its normal (vertical) operating position. This permits the use of secondary or primary coated fibres throughout the equipment housing. In particular, there is no need for the incoming optical fibres to be ruggedised, so there is a substantial cost saving over prior art optically-cabled exchange equipment.

Another advantage of the optical fibre back plane 4 is that its three-dimensional moulding allows minimum bend radius of fibre (35 mm approximately) to be maintained from the fibre entry region to the exit connectors, via the storage areas 15 and 18 and all intermediate regions. Moreover, by pivotally mounting the optical fibre back plane 4 on its hinge 8, access for maintenance and installation purposes is facilitated. Furthermore, because the incoming fibres enter the back plane 4 substantially along the hinge axis 9, this pivoting can occur without the fibres being terminated on the back plane undergoing any stress as a result of the pivoting movement of the back plane.

The optical fibre back plane 4 can be manufactured on the bench, or in the factory, to any given specification. No field installation work is required, except for connection to the incoming optical fibres via the optical interface. Installation of optical fibre inputs to exchange equipment is, therefore, simplified. Moreover, the optical fibre back plane can be a standard item which can be used in many different types of exchange equipment; the back plane being adaptable to different situations by the incorporation of different optical components and devices, and by using different numbers of exit connectors.

It will be apparent that the optical fibre back plane described above would be modified in a number of ways. For example, the entire back plane (including the fibre guide member 7 and the chassis 6) could be moulded in one piece from a suitable plastics material. Also, the optical interface between the incoming fibres and the on-board fibres could be positioned in any convenient site on either side of the back plane. Similarly, the optical interface between the on-board fibres and the cards need not be in the form of complementary optical connectors, but would take the form of pigtails, in which case ruggedised optical fibres would be used. In a further modification, the optical components (such as couplers, switches, WDM devices or filters) could be stored in a dedicated storage area instead of in the storage area 18. In this case, the back plane moulding would be appropriately modified to form this dedicated storage area.

In a particularly advantageous modified embodiment,

the optical fibre back plane could be enhanced by the inclusion of a free space optical waveguide mounted in such a manner as to allow clock and/or data distribution between the cards 3. In this case optical signals could be transmitted from the waveguide to a receiver on an associated card 3 via a perspex rod fixed to the card. One end of the perspex rod would be aligned with the receiver, the other end passing through a cut-out in the optical fibre back plane and being in alignment with the waveguide. In practice, the waveguide runs at right-angles to the receiver, so that the perspex rod must deflect the light it carries through 90°. This can be done by cutting the waveguide and surface of the rod at 45° and polishing this cut surface to form a transparent surface. The rod then acts as a 'periscope' to reflect incoming light through 90°.

Claims

1. An optical fibre back plane (4) for connecting incoming optical fibres (11) to exchange equipment, the optical fibre back plane (4) comprising a support member (5), attachment means (8) for attaching the support member (5) to the exchange equipment and allowing pivotal movement of the support member (5) about an axis (9), and optical interface means for connecting the incoming optical fibres (11) to on-board optical fibres, characterised in that the optical fibre back plane (4) is provided with fibre support means (12) for supporting the incoming optical fibres, the support means extending parallel, and closely adjacent, to said axis (9), so as to support said incoming optical fibres parallel, and closely adjacent, to said axis (9).
2. A back plane as claimed in claim 1, wherein the back plane (4) is provided with second optical interface means for connecting on-board optical fibres to optical fibres leading to the exchange equipment.
3. A back plane as claimed in claim 1 or claim 2, wherein a first fibre storage area (15) is formed on the support member (5), the first fibre storage area (15) being provided for storing spare incoming optical fibres (11).
4. A back plane as claimed in any one of claims 1 to 3, wherein a second fibre storage area (18) is formed on the support member (5), the second fibre storage area (11) being provide for storing spare on-board optical fibres.
5. A back plane as claimed in claim 4 when appendant to claim 3, wherein the first and second fibre



storage areas (15, 18) are positioned on opposite sides of the support member (5).

6. A back plane as claimed in any one of claims 3 to 5, wherein the or each fibre storage area (15 or 18) is provided with at least one generally cylindrical boss (16 or 19) whose radius of curvature is at least equal to the minimum bend radius for the optical fibres stored in that area. 5
7. A back plane as claimed in any of claims 1 to 6, wherein the fibre support means (12) is constituted by a tube extending part way along the support member (5) adjacent to one edge thereof, said one edge being adjacent to a hinge which constitutes the attachment means. 10 15
8. A back plane as claimed in claim 7, wherein the incoming optical fibres (11) exiting the tube (12) are guided towards the first fibre storage area (15) by a curved channel (13) whose radius of curvature is at least equal to the minimum bend radius for the incoming optical fibres (11). 20
9. A back plane as claimed in claim 8, wherein the first fibre storage area (15) is positioned on the opposite side of the support member (5) to the tube (12), the incoming optical fibres (11) passing from the curved channel (13) to the first fibre storage area (15) via a slot (14) formed in the support member (5). 25 30
10. A back plane as claimed in any one of claims 3 to 9, wherein the first-mentioned optical interface means is positioned within the first fibre storage area (15). 35
11. A back plane as claimed in claim 9, or in claim 10 when appendant to claim 9, wherein the on-board optical fibres pass from the first fibre storage area (15) to the second fibre storage area (18) via said slot (14) and via a second curved channel (17) formed adjacent to the second fibre storage area (18), the radius of curvature of the second curved channel (17) being at least equal to the minimum bend radius for the on-board optical fibres. 40 45
12. A back plane as claimed in any one of claims 1 to 11, wherein the support member (5) is provided with optical components such as couplers, switches, WDM devices or filters. 50
13. A back plane as claimed in claim 12 when appendant to claim 3 or claim 4, wherein the optical components are positioned within a fibre storage area (15 or 18). 55

14. A back plane as claimed in claim 2, or in any one of claims 3 to 13 when appendant to claim 2, wherein each of the on-board optical fibres is guided towards a respective optical connector by a respective guide means (21, 22), the optical connectors constituting the second optical interface means.

15. A back plane as claimed in claim 14, wherein each of said guide means (21, 22) is constituted by first and second curved guide surfaces (21, 22), the first guide surfaces (21a) being constituted by individual guide surfaces, and the second guide surfaces being constituted by a common guide surface (22), each of said guide surfaces (21a, 22) having a radius of curvature which is at least equal to the minimum bend radius for the on-board optical fibres.

16. A back plane as claimed in claim 15, wherein the first guide surfaces (21a) are formed in a guide block made of machined aluminium or ABS.

17. A back plane as claimed in any one of claims 1 to 16, wherein the support member (5) is made of a vacuum-formed plastics material such as polystyrene.

18. A back plane as claimed in any one of claims 1 to 17, wherein the support member (5) is fixed to a chassis made of steel.

Patentansprüche

1. Verdrahtungsplatte (back plane) (4) für optische Fasern, zum Verbinden von ankommenden optischen Fasern (11) mit einer Vermittlungseinrichtung, welche umfaßt: ein Trägerorgan (5), ein Befestigungsmittel (8) zum Befestigen des Trägerorgans (5) an der Vermittlungseinrichtung, das eine Schwenkbewegung des Trägerorgans (5) um eine Achse (9) ermöglicht, und ein optisches Schnittstellenmittel zum Verbinden der ankommenden optischen Fasern (11) mit optischen Fasern auf der Platine, dadurch gekennzeichnet, daß die Verdrahtungsplatte (4) mit einem Faserträgermittel (12) zum Tragen der ankommenden optischen Fasern versehen ist, das parallel und eng benachbart zu der Achse (9) verläuft, um die ankommenden optischen Fasern parallel und eng benachbart zur Achse (9) zu tragen.
2. Verdrahtungsplatte nach Anspruch 1 mit einem zweiten optischen Schnittstellenmittel zum Verbinden von optischen Fasern auf der Platte mit optischen Fasern, die zur Vermittlungseinrichtung



tung führen.

3. Verdrahtungsplatte nach Anspruch 1 oder 2,
bei der ein erster Faserspeicherbereich (15) am
Trägerorgan (5) gebildet ist und vorgesehen ist, 5
um eine Reserve von ankommenden Fasern (11)
zu speichern.
4. Verdrahtungsplatte nach einem der Ansprüche 1
bis 3, 10
bei der ein zweiter Faserspeicherbereich (18) am
Trägerorgan (5) gebildet ist und vorgesehen ist,
um eine Reserve von optischen Fasern der Plat-
te zu speichern. 15
5. Verdrahtungsplatte nach Anspruch 4 in Verbin-
dung mit Anspruch 3,
bei der der erste und der zweite Faserspeicher-
bereich (15, 18) auf entgegengesetzten Seiten
des Trägerorgans (5) angeordnet sind. 20
6. Verdrahtungsplatte nach einem der Ansprüche 3
bis 5,
bei der der oder jeder Faserspeicherbereich (15
oder 18) mit wenigstens einem im wesentlichen
zylindrischen Vorsprung (16 oder 19) versehen
ist, dessen Krümmungsradius wenigstens gleich
dem Minimalkrümmungsradius der in diesem Be-
reich gespeicherten optischen Fasern ist. 25
7. Verdrahtungsplatte nach einem der Ansprüche 1
bis 6, 30
bei der das Faserträgermittel (12) durch ein Rohr
gebildet ist, das sich über einen Teil des Träger-
organs (5) zu einer Kante desselben benachbart
erstreckt, wobei diese eine Kante einem Schar-
nier benachbart ist, welches das Befestigungs-
mittel bildet. 35
8. Verdrahtungsplatte nach Anspruch 7, 40
bei der die das Rohr (12) verlassenden ankom-
menden optischen Fasern (11) zum ersten Fa-
serspeicherbereich (15) durch einen gekrümm-
ten Kanal (13) zugeführt werden, dessen Krüm-
mungsradius wenigstens gleich dem Minimal-
krümmungsradius der ankommenden optischen
Fasern (11) ist. 45
9. Verdrahtungsplatte nach Anspruch 8, 50
bei der der erste Faserspeicherbereich (15) auf
der dem Rohr (12) entgegengesetzten Seite des
Trägerorgans (5) angeordnet ist und die ankom-
menden optischen Fasern (11) vom gekrümmten
Kanal (13) zum ersten Speicherbereich (15)
durch einen im Trägerorgan (5) gebildeten
Schlitz (14) übergehen. 55
10. Verdrahtungsplatte nach einem der Ansprüche 3

bis 9,

bei der das erstgenannte optische Schnittstellen-
mittel im ersten Faserspeicherbereich (15) ange-
ordnet ist.

11. Verdrahtungsplatte nach Anspruch 9 oder An-
spruch 10 in Verbindung mit Anspruch 9,
bei der die optischen Fasern der Platte vom er-
sten Faserspeicherbereich (15) zum zweiten Fa-
serspeicherbereich (18) durch den Schlitz (14)
und einen zweiten gekrümmten Kanal (17) über-
gehen, der dem zweiten Faserspeicherbereich
(18) benachbart gebildet ist und dessen Krüm-
mungsradius wenigstens gleich dem Minimal-
krümmungsradius der optischen Fasern der Plat-
te ist.
12. Verdrahtungsplatte nach einem der Ansprüche 1
bis 11, 20
bei der das Trägerorgan (5) mit optischen Kom-
ponenten wie Kopplern, Schaltern, Wellenlän-
genmultiplexern oder Filtern versehen ist.
13. Verdrahtungsplatte nach Anspruch 12 in Verbin-
dung mit Anspruch 3 oder 4,
bei der die optischen Komponenten in einem Fa-
serspeicherbereich (15 oder 18) angebracht sind.
14. Verdrahtungsplatte nach Anspruch 2 oder einem
der Ansprüche 3 bis 13 in Verbindung mit An-
spruch 2, 30
bei der jede der optischen Fasern der Platte
durch ein entsprechendes Führungsmittel (21,
22) zu einem entsprechenden optischen Verbin-
der geführt wird, wobei die optischen Verbind-
er die zweiten optischen Schnittstellenmittel bilden.
15. Verdrahtungsplatte nach Anspruch 14, 40
bei der jedes der Führungsmittel (21, 22) durch
erste und zweite gekrümmte Führungsoberflä-
chen (21, 22) gebildet ist, wobei die ersten Füh-
rungsoberflächen (21a) durch individuelle Füh-
rungsoberflächen gebildet sind und die zweiten
Führungsoberflächen durch eine gemeinsame
Führungsoberfläche (22) gebildet sind, wobei je-
de der Führungsoberflächen (21a, 22) einen
Krümmungsradius hat, der wenigstens gleich
dem Minimalkrümmungsradius der optischen Fa-
sern der Platte ist.
16. Verdrahtungsplatte nach Anspruch 15, 45
bei der die ersten Führungsoberflächen (21a) in
einem aus gefrästem Aluminium oder ABS herge-
stellten Führungsblock gebildet sind.
17. Verdrahtungsplatte nach einem der Ansprüche 1
bis 16, 50
bei der das Trägerorgan (5) aus einem vakuum-



geformten Kunststoffmaterial wie etwa Polystyrol hergestellt ist.

18. Verdrahtungsplatte nach einem der Ansprüche 1 bis 17,
bei dem das Trägerorgan (5) an einem aus Stahl hergestellten Chassis befestigt ist.

Revendications

1. Panneau arrière pour fibres optiques (4) permettant de raccorder des fibres optiques entrantes (11) à un équipement de central, le panneau arrière pour fibres optiques (4) comprenant un élément de support (5), des moyens de fixation (8) pour fixer l'élément de support (5) à l'équipement de central et permettre le déplacement pivotant de l'élément de support (5) autour d'un axe (9), et des moyens d'interface optique pour raccorder les fibres optiques entrantes (11) à des fibres optiques sur carte, caractérisé en ce que le panneau arrière pour fibres optiques (4) est muni de moyens de support de fibres (12) destinés à supporter les fibres optiques entrantes, les moyens de support s'étendant parallèlement audit axe et à proximité immédiate dudit axe (9), de manière à supporter lesdites fibres optiques entrantes parallèles et à proximité immédiate dudit axe (9). 15
2. Panneau arrière selon la revendication 1, dans lequel le panneau arrière (4) est muni de seconds moyens d'interface optique pour raccorder des fibres optiques sur carte à des fibres optiques menant à l'équipement de central. 20
3. Panneau arrière selon la revendication 1 ou la revendication 2, dans lequel une première zone de rangement de fibres (15) est formée sur l'élément de support (5), la première zone de rangement de fibres (15) étant prévue pour ranger des fibres optiques entrantes de rechange (11). 25
4. Panneau arrière selon l'une quelconque des revendications 1 à 3, dans lequel une seconde zone de rangement de fibres (18) est formée sur l'élément de support (5), la seconde zone de rangement de fibres (18) étant prévue pour ranger des fibres optiques sur carte de rechange. 30
5. Panneau arrière selon la revendication 4 lorsqu'elle dépend de la revendication 3, dans lequel les première et seconde zones de rangement de fibres (15, 18) sont positionnées sur des côtés opposés de l'élément de support (5). 35
6. Panneau arrière selon l'une quelconque des re- 40

vendications 3 à 5, dans lequel la ou chaque zone de rangement de fibres (15 ou 18) est munie d'au moins un bossage généralement cylindrique (16 ou 19) dont le rayon de courbure est au moins égal au rayon de cintrage minimum admissible pour les fibres optiques rangées dans cette zone.

7. Panneau arrière selon l'une quelconque des revendications 1 à 6, dans lequel le moyen de support de fibres (12) est constitué d'un tube s'étendant sur une partie de la longueur de l'élément de support (5) à proximité d'un bord de celui-ci, ledit un bord étant à proximité d'une charnière qui constitue le moyen de fixation. 45
8. Panneau arrière selon la revendication 7, dans lequel les fibres optiques entrantes (11) sortant du tube (12) sont guidées vers la première zone de rangement de fibres (15) par un canal incurvé (13) dont le rayon de courbure est au moins égal au rayon de cintrage minimum admissible pour les fibres optiques entrantes (11). 50
9. Panneau arrière selon la revendication 8, dans lequel la première zone de rangement de fibres (15) est positionnée sur le côté opposé de l'élément de support (5) par rapport au tube (12), les fibres optiques entrantes (11) passant du canal incurvé (13) à la première zone de rangement de fibres (15) via une fente (14) formée dans l'élément de support (5). 55
10. Panneau arrière selon l'une quelconque des revendications 3 à 9, dans lequel le moyen d'interface optique cité en premier est positionné à l'intérieur de la première zone de rangement de fibres (15). 60
11. Panneau arrière selon la revendication 9, ou selon la revendication 10 lorsqu'elle dépend de la revendication 9, dans lequel les fibres optiques sur carte passent de la première zone de rangement de fibres (15) à la seconde zone de rangement de fibres (18) via ladite fente (14) et via un second canal incurvé (17) formé à proximité de la seconde zone de rangement de fibres (18), le rayon de courbure du second canal incurvé (17) étant au moins égal au rayon de cintrage minimum admissible pour les fibres optiques sur carte. 65
12. Panneau arrière selon l'une quelconque des revendications 1 à 11, dans lequel l'élément de support (5) est muni de composants optiques tels que des coupleurs, des commutateurs, des dispositifs de multiplexage par différence de longueur d'ondes ou des filtres. 70



13. Panneau arrière selon la revendication 12 lorsqu'elle dépend de la revendication 3 ou de la revendication 4, dans lequel les composants optiques sont positionnés à l'intérieur d'une zone de rangement de fibres (15 ou 18). 5
14. Panneau arrière selon la revendication 2, ou l'une quelconque des revendications 3 à 13 lorsqu'elles dépendent de la revendication 2, dans lequel chacune des fibres optiques sur carte est guidée vers un connecteur optique respectif par un moyen de guidage respectif (21, 22), les connecteurs optiques constituant le second moyen d'interface optique. 10
15. Panneau arrière selon la revendication 14, dans lequel chacun desdits moyens de guidage (21, 22) est constitué de premières et secondes surfaces de guidage incurvées (21, 22), les premières surfaces de guidage (21a) étant constituées de surfaces de guidage individuelles, et les secondes surfaces de guidage étant constituées d'une surface de guidage commune (22), chacune desdites surfaces de guidage (21a, 22) présentant un rayon de courbure qui est au moins égal au rayon de cintrage minimum admissible pour les fibres optiques sur carte. 15
16. Panneau arrière selon la revendication 15, dans lequel les premières surfaces de guidage (21a) sont formées dans un bloc de guidage fait d'aluminium usiné ou d'ABS. 20
17. Panneau arrière selon l'une quelconque des revendications 1 à 16, dans lequel l'élément de support (5) est fait d'un matériau plastique formé sous vide tel que du polystyrène. 25
18. Panneau arrière selon l'une quelconque des revendications 1 à 17, dans lequel l'élément de support (5) est fixé à un châssis fait d'acier. 30
- 35
- 40
- 45
- 50
- 55

