

Sealed and thermally insulating wall for a tank for storing fluid

Technical field

The invention relates to the field of sealed and thermally insulating tanks for storing and/or transporting fluid, such as cryogenic fluid.

5 The invention relates more particularly to the field of tanks, the sealing thereof being implemented by metal membranes having corrugations which provide said metal membranes with a flexibility and a capacity for elongation in one or more directions of a plane.

10 Such tanks are used, in particular, for the transport or storage of liquefied natural gas (LNG) which is stored at atmospheric pressure at approximately -162°C.

Prior art

15 Sealed and thermally insulating tanks for transporting and/or storing cryogenic fluid are known from the patent application FR 2 861 060, said tanks comprising heat-insulating panels covered by a corrugated sealing membrane. The sealing membrane comprises an inner face which is designed to be in contact with the fluid contained in the tank and an outer face which is anchored to the inner face
20 of the heat-insulating panel. The sealing membrane consists of a plurality of metal plates which are made of stainless steel and have series of perpendicular corrugations which enable the forces to be absorbed. The corrugated plates are welded to one another along the edges thereof and are anchored to the panels by welding the edges of the plates to strips which are also made of stainless steel and
25 riveted to said heat-insulating panels.

 The inner face of the heat-insulating panels has slots extending in the transverse direction relative to the length of the vessel, over the entire length of the heat-insulating panels. Such slots permit a deformation of the corrugations, without
30 the heat-insulating panels becoming cracked when the tank is subjected to cold temperatures.

Summary

One idea on which the invention is based is to propose a sealed and thermally insulating wall having a corrugated membrane which is resistant to low
 5 temperatures and has limited flexion when subjected to cold temperatures.

According to one embodiment, the invention provides a sealed and thermally insulating wall for a tank for storing fluid, comprising:

- a heat-insulating panel having an inner face; and
- 10 • a sealing plate having an inner face which is designed to be in contact with the fluid contained in the tank and an outer face which is anchored to the inner face of the panel in the region of a plurality of anchoring areas, said sealing plate comprising at least one corrugation which protrudes from the side of the inner face of the sealing plate, extending in a direction d_1 ; in which:
- 15 • the inner face of the heat-insulating panel comprises a stress-relieving slot between two adjacent anchoring areas arranged on either side of said corrugation, said stress-relieving slot having an axis extending in the direction d_1 so as to permit a deformation of the corrugation transversely to the direction d_1 ; and
- the stress-relieving slot has a length which is less than the dimension of
 20 the heat-insulating panel along the axis of the stress-relieving slot.

Thus, the corrugation provides the sealing membrane with a flexibility which enables it to deform, in particular under the action of the flexion of the heat-insulating panels and the thermal contraction of the sealing membrane.

25

Moreover, the stress-relieving slot makes it possible to exploit fully this corrugation since it permits a deformation of the sealing membrane without imposing mechanical stresses which are too great on the heat-insulating panel.

30 Moreover, when a tank is filled with a cryogenic fluid, such as liquefied natural gas, the difference in temperature between the outside of the tank and the inside generates a thermal gradient within the heat-insulating panels. This thermal gradient may cause the flexion of the heat-insulating panels and thus the flexion of the sealing membrane. In contrast to a slot extending on either side of a heat-

insulating panel, a stress-relieving slot which does not extend over the entire width or length of the panel makes it possible for the panel to preserve a certain degree of rigidity and thus limits the impact of a stress-relieving slot on the flexibility of the heat-insulating panel under thermal load.

5

According to the embodiments, such a sealed and thermally insulating wall may comprise one or more of the following features:

- the stress-relieving slot does not extend as far as the periphery of the heat-insulating panel.
- 10 • the stress-relieving slot is a through-slot which opens into the outer face of the heat-insulating panel.
- the stress-relieving slot is a blind slot which does not open into the outer face of the panel and comprises ends which are radiused.
- the stress-relieving slot extends opposite the corrugation.
- 15 • the sealing plate comprises a corrugation extending in a direction d_2 perpendicular to the direction d_1 , the inner face of the heat-insulating panel comprising a stress-relieving slot between two adjacent anchoring areas extending on either side of said corrugation extending in the direction d_2 , said stress-relieving slot having an axis extending in the direction d_2 and having a length which is less
- 20 than the dimension of the heat-insulating panel along the axis of said stress-relieving slot.
- the sealing plate comprises a first series of corrugations extending in the direction d_1 and a second series of corrugations extending in the direction d_2 , the outer face of the sealing plate being anchored to the inner face of the heat-insulating
- 25 panel in the region of a plurality of anchoring areas arranged between the corrugations of the first and the second series, the inner face of the heat-insulating panel comprising a stress-relieving slot between each pair of adjacent anchoring areas extending on either side of a corrugation, said stress-relieving slot having an axis which extends in the direction d_1 or d_2 of said corrugation and having a length
- 30 which is less than the dimension of the heat-insulating panel along the axis of said stress-relieving slot.
- a stress-relieving slot has a length corresponding to the distance between two intersections of corrugations in the direction d_1 or d_2 of the stress-relieving slot.

- the anchoring areas are aligned along two secant edges of the metal plate.

- a stress-relieving slot adjacent to the intersection between the alignments of the anchoring areas has an additional portion extending in a central direction d3
5 relative to the directions d1 or d2.

- the sealing plate is a metal plate and the inner face of the heat-insulating panel comprises, in the region of the anchoring areas, metal anchoring plates permitting the welding of the sealing plate to the heat-insulating panel.

- the heat-insulating panel comprises a layer of insulating polymer foam
10 sandwiched between two sheets of plywood.

- the heat-insulating panel constitutes a primary insulating barrier of the wall, the wall further comprising a secondary sealed and insulating barrier, the heat-insulating panel being fastened to the secondary sealed and insulating barrier by a fastening member cooperating with a central area of the panel, remote from the
15 edges of the panel.

- the heat-insulating panel comprises, in a central area, members for fixing to a load-bearing structure.

According to one embodiment, the invention also provides a fluid storage
20 tank comprising a load-bearing structure and at least one wall as mentioned above which is fixed to the load-bearing structure.

Such a tank may form part of a land-based storage installation, for example to store LNG, or may be installed in a floating structure which is inshore or offshore,
25 in particular an LNG carrier, a floating storage and regasification unit (FSRU), a floating production, storage and offloading unit (FPSO) and the like.

According to one embodiment, a vessel for the transport of a fluid comprises a double hull forming the load-bearing structure and a tank as mentioned
30 above and arranged in the double hull.

According to one embodiment, the invention also provides a use of a vessel as mentioned above and in which a fluid is conducted through insulated pipelines

from or toward a floating or land-based storage installation toward or from the tank of the vessel in order to load or unload the vessel.

According to one embodiment, the invention also provides a system for the transfer of a fluid, the system comprising the aforementioned vessel, insulated pipelines being arranged so as to connect the tank installed in the hull of the vessel to a floating or land-based storage installation and a pump to drive a flow of fluid through the insulated pipelines from or toward the floating or land-based storage installation toward or from the tank of the vessel.

10

According to one embodiment, the invention is particularly advantageous when the means for fastening the heat-insulating panels to the load-bearing structure are not capable of absorbing the flexural stresses of the heat-insulating element, for example when the heat-insulating panel is not fixed in its peripheral area but solely in the region of a central area of its external surface.

15

According to one embodiment, the invention also makes it possible to obtain improved behavior relative to the ageing of the insulating foam of the heat-insulating panels. More specifically, the stress-relieving slots do not extend over the entire length or width of the heat-insulating panels, the exchange surface between the insulating foam and the ambient air being restricted such that the diffusion of the expansion gas outside the cells of the foam and the migration of air therein are limited.

20

The invention will be understood, and further objects, details, features and advantages thereof, will appear more clearly from the following description of several particular embodiments of the invention provided solely by way of illustrative and non-limiting example with reference to the accompanying drawings, in which:

25

- figure 1 is a perspective view of a heat-insulating panel.
- figures 2, 3, and 4 are detailed views according to three variants of a heat-insulating panel in the area receiving the corners of the metal plates.
- figure 5 is a view of a sealed and thermally insulating wall in cross section, passing through a stress-relieving slot.

30

- figure 6 is a view similar to that of figure 5 with a stress-relieving slot according to a further embodiment.

- figure 7 is a perspective view of a corrugated metal plate of the sealing membrane.

5 • figure 8 is a plan view illustrating the relative positioning of a metal plate of the sealing membrane relative to a heat-insulating panel.

- figure 9 is a perspective view of a heat-insulating panel fixed to the load-bearing structure in its central area.

10 • figure 10 is a detailed perspective view of the members for fixing to the load-bearing structure of the heat-insulating panel of figure 9.

- figure 11 is a longitudinal sectional view of the heat-insulating panel of figures 9 and 10 in the region of members for fixing to the load-bearing structure.

- figure 12 is a schematic cut-away view of an LNG carrier tank and a terminal for the supply/discharge of said tank.

15

Conventionally, the terms "external" and "internal" are used to define the relative position of one element relative to another, with reference to the inside and outside of the tank.

20

Each tank wall in the thickness direction, successively from the inside to the outside of the tank, has at least one sealing membrane in contact with the fluid contained in the tank, a thermally insulating barrier and a load-bearing structure, not shown. In one particular embodiment, not illustrated, a wall may also comprise two levels of sealing and thermal insulation.

25

Figure 1 shows a heat-insulating panel 1. The panel 1 in this case has substantially the shape of a rectangular parallelepiped. It comprises a layer of insulating polymer foam 2 sandwiched between an internal rigid plate 3 and an external rigid plate 4. The internal rigid plate 3 and the external rigid plate 4 are, for example, sheets of plywood bonded to said foam layer 2. The insulating polymer foam may, in particular, be a polyurethane-based foam. The polymer foam may advantageously be reinforced by glass fibers which contribute to reducing its thermal contraction.

30

By way of example, the panel 1 has a length of 3 meters by a width of 1 meter. The internal sheet of plywood 3 may have a thickness of 12 mm; the external sheet of plywood 4: a thickness of 9 mm and the layer of insulating foam 2: a thickness of 200 mm. Naturally, the dimensions and thicknesses are provided by way of indication and vary according to the desired applications and thermal insulating performance.

The internal surface of the panel 1 comprises metal anchoring plates 5, 6 designed to anchor the metal plates 7, one example thereof being illustrated in figure 7, forming the sealing membrane. Metal anchoring plates 5 extend longitudinally on the internal plate 3 of the panel 1 and metal anchoring plates 6 extend transversely. The metal anchoring plates 5, 6 are riveted, for example, to the internal plate 3 of the panel 1. The metal anchoring plates 5, 6 may be produced, in particular, from stainless steel or Invar®: an alloy of iron and nickel, the principal property thereof being that it has a very low coefficient of expansion. The thickness of the metal anchoring plates 5, 6 is, for example, in the order of 2 mm. A thermal protection strip, not illustrated, may be placed below the metal anchoring plates 5, 6. The anchoring between the metal plate 7 and the metal anchoring plates 5, 6 is implemented by tack welds.

20

The sealing membrane is obtained by assembling multiple metal plates 7 welded to one another along their edges. As illustrated in figure 7, a metal plate 7 comprises a first series of parallel corrugations, called lower corrugations 8, extending in a direction y and a second series of parallel corrugations, called upper corrugations 9 extending in a direction x. The directions x and y of the series of corrugations 8, 9 are perpendicular. The corrugations 8, 9 protrude from the side of the inner face of the metal plate 7. The edges of the metal plate 7 are in this case parallel to the corrugations 8, 9. The metal plate 7 comprises between the corrugations 8, 9 a plurality of planar surfaces 11. It is worth noting that the terms "upper" and "lower" have a relative meaning and indicate that the first series of corrugations 8 has a height which is lower than the second series of corrugations 9. In the region of an intersection 10 between a lower corrugation 8 and an upper corrugation 9, the lower corrugation is discontinuous, i.e. it is interrupted by a fold which extends the top edge of the upper corrugation 9 protruding above the top

25
30

edge of the lower corrugation 8. The corrugations 8, 9 permit the sealing membrane to be substantially flexible in order to be able to deform under the effect of stresses, in particular thermal stresses, generated by the fluid stored in the tank.

5 The metal plate 7 is produced from stainless steel or aluminum sheet, shaped by folding or stamping. Further metals or alloys are also possible. By way of example, the metal plate 7 has a thickness of approximately 1.2 mm. Further thicknesses are also conceivable, given that a thickening of the metal plate 7 results in an increase in its cost and generally increases the rigidity of the corrugations.

10

In the region of one of the two transverse edges 13 and in the region of one of the two longitudinal edges 12, the metal plate 7 has a stamped strip, not shown, which is inwardly offset in the thickness direction relative to the plane of the plate 7 in order to cover the edge of an adjacent metal plate 7.

15

A relative positioning of a metal plate 7 in relation to a heat-insulating panel 1 is illustrated in figure 8. The metal plates 7 in this case are arranged offset by half a length and half a width relative to the heat-insulating panel 1. A wall comprises, therefore, a plurality of heat-insulating panels 1 and a plurality of metal plates 7 and
20 each of said metal plates 7 extends over four adjacent heat-insulating panels 1.

One of the longitudinal edges 12 of the metal plate 7 is anchored to the heat-insulating panel 1 by welding said longitudinal edge 12 to the metal anchoring plates 5. Similarly, one of the transverse edges 13 is anchored to the heat-insulating
25 panel 1 by welding said transverse edge 13 to the metal anchoring plates 6. The anchoring areas 14 between the metal plate 7 and the heat-insulating panel 1 are located on either side of the corrugations 8, 9. In other words, the anchoring areas 14 are formed at the interface between the planar portions 11 of the edges 12, 13 of the metal plates 7 extending on either side of the corrugations 8, 9 and the metal
30 anchoring plates 5, 6.

It is noteworthy that the central corrugation of each of the series of corrugations 8, 9 advantageously extends opposite the join between two adjacent heat-insulating panels 1.

The internal surface of the heat-insulating panel 1 is provided with a plurality of stress-relieving slots 15, 16. A first series of stress-relieving slots 15 extends in the direction y of the corrugations 8. A second series of stress-relieving slots 16 extends in the direction x of the corrugations 9.

In figure 8, the heat-insulating panel 1 has a stress-relieving slot 15, 16 between each pair of adjacent anchoring areas 14 extending on either side of a corrugation 8, 9. The stress-relieving slots 15, 16 extend in this case opposite their respective corrugation 8, 9. The stress-relieving slots 15, 16 are thus arranged to permit a deformation of their respective corrugation 8, 9 according to a direction transversely to the direction thereof. More specifically, without the stress-relieving slot 15, 16, any corrugation 8, 9 bordered by anchoring areas 14 is not able to be deformed without imposing significant mechanical stresses on the heat-insulating panel 1.

The stress-relieving slots 15, 16 have lengths which are shorter than the dimension of the heat-insulating panel 1 along their axis. In other words, the stress-relieving slots 15, 16 do not extend as far as the periphery of the heat-insulating panel 1. Advantageously, the length of a stress-relieving slot 15, 16 substantially corresponds to the spacing between two intersections 10 of corrugations in the direction of the slot 15, 16.

In one embodiment shown in figure 5, the stress-relieving slot 15 is a through-slot extending over the entire thickness of the heat-insulating panel and, as a result, opening into the outer face of the panel 1. Such a stress-relieving slot 15 makes it possible to confer a high degree of flexibility to the sealing membrane relative to the deformations of the heat-insulating panel 1 whilst preserving a continuity of the internal rigid plate 3 in certain areas thereof. This continuity permits the flexibility of the heat-insulating panel 1 to be limited under thermal load. It also permits the bonding of the rigid plates 3, 4 to the layer of foam 2 to be facilitated and, as a result, incipient fractures to be limited.

In a further embodiment shown in figure 6, the stress-relieving slot 15 is a blind slot which does not open into the outer face of the panel. Such a stress-relieving slot 15 substantially extends as far as half of the thickness of the heat-insulating panel 1. In order to limit the concentrations of stresses in the region of the bottom of the ends 17, 18 of the slot 15, the ends 17, 18 of the stress-relieving slot 15 are radiused. In order to produce these radiused portions, the stress-relieving slot 15 is typically produced by a circular saw.

Figures 2 to 4 illustrate in a detailed manner the intersection area between the axis of alignment of the metal anchoring plates 5 extending longitudinally to the panel 1 and the axis of alignment of the metal anchoring plates 6 extending transversely. This intersection area corresponds to the area for fixing a corner of the metal plate 7.

In the embodiments of figures 2 and 4, the stress-relieving slots 15, 16 which are arranged on either side of the intersection between the alignments of the metal anchoring plates 5, 6 are extended by an additional portion 17, 18 extending in a central direction relative to the directions x and y. In other words, the directions x and y are perpendicular here, the additional portions 17, 18 forming an angle of 45° relative to the directions x and y.

In the embodiment of figure 3, the decision has been made to reduce the length of the transverse stress-relieving slots 15 such that they do not intersect the longitudinal stress-relieving slots 16.

The manufacture of the heat-insulating panels 1 may be carried out according to various embodiments. According to one embodiment, the internal plate 3 and external plate 4 are, for example, bonded on either side of the layer of insulating polymer foam 2 and then the stress-relieving slots 15, 16 are cut out. Finally, when the stress-relieving slots 15, 16 have been cut out, the metal anchoring plates 5, 6 are fixed, for example, by riveting to the internal rigid plate 3.

Alternatively, it is also possible to cut out previously the internal rigid plate 3, the layer of insulating polymer foam 2 and optionally the external rigid plate 4 and

then to bond the internal rigid plate 3 and external rigid plate 4 to the layer of insulating polymer foam 2 by adjusting the slots formed in the internal plate 3 and in the layer of insulating polymer foam 2.

- 5 The slots 15, 16 may be cut out by means of a device of the slotting machine type or any other appropriate device such as by means of a water jet, laser cutting, jigsaw, fret saw, milling, circular saw, or the like.

10 Figures 9 to 11 illustrate a heat-insulating panel 1 comprising, in its central area, members for fixing to the load-bearing structure. The heat-insulating panel 1 comprises, in its central area, an orifice 19 receiving a pin 20 fixed to the load-bearing structure or to a secondary sealed and thermally insulating barrier, which is in turn fixed to the load-bearing structure when the tank has two levels of sealing and thermal insulation. The pin 20 comprises a threaded part cooperating with a nut
15 21. The orifice 19 comprises a shoulder 22. One or more planar washers and/or Belleville washers 23 are inserted between the nut 21 and the shoulder 22. The housing 22 in this case is sealed by a sealing disc 24.

20 A sealed and thermally insulating tank may comprise one or more walls as disclosed above. Such a tank may form part of a land-based storage installation, for example to store LNG, or may be installed in a floating structure, onshore or offshore, in particular an LNG carrier, a floating storage and regasification unit (FSRU), a floating production, storage and offloading unit (FPSO) and the like.

25 With reference to figure 12, a cut-away view of an LNG carrier 70 shows a sealed and insulated tank 71 of generally prismatic shape mounted in the double hull 72 of the vessel. The wall of the tank 71 comprises a primary sealed barrier designed to be in contact with the LNG contained in the tank, a secondary sealed barrier arranged between the primary sealed barrier and the double hull 72 of the
30 vessel and two insulating barriers respectively arranged between the primary sealed barrier and the secondary sealed barrier and between the secondary sealed barrier and the double hull 72.

In the manner known per se, supply/discharge pipelines 73 arranged on the upper bridge of the vessel may be connected by means of appropriate connectors to a marine or harbor terminal to transfer an LNG cargo from or toward the tank 71.

5 Figure 12 shows an example of a marine terminal comprising a supply and discharge station 75, an underwater pipe 76 and a land-based installation 77. The supply and discharge station 75 is a fixed offshore installation comprising a mobile arm 74 and a tower 78 which supports the mobile arm 74. The mobile arm 74 carries a bundle of insulated flexible pipes 79 which are able to be connected to the
10 supply/discharge pipelines 73. The mobile arm 74, which is able to be oriented, is adapted to all types of LNG carriers. A connecting pipe, not shown, extends inside the tower 78. The supply and discharge station 75 permits the supply and discharge of the LNG carrier 70 from or toward the land-based installation 77. Said land-based installation comprises tanks for storing liquefied gas 80 and connecting pipes 81
15 connected by the underwater pipe 76 to the supply or discharge station 75. The underwater pipe 76 permits the transfer of liquefied gas between the supply or discharge station 75 and the land-based installation 77 over a long distance, for example 5 km, which permits the LNG carrier 70 to be kept at a long distance from the coast during supply and discharge operations.

20

To create the pressure necessary for the transfer of the liquefied gas, pumps mounted on board the vessel 70 and/or pumps provided on the land-based installation 77 and/or pumps provided at the supply and discharge station 75 are used.

25

Although the invention has been described in connection with several particular embodiments, it is obvious that it is not limited thereby in any respect and it comprises all the technical equivalents of the means disclosed, in addition to combinations thereof if they fall within the scope of the invention.

30

The use of the verbs "to consist of" "to comprise" or "to include" and their conjugated forms does not exclude the presence of other elements or other steps from those cited in a claim. The use of the indefinite article "a" or "an" for an element

or a step does not exclude, unless indicated to the contrary, the presence of a plurality of such elements or steps.

In the claims, any reference between parentheses should not be interpreted
5 as a limitation to the claim.

CLAIMS

1. A sealed and thermally insulating wall for a tank for storing fluid, comprising:
 - 5 • a heat-insulating panel (1) having an inner face and a periphery; and
 - a sealing plate (7) having an inner face designed to be in contact with the fluid contained in the tank and an outer face anchored to the inner face of the panel (1) in the region of a plurality of anchoring areas (14), said sealing plate (7) comprising at least one corrugation (8; 9) which protrudes from the side of the
 - 10 inner face of the sealing plate (7), extending in a direction $d_1(x; y)$; in which:
 - the inner face of the heat-insulating panel (1) comprises a stress-relieving slot (15; 16) between two adjacent anchoring areas (14) arranged on either side of said corrugation (8; 9), said stress-relieving slot having an axis extending in the direction $d_1(x, y)$ so as to permit a deformation of the corrugation transversely to
 - 15 the direction $d_1(x, y)$; and
 - the stress-relieving slot (15; 16) has a length which is less than the dimension of the heat-insulating panel (1) along the axis of the stress-relieving slot (15; 16) and does not extend as far as the periphery of the heat-insulating panel (1).
 2. The wall as claimed in claim 1, in which the stress-relieving slot
 - 20 (15; 16) is a through-slot which opens into the outer face of the heat-insulating panel (1).
 3. The wall as claimed in claim 1 or 2, in which the stress-relieving slot (15; 16) is a blind slot which does not open into the outer face of the panel and comprises ends (17, 18) which are radiused.
 - 25 4. The wall as claimed in any one of claims 1 to 3, in which the stress-relieving slot (15; 16) extends opposite the corrugation (8; 9).
 5. The wall as claimed in any one of claims 1 to 4, in which the sealing plate (7) comprises a corrugation (9; 8) extending in a direction $d_2(y; x)$ perpendicular to the direction $d_1(x; y)$, the inner face of the heat-insulating panel (1)
 - 30 comprising a stress-relieving slot (16; 15) between two adjacent anchoring areas (14) extending on either side of said corrugation (9; 8) extending in the direction $d_2(y; x)$, said stress-relieving slot having an axis extending in the direction $d_2(y; x)$ and having a length which is less than the dimension of the heat-insulating panel along the axis of said stress-relieving slot (16; 15).

6. The wall as claimed in claim 5 in which the sealing plate (7) comprises a first series of corrugations (15; 16) extending in the direction d_1 (x; y) and a second series of corrugations (16; 15) extending in the direction d_2 (y; x), the outer face of the sealing plate (7) being anchored to the inner face of the heat-insulating panel (1) in the region of a plurality of anchoring areas (14) arranged between the corrugations (15, 16) of the first and second series, the inner face of the heat-insulating panel (1) comprising a stress-relieving slot (8, 9) between each pair of adjacent anchoring areas (14) extending on either side of a corrugation (15, 16), said stress-relieving slot having an axis which extends in the direction d_1 (x; y) or d_2 (y; x) of said corrugation and having a length which is less than the dimension of the heat-insulating panel (1) along the axis of said stress-relieving slot (8, 9).

7. The wall as claimed in claim 6, in which a stress-relieving slot (15, 16) has a length corresponding to the distance between two intersections (10) of corrugations (8, 9) in the direction d_1 (x; y) or d_2 (y; x) of the stress-relieving slot (15, 16).

8. The wall as claimed in any one of claims 5 to 7, in which the anchoring areas (14) are aligned along two secant edges (12, 13) of the metal plate (7).

9. The wall as claimed in claim 8, in which a stress-relieving slot (15, 16) adjacent to the intersection between the alignments of anchoring areas (14) has an additional portion (17, 18) extending in a central direction d_3 relative to the directions d_1 (x; y) or d_2 (y; x).

10. The wall as claimed in any one of claims 1 to 9, in which the sealing plate (7) is a metal plate and in which the inner face of the heat-insulating panel (1) comprises, in the region of the anchoring areas (14), metal anchoring plates permitting the welding of the sealing plate (7) to the heat-insulating panel (1).

11. The wall as claimed in any one of claims 1 to 10 in which the heat-insulating panel (1) comprises a layer of insulating polymer foam (2) sandwiched between two sheets of plywood (3, 4).

12. The wall as claimed in any one of claims 1 to 11, in which the heat-insulating panel (1) constitutes a primary insulating barrier of the wall, the wall further comprising a secondary sealed and insulating barrier, and the heat-insulating panel (1) being fastened to the secondary sealed and insulating barrier by a

fastening member cooperating with a central area of the panel (1), remote from the edges of the panel (1).

13. The wall as claimed in any one of claims 1 to 12, in which the heat-insulating panel (1) comprises, in a central area, members for fixing to a load-bearing structure.

14. A tank for the storage of fluid comprising a load-bearing structure and at least one wall as claimed in one of claims 1 to 13 fixed to the load-bearing structure.

15. A vessel (70) for the transport of a fluid, the vessel comprising a double hull (72) forming the load-bearing structure and a tank (71), as claimed in claim 14, arranged in the double hull.

16. A use of a vessel (70) as claimed in claim 16, in which a fluid is conducted through insulated pipelines (73, 79, 76, 81) from or toward a floating or land-based storage installation (77) toward or from the tank of the vessel (71) in order to load or unload the vessel.

17. A system for the transfer of a fluid, the system comprising a vessel (70) as claimed in claim 15, insulated pipelines (73, 79, 76, 81) being arranged so as to connect the tank (71) installed in the hull of the vessel to a floating or land-based storage installation (77) and a pump to drive a flow of fluid through insulated pipelines from or toward the floating or land-based storage installation toward or from the tank of the vessel.