



(51) International Patent Classification:

C22C 1/10 (2006.01) *B22F 3/00* (2006.01)
C22C 1/05 (2006.01) *B22F 7/06* (2006.01)

(21) International Application Number:

PCT/US2012/059490

(22) International Filing Date:

10 October 2012 (10.10.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/271,415 12 October 2011 (12.10.2011) US

(71) Applicant (for all designated States except US): NATIONAL OILWELL DHT, L.P. [US/US]; 7909 Parkwood Circle Drive, Houston, Texas 77036 (US).

(72) Inventor; and

(71) Applicant (for US only): SRESHTA, Harold A. [US/US]; 2210 Westview Blvd, Apt# 139, Conroe, Texas 77304 (US).


(74) Agents: MAAG, Greogry et al.; CONLEY ROSE, P.C., P. O. Box 3267, Houston, Texas 77253-3267 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) Title: DISPERSION OF HARDPHASE PARTICLES IN AN INFILTRANT



(57) Abstract: Composite materials for use with a drill bit for drilling a bore-hole in earthen formations. The composite material comprises a first pre-infiltrated hardphase constituent and a second preinfiltrated hardphase constituent. The second pre-infiltrated hardphase constituent is a carbide which comprises at least 0.5 weight % of a binder and at least about 1% porosity. The composite material further comprises an infiltrant.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

13 March 2014