

A VARIABLE BEHAVIOUR CONTROL MECHANISM FOR A MOTIVE SYSTEM

RELATED APPLICATIONS

This application derives priority from New Zealand patent application number 715391
5 the contents of which are incorporated herein by reference.

TECHNICAL FIELD

Described herein is a variable behaviour control mechanism for a motive system. More specifically, a mechanism is described with sensitivity to a variety of motion
10 characteristics, the mechanism comprising means to measure a plurality of motion characteristics and, where the system is activated to complete some manner of movement, or movement prevention, in response to the mechanism dynamics of movement, activation only occurs as a result of sensitivity to a plurality of characteristics of motion.

15

BACKGROUND ART

As noted above, this disclosure relates to a mechanism for a motive system whose activation alters in response to the characteristic of the dynamics of the motion of the system.

20 Known art systems use a single characteristic measure on the dynamic motion as the input for determining a point of activation (e.g. position, velocity, acceleration, or jerk). These systems provide an activation of the systems based on the input characteristics of a single threshold value of the measured metric. An example of this type of mechanism may be a seat belt used in a vehicle. The seat belt mechanism allows line
25 extension and retraction however, when a sudden acceleration occurs, latches engage a stop mechanism and line extension halts. In this example the single motion characteristic measured is acceleration. No other aspects of system motion are measured or used to control the activation of the stop mechanism. This type of system

is clearly effective however it is far from perfect, for example, because the system is prone to unwanted activation for example when the user fits the seatbelt and pulls the belt too rapidly.

5 In many situations and applications it is desired (and beneficial) to have the activation of the system vary based on the dynamics of the motion – the dynamics of the motion being determined by considering the variation in motion characteristic(s) with respect to time.

By definition, a system setting an activation threshold value based on a single characteristic measure is unable to determine activation based on a threshold set by
10 that single characteristic measure itself.

However, if a change of the characteristic measure was determined, or the characteristic behaviour of the motion with respect to a time reference was considered, or an alternative characteristic measure was considered, and a measure or assessment of this was then used in some manner with or alongside the single
15 characteristic measured to determine the activation, then the desired system activation response could be achieved. Activation may for example be a threshold, varied by one or more motion characteristic measures or using a plurality of characteristic measures to determine a fixed activation threshold. Expressed another way, if a greater range of motion characteristics are measured, the eventual
20 mechanism may be less prone to false activations, more likely to activate when needed and potentially more likely to activate faster than perhaps might be the case when a single motion characteristics is measured.

An aim of the mechanism described herein may be to provide an alternative variable behaviour control mechanism for a motive system or at least provide the public with a
25 choice.

Further aspects and advantages of the control mechanism and method of use will become apparent from the ensuing description that is given by way of example only.

SUMMARY

Described herein is a variable behaviour control mechanism with a variety of motion characteristics, the mechanism comprising means to reference a plurality of motion characteristics and, where the mechanism activates when a threshold is reached to
5 complete some manner of control or control prevention in response to the motion characteristics, activation only occurring as a result of a plurality of characteristic of motion. The mechanism described is comparatively more complicated than art single motion characteristic measurement system like a simple vehicle seat belt and as a result may be used to for example, minimise or prevent unwanted activation thereby
10 creating increased functional and application yet operate with great accuracy when activation is required.

In a first aspect, there is provided a variable behaviour control mechanism in a motive system, the mechanism comprising:

at least one primary system that is configured to undergo motion according to a
15 kinematic relationship when a change is imposed on the primary system, the at least one primary system having:

(a) at least one sensor that measures at least two motion characteristics of the at least one primary system according to the kinematic relationship; or

(b) at least two sensors, the sensors each measuring at least one motion
20 characteristics of the at least one primary system according to the kinematic relationship; and

wherein, activation occurs between the at least one primary system and at least one secondary system when a combination of the sensed motion characteristics achieves a threshold.

25 In a second aspect, there is provided a variable behaviour control mechanism in a motive system, the mechanism comprising:

at least one primary system that is configured to undergo motion according to a kinematic relationship when a change is imposed on the primary system, the at least one primary system having:

(a) at least one sensor that measures at least two motion characteristics of the at least one primary system according to the kinematic relationship; or

(b) at least two sensors, the sensors each measuring at least one motion characteristics of the at least one primary system according to the kinematic relationship; and

wherein, activation occurs between the at least one primary system and at least one secondary system when the at least one sensed motion characteristic achieves a threshold, the threshold being determined based on the measure of at least one further motion characteristic.

10 In a third aspect, there is provided a variable behaviour control mechanism in a motive system, the mechanism comprising:

at least one primary system that is configured to undergo motion according to a kinematic relationship when a change is imposed on the primary system, the at least one primary system having:

15 (a) at least one sensor that measures at least two motion characteristics of the at least one primary system according to the kinematic relationship; or

(b) at least two sensors, the sensors each measuring at least one motion characteristics of the at least one primary system according to the kinematic relationship; and

20 wherein, activation occurs between the at least one primary system and at least one secondary system when a set of criteria is met by at least two or more motion characteristics.

In a fourth aspect, there is provided a method of controlling a variable behaviour control mechanism in a motive system by the steps of:

25 (a) providing a mechanism substantially as described above; and

(b) providing a motive force on the at least one primary mechanism;

(c) referencing at least two motion characteristics;

(d) when a threshold is reached based on the reference motion characteristics,

activation occurs between the at least one primary system and the at least one secondary system.

Advantages of the above may comprise one or more of:

- 5 - Differentiation between motion types - the mechanism can be tuned to distinguish different motion types based on the 'signature' of the motion. For example a free falling object is subject to a constant acceleration of 9.81 m/s^2 and a linearly increasing velocity while a person walking has a varying acceleration and velocity. Although both motions may reach an equal velocity or acceleration the device can have a different response the each situation;
- 10 - Short fall distance/ lower nuisance lock off occurrence - when the device is used in an SRL, the system can be tuned to quickly active under the correct combination of acceleration and velocity thereby obtaining short fall distance. This would occur in a free fall event. However the same device will be keep false activations during normal work events (nuisance lock off) to a minimum by
15 differentiating the different combinations of accelerations and velocities in these events;
- 20 - Tuneability - it may be possible to control the sensitivity of the device to the actual and relative values of motion (including velocity and acceleration). Likewise, it may be possible to control the sensitivity of the device to how the effects of motion (for example velocity and acceleration) are combined. Furthermore, using the effects it may be possible to control the threshold of the device at which a secondary system within the device is activated or engaged.
- 25 - Increased functionality – Based on the tuneability of the device, it is possible for the device to have an increase in functionality when used in specific application, particular where the 'signatures' of the input motion in which the device should
30 not activate are close to those where activation is essential. As will be understood, as the device has the ability to sense and activate from a range of motion characteristics, the combination of the motion characteristics, and the relative thresholds of the characteristics, the accuracy of the device for determining the need to active secondary functions is significantly improved.

- Quicker activation times and lower nuisance lock off occurrence - when the device is used in a self retracting lifeline (SRL) application, the activation time for the device can be improved thereby resulting in short fall distances whilst maintaining or reducing in potential nuisance lock-off events. Equally, in seat belt applications, the device can increase the useability of the product by reducing the number of accidental activations of the locking mechanism when the belt is extracted by the users whilst improving the activation time and accuracy during an actual accident or collision;
- The mechanism disclosed may overcome the shortcoming of the known art systems in the way noted above, by characterising the motion of the system through a richer set of characteristic measures. Activation of the mechanism may be determined based on variation of a threshold value of one characteristic motion measure by another (or combination of) characteristic measure(s). Alternatively, the threshold for activation may be determined by the profile of one or more characteristic measures values considered with respect to a time reference. This may be achieved mechanically, electrically/electronically, or a combination of both. The characteristic of motion may be determined instantaneously at a point in time, or over a time period.
- Processors and/or algorithms may further be utilised alongside the mechanism to further tune the mechanism dynamics thus providing greater mechanism versatility.

BRIEF DESCRIPTION OF THE DRAWINGS

Further aspects of the variable behaviour control mechanism and method of use will become apparent from the following description that is given by way of example only and with reference to the accompanying drawings in which:

Figure 1 illustrates one stylised embodiment of the activation mechanism;

Figure 2 illustrates graphs showing possible profiles over time of the first and second motion characteristics;

- Figure 3 is a flow diagram illustrating a process of operation of the mechanism;
- Figure 4 illustrates an alternative embodiment of the activation mechanism;
- Figure 5 illustrates graphs showing possible profiles over time of the first and second motion characteristics;
- 5 Figure 6 illustrates the stylized embodiment of the activation mechanism as shown in Figure 1;
- Figure 7 illustrates graphs showing possible profiles sensed by the first sensor of the first and second motion characteristics as measured at an instance of time;
- Figure 8 illustrates possible profiles sensed by the first sensor of the first and second motion characteristics as measured over time according to a further embodiment;
- 10 Figure 9 illustrates a flow diagram of operation of the above further embodiment;
- Figure 10 illustrates an alternative flow diagram of operation of the above further embodiment;
- 15 Figure 11 illustrates a further alternative embodiment of the activation mechanism;
- Figure 12 illustrates a flow diagram of operation of the above further embodiment;
- Figure 13 illustrates a flow diagram of operation of a yet further embodiment;
- 20 Figure 14 illustrates possible profiles sensed by the first sensor of the first and second motion characteristics as measured over time according to the above further embodiment;
- Figure 15 illustrates a rotary mechanism embodiment where activation results when one motion characteristic influences the threshold of activation for sensing on another motion characteristic;
- 25 Figure 16 illustrates a first graphed profile for a sensed combination of motion characteristics based on the above rotary mechanism embodiment;
- Figure 17 illustrates a second graphed profile for a sensed combination of motion characteristics based on the above rotary mechanism embodiment;
- 30 Figure 18 illustrates a third graphed profile for a sensed combination of motion

characteristics based on the above rotary mechanism embodiment;

Figure 19 illustrates a further embodiment of a mechanism using multiple sensors located on and acting directly on the primary system along with an external controller/processor;

- 5 Figure 20 illustrates a further embodiment of a rotary embodiment where the primary system and secondary system are coupled and the secondary system is motor, the activation of the system occurring when the motor is controlled by a controller and/or processor to provide resistance to motion;

10 Figure 21 illustrates an alternative linear embodiment of the activation mechanism;

Figure 22 illustrates a further alternative rotary embodiment of the activation mechanism; and

Figure 23 illustrates a further alternative linear embodiment of the activation mechanism.

15

DETAILED DESCRIPTION

As noted above, described herein is a variable behaviour control mechanism with a variety of motion characteristics, the mechanism comprising means to reference a plurality of motion characteristics and, where the mechanism activates when a threshold is reached to complete some manner of control or control prevention in response to the motion characteristics, activation only occurring as a result of a plurality of characteristic of motion. The mechanism described is comparatively more complicated than art single motion characteristic measurement system like a vehicle seat belt and as a result may be used to for example, minimise or prevent unwanted activation thereby creating increased functional and application yet operate with great accuracy when activation is required.

20

25

For the purposes of this specification, the term 'about' or 'approximately' and grammatical variations thereof mean a quantity, level, degree, value, number, frequency, percentage, dimension, size, amount, weight or length that varies by as

much as 30, 25, 20, 15, 10, 9, 8, 7, 6, 5, 4, 3, 2, or 1% to a reference quantity, level, degree, value, number, frequency, percentage, dimension, size, amount, weight or length.

The term 'substantially' or grammatical variations thereof refers to at least about 50%,
5 for example 75%, 85%, 95% or 98%.

The term 'comprise' and grammatical variations thereof shall have an inclusive meaning - i.e. that it will be taken to mean an inclusion of not only the listed components it directly references, but also other non-specified components or elements.

10 The term 'member' may refer to one part or element or a plurality of parts or elements that together achieve the function noted.

The term 'sensor' or grammatical variations thereof refers to either, or a combination of; an individual sensing element, combination of sensing elements, a sensing system, a sensing element and measurement system, a signal processing and manipulation
15 system, and that it may be a single system or combination of systems, either combined or separated. Further, the term 'sensor' or grammatical variations thereof refers to an item or items that both references at least one motion characteristic and then undergoes some behaviour itself (active) or actions some behaviour on another mechanism (passive), this behaviour causing or leading to an activation event. In
20 summary, the at least one sensor is able to respond to the applied conditions imposed by the component dynamics and statics that then lead the sensor to operate directly or indirectly in response to these to achieve an activation event.

The term 'threshold' or grammatical variations thereof refers to a value, or being determined as an event that is determined from a set of motion characteristics,
25 equating to a point at which activation action occurs.

The term 'variable behaviour' or grammatical variations thereof refers to the mechanism varying its response based on a plurality of inputs, the a plurality of inputs giving a greater number of possible but yet predictable and predetermined responses than single input mechanisms. Specifically, the variable behaviour may be variation
30 with respect to one motion characteristic due to the influence of other motion

characteristics.

The term 'measure' or grammatical variations thereof refers to ascertaining the size, amount, or degree of at least one mechanism motion characteristic.

5 The term 'signal' or grammatical variations thereof refers to at least one motion characteristic that provides an indication, warning, or command, or value e.g. voltage, current, force, binary, reaction of the mechanism configuration or possible future predicted position.

In a first aspect, there is provided a variable behaviour control mechanism in a motive system, the mechanism comprising:

10 at least one primary system that is configured to undergo motion according to a kinematic relationship when a change is imposed on the primary system, the at least one primary system having:

(a) at least one sensor that measures at least two motion characteristics of the at least one primary system according to the kinematic relationship; or

15 (b) at least two sensors, the sensors each measuring at least one motion characteristics of the at least one primary system according to the kinematic relationship; and

wherein, activation occurs between the at least one primary system and at least one secondary system when a combination of the sensed motion characteristics
20 achieves a threshold.

As may be appreciated from the above, the inventors have identified a design of mechanism where activation occurs with the motion characteristic both having an absolute and relative direct measurement against the threshold and therefore singularly and combined have direct influence on the activation.

25 In one embodiment, activation as noted above may result when the threshold is reached, this being when the two or more motion characteristic measures reach a predefined threshold, each motion characteristic given a direct weighting.

In an alternative embodiment, activation may result when the threshold is reached, wherein at least one motion characteristic measure is given a relatively higher

threshold weighting than the at least one further motion characteristic when measured against a fixed threshold.

In a second aspect, there is provided a variable behaviour control mechanism in a motive system, the mechanism comprising:

- 5 at least one primary system that is configured to undergo motion according to a kinematic relationship when a change is imposed on the primary system, the at least one primary system having:

(a) at least one sensor that measures at least two motion characteristics of the at least one primary system according to the kinematic relationship; or

- 10 (b) at least two sensors, the sensors each measuring at least one motion characteristics of the at least one primary system according to the kinematic relationship; and

wherein, activation occurs between the at least one primary system and at least one secondary system when the at least one sensed motion characteristic achieves a threshold, the threshold being determined based on the measure of at least one further motion characteristic.

As may be appreciated from the above, the inventors in this aspect have identified a mechanism where sensing of the one or more motion characteristic influences the activation threshold that one other motion characteristic senses and activates upon.

20 That is, the mechanism provides a means of activating when a weighted combination of motion characteristics exceed a chosen threshold while remaining un-activated or dis-engaged at all other times.

In a third aspect, there is provided a variable behaviour control mechanism in a motive system, the mechanism comprising:

- 25 at least one primary system that is configured to undergo motion according to a kinematic relationship when a change is imposed on the primary system, the at least one primary system having:

(a) at least one sensor that measures at least two motion characteristics of the at least one primary system according to the kinematic relationship; or

(b) at least two sensors, the sensors each measuring at least one motion characteristics of the at least one primary system according to the kinematic relationship; and

wherein, activation occurs between the at least one primary system and at least one secondary system when a set of criteria is met by at least two or more motion characteristics.

In a further embodiment common to both of the above aspects, the mechanism may utilise direct sensing and activation where the mechanism is configured with at least one sensor located on the mechanism or a part thereof that senses at least one motion characteristic and, when the threshold is met the at least one sensor causes activation directly on the mechanism, system, or a part thereof.

The at least one sensor may also move with the mechanism or part thereof.

Alternatively to the above embodiment, the mechanism may utilise indirect sensing. Only indirect or remote sensing may be used. Alternatively, a combination of indirect and direct sensing may be used. For example, the mechanism may be configured with at least one sensor located remotely from the mechanism, optionally with or without a further sensor located directly on the primary system and, when the threshold is met, activation occurs with the secondary system. As may be appreciated, in an embodiment where two sensors are used, one direct on the primary system and another indirect, each sensor may sense at least one motion characteristic. By contrast, in the embodiment where only a single indirect sensor is used, the indirect sensor senses at least two motion characteristics. Also, as noted above, there may be two indirect or remote sensors, each sensing at least one motion characteristic. Where multiple indirect sensors are used, the sensors may be on different remote objects.

In a further embodiment, activation may result when the threshold is reached, the threshold being derived from motion characteristics determined at a single instant in time.

In an alternative embodiment to the above, activation may result when the threshold is reached, the threshold being determined based on a profile of at least two of the sensed motion characteristic established. As may be appreciated, reference to a single

motion characteristic may inherently capture or require reference also to another motion characteristic, particularly when the motion characteristics are measured over a time period as opposed to a single instant of time, the further inherent motion characteristic being time and the way the motion characteristics change over time.

5 Reference herein to a single motion characteristic should not be given strict interpretation and it should be appreciated that the motion characteristic may also use time as a further motion characteristic.

As may be appreciated from the above embodiments, activation may occur when a signature of motion characteristics exceed a chosen threshold while remaining un-
10 activated at all other times. The signature of motion characteristics may be a unique combination of the motion characteristic attributes at a single instant in time. Alternatively, the signature of motion characteristics may be a unique combination of the motion characteristic attributes determined over a period time.

As noted above, activation may occur based on a measured threshold being achieved.
15 Activation may be due to an exceeding action, or alternatively, a decreasing action. For example, the threshold being reached and activation occurring, may only happen when at least one of the measured motion characteristics exceeds a desired threshold. Alternatively, the threshold being reached and activation occurring may only happen when at least one of the measured motion characteristics decreases below a desired
20 threshold. Expressed another way, the term 'activation' covers both activating an action to take place as well as deactivating the action, activation or deactivation being changes or alterations in relationship between the primary system and secondary system.

In one embodiment for example, activation occurs in response to a sudden jerk action
25 in combination with a measured high velocity triggering activation due to a threshold of jerk and velocity or ratio of jerk to velocity (or other relationships) being exceeded. Conversely, in a different mechanism, the opposite set of inputs may trigger the threshold being reached i.e. the jerk motion characteristics stop and/or the velocity decreases (or the relationship between these two motion characteristics decreases in
30 some manner), the threshold occurring due to a decreased measure. As should be appreciated, either an increase or decrease action may trigger a threshold being

reached and activation occurring and reference to one action or the other should not be seen as limiting.

The at least two motion characteristics may be selected as absolute or relative measures from: displacement, force degree and/or direction, velocity, acceleration,
5 deceleration, movement direction, jerk, time reference, and combinations thereof.

The at least two motion characteristics may alternatively or in combination with the above be selected as absolute or relative measures from a modified signal of: displacement, force degree and/or direction, velocity, acceleration, deceleration, movement direction, jerk, and combinations thereof.

10 By way of example, if the primary system was a pawl or inertial disk and motion of the pawl or inertial disk was damped, the signal from the pawl or inertial disk would be 'modified', damping therefore being the modification means. Equally an electronic signal could be processed and modified, offset, multiplied and so on hence reference to a mechanical embodiment should not be seen as limiting.

15 In one embodiment the characteristic of motion is displacement or any differential of displacement with respect to time. The first, second, third, fourth, fifth and sixth differentials of displacement with respect to time are velocity, acceleration, jerk, snap (or jounce), crackle and pop respectively. These motion characteristics are physical vector quantities meaning a direction and magnitude defines them. Although most of
20 these motion characteristics are the rate of change of another quantity with respect to time, they can be measured at an instant in time or evaluated over a period of time.

Two or more motion characteristics can be combined in various ways to define a threshold or a set of criteria. Input motion characteristics can be assessed to determine if the threshold has been exceeded or the criteria has been met.

25 Examples of when a threshold is exceeded may be: when the sum of the measured velocity and acceleration is greater than x , when the measured velocity is greater than x where x is inversely proportional to acceleration at that moment in time. Examples of when a criteria is met may be: when the measured velocity exceeds x and the measured acceleration exceeds y , when the acceleration is greater than x or the
30 displacement is less than y .

It should be noted that the measured motion characteristic value or measure may range from not changing over time e.g. a constant velocity, or may change slowly over time e.g. a gradual increase or decrease in acceleration, or may undergo a sudden change e.g. sudden displacement. Each one of these measured motion characteristics may only provide part of the overall mechanism (or at least primary system) kinematics and hence, why basing a threshold on a plurality of motion characteristics may be important or at least useful. For example, the mechanism may be a fall safety device such as a self retracting lifeline (SRL) and the measured motion characteristics may be displacement of line from a spool along with line acceleration. During a fall, the line acceleration may be gradual or even non-existent if the user was already in motion prior to a fall hence, if only rate of change in acceleration were measured, payout of line may well continue despite the fall since the sensor of acceleration 'sees' or senses no change occurring. When the acceleration rate is sensed in combination or in relation to line displacement from a spool, the mechanism may 'see' that the rate of line payout exceeds a threshold, this threshold equating to a fall scenario and activation resulting in a halt or slowing of line payout being initiated through secondary system activation, the secondary system being a braking mechanism in this example.

Activation may cause at least partial engagement between the at least one primary system and the at least one secondary system or parts thereof. Engagement may be full engagement. Activation may instead by disengagement. Reference is made for brevity herein to the term engagement, however, it should be appreciated that the opposite of disengagement may also be read where the term engagement is referred to and reference to engagement should not be seen as limiting in all cases noted.

The at least partial engagement may be direct. For example, direct may refer to an element or elements of the primary system directly touching and/or mating with an element or elements of the secondary system. The at least partial engagement may instead be indirect. In this case, engagement may be between an element or elements of the primary system activating an additional member or members that in turn engage with the secondary system. In either case, the final result of engagement between the primary and secondary systems or parts thereof, are common whether direct or indirect engagement methods are used.

The at least partial engagement may result in synchronised motion between the at least one primary system and the at least one secondary system. Both systems may for example be in a rotary mechanism, once engaged, spin together with no independent motion between the systems.

- 5 The at least partial engagement may cause the at least one secondary system to resist change (in one example being movement) of the at least one primary system. Alternatively, engagement may cause the at least one primary system to resist change of the at least one secondary system.

10 The at least partial engagement may halt motion of the at least one primary mechanism and the at least one secondary system.

The at least partial engagement may result in change to the interaction with the secondary system.

The at least partial engagement may result in alteration/modification/change to the characteristics of the secondary system.

- 15 The at least one sensor may be selected from: at least one mechanical sensor, at least one fluidic sensor, at least one thermal sensor, at least one magnetic sensor, at least one electrical sensor, at least one electronic sensor, and combinations thereof.

20 A sensor as described herein may be a discrete element or a system of elements comprised such that, in combination, their behaviour is sensitive to particular input conditions (such as motion behaviour) and optionally, providing a repeatable response to the sensed (motion) behaviour. The response noted may provide a signal output to an external system or element, or may act to alter or influence the operational conditions of a related system or element (that is not part of the sensor itself).

25 As noted above, the sensor may be a non-acting passive element or elements simply sensing the motion characteristic and sending this sensed information to another element. The sensor may instead be an active device that senses and is or are the activation/engagement means or mechanisms. Combinations of both forms of sensor (active and passive) may be used and reference to a passive sensor or active sensor should not be seen as limiting. One example of an active activation/engagement

system may for example be a pawl in a rotary system (together being the primary system) where the pawl is velocity sensitive/sensing and which rotates about an axis away from the rotary system when the threshold is reached, the pawl then latching with a secondary system. It should further be appreciated that a component's function
5 for sensing may not limit the ability of the component to provide function in other aspects of the primary system.

One advantage of the described mechanism is that the sensor dynamics may be tuned to vary the primary system dynamics. By way of example, if the sensor were a pawl that senses velocity, the sensitivity of the sensor may be tuned by varying the pawl, for
10 example by varying the pawl shape, varying the pawl centre of gravity, varying the pawl pivot point location and by having a bias that restricts pawl movement.

In one embodiment, the at least one primary system may comprise a carriage or rotor and the at least one sensing member may be linked to the carriage or rotor. The at least one sensing member linked to the carriage or rotor may for example be selected
15 from: a pawl, rocker, cam system, latch, disk, carrier, carriage, spool, and combinations thereof. This list should not be seen as limiting since a variety of other sensing members may be used.

As noted above, the primary system and sensor may be combined elements. In one example, a combined mechanical sensor / primary system may consist of elements
20 containing, but not limited to; masses, biasing elements, levers, cams, and/or magnetic drag elements. For example, an acceleration sensor may take the form of a mass constrained in the direction of acceleration by a biasing element whose resistance force alters predictably with displacement. The act of applying motion acceleration to a free end of the biasing element in line with the bias device will result in change in the
25 biasing element until a sufficient force is applied to the free mass by the biasing element to accelerate the free mass at the same rate as the external acceleration. As the mass accelerates in proportion to its mass and the force applied, the change in the biasing element may vary for different values of acceleration. In this way, the external acceleration is sensed by the mass and bias device interaction and the level of
30 acceleration may be determined by the level of change in the biasing element.

In another example, a rotational velocity may be sensed through mechanical means by a mass on a rotational element with a degree of motion freedom in the radial direction. Under rotation the mass will exhibit a tendency to accelerate in the radial direction proportional to the square of the rotational velocity. Restraining the mass by a bias device of similar properties to the above example, the radial change in the bias may be referenced to determine the rotational velocity.

The at least one sensor need not provide a discrete output in proportion to the sensed motion to be utilised and effective in the activation of a system. Instead, the at least one sensor may act upon its own elements to provide an activation behaviour, or interact with the constraints and/or variables of other systems to affect an activation behaviour.

A further sensor may be the use of electrical elements such as switches, electrical generators, and electric solenoids. Although not essential, these may be combined with mechanical elements to form the at least one sensor or sensors. An example of an electric speed sensor is an electrical generator whose electrical voltage output is proportional to the velocity of rotation. In another example, an electric solenoid may be combined with a magnet mass attached to a bias device as detailed in the above mechanical example. The motion of the magnet in the solenoid coil may result in an electrical voltage proportional to the velocity. As the movement of the magnet mass occurs with a change in acceleration, the rate of change in acceleration results in a velocity of the magnet with respect to the solenoid coil. The resulting voltage is therefore proportional to the rate of change of acceleration – i.e. a jerk motion characteristic.

An at least one sensor may comprise electronic components and discrete sensing elements configured to provide a sensor output related to the motion characteristic being measured. Such a sensor may utilise passive elements, or alternatively, may use a processor and/or algorithm in defining the sensor output or response. Alternatively, an electronic sensor may provide output signals for external input into a processor and/or algorithm for subsequent determination of an activation.

The at least one secondary system may be a mechanical mechanism that the primary

system or a part thereof engages. The at least one secondary system may for example be: a stop such as a cam plate, or latch plate and combinations thereof. This list should not be seen as limiting since a variety of other mechanical secondary system configurations may used.

- 5 The at least one secondary system may alternatively be an electrical or electronic mechanism comprising: a transmission mechanism, a motor, a solenoid, and combinations thereof. This list should not be seen as limiting since a variety of other electrical and electronic secondary system configurations may used. In this embodiment, the at least one secondary system may be a motor or brake that is
- 10 directly coupled to the primary system and upon activation the motor or brake then provides resistance to movement of the primary system.

In one example, the motor noted above may for example be the secondary system and if so, it may then be coupled to the primary system before activation and the activation causes the motor or brake to be powered to resist or stop the motion.

- 15 In a fourth aspect, there is provided a method of controlling a variable behaviour control mechanism in a motive system by the steps of:

- (a) providing a mechanism substantially as described above; and
- (b) providing a motive force on the at least one primary mechanism;
- (c) referencing at least two motion characteristics;
- 20 (d) when a threshold is reached based on the reference motion characteristics, activation occurs between the at least one primary system and the at least one secondary system.

The at least one primary member may contain at least one member sensitive to velocity and, at least one member sensitive to acceleration and a carrier in which the at

25 least two members are mounted on.

The at least one acceleration sensitive member has a sensing means that alters the characteristics of the at least one acceleration sensitive member relative to the carrier. The sensing means may for example be a force sensor.

The relative characteristics of the at least one acceleration sensing member may be

proportional to the acceleration present.

The characteristics of the at least one velocity sensing member may alter when the velocity passes a threshold, thus engaging or activating the at least one secondary system. The threshold at which the at least one velocity sensitive member changes
5 may be altered by the characteristics of the at least one acceleration sensitive member.

The characteristics of the acceleration sensor may be controlled by at least one bias element and the at least one bias element in turn may alter at least one second bias element between the at least one acceleration sensing member and the at least one velocity sensing member. The bias element or elements may be a spring or springs.

10 Alternately a single primary member may be mounted to a carrier and may be sensitive to both velocity and acceleration.

The single primary member may be configured in such a way that the forces acting on it due to velocity and acceleration combine, with the combined force altering the characteristics of a single primary member relative to the carrier when a pre-
15 determined threshold is exceeded, thus activating or engaging the at least one secondary system.

Velocity sensing noted above may be achieved in various ways beyond those noted above. For example, the velocity activation system may use the dynamics of a rocker travelling over a ramp and the dynamics making the rocker move into a latched
20 position above a velocity threshold. The rocker resistance to latched position movement may be modified through changing the bias on the rocker in response the acceleration on the system.

Activation in the above example may be at least in part related to velocity, the carrier being a rocker and the velocity sensed using the dynamics of a rocker travelling over a
25 ramp and the dynamics making the rocker move into an activated position above a velocity threshold.

Activation causes the rocker to engage the primary and secondary systems together and/or engage the at least one additional latching member if present.

The rocker resistance to latched position movement is modified through changing the

bias on the rocker in response to acceleration on the mechanism or part thereof.

Final embodiments for the mechanism described herein may be varied. For example, an automatic belay device (autobelay) or self retracting lifeline (SRL) embodiment may use the mechanisms. In an SRL embodiment, a line may extend and retract from the SRL device and when the line extends from the SRL device at a rate beyond the threshold, the mechanism engages and applies a retarding force on the rate of line extension. SRL and autobelay applications should not be seen as limiting since the devices described may be used for a wide variety of other applications, non-limiting examples including speed control or load control of:

- 10 • a rotor in a rotary turbine;
- exercise equipment e.g. rowing machines, epicyclic trainers, weight training equipment;
- roller-coasters and other amusement rides;
- Elevator and escalator systems;
- 15 • evacuation descenders and fire escape devices;
- conveyer systems:
- rotary drives in factory production facilities;
- materials handling devices such as conveyer belts or a braking device in a chute;
- roadside safety systems e.g. the energy absorber may be connected in a system
20 to provide crash attenuation through the dissipation of energy via the energy absorber e.g. a roadside barrier or roadside barrier terminal end;
- seat belts in vehicles;
- zip lines;
- braking mechanisms for trolleys and carriages;
- 25 • Bumpstops in transport applications;
- Bumpstops in crane applications;
- Torque or force limiting devices in mechanical drive train;

- Structural overload protection in wind turbines;
- Load limiting and energy dissipation in structures, buildings and bridges.

Advantages of the above may comprise one or more of:

- Differentiation between motion types - the mechanism can be tuned to distinguish different motion types based on the 'signature' of the motion. For example a free falling object is subject to a constant acceleration of 9.81 m/s^2 and a linearly increasing velocity while a person walking has a varying acceleration and velocity. Although both motions may reach an equal velocity or acceleration the device can have a different response the each situation;
- Short fall distance/ lower nuisance lock off occurrence - when the device is used in an SRL, the system can be tuned to quickly active under the correct combination of acceleration and velocity thereby obtaining short fall distance. This would occur in a free fall event. However the same device will be keep false activations during normal work events (nuisance lock off) to a minimum by differentiating the different combinations of accelerations and velocities in these events;
- Tuneability - it may be possible to control the sensitivity of the device to the actual and relative values of motion (including velocity and acceleration). Likewise, it may be possible to control the sensitivity of the device to how the effects of motion (for example velocity and acceleration) are combined. Furthermore, using the effects it may be possible to control the threshold of the device at which a secondary system within the device is activated or engaged.
- Increased functionality – Based on the tuneability of the device, it is possible for the device to have an increase in functionality when used in specific application, particular where the 'signatures' of the input motion in which the device should not activate are close to those where activation is essential. As will be understood, as the device has the ability to sense and activate from a range of motion characteristics, the combination of the motion characteristics, and the relative thresholds of the characteristics, the accuracy of the device for determining the need to active secondary functions is significantly improved.

- Quicker activation times and lower nuisance lock off occurrence - when the device is used in a self retracting lifeline (SRL) application, the activation time for the device can be improved thereby resulting in short fall distances whilst maintaining or reducing in potential nuisance lock-off events. Equally, in seat belt applications, the device can increase the useability of the product by reducing the number of accidental activations of the locking mechanism when the belt is extracted by the users whilst improving the activation time and accuracy during an actual accident or collision;
- The mechanism disclosed may overcome the shortcoming of the known art systems in the way noted above, by characterising the motion of the system through a richer set of characteristic measures. Activation of the mechanism may be determined based on variation of a threshold value of one characteristic motion measure by another (or combination of) characteristic measure(s). Alternatively, the threshold for activation may be determined by the profile of one or more characteristic measures values considered with respect to a time reference. This may be achieved mechanically, electrically/electronically, or a combination of both. The characteristic of motion may be determined instantaneously at a point in time, or over a time period.
- Processors and/or algorithms may further be utilised alongside the mechanism to further tune the mechanism dynamics thus providing greater mechanism versatility.

The embodiments described above may also be said broadly to consist in the parts, elements and features referred to or indicated in the specification of the application, individually or collectively, and any or all combinations of any two or more said parts, elements or features.

Further, where specific integers are mentioned herein which have known equivalents in the art to which the embodiments relate, such known equivalents are deemed to be incorporated herein as of individually set forth.

WORKING EXAMPLES

The above described control mechanism and method of use are now described by reference to specific examples.

5

EXAMPLE 1

As noted in the detailed description above, one activation sensing mechanism may sense at least two motion characteristics on a primary system.

This embodiment is described in more detail below with reference to Figure 1 which shows a stylised mechanism with a primary system 1, a secondary system 2 and, a force in direction F applied on the primary system 1 that causes motion M of the primary system 1. A sensor 3 may be located on the primary system 1 that measures two motion characteristics.

Figure 2 in the upper graph shows a possible profile P1 of the first motion characteristic MC1 as measured over time t on the x-axis and the first motion characteristic measure MC1 on the y-axis e.g. displacement, force degree and/or direction, acceleration, jerk, velocity and so on. The Figure 2 bottom graph shows a possible profile P2 of the second motion characteristic MC2 as measured over the same time period, time being on the x-axis, and the second motion characteristic MC2 measure on the y-axis.

Figure 3 is a flow diagram illustrating the process of operation beginning with an external force being imposed, causing motion of the primary system, sensing then commenced of two or motion characteristics, a decision step testing whether the motion characteristics have reached a threshold and if not, repeating the sensing step, and if yes, activation occurs with the secondary system.

Note that in this example activation may occur by a direct action of the sensor causing activation with the secondary system, for example by causing primary and secondary system engagement.

EXAMPLE 2

As noted in the detailed description above, one activation sensing mechanism may sense at least two motion characteristics one motion characteristic being directly on the primary system and another at a point remote to the primary system.

This embodiment is described in more detail below with reference to Figure 4 which shows a stylised mechanism with a primary system 1, a secondary system 2 and, a force in direction F applied on the primary system 1 that causes motion M of the primary system 1. A first sensor 3 may be located on the primary system 1 that may measure two motion characteristics MC1, MC2 while a second sensor 4 located distal to the primary system 1 and sensor 3 may be located on another object 5 e.g. a person or weight attached distant to the primary system 1 and the second sensor 4 may measure two motion characteristics MC3, MC4 of the person or weight 5.

Figure 5 in the left hand graphs show possible profiles P1, P2 sensed by the first sensor of the first and second motion characteristics MC1, MC2 as measured over time (time t being on the x-axis and the motion characteristic measures MC1, MC2 being on the y-axis e.g. displacement, force degree and/or direction, acceleration, jerk, velocity and so on). Figure 5 on the right hand side shows possible profiles P3, P4 of the second sensed motion characteristics MC3, MC4 as measured over the same time period, time t again being on the x-axis, and the motion characteristic measure on the y-axis.

The flow diagram shown in Figure 3 also applies to this system albeit using different sensor configuration and measuring four motion characteristics MC1, MC2, MC3, MC4.

Note that in this example activation may occur by a combination of direct 3 and indirect 4 sensing causing activation with the secondary system 2, activation being via a direct action of the first sensor 3 causing activation.

EXAMPLE 3

As noted in the detailed description above, a further activation sensing mechanism may sense at least two motion characteristics at an instant of time and base activation on the sensed characteristics at the instant of time.

This embodiment is described in more detail below with reference to the mechanism of

Figure 1 again.

Figure 6 in the graphs show possible profiles P1, P2 sensed by the first sensor 3 of the first and second motion characteristics MC1, MC2 as measured over time (time t being on the x-axis and the motion characteristic measures being on the y-axis (e.g. displacement, force degree and/or direction, acceleration, jerk, velocity and so on). The motion characteristics MC1, MC2 may be measured at a single instant of time t_i denoted by the dashed line AA, this time t_i equating for example to a specific pre-determined moment or this instant of time being one of a number of time instants that the sensor 3 senses.

- 10 The flow diagram shown in Figure 3 also applies to this system albeit using sensor 3 timing t_i based around measuring characteristics MC1, MC2 at a single instant t_i or instants of time t_i .

Note that while direct sensing 3 is indicated in Figure 1, the same principle of sensing at an instant of time t_i may apply to the direct 3 and indirect 4 sensing mechanism of

- 15 Example 2.

EXAMPLE 4

- Example 3 illustrated measurement at an instant of time. By contrast, the mechanism may sensing the two or more motion characteristics over a period of time and basing activation on the system behaviour over time, more like a signature of motion or mechanism behaviour.

- Using the same mechanism is that shown in Figure 1, the resulting graphs shown in Figure 7 show possible profiles P1, P2 sensed by the first sensor 3 of the first and second motion characteristics MC1, MC2 as measured over time (time t being on the x-axis and the motion characteristic measures being on the y-axis). The motion characteristics MC1, MC2 may be measured over a selected time period t_p shown in shading, this time period t_p equating for example to a specific pre-determined time period or being one of a number of time periods t_p that the sensor 3 senses.

In this mechanism, the flow diagram may be slightly different as shown in Figure 8.

Steps of imposing an external force and subsequent primary system movement remain the same. The next step of sensing occurs over a time period t_p . The threshold decision step is then one of comparing the time period t_p sensed motion characteristics against a library of signature motion characteristic profiles or a motion profile set. If the sensed time period characteristics meet with the library 'normal' operation characteristics, measurement may then recommence over a further time period. If the motion characteristics over the time period noted fall outside the 'normal' range as determined by the library of profiles, activation may then occur.

The process may also follow the flow diagram shown in Figure 9 where, between collecting the sensed characteristic information of the time period and the threshold decision step, an algorithm may be applied to the sensed time period information to alter the data collected. For example, the time period data collected may be amplified, one characteristic weighted over the other and so on. Once the algorithm is applied, the threshold decision is then completed as per the Figure 9 process.

15

EXAMPLE 5

In this Example, an embodiment is described where activation is based on at least two measured motion characteristics acting in conjunction directly to activate against a threshold, the threshold being set by a bias spring.

Figure 10 illustrates a potential mechanism with the above activation process. The mechanism shown may have a shaft 21 with primary system rotating about the shaft 21, the primary system comprising an inertial ring 22 and pawl 23. The secondary system 24 is a latch member 25 that surrounds the primary system. One motion characteristic (acceleration) influences the threshold of activation for sensing on another motion characteristic (velocity) where the pawl 23 acts as a velocity sensor and the inertial ring 22 acts as an acceleration sensor. On application of a force, for example to the shaft 21, the inertial ring 22 rotates, and when the velocity and acceleration motion characteristics reach or exceed a threshold, in this case being when one or both motion characteristics (velocity and acceleration) reach or exceed a magnitude sufficient to overcome a spring bias 26, the inertial ring 22 responds to

30

acceleration and the pawl 23 responds to velocity so that the primary system moves relative to the shaft 21 and the inertial ring 22 and pawl 23 engage with an outer secondary system 24 latch member 25. In the embodiment shown, distance 'd' is the moment arm for centrifugal force. As may be appreciated, both motion characteristics
5 velocity and acceleration act directly on the pawl 23 and act in combination.

The activation process for this mechanism is further described in the flow diagram of Figure 11. Each sensed motion characteristic (e.g. velocity and acceleration) are added together at an equal weighting and a threshold decision occurs against a given threshold (e.g. the spring bias). If the threshold is not reached, further sensing occurs
10 and, if activation does occur, the mechanism activates.

EXAMPLE 6

As an alternative to the additive weighting or even weighting described in Example 5, the different characteristics may be given a varied weighting relative to one another to
15 achieve and different activation threshold.

Using the basic mechanism of Example 1 and Figure 1 and referring to the flow diagram of Figure 12, the mechanism may measure two motion characteristics via two different sensors. A measured first motion characteristic may provide a threshold limit and the measured second motion characteristic is compared to the first motion characteristic,
20 activation only occurring when the second motion characteristic achieves the first motion characteristic threshold. Using this mechanism, the threshold may vary as opposed to being a fixed measure for all sets off motion characteristic. The graphs shown in Figure 13 further illustrate this mechanism where the first motion characteristic measurement MC1 profile P1 varies over time as shown in the right hand
25 side graph. The left hand side graph shows the measured behaviour of the second motion characteristic MC2 profile P2 over time with the first motion characteristic MC1 profile P1 superimposed (the dotted line). Activation might only occur for example at point BB when the second measured motion characteristic MC2 achieves the first measured motion characteristic.

30

EXAMPLE 7

In this example a more practical approach is shown of the mechanism of Example 7 above where activation results when one motion characteristic e.g. acceleration, influences the threshold of activation for sensing on another motion characteristic e.g. velocity.

As shown in Figure 14, the activation mechanism may comprise a pawl 50 mounted on a rotating disk 51 that is retained by a bias element 52 (magnet, spring etc.) between the pawl 50 and an inertial mass 53 also mounted on the rotating disk 51. When the disk 51 is spinning, a centripetal force is present on the pawl 50 that acts against the bias element 52. Another bias element 54 is present between the rotating disk 51 and the inertial mass 53. Upon rotational acceleration of the disk 51, the inertial mass 53 acts against the bias element 52 and rotates relative to the disk 51, moving the pawl 50 bias element 52 closer to the pawl 50 pivot axis 55, thereby reducing the restraining torque and lowering the rotational velocity at which the pawl 50 overcomes the bias element 52. When the disk 51 is spinning at a constant velocity or subjected to only a small acceleration the bias element 52 between the pawl 50 and the inertial mass 53 remains further away from the pawl 50 pivot axis 55, thus providing a higher restraining torque, requiring a greater rotational velocity for the pawl 50 to overcome the bias element 52. When the pawl 50 overcomes the bias element 52 a secondary stopping or braking system 56 is engaged (activation).

The possible resulting profiles for the above mechanism, assuming velocity and acceleration are the motion characteristics might look as per:

- Figure 15 where the threshold T is reached when a combination of high acceleration and low velocity occurs, the profile changing via a curved path;
- Figure 16 where the threshold T is reached when a combination of high acceleration and low velocity occurs, the profile changing in a linear step manner; or
- Figure 17 where the threshold T is reached when a combination of a high acceleration and high velocity occurs and the profile changing in a relatively linear manner.

As should be appreciated, the exact profile will be dependent on the system dynamics.

EXAMPLE 8

In this Example a more practical approach is described illustrating a mechanism using
5 multiple sensors located on and acting directly on the primary system along with an indirect sensor, the combination of sensors being both mechanical and electronic sensors.

Figure 18 shows the embodiment noted. The mechanism has a primary system comprising a rotor 30 mounted to a shaft 31. The rotor 30 rotates on application of a
10 force to the shaft 31. Located on the rotor 30 distal to the shaft 31 is a motion sensor 32 that may be used to sense changes in shaft 31 acceleration. The rotor 30 may also have a pawl 33 that pivots from the rotor 30 due to centrifugal force, the pawl 33 pivot point 34 offset from the rotor 30 shaft 31. The pawl 33 may be a velocity sensor. A third sensor 35 may also be used, in this example being an electronic controller 35 that
15 receives at least one of the sensed motion characteristics shown in the Figure as receiving the motion sensor 32 sensed motion characteristic (acceleration). The controller 35 in turn varying a threshold varying device 36, in this case being a solenoid 36 on the rotor 30 that provides a bias force against pawl 33 rotating outwards relative to the rotor 30 due to centrifugal force F . Not shown for clarity is a secondary system
20 around at least part of the primary system. When the threshold is reached or exceeded, the pawl 33 rotates about the pivot point 34 away from the rotor 30 shaft 31 axis of rotation and the pawl 33 engages with the secondary system or a part thereof.

EXAMPLE 9

25 Figure 19 illustrates a linear embodiment of the mechanism.

The primary system in this embodiment may be a carriage 40 that a pawl 41 is rotatably linked to about axis 42. The pawl 41 may be paramagnetic and, when the primary system moves by carriage 40 motion M through a magnetic field 43 shown as the shaded area in Figure 20, an eddy current drag force is imposed on the pawl 41

urging rotating movement of the pawl 41 about the pivot axis 42. A secondary system 44 may be engaged by the pawl 41 when rotation occurs. The pawl 41 may be a first sensor that is sensitive to velocity and a force sensor 45 may be located on the pawl 41 being a second sensor motion characteristic. A spring 46 may be located between the pawl 41 and carriage 40 that acts to provide a threshold and it is only when the sensed motion characteristics reach a predetermined level that the threshold is overcome and the pawl 41 may activate with the secondary system 44.

EXAMPLE 10

Figure 20 illustrates a further embodiment using a primary system with a rotating rotor 50 that rotates on application of a force F to the rotor 50. The rotor 50 may have sensors 51 (only one shown for clarity) and the sensed motion characteristics are received and measured by a controller 52 such as a processor or micro-processor. The controller 52 need not be directly on the primary system 50, 51 or a part thereof as illustrated schematically in Figure 20. The controller 52 compares the sensed motion characteristics against a database of known motion characteristic measurements and/or profiles and determines if the sensed motion characteristics have reached or exceeded a threshold. Alternatively, the controller may compare the motion characteristic values against a set threshold level. On activation, the controller 52 operates a motor 53 (a secondary system) that resists or halts the primary system (rotor 50 and sensors 51) rate of rotation.

EXAMPLE 11

Figure 21 illustrates a further rotary embodiment, the activation mechanism having a pawl 60 mounted to a rotating disk 61 retained by a bias element 62. The pawl 60 is affected by centripetal force due to rotational velocity as well as inertial force caused by acceleration, both of which act against the bias element 62. The pawl 60 moves relative to the disk 61 when the combination of velocity and acceleration achieves a predetermined threshold, thus engaging the secondary stopping or braking system 63.

EXAMPLE 12

Figure 22 illustrates an alternative linear embodiment of the activation mechanism comprising a pawl 70 mounted to a carriage 71, the pawl 70 being retained by a bias element 72 connected to an inertial mass 73. The inertial mass 73 has a bias element 74 connected to the carriage 71. A drag force proportional to velocity acts on the pawl 70 against the bias element 72, upon acceleration the inertial mass 73 moves relative to the carriage 71, against the bias element 74, thereby moving the bias element 74 closer to the pawl 70 pivot axis 75, reducing the restraining torque and therefore the velocity at which the pawl 70 is released. When the carriage 71 velocity is constant or subjected to a small acceleration, the pawl bias element 72 remains further from the pawl 70 pivot axis 75, thus providing a higher restraining torque, requiring a greater velocity for the pawl 70 to overcome the bias element 74. When a combination of velocity and acceleration achieves a predetermined threshold, the pawl 70 is released and activates with the secondary stopping or braking system 76 by engaging the pawl 70 with an adjacent latching point 77.

Aspects of the variable behaviour control mechanism and method of use have been described by way of example only and it should be appreciated that modifications and additions may be made thereto without departing from the scope of the claims herein.

WHAT IS CLAIMED IS:

1. A mechanism, comprising:

a primary system configured to undergo motion according to a kinematic relationship when a force is imposed on the primary system, the primary system comprising a moving member and at least one further member linked to the moving member, the at least one further member acting as a first motion characteristic sensor that senses at least two motion characteristics of the primary system over a time period; and
a secondary system;

wherein, below a threshold of sensed motion characteristics, no activation occurs and the primary system and secondary system remain kinematically independent of one another, and, above the threshold of sensed motion characteristics, the at least one further member moves to cause direct engagement between the primary system and the secondary system, thereby slowing or stopping independent kinematic motion between the primary system and the secondary system.

2. The mechanism as claimed in claim 1 wherein the at least two motion characteristics are selected as absolute or relative measures from: displacement, force degree and/or direction, velocity, acceleration, deceleration, movement direction, jerk, and combinations thereof.

3. The mechanism as claimed in claim 1 wherein the first motion characteristic sensor is selected from: a mechanical sensor, a fluidic sensor, a thermal sensor, a magnetic sensor, an electrical sensor, an electronic sensor, and combinations thereof.

4. The mechanism as claimed in claim 1 wherein the at least one further member linked to the moving member is selected from: a pawl, a rocker, a cam system, a latch, a disk, a carrier, a carriage, a spool, and combinations thereof.

5. The mechanism as claimed in claim 1 wherein the secondary system is selected from: a cam plate, a latch plate, and combinations thereof.

6. The mechanism as claimed in claim 1 wherein the moving member is a carriage or rotor.

7. A mechanism, comprising:

a primary system configured to undergo motion according to a kinematic relationship when a force is imposed on the primary system, the primary system comprising a moving member and at least one further member linked to the moving member, the at least one further member acting as a first motion characteristic sensor that senses at least two motion characteristics of the primary system; and

a secondary system;

wherein, below a threshold of sensed motion characteristics, no activation occurs and the primary system and secondary system remain kinematically independent of one another, and, above the threshold of sensed motion characteristics, the at least one further member moves to cause direct engagement between the primary system and the secondary system, thereby slowing or stopping independent kinematic motion between the primary system and the secondary system;

wherein the primary system further comprises a second motion characteristic sensor located on an object or person distal to the primary system and first sensor, the object or person attached to the distal primary system and the second motion characteristic sensor measuring two motion characteristics of the distal object or person;

wherein the second motion characteristic sensor is an indirect motion characteristic sensor;

wherein, below a threshold of the sensed motion characteristics from both the first and second motion characteristic sensors, no activation occurs and the primary and secondary systems remain kinematically independent of one another; and

wherein, above a threshold of the sensed motion characteristics from both the first and second motion characteristic sensors, the at least one further member moves to cause direct

engagement between the primary system and secondary system slowing or stopping independent kinematic motion between the systems.

8. The mechanism of claim 1 wherein the moving member comprises a shaft and the at least one further member comprises an inertial ring and a pawl, the inertial ring and pawl being linked to and rotating about the shaft, the primary system undergoing motion according to a kinematic relationship when a force is imposed on the shaft, wherein the inertial ring senses acceleration of the primary system and the pawl senses velocity of the primary system;

wherein the secondary system comprises a latch member;

wherein, below a threshold of acceleration and velocity of the primary system, no activation occurs and the primary and the secondary systems remain kinematically independent; and

wherein, above a threshold of acceleration and velocity of the primary system, activation occurs, activation being engagement of the primary system pawl and the secondary system latch member so that the primary system and secondary system engage and are no longer kinematically independent.

9. The mechanism as claimed in claim 1 wherein the primary system comprises a pawl sensing a velocity of the primary system and an inertial mass sensing an acceleration of the primary system, the pawl and inertial mass both mounted on a rotatable disk, the pawl and inertial mass retained together via a first bias element, the rotatable disk movable about a central axis, wherein in use, the primary system undergoes motion according to a kinematic relationship when a force is imposed on the rotatable disk, the pawl having a centripetal force acting thereon when the rotatable disk spins, this centripetal force acting against the first bias element; and the primary system further comprising a second bias element located between the rotatable disk and the inertial mass that acts to weight the sensed motion characteristics and influence activation where, upon rotational acceleration of the rotatable disk, the inertial mass acts against the second bias element, rotating relative to the rotatable disk and in doing so, moving the first

bias element closer to the pawl pivot axis thereby reducing the restraining torque and lowering the rotational velocity at which the pawl overcomes the first bias element; and

wherein the secondary system is kinematically independent to and surrounds at least part of the primary system, the secondary system comprising a latch member;

wherein:

below a threshold of acceleration and velocity of the primary system, no activation occurs and the primary and the secondary systems remain independent; and

above a threshold of acceleration and velocity of the primary system, activation occurs, activation being engagement of the primary system pawl and the secondary system latch member so that the primary system and secondary system engage and are no longer kinematically independent.

10. A mechanism, comprising:

a primary system configured to undergo motion according to a kinematic relationship when a force is imposed on the primary system, the primary system comprising a moving member and at least one further member linked to the moving member, the at least one further member acting as a first motion characteristic sensor that senses at least two motion characteristics of the primary system; and

a secondary system;

wherein, below a threshold of sensed motion characteristics, no activation occurs and the primary system and secondary system remain kinematically independent of one another, and, above the threshold of sensed motion characteristics, the at least one further member moves to cause direct engagement between the primary system and the secondary system, thereby slowing or stopping independent kinematic motion between the primary system and the secondary system;

wherein the primary system further comprises a rotor mounted to a shaft, the rotor rotating on application of a force to the shaft;

wherein the first motion characteristic sensor is a direct motion characteristic sensor and is linked to and located on the rotor, the first motion characteristic sensor moving with the rotor, the first motion characteristic sensor measuring changes in acceleration of the shaft;

wherein the primary system further comprises a pawl linked to and which pivots from the rotor due to centrifugal force, the pawl pivot point off set from the rotor shaft, the pawl acting as a second direct motion characteristic sensor that measures changes in velocity of the shaft;

wherein the mechanism further comprises an indirect motion characteristic sensor being an electronic controller that receives the first and second direct sensed motion characteristics, the controller in turn varying a threshold varying device, the threshold varying device being a solenoid on the rotor that provides a bias force against pawl rotation outwards from the rotor due to centrifugal force;

wherein the secondary system is kinematically independent to the primary system, the secondary system located around at least part of the primary system;

wherein, below a threshold of the sensed motion characteristics, no activation occurs and the primary and secondary systems remain independent; and

wherein, above a threshold of the sensed motion characteristics, activation occurs, activation being engagement of the primary system and the secondary system as a direct action of the pawl causing activation so that the primary system and secondary system engage and are no longer kinematically independent.

11. A mechanism, comprising:

a primary system configured to undergo motion according to a kinematic relationship when a force is imposed on the primary system, the primary system comprising a moving member and at least one further member linked to the moving member, the at least one further member acting as a first motion characteristic sensor that senses at least two motion characteristics of the primary system; and
a secondary system;

wherein, below a threshold of sensed motion characteristics, no activation occurs and the primary system and secondary system remain kinematically independent of one another, and, above the threshold of sensed motion characteristics, the at least one further member moves to cause direct engagement between the primary system and the secondary system, thereby

slowing or stopping independent kinematic motion between the primary system and the secondary system;

wherein the primary system comprises a carriage and a pawl, the pawl rotatably linked to the carriage about a pawl axis, the pawl being a first velocity sensor and the pawl being paramagnetic;

wherein the mechanism further comprises:

a force sensor located on the pawl and a biasing member linked between the pawl and the carriage;

a magnetic field located adjacent the carriage and pawl; and

a secondary system kinematically independent to the primary system;

wherein, when the carriage moves linearly due to an imposed force and below a threshold of sensed velocity and force, no activation occurs and the primary and secondary systems remain independent; and

wherein, above a threshold of the sensed velocity and force, the threshold provided by the biasing and an eddy current drag force imposed on pawl motion as the pawl moves through the magnetic field, activation occurs, activation being engagement of the primary system pawl and the secondary system as a direct action of the pawl causing activation so that the primary system via the pawl and secondary system engage and are no longer kinematically independent.

12. A mechanism, comprising:

a primary system configured to undergo motion according to a kinematic relationship when a force is imposed on the primary system, the primary system comprising a moving member and at least one further member linked to the moving member, the at least one further member acting as a first motion characteristic sensor that senses at least two motion characteristics of the primary system; and

a secondary system;

wherein, below a threshold of sensed motion characteristics, no activation occurs and the primary system and secondary system remain kinematically independent of one another, and, above the threshold of sensed motion characteristics, the at least one further member moves to

cause direct engagement between the primary system and the secondary system, thereby slowing or stopping independent kinematic motion between the primary system and the secondary system;

wherein the primary system comprises a rotor, the rotor rotating on application of a force to the rotor, and, located on and moving with the rotor is a direct motion characteristic sensor measuring motion characteristics of the primary system and an electronic controller not directly on the primary system that receives at least one of the sensed motion characteristics from the primary system;

wherein the secondary system is kinematically independent to the primary system and linked to the controller in the form of a motor that is configured to resist or halt a rate of movement of the primary system;

wherein, when a force is imposed on the rotor causing rotation and primary system movement, the controller compares the sensed motion characteristics from the sensor against a database of known motion characteristic measurements and/or profiles and determines if the sensed motion characteristics have reached or exceeded a threshold and/or reached a set threshold level;

wherein, below a threshold of the sensed motion characteristics from the sensor, no activation occurs and the primary and secondary systems remain independent; and

wherein, above a threshold of the sensed motion characteristics, activation occurs, activation being the controller operating the motor to resist or halt the rate of movement of the primary system so that the primary system and secondary system no longer move kinematically independently.

13. A mechanism, comprising:

a primary system configured to undergo motion according to a kinematic relationship when a force is imposed on the primary system, the primary system comprising a moving member and at least one further member linked to the moving member, the at least one further member acting as a first motion characteristic sensor that senses at least two motion characteristics of the primary system; and

a secondary system;

wherein, below a threshold of sensed motion characteristics, no activation occurs and the primary system and secondary system remain kinematically independent of one another, and, above the threshold of sensed motion characteristics, the at least one further member moves to cause direct engagement between the primary system and the secondary system, thereby slowing or stopping independent kinematic motion between the primary system and the secondary system;

wherein the primary system comprises a carriage, a pawl and an inertial mass, the pawl and inertial mass mounted on the carriage, the pawl linked to the inertial mass via a first bias element; the primary system configured to undergo motion according to a kinematic relationship when a force is imposed on the carriage, the pawl having a drag force acting thereon when the carriage moves, this drag force acting against the first bias element;

wherein the primary system further comprises a second bias element located between the carriage and the inertial mass that acts to weight the sensed motion characteristics and influence activation where, upon linear acceleration of the carriage, the inertial mass acts against the second bias element, moving relative to the carriage and in doing so, moving the first bias element closer to the pawl pivot axis thereby reducing the restraining torque and lowering the drag force at which the pawl overcomes the first bias element;

wherein the secondary system is kinematically independent to and surrounds the primary system, the secondary system comprising a latch member;

wherein, below a threshold of acceleration and velocity of the primary system, no activation occurs and the primary and the secondary systems remain independent; and

wherein, above a threshold of acceleration and velocity of the primary system, activation occurs, activation being engagement of the primary system pawl and the secondary system latch member so that the primary system and secondary system engage and are no longer kinematically independent.

14. The mechanism as claimed in claim 1 wherein sensing of the motion characteristics occurs at a time instant.

15. A mechanism, comprising:

a primary system configured to undergo motion according to a kinematic relationship when a force is imposed on the primary system, the primary system comprising a moving member and at least one further member linked to the moving member, the at least one further member acting as a first motion characteristic sensor that senses at least two motion characteristics of the primary system; and

a secondary system;

wherein, below a threshold of sensed motion characteristics, no activation occurs and the primary system and secondary system remain kinematically independent of one another, and, above the threshold of sensed motion characteristics, the at least one further member moves to cause direct engagement between the primary system and the secondary system, thereby slowing or stopping independent kinematic motion between the primary system and the secondary system;

wherein at least one sensed motion characteristic is weighted more than another motion characteristic to alter the threshold causing activation.

16. The mechanism as claimed in claim 1 wherein the mechanism is linked to a spool of line and if the line extends at a rate beyond the threshold, mechanism activation results in application of a retarding force on the rate of line extension.

17. The mechanism as claimed in claim 1 wherein the mechanism governs speed control or line dispensing control.

18. The mechanism as claimed in claim 1, wherein the mechanism is a component within an auto-belay system.

19. The mechanism as claimed in claim 1, wherein the mechanism is a component within a self-retracting lifeline device.

20. The mechanism as claimed in claim 1, wherein the mechanism is a component within an evacuation descender and fire escape device.

21. The mechanism as claimed in claim 1, wherein the mechanism is a component within a braking device.

22. The mechanism as claimed in claim 1, wherein the at least one further member is exactly one further member.

23. The mechanism as claimed in claim 1, wherein the at least one further member is at least two further members.

24. A mechanism, comprising:

a primary system configured to undergo motion when a force is imposed on the primary system, the primary system comprising a rotatable disk rotatably movable about a central axis, and at least one further member linked to the rotatable disk, the at least one further member acting as a first motion characteristic sensor that senses at least two motion characteristics of the primary system; and a secondary system;

wherein the primary system and secondary system are configured to remain kinematically independent of one another below a threshold of sensed motion characteristics, and, above the threshold of sensed motion characteristics, the at least one further member is configured to move to cause direct engagement between the primary system and the secondary system, thereby slowing or stopping independent kinematic motion between the primary system and the secondary system;

wherein the at least one further member of the primary system comprises a pawl mounted on the rotatable disk on a pawl pivot axis for sensing primary system velocity and an inertial mass mounted on the rotatable disk sensing primary system acceleration, the pawl and inertial mass being retained together by a pawl bias element and a mass bias element being

provided between the rotating disk and the inertial mass, wherein in use, the primary system is configured to undergo motion according to a kinematic relationship when a force is imposed on the rotatable disk, the pawl having a centrifugal force acting thereon when the rotatable disk spins, this centrifugal force acting against the pawl bias element and the inertial mass being configured to rotate relative to the disk, against the mass bias element, on rotational acceleration of the disk, thereby moving the pawl bias element closer to the pawl pivot axis; and

wherein the secondary system is kinematically independent to and surrounds at least part of the primary system, the secondary system comprising a latch member.

25. The mechanism of claim 24 wherein the at least two motion characteristics of the primary system comprise velocity and acceleration and wherein:

below a threshold of acceleration and/or velocity of the primary system, the primary and the secondary systems remain independent; and

above a threshold of acceleration and/or velocity of the primary system, the primary system pawl engages the secondary system latch member so that the primary system and secondary system engage and are no longer kinematically independent.

26. The mechanism of claim 25 wherein the at least two motion characteristics of the primary system are rotational velocity and rotational acceleration.

27. The mechanism of claim 25 wherein the primary system is configured so that when a combination of velocity and acceleration achieves a predetermined threshold, the pawl overcomes the pawl bias element to engage the secondary system latch member.

28. The mechanism of claim 25 wherein an exceeding of a threshold of acceleration and/or velocity for activation of the primary system to engage the secondary system is sensed mechanically, with the proviso that the exceeding of the threshold is not sensed electrically or electronically.

29. The mechanism of claim 24 wherein the pawl bias element via which the pawl and inertial mass are retained together comprises a spring.
30. The mechanism of claim 24 wherein the inertial mass is an inertial disk or an inertial ring.
31. The mechanism of claim 24 wherein the at least one further member of the primary system comprises at least two pawls.
32. The mechanism of claim 24 wherein the first motion characteristic sensor is a mechanical sensor, with the proviso that the first motion characteristic sensor does not include a magnetic sensor, an electrical sensor, or an electronic sensor.
33. The mechanism of claim 24 wherein the sensing of the at least two motion characteristics of the primary system is performed instantaneously.
34. The mechanism of claim 24 wherein the sensing of the at least two motion characteristics of the primary system is performed over a period of time.
35. The mechanism of claim 24 wherein the rotatable disk, the inertial mass and the pawl comprise a common axis of rotation that is the central axis about which the rotatable disk rotatably moves.
36. The mechanism of claim 35 wherein the mechanism comprises a shaft that defines the central axis about which the rotatable disk rotates, and wherein the inertial mass and the pawl are rotatable about the shaft that defines the central axis about which the rotatable disk rotates.
37. The mechanism of claim 35 wherein the secondary system is a radially outer system that circumferentially surrounds the primary system.

38. The mechanism of claim 24 wherein the secondary system comprises a rotary mechanism that, upon the engagement between the primary system and the secondary system, rotates with the primary system.

39. A fall protection apparatus comprising the mechanism of claim 24.

40. The fall protection apparatus of claim 39 wherein the fall protection apparatus is a self-retracting lifeline (SRL).

41. The SRL of claim 40 wherein the SRL comprises an extendable/retractable line and wherein upon the engagement of the primary system pawl with the secondary system latch member, a retarding force is applied on a rate of extension of the extendable/retractable line.