

LIGHT-EMITTING DEVICES WITH FULLERENE LAYER

FIELD OF THE INVENTION

5 The present invention relates to organic-based light-emitting devices (OLEDs) and more particularly the present invention relates to hybrid electroluminescence devices in which a fullerene layer is used as the electron transport layer, replacing the problematic organic electron transport layer currently used in OLEDs. The present invention also relates to the use of interfacial contact layers for making Ohmic contact to the fullerene layer.

10

BACKGROUND OF THE INVENTION

A typical organic light-emitting device includes an anode, an active light-emitting zone comprising one or more electroluminescent organic material(s), and a cathode. One of the electrodes is optically transmissive while the other one is optically reflective. The function of the anode is to inject positively charged particles referred to as holes into the light-emitting zone, and that of the cathode is to inject electron into the emission zone. A process involved in the recombination of the electron and the hole leads to the creation of light wave. The light wave is escaped through one of the

15

20

25

30

35

40

45

50

55

60

65

70

75

80

85

90

95

100

105

110

115

120

125

130

135

140

145

150

155

160

165

170

175

180

185

190

195

200

205

210

215

220

225

230

235

240

245

250

255

260

265

270

275

280

285

290

295

300

305

310

315

320

325

330

335

340

345

350

355

360

365

370

375

380

385

390

395

400

405

410

415

420

425

430

435

440

445

450

455

460

465

470

475

480

485

490

495

500

505

510

515

520

525

530

535

540

545

550

555

560

565

570

575

580

585

590

595

600

605

610

615

620

625

630

635

640

645

650

655

660

665

670

675

680

685

690

695

700

705

710

715

720

725

730

735

740

745

750

755

760

765

770

775

780

785

790

795

800

805

810

815

820

825

830

835

840

845

850

855

860

865

870

875

880

885

890

895

900

905

910

915

920

925

930

935

940

945

950

955

960

965

970

975

980

985

990

995

1000

1005

1010

1015

1020

1025

1030

1035

1040

1045

1050

1055

1060

1065

1070

1075

1080

1085

1090

1095

1100

1105

1110

1115

1120

1125

1130

1135

1140

1145

1150

1155

1160

1165

1170

1175

1180

1185

1190

1195

1200

1205

1210

1215

1220

1225

1230

1235

1240

1245

1250

1255

1260

1265

1270

1275

1280

1285

1290

1295

1300

1305

1310

1315

1320

1325

1330

1335

1340

1345

1350

1355

1360

1365

1370

1375

1380

1385

1390

1395

1400

1405

1410

1415

1420

1425

1430

1435

1440

1445

1450

1455

1460

1465

1470

1475

1480

1485

1490

1495

1500

1505

1510

1515

1520

1525

1530

1535

1540

1545

1550

1555

1560

1565

1570

1575

1580

1585

1590

1595

1600

1605

1610

1615

1620

1625

1630

1635

1640

1645

1650

1655

1660

1665

1670

1675

1680

1685

1690

1695

1700

1705

1710

1715

1720

1725

1730

1735

1740

1745

1750

1755

1760

1765

1770

1775

1780

1785

1790

1795

1800

1805

1810

1815

1820

1825

1830

1835

1840

1845

1850

1855

1860

1865

1870

1875

1880

1885

1890

1895

1900

1905

1910

1915

1920

1925

1930

1935

1940

1945

1950

1955

1960

1965

1970

1975

1980

1985

1990

1995

2000

2005

2010

2015

2020

2025

2030

2035

2040

2045

2050

2055

2060

2065

2070

2075

2080

2085

2090

2095

2100

2105

2110

2115

2120

2125

2130

2135

2140

2145

2150

2155

2160

2165

2170

2175

2180

2185

2190

2195

2200

2205

2210

2215

2220

2225

2230

2235

2240

2245

2250

2255

2260

2265

2270

2275

2280

2285

2290

2295

2300

2305

2310

2315

2320

2325

2330

2335

2340

2345

2350

2355

2360

2365

2370

2375

2380

2385

2390

2395

2400

2405

2410

2415

2420

2425

2430

2435

2440

2445

2450

2455

2460

2465

2470

2475

2480

2485

2490

2495

2500

2505

2510

2515

2520

2525

2530

2535

2540

2545

2550

2555

2560

2565

2570

2575

2580

2585

2590

2595

2600

2605

2610

2615

2620

2625

2630

2635

2640

2645

2650

2655

2660

2665

2670

2675

2680

2685

2690

2695

2700

2705

2710

2715

2720

2725

2730

2735

2740

2745

2750

2755

2760

2765

2770

2775

2780

2785

2790

2795

2800

2805

2810

2815

2820

2825

2830

2835

2840

2845

2850

2855

2860

2865

2870

2875

2880

2885

2890

2895

2900

2905

2910

2915

2920

2925

2930

2935

2940

2945

2950

2955

2960

2965

2970

2975

2980

2985

2990

2995

3000

3005

3010

3015

3020

3025

3030

3035

3040

3045

3050

3055

3060

3065

3070

3075

3080

3085

3090

3095

3100

3105

3110

3115

3120

3125

3130

3135

3140

3145

3150

3155

3160

3165

3170

3175

3180

3185

3190

3195

3200

3205

3210

3215

3220

3225

3230

3235

3240

3245

3250

3255

3260

3265

3270

3275

3280

3285

3290

3295

3300

3305

3310

3315

3320

3325

3330

3335

3340

3345

3350

3355

3360

3365

3370

3375

3380

3385

3390

3395

3400

3405

3410

3415

3420

3425

3430

3435

3440

3445

3450

3455

3460

3465

3470

3475

3480

3485

3490

3495

3500

3505

3510

3515

3520

3525

3530

3535

3540

3545

3550

3555

3560

3565

3570

3575

3580

3585

3590

3595

3600

3605

3610

3615

3620

3625

3630

3635

3640

3645

3650

3655

3660

3665

3670

3675

3680

3685

3690

3695

3700

3705

3710

3715

3720

3725

3730

3735

3740

3745

3750

3755

3760

3765

3770

3775

3780

3785

3790

3795

3800

3805

3810

3815

3820

3825

3830

3835

3840

3845

3850

3855

3860

3865

3870

3875

3880

3885

3890

3895

3900

3905

3910

3915

3920

3925

3930

3935

3940

3945

3950

3955

3960

3965

3970

3975

3980

3985

3990

3995

4000

4005

4010

4015

4020

4025

4030

4035

4040

4045

4050

4055

4060

4065

4070

4075

4080

4085

4090

4095

4100

4105

4110

4115

4120

4125

4130

4135

4140

4145

4150

4155

4160

4165

4170

4175

4180

4185

4190

4195

4200

4205

4210

4215

4220

4225

4230

4235

4240

4245

4250

4255

4260

4265

4270

4275

4280

4285

4290

4295

4300

4305

4310

4315

4320

4325

4330

4335

4340

4345

4350

4355

4360

4365

4370

4375

4380

4385

4390

4395

4400

4405

4410

4415

4420

4425

4430

4435

4440

4445

4450

4455

4460

4465

4470

4475

4480

4485

4490

4495

4500

4505

4510

4515

4520

4525

4530

4535

4540

4545

4550

4555

4560

4565

4570

4575

4580

4585

4590

4595

4600

4605

4610

4615

4620

4625

4630

4635

4640

4645

4650

4655

4660

4665

4670

4675

4680

4685

4690

4695

4700

4705

4710

4715

4720

4725

4730

4735

4740

4745

4750

4755

4760

4765

4770

4775

4780

4785

4790

4795

4800

4805

4810

4815

4820

4825

4830

4835

4840

4845

4850

4855

4860

4865

4870

4875

4880

4885

4890

4895

4900

4905

4910

4915

4920

4925

4930

4935

4940

4945

4950

4955

4960

4965

4970

4975

4980

4985

4990

4995

5000

5005

5010

5015

5020

5025

5030

5035

5040

5045

5050

5055

5060

5065

5070

5075

5080

5085

5090

5095

5100

5105

5110

5115

5120

5125

5130

5135

5140

5145

5150

5155

5160

5165

5170

5175

5180

5185

5190

5195

5200

5205

5210

5215

5220

5225

5230

5235

5240

5245

5250

5255

5260

5265

5270

5275

5280

5285

5290

5295

5300

5305

5310

5315

5320

5325

5330

5335

5340

5345

5350

5355

5360

5365

5370

5375

5380

5385

5390

5395

5400

5405

5410

5415

5420

5425

5430

5435

5440

5445

5450

5455

5460

5465

5470

5475

5480

5485

5490

5495

5500

5505

5510

5515

5520

5525

5530

5535

5540

5545

5550

5555

5560

5565

5570

5575

5580

5585

5590

5595

5600

5605

5610

5615

5620

5625

5630

5635

5640

5645

5650

5655

5660

5665

5670

5675

5680

5685

5690

5695

5700

5705

5710

5715

5720

5725

5730

5735

5740

5745

5750

5755

5760

5765

5770

5775

5780

5785

5790

5795

5800

5805

5810

5815

5820

5825

5830

5835

5840

5845

5850

5855

5860

5865

5870

5875

5880

5885

5890

5895

5900

5905

5910

5915

5920

5925

5930

5935

5940

5945

5950

5955

5960

5965

5970

5975

5980

5985

5990

5995

6000

6005

6010

6015

6020

6025

6030

6035

6040

6045

6050

6055

6060

6065

6070

6075

6080

6085

6090

6095

6100

6105

6110

6115

6120

6125

6130

6135

6140

6145

6150

6155

6160

6165

6170

6175

6180

6185

6190

6195

6200

6205

6210

6215

6220

6225

6230

6235

6240

6245

6250

6255

6260

6265

6270

6275

6280

6285

6290

6295

6300

6305

6310

6315

6320

6325

6330

6335

6340

6345

6350

6355

6360

6365

6370

6375

6380

6385

6390

6395

6400

6405

6410

6415

6420

6425

6430

6435

6440

6445

6450

6455

6460

6465

6470

6475

6480

6485

6490

6495

6500

6505

6510

6515

6520

6525

6530

6535

6540

6545

6550

6555

6560

6565

6570

6575

6580

6585

6590

6595

6600

6605

6610

6615

6620

6625

6630

6635

6640

6645

6650

6655

6660

6665

6670

6675

6680

6685

6690

6695

6700

6705

6710

6715

6720

Grozea, X.D. Feng, Z.H. Lu, H. Aziz, and A.M. Hor, "Metal/Alq Interface Structures", Appl. Phys. Lett. 81, 766 (2002).]. This limits the ability to use low work function metals as cathode. In general the cathode interface stability suffers from the fact that organic and polymeric materials contain more than one element which are very reactive. Some elements such as oxygen readily react with elements making up the cathode to form interfacial oxides, which results in electrical degradation [A. Turak, D. Grozea, X.D. Feng, Z.H. Lu, H. Aziz, and A.M. Hor, "Metal/Alq Interface Structures", Appl. Phys. Lett. 81, 766 (2002)].

As a family member of naturally occurring allotropes of carbon, fullerene materials are known for their robust structures and superior charge transport properties. United States Patent No. 5,861,219 discloses the use of fullerenes as a dopant added to a host metal complex of 5-hydroxy-quinoxaline used in organic light emitting diodes. The host metal complex of 5-hydroxy-quinoxaline is contained in the electroluminescent layer which forms the emission zone in the structure. United States Patent Publication US 2002/0093006 A1 discloses the use of a fullerene layer as the light emissive layer in an organic light emitting diode structure.

United States Patent Publication US 2003/0042846 A1 discloses the use of a fullerene layer as an electron acceptor layer in organic photovoltaic devices.

Japan Patent 3227784 and Japanese patent application 04-144479 disclose the use of fullerenes as a hole transport layer.

United States Patent No. 5,171,373 discloses the use of fullerenes in solar cells. United States Patent No. 5,759,725 discloses the use of fullerenes in photoconductors.

The use of fullerenes as an interface layer between the hole transport layer and the light emission layer has been disclosed by Keizo Kato, Keisuke Suzuki, Kazunari Shinbo, Futao Kaneko, Nozomu Tsuboi, Satoshi Kobayashi, Toyoyasu Tadokoro, and Shinichi Ohta, Jpn. J. Appl. Phys. Vol. 42, 2526 (2003).

United States Patent No. 5,776,622 issued to Hung et al. discloses an electroluminescence device including an anode, cathode and EL layer, in

which the cathode layer contacts the EL layer and includes a fluoride layer in direct contact with the EL layer and a conductive layer in direct contact with the fluoride layer.

5 The light output of a typical OLED involves two-coupled light waves, one propagates directly through of the light-transmissive electrode, and the other reflected back from the reflective electrode and then propagate through the light-transmissive electrode. These two light waves have approximately the same amplitude and the optical interference of these two light beams dictates the total amplitude and spectral profile of the final output light waves.

10 It would be very advantageous to provide an organic-based electroluminescence device which provides better electronic transport in the electronic transport layer and better transport across the electronic transport layer from the cathode electrode layer to the light emission zone.

15 SUMMARY OF THE INVENTION

It is the object of the present invention to provide an organic-based electroluminescence device in which a fullerene layer is used as the electron transport layer, replacing the current problematic organic molecule-based electron transport layer and it is another objective of this invention to provide
20 an interfacial layer between the fullerene layer and a cathode electrode layer which makes Ohmic contact with the fullerene layer so that there is little or no potential barrier for electrons traveling across the fullerene/interfacial layer/metallic cathode region.

It is a further object of the present invention to provide a hybrid organic-
25 based light-emitting device that permits optical tuning of the output spectral and power efficiency.

In one aspect of the invention there is provided a layered structure including a fullerene layer exhibiting Ohmic behavior. The layered device includes a first layer comprising fullerenes having a first surface and a second
30 surface opposed to the first surface. The layered structure includes a second layer of pre-selected thickness comprising a fluoride compound located on the first surface of the first layer. The layered structure includes a third layer comprising an electrically conductive material located on the second layer.

The pre-selected thickness of the second layer is selected so that the layered structure exhibits substantially Ohmic behavior across the first, second and third layers.

5 In another aspect of the present invention there is provided a layered structure including a fullerene layer exhibiting Ohmic behavior. The layered structure includes a first layer comprising fullerenes having a first surface and a second surface opposed to the first surface. The layered structure includes a second layer comprising a low work function material located on the first surface of the first layer comprising fullerenes. The layered structure includes
10 a third layer comprising an electrically conductive material located on the second layer. The low work function material is chosen on the basis that the layered structure exhibits substantially Ohmic behavior across the first, second and third layers.

In another aspect of the invention there is provided a light-emitting
15 device, comprising a substrate and a first electrically conductive layer defining an anode electrode layer on the substrate. The device includes an electron transport layer comprising fullerenes, and a second electrically conductive layer defining a cathode electrode layer on the electron transport layer. The device includes a layer comprising a light-emissive material interposed
20 between the anode electrode layer and the electron transport layer.

In this aspect of the invention the device may include a hole transport layer interposed between the anode electrode layer and the light-emissive material. The hole transport layer may be comprised of organic molecules which conduct holes.

25 In this aspect of the invention the device may include an interfacial layer interposed between the layer comprising a fullerene and the electrically conductive layer defining a cathode electrode with the material of the interfacial layer being selected so that the interfacial layer makes Ohmic contact with the fullerene layer. The interfacial layer may comprise a fluoride compound and may be an alkaline fluoride compound. The fluoride compound
30 may be calcium fluoride (CaF_2).

There may also be an a lithium fluoride (LiF) layer of thickness from about 0.2nm to about 3nm located between the electron transport layer

comprising fullerenes and the layer of light-emissive material.

There may also be an interfacial layer interposed between the layer

from leaking into the fullerene layer.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The layered structure and the light-emitting device produced according to the present invention will now be described, by way of example only, reference being made to the accompanying drawings, in which:

Figure 1 is a sectional view of a layered structure exhibiting Ohmic behavior produced in accordance with the present invention;

10 Figure 2 is a plot of current versus voltage of a bi-layer interfacial structure, namely Al/LiF/C60 (solid line), and of a simple layered structure Al/C60 produced in accordance with the present invention;

Figure 3 is a schematic cross sectional view of a fullerene hybrid light-emitting device constructed in accordance with the present invention;

15 Figure 4 is a plot of current versus voltage relationship for hybrid organic EL devices of Figure 3 with four different thicknesses for the fullerene (C60) electron transport layer;

20 Figure 5 shows plots of luminance versus voltage of hybrid organic EL devices of Figure 3 with four different thicknesses for the fullerene (C60) electron transport layer with the four different curves corresponding to the four different thicknesses of the fullerene electron transport layer;

Figure 6 shows the optical spectra of the hybrid organic EL devices of Figure 3 with four different thicknesses for the fullerene (C60) electron transport layer;

25 Figure 7 shows two current-voltage characteristics of Prior Art organic EL devices having electron transport layers made from conventional tris-(8-hydroxyquinoline) aluminum (Alq) organics and a thickness of 20 nm and 110 nm; and

30 Figure 8 compares luminance-voltage characteristics of two OLEDs with (●), and without (○) an embedded LiF layer, the test device structure is: glass substrate/ITO/TPD(50nm)/Alq(25 nm)/[embedded LiF layer(0 nm (○), 1nm (●))/fullerene (25nm)/LiF(0.5nm)/Al(100nm).

DETAILED DESCRIPTION OF THE INVENTION

Definitions

DETAILED DESCRIPTION OF THE INVENTION

Definitions

As used herein, the phrase "electron transport layer" means a thin-film material having a primary function of conducting or transporting electrons across the layer from one region to another region.

As used herein, the phrase "hole transport layer" means a thin-film material having a primary function to conduct holes across the layer from one region to another region.

As used herein, the phrase "light emissive layer or light-emission layer" means a thin-film material having the primary function of emitting light.

As used herein, the phrase "electroluminescence layer" means a thin-film material having a primary function of emitting light under electrical stimulation.

As used herein, the phrase "Ohmic contact (or Ohmic behavior)" means that electrical current increases linearly as a function of applied voltage across one (or more) contact interface(s) made between two (or more) different materials.

As used herein, the term "fullerene" means nanostructured carbon consisting of 60, 70, or more carbon atoms self-bonded in spherical forms which are also referred to as Buckminster fullerenes, nano bucky balls (NBB) or bucky balls (BB) in the literature. The carbon atoms may be bonded to additional atoms or functional groups.

As used herein, the phrase "hole injection layer (or hole injection electrode)" means a thin film layer having a primary function of facilitating hole injection into a hole transport layer and the hole injection layer is typically the anode.

As used herein, the phrase "interfacial contact layer", or "interfacial layer" means an ultra-thin layer inserted between two adjacent layers to serve as an interface transition layer.

Layered Structure Exhibiting Ohmic Behavior

Referring first to Figure 1 there is shown a layered structure 10 including a fullerene layer exhibiting Ohmic behavior. The layered structure 10 includes a first layer 12 comprising fullerenes and a second layer 14 of pre-

selected thickness comprising a fluoride compound located on a first surface of layer 12. A third layer 16 comprising an electrically conductive material is located on the second layer 14 to which electrical contact can be made, the pre-selected thickness of the fluoride compound being selected so that the layered structure exhibits substantially Ohmic behavior across the first, second and third layers.

The fullerene may be C60, C70 or combinations thereof. Layer 12 comprising fullerenes may also include a mixture of fullerenes and organic molecules, a mixture of fullerenes and inorganic materials, polymeric fullerenes, and fullerenes chemically bonded to conducting polymers.

The fluoride compound may be alkaline fluoride compound, and preferably the alkaline fluoride compound is lithium fluoride (LiF). The pre-selected thickness of the lithium fluoride layer is in a range from about 0.2 nm to about 5 nm to give Ohmic behavior. The electrically conductive material may be Al, Cr, Cu, Ag, Au, Ni, Fe, Ni, W, Mo, Co or alloys of Mg:Ag and Li:Al. Preferably the electrically conductive material is aluminum (Al).

The layered structure 10 may be applied with a second surface of the layer comprising fullerenes opposed to the first surface physically contacted to a surface of a substrate for making electrical contact between the layered structure and the substrate. The substrate may be part of an optoelectronic device such as, but not limited to, light-emitting diodes, solar cells, photodetectors etc. The substrate may also be part of an electronic device such as field-effect transistors, tunneling diodes to mention just a few.

In another embodiment of a layered structure exhibiting Ohmic behavior included is a first layer comprising fullerenes, a second layer including a low work function material located on a first surface of the layer of fullerenes. The layered structure includes a third layer which is an electrically conductive material located on the second layer to which electrical contact can be made, the low work function material being selected so that the layered structure exhibits substantially Ohmic contact across the first, second and third layers.

The fullerene may be C60, C70 or combinations thereof. The layer comprising fullerenes may also include a mixture of fullerenes and organic

molecules, a mixture of fullerenes and inorganic materials, polymeric fullerenes, and fullerenes chemically bonded to conducting polymers.

The electrically conductive material may be one of Al, Cr, Cu, Ag, Au, Ni, Fe, Ni, W, Mo, Co and alloys or mixtures of Mg:Ag or Li:Al to mention just a few. The layered structure 10 may be applied with a second surface of the fullerene layer (opposed to the first surface) physically contacted to a surface of a substrate for making electrical contact between the layered structure and the substrate. The substrate may be part of an optoelectronic device such as, but not limited to, light-emitting diodes, solar cells, photodetectors etc. The substrate may also be part of an electronic device such as field-effect transistors, tunneling diodes to mention just a few.

Figure 2 shows in graphic form a current-voltage relationship of 100 nm thick C60 fullerene sandwiched between two contacting electrodes with a stacking sequence, substrate/Al/C60/Al; and substrate/Al/LiF/C60/LiF/Al. A true interface Ohmic contact is characterized by no electron current barrier present across the interface. In the present test case, the current-voltage relationship should follow a linear relationship, where the slope of the linear line is determined by the resistivity of the layer. Figure 2 shows that Al/C60 has strong rectifying characteristics; that Al/LiF/C60 shows excellent Ohmic contact characteristics.

Electroluminescent Device

Referring to Figure 3, an EL device 18 has been constructed to demonstrate the integration of a fullerene layer into a typical small organic molecule based device of the type disclosed in United States Patent No. 4,356,429. The device 18 comprises a substrate 20, a conductive anode electrode layer 30 for hole injection, a hole transport layer 40 for hole transport, a light emissive or light-emission layer 50 capable of emitting light formed on the hole transport layer 40, a fullerene layer 60 formed on the light-emission layer 50, an outer conductive cathode layer 90 and an interfacial contact layer 80 sandwiched between fullerene layer 60 and cathode layer 90 which makes Ohmic contact with fullerene layer 60 and cathode layer 90. An optional cathode capping layer 100 made of a dielectric, such as Si oxides and nitrides, may be deposited on the cathode layer 90. The protective

coating may also be a fullerene layer.

Substrate 20 may be a glass or alternatively it could be made of any material capable of providing mechanical support to thin films. It could be coated with functional thin-film transistors which may be used as electrical drivers. Substrate 20 may be optically transparent for light emitted from the light emissive layer. Alternatively, layers 80, 90 and 100 may be made of suitable materials and thickness to ensure light is coupled out of the light emissive layer 50 through these layers.

Conductive anode layer 30 is a hole injection electrode when a positive bias is applied and it may be, for example, of ITO. Electrode layer 30 may also be any other metal or alloy with a high work function. For example, anode layer 30 may be selected from high work function conducting materials including SnO₂, Ni, Pt, Au, p++ semiconductors (c-Si, a-Si, a-Si:H, poly-silicon). Additional anode materials are disclosed in United States Patent No. 4,885,211.

Hole transport layer (HTL) 40 is preferably an organic-based layer and may be N-N'-diphenyl-N,N'-bis (3-methylphenyl) (1,1'-biphenyl) 4,4'-diamine (TPD) which is commonly used as the HTL, and may have a thickness of about, but not limited to, 60 nm. It could also be any other one or more layers of organic or polymer materials capable of transporting holes and having a thickness range from about 10 nm to about 300 nm. The hole-transport layer 40 may be comprised of those materials disclosed in United States Patent Publication No. 20020180349 which is Serial No. 10/117,812 published December 5, 2002 which refers to United States Patent Nos. 4,539,507; 5,151,629; 5,150,006; 5,141,671 and 5,846,666. This reference discloses different hole transport layer materials, electron transport layer materials, anode materials and cathode materials, which application refers to United States Patent Nos. 4,539,507, 5,942,340 and 5,952,115.

Light emissive or light-emission layer 50 may be an organic electroluminescence layer comprised of, for example, tris-(8-hydroxyquinoline) aluminum (Alq) and may have a thickness of 25 nm. It could also be a layer of an organic compound capable of emitting different colors and having a thickness in the range from about 10 nm to about 100 nm.

Other suitable materials useful for the light emission-layer include conjugated

polymers such as poly (paraphenylene vinylene) (PPV); various members of PPV with and without pigment dyes such as disclosed in United States Patent Nos. 5,294,869 and 5,151,629; rare earth metal, actinide or transition metal organic complex as disclosed in United States Patent No. 6,524,727.

5 The active light-emission layer 50 region can also include any one or a mixture of two or more of fluorescent and phosphorescent materials including small molecules and polymers. For example, the active light-emission layer 50 may be comprised of those materials disclosed in United States Patent publication 20020180349. United States patent application Serial Nos.
10 08/829,398; 09/489,144 and United States Patent No. 6,057,048 also disclose materials which may be used for the light-emission layer.

Electron transport layer 60 is preferably comprised of the fullerene compound C60 and has a thickness range from about 1 nm to about 300 nm, and more preferably from about 1 nm to 120 nm. The fullerene layer thickness
15 may be selected to produce desired optical interference to generate multiple colors, colors of desired wavelength, and optimum optical power output.

Besides C60, the fullerene compound could be any other member of fullerenes such as C70, a mixture of two or more fullerene compounds such as C60:C70, a mixture of fullerenes with one or more organic molecules or
20 polymers such as C60:Alq, C60:PPV. The electron transport layer 60 may include an organic molecule or polymer which are electron conductors mixed with the fullerenes. In addition, the electron transport layer may includes lithium fluoride (LiF) mixed with the fullerenes, or the electron transport layer may includes metal particles mixed with the fullerenes. Preferred metal
25 particles are silver metal particles.

The interfacial layer 80 which makes contact with fullerene layer 60 is preferably made of a bi-layer of 2 nm LiF and Al. However, it will be appreciated by those skilled in the art that it could be any fluoride provided it is in direct contact with the fullerene layer. The interfacial layer 80 may be
30 made using any low work function metals and alloys or mixtures such as Ca, Mg, Mg:Ag and Li:Al to mention just a few.

Cathode layer 90 is preferably aluminum (Al) and that which has a thickness of 100 nm has shown good behavior but other thickness may

certainly be used. In addition, cathode 90 may be made of one or more layers of other well known conductive metals and/or alloys. For example, cathode 90 may be produced from one or more layers of highly conductive metals and alloys such as ITO, Al, Cr, Cu, Ag, Au, Ni, Fe, Ni, W, Mo, Co, Mg:Ag, Li:Al. An optional cathode capping layer 100 made of a dielectric, such as Si oxides and nitrides, may be deposited on the cathode by sputtering or any of the other coating techniques known to those skilled in the art.

The present invention provides a hybrid light-emitting device which uses a fullerene layer as a robust electron transport layer. The electrical properties of the fullerene layer, such as high electrical conductivity and excellent electrical contact with the cathode, has made possible to maintain similar current-voltage characteristics for a wide range of thickness, as is shown in Figure 4. The difference in optical constant of the fullerene layers and light-emitting organics permits engineering of light out of the sandwich structure as is shown in Figure 5, and engineering of light spectral distribution as is shown in Figure 6.

To further demonstrate the advantage of the present light-emitting device 18 using fullerene layers over conventional pure organic based light-emitting devices, Figure 7 shows the current-voltage characteristics of prior art devices made with a conventional electron transport layer 60 made of Alq. The thickness of the Alq electron transport layer is shown to alter the current-voltage characteristics, and to increase the driving voltage by several electron volts.

It will be appreciated by those skilled in the art that the fullerene layer may comprise a mixture of two or more fullerenes, e.g. C60:C70. The fullerene layer may also comprise carbon nano-tubes, and fullerenes deposited by vapor-phase deposition.

Referring again to Figure 3 again, an alternative embodiment of the OLED display device includes inserting an interfacial layer (not shown) between fullerene layer 60 and light emissive layer 50. Based on studies by the inventors of devices which incorporate this interfacial layer, the latter provides further improvement in device performance. A thin lithium fluoride (LiF) layer of thickness (0.2-3nm) is inserted which provides a better contact

between layer 60 and layer 50 and results in a lower driving voltage for the device. Figure 8 compares luminance-voltage characteristics of two OLEDs with (●) and without (○) embedded LiF layer. The test device structure is: glass substrate/ITO/TPD(50nm)/Alq(25 nm)/[embedded LiF layer(0 nm (○), 1 nm (●)]/fullerene (25nm)/LiF(0.5nm)/Al(100nm).

In another alternative embodiment of the OLED devices a layer of organic molecules with a lowest unoccupied molecular orbital (LUMO) energy of about 2eV-3eV and highest occupied molecular orbital (HOMO) energy of about 5-7eV is inserted between layer 60 and layer 50. Such organic molecular layer will function as a hole blocking layer and would thus enhance exciton density in the EL layer 50 and consequently lead to a more efficient device. Non-limiting examples of such molecules include 4,4'-bis(carbazol-9-yl)-biphenyl; 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline; 1,3-Bis(5-(4-diphenylamino)phenyl-1,3,4-oxadiazol-2-yl)benzene; 3,4,5-Triphenyl-1,2,4-triazole; 3-(Biphenyl-4-yl)-4-phenyl-5-tert-butylphenyl-1,2,4-triazole; 3,5-Bis(4-tert-butylphenyl)-4-phenyl-[1,2,4]triazole; 2-(4-Biphenyl)-5-(4-tert-butylphenyl)-1,3,4-oxadiazole; 1,3-Bis[5-(4-(1,1-dimethylethyl)phenyl)-1,3,4-oxadiazol-2-yl]benzene; 1,4-Bis(5-(4-diphenylamino)phenyl-1,3,4-oxadiazol-2-yl)benzene; 1,3,5-Tris[5-(4-(1,1-dimethylethyl)phenyl)-1,3,4-oxadiazol-2-yl]benzene.

As used herein, the terms "comprises", "comprising", "including" and "includes" are to be construed as being inclusive and open ended, and not exclusive. Specifically, when used in this specification including claims, the terms "comprises", "comprising", "including" and "includes" and variations thereof mean the specified features, steps or components are included. These terms are not to be interpreted to exclude the presence of other features, steps or components.

The foregoing description of the preferred embodiments of the invention has been presented to illustrate the principles of the invention and not to limit the invention to the particular embodiment illustrated. It is intended that the scope of the invention be defined by all of the embodiments encompassed within the following claims and their equivalents.

THEREFORE WHAT IS CLAIMED IS:

1. A layered structure including a fullerene layer exhibiting Ohmic behavior, comprising:
 - a) a first layer comprising fullerenes, said first layer having a first surface and a second surface opposed to the first surface;
 - b) a second layer of pre-selected thickness comprising a fluoride compound located on said first surface of said first layer comprising fullerenes; and
 - c) a third layer comprising an electrically conductive material located on the second layer, the pre-selected thickness of the second layer being selected so that the layered structure exhibits substantially Ohmic behavior across the first, second and third layers.
2. The layered structure according to claim 1 wherein said fullerenes are selected from the group consisting of C60, C70 and combinations thereof.
3. The layered structure according to claim 1 or 2 wherein said fluoride compound is an alkaline fluoride compound.
4. The layered structure according to claim 3 wherein said alkaline fluoride compound is lithium fluoride (LiF).
5. The layered structure according to claim 4 wherein said pre-selected thickness of the lithium fluoride layer is in a range from about 0.2 nm to about 5 nm.
6. The layered structure according to claim 1, 2, 3, 4 or 5 wherein said electrically conductive material is selected from the group consisting of Al, Cr, Cu, Ag, Au, Ni, Fe, Ni, W, Mo, Co and alloys or metal mixtures of Mg:Ag and Li:Al.
7. The layered structure according to claim 1, 2, 3, 4 or 5 wherein said electrically conductive material is aluminum (Al).

8. The layered structure according to claim 1, 2, 3, 4, 5, 6 or 7 wherein a second surface of the layer comprising fullerenes opposed to the first surface is physically contacted to a surface of a substrate for making electrical contact between the layered structure and the substrate.
9. The layered structure according to claim 1, 2, 3, 4, 5, 6, 7 or 8 wherein said layer comprising fullerenes includes one of a mixture of fullerenes and organic molecules, a mixture of fullerenes and inorganic materials, polymeric fullerenes, and fullerenes chemically bonded to conducting polymers.
10. A layered structure including a fullerene layer exhibiting Ohmic behavior, comprising:
 - a) a first layer comprising fullerenes, said first layer having a first surface and a second surface opposed to the first surface;
 - b) a second layer comprising a low work function material located on said first surface of said layer comprising fullerenes; and
 - c) a third layer comprising an electrically conductive material located on the second layer, the low work function material being selected so that the layered structure exhibits substantially Ohmic behavior across the first, second and third layers.
11. The layered structure according to claim 10 wherein said fullerenes are selected from the group consisting of C60, C70 and combinations thereof.
12. The layered structure according to claim 10 or 11 wherein said electrically conductive material is selected from the group consisting of Al, Cr, Cu, Ag, Au, Ni, Fe, Ni, W, Mo, Co and alloys of Mg:Ag and Li:Al.
13. The layered structure according to claim 10, 11 or 12 wherein a second surface of the layer comprising fullerenes opposed to the first surface is physically contacted to a surface of a substrate for making electrical contact between the layered structure and the substrate.
14. The layered structure according to claim 10, 11, 12 or 13 wherein said

layer comprising fullerenes includes one of a mixture of fullerenes and organic molecules, a mixture of fullerenes and inorganic materials, polymeric fullerenes, and fullerenes chemically bonded to conducting polymers.

15. A light-emitting device, comprising:

- a) a substrate;
- b) a first electrically conductive layer forming an anode electrode layer on the substrate;
- c) a hole transport layer on said anode electrode layer;
- d) a layer of a light emissive material on said hole transport layer;
- e) an electron transport layer comprising fullerenes located on said layer of a light emissive material;
- f) a first interfacial layer located between said layer of light emissive material and said electron transport material for improving electrical contact between said layer of light emissive material and said layer of electron transport material;
- g) a second electrically conductive layer forming a cathode electrode layer located on said electron transport layer; and
- h) a second interfacial layer located between said electron transport layer and said second electrically conductive layer, said interfacial layer comprising a fluoride compound for providing an Ohmic contact between said cathode electrode layer and said fullerene layer.

16. The light-emitting device of claim 15 wherein said first interfacial layer located between said layer of light emissive material and said electron transport material is a lithium fluoride (LiF) layer having a thickness from about 0.2nm to about 3nm.

17. The light-emitting device of claim 15 wherein said first interfacial layer

located between said layer of light emissive material and said electron transport material is comprised of organic molecules with a LUMO energy level of about 2eV to about 3eV and HOMO energy of about 5 eV to about 7eV located on said layer of light emissive material.

18. The light-emitting device of claim 15, 16 or 17 wherein said hole transport layer is comprised of organic molecules which conduct holes.

19. The light-emitting device of claim 15, 16 or 17 wherein said hole transport layer has a thickness in a range from about 1 nm to about 300 nm.

20. The light-emitting device of claim 15, 16, 17, 18 or 19 wherein said second electrically conductive layer defining a cathode electrode layer is selected from the group consisting of Al, Cr, Cu, Ag, Au, Ni, Fe, Ni, W, Mo, Co and alloys or metal mixtures.

21. The light-emitting device of claim 20 wherein said alloy is a Mg:Ag or Li:Al.

22. The light-emitting device of claim 15, 16, 17, 18, 19 or 20 wherein said interfacial layer comprising a fluoride compound has a thickness in a range from about 0.2 nm to about 10 nm.

23. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21 or 22 wherein said fluoride compound is an alkaline fluoride compound.

24. The light-emitting device of claim 23 wherein said alkaline fluoride compound is lithium fluoride (LiF).

25. The light-emitting device of claims 15, 16, 17, 18, 19, 20, 21 or 22 wherein said fluoride compound is calcium fluoride (CaF_2).

26. The light-emitting device of any one of claims 15 to 25 wherein said second electrically conductive layer defining a cathode electrode layer is aluminum (Al).

27. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25 or 26 wherein said fullerenes are selected from the group consisting of C60, C70 and combinations thereof.

28. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26 or 27 wherein said electron transport layer includes an organic molecule or polymer which are electron conductors mixed with said fullerenes.

29. The light-emitting device of claim 28 wherein said organic molecule is tris-(8-hydroxyquinoline) aluminum (Alq), and wherein said fullerenes are selected from the group consisting of C60, C70 and combinations thereof.

30. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22,

23, 24, 25, 26, 27, 28 or 29 wherein said electron transport layer includes lithium fluoride (LiF) mixed with said fullerenes.

31. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26 or 27 wherein said electron transport layer includes metal particles mixed with said fullerenes.

32. The light-emitting device of claim 31 wherein said metal particles are silver metal particles.

33. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31 or 32 wherein said electron transport layer has a thickness in a range from about 1 nm to about 300 nm.

34. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31 or 32 wherein the electron transport layer comprising fullerenes has a thickness selected to produce pre-selected optical interference to generate multiple colors, colors of desired wavelength, and optimum optical power output.

35. The light-emitting device of claim 17 wherein the organic molecules are selected from the group consisting of 4,4'-bis(carbazol-9-yl)-

biphenyl; 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline; 1,3-Bis(5-(4-diphenylamino)phenyl-1,3,4-oxadiazol-2-yl)benzene; 3,4,5-Triphenyl-1,2,4-triazole; 3-(Biphenyl-4-yl)-4-phenyl-5-tert-butylphenyl-1,2,4-triazole; 3,5-Bis(4-tert-butylphenyl)-4-phenyl-[1,2,4]triazole; 2-(4-Biphenyl)-5-(4-tert-butylphenyl)-1,3,4-oxadiazole; 1,3-Bis[5-(4-(1,1-dimethylethyl)phenyl)-1,3,4-oxadiazol-2-yl]benzene; 1,4-Bis(5-(4-diphenylamino)phenyl-1,3,4-oxadiazol-2-yl)benzene; and 1,3,5-Tris[5-(4-(1,1-dimethylethyl)phenyl)-1,3,4-oxadiazol-2-yl]benzene.

36. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34 or 35, wherein the first electrically conductive layer defining an anode electrode layer on the substrate is a high work function material.

37. The light-emitting device of claim 36 wherein the high work function material is selected from the group consisting of ITO, SnO₂, Ni, Pt, Au, p⁺⁺ semiconductors including c-Si, a-Si, a-Si:H, and poly silicon.

38. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36 or 37, including a protective coating deposited on a top surface of the electrically conductive layer defining the cathode electrode.

39. The light-emitting device of claim 38 wherein said protective coating is selected from the group consisting of dielectrics including oxides of Si and nitrides.

40. The light-emitting device of claim 38 wherein said protective coating is a fullerene layer.

41. The light-emitting device of claim 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39 or 40, including a power supply for applying a voltage across the anode electrode layer and the cathode electrode layer.

42. The layered structure according to claim 10 wherein said substrate is part of a device selected from the group consisting of optoelectronic devices and electronic devices.

43. The layered structure according to claim 42 wherein said optoelectronic device is selected from the group consisting of light-emitting diodes, solar cells and photodetectors.

44. The layered structure according to claim 42 wherein said electronic device is selected from the group consisting of field-effect transistors and tunneling diodes.